Office State of New Mexico	
Office State of New Mexico District I ~ (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240	Form C-103
District I ~ (575) 393-6161 Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240	Revised August 1 2011
District II - (575) 748-1283	WELL API NO.
811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	30-025-04101
District III - (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410 1220 South St. Francis Dr.	5. Indicate Type of Lease
District IV - (505) 476-3460 Santa Fo NTM 97505	STATE FEE 🖂
1220 S. St. Francis Dr., Santa Fe. NM	6. State Oil & Gas Lease No.
87505	.,
SUNDRY NOTICES AND REPORTS ON WELLS	
	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	M.E. GAITHER
1. Type of Well: Oil Well Gas Well Other	0 177 11 22
2. Name of Operator	8. Well Number #01
APACHE CORPORATION	9. OGRID Number
3. Address of Operator	873
303 VETERANS AIRPARK LANE, STE 3000, MIDLAND, TX 79705	10. Pool name or Wildcat
4. Well Location	EUMONT/YATES/7 RVRS/QN
Unit Letter I : 1980 feet from the S line and 660	feet from the C 11
Section 34 Township 19S Range 36F	3 C C C C C C C C C C C C C C C C C C C
11. Elevation (Show whether DR, RKB, RT, GR, et	NMPM LEA County
3632' GL	c.)
3032 QE	
12 Check Ammonist Day I II	
12. Check Appropriate Box to Indicate Nature of Notice	e, Report or Other Data
NOTICE OF INTENTION TO	
PERFORM REMEDIAL MODIZ CO. STATE AND A	BSEQUENT REPORT OF:
TEMPORARII Y ARANDON DI REMEDIAL WO	RK ALTERING CASING T
PULL OR ALTER CASING ID	RILLING OPNS. PAND A
MOLTIPLE COMPL CASING/CEME	NT JOB D PNR
DOWNHOLE COMMINGLE	PINK
OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, a of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Complete Complet	nd give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Coproposed completion or recompletion.	ompletions: Attach wellhore diagram of
proposed completion of recompletion.	
08/23/21-NOTIFIED NIMOOD	. Stagian of
08/23/21-NOTIFIED NMOCD.	
08/23/21-NOTIFIED NMOCD. 08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3	
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'.	688'-3333'. WOC&TAGGED@
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SOLIFEZED 60SX OF CLASS "C" CEMENT FROM 3	688'-3333'. WOC&TAGGED@
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362', PERFD@1425', SQUIEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/20'-2-08/26', TAGGED@25', TA	688'-3333'. WOC&TAGGED@
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING, W/OC 5 TAGGED@1160'.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225'
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 2012 10 10 10 10 10 10 10 10 10 10 10 10 10	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUIEFZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURF	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURF	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 2012 10 10 10 10 10 10 10 10 10 10 10 10 10	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-26 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-26 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACTOR OF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURF	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMEN W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURICUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMEN W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURICUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date:	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date:	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACTOR WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS.	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief.
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date:	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief.
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEMENT W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date:	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief.
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFOCE CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledge SIGNATURE TITLE PLUGGING AGENT	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief.
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURF CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledg SIGNATURE TITLE PLUGGING AGENT Type or print name M. LEEROARK Famil address LEE@BARGERN E-mail address LEE@BARGERN E-mai	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2-2	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2. 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'. 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE. AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: I hereby certify that the information above is true and complete to the best of my knowledged SIGNATURE TITLE PLUGGING AGENT Type or print name M. LEF ROARK E-mail address: LEE@JMRSERVICE For State Use Only	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'-2- 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE AND INSTALL DRYHOLE RECLAMATION. CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: Title PLUGGING AGENT Type or print name M. LEE ROARK E-mail address: LEE@JMRSERVICE For State Use Only APPROVED BY: TITLE	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'-2- 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE AND 8-5/8" CASING FROM 100'-SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: Title Plugging Agent Type or print name M. LEEROARK E-mail address: LEE@JMRSERVICE For State Use Only APPROVED BY: TITLE Compliance Officer A	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'-2- 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE AND 8-5/8" CASING FROM 100'-SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: Title Plugging Agent Type or print name M. LEEROARK E-mail address: LEE@JMRSERVICE For State Use Only APPROVED BY: TITLE Compliance Officer A	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'-2- 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE AND INSTALL DRYHOLE RECLAMATION. CUTOFF WELLHEAD, ANCHORS 3' BELOW SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: TITLE PLUGGING AGENT Type or print name M. LEE FOARK E-mail address: LEE@JMRSERVICE For State Use Only APPROVED BY: TITLE	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21
08/24/21-TAGGED CIBP@3688'. SPOTTED 60SX OF CLASS "C" CEMENT FROM 3 3280'. 08/25/21-PERFD@2590'. SQUEEZED 60SX OF CLASS "C" CEMENT FROM 2590'-2- 08/26/21-TAGGED@2362'. PERFD@1425'. SQUEEZED 60SX OF CLASS "C" CEME W/RETURNS OUT 8-5/8" CASING. WOC&TAGGED@1168'. PERFD@300'-2- 200SX OF CLASS "C" CEMENT I/O OF 6-5/8" CASING FROM 300'-SURFA AND 8-5/8" CASING FROM 100'-SURFACE. VERIFIED CEMENT AT SURFACE AND 8-5/8" CASING FROM 100'-SURFACE AND INSTALL DRYHOLE RECLAMATION. CLOSED LOOP CONTAINMENT SYSTEM WILL BE USED FOR FLUIDS. Spud Date: Rig Release Date: Title Plugging Agent Type or print name M. LEEROARK E-mail address: LEE@JMRSERVICE For State Use Only APPROVED BY: TITLE Compliance Officer A	688'-3333'. WOC&TAGGED@ 418'. NT FROM 1425'-1225' PERFD@100'. SQUEEZED CE AND I/O OF 6-5/8" CASING FACE. MARKER. TURN OVER FOR e and belief. DATE 09/12/21 SS.COM PHONE: (432) 618-1050

17 1/2" Hole

12 1/2" 40@ @ 222'

w/ 150 sx, Cal TOC @ 106'

11" Hole

8 5/8" 32# @ 2540'

w/500 sx, Cal TOC @ 463'

TOC @ 2751' Cal

0

165

329

494

658

823

988

1152

1317

1481

1646

1810

1975

2140

2304

2469

2633

2798

2963

3127

3292

3456

3621

3785

3950



TOC @ 463'

 LEASE NAME
 M.E. GAITHER

 WELL #
 #01

 API #
 30.025.04101

 COUNTY
 LEA, NM

WELL BORE INFO. DEPTH SX/CMT

FINAL P&A WB DIAGRAM

4. PUH & PERF'D @ (300' & 100') CIRC'D 200 SX CLASS "C" CMT FROM 300' TO SURF INSIDE & OUTSIDE OF 6 5/8" CSG & FROM 100' TO SURF INSIDE & OUTSIDE OF 6 5/8" & 8 5/8" CSG. RDMO, CUT OFF WH, INSTALL DRY HOLE MARKER, CLEAN LOCATION, P&A COMPLETE 8/26/2021.

SURF SHOE, WATER BOARD, & SURF PLUG

1168' 60 SX

300

200 sx

3. PUH & PERF'D @ 1425', SQZ'D 60 SX CLASS "C" CMT W/RETURNS OUT 8 5/8", TAGGED TOC @ 1168' INSIDE 6 5/8" CSG.

TOP OF SALT

2362' 2. PUH & PERF'D @ 2590', SQZ'D 60 SX CLASS "C" CMT, TAGGED TOC @ 2362'INSIDE 6 5/8" CSG.

INTERIM SHOE & BASE OF SALT

Prod equipment in hole?

3280'
60 SX
7 7/8" Hole

PBTD @ 3730' TD @ 3950' 1. MIRU P&A RIG. RIH W/TBG & VERIFIED CIBP @ 3688', CIRC'D W/MLF, SPOTTED 60 SX CLASS "C" CMT, TAGGED TOC @ 3280' INSIDE 6 5/8"CSG.

EUMONT PERFS

Perfs @ 3730'-3820'

CIBP @ 3900' Perfs @ 3932'-3948'

6 5/8" 20# @ 3819'

w/ 100 sx, Cal TOC @ 2751'

5" Liner @ 3780'-3950'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 48634

CONDITIONS

Operator:	OGRID:
APACHE CORPORATION	873
303 Veterans Airpark Ln	Action Number:
Midland, TX 79705	48634
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
kfortner	None	9/21/2021