

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Sundry Print Report

09/02/2021

Well Name: FARRELL FEDERAL	Well Location: T7S / R33E / SEC 28 / NESW /	County or Parish/State: ROOSEVELT / NM
Well Number: 5	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM83197	Unit or CA Name:	Unit or CA Number:
US Well Number: 300411024000S1	Well Status: Oil Well Shut In	Operator: RIDGEWAY ARIZONA OIL CORPORATION

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 08/25/2021

Time Sundry Submitted: 04:23

Date proposed operation will begin: 09/19/2021

Procedure Description: 1) SET 4-1/2" CIBP @ 4,180'; CIRC. WELL W/ M.L.F.; PRES. TEST 4-1/2" CSG. X CIBP; PUMP 25 SXS. CMT. @ 4,180'-3,980'; WOC X TAG CMT. PLUG. 2) PUMP 50 SXS. CMT. @ 3,549'-3,419' (T/S.A.); WOC X TAG CMT. PLUG. 3) PERF. X ATTEMPT TO SQZ. 45 SXS. CMT. @ 2,365'-2,245' (T/YATES, B/SALT); WOC X TAG CMT. PLUG. 4) PERF. X ATTEMPT TO SQZ. 40 SXS. CMT. @ 1,955'-1,845' (T/SALT); WOC X TAG CMT. PLUG. 5) PERF. X CIRC. TO SURF., FILLING ALL ANNULI, 150 SXS. CMT. @ 468'-3' (8-5/8" CSG.SHOE). 6) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; VERIFY CMT. TO SURF. ON ALL ANNULI; WELD ON STEEL PLATE TO CSGS. X INSTALL BELOW GROUND LEVEL DRY HOLE MARKER. DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM W/ A STEEL TANK AND HAUL THE CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Accepted for Record Only

SUBJECT TO LIKE
APPROVAL BY BLM

KF

NMOCD 9/27/21

State of New Mexico
Energy, Minerals and Natural ResourcesForm **Page 2 of 10**
Revised July 18, 2013Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-041-10240
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Farrell Federal
8. Well Number 5
9. OGRID Number 164557
10. Pool name or Wildcat SAN ANDRES
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4421' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other2. Name of Operator
Ridgeway Arizona Operating Company3. Address of Operator
575 N Dairy Ashford Rd, EC II Suite 210, Houston, TX 770794. Well Location
Unit Letter K : 1980 feet from the South line and 1980 feet from the West line
Section 28 Township 07S Range 33E NMPM County Roosevelt

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐
 CLOSED-LOOP SYSTEM ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

BLM COA attached including procedure and WBS

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William Boyd TITLE Land & Regulatory Mgr DATE 9/14/2021Type or print name William Boyd E-mail address: wboyd@pedevco.com PHONE: 713-574-7912**For State Use Only**

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any): _____

2-3/8" @ 4,215' ???

Well Name: Farrell Federal 05	
Well API #: 30-041-10240	
County, State: Roosevelt Co NM	
Date:	
Final Installation	
Installation	Surface Casing
	OD: 8-5/8" Weight: 24 Grade: Top: 0 Bottom: 418 Intermediate Csg. OD: Weight: Grade: Top: Bottom:
	PERF. X CIRC. 150 SKS. @ 468'-3'
	Production Casing OD: 4.5 Weight: 9.5 Grade: Top: 0 Bottom: 4454 TOC 800 sacks DV Tool
	PERF. X SQ2. 40 SKS. @ 1,955'-1,845'-TAG
	PERF. X SQ2. 45 SKS. @ 2,365'-2,245'-TAG
	Liner Top N/A KOP N/A Top Perf 4248' Bottom Perf 4402' TD 4454 PBTD 4418 TVD 4454
	PERF. X SQ2. 50 SKS. @ 3,549'-3,419'-TAG
	Pump 25 SKS @ 4,180'-3,980'-TAG SET 4-1/2" CIBP @ 4,180'
	4-1/2" @ 4,454' w/800 SKS.
	T/SALT ~ 1,900' T/YATES ~ 2,305' T/ON. ~ 3,000' T/S.H. ~ 3,484'

Farrell Federal #05
30-041-10423
Ridgeway Arizona Oil Corp
September 02, 2021
Conditions of Approval

1. Operator shall place CIBP at 4,180' (50'-100' above top most perf) and place 25 sx of Class C cement on top. WOC and TAG.
2. Operator shall perf at 3,549' and squeeze Class C cement to 3,419' as proposed. WOC and TAG.
3. Operator shall perf at 2,365' and squeeze Class C cement to 2,245' to seal the Yates Formation and the bottom of the Salt. WOC and TAG.
4. Operator shall perf at 2,042' and squeeze Class C cement to 1,922' to seal the top of the Salt. WOC and TAG.
5. Operator shall perf at 468' and squeeze Class C cement to surface to seal the 8-5/8" shoe.
6. See Attached for general plugging stipulations.

JAM 09022021

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Sundry Print Report

09/02/2021

Well Name: FARRELL FEDERAL	Well Location: T7S / R33E / SEC 28 / NESW /	County or Parish/State: ROOSEVELT / NM
Well Number: 5	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM83197	Unit or CA Name:	Unit or CA Number:
US Well Number: 300411024000S1	Well Status: Oil Well Shut In	Operator: RIDGEWAY ARIZONA OIL CORPORATION

Notice of Intent

Type of Submission: Notice of Intent**Type of Action:** Plug and Abandonment**Date Sundry Submitted:** 08/25/2021**Time Sundry Submitted:** 04:23**Date proposed operation will begin:** 09/19/2021

Procedure Description: 1) SET 4-1/2" CIBP @ 4,180'; CIRC. WELL W/ M.L.F.; PRES. TEST 4-1/2" CSG. X CIBP; PUMP 25 SXS. CMT. @ 4,180'-3,980'; WOC X TAG CMT. PLUG. 2) PUMP 50 SXS. CMT. @ 3,549'-3,419' (T/S.A.); WOC X TAG CMT. PLUG. 3) PERF. X ATTEMPT TO SQZ. 45 SXS. CMT. @ 2,365'-2,245' (T/YATES, B/SALT); WOC X TAG CMT. PLUG. 4) PERF. X ATTEMPT TO SQZ. 40 SXS. CMT. @ 1,955'-1,845' (T/SALT); WOC X TAG CMT. PLUG. 5) PERF. X CIRC. TO SURF., FILLING ALL ANNULI, 150 SXS. CMT. @ 468'-3' (8-5/8" CSG.SHOE). 6) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; VERIFY CMT. TO SURF. ON ALL ANNULI; WELD ON STEEL PLATE TO CSGS. X INSTALL BELOW GROUND LEVEL DRY HOLE MARKER. DURING THIS PROCEDURE WE PLAN TO USE THE CLOSED-LOOP SYSTEM W/ A STEEL TANK AND HAUL THE CONTENTS TO THE REQUIRED DISPOSAL, PER OCD RULE 19.15.17.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

2. $3\frac{1}{8}'' @ 4,215'$???

Well Name: Farrell Federal 05	
Well API #: 30-041-10240	
County, State: Roosevelt Co NM	
Date:	
Final Installation	
Installation	Surface Casing
	OD: 8-5/8" Weight: 24 Grade: Top: 0 Bottom: 418 Intermediate Csg. OD: Weight: Grade: Top: Bottom: Production Casing OD: 4.5 Weight: 9.5 Grade: Top: 0 Bottom: 4454 TOC 800 sacks DV Tool Liner Top N/A KOP N/A Top Perf 4248' Bottom Perf 4402' TD 4454 PBT 4418 TVD 4454
	PERF. X CIRC. 150 SKS. @ 468'-3'
	PERF. X SQ2. 40 SKS. @ 1,955'-1,845'-TAG
	PERF. X SQ2. 45 SKS. @ 2,365'-2,245'-TAG
	PERF. X SQ2. 50 SKS. @ 3,549'-3,419'-TAG
	PUMP 25 SKS @ 4,180'-3,980'-TAG
	SET 4-1/2" @ IBP @ 4,180'

T/SALT ~ 1,900'
 T/YATES ~ 2,305'
 T/ON. ~ 3,000'
 T/S.H. ~ 3,484'

DAE 08/09/21

Farrell Federal #05
30-041-10423
Ridgeway Arizona Oil Corp
September 02, 2021
Conditions of Approval

1. Operator shall place CIBP at 4,180' (50'-100' above top most perf) and place 25 sx of Class C cement on top. WOC and TAG.
2. Operator shall perf at 3,549' and squeeze Class C cement to 3,419' as proposed. WOC and TAG.
3. Operator shall perf at 2,365' and squeeze Class C cement to 2,245' to seal the Yates Formation and the bottom of the Salt. WOC and TAG.
4. Operator shall perf at 2,042' and squeeze Class C cement to 1,922' to seal the top of the Salt. WOC and TAG.
5. Operator shall perf at 468' and squeeze Class C cement to surface to seal the 8-5/8" shoe.
6. See Attached for general plugging stipulations.

JAM 09022021

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 51991

CONDITIONS

Operator: RIDGEWAY ARIZONA OIL CORP. 575 N. Dairy Ashford Houston, TX 77079	OGRID: 164557
	Action Number: 51991
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	Need BLM approval	9/27/2021