

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-10268
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2480
7. Lease Name or Unit Agreement Name Marathon AGI State
8. Well Number 1
9. OGRID Number 7377
10. Pool name or Wildcat Collins Ranch; Wolfcamp

<p>SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	
2. Name of Operator EOG Resources, Inc.	
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>A</u> : <u>660</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>East</u> line Section <u>33</u> Township <u>17S</u> Range <u>24E</u> NMPM <u>Eddy</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3790'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

<p>NOTICE OF INTENTION TO:</p> <p>PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/></p>	<p>SUBSEQUENT REPORT OF:</p> <p>REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/></p>
--	--

Notify OCD 24 hrs. prior to any work done

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Must use closed loop system

EOG Resources, Inc. plans to plug and abandon this well as follows:

CIBP @ 7730' & Dumpbail 35' of CI H cmt. - WOC & tag - Morrow

- MIRU all safety equipment as needed. NU BOP. POOH with production equipment. 25 sx cmt
- RIH and pull bridge plug at 4999' and POOH. Set a CIBP at 7563' with 40 sx Class "C" cement on top to 7463'. WOC and tag. This will cover Atoka and Morrow perms.
- Spot a 25 sx Class "C" cement plug from 6921'-6669'. This will cover B Cisco top.
- Spot a 25 sx Class "C" cement plug from 6606'-6354'. This will cover T Cisco top.
- Spot a 25 sx Class "C" cement plug from 5363'-5111'. This will cover DV tool. Must Run CBL to determine TOC
- Set a CIBP at 4831' with 40 sx Class "C" cement on top to 4731'. This will cover Wolfcamp perms. 25 sx cmt
- Spot a 25 sx Class "C" cement plug from 3951'-3699'. This will cover Abo top.
- Spot a 25 sx Class "C" cement plug from 3286'-3034'. This will cover Drinkard top.
- Spot a 25 sx Class "C" cement plug from 1996'-1744'. This will cover Glorieta top.
- Perforate at 1544'. Spot a 25 sx Class "C" cement plug from 1544'-1292'. WOC and tag. This will cover intermediate casing shoe. Perf @ 1482'
- Perforate at 648'. Spot a 25 sx Class "C" cement plug from 648'-396'. WOC and tag plug. This will cover intermediate casing shoe II and San Andres top.
- Perforate at 252'. Spot a 25 sx Class "C" cement plug from 252' up to surface. WOC and tag plug. This will cover surface casing shoe and surface plug.
- Cut off wellhead and weld on dry hole marker. Clean location as per regulated.

Wellbore schematics attached

Spud Date:

Rig Release Date:

****SEE ATTACHED COA's****

Must be plugged by 10/1/2022

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE September 29, 2021

Type or print name Tina Huerta E-mail address: tina.huerta@eogresources.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 10/1/2021

Conditions of Approval (if any):

Sec-TWN-RNG:	Sec. 33-17S-24E
FOOTAGES:	660' FNL & 660' FEL

API:	30-015-10268
GL:	3790
KB:	

CASING DETAIL

[illegible]

FORMATION TOPS

Name		Formation	Top	Name		Formation	Top
		SA	490			Austin Cycle	7786
		Glorieta	1870			Chester Lm	7908
		Drinkard	3160				
		Abo	3825				
		WC	5070				
		T Cisco	6480				
		B Bisco	6795				
		Canyon	6960				
		Strawn	7255				
		Atoka	7592				
		Morrow Cl	7768				

TUBING DETAIL

[illegible]

Perforation Detail	
Perforation Type	Standard
Perforation Size	1/8" x 1/8"
Perforation Spacing	1/4" x 1/4"
Perforation Material	304 Stainless Steel
Perforation Finish	Brushed
Perforation Location	Top and Bottom
Perforation Quantity	100
Perforation Unit Price	\$0.50
Perforation Total Price	\$50.00

	Formation	Top	Bottom	Treatment			
A	WC	4,881	4,925	Acidized w/6000g 15% NEFE acid			
B	Atoka/Morrow	7,772	7,780	Natural			
C	Atoka/Morrow	7,613	7,651	Acidized w/1500g 7 1/2% acid			

PBTD:	4,999	MD
TD:	7,970	MD

DKC 2/17/21

4/18-19/89 - RTTS set @ 4790'
Perf A
4/18-19/89 - BP set @ 4999'

11/16/89 - Set o/o tool at 7709
11/16/89 - Set sliding sleeve @ 5056

Perf B
11/16/89 - Set o/o tool at 7709

Perf C

Marathon State AGI #1 Proposed				Sec. 33-17S-24E FOOTAGES: 660' FNL & 660' FEL				API: 30-015-10268 GL: 3790 KB:																																																																																																																																																																																																																																																																		
<div>11th Plug</div> <div>10th Plug</div> <div>9th Plug</div> <div>8th Plug</div> <div>7th Plug</div> <div>6th Plug</div> <div>5th Plug</div> <div>Existing Wolfcamp Perfs: 4881' - 4925'</div> <div>Existing Bridge Plug at 4999'</div> <div>4th Plug</div> <div>DV Tool at 5237'</div> <div>3rd Plug</div> <div>2nd Plug</div> <div>1st Plug</div> <div>Existing Atoka Perfs: 7613' - 7651'</div> <div>Existing Morrow Perfs: 7772' - 7780'</div>	<div>CASING DETAIL</div> <table><thead><tr><th>#</th><th>HOLE SIZE</th><th>SIZE</th><th>WGHT</th><th>GRADE</th><th>Top</th><th>Bottom</th><th>Sx Cmt</th><th>Circ/TOC</th><th>TOC Method</th></tr></thead><tbody><tr><td>A</td><td>17</td><td>12 3/4</td><td>48</td><td></td><td>0</td><td>109</td><td>250</td><td>Circ</td><td></td></tr><tr><td>B</td><td>11</td><td>8 5/8</td><td>24</td><td></td><td>0</td><td>598</td><td>300</td><td>Circ</td><td></td></tr><tr><td>C</td><td>11</td><td>7</td><td>17</td><td></td><td>0</td><td>1,418</td><td>350</td><td>Circ</td><td></td></tr><tr><td>D</td><td>6.25</td><td>4 1/2</td><td>11.6</td><td></td><td>0</td><td>7970</td><td>1500</td><td>Circ</td><td></td></tr></tbody></table> <div>FORMATION TOPS</div> <table><thead><tr><th></th><th>Formation</th><th>Top</th><th></th><th>Formation</th><th>Top</th><th></th><th>Formation</th><th>Top</th><th></th></tr></thead><tbody><tr><td></td><td>San Andres</td><td>490</td><td></td><td>T. Cisco</td><td>6480</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>Glorieta</td><td>1870</td><td></td><td>B. Cisco</td><td>6795</td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>Drinkard</td><td>3160</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>Abo</td><td>3825</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td>Wolfcamp</td><td>4874</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> <div>TUBING DETAIL</div> <table><thead><tr><th>#</th><th>Joints</th><th>Description</th><th>Length</th><th>OD</th><th>ID</th><th>Grade</th><th>Wt (lb/ft):</th><th>Top (ftKB):</th><th>Btm (ftKB):</th></tr></thead><tbody><tr><td></td><td></td><td colspan="2">2.375" Tbg & Packer</td><td></td><td></td><td></td><td></td><td></td><td>4790</td></tr></tbody></table> <div>PLUGS</div> <table><thead><tr><th>#</th><th>SX</th><th>Class</th><th>Top</th><th>Bottom</th><th>Δ</th><th>Notes</th><th>Tag</th></tr></thead><tbody><tr><td>1</td><td>10</td><td>C</td><td>7463</td><td>7563</td><td>100</td><td>Atoka & Morrow Perfs</td><td>Y</td></tr><tr><td>2</td><td>25</td><td>C</td><td>6669</td><td>6921</td><td>252</td><td>B Cisco Top</td><td>N</td></tr><tr><td>3</td><td>25</td><td>C</td><td>6354</td><td>6606</td><td>252</td><td>T Cisco Top</td><td>N</td></tr><tr><td>4</td><td>25</td><td>C</td><td>5111</td><td>5363</td><td>252</td><td>DV Tool</td><td>N</td></tr><tr><td>5</td><td>10</td><td>C</td><td>4731</td><td>4831</td><td>100</td><td>Wolfcamp Perfs</td><td>N</td></tr><tr><td>6</td><td>25</td><td>C</td><td>3699</td><td>3951</td><td>252</td><td>Abo Top</td><td>N</td></tr><tr><td>7</td><td>25</td><td>C</td><td>3034</td><td>3286</td><td>252</td><td>Drinkard Top</td><td>N</td></tr><tr><td>8</td><td>25</td><td>C</td><td>1744</td><td>1996</td><td>252</td><td>Glorieta Top</td><td>N</td></tr><tr><td>9</td><td>25</td><td>C</td><td>1292</td><td>1544</td><td>252</td><td>Int. Csg. Shoe I</td><td>Y</td></tr><tr><td>10</td><td>25</td><td>C</td><td>396</td><td>648</td><td>252</td><td>Int. Csg. Shoe II & San Andres Top</td><td>Y</td></tr><tr><td>11</td><td>25</td><td>C</td><td>0</td><td>252</td><td>252</td><td>Sur. Csg. Shoe & Surface Plug</td><td>Y</td></tr></tbody></table> <div>PERFORATION DETAIL</div> <table><thead><tr><th></th><th>Formation</th><th>Top</th><th>Bottom</th><th></th><th>Formation</th><th>Top</th><th>Bottom</th><th></th><th></th></tr></thead><tbody><tr><td></td><td>Morrow</td><td>7,772</td><td>7,780</td><td></td><td>Wolfcamp</td><td>4,881</td><td>4,925</td><td></td><td></td></tr><tr><td></td><td>Atoka</td><td>7,613</td><td>7,651</td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> <div>ADDITIONAL DETAIL</div> <div>NMOCD file unclear, appears that on/off tool, Guiberson packer and tubing used to produced Atoka/Morrow in the previous dual completion were removed cleanly. Only a bridge plug at 4999' and the RTTS packer & tubing at 4790' appear to have been left in this well according to the file.</div> <div>Prepared by: KJP</div>										#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC Method	A	17	12 3/4	48		0	109	250	Circ		B	11	8 5/8	24		0	598	300	Circ		C	11	7	17		0	1,418	350	Circ		D	6.25	4 1/2	11.6		0	7970	1500	Circ			Formation	Top		Formation	Top		Formation	Top			San Andres	490		T. Cisco	6480						Glorieta	1870		B. Cisco	6795						Drinkard	3160									Abo	3825									Wolfcamp	4874								#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft):	Top (ftKB):	Btm (ftKB):			2.375" Tbg & Packer							4790	#	SX	Class	Top	Bottom	Δ	Notes	Tag	1	10	C	7463	7563	100	Atoka & Morrow Perfs	Y	2	25	C	6669	6921	252	B Cisco Top	N	3	25	C	6354	6606	252	T Cisco Top	N	4	25	C	5111	5363	252	DV Tool	N	5	10	C	4731	4831	100	Wolfcamp Perfs	N	6	25	C	3699	3951	252	Abo Top	N	7	25	C	3034	3286	252	Drinkard Top	N	8	25	C	1744	1996	252	Glorieta Top	N	9	25	C	1292	1544	252	Int. Csg. Shoe I	Y	10	25	C	396	648	252	Int. Csg. Shoe II & San Andres Top	Y	11	25	C	0	252	252	Sur. Csg. Shoe & Surface Plug	Y		Formation	Top	Bottom		Formation	Top	Bottom				Morrow	7,772	7,780		Wolfcamp	4,881	4,925				Atoka	7,613	7,651						
	#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC Method																																																																																																																																																																																																																																																																
	A	17	12 3/4	48		0	109	250	Circ																																																																																																																																																																																																																																																																	
	B	11	8 5/8	24		0	598	300	Circ																																																																																																																																																																																																																																																																	
	C	11	7	17		0	1,418	350	Circ																																																																																																																																																																																																																																																																	
	D	6.25	4 1/2	11.6		0	7970	1500	Circ																																																																																																																																																																																																																																																																	
		Formation	Top		Formation	Top		Formation	Top																																																																																																																																																																																																																																																																	
		San Andres	490		T. Cisco	6480																																																																																																																																																																																																																																																																				
		Glorieta	1870		B. Cisco	6795																																																																																																																																																																																																																																																																				
		Drinkard	3160																																																																																																																																																																																																																																																																							
	Abo	3825																																																																																																																																																																																																																																																																								
	Wolfcamp	4874																																																																																																																																																																																																																																																																								
#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft):	Top (ftKB):	Btm (ftKB):																																																																																																																																																																																																																																																																	
		2.375" Tbg & Packer							4790																																																																																																																																																																																																																																																																	
#	SX	Class	Top	Bottom	Δ	Notes	Tag																																																																																																																																																																																																																																																																			
1	10	C	7463	7563	100	Atoka & Morrow Perfs	Y																																																																																																																																																																																																																																																																			
2	25	C	6669	6921	252	B Cisco Top	N																																																																																																																																																																																																																																																																			
3	25	C	6354	6606	252	T Cisco Top	N																																																																																																																																																																																																																																																																			
4	25	C	5111	5363	252	DV Tool	N																																																																																																																																																																																																																																																																			
5	10	C	4731	4831	100	Wolfcamp Perfs	N																																																																																																																																																																																																																																																																			
6	25	C	3699	3951	252	Abo Top	N																																																																																																																																																																																																																																																																			
7	25	C	3034	3286	252	Drinkard Top	N																																																																																																																																																																																																																																																																			
8	25	C	1744	1996	252	Glorieta Top	N																																																																																																																																																																																																																																																																			
9	25	C	1292	1544	252	Int. Csg. Shoe I	Y																																																																																																																																																																																																																																																																			
10	25	C	396	648	252	Int. Csg. Shoe II & San Andres Top	Y																																																																																																																																																																																																																																																																			
11	25	C	0	252	252	Sur. Csg. Shoe & Surface Plug	Y																																																																																																																																																																																																																																																																			
	Formation	Top	Bottom		Formation	Top	Bottom																																																																																																																																																																																																																																																																			
	Morrow	7,772	7,780		Wolfcamp	4,881	4,925																																																																																																																																																																																																																																																																			
	Atoka	7,613	7,651																																																																																																																																																																																																																																																																							
<div>D</div> <div>PBTD: 4,999 MD</div> <div>TD: 7,970 MD</div>																																																																																																																																																																																																																																																																										

CONDITIONS FOR PLUGGING AND ABANDONMENT

OCD - Southern District

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, **Notify NMOCD District Office II at (575)-748-1283 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down. Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal – commercial or private – shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water **will not** be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.

16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).
19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
 - A) Fusselman
 - B) Devonian
 - C) Morrow
 - D) Wolfcamp
 - E) Bone Springs
 - F) Delaware
 - G) Any salt sections
 - H) Abo
 - I) Glorieta
 - J) Yates.
 - K) Potash---(In the R-111-P Area (Page 3 & 4), a solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing

DRY HOLE MARKER REQUIREMENTS

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name 2. Lease and Well Number 3. API Number 4. Unit Letter 5. Quarter Section (feet from the North, South, East or West) 6. Section, Township and Range 7. Plugging Date 8. County (SPECIAL CASES)-----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION

R-111-P Area

T 18S – R 30E

Sec 10 Unit P. Sec 11 Unit M,N. Sec 13 Unit L,M,N. Sec 14 Unit C -P. Sec 15 Unit A G,H,I,J,K,N,O,P. Sec 22 Unit All except for M. Sec 23, Sec 24 Unit C,D,E,L, Sec 26 Unit A-G, Sec 27 Unit A,B,C

T 19S – R 29E

Sec 11 Unit P. Sec 12 Unit H-P. Sec 13. Sec 14 Unit A,B,F-P. Sec 15 Unit P. Sec 22 Unit A,B,C,F,G,H,I,J K,N,O,P. Sec 23. Sec 24. Sec 25 Unit D. Sec 26 Unit A- F. Sec 27 Unit A,B,C,F,G,H.

T 19S – R 30E

Sec 2 Unit K,L,M,N. Sec 3 Unit I,L,M,N,O,P. Sec 4 Unit C,D,E,F,G,I-P. Sec 5 Unit A,B,C,E-P. Sec 6 Unit I,O,P. Sec 7 – Sec 10. Sec 11 Unit D, G—P. Sec 12 Unit A,B,E-P. Sec 13 Unit A-O. Sec 14-Sec 18. Sec 19 Unit A-L, P. Sec 20 – Sec 23. Sec 24 Unit C,D,E,F,L,M,N. Sec 25 Unit D. Sec 26 Unit A-G, I-P. Sec 27, Sec 28, Sec 29 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 32 Unit A,B,G,H,I,J,N,O,P. Sec 33. Sec 34. Sec 35. Sec 36 Unit D,E,F,I-P.

T 19S – R 31E

Sec 7 Unit C,D,E,F,L. Sec 18 Unit C,D,E,F,G,K,L. Sec 31 Unit M. Sec 34 Unit P. Sec 35 Unit M,N,O. Sec 36 Unit O,P.

T 20S – R 29E

Sec 1 Unit H,I,P. Sec 13 Unit E,L,M,N. Sec 14 Unit B-P. Sec 15 Unit A,H,I,J,N,O,P. Sec 22 Unit A,B,C,F,G,H,I,J,O,P. Sec 23. Sec 24 Unit C,D,E,F,G,J-P. Sec 25 Unit A-O. Sec 26. Sec 27 Unit A,B,G,H,I,J,O,P. Sec 34 Unit A,B,G,H. Sec 35 Unit A-H. Sec 36 Unit B-G.

T 20S – R 30E

Sec 1 – Sec 4. Sec 5 Unit A,B,C,E-P. Sec 6 Unit E,G-P. Sec 7 Unit A-H,I,J,O,P. Sec 8 – 17. Sec 18 Unit A,B,G,H,I,J,O,P. Sec 19 Unit A,B,G,H,I,J,O,P. Sec 20 – 29. Sec 30 Unit A-L,N,O,P. Sec 31 Unit A,B,G,H,I,P. Sec 32 – Sec 36.

T 20S – R 31E

Sec 1 Unit A,B,C,E-P. Sec 2. Sec 3 Unit A,B,G,H,I,J,O,P. Sec 6 Unit D,E,F,J-P. Sec 7. Sec 8 Unit E-P. Sec 9 Unit E,F,J-P. Sec 10 Unit A,B,G-P. Sec 11 – Sec 36.

T 21S – R 29E

Sec 1 – Sec 3. Sec 4 Unit L1 – L16,I,J,K,O,P. Sec 5 Unit L1. Sec 10 Unit A,B,H,P. Sec 11 – Sec 14. Sec 15 Unit A,H,I. Sec 23 Unit A,B. Sec 24 Unit A,B,C,D,F,G,H,I,J,O,P. Sec 25 Unit A,O,P. Sec 35 Unit G,H,I,J,K,N,O,P. Sec 36 A,B,C,F – P.

T 21S – R 30E

Sec 1 – Sec 36

T 21S – R 31E

Sec 1 – Sec 36

T 22S – R 28E

Sec 36 Unit A,H,I,P.

T 22S – R 29E

Sec 1. Sec2. Sec 3 Unit I,J,N,O,P. Sec 9 Unit G – P. Sec 10 – Sec 16. Sec 19 Unit H,I,J. Sec 20 – Sec 28. Sec 29 Unit A,B,C,D,G,H,I,J,O,P. Sec 30 Unit A. Section 31 Unit C – P. Sec 32 – Sec 36

T 22S – R 30E

Sec 1 – Sec 36

T 22S – R 31E

Sec 1 – Sec 11. Sec 12 Unit B,C,D,E,F,L. Sec 13 Unit E,F,K,L,M,N. Sec 14 – Sec 23. Sec 24 Unit C,D,E,F,K,L,M,N. Sec 25 Unit A,B,C,D. Sec 26 Unit A,BC,D,G,H. Sec 27 – Sec 34.

T 23S – R 28E

Sec 1 Unit A

T 23S – R 29E

Sec 1 – Sec 5. Sec 6 Unit A – I, N,O,P. Sec 7 Unit A,B,C,G,H,I,P. Sec 8 Unit A – L, N,O,P. Sec 9 – Sec 16. Sec 17 Unit A,B,G,H,I,P. Sec 21 – Sec 23. Sec 24 Unit A – N. Sec 25 Unit D,E,L. Sec 26. Sec 27. Sec 28 Unit A – J, N,O,P. Sec 33 Unit A,B,C. Sec 34 Unit A,B,C,D,F,G,H. Sec 35. Sec 36 Unit B,C,D,E,F,G,K,L.

T 23S – R 30E

Sec 1 – Sec 18. Sec 19 Unit A – I,N,O,P. Sec 20, Sec 21. Sec 22 Unit A – N, P. Sec 23, Sec 24, Sec 25. Sec 26 Unit A,B,F-P. Sec 27 Unit C,D,E,I,N,O,P. Sec 28 Unit A – H, K,L,M,N. Sec 29 Unit A – J, O,P. Sec 30 Unit A,B. Sec 32 A,B. Sec 33 Unit C,D,H,I,O,P. Sec 34, Sec 35, Sec 36.

T 23S – R 31E

Sec 2 Unit D,E,J,O. Sec 3 – Sec 7. Sec 8 Unit A – G, K – N. Sec 9 Unit A,B,C,D. Sec 10 Unit D,P. Sec 11 Unit G,H,I,J,M,N,O,P. Sec 12 Unit E,L,K,M,N. Sec 13 Unit C,D,E,F,G,J,K,L,M,N,O. Sec 14. Sec 15 Unit A,B,E – P. Sec 16 Unit I, K – P. Sec 17 Unit B,C,D,E, I – P. Sec 18 – Sec 23. Sec 24 Unit B – G, K,L,M,N. Sec 25 Unit B – G, J,K,L. Sec 26 – Sec 34. Sec 35 Unit C,D,E.

T 24S – R 29E

Sec 2 Unit A, B, C, D. Sec 3 Unit A

T 24S – R 30E

Sec 1 Unit A – H, J – N. Sec 2, Sec 3. Sec 4 Unit A,B,F – K, M,N,O,P. Sec 9 Unit A – L. Sec 10 Unit A – L, O,P. Sec 11. Sec 12 Unit D,E,L. Sec 14 Unit B – G. Sec 15 Unit A,B,G,H.

T 24S – R 31E

Sec 3 Unit B – G, J – O. Sec 4. Sec 5 Unit A – L, P. Sec 6 Unit A – L. Sec 9 Unit A – J, O,P. Sec 10 Unit B – G, K – N. Sec 35 Unit E – P. Sec 36 Unit E,K,L,M,N.

T 25S – R 31E

Sec 1 Unit C,D,E,F. Sec 2 Unit A – H.

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 52949

CONDITIONS

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 52949
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Must run CBL. Must set CIBP @ 7730'	10/1/2021