

Well Name: FED GR COM	Well Location: T17S / R24E / SEC 25 / SWNW /	County or Parish/State: EDDY / NM
Well Number: 1	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMNM660	Unit or CA Name: FEDERAL GR COM	Unit or CA Number: NMNM72034
US Well Number: 300152195000S1	Well Status: Producing Gas Well	Operator: EOG RESOURCES INCORPORATED

Accepted for record – NMOCD gc 9/30/2021

Notice of Intent

Sundry ID: 2634066

Type of Submission: Notice of Intent	Type of Action: Plug and Abandonment
Date Sundry Submitted: 09/14/2021	Time Sundry Submitted: 10:21
Date proposed operation will begin: 10/07/2021	

Procedure Description: Please attached Notice of Intent to P&A. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Federal\_GR\_Com\_1\_9\_14\_21\_20210914102103.pdf

<b>Well Name:</b> FED GR COM	<b>Well Location:</b> T17S / R24E / SEC 25 / SWNW /	<b>County or Parish/State:</b> EDDY / NM
<b>Well Number:</b> 1	<b>Type of Well:</b> CONVENTIONAL GAS WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM660	<b>Unit or CA Name:</b> FEDERAL GR COM	<b>Unit or CA Number:</b> NMNM72034
<b>US Well Number:</b> 300152195000S1	<b>Well Status:</b> Producing Gas Well	<b>Operator:</b> EOG RESOURCES INCORPORATED

Conditions of Approval

Specialist Review

Fed\_GR\_Com\_1\_Sundry\_ID\_2634066\_P\_A\_20210925094547.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

<b>Operator Electronic Signature:</b> TINA HUERTA	<b>Signed on:</b> SEP 14, 2021 10:21 AM
<b>Name:</b> EOG RESOURCES INCORPORATED	
<b>Title:</b> Regulatory Specialist	
<b>Street Address:</b> 104 SOUTH FOURTH STREET	
<b>City:</b> Artesia	<b>State:</b> NM
<b>Phone:</b> (575) 748-4168	
<b>Email address:</b> tina_huerta@eogresources.com	

Field Representative

<b>Representative Name:</b>		
<b>Street Address:</b>		
<b>City:</b>	<b>State:</b>	<b>Zip:</b>
<b>Phone:</b>		
<b>Email address:</b>		

BLM Point of Contact

<b>BLM POC Name:</b> LONG VO	<b>BLM POC Title:</b> Petroleum Engineer
<b>BLM POC Phone:</b> 5752345972	<b>BLM POC Email Address:</b> LVO@BLM.GOV
<b>Disposition:</b> Approved	<b>Disposition Date:</b> 09/25/2021
<b>Signature:</b> Long Vo	

Federal GR Com 1  
 30-015-21950  
 Lease # NM-660  
 2050' FNL & 660' FWL  
 Unit Letter E-25-17S-24E  
 Eddy County, New Mexico

EOG Resources, Inc. plans to plug and abandon this well as follows:

1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
2. Set a CIBP at 7354' with 4 sx Class C cement on top to 7304'. WOC and tag. This will cover Strawn perfs.
3. Set a CIBP at 7198' with 4 sx Class C cement on top to 7148'. This will cover Canyon perfs. *WOC & TAG*
4. Set a CIBP at 6164' with 4 sx Class C cement on top to 6114'. This will cover Cisco perfs. *WOC & TAG*
5. Set a CIBP at 4965' with 4 sx Class C cement on top to 4915'. This will cover Wolfcamp perfs. *WOC & TAG*
6. Perforate at 4671'. Spot a 25 sx Class C cement plug from 4671'-4509'. WOC and tag. This will cover TOC. *4090' 542. 75* *WOC & TAG* *Leak test CIBP*
7. Perforate at 3958'. Spot a 34 sx Class C cement plug from 3958'-3818'. WOC and tag. This will cover Abo top. *4090' - 3799'* *(in/out)*
8. Perforate at 1055'. Spot a 27 sx Class C cement plug from 1055'-945'. WOC and tag. This will cover Intermediate casing shoe. *1065' 542. 90* *1065' 741'* *(in/out)*
9. Perforate at 601'. Spot a 28 sx Class C cement plug from 601'-495'. WOC and tag. This will cover San Andres top. *450' 120 sx*
10. Perforate at 322'. Spot a 27 sx Class C cement plug from 322'-218'. WOC and tag. This will cover surface casing shoe. *450'* *surface* *(in/out)*
11. ~~Perforate at 100'. Spot a 26 sx Class C cement plug from 100' up to surface. Back fill as needed.~~
12. Cut off wellhead and install dry hole marker. Clean location as per regulated. *Verify @ surface*

Wellbore schematics attached



## Federal GR Com #1 Proposed

Sec-TWN-RNG: 25-17S-24E  
 FOOTAGES: 2050' FNL & 660' FWL  
 API: 30-015-21950  
 GL: 3706  
 KB:

CASING DETAIL							
#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt
A	17 1/2	13 3/8	48	-	0	270	225
B	12 1/4	8 5/8	24	J-55	0	1,000	450
C	7 7/8	4 1/2	10.5/11.6	K-55	0	7,621	895
							5112
							4590

FORMATION TOPS							
Formation	Top	Formation	Top	Formation	Top	Formation	Top
SA	548	Atoka	7609	Yates	6015		
Abo	3888	Morrow Cl	7806	T. Salt	400		
Cisco	6145	Chester	7939	B. Salt	600		
L. Canyon	6996	Mississippian	8062				
Strawn	7245	Glennville	4040				

TUBING DETAIL							
#	Joints	Description	Length	OD	ID	Grade	WT (lb/ft):
		2 3/8" Tubing & TAC					6184'

PLUGS							
#	SX	Class	Top	Bottom	Δ	Notes	
1	4	C	7304	7354	50	Strawn Perfs	
2	4	C	7148	7198	50	Canyon Perfs	
3	4	C	6114	6164	50	Cisco Perfs	
4	4	C	4915	4965	50	Wolfcamp Perfs	
5	25	C	4509	4671	162	TOC	
6	34 1/2	C	3818	4040	222	Abo Top	
7	27 9/10	C	945	1065	120	Int. Csg. Shoe	
8	28	C	495	601	106	San Andres Top	
9	27 1/20	C	2480	3224	744	Sur. Csg. Shoe	
10	28	C	0	190	190	Surface Plug	

PERFORATION DETAIL							
Formation	Top	Bottom	Formation	Top	Bottom	Formation	Top
Strawn	7,404	7,408	Cisco	6,214	6,226		
Canyon	7,248	7,254	Wolfcamp	5,015	5,020		

ADDITIONAL DETAIL							
Packer with Standing Valve at 7208' - Needs to be removed for P&A							
Packer with Standing Valve at 7374'							

Prepared by: KJP

10th Plug

9th Plug

8th Plug

7th Plug

6th Plug

5th Plug

Block Squeeze TOC ~4590'

4th Plug

Existing Wolfcamp Perfs: 5015' - 5020'

Sqz. Perfs at 5100'

TOC-5112' Prior to cmt. sqz.

3rd Plug

Existing Cisco Perfs: 6214' - 6226'

2nd Plug

Packer with Standing Valve at 7208'

Existing Canyon Perfs: 7248' - 7254'

1st Plug

Packer with Standing Valve at 7374'

Existing Strawn Perfs: 7404' - 7408'

PBTD ~7589'

PBTD: 7,589 MD

TD: 8,200 MD



low core

## Federal GR Com #1 Current

Sec-TWN-RNG: 25-17S-24E  
 FOOTAGES: 2050' FNL & 660' FWL  
 API: 30-015-21950  
 GL: 3706  
 KB:

## Casing Detail

#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cnt	Circ/TOC	TOC Method
A	17 1/2	13 3/8	48		0	270	225	Circ/TOC	
B	12 1/4	8 5/8	24		0	1,000	450	Circ/TOC	
C	7 7/8	4 1/2	10.5/11.6		0	7,621	895	4590	

## FORMATION TOPS

Formation	Top	Formation	Top
SA	548		
Abo	3888		
Cisco	6145		
L. Canyon	6996		
Strawn	7245		
atoka	7609		
Morrow Cl	7806		
Chester	7939		
Mississippian	8062		

## TUBING DETAIL

#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft)	Top (ftKB)	Botm (ftKB)
		2 3/8" Tubing & Packer						6184'	

## Perforation Detail

Formation	Top	Bottom	Treatment
WC	5,015	5,020	1000g 15% DS-30 & N2
Cisco	6,214	6,226	2000g of 15% DS-30 & 100000g 20% Doleitol acid
Canyon	7,248	7,254	1000g of 15% DS-30
Strawn	7404	7408	1000g 15% DS-30 & N2

DKC 2/10/21

PBTD: 7,562 MD  
 TD: 8,200 MD

TOC @ 4590

Top of primary cmt @ 5112 KB. Perf csg @ 5100  
 & block sqz w/50 sx Poz Mix + 50 sx Cl C

Perf A

Perf B

Packer w/standing valve @ 7203

Perf C

Packer w/standing valve @ 7374

Perf D



**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.





# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm

In Reply Refer To: 1310

TAKE PRIDE  
IN AMERICA

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the riggers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you



have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Melissa Horn  
Environmental Protection Specialist  
575-234-5951

Kelsey Wade  
Environmental Protection Specialist  
575-234-2220

Trishia Bad Bear, Hobbs Field Station  
Natural Resource Specialist  
575-393-3612

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 52401

**CONDITIONS**

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 52401
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	None	9/30/2021