

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT Sundry Print Report

Well Name: BANQUET BKQ FEDERAL Well Location: T21S / R21E / SEC 24 / County or Parish/State: EDDY /

NWSW /

...

NM

Well Number: 1 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM100817 Unit or CA Name: Unit or CA Number:

US Well Number: 300153631600S1 Well Status: Gas Well Shut In Operator: EOG RESOURCES

INCORPORATED

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 06/16/2021 Time Sundry Submitted: 09:44

Date proposed operation will begin: 07/05/2021

Procedure Description: Please see attached. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Banquet_BKQ_Federal_1_6_16_21_20210616094354.pdf

Conditions of Approval

Specialist Review

Banquet_BKQ_Federal_1_Sundry_ID_2503685_P_A_20210703114634.pdf

Page 1 of 2

rceived by OCD: 10/6/2021 9:24:37 AM Well Name: BANQUET BKQ FEDERAL Well Location: T21S / R21E / SEC 24 / County or Parish/State: EDDY /

NWSW /

Well Number: 1 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM100817 Unit or CA Name: Unit or CA Number:

US Well Number: 300153631600S1 Well Status: Gas Well Shut In Operator: EOG RESOURCES

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA Signed on: JUN 16, 2021 09:44 AM

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 104 SOUTH FOURTH STREET

City: Artesia State: NM

Phone: (575) 748-4168

Email address: tina_huerta@eogresources.com

Field Representative

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: LVO@FAKE.GOV

Disposition: Approved **Disposition Date:** 07/03/2021

Signature: Long Vo

Page 2 of 2

30-015-36316

EOG Resources, Inc. plans to plug and abandon this well as follows:

- 1. MIRU all safety equipment as needed. NU BOP. POOH with production equipment.
- 2. Set a CIBP at 7902 ft with 18 sx Class H cement on top to 7744 ft. WOC and tag. This will cover Atoka perfs and top. 92 EX
- 3. Set a CIBP at 7310 ft with 18 sx Class H cement on top to 7152 ft. WOC and tag. This will cover
- Strawn perfs and top.

 4. Set a CIBP at 5905 ft with 15 sx Class C cement on top to 5757 ft. WOC and tag. This will cover Cisco perfs and top. Lenk test CIBP
- 5. Spot a 25 sx Class C cement plug from 4751 ft 4504 ft. This will cover Wolfcamp top.
- 6. Spot a 25 sx Class C cement plug from 3570 ft 3323 ft. This will cover Abo top.
- 7. Spot a 25 sx Class C cement plug from 2946 ft 2699 ft. This will cover L Yeso top.
- 8. Spot a 25 sx Class C cement plug from 2833 ft 2586 ft. This will cover Tubb top.
- 9. Perforate at 2172 ft. Spot a 26 sx Class C cement plug from 2172 ft 1916 ft. WOC and tag. This will cover U Yeso, Glorieta tops and casing shoe. Surface
- 10. Perforate at 644 ft. Spot a 31 sx Class C cement plug from 644 ft 388 ft. WOC and tag. This will cover San Andres top and casing shoe. Verity @ surface
- 11. Spot a 10 sx Class C cement plug from 98 ft up to surface. WOC and tag. Back fill as needed
- 12. Cut off wellhead and install dry hole marker. Clean location as per regulated.

Wellbore schematics attached

Carre	
H. A.	フ

Page 2 to the read of the control good Page 2 to the read of the control good Page 2 to the read of the control good Page 2 to the read of the control good Page 2 to the read of the read of the control good Page 2 to the read of the r	## HOLE SIZE SIZE WOHT ## HOLE SIZE ## HOL		CCCF COM		
Color Colo	8: Upper Yeach Cloudes + Casing Stoce 9: Stand Andress + Casing Stoce 9: Stand Andress + Casing Stoce 9: Stand Andress + Casing Stoce 9: Upper Yeach Cloudes + Casing Stoce 9: Upper Yeach Cloudes + Casing Stoce 9: Stand Andress + Casing Stoce 9: Upper Yeach Cloudes + Casing Stoce 9: Stand Andress + C				
E Sinch Marker L' Califor 4 Califor 1 Califor	8: Sand Andrines + Cusing Shope 8: Upper Years + Caring Shope 9: Caring Shope 9: Upper Years + C	WGHT 48	Top		Circ/TOC TOC Method
## Short Andrew - Cabing Show Cabing Show	8: Sand Andries + Chasing Shoe 8: Upper Years + Chaning Shoe 8: Upper Years + Chaning Shoe 9: Lover Years 17p 17: Tubb 17p 18: Lover Years 17p 19: Lov	36	000		
# Short Andrew - Claims Show # Upper Year - Claims Top # Local Year - Cla	8: Upper Yeso + Clorinia Casing Shoe 8: Upper Yeso Top 9: Upper Yeso T	15.5. 17			25
1	## CORNATION TOPS ## John's Perfection Detail ## John's Perfection Detai				Circ
Friend Type Chart	## CIBP + Classing Shoe ## Joining ## Joining ## Joining ## Classing ## Joining ## J				
Common C	C. CIBP + Stravm Paris + Aubia		1		
7. Trub Trip 6. Comer Year Trip 7. College - Strong Trip 7. College	7. Tubb Top 6. Lover Yeso Top 7. Lover Yeso Top 8. Lover Top 8. Lover Yeso Top 8. Lover Top 8. Lover Yeso Top 8. Lover Top 8. Lover Yeso T		TOTAL	<u> </u>	Top
Color From Paris Color From	7: Tubb Top 6: Lower Yeao Top 6: Lower Yeao Top 7: Lower Year				
CLORD Top CONTROL TOP CO	## CIBP + Aloka perfs + Aloka 70p CIBP + Aloka 20p C				
Color Vino Top Color Of Top Co	E. CIBP + Aloka perfs + Aloka 70p CIBP + Aloka 70p CIBP + Aloka 70p CIBP + Aloka perfs + Aloka 70p CIBP + Aloka perfs + Aloka 70p CIBP + Al				
College Altoing parts Al	S. Lower Year Top S. Abo Top S. Abo Top S. Worksamp Top Flow thru play @ 7902 CIBP + Strawn Top Flow thru play @ 7903 CIBP + Strawn Top S. Worksamp Top Flow thru play @ 7902 CIBP + Strawn Top CIBP + Strawn Top Flow thru play @ 7902 CIBP + Strawn Top				
Client Vea 70p Client Ve	S: Lower Yeso Top S: Workamp				
CIRP + Circum Top	CIBP + Strawn Perfs + Atoka pe	dms			
CARP + CARD Part Annual Pa	CIBP + Claro perfs + Aloka Top CIBP + Aloka perfs + Aloka Top CIBP + Aloka perfs + Aloka Top CIBP +				
CIRP + Cisco perfs + Alois p	S: Wolfcamp Top I: Wol				
TUBING DEFAIL Foreign Langth Characteristics Langth Characteristics Langth Characteristics Characteris	CIBP + Strawn Perfs + Atoka				
CIBP + Claco perís + Claco Top Figure 1	CIBP + Cisco perfs + Cisco Top CIBP + Strawn Perfs + Strawn Top CIBP + Aloka perfs + Aloka 70p CIBP + Aloka 70p CIPP + Alo				
TUBINO DETAIL # Johns Detail Condition Condi	CIBP + Claco perís + Claco Top CIBP + Sirawn Perís + Aloka perís + Alok				
CIBP + Stream Paris + Stream Top CIBP + Stream Paris + Stream Top CIBP + Stream Paris + St	CIBP + Strawn Perfs + Aloka perfs + Aloka 70p CIBP + Aloka perfs + Aloka 70p CIBP + Strawn 70p CIPP + Str				
CIBP + Strawn Perfs + Strawn Top From thru plag @ 7902 CIBP + Cibro parks CiBP + Strawn Top CiBP + Strawn Perfs + Strawn Top CiBP + CiBP + Strawn Perfs + Strawn Top CiBP + CiBP CiBP	CIBP + Cisco perfs + Cisco Top CIBP + Strawn Perfs + Strawn Top CIBP + Strawn Perfs + Aloka perfs + Aloka Top CIBP + Aloka perfs + Aloka Top CIBP + Aloka perfs + Aloka Top CIBP + Strawn Perfs + Strawn Top CIBP + Aloka perfs + Aloka Top CIBP + Aloka perfs + Aloka Top CIBP + Aloka Perfs + Cibr Top CIBP + Aloka Perfs + Cibr Top CIBP + Strawn Top CIPP + Strawn Top	Londit			
CIBP + Claco parts + Claco Top Flow thrus play @ 7902 CIBP + Aloke perfs + Aloke Top Flow thrus play @ 7902 CIBP + Aloke perfs + Aloke Top Flow thrus play @ 7902 Flow thrus play & 7702 Flow t	CIBP + Claco perfs + Claco Top Flow thru plug @ 7302 CIBP at 7235 RBP at 7235 CIBP at 8043 A Morrow 6,036 CIBP at 8043 A Morrow 6,036 CIBP + Aloka perfs + Aloka 70p Plugs CIBP + Aloka perfs + Aloka 70p CIBP + Aloka 70p	\dagger	Q		Top (ftKB): Btm (ftKB):
CIBP + Strawn Perfs + Strawn Top Four thru plug @ 7902	CIBP + Strawn Perfs + Strawn Top CIBP + Atoka perfs + Atoka 70p CIBP +	tubing and packer			
CIBP + Strawn Perfs + Strawn Top CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p	CIBP + Strawn Perfs + Strawn Top CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka Perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka Perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka Perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka Perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka Perfs + Atoka Top CIBP + Atoka Top CIPP				
CIBP + Strawn Top Perforation Detail Formation Top Bottom	CIBP + Strawn Parts + Strawn Top Perforation Datail Perforation Dat				
CIBP + Strawn Perfs + Strawn Top Perforation Detail Formation Top Bottom Rober Post Perforation P	CIBP + Strawn Perfs + Strawn Top Performation Detail Performation Top Bottom 8,126 1,738				
CIBP + Strawn Top Formation Detail Formation Detail Formation Detail Formation Top Bottom A Mourow B.098 B.126 Formation Top Bottom A Mourow B.098 B.126 Formation Top B.098 Formation Top Formation Top B.098 Formation Top B.098 Formation Top	CIBP + Strawn Top Ferforation Detail Ferforati				
CIBP + Atoka parís + Atoka Top CIBP + Atoka Top CI	CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p CIPP + Atoka 7				
CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIPP	CIBP + Atoka parfs + Atoka Top TiBR SX CIBBS TOP TiBR H T744 TiBR H T7744 TiBR H T774				
CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p CI	CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p CIBP + Atoka perfs + Atoka 70p CIBP + Atoka 70p	Bottom	T		
CIBP + Atoka perfs + Atoka Top CIBP + Atoka T	CIBP + Atoka perfs + Atoka Top TIBP + Top TIPP + Top TI		l reatment		
CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIBP + Atoka perfs + Atoka Top CIBP + Atoka Top CIPP + A	CIBP + Atoka perfs + Atoka Top Flugs # SX Class Top 1 196 H 7744 2 18		Acidized w/3000g 7-1/2% acid ar	d 1000# rock salt	
CIBP + Atoka perfs + Atoka Top CIBP + Atoka T	CIBP + Atoka perfs + Atoka Top Plugs # SX Class Top # T744 2 18 H 7744 2 18 C 500 5 500 5 500 6 600 7 25 C 5600 7 25 C 2690 7 25 C 2690 7 25 C 2690	-	Acidized w/4000g 15% NEFE aci	d and 20 balls	
CIBP + Atoka perfs + Atoka Top Plugs # SX Class Top Bottom 1 1975 H 7744 7902 2 18 H 7744 7902 3 16 C 3323 3570 6 25 C 2889 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 7 26 8 289 2946 7 8 28 C 3323 3570 8 28 28 C 3329 3570 9 34 70 C 396 0 844	CIBP + Atoka perfs + Aloka Top Plugs # SX Class Top # T744 2 18 H 7744 2 18 H 7744 2 18 Class Top 1 15 C 5399 6 4504 7 25 C 5899 7 26 C 2899 7 26 C 2899		Acidized w/1000g 7-1/2%IC acid		
CIBP + Atoka perfs + Atoka Top Plugs # SX Class Top Betom # SX Class Top Betom # T774 T792 # T774 T792 # T774 T792 # T775 # T774 T792 # T775 # T774 T792 # T775 # T775 # T776 # T777	CIBP + Atoka perfs + Atoka Top Plugs Plugs # SX Class Top 1 18 H 7744 2 18 H 7752 3 15 C 5757 4 25 C 2689 7 25 C 2689 7 25 C 2689	-	Acidized w/3000g 7-1/2% HCL ar	d 60 BS	
CIBP + Atoka perfs + Atoka Top Plugs # SX Class Top Bottom # 126 C 5757 5985 4 25 C 4504 4751 5 25 C 4504 4751 6 25 C 2569 2946 7 26 C 1916 2172 9 34 70 C 396 C 644	CIBP + Atoka perfs + Atoka Top Plugs # SX Class Top 1 18 H 7744 2 18 H 7744 2 18 H 7752 3 15 C 5767 5 25 C 3323 6 25 C 2699 7 26 C 1916		Acidized w/2500g 20% gelled aci		
Plugs 1	Plugs SX Class Top 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Acidized 6104-6138 w/2500g 209	gelled acid	
Plugs # SX Class Top Bottom 1 19.55 H 7744 7902 3 18 H 7744 7902 3 18 C 5787 2986 4 25 C 5787 2986 7 25 C 2889 2946 7 25 C 2889 2946 7 25 C 2889 2946 7 26 C 3323 3570 7 26 C 2889 2946 10 30 0 0 0 0	Plugs # SX Class Top 1 18 H 7744 2 18 H 7744 2 18 C 5767 3 15 C 5767 4 25 C 5769 5 25 C 2699 7 26 26 C 2699 7 26 C 2699		Acidized 5930-6138 w/2500g 20%	o delled acid and 60 halls	
C STATE OF S	Tidgs SX Class Top 1 <t< td=""><td></td><td></td><td></td><td></td></t<>				
C STORY OF S	7 3X Class TOP 1 1 1 1744 2 18 H 7742 3 15 C 5757 4 25 C 5767 5 25 C 3323 6 25 C 2699 7 26 C 2699 8 26 C 1916				
C 5 1 18	C	Top	٧	T CeT	
C 18 H 7152 7310 156 Strawn Peris - Strawn Peris - Strawn Peris - Strawn Peris - Strawn Top 156 C 1567 596 148 Cleop Peris - Strawn Top 156 C 25 C 3323 3570 2946 247 Wolfeamp Top 17 256 C 2598 2946 247 Lower Yeas Top 17 256 C 2588 283 247 Lower Yeas Top 10 34 70 C 2588 283 247 Lower Yeas Top 10 40 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 18 H 7152 3 15 C 5767 4 25 C 4504 5 25 C 3323 6 25 C 2689 7 25 C 2689 8 26 C 1916	-			
3 15 C 5757 5986 148 Clisco Perfs - Surfamin Top 4 25 C 4504 4751 247 Wolfcamp Top 5 25 C 3323 3570 247 Abo Top 7 25 C 2689 2946 247 Lower Yeas Top 8 26 C 1916 2172 256 Upper Yeas - Clinicla + Casing Shoe 10 10 C 396 C 644 306 Sen Andres + Casing Shoe 10 10 0 0 98 98 Sen Andres + Casing Shoe 10 10 0 0 0 0 0 11 12 0 0 0 0 0 12 0 0 0 0 0 0 13 0 0 0 0 0 0 14 0 0 0 0 0 0 15 0 0 0 0 0 0 16 0 0 0 0 0 0 17 0 0 0 0 0 0 18 0 0 0 0 0 0 19 0 0 0 0 0 0 10 0 0 0 0 0 0 10 0 0 0 0 0 0 10 0 0 0 0 0 0 10 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 0 10 0 0 0 0 0 0 0 0 0	3 15 C 5767 4 25 C 4604 5 25 C 3323 6 25 C 2899 7 25 C 2899 8 26 C 1916		158		
4 25 C 4564 4751 149 UBGD Feffs + Clack Top 5 25 C 3323 3570 247 Wolfcamp Top 6 25 C 2899 2946 247 Wolfcamp Top 7 25 C 2896 2833 247 Tub Top 8 26 C 1916 2172 256 Upper Yeso + Gloride + Casing Shoe 10 10 0 0 98 90 San Andree + Casing Shoe 10 10 0 0 0 0 0 11 12 13 14 0 0 0 12 14 15 15 15 15 15 13 14 15 15 15 15 15 15 15	4 25 C 4604 5 25 C 3323 6 25 C 2699 7 25 C 2696 8 26 C 1916	T	140		
5 25 C 38.23 3570 2.47 Wolfcamp Top 6 25 C 2899 2946 247 Wolfcamp Top 7 255 C 2899 2946 247 Lower Year Opp 7 255 C 2896 2833 247 Lower Year Opp 8 26 C 1916 2172 256 Upper Year + Casing Shoe 10 40 644 396 San Andrea + Casing Shoe 10 40 69 89 Sear Andrea + Casing Shoe	6 25 C C C C C C C C C C C C C C C C C C	t	140		
25 C 2639 2946 247 Abo Top 25 C 2639 2946 247 Lower Yeso Top 26 C 2658 2833 2843 Lower Yeso Top 27 C 268 2833 2843 See Opp 28 C 1916 2172 286 Upper Yeso Horieta + Casing Shoe 34 70 C 336 644 306 San Andres + Casing Shoe	25 C C 26 C C 26 C C	+			
26 C 2889 2946 247 Lower Yeso Top 26 C 1916 2172 26 Upper Yeso + Glories + Casing Shoe 34 70 C 396 644 266 San Andres + Casing Shoe 40 6 644 866 San Andres + Casing Shoe	25 C C 26 C C	+			
25 C 2586 2833 247 Tubb Top 26 C 1916 2172 256 Upper Yeac + Gloriels + Casing Shoe 34 70 C 326 644 306 San Andres + Casing Shoe 40 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	25 C	+			
26 C 1916 2172 256 Upper Yeso + Gloriela + Casing Shoe 347 C 336 C 644 306 San Andres + Casing Shoe 40 C 98 6 San Andres + Casing Shoe 64 806 San Andres Plug	26 C	1			
34 0 C 39 644 396 San Andres + Casing Since Andre + Casing	The same of the sa	-		F	The second secon
10 C 0 88 00 County Street	0 01 %		-	+	
Gill dosing	10 G			1	
PBTD: 7,295 MD	7,295 MD				

High Cave

TOC Methoc Btm (ftKB): Acidized 5930-6138 w/2500g 20% gelled acid and 60 balls Acidized w/3000g 7-1/2% acid and 1000# rock sal Circ/TOC Acidized w/4000g 15% NEFE acid and 20 balls Acidized 6104-6138 w/2500g 20% gelled acid Top (ftKB): Circ Circ Circ 5,830 Acidized w/3000g 7-1/2% HCL and 60 BS Top Acidized w/2500g 20% gelled acid API: 30-015-36316 GL: 4537 KB: 4555 Acidized w/1000g 7-1/2%IC acid Sx Cmt 1180 Grade | Wt (lb/ft): 785 915 Formation Bottom 2,122 8,500 417 Treatment Top 0 0 C ₽ GRADE J-55, L-80 H-40 J-55 OD 2783 2896 3520 Sec-TWN-RNG: | Sec. 24-21S-21E FOOTAGES: | 1680'FSL & 840'FWL 4701 5910 7,990 7,738 7,612 6,496 15.5, 17 WGHT Length 36 2-7/8" Tubing and packer Bottom Top Glorieta Upper Yeso Tubb Lower Yeso Formation San Andres Description 8,098 7,952 7,730 7,396 5,930 13 3/8 SIZE 9 2/8 5 1/2 Wolfcamp Prepared by: TH Strawn Cisco Atoka Abo Top Flow thru plug @ 7902 CIBP at 8058 17 1/2 12 1/4 HOLE SIZE 8 3/4 FORMATION TOPS Joints CASING DETAIL Perforation Detail TUBING DETAIL Formation Morrow Strawn Strawn Atoka RBP at 7295 * Ø В O Banquet BKQ Federal 1 Current Flow Thru Plug QW QW 7,295 PBTD: TD: O Perf E PerfD Perf C Perf B Perf A

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification</u>: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the

Released to Imaging: 10/7/2021 7:34:47 AM

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

 The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The number, name of the operator, lease serial number, surveyed location (quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized
- 7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of casing left in the well.
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Received by OCD: 1066/2021-9:24:37 AM



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/mn



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration. including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have therisers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to

- 1. The Application for Permit to Drill or Reemer (APD, Form 3160-3). Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Supervisory Petroleum Engineering Tech 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist

Melissa Horn Environmental Protection Specialist 575-234-5951

Kelsey Wade Environmental Protection Specialist

Trishia Bad Bear, Hobbs Field Station Natural Resource Specialist 575-393-3612



U.S. Department of the Interior BUREAU OF LAND MANAGEMENT Sundry Print Report

Well Name: BANQUET BKQ FEDERAL Well Location: T21S / R21E / SEC 24 / County or Parish/State: EDDY /

NWSW /

Type of Well: CONVENTIONAL GAS Well Number: 1

Allottee or Tribe Name:

Unit or CA Number: Unit or CA Name:

US Well Number: 300153631600S1 Well Status: Gas Well Shut In **Operator:** EOG RESOURCES

INCORPORATED

Accepted for record – NMOCD gc 10/5/2021

Notice of Intent

Lease Number: NMNM100817

Sundry ID: 2637129

Type of Submission: Notice of Intent Type of Action: Plug and Abandonment

Date Sundry Submitted: 10/04/2021 **Time Sundry Submitted: 11:01**

Date proposed operation will begin: 10/12/2021

Procedure Description: EOG Resources, Inc. requests a 90 day extension for the NOI to P&A that was submitted 6/16/21, approved 7/3/21 and expires on 10/3/21. This is due to complications during plugging and we had to move off and plan to continue plugging on 10/12/21. Thank you.

Surface Disturbance

Is any additional surface disturbance proposed?: No

Page 1 of 2

red by OCD: 10/6/2021 9:24:37 AM eli Name: BANQUET BKQ FEDERAL Well Location: T21S / R21E / SEC 24 / County or Parish/State: Page 11 of

NWSW /

Well Number: 1 Type of Well: CONVENTIONAL GAS Allottee or Tribe Name:

WELL

Lease Number: NMNM100817 Unit or CA Name: **Unit or CA Number:**

US Well Number: 300153631600S1 Well Status: Gas Well Shut In **Operator:** EOG RESOURCES

INCORPORATED

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: TINA HUERTA Signed on: OCT 04, 2021 11:01 AM

Name: EOG RESOURCES INCORPORATED

Title: Regulatory Specialist

Street Address: 104 SOUTH FOURTH STREET

City: Artesia State: NM

Phone: (575) 748-4168

Email address: tina_huerta@eogresources.com

Field Representative

Representative Name:

Street Address:

State: City: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved Disposition Date: 10/06/2021

Signature: Long Vo

Page 2 of 2

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 54372

CONDITIONS

Operator:	OGRID:
EOG RESOURCES INC	7377
P.O. Box 2267	Action Number:
Midland, TX 79702	54372
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	10/6/2021