

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-015-26383
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-2531
7. Lease Name or Unit Agreement Name Algerita AHR State
8. Well Number 1
9. OGRID Number 7377
10. Pool name or Wildcat Dagger Draw; Upper Penn, South

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other P&A <input type="checkbox"/>	
2. Name of Operator EOG Resources, Inc.	
3. Address of Operator 104 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>H</u> : <u>1980</u> feet from the <u>North</u> line and <u>660</u> feet from the <u>East</u> line Section <u>16</u> Township <u>20S</u> Range <u>24E</u> NMPM <u>Eddy</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3718'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐
 CLOSED-LOOP SYSTEM ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☒
 CASING/CEMENT JOB ☐
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/25/21 – MIRU and NU BOP. RIH with casing scraper and tagged top of fish at 7286'.

10/27/21 – Rigged down. Waiting on approval to continued plugging well.

1/27/22 – MIRU and NU BOP to continue plugging operations. Set a CIBP at 7284'. Pressured up to 600 psi, held good. Texted David Alvarado with NMOCD-Artesia and let him know set CIBP and pressure tested and he was good with it. Spotted 45 sx Class "C" cement on top of CIBP to 7268'.

1/28/22 – Tagged TOC 7268'. Tag was 257' low, called David Alvarado with NMOCD-Artesia and let him know and need to pump another 35 sx cement and retag. Spotted another 35 sx Class "C" cement from 7268'-7090', tagged. David Alvarado was good with tag. Perforated at 5550'. Pressured up to 550 psi, good. Spotted a 35 sx Class "C" cement plug from 5665'-5495', tagged. David Alvarado was good with tag.

1/31/22 – Spotted a 55 sx Class "C" cement plug from 5332'-4995'. No tag required. Spotted a 35 sx Class "C" cement plug from 2060'-1846'. No tag required. Perforated at 1274'. Pressure tested to 550 psi for 15 min, held good. Texted David Alvarado and let him know we could not circulate and drop down 50' and spot 40 sx cement. Spotted a 40 sx Class "C" cement plug from 1330'-1225', tagged.

2/1/22 – Re-spotted with 25 sx Class "C" cement from 1225'-1076' calc TOC. David Alvarado gave approval to forego tagging this plug at 9:30 AM.

Spotted 80 sx Class "C" cement from 488' and circulated up to surface. David Alvarado with NMOCD-Artesia verified cement to surface by picture, ok.

2/14/22 – Cut off wellhead and installed above ground dry hole marker. Cut off anchors and cleaned location. **WELL IS PLUGGED AND ABANDONED.**

Spud Date:

Rig Release Date:

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Specialist DATE March 4, 2022

Type or print name Tina Huerta E-mail address: tina.huerta@eogresources.com PHONE: 575-748-4168
For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 3/17/2022
 Conditions of Approval (if any):

Algerita AHR State #1		Sec-TWN-RNG: 16-20S-24E	API: 30-015-26383																																																														
		FOOTAGES: 1980' FSL & 660' FEL	GL: 3718																																																														
			KB: 3732																																																														
Plug 8	A	CASING DETAIL <table border="1"> <thead> <tr> <th>#</th> <th>HOLE SIZE</th> <th>SIZE</th> <th>WGHT</th> <th>GRADE</th> <th>Top</th> <th>Bottom</th> <th>Sx Cmt</th> <th>Circ/TOC</th> <th>TOC by</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>14 3/4</td> <td>9 5/8</td> <td>36</td> <td>J-55</td> <td>0</td> <td>1,224</td> <td>1450</td> <td>w/Redi Mix</td> <td></td> </tr> <tr> <td>B</td> <td>8 3/4</td> <td>7</td> <td>23 & 26</td> <td>J-55/N-80</td> <td>0</td> <td>9,400</td> <td>2650</td> <td>2 Stages/Circ</td> <td></td> </tr> <tr> <td colspan="10"> 42 Joints 7" 26# N-80 LT&C (1832.97') 67 Joints 7" 26# J-55 LT&C (2737.68') 58 Joints 7" 25# J-55 LT&C (2348.89') 57 Joints 7" 23# N-80 LT&C (2352.56') 3 Joints 7" 26# N-80 LT&C (133.02') </td> </tr> </tbody> </table>		#	HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC by	A	14 3/4	9 5/8	36	J-55	0	1,224	1450	w/Redi Mix		B	8 3/4	7	23 & 26	J-55/N-80	0	9,400	2650	2 Stages/Circ		42 Joints 7" 26# N-80 LT&C (1832.97') 67 Joints 7" 26# J-55 LT&C (2737.68') 58 Joints 7" 25# J-55 LT&C (2348.89') 57 Joints 7" 23# N-80 LT&C (2352.56') 3 Joints 7" 26# N-80 LT&C (133.02')																															
#		HOLE SIZE	SIZE	WGHT	GRADE	Top	Bottom	Sx Cmt	Circ/TOC	TOC by																																																							
A		14 3/4	9 5/8	36	J-55	0	1,224	1450	w/Redi Mix																																																								
B		8 3/4	7	23 & 26	J-55/N-80	0	9,400	2650	2 Stages/Circ																																																								
42 Joints 7" 26# N-80 LT&C (1832.97') 67 Joints 7" 26# J-55 LT&C (2737.68') 58 Joints 7" 25# J-55 LT&C (2348.89') 57 Joints 7" 23# N-80 LT&C (2352.56') 3 Joints 7" 26# N-80 LT&C (133.02')																																																																	
Plug 7		FORMATION TOPS <table border="1"> <thead> <tr> <th>Formation</th> <th>Top</th> <th>Formation</th> <th>Top</th> </tr> </thead> <tbody> <tr> <td>San Andres</td> <td>430</td> <td></td> <td></td> </tr> <tr> <td>Glorieta</td> <td>1959</td> <td></td> <td></td> </tr> <tr> <td>Yeso</td> <td>2034</td> <td></td> <td></td> </tr> <tr> <td>WC Lm</td> <td>5282</td> <td></td> <td></td> </tr> <tr> <td>Canyon Lm</td> <td>7306</td> <td></td> <td></td> </tr> <tr> <td>Morrow</td> <td>8838</td> <td></td> <td></td> </tr> </tbody> </table>		Formation	Top	Formation	Top	San Andres	430			Glorieta	1959			Yeso	2034			WC Lm	5282			Canyon Lm	7306			Morrow	8838																																				
Formation		Top	Formation	Top																																																													
San Andres		430																																																															
Glorieta		1959																																																															
Yeso		2034																																																															
WC Lm	5282																																																																
Canyon Lm	7306																																																																
Morrow	8838																																																																
Plug 6	TUBING DETAIL <table border="1"> <thead> <tr> <th>#</th> <th>Joints</th> <th>Description</th> <th>Length</th> <th>OD</th> <th>ID</th> <th>Grade</th> <th>Wt (lb/ft)</th> <th>Top (ftKB)</th> <th>Btm (ftKB)</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>3 1/2" Tubing</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>7,260</td> </tr> </tbody> </table>		#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft)	Top (ftKB)	Btm (ftKB)			3 1/2" Tubing							7,260																																											
#	Joints	Description	Length	OD	ID	Grade	Wt (lb/ft)	Top (ftKB)	Btm (ftKB)																																																								
		3 1/2" Tubing							7,260																																																								
Plug 5	NOTES 																																																																
Plug 4	Perforation Detail <table border="1"> <thead> <tr> <th>Formation</th> <th>Top</th> <th>Bottom</th> <th>Treatment</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>Canyon</td> <td>7,438</td> <td>7,572</td> <td>Acidize w/ 2200g 20% NEFE acid; w/14000g 20% NEFE acid; w/900#block</td> <td></td> </tr> </tbody> </table>		Formation	Top	Bottom	Treatment	Notes	Canyon	7,438	7,572	Acidize w/ 2200g 20% NEFE acid; w/14000g 20% NEFE acid; w/900#block																																																						
Formation	Top	Bottom	Treatment	Notes																																																													
Canyon	7,438	7,572	Acidize w/ 2200g 20% NEFE acid; w/14000g 20% NEFE acid; w/900#block																																																														
DV Tool @ 5614	PLUGS <table border="1"> <thead> <tr> <th>#</th> <th>SX</th> <th>Class</th> <th>Top</th> <th>Bottom</th> <th>Tag</th> <th>Notes</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>45</td> <td>C</td> <td>7268</td> <td>7284</td> <td>Y</td> <td>CIBP</td> </tr> <tr> <td>2</td> <td>35</td> <td>C</td> <td>7090</td> <td>7268</td> <td>Y</td> <td></td> </tr> <tr> <td>3</td> <td>35</td> <td>C</td> <td>5495</td> <td>5665</td> <td>Y</td> <td>Perforate</td> </tr> <tr> <td>4</td> <td>55</td> <td>C</td> <td>4995</td> <td>5332</td> <td>N</td> <td></td> </tr> <tr> <td>5</td> <td>35</td> <td>C</td> <td>1846</td> <td>2060</td> <td>N</td> <td></td> </tr> <tr> <td>6</td> <td>40</td> <td>C</td> <td>1225</td> <td>1330</td> <td>Y</td> <td>Perforate</td> </tr> <tr> <td>7</td> <td>25</td> <td>C</td> <td>1076</td> <td>1225</td> <td>N</td> <td></td> </tr> <tr> <td>8</td> <td>80</td> <td>C</td> <td>0</td> <td>488</td> <td>N</td> <td></td> </tr> </tbody> </table>		#	SX	Class	Top	Bottom	Tag	Notes	1	45	C	7268	7284	Y	CIBP	2	35	C	7090	7268	Y		3	35	C	5495	5665	Y	Perforate	4	55	C	4995	5332	N		5	35	C	1846	2060	N		6	40	C	1225	1330	Y	Perforate	7	25	C	1076	1225	N		8	80	C	0	488	N	
#	SX	Class	Top	Bottom	Tag	Notes																																																											
1	45	C	7268	7284	Y	CIBP																																																											
2	35	C	7090	7268	Y																																																												
3	35	C	5495	5665	Y	Perforate																																																											
4	55	C	4995	5332	N																																																												
5	35	C	1846	2060	N																																																												
6	40	C	1225	1330	Y	Perforate																																																											
7	25	C	1076	1225	N																																																												
8	80	C	0	488	N																																																												
Plug 3	ADDITIONAL DETAIL 7/26/2016 Equipment failure WO to lost tbg in hole. Fish not recovered. TOF @ 7289' 2 7/8" TBG set above TOF. Multiple attempts made to recover fish were unsuccessful.																																																																
Plug 2																																																																	
Plug 1																																																																	
Tagged TOF @ 7268'																																																																	
Multiple attempts to recover fish were unsuccessful																																																																	
Canyon perms 7438-7572																																																																	
	B	PBTD: 9,290 MD TD: 9,400 MD																																																															
		3/4/22																																																															

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 87162

CONDITIONS

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 87162
	Action Type: [C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	3/17/2022