

|                            |                                              |                                      |
|----------------------------|----------------------------------------------|--------------------------------------|
| Well Name: FEDERAL 30      | Well Location: T19S / R33E / SEC 30 / NESE / | County or Parish/State: LEA / NM     |
| Well Number: 1             | Type of Well: CONVENTIONAL GAS WELL          | Allottee or Tribe Name:              |
| Lease Number: NMNM073240   | Unit or CA Name: FEDERAL 30                  | Unit or CA Number: NMNM72199         |
| US Well Number: 3002527069 | Well Status: Producing Oil Well              | Operator: MATADOR PRODUCTION COMPANY |

Notice of Intent

Sundry ID: 2662625

Type of Submission: Notice of Intent

Date Sundry Submitted: 03/17/2022

Date proposed operation will begin: 05/01/2022

Type of Action: Plug and Abandonment

Time Sundry Submitted: 10:32

Procedure Description: Matador requests the extension of the previously approved NOI P&A. Matador has had trouble securing a P&A rig, but Matador has secured a rig and plan to plug in or around May 1.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

BLM\_approved\_08.17.21\_20220317103052.pdf

Accepted for Record Only

SUBJECT TO LIKE  
APPROVAL BY BLM

K7

NMOCD 4/15/22

Received by OCD: 4/14/2022 8:48:24 AM

Well Name: FEDERAL 30

Well Location: T19S / R33E / SEC 30 / NESE /

County or Parish/State: LEA / NM

Well Number: 1

Type of Well: CONVENTIONAL GAS WELL

Allottee or Tribe Name:

Lease Number: NMNM073240

Unit or CA Name: FEDERAL 30

Unit or CA Number: NMNM72199

US Well Number: 3002527069

Well Status: Producing Oil Well

Operator: MATADOR PRODUCTION COMPANY

Conditions of Approval

Specialist Review  
Federal\_30\_1\_Sundry\_ID\_2662625\_P\_A\_20220414081610.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: BRETT JENNINGS

Signed on: MAR 17, 2022 10:31 AM

Name: MATADOR PRODUCTION COMPANY

Title: Regulatory Analyst

Street Address: 5400 LBJ FREEWAY, STE 1500

City: DALLASState: TX

Phone: (972) 629-2160

Email address: BRETT.JENNINGS@MATADORRESOURCES.COM

Field Representative

Representative Name:

Street Address:

City:State:Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved

Disposition Date: 04/14/2022

Signature: Long Vo

|                            |                                              |                                      |
|----------------------------|----------------------------------------------|--------------------------------------|
| Well Name: FEDERAL 30      | Well Location: T19S / R33E / SEC 30 / NESE / | County or Parish/State: LEA / NM     |
| Well Number: 1             | Type of Well: CONVENTIONAL GAS WELL          | Allottee or Tribe Name:              |
| Lease Number: NMNM073240   | Unit or CA Name: FEDERAL 30                  | Unit or CA Number: NMNM72199         |
| US Well Number: 3002527069 | Well Status: Producing Oil Well              | Operator: MATADOR PRODUCTION COMPANY |

Notice of Intent

Type of Submission: Notice of Intent

Type of Action Plug and Abandonment

Date Sundry Submitted: 08/10/2021

Time Sundry Submitted: 01:17

Date proposed operation will begin: 09/14/2021

**Procedure Description:** \*Resubmitting due to characters in file name. Matador is requesting to plug and abandon the Federal 30 #1, per the required COA, following the procedure below: • Notify NMOCD 24 hrs before MIRU. • Safety mtg, MIRU, check pressures, pull rods and pump. • ND wellhead, NU BOPs & TOO H w/ tbg. • RU WL. WL set CIBP @ 7,766'. RD WL. TIH w/ tbg and spot 35 sx CI H cmt on top of CIBP. WOC & Tag. • Circ and displace hole w/ MLF. Come up & perf @ 5,260, sqz CI C cmt. Spot from 5,260 – 5,110'. WOC & Tag. • Perf @ 3,290' & sqz CI C cmt. Spot from 3,290' – 3,160'. WOC & Tag. • Perf @ 1,326' & Sqz CI C cmt to surface. • Cut off wellhead and ensure cmt to surface on all csg strings. • Install above ground marker per BLM and NMOCD specifications. \*Current and proposed wellbore diagrams attached \*\*Mud laden fluid (MLF) mixed at 25sx/100 bbls water will be spotted between each plug. Additional information attached

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

- Procedure Description
- Federal\_30\_1\_\_Procedure\_20210810131631.pdf
  - Federal\_30\_1\_\_Proposed\_PA\_WBD\_20210810131626.pdf
  - Federal\_30\_1\_\_Current\_WBD\_20210810131619.pdf

|                                   |                                                     |                                             |
|-----------------------------------|-----------------------------------------------------|---------------------------------------------|
| <b>Well Name:</b> FEDERAL 30      | <b>Well Location:</b> T19S / R33E / SEC 30 / NESE / | <b>County or Parish/State:</b> LEA / NM     |
| <b>Well Number:</b> 1             | <b>Type of Well:</b> CONVENTIONAL GAS WELL          | <b>Allottee or Tribe Name:</b>              |
| <b>Lease Number:</b> NMNM073240   | <b>Unit or CA Name:</b> FEDERAL 30                  | <b>Unit or CA Number:</b> NMNM72199         |
| <b>US Well Number:</b> 3002527069 | <b>Well Status:</b> Producing Oil Well              | <b>Operator:</b> MATADOR PRODUCTION COMPANY |

Conditions of Approval

Specialist Review  
Federal\_30\_1\_Sundry\_ID\_2628174\_P\_A\_20210814103314.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

**Operator Electronic Signature:** BRETT JENNINGS  
**Signed on:** AUG 10, 2021 01:16 PM  
**Name:** MATADOR PRODUCTION COMPANY  
**Title:** Regulatory Analyst  
**Street Address:** 5400 LBJ FREEWAY, STE 1500  
**City:** DALLAS **State:** TX  
**Phone:** (972) 629-2160  
**Email address:** BRETT.JENNINGS@MATADORRESOURCES.COM

Field Representative

**Representative Name:**  
**Street Address:**  
**City:** **State:** **Zip:**  
**Phone:**  
**Email address:**

BLM Point of Contact

**BLM POC Name:** LONG VO  
**BLM POC Phone:** 5752345972  
**Disposition:** Approved  
**Signature:** Long Vo  
**BLM POC Title:** Petroleum Engineer  
**BLM POC Email Address:** LVO@BLM.GOV  
**Disposition Date:** 08/14/2021


---

Matador is requesting to plug and abandon the Federal 30 #1, per the required COA, following the procedure below:

- Notify NMOCD 24 hrs before MIRU.
- Safety mtg, MIRU, check pressures, pull rods and pump.
- ND wellhead, NU BOPs & TOOH w/ tbg.
- RU WL. WL set CIBP @ 7,766'. RD WL. TIH w/ tbg and spot 35 sx Cl H cmt on top of CIBP. WOC & Tag.
- Circ and displace hole w/ MLF. Come up & perf @ 5,260, sqz Cl C cmt. Spot from 5,260 – 5,110'. WOC & Tag.
- Perf @ 3,290' & sqz Cl C cmt. Spot from 3,290' – 3,160'. WOC & Tag.
- Perf @ 1,326' & Sqz Cl C cmt to surface.
- Cut off wellhead and ensure cmt to surface on all csg strings.
- Install above ground marker per BLM and NMOCD specifications.

\*Current and proposed wellbore diagrams attached

Matador Production Company  
Federal 30 #1  
1980' FSL & 760' FEL Sec 30 - 19S - 33E  
Lea County, NM  
API: 30-025-27069  
**CURRENT WELLBORE SCHEMATIC**  
Spudded: 6/19/1981




| Casing Information |               |                                       |          |           |                                    |        |
|--------------------|---------------|---------------------------------------|----------|-----------|------------------------------------|--------|
|                    | Casing Size   | Weight lb/ft                          | Depth Se | Hole Size | Cementing Record                   |        |
| Surface            | 13 3/8        | 48# H40 ST&C                          | 1276'    | 17 1/2    | 975 sks. Class "C"                 |        |
| Intermediate       | 9 5/8         | 76 jts 36# K55 & 50 jts 40# K55       | 5310'    | 12 1/4    | 3440 sks. Halib. Lite              |        |
| Production         | 5 1/2         | 230 jts 17# K55, N80 & 90 jts 20# N80 | 13712'   | 8 3/4     | 2150 sks. Halib. Lite (TOC @ 5250) |        |
| Production Casing  |               |                                       |          |           |                                    |        |
|                    | Prod. Casing  | Weight                                | Joints   | Length    | Top                                | Bottom |
| Top                | N-80 Buttress | 17#                                   | 64       | 2665      |                                    | 2640   |
|                    | X-over        | 17#                                   | 1        | 42        | 2640                               | 2682   |
|                    | K-55 ST&C     | 17#                                   | 166      | 6985      | 2682                               | 9666   |
|                    | N-80 ST&C     | 20#                                   | 3        | 124       | 9666                               | 9791   |
|                    | DV Tool       |                                       |          | 3         | 9791                               | 9794   |
|                    | N-80 ST&C     | 20#                                   | 87       | 3876      | 9794                               | 13670  |
|                    | Float Collar  |                                       |          | 2         | 13670                              | 13672  |
|                    | N-80 ST&C     | 20#                                   | 1        | 39        | 13672                              | 13711  |
| Bottom             | Guide Shoe    |                                       |          | 1         | 13711                              | 13712  |

| Tubing String - 2-7/8" #6.5 L-80 (KB 20') |                                 |       |
|-------------------------------------------|---------------------------------|-------|
| Item                                      |                                 | Depth |
| 2-7/8"                                    | 244 joints                      | 7326  |
| TAC                                       | Set w/ 14k tension              | 7329  |
| 2-7/8"                                    | 10 joints                       | 7627  |
| SN (Mech)                                 | Mechanical SN                   | 7628  |
| Pup Jt                                    | 4.2'                            | 7632  |
| Desander                                  | 3" x 25'                        | 7657  |
| 2 7/8"                                    | 5 jts tail pipe                 | 7808  |
| Bull Plug                                 |                                 | 7809  |
| PBTD                                      | TCP Guns/Fish                   | 7842  |
| Rod String                                |                                 |       |
| Item                                      |                                 | Depth |
| Polish Rod                                | 1 1/2 x 1 1/4 liner x 26' (-3') |       |
| 7/8"                                      | 84 Weatherford HD               |       |
| 3/4" Rods                                 | 189 Norris 97 Rods              |       |
| 7/8" Rods                                 | 34 Weatherford HD               |       |
| Pump                                      | 2.5 x 1.75 x 20-6-4 RHBM        |       |

| Geologic Markers |        |
|------------------|--------|
| San Andres       | 2200'  |
| Delaware Sand    | 5340'  |
| Bone Springs     | 7880'  |
| Wolfcamp         | 10818' |
| Cisco            | 11752' |
| Strawn           | 12078' |
| Atoka            | 12410' |
| Atoka Ls.        | 12748' |
| Morrow Ls.       | 12916' |
| Morrow Clastic   | 13015' |
| T.D.             | 13712' |

Matador Production Company  
Federal 30 #1  
1980' FSL & 760' FEL Sec 30 - 19S - 33E  
Lea County, NM  
API: 30-025-27069  
**PROPOSED P&A WELLBORE SCHEMATIC**  
Spudded: 6/19/1981



| Casing Information |               |                                       |           |           |                                  |        |
|--------------------|---------------|---------------------------------------|-----------|-----------|----------------------------------|--------|
|                    | Casing Size   | Weight lb/ft                          | Depth Set | Hole Size | Cementing Record                 |        |
| Surface            | 13 3/8        | 48# H40 ST&C                          | 1276'     | 17 1/2    | 975 sx Class "C"                 |        |
| Intermediate       | 9 5/8         | 76 jts 36# K55 & 50 jts 40# K55       | 5310'     | 12 1/4    | 3440 sx Halib. Lite              |        |
| Production         | 5 1/2         | 230 jts 17# K55, N80 & 90 jts 20# N80 | 13712'    | 8 3/4     | 2150 sx Halib. Lite (TOC @ 5250) |        |
| Production Casing  |               |                                       |           |           |                                  |        |
|                    | Prod. Casing  | Weight                                | Joints    | Length    | Top                              | Bottom |
| Top                | N-80 Buttress | 17#                                   | 64        | 2665      |                                  | 2640   |
|                    | X-over        | 17#                                   | 1         | 42        | 2640                             | 2682   |
|                    | K-55 ST&C     | 17#                                   | 166       | 6985      | 2682                             | 9666   |
|                    | N-80 ST&C     | 20#                                   | 3         | 124       | 9666                             | 9791   |
|                    | DV Tool       |                                       |           | 3         | 9791                             | 9794   |
|                    | N-80 ST&C     | 20#                                   | 87        | 3876      | 9794                             | 13670  |
|                    | Float Collar  |                                       |           | 2         | 13670                            | 13672  |
|                    | N-80 ST&C     | 20#                                   | 1         | 39        | 13672                            | 13711  |
| Bottom             | Guide Shoe    |                                       |           | 1         | 13711                            | 13712  |

| Geologic Markers |        |
|------------------|--------|
| San Andres       | 2200'  |
| Delaware Sand    | 5340'  |
| Bone Springs     | 7880'  |
| Wolfcamp         | 10818' |
| Cisco            | 11752' |
| Strawn           | 12078' |
| Atoka            | 12410' |
| Atoka Ls.        | 12748' |
| Morrow Ls.       | 12916' |
| Morrow Clastic   | 13015' |
| T.D.             | 13712' |

RIIIP, Capitan Reef, Prairie Chicken

Sec 30-19S-33E

API: 30-025-27069

Matador is requesting to plug and abandon the Federal 30 #1, per the required COA, following the procedure below:

- Notify NMOCD 24 hrs before MIRU.
- Safety mtg, MIRU, check pressures, pull rods and pump.
- ND wellhead, NU BOPs & TOOH w/ tbg.
- RU WL. WL set CIBP @ 7,766'. RD WL. TIH w/ tbg and spot 35 sx CI H cmt on top of CIBP. WOC & Tag. (7766' - 7482') Leak test CIBP
- Circ and displace hole w/ MLF. Come up & perf @ 5,260, sqz CI C cmt. Spot from 5,260 - 5,110'. WOC & Tag. 50 SX 5260 5260'
- Perf @ 3,290' & sqz CI C cmt. Spot from 3,290' - 3,160'. WOC & Tag. (2110' - 1504')
- Perf @ 1,326' & Sqz CI C cmt to surface. (1480' - surface) 455 SX (in/out) 185 SX 2 In/out)
- Cut off wellhead and ensure cmt to surface on all csg strings.
- Install above ground marker per BLM and NMOCD specifications.

\*Current and proposed wellbore diagrams attached

7 (5360' - 5260') spot 10 sx class C




Matador Production Company  
Federal 30 #1  
1980' FSL & 760' FEL Sec 30 - 195 - 33E  
Lea County, NM  
API: 30-025-27069  
**PROPOSED P&A WELLBORE SCHEMATIC**  
Spudded: 6/19/1981

| Casing Information |               |                                       |           |           |                                    |
|--------------------|---------------|---------------------------------------|-----------|-----------|------------------------------------|
| Surface            | Casing Size   | Weight lb/ft                          | Depth Set | Hole Size | Cementing Record                   |
| Intermediate       | 13 3/8        | 48# H40 ST&C                          | 1276'     | 17 1/2    | 975 sx Class "C"                   |
| Production         | 9 5/8         | 76 Jts 36# K55 & 50 Jts 40# K55       | 5310'     | 12 1/4    | 3440 sx Hallib. Lite               |
|                    | 5 1/2         | 230 Jts 17# K55, N80 & 90 Jts 20# N80 | 13712'    | 8 3/4     | 2150 sx Hallib. Lite (TOC @ 5250') |
| Production Casing  |               |                                       |           |           |                                    |
| Top                | Prod. Casing  | Weight                                | Joints    | Length    | Top                                |
|                    | N-80 Buttruss | 17#                                   | 64        | 2665      | Bottom                             |
|                    | X-Over        | 17#                                   | 1         | 42        | 2640                               |
|                    | K-55 ST&C     | 17#                                   | 166       | 6985      | 2682                               |
|                    | N-80 ST&C     | 20#                                   | 3         | 124       | 9666                               |
|                    | DV Tool       |                                       |           | 3         | 9791                               |
|                    | N-80 ST&C     | 20#                                   | 87        | 3876      | 9794                               |
|                    | Float Collar  |                                       |           | 2         | 13670                              |
|                    | N-80 ST&C     | 20#                                   | 1         | 39        | 13672                              |
| Bottom             | Guide Shoe    |                                       |           | 1         | 13711                              |
|                    |               |                                       |           |           | 13712                              |

| Geologic Markers |        |
|------------------|--------|
| San Andres       | 2200'  |
| Delaware Sand    | 5340'  |
| Bone Springs     | 7880'  |
| Wolfcamp         | 10818' |
| Cisco            | 11752' |
| Strawn           | 12078' |
| Atoka            | 12410' |
| Atoka Ls.        | 12748' |
| Morrow Ls.       | 12916' |
| Morrow Clastic   | 13015' |
| T.D.             | 13712' |

T. Smith @ 370'  
B. Smith @ 1430'  
Yates @ 1570'  
Capitan @ 1990'




Matador Production Company  
Federal 30 #1  
1980' FSL & 760' FEL Sec 30 - 19S - 33E  
Lea County, NM  
API: 30-025-27069  
CURRENT WELLBORE SCHEMATIC  
Spudded: 6/19/1981

| Casing Information |                                       |          |           |                                     |
|--------------------|---------------------------------------|----------|-----------|-------------------------------------|
| Casing Size        | Weight lb/ft                          | Depth Se | Hole Size | Cementing Record                    |
| 13 3/8             | 48# H40 ST&C                          | 1276'    | 17 1/2    | 975 sks. Class "C"                  |
| 9 5/8              | 76 jts 36# K55 & 50 jts 40# K55       | 5310'    | 12 1/4    | 3440 sks. Halib. Lite               |
| 5 1/2              | 230 jts 17# K55, N80 & 90 jts 20# N80 | 13712'   | 8 3/4     | 2150 sks. Halib. Lite (TOC @ 5250') |
| Production Casing  |                                       |          |           |                                     |
| Prod. Casing       | Weight                                | Joints   | Length    | Top                                 |
| N-80 Buttress      | 17#                                   | 64       | 2665      | Bottom                              |
| X-over             | 17#                                   | 1        | 42        | 2640                                |
| K-55 ST&C          | 17#                                   | 166      | 6985      | 2682                                |
| N-80 ST&C          | 20#                                   | 3        | 124       | 2682                                |
| DV Tool            |                                       |          | 3         | 9666                                |
| N-80 ST&C          | 20#                                   | 87       | 3876      | 9791                                |
| Float Collar       |                                       |          | 2         | 9794                                |
| N-80 ST&C          | 20#                                   | 1        | 39        | 13670                               |
| Guide Shoe         |                                       |          | 1         | 13672                               |
| Bottom             |                                       |          |           | 13711                               |
|                    |                                       |          |           | 13712                               |

| Tubing String - 2-7/8" #6.5 L-80 (KB 20') |                                 |
|-------------------------------------------|---------------------------------|
| Item                                      | Depth                           |
| 2-7/8"                                    | 7326                            |
| TAC                                       | 7329                            |
| 2-7/8"                                    | 7627                            |
| SN (Mech)                                 | 7628                            |
| Pup It                                    | 7632                            |
| Desander                                  | 7657                            |
| 2 7/8"                                    | 7808                            |
| Bull Plug                                 | 7809                            |
| P8TD                                      | 7842                            |
| Rod String                                |                                 |
| Item                                      | Depth                           |
| Polish Rod                                | 1 1/2 x 1 1/4 liner x 26' (-3') |
| 7/8"                                      | 84 Weatherford HD               |
| 3/4" Rods                                 | 189 Norris 97 Rods              |
| 7/8" Rods                                 | 34 Weatherford HD               |
| Pump                                      | 2.5 x 1.75 x 20-6-4 RHBM        |

| Geologic Markers |        |
|------------------|--------|
| San Andres       | 2200'  |
| Delaware Sand    | 5340'  |
| Bone Springs     | 7880'  |
| Wolfcamp         | 10818' |
| Cisco            | 11752' |
| Strawn           | 12078' |
| Atoka            | 12410' |
| Atoka Ls.        | 12748' |
| Morrow Ls.       | 12916' |
| Morrow Clastic   | 13015' |
| T.D.             | 13712' |





BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972

Permanent Abandonment of Federal Wells  
Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.
5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off. Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:

From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted





# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm

In Reply Refer To: 1310

TAKE PRIDE  
IN AMERICA

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/wrath, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Melissa Horn  
Environmental Protection Specialist  
575-234-5951

Kelsey Wade  
Environmental Protection Specialist  
575-234-2220

Trishia Bad Bear, Hobbs Field Station  
Natural Resource Specialist  
575-393-3612

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

COMMENTS  
  
Action 98521

COMMENTS

|                                                                                   |                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------|
| Operator:<br>MATADOR PRODUCTION COMPANY<br>One Lincoln Centre<br>Dallas, TX 75240 | OGRID:<br>228937                                    |
|                                                                                   | Action Number:<br>98521                             |
|                                                                                   | Action Type:<br>[C-103] NOI Plug & Abandon (C-103F) |

COMMENTS

| Created By | Comment       | Comment Date |
|------------|---------------|--------------|
| plmartinez | DATA ENTRY PM | 4/19/2022    |



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 98521

CONDITIONS

|                                                                                   |                                                     |
|-----------------------------------------------------------------------------------|-----------------------------------------------------|
| Operator:<br>MATADOR PRODUCTION COMPANY<br>One Lincoln Centre<br>Dallas, TX 75240 | OGRID:<br>228937                                    |
|                                                                                   | Action Number:<br>98521                             |
|                                                                                   | Action Type:<br>[C-103] NOI Plug & Abandon (C-103F) |

CONDITIONS

| Created By | Condition              | Condition Date |
|------------|------------------------|----------------|
| kfortner   | Like approval from BLM | 4/15/2022      |