<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV** 

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

## **State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form C-101 August 1, 2011

Permit 317425

	APPLICATION FOR PERMIT TO DRILL	. RE-ENTER. DEEPEN	. PLUGBACK	OR ADD A ZONE
--	---------------------------------	--------------------	------------	---------------

Operator Name and Address		2. OGRID Number
MEWBOURNE OIL CO		14744
P.O. Box 5270		3. API Number
Hobbs, NM 88241		30-015-49581
4. Property Code	5. Property Name	6. Well No.
332893	Wild Turkey 36/35 B2HE State Com	001H

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
1	36	18S	28E	1	1500	S	290	E	Eddy

8. Proposed Bottom Hole Location

ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	E	35	18S	28E	E	1700	N	100	W	Eddy

9. Pool Information

49553 49553

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation
New Well	OIL		State	3395
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
N	17929	2nd Bone Spring Sand		6/23/2022
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

#### ☑ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

			opecou oucg .			
Туре	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	280	116
Int1	12.25	9.625	36	1100	280	426
Prod	8.75	7	26	7300	750	4812
Liner1	6.125	4.5	13.5	17929	430	7100

#### Casing/Cement Program: Additional Comments

MOC proposed to drill & test the Bone Springs formation. H2S rule 118 does not apply because MOC has researched the area & no high concentrations were found. Will have on location & working all H2S safety equiptment before Yates formation for safety & insurance purposes. Will stimulate as needed for production.

22. Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
Annular	5000	2500	Schaffer
Double Ram	5000	5000	Schaffer
Annular	5000	2500	Schaffer

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief.  I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒, if applicable.  Signature:				OIL CONSERVATIO	ON DIVISION
Printed Name:	Electronically filed by Monty Whe	tstone	Approved By:	Katherine Pickford	
Title:	Vice President Operations		Title:	Geoscientist	
Email Address: fking@mewbourne.com			Approved Date:	5/31/2022	Expiration Date: 5/31/2024
Date:	5/25/2022	Phone: 903-561-2900	Conditions of Appr	oval Attached	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

320

# State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505


Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

☐ AMENDED REPORT

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

30-015-49	API Number	r		2Pool Code 49553  PALMILLO; BONE SPRING EAST						ST
<sup>4</sup> Property Coo 332893	de		<sup>5</sup> Property Name WILD TURKEY 36/35 B2HE STATE COM						6	Well Number 1H
70GRID NO. 8 Operator Name 9 Elevation 14744 MEWBOURNE OIL COMPANY 3395'										
	<sup>10</sup> Surface Location									
UL or lot no.	Section	Township	Range	Lot Idn	Feet from th	e North/South line	Feet From the	East/We	st line	County
I	36	18S	28E		1500	SOUTH	290	EAS	ST	EDDY
			<sup>11</sup> ]	Bottom I	Hole Locat	ion If Different Fi	om Surface			
UL or lot no.	Section	Township Range Lot Idn Feet from the North/South line Feet from the East/West line Coun						County		
E	35	18S	28E	8E 1700 NORTH 100 WEST EDDY						EDDY
12 Dedicated Acres	13 Joint	or Infill 14	4 Consolidation	Code 15	Order No.		•			

No allowable will be assigned to this completion until all interest have been consolidated or a non-standard unit has been approved by the division.



District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

District III

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

		GA:	S CAPTURE I	PLAN			
Date: <u>5/31/2022</u>							
☑ Original	Operator & OGRID No.:	[14744] MEV	VBOURNE OIL CO				
☐ Amended - Reason for Amendment:							
his Gas Capture Plan outlines actions	, ,			0 0		w drill, recom	plete to new zone, re-frac) activity.
Vell(s)/Production Facility - Name of	facility						
he well(s) that will be located at the p	production facility are shown	in the table belo	ow.				
Well Name	API		Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Wild Turkey 36/35 B2HE State Com #	#001H 30-	015-49581	I-36-18S-28E	1500S 0290E	10	Flared	ONLINE AFTER FRAC
Cathoring System and Dinaline Notifi	action						

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to LUCID ENERGY DELAWARE, LLC and will be connected to LUCID ENERGY DELAWARE, LLC High Pressure gathering system located in Eddy

New Mexico. It will require 3400' of pipeline to connect the facility to High Pressure gathering system. MEWBOURNE OIL CO provides (periodically) to LUCID ENERGY DELAWARE, LLC a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, MEWBOURNE OIL CO and LUCID ENERGY DELAWARE, LLC have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at LUCID ENERGY DELAWARE, LLC Processing Plant located in Sec. 25, Twn. 18S, Rng. 25E, Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on LUCID ENERGY DELAWARE, LLC system at that time. Based on current information, it is MEWBOURNE OIL CO's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

#### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- - · Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

Form APD Conditions

Permit 317425

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

#### PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
MEWBOURNE OIL CO [14744]	30-015-49581
P.O. Box 5270	Well:
Hobbs, NM 88241	Wild Turkey 36/35 B2HE State Com #001H

OCD	Condition
Reviewer	
kpickford	Notify OCD 24 hours prior to casing & cement
kpickford	Will require a File As Drilled C-102 and a Directional Survey with the C-104
kpickford	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud
	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
kpickford	Cement is required to circulate on both surface and intermediate1 strings of casing
	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system

Oper	rator Nai		Prop	erty N	ame	:					Well Number			
Kick C	off Point	(KOP)												
UL	Section	Township	Range	Lot	Feet		From N	I/S	Feet		From	ı E/W	County	
Latitu	de				Longitu	ıde							NAD	
First T	ake Poir	nt (FTP)			<u> </u>									
UL	Section	Township	Range	Lot	Feet		From N	I/S	Feet		From	ı E/W	County	
Latitu	de				Longitu	ıde							NAD	
Last T	ake Poin	t (LTP)	Range	Lot	Feet	Fron	n N/S	Feet	:	From E/	/w	Count	у	
Latitu	de				Longitu	ide						NAD		
Is this well the defining well for the Horizontal Spacing Unit?  Is this well an infill well?														
	l is yes p ng Unit.	lease provi	de API if	availab	ole, Oper	rator N	Name :	and v	well n	umber 1	for [	Definir	ng well fo	r Horizontal
AF1#														
Oper	rator Nai	me:				Prop	erty N	ame	:					Well Number

## **Mewbourne Oil Company**

Eddy County, New Mexico NAD 83 Wild Turkey 36/35 B2HE State Com #1H

Sec 36, T18S,R28E

SHL: 1500' FSL & 290' FEL (Sec 36) BHL: 1700' FNL & 100' FWL (Sec 35)

Plan: Design #1

## **Standard Planning Report**

23 May, 2022

Database: Company:

Hobbs

Mewbourne Oil Company

Project: Eddy County, New Mexico NAD 83 Wild Turkey 36/35 B2HE State Com #1H Site:

Well: Sec 36, T18S,R28E

Wellbore: Design:

BHL: 1700' FNL & 100' FWL (Sec 35)

Design #1

**Local Co-ordinate Reference:** 

TVD Reference: MD Reference: North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H

WELL @ 3423.0usft (Original Well Elev) WELL @ 3423.0usft (Original Well Elev)

Minimum Curvature

Project Eddy County, New Mexico NAD 83

Map System: Geo Datum:

Map Zone:

US State Plane 1983 North American Datum 1983 New Mexico Eastern Zone

System Datum:

Ground Level

Wild Turkey 36/35 B2HE State Com #1H Site

Site Position: From:

**Position Uncertainty** 

Мар

Northing: Easting:

619,013.00 usft 606,087.00 usft

Longitude:

Latitude: 32.7015323 -104.1228376

**Position Uncertainty:** 0.0 usft Slot Radius: 13-3/16 "

Well Sec 36, T18S,R28E

**Well Position** +N/-S +E/-W

0.0 usft 0.0 usft 0.0 usft

Northing: Easting: Wellhead Elevation: 619,013.00 usft 606,087.00 usft 3,423.0 usft Latitude: Longitude: **Ground Level:** 

32.7015323 -104.1228376

3,395.0 usft

0.11° **Grid Convergence:** 

BHL: 1700' FNL & 100' FWL (Sec 35)

Declination Magnetics **Model Name** Sample Date Dip Angle Field Strength (°) (°) (nT) IGRF2010 48,463.72874014 12/31/2014 7.44 60.45

Design #1 Design

**Audit Notes:** 

Version:

Wellbore

Vertical Section:

Phase:

**PROTOTYPE** 

Tie On Depth: +E/-W

0.0

Depth From (TVD) +N/-S Direction (usft) (usft) (usft) (°) 281.18 0.0 0.0 0.0

Plan Survey Tool Program

Date 5/23/2022

**Depth From** Depth To

(usft) (usft) Survey (Wellbore)

**Tool Name** 

Remarks

0.0 17,929.3 Design #1 (BHL: 1700' FNL & 100

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,349.0	24.98	7.66	2,309.8	265.6	35.7	2.00	2.00	0.00	7.66	
6,109.1	24.98	7.66	5,718.2	1,839.4	247.3	0.00	0.00	0.00	0.00	
7,358.2	0.00	0.00	6,928.0	2,105.0	283.0	2.00	-2.00	0.00	180.00	KOP: 1700' FNL & 10
8,270.3	91.19	269.24	7,501.0	2,097.2	-301.9	10.00	10.00	0.00	-90.76	
17,929.3	91.19	269.24	7,301.0	1,969.0	-9,958.0	0.00	0.00	0.00	0.00	BHL: 1700' FNL & 100

Database: Hobbs

Company: Mewbourne Oil Company

Project: Eddy County, New Mexico NAD 83
Site: Wild Turkey 36/35 B2HE State Com #1H

Well: Sec 36, T18S,R28E

Wellbore: BHL: 1700' FNL & 100' FWL (Sec 35)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H WELL @ 3423.0usft (Original Well Elev)

WELL @ 3423.0usft (Original Well Elev)
WELL @ 3423.0usft (Original Well Elev)

Grid

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
	FSL & 290' FEL (		0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	2.00	7.66	1,100.0	1.7	0.0	0.0	2.00	2.00	0.00
1,300.0	4.00	7.66	1,200.0	6.9	0.2	0.1	2.00	2.00	0.00
1,400.0	6.00	7.66	1,399.5	15.6	2.1	1.0	2.00	2.00	0.00
1,500.0	8.00	7.66	1,498.7	27.6	3.7	1.7	2.00	2.00	0.00
1,600.0	10.00	7.66	1,597.5	43.1	5.8	2.7	2.00	2.00	0.00
1,700.0	12.00	7.66	1,695.6	62.0	8.3	3.9	2.00	2.00	0.00
1,800.0	14.00	7.66	1,793.1	84.3	11.3	5.2	2.00	2.00	0.00
1,900.0	16.00	7.66	1,889.6	110.0	14.8	6.8	2.00	2.00	0.00
2,000.0	18.00	7.66	1,985.3	139.0	18.7	8.6	2.00	2.00	0.00
2,100.0	20.00	7.66	2.079.8	171.2	23.0	10.6	2.00	2.00	0.00
2,100.0	22.00	7.66	2,173.2	206.7	27.8	12.8	2.00	2.00	0.00
2,300.0	24.00	7.66	2,265.2	245.5	33.0	15.2	2.00	2.00	0.00
2,349.0	24.98	7.66	2,309.8	265.6	35.7	16.5	2.00	2.00	0.00
2,400.0	24.98	7.66	2,356.0	286.9	38.6	17.8	0.00	0.00	0.00
2,500.0	24.98	7.66	2,446.7	328.8	44.2	20.4	0.00	0.00	0.00
2,600.0	24.98	7.66	2,537.3	370.7	49.8	23.0	0.00	0.00	0.00
2,700.0	24.98	7.66	2,628.0	412.5	55.5	25.6	0.00	0.00	0.00
2,800.0	24.98	7.66	2,718.6	454.4	61.1	28.2	0.00	0.00	0.00
2,900.0	24.98	7.66	2,809.3	496.2	66.7	30.8	0.00	0.00	0.00
3,000.0	24.98	7.66	2,899.9	538.1	72.3	33.4	0.00	0.00	0.00
3,100.0	24.98	7.66	2.990.5	579.9	78.0	36.0	0.00	0.00	0.00
3,200.0	24.98	7.66	3,081.2	621.8	83.6	38.6	0.00	0.00	0.00
3,300.0	24.98	7.66	3,171.8	663.6	89.2	41.2	0.00	0.00	0.00
3,400.0	24.98	7.66	3,262.5	705.5	94.8	43.8	0.00	0.00	0.00
3,500.0	24.98	7.66	3,353.1	747.3	100.5	46.4	0.00	0.00	0.00
3,600.0	24.98	7.66	3,443.8	789.2	106.1	49.0	0.00	0.00	0.00
3,700.0	24.98	7.66	3,534.4	831.1	111.7	51.6	0.00	0.00	0.00
3,800.0	24.98	7.66	3,625.1	872.9	117.4	54.2	0.00	0.00	0.00
3,900.0	24.98	7.66	3,715.7	914.8	123.0	56.8	0.00	0.00	0.00
4,000.0	24.98	7.66	3,806.4	956.6	128.6	59.4	0.00	0.00	0.00
4,100.0	24.98	7.66	3,897.0	998.5	134.2	62.0	0.00	0.00	0.00
4,200.0	24.98	7.66	3,987.6	1,040.3	139.9	64.6	0.00	0.00	0.00
4,300.0	24.98	7.66	4,078.3	1,082.2	145.5	67.2	0.00	0.00	0.00
4,400.0	24.98	7.66	4,168.9	1,124.0	151.1	69.8	0.00	0.00	0.00
4,500.0	24.98	7.66	4,259.6	1,165.9	156.7	72.4	0.00	0.00	0.00
4,600.0	24.98	7.66	4,350.2	1,207.7	162.4	75.0	0.00	0.00	0.00
4,700.0	24.98	7.66	4,440.9	1,249.6	168.0	77.6	0.00	0.00	0.00
4,800.0	24.98	7.66	4,531.5	1,291.5	173.6	80.2	0.00	0.00	0.00
4,900.0	24.98	7.66	4,622.2	1,333.3	179.3	82.8	0.00	0.00	0.00
5,000.0	24.98	7.66	4,712.8	1,375.2	184.9	85.4	0.00	0.00	0.00
5,100.0	24.98	7.66	4,803.4	1,417.0	190.5	88.0	0.00	0.00	0.00

Database: Company:

Project:

Site:

Hobbs

Mewbourne Oil Company

Eddy County, New Mexico NAD 83

Wild Turkey 36/35 B2HE State Com #1H

**Well:** Sec 36, T18S,R28E

**Wellbore:** BHL: 1700' FNL & 100' FWL (Sec 35)

Design: Design #1

Local Co-ordinate Reference:

TVD Reference:
MD Reference:
North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H

WELL @ 3423.0usft (Original Well Elev)
WELL @ 3423.0usft (Original Well Elev)

Grid

lanned	I Survey									
	Measured Depth (usft)	Inclination	Azimuth	Vertical Depth (usft)	+N/-S	+E/-W	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
	(usit)	(°)	(°)	(usit)	(usft)	(usft)	(usit)	(7100usit)	( / Ioousit)	(7100usit)
	5,200.0	24.98	7.66	4,894.1	1,458.9	196.1	90.6	0.00	0.00	0.00
	5,300.0	24.98	7.66	4,984.7	1,500.7	201.8	93.2	0.00	0.00	0.00
			7.00			007.4			0.00	
	5,400.0	24.98	7.66	5,075.4	1,542.6	207.4	95.8	0.00	0.00	0.00
	5,500.0	24.98	7.66	5,166.0	1,584.4	213.0	98.4	0.00	0.00	0.00
	5,600.0	24.98	7.66	5,256.7	1,626.3	218.6	101.0	0.00	0.00	0.00
	5,700.0	24.98	7.66	5,347.3	1,668.2	224.3	103.6	0.00	0.00	0.00
	5,800.0	24.98	7.66	5,438.0	1,710.0	229.9	106.2	0.00	0.00	0.00
	5,900.0	24.98	7.66	5,528.6	1,751.9	235.5	108.8	0.00	0.00	0.00
	6,000.0	24.98	7.66	5,619.3	1,793.7	241.2	111.4	0.00	0.00	0.00
	6,109.1	24.98	7.66	5,718.2	1,839.4	247.3	114.2	0.00	0.00	0.00
				,			114.2			
	6,200.0	23.16	7.66	5,801.1	1,876.1	252.2		2.00	-2.00	0.00
	6,300.0	21.16	7.66	5,893.7	1,913.5	257.3	118.8	2.00	-2.00	0.00
	6,400.0	19.16	7.66	5,987.6	1,947.7	261.8	120.9	2.00	-2.00	0.00
	6,500.0	17.16	7.66	6,082.6	1,978.6	266.0	122.8	2.00	-2.00	0.00
	6,600.0	15.16	7.66	6,178.7	2,006.2	269.7	124.6	2.00	-2.00	0.00
	6,700.0	13.16	7.66	6,275.6	2,030.4	273.0	124.0	2.00	-2.00	0.00
	6,800.0	11.16	7.66	6,373.4	2,051.3	275.8	127.4	2.00	-2.00	0.00
	0,000.0	11.10	7.00	0,373.4	2,001.0	275.0	121.4	2.00	-2.00	0.00
	6,900.0	9.16	7.66	6,471.8	2,068.8	278.1	128.4	2.00	-2.00	0.00
	7,000.0	7.16	7.66	6,570.8	2,082.8	280.0	129.3	2.00	-2.00	0.00
	7,100.0	5.16	7.66	6,670.2	2,093.5	281.5	130.0	2.00	-2.00	0.00
	7,200.0	3.16	7.66	6,769.9	2,100.7	282.4	130.4	2.00	-2.00	0.00
	7,300.0	1.16	7.66	6,869.9	2,104.4	282.9	130.7	2.00	-2.00	0.00
	7,358.2	0.00	0.00	6,928.0	2,105.0	283.0	130.7	2.00	-2.00	0.00
	KOP: 1700' F	NL & 10' FEL ( \$	Sec 36)							
	7,400.0	4.18	269.24	6,969.8	2,105.0	281.5	132.2	10.00	10.00	0.00
	7,450.0	9.18	269.24	7,019.5	2,104.9	275.7	137.9	10.00	10.00	0.00
	7,500.0	14.18	269.24	7,068.4	2,104.8	265.5	147.8	10.00	10.00	0.00
	7,550.0	19.18	269.24	7,116.3	2,104.6	251.2	161.8	10.00	10.00	0.00
	7,600.0	24.18	269.24	7,162.7	2,104.3	232.7	179.9	10.00	10.00	0.00
	7,650.0	29.18	269.24	7,207.4	2,104.0	210.3	201.8	10.00	10.00	0.00
	7,685.6	32.73	269.24	7,237.9	2,103.8	192.0	219.7	10.00	10.00	0.00
	FTP: 1700' F	NL & 100' FEL (	Sec 36)							
	7,700.0	34.17	269.24	7,249.9	2,103.7	184.0	227.5	10.00	10.00	0.00
	7,750.0	39.17	269.24	7,290.0	2,103.3	154.2	256.7	10.00	10.00	0.00
	7.000.0	44.47	000.04	7.007.4	0.400.0	101.0	000.0	40.00	40.00	0.00
	7,800.0	44.17	269.24	7,327.4	2,102.8	121.0	289.2	10.00	10.00	0.00
	7,850.0	49.17	269.24	7,361.7	2,102.4	84.6	324.8	10.00	10.00	0.00
	7,900.0	54.17	269.24	7,392.7	2,101.8	45.4	363.2	10.00	10.00	0.00
	7,950.0	59.17	269.24	7,420.1	2,101.3	3.6	404.0	10.00	10.00	0.00
	8,000.0	64.17	269.24	7,443.8	2,100.7	-40.3	447.1	10.00	10.00	0.00
	8,050.0	69.16	269.24	7,463.6	2,100.1	-86.2	492.0	10.00	10.00	0.00
	8,100.0	74.16	269.24	7,479.4	2,099.5	-133.7	538.4	10.00	10.00	0.00
	8,150.0	79.16	269.24	7,479.4	2,098.8	-182.3	586.0	10.00	10.00	0.00
	8,200.0	84.16	269.24	7,490.9	2,098.2	-162.3	634.4	10.00	10.00	0.00
	8,250.0	89.16	269.24	7,501.1	2,097.5	-281.7	683.2	10.00	10.00	0.00
	8,258.3	89.99	269.24	7,501.1	2,097.4	-290.0	691.3	10.00	10.00	0.00
		L & 583' FEL (Se								
	8,270.3	91.19	269.24	7,501.0	2,097.2	-301.9	703.0	10.00	10.00	0.00
	8,300.0	91.19	269.24	7,500.4	2,096.8	-331.6	732.1	0.00	0.00	0.00
	8,400.0	91.19	269.24	7,498.3	2,095.5	-431.6	829.9	0.00	0.00	0.00
	8,500.0	91.19	269.24	7,496.3 7,496.2		-431.6 -531.6	927.7		0.00	
	0,000.0		209.24		2,094.2	-331.0	921.1	0.00	0.00	0.00
	8,600.0	91.19	269.24	7,494.2	2,092.9	-631.6	1,025.5	0.00	0.00	0.00
	8,700.0	91.19	269.24	7,492.1	2,091.5	-731.5	1,123.3	0.00	0.00	0.00
	8,800.0	91.19	269.24	7,490.0	2,090.2	-831.5	1,221.2	0.00	0.00	0.00

Database: Company:

Project:

Wellbore:

Site:

Hobbs

Mewbourne Oil Company

Sec 36, T18S,R28E

Eddy County, New Mexico NAD 83

Wild Turkey 36/35 B2HE State Com #1H

Well:

BHL: 1700' FNL & 100' FWL (Sec 35)

Design:

Design #1

Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H

WELL @ 3423.0usft (Original Well Elev) WELL @ 3423.0usft (Original Well Elev)

esign:		Design #1								
Planned Sur	vey									
De	sured epth isft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
	0 000 0			7 400 0			1 210 0	0.00	0.00	0.00
	8,900.0 9,000.0	91.19 91.19	269.24 269.24	7,488.0 7,485.9	2,088.9	-931.5	1,319.0	0.00	0.00 0.00	0.00
	9,000.0	91.19	269.24	7,485.9	2,087.5	-1,031.4	1,416.8	0.00	0.00	0.00
	9,100.0	91.19	269.24	7,483.8	2,086.2	-1,131.4	1,514.6	0.00	0.00	0.00
	9,200.0	91.19	269.24	7,481.7	2,084.9	-1,231.4	1,612.4	0.00	0.00	0.00
	9,300.0	91.19	269.24	7,479.7	2,083.6	-1,331.3	1,710.2	0.00	0.00	0.00
	9,400.0	91.19	269.24	7,477.6	2,082.2	-1,431.3	1,808.0	0.00	0.00	0.00
	9,500.0	91.19	269.24	7,475.5	2,080.9	-1,531.3	1,905.8	0.00	0.00	0.00
	9,600.0	91.19	269.24	7,473.5	2,079.6	-1,631.3	2,003.7	0.00	0.00	0.00
	9,700.0	91.19	269.24	7,473.5 7,471.4	2,079.0	-1,731.2	2,003.7	0.00	0.00	0.00
	9,800.0	91.19	269.24	7,471.4	2,076.9	-1,731.2	2,101.3	0.00	0.00	0.00
	9,900.0	91.19	269.24	7,469.3 7,467.3	2,076.9	-1,031.2	2,199.3	0.00	0.00	0.00
	0,000.0	91.19	269.24	7,467.3 7,465.2	2,073.0	-1,931.2	2,394.9	0.00	0.00	0.00
'	0,000.0	91.19		7,405.2		-2,031.1	2,394.9	0.00	0.00	0.00
	0,100.0	91.19	269.24	7,463.1	2,072.9	-2,131.1	2,492.7	0.00	0.00	0.00
1	0,200.0	91.19	269.24	7,461.0	2,071.6	-2,231.1	2,590.5	0.00	0.00	0.00
1	0,300.0	91.19	269.24	7,459.0	2,070.3	-2,331.0	2,688.4	0.00	0.00	0.00
1	0,400.0	91.19	269.24	7,456.9	2,069.0	-2,431.0	2,786.2	0.00	0.00	0.00
1	0,500.0	91.19	269.24	7,454.8	2,067.6	-2,531.0	2,884.0	0.00	0.00	0.00
4	0,600.0	91.19	269.24	7,452.8	2,066.3	-2,631.0	2,981.8	0.00	0.00	0.00
	0,700.0	91.19	269.24	7,452.6 7,450.7	2,065.0	-2,031.0 -2,730.9	3,079.6	0.00	0.00	0.00
		91.19	269.24						0.00	
	0,800.0	91.19	269.24	7,448.6	2,063.6	-2,830.9	3,177.4	0.00	0.00	0.00
	0,900.0			7,446.5	2,062.3	-2,930.9	3,275.2	0.00		0.00
1	1,000.0	91.19	269.24	7,444.5	2,061.0	-3,030.8	3,373.0	0.00	0.00	0.00
1	1,100.0	91.19	269.24	7,442.4	2,059.7	-3,130.8	3,470.9	0.00	0.00	0.00
1	1,200.0	91.19	269.24	7,440.3	2,058.3	-3,230.8	3,568.7	0.00	0.00	0.00
1	1,300.0	91.19	269.24	7,438.3	2,057.0	-3,330.7	3,666.5	0.00	0.00	0.00
1	1,400.0	91.19	269.24	7,436.2	2,055.7	-3,430.7	3,764.3	0.00	0.00	0.00
1	1,500.0	91.19	269.24	7,434.1	2,054.4	-3,530.7	3,862.1	0.00	0.00	0.00
1	1 600 0	91.19	269.24	7 420 4	2,053.0	2 620 7	2.050.0	0.00	0.00	0.00
	1,600.0	91.19	269.24	7,432.1 7,430.0		-3,630.7	3,959.9		0.00	
	1,700.0	91.19	269.24		2,051.7	-3,730.6	4,057.7 4,155.6	0.00		0.00
	1,800.0			7,427.9	2,050.4	-3,830.6		0.00	0.00	0.00
	1,900.0	91.19	269.24	7,425.8	2,049.0	-3,930.6	4,253.4	0.00	0.00	0.00
1	2,000.0	91.19	269.24	7,423.8	2,047.7	-4,030.5	4,351.2	0.00	0.00	0.00
1	2,100.0	91.19	269.24	7,421.7	2,046.4	-4,130.5	4,449.0	0.00	0.00	0.00
	2,200.0	91.19	269.24	7,419.6	2,045.1	-4,230.5	4,546.8	0.00	0.00	0.00
	2,300.0	91.19	269.24	7,417.6	2,043.7	-4,330.4	4,644.6	0.00	0.00	0.00
	2,400.0	91.19	269.24	7,415.5	2,042.4	-4,430.4	4,742.4	0.00	0.00	0.00
	2,500.0	91.19	269.24	7,413.4	2,041.1	-4,530.4	4,840.2	0.00	0.00	0.00
4	2.600.0		260.24	7.411.3	2 020 0	4 620 2		0.00	0.00	0.00
		91.19	269.24	,	2,039.8	-4,630.3	4,938.1	0.00	0.00	0.00
	2,700.0	91.19	269.24	7,409.3	2,038.4	-4,730.3	5,035.9	0.00	0.00	0.00
	2,800.0	91.19	269.24	7,407.2	2,037.1	-4,830.3	5,133.7	0.00	0.00	0.00
	2,900.0	91.19	269.24	7,405.1	2,035.8	-4,930.3	5,231.5	0.00	0.00	0.00
1	3,000.0	91.19	269.24	7,403.1	2,034.4	-5,030.2	5,329.3	0.00	0.00	0.00
1	3,100.0	91.19	269.24	7,401.0	2,033.1	-5,130.2	5,427.1	0.00	0.00	0.00
1	3,200.0	91.19	269.24	7,398.9	2,031.8	-5,230.2	5,524.9	0.00	0.00	0.00
1	3,300.0	91.19	269.24	7,396.9	2,030.5	-5,330.1	5,622.8	0.00	0.00	0.00
1	3,400.0	91.19	269.24	7,394.8	2,029.1	-5,430.1	5,720.6	0.00	0.00	0.00
	3,500.0	91.19	269.24	7,392.7	2,027.8	-5,530.1	5,818.4	0.00	0.00	0.00
	3,600.0	91.19	269.24	7,390.6	2,026.5	-5,630.0	5,916.2	0.00	0.00	0.00
	3,700.0	91.19	269.24	7,388.6	2,025.1	-5,730.0	6,014.0	0.00	0.00	0.00
	3,800.0	91.19	269.24	7,386.5	2,023.8	-5,830.0	6,111.8	0.00	0.00	0.00
	3,900.0	91.19	269.24	7,384.4	2,022.5	-5,930.0	6,209.6	0.00	0.00	0.00
1	4,000.0	91.19	269.24	7,382.4	2,021.2	-6,029.9	6,307.5	0.00	0.00	0.00
1	4,100.0	91.19	269.24	7,380.3	2,019.8	-6,129.9	6,405.3	0.00	0.00	0.00
	4,200.0	91.19	269.24	7,378.2	2,018.5	-6,229.9	6,503.1	0.00	0.00	0.00

Database: Company: Project:

Site:

Hobbs

Mewbourne Oil Company

Eddy County, New Mexico NAD 83 Wild Turkey 36/35 B2HE State Com #1H

Sec 36, T18S,R28E Well:

BHL: 1700' FNL & 100' FWL (Sec 35) Wellbore:

Design: Design #1 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H

WELL @ 3423.0usft (Original Well Elev) WELL @ 3423.0usft (Original Well Elev)

ed Survey									
Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Vertical Section	Dogleg Rate	Build Rate	Turn Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
14,300.0	91.19	269.24	7,376.1	2,017.2	-6,329.8	6,600.9	0.00	0.00	0.00
14,400.0	91.19	269.24	7,374.1	2,015.9	-6,429.8	6,698.7	0.00	0.00	0.00
14,500.0	91.19	269.24	7,372.0	2,014.5	-6,529.8	6,796.5	0.00	0.00	0.00
14,600.0	91.19	269.24	7,369.9	2,013.2	-6,629.7	6,894.3	0.00	0.00	0.00
14,700.0	91.19	269.24	7,367.9	2,011.9	-6,729.7	6,992.1	0.00	0.00	0.00
14,800.0	91.19	269.24	7,365.8	2,010.5	-6,829.7	7,090.0	0.00	0.00	0.00
14,900.0	91.19	269.24	7,363.7	2,009.2	-6,929.7	7,187.8	0.00	0.00	0.00
15,000.0	91.19	269.24	7,361.7	2,007.9	-7,029.6	7,285.6	0.00	0.00	0.00
15,100.0	91.19	269.24	7,359.6	2,006.6	-7,129.6	7,383.4	0.00	0.00	0.00
15,200.0	91.19	269.24	7,357.5	2,005.2	-7,229.6	7,481.2	0.00	0.00	0.00
15,300.0	91.19	269.24	7,355.4	2,003.9	-7,329.5	7,579.0	0.00	0.00	0.00
15,400.0	91.19	269.24	7,353.4	2,002.6	-7,429.5	7,676.8	0.00	0.00	0.00
15,500.0	91.19	269.24	7,351.3	2,001.3	-7,529.5	7,774.7	0.00	0.00	0.00
15,600.0	91.19	269.24	7,349.2	1,999.9	-7,629.4	7,872.5	0.00	0.00	0.00
15,700.0	91.19	269.24	7,347.2	1,998.6	-7,729.4	7,970.3	0.00	0.00	0.00
15,800.0	91.19	269.24	7,345.1	1,997.3	-7,829.4	8,068.1	0.00	0.00	0.00
15,900.0	91.19	269.24	7,343.0	1,995.9	-7,929.3	8,165.9	0.00	0.00	0.00
16,000.0	91.19	269.24	7,340.9	1,994.6	-8,029.3	8,263.7	0.00	0.00	0.00
16,100.0	91.19	269.24	7,338.9	1,993.3	-8,129.3	8,361.5	0.00	0.00	0.00
16,200.0	91.19	269.24	7,336.8	1,992.0	-8,229.3	8,459.3	0.00	0.00	0.00
16,300.0	91.19	269.24	7,334.7	1,990.6	-8,329.2	8,557.2	0.00	0.00	0.00
16,400.0	91.19	269.24	7,332.7	1,989.3	-8,429.2	8,655.0	0.00	0.00	0.00
16,500.0	91.19	269.24	7,330.6	1,988.0	-8,529.2	8,752.8	0.00	0.00	0.00
16,600.0	91.19	269.24	7,328.5	1,986.6	-8,629.1	8,850.6	0.00	0.00	0.00
16,700.0	91.19	269.24	7,326.5	1,985.3	-8,729.1	8,948.4	0.00	0.00	0.00
16,800.0	91.19	269.24	7,324.4	1,984.0	-8,829.1	9,046.2	0.00	0.00	0.00
16,900.0	91.19	269.24	7,322.3	1,982.7	-8,929.0	9,144.0	0.00	0.00	0.00
17,000.0	91.19	269.24	7,320.2	1,981.3	-9,029.0	9,241.9	0.00	0.00	0.00
17,100.0	91.19	269.24	7,318.2	1,980.0	-9,129.0	9,339.7	0.00	0.00	0.00
17,200.0	91.19	269.24	7,316.1	1,978.7	-9,229.0	9,437.5	0.00	0.00	0.00
17,300.0	91.19	269.24	7,314.0	1,977.4	-9,328.9	9,535.3	0.00	0.00	0.00
17,400.0	91.19	269.24	7,312.0	1,976.0	-9,428.9	9,633.1	0.00	0.00	0.00
17,500.0	91.19	269.24	7,309.9	1,974.7	-9,528.9	9,730.9	0.00	0.00	0.00
17,600.0	91.19	269.24	7,307.8	1,973.4	-9,628.8	9,828.7	0.00	0.00	0.00
17,700.0	91.19	269.24	7,305.7	1,972.0	-9,728.8	9,926.5	0.00	0.00	0.00
17,800.0	91.19	269.24	7,303.7	1,970.7	-9,828.8	10,024.4	0.00	0.00	0.00
17,900.0	91.19	269.24	7,301.6	1,969.4	-9,928.7	10,122.2	0.00	0.00	0.00
17,929.3	91.19	269.24	7,301.0	1,969.0	-9,958.0	10,150.8	0.00	0.00	0.00

Database: Company:

Hobbs

Mewbourne Oil Company

Eddy County, New Mexico NAD 83

Wild Turkey 36/35 B2HE State Com #1H

Well:

Project:

Site:

Sec 36, T18S,R28E

BHL: 1700' FNL & 100' FWL (Sec 35) Wellbore:

Design: Design #1 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

**Survey Calculation Method:** 

Site Wild Turkey 36/35 B2HE State Com #1H

WELL @ 3423.0usft (Original Well Elev) WELL @ 3423.0usft (Original Well Elev)

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
SHL: 1500' FSL & 290' F - plan hits target cent - Point	0.00 er	0.00	0.0	0.0	0.0	619,013.00	606,087.00	32.7015323	-104.1228376
KOP: 1700' FNL & 10' Fl - plan hits target cent - Point	0.00 er	0.00	6,928.0	2,105.0	283.0	621,118.00	606,370.00	32.7073167	-104.1219040
FTP: 1700' FNL & 100' F - plan hits target cent - Point	0.00 er	0.00	7,237.9	2,103.8	192.0	621,116.80	606,279.00	32.7073139	-104.1221999
BHL: 1700' FNL & 100' F - plan hits target cent - Point	0.00 er	0.00	7,301.0	1,969.0	-9,958.0	620,982.00	596,129.00	32.7069946	-104.1551994
LP: 1700' FNL & 583' FE - plan hits target cent - Point	0.00 er	0.00	7,501.1	2,097.4	-290.0	621,110.39	605,797.00	32.7072989	-104.1237669

Page 5

## State of New Mexico Energy, Minerals and Natural Resources Department

Submit Electronically Via E-permitting

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN										
This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.										
Section 1 – Plan Description <u>Effective May 25, 2021</u>										
I. Operator: Mewbourne Oil Co. OGRID: 14744 Date: 5/2/22										
II. Type: X Original	☐ Amendment	due to □ 19.15.27.	9.D(6)(a) NMA(	C □ 19.15.27.9.D(	6)(b) NMAC □ (	Other.				
If Other, please describe	:									
III. Well(s): Provide the be recompleted from a s	III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.									
Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D		Anticipated oduced Water BBL/D			
Wild Turkey 36/35 B2HE State Com	#1H	l 36 18S 28E	1500' FSL x 290' F	∟ 2000	3500		3500			
IV. Central Delivery P		Wild Turkey 36/3					7.9(D)(1) NMAC]			
V. Anticipated Schedu proposed to be recomple	le: Provide the eted from a sin	following informat gle well pad or com	tion for each new nected to a centr	or recompleted was all delivery point.	ell or set of wells	s propo	sed to be drilled or			
Well Name	API	Spud Date	TD Reached Date	Completion Commencement			First Production Date			
Wild Turkey 36/35 B2HE State Com	#1H	7/2/22	8/2/22	9/2/22	9/17/2	2	9/17/22			
VI. Separation Equipment: 🛮 Attach a complete description of how Operator will size separation equipment to optimize gas capture.										
VII. Operational Practices:   ✓ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.										
VIII. Best Management Practices: ☑ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.										

Page 6

#### Section 2 – Enhanced Plan EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

M Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

#### IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF
		9:	

#### X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map.   Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the
production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of
the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system $\square$ will $\square$ will not have capacity to gather 100% of the anticipated	. natural gas
production volume from the well prior to the date of first production.	

XIII. Line Pressure. Operator $\Box$ does $\Box$ does not anticipate that its existing well( $\epsilon$ ) connected to the same segment, or	r portion, o	of the
natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the	ie new we	ll(s).

 $\square$  Attach Operator's plan to manage production in response to the increased line pressure.

XIV. Confidentiality: 

Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

# Section 3 - Certifications Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

⚠ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

#### Section 4 - Notices

- 1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:
- (a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or
- (b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.
- 2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

#### Page 8

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature:	Bradley Bishop
Printed Name:	BRADLEY BISHOP
Title:	REGULATORY MANAGER
E-mail Address:	BBISHOP@MEWBOURNE.COM
Date:	5/2/22
Phone:	575-393-5905
	OIL CONSERVATION DIVISION (Only applicable when submitted as a standalone form)
Approved By:	
Title:	
Approval Date:	
Conditions of Ap	proval:

### Mewbourne Oil Company

#### Natural Gas Management Plan - Attachment

- VI. Separation equipment will be sized by construction engineering staff based on stated manufacturer daily throughput capacities and anticipated daily production rates to ensure adequate capacity. Closed vent system piping, compression needs, and VRUs will be sized utilizing ProMax modelling software to ensure adequate capacity for anticipated production volumes and conditions.
- VII. Mewbourne Oil Company (MOC) will take following actions to comply with the regulations listed in 19.15.27.8:
  - A. MOC will maximize the recovery of natural gas by minimizing the waste, as defined by 19.15.2 NMAC, of natural gas through venting and flaring. MOC will ensure that well(s) will be connected to a natural gas gathering system with sufficient capacity to transport natural gas. If there is no adequate takeaway for the gas, well(s) will be shut in until the natural gas gathering system is available.
  - B. All drilling operations will be equipped with a rig flare located at least 100 ft from the nearest surface hole. Rig flare will be utilized to combust any natural gas that is brought to surface during normal drilling operations. In the case of emergency venting or flaring the volumes will be estimated and reported appropriately.
  - C. During completion operations any natural gas brought to surface will be flared. Immediately following the finish of completion operations, all well flow will be directed to permanent separation equipment. Produced natural gas from separation equipment will be sent to sales. It is not anticipated that gas will not meet pipeline standards. However, if natural gas does not meet gathering pipeline quality specifications, MOC will flare the natural gas for 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner. MOC will ensure that the flare is sized properly and is equipped with automatic igniter or continuous pilot. The gas sample will analyzed twice per week and the gas will be routed into a gathering system as soon as pipeline specifications are met.
  - D. Natural gas will not be flared with the exceptions and provisions listed in the 19.15.27.8 D.(1) through (4). If there is no adequate takeaway for the separator gas, well(s) will be shut in until the natural gas gathering system is available with exception of emergency or malfunction situations. Venting and/or flaring volumes will be estimated and reported appropriately.
  - E. MOC will comply with the performance standards requirements and provisions listed in 19.15.27.8 E.(1) through (8). All equipment will be designed and sized to handle maximum anticipated pressures and throughputs in order to minimize the waste. Production storage tanks constructed after May 25, 2021 will be equipped with automatic gauging system. Flares constructed after May 25, 2021 will be equipped with automatic igniter or continuous pilot. Flares will be located at least 100' from the well and storage tanks unless otherwise approved by the division. MOC will conduct AVO inspections as described in 19.15.27.8 E (5) (a) with frequencies specified in 19.15.27.8 E (5) (b) and (c). All emergencies will be resolved as quickly and safely as feasible to minimize waste.
  - F. The volume of natural gas that is vented or flared as the result of malfunction or emergency during drilling and completions operations will be estimated. The volume of natural gas that is vented, flared or beneficially used during production operations, will be measured or estimated. MOC will install equipment to measure

the volume of natural gas flared from existing process piping or a flowline piped from equipment such as high pressure separators, heater treaters, or vapor recovery units associated with a well or facility associated with a well authorized by an APD issued after May 25, 2021 that has an average daily production greater than 60 Mcf/day. If metering is not practicable due to circumstances such as low flow rate or low pressure venting and flaring, MOC will estimate the volume of vented or flared natural gas. Measuring equipment will conform to industry standards and will not be designed or equipped with a manifold that allows the diversion of natural gas around the metering element except for the sole purpose of inspecting and servicing the measurement equipment.

VIII. For maintenance activities involving production equipment and compression, venting will be limited to the depressurization of the subject equipment to ensure safe working conditions. For maintenance of production and compression equipment the associated producing wells will be shut in to eliminate venting. For maintenance of VRUs all gas normally routed to the VRU will be routed to flare to eliminate venting.