

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-49221
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator Redwood Operating LLC		6. State Oil & Gas Lease No.
3. Address of Operator PO Box 1370 Artesia, NM 88211-1370		7. Lease Name or Unit Agreement Name Leavitt 13
4. Well Location Unit Letter Lot 3 : 2528 feet from the South line and 737 feet from the West line Section 18 Township 18S Range 27E NMPM County Eddy		8. Well Number 7H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3292' GR		9. OGRID Number 330211
		10. Pool name or Wildcat Red Lake; Glorieta-Yeso

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐
 CLOSED-LOOP SYSTEM ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Redwood Operating LLC would like to move this surface location from the original footages per the C-101. New footages will be Lot 3, 2528 FSL 737 FWL Sec. 18 T18S R27E. This location was moved +or- 560' to the northeast. Location is still in Lot 3.


Attachments: Revised C-102, Revised Directional Plan and Revised Casing and Cement Detail.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE Regulatory Supervisor

DATE 7/21/2022

Type or print name Jerry W Sherrell

E-mail address: jerrys@mec.com

PHONE: 575-748-1288

For State Use Only

APPROVED BY:

TITLE

DATE

Conditions of Approval (if any):

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-49221	² Pool Code 51120	³ Pool Name Red Lake; Glorieta - Yeso
⁴ Property Code 329504	⁵ Property Name LEAVITT 13	⁶ Well Number 7H
⁷ OGRID No. 330211	⁸ Operator Name REDWOOD OPERATING, LLC	⁹ Elevation 3292.1

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
3	18	18 S	27 E		2528	SOUTH	737	WEST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	13	18 S	26 E		1980	SOUTH	1	WEST	EDDY

¹² Dedicated Acres 160	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
---	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Jerry W. Sherrell</i> 7/21/2022 Signature Date Jerry W. Sherrell Printed Name jerry@mecc.com E-mail Address		¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JUNE 29, 2022 Date of Survey <i>William F. Jarantillo</i> Signature and Seal of Professional Surveyor Certificate Number: 12797 SURVEYOR NO. 9191A	
--	--	---	--

Leavitt 13 #7H

--	--

Surface- 12 ¼" hole 1,230'
9 5/8"-36#-J-55

Stage 1	Slurry	Density	Yield	Mix H2O Gals./sk	# of Sacks	% Excess	Slurry Top
Lead	Class C +4%PF20+1% PF1+0.125#/skPF29+.4%PF 45	13.5	1.72	9.102	250	100	Surface
Tail	Class C+.1%PF1	14.8	1.34	6.307	200	100	1,800'

Comments	20bbls Gel Spacer. 50 sacks of 11# Scavenger cement.	Cu/Ft per lin/Ft 385.23
----------	--	----------------------------------

Production-9,018' 7"-26#-L-80
LT&C and BTC (3,125') XO 5 ½"
17# L-80 BTC (5,893')

Stage 1	Slurry	Density	Yield	Mix H2O Gals./sk	# of Sacks	% Excess	Slurry Top
Lead	35/65 Perlite/C 5% PF44+6%PF20+.2%PF13+3ppsPF 42+.4ppsPF45+.125ppsPF29	12.9	1.82	9.21	400	35	Surface
Tail	PVL+1.3%PF44(BWOW)+5%PF1 74+.5%PF506+0.1%PF153+.4#PF 45	13	1.48	7.57	1600	35	2,100'
Comments	20bbls Gel Spacer. 50 sacks of 11# Scavenger cement.	Cu/Ft per lin/Ft 2178					

Casing DesignWell:Leavitt 13 #7H

String Size & Function:9.5/8 in surface x intermediate

Total Depth:1230 ft

Pressure Gradient for Calculations				(While drilling)
Mud weight, collapse:	9.6 #/gal	Safety Factor Collapse:	1.125	
Mud weight, burst:	9.6 #/gal	Safety Factor Burst:	1.25	
Mud weight for joint strength:	9.6 #/gal	Safety Factor Joint Strength	1.8	
BHP @ TD for:	collapse: 614.016 psi	Burst: 614.016 psi,	joint strength: 614.016 psi	

Partially evacuated hole?Pressure gradient remaining:30 #/gal

Max. Shut in surface pressure:500 psi

1st segment	1230 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	1230
O.D.	Weight	Grade	Threads	opt.	min.	mx.
9.625 inches	36 #/ft	J-55	ST&C	3,940	2,960	4,930
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
2,020 psi	3,520 psi	394,000 #	564,000 #	8.765		
2nd segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			
3rd segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			
4th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			
5th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			
6th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			

Select	1st segment bottom	1230	S.F.	Actual	Desire
			collapse	3.289817	>= 1.125
	1230 ft to 0 ft		burst-b	6.697312	>= 1.25
	9.625 36 J-55 ST&C		burst-t	7.04	
	Top of segment 1 (ft)	0	S.F.	Actual	Desire
Select	2nd segment from bottom		collapse	#DIV/0!	>= 1.125
			burst-b	0	>= 1.25
	0 ft to 0 ft		burst-t	0	
	0 0 0 0		jnt strngth	10.42986	>= 1.8

Casing DesignWell:Leavitt 13 #7H

String Size & Function:5 1/2 x 7 inProductionX

Total Depth:9018 ftTVD:3083 ft

Pressure Gradient for Calculations(While drilling)

Mud weight, collapse:10.5 #/galSafety Factor Collapse:1.125

Mud weight, burst:10.3 #/galSafety Factor Burst:1.25

Mud weight for joint strength:10.3 #/galSafety Factor Joint Strength1.8

BHP @ TD for:collapse:1651.255 psiBurst:1651.255 psi, joint strength:1651.255 psi

Partially evacuated hole?Pressure gradient remaining:10 #/gal

Max. Shut in surface pressure:3000 psi

1st segment	9018 ft	to	3125 ft	Make up Torque ft-lbs	Total ft =	5893
O.D.	Weight	Grade	Threads	opt.	min.	mx.
5.5 inches	17 #/ft	L-80	BTC	3410	2560	4260
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
6,290	7,740 psi	338,000 #	397,000 #	4,767		

2nd segment	2200 ft	to	3125 ft	Make up Torque ft-lbs	Total ft =	925
O.D.	Weight	Grade	Threads	opt.	min.	mx.
7 inches	26 #/ft	L-80	BTC	5110	3830	6390
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
5,410 psi	7,240 psi	511,000 #	604,000 #	6,151		

3rd segment	2200 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	2200
O.D.	Weight	Grade	Threads	opt.	min.	mx.
7 inches	26 #/ft	L-80	LT&C	5110	3830	6390
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
5,410 psi	7,240 psi	511,000 #	604,000 #	6,151		

4th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			

5th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			

6th segment	0 ft	to	0 ft	Make up Torque ft-lbs	Total ft =	0
O.D.	Weight	Grade	Threads	opt.	min.	mx.
inches	#/ft					
Collapse Resistance	Internal Yield	Joint Strength	Body Yield	Drift		
psi	psi	,000 #	,000 #			

Select	1st segment bottom	9018	S.F.	Actual	Desire
			collapse	3.809224	>= 1.125
	9018 ft to 3125 ft		burst-b	2.706938	>= 1.25
	5.5 26 L-80 BTC		burst-t	2.622618	
	Top of segment 1 (ft)	3125	S.F.	Actual	Desire
Select	2nd segment from bottom		collapse	3.085286	>= 1.125
			burst-b	2.453198	>= 1.25
	3125 ft to 2200 ft		burst-t	2.441261	
	7 26 L-80 BTC		jnt strngth	4.005049	>= 1.8

Leavitt 13 7H, Plan 1

Operator Redwood Operating LLC		Units feet, °/100ft		11:38 Wednesday, July 20, 2022 Page 1 of 4						
Field Red Lake		County Eddy		Vertical Section Azimuth 270.13						
Well Name Leavitt 13 7H		State New Mexico		Survey Calculation Method Minimum Curvature						
Plan 1		Country USA		Database Access						
Location SL: 2528 FSL & 737 FWL Section 18-T18S-R27E BHL: 1980 FSL & 1 FWL Section 13-T18S-R26E		Map Zone UTM		Lat Long Ref						
Site		Surface X 1848212.1		Surface Long						
Slot Name		Surface Y 11887443.1		Surface Lat						
Well Number 7H		Surface Z 3309.1		Global Z Ref KB						
Project		Ground Level 3291.1		Local North Ref Grid						
UWI										
API										
MD/TVD Ref KB										
DIRECTIONAL WELL PLAN										
MD*	INC*	AZI*	TVD*	N*	E*	DLS*	V. S.*	MapE*	MapN*	SysTVD*
ft	deg	deg	ft	ft	ft	°/100ft	ft	ft	ft	ft
*** TIE (at MD = 2247.00)										
2247.00	0.00	0.0	2247.00	0.00	0.00		0.00	1848212.10	11887443.10	1062.10
2250.00	0.00	0.0	2250.00	0.00	0.00	0.00	0.00	1848212.10	11887443.10	1059.10
2300.00	0.00	0.0	2300.00	0.00	0.00	0.00	0.00	1848212.10	11887443.10	1009.10
*** KOP 8 DEGREES (at MD = 2347.00)										
2347.00	0.00	0.0	2347.00	0.00	0.00	0.00	0.00	1848212.10	11887443.10	962.10
2350.00	0.24	224.0	2350.00	0.00	0.00	8.00	0.00	1848212.10	11887443.10	959.10
2400.00	4.24	224.0	2399.95	-1.41	-1.36	8.00	1.36	1848210.74	11887441.69	909.15
2450.00	8.24	224.0	2449.65	-5.32	-5.14	8.00	5.12	1848206.96	11887437.78	859.45
2500.00	12.24	224.0	2498.84	-11.71	-11.31	8.00	11.28	1848200.79	11887431.39	810.26
2550.00	16.24	224.0	2547.29	-20.56	-19.85	8.00	19.80	1848192.25	11887422.54	761.81
2600.00	20.24	224.0	2594.77	-31.81	-30.72	8.00	30.65	1848181.38	11887411.29	714.33
2650.00	24.24	224.0	2641.04	-45.42	-43.86	8.00	43.76	1848168.24	11887397.68	668.06
2700.00	28.24	224.0	2685.88	-61.32	-59.22	8.00	59.08	1848152.88	11887381.78	623.22
2750.00	32.24	224.0	2729.07	-79.43	-76.71	8.00	76.53	1848135.39	11887363.67	580.03
2800.00	36.24	224.0	2770.39	-99.66	-96.24	8.00	96.02	1848115.86	11887343.44	538.71
2850.00	40.24	224.0	2809.66	-121.92	-117.74	8.00	117.46	1848094.36	11887321.18	499.44
2900.00	44.24	224.0	2846.67	-146.10	-141.08	8.00	140.75	1848071.02	11887297.00	462.43
2950.00	48.24	224.0	2881.24	-172.07	-166.16	8.00	165.77	1848045.94	11887271.03	427.86
3000.00	52.24	224.0	2913.21	-199.71	-192.86	8.00	192.40	1848019.24	11887243.39	395.89
*** 55 DEGREE TANGENT (at MD = 3034.50)										
3034.50	55.00	224.0	2933.67	-219.69	-212.15	8.00	211.65	1847999.95	11887223.41	375.43
3050.00	55.00	224.0	2942.56	-228.82	-220.97	0.00	220.45	1847991.13	11887214.28	366.54
3100.00	55.00	224.0	2971.24	-258.28	-249.42	0.00	248.84	1847962.68	11887184.82	337.86
3150.00	55.00	224.0	2999.92	-287.75	-277.87	0.00	277.22	1847934.23	11887155.35	309.18
3200.00	55.00	224.0	3028.60	-317.21	-306.33	0.00	305.61	1847905.77	11887125.89	280.50
3250.00	55.00	224.0	3057.28	-346.67	-334.78	0.00	333.99	1847877.32	11887096.43	251.82
*** 10 DEGREE BUILD (at MD = 3284.50)										
3284.50	55.00	224.0	3077.07	-367.00	-354.41	0.00	353.58	1847857.69	11887076.10	232.03
3300.00	55.80	225.6	3085.87	-376.05	-363.40	10.00	362.55	1847848.70	11887067.05	223.23
3350.00	58.50	230.6	3113.01	-404.05	-394.67	10.00	393.76	1847817.43	11887039.05	196.10
3400.00	61.38	235.3	3138.06	-430.07	-429.23	10.00	428.25	1847782.87	11887013.03	171.04
3450.00	64.43	239.8	3160.84	-453.91	-466.79	10.00	465.76	1847745.31	11886989.19	148.26
3500.00	67.60	244.0	3181.17	-475.39	-507.09	10.00	506.01	1847705.01	11886967.72	127.93
3550.00	70.87	248.1	3198.90	-494.33	-549.81	10.00	548.68	1847662.29	11886948.77	110.20
3600.00	74.23	252.0	3213.90	-510.61	-594.62	10.00	593.46	1847617.48	11886932.49	95.20
3650.00	77.66	255.7	3226.05	-524.10	-641.20	10.00	640.01	1847570.90	11886919.00	83.05
3700.00	81.13	259.4	3235.25	-534.68	-689.17	10.00	687.96	1847522.93	11886908.42	73.85

Leavitt 13 7H, Plan 1

Operator Redwood Operating LLC		Units feet, °/100ft		11:38 Wednesday, July 20, 2022 Page 2 of 4					
Field Red Lake		County Eddy		Vertical Section Azimuth 270.13					
Well Name Leavitt 13 7H		State New Mexico		Survey Calculation Method Minimum Curvature					
Plan 1		Country USA		Database Access					
Location SL: 2528 FSL & 737 FWL Section 18-T18S-R27E BHL: 1980 FSL & 1 FWL Section 13-T18S-R26E		Map Zone UTM		Lat Long Ref					
Site		Surface X 1848212.1		Surface Long					
Slot Name		Surface Y 11887443.1		Surface Lat					
Well Number 7H		Surface Z 3309.1		Global Z Ref KB					
Project		Ground Level 3291.1		Local North Ref Grid					
UWI									
API									
MD/TVD Ref KB									
DIRECTIONAL WELL PLAN									
MD*	INC*	AZI*	TVD*	N*	E*	DLS*	V. S.*	MapE*	MapN* SysTVD*
ft	deg	deg	ft	ft	ft	°/100ft	ft	ft	ft
3750.00	84.64	263.0	3241.45	-542.29	-738.18	10.00	736.95	1847473.92	11886900.81 67.65
3800.00	88.17	266.5	3244.58	-546.87	-787.86	10.00	786.62	1847424.24	11886896.23 64.52
3850.00	91.71	270.0	3244.63	-548.37	-837.82	10.00	836.57	1847374.28	11886894.73 64.47
*** LANDING POINT (at MD = 3851.24)									
3851.24	91.80	270.1	3244.59	-548.37	-839.06	10.00	837.82	1847373.04	11886894.73 64.51
3900.00	91.80	270.1	3243.06	-548.26	-887.80	0.00	886.55	1847324.30	11886894.84 66.04
3950.00	91.80	270.1	3241.49	-548.15	-937.77	0.00	936.52	1847274.33	11886894.95 67.61
4000.00	91.80	270.1	3239.92	-548.03	-987.75	0.00	986.50	1847224.35	11886895.07 69.18
4050.00	91.80	270.1	3238.35	-547.92	-1037.72	0.00	1036.48	1847174.38	11886895.18 70.75
4100.00	91.80	270.1	3236.78	-547.81	-1087.70	0.00	1086.45	1847124.40	11886895.29 72.32
4150.00	91.80	270.1	3235.21	-547.69	-1137.67	0.00	1136.43	1847074.43	11886895.41 73.89
4200.00	91.80	270.1	3233.64	-547.58	-1187.65	0.00	1186.40	1847024.45	11886895.52 75.46
4250.00	91.80	270.1	3232.07	-547.47	-1237.62	0.00	1236.38	1846974.48	11886895.63 77.03
4300.00	91.80	270.1	3230.49	-547.35	-1287.60	0.00	1286.35	1846924.50	11886895.75 78.61
4350.00	91.80	270.1	3228.92	-547.24	-1337.57	0.00	1336.33	1846874.53	11886895.86 80.18
4400.00	91.80	270.1	3227.35	-547.13	-1387.55	0.00	1386.30	1846824.55	11886895.97 81.75
4450.00	91.80	270.1	3225.78	-547.01	-1437.52	0.00	1436.28	1846774.58	11886896.09 83.32
4500.00	91.80	270.1	3224.21	-546.90	-1487.50	0.00	1486.25	1846724.60	11886896.20 84.89
4550.00	91.80	270.1	3222.64	-546.79	-1537.47	0.00	1536.23	1846674.63	11886896.31 86.46
4600.00	91.80	270.1	3221.07	-546.67	-1587.45	0.00	1586.20	1846624.65	11886896.43 88.03
4650.00	91.80	270.1	3219.50	-546.56	-1637.42	0.00	1636.18	1846574.68	11886896.54 89.60
4700.00	91.80	270.1	3217.93	-546.45	-1687.40	0.00	1686.15	1846524.70	11886896.65 91.17
4750.00	91.80	270.1	3216.36	-546.33	-1737.37	0.00	1736.13	1846474.73	11886896.77 92.74
4800.00	91.80	270.1	3214.79	-546.22	-1787.35	0.00	1786.11	1846424.75	11886896.88 94.31
4850.00	91.80	270.1	3213.22	-546.11	-1837.32	0.00	1836.08	1846374.78	11886897.00 95.88
4900.00	91.80	270.1	3211.65	-545.99	-1887.30	0.00	1886.06	1846324.80	11886897.11 97.45
4950.00	91.80	270.1	3210.08	-545.88	-1937.28	0.00	1936.03	1846274.83	11886897.22 99.02
5000.00	91.80	270.1	3208.51	-545.76	-1987.25	0.00	1986.01	1846224.85	11886897.34 100.59
5050.00	91.80	270.1	3206.94	-545.65	-2037.23	0.00	2035.98	1846174.87	11886897.45 102.16
5100.00	91.80	270.1	3205.37	-545.54	-2087.20	0.00	2085.96	1846124.90	11886897.56 103.73
5150.00	91.80	270.1	3203.80	-545.42	-2137.18	0.00	2135.93	1846074.92	11886897.68 105.30
5200.00	91.80	270.1	3202.22	-545.31	-2187.15	0.00	2185.91	1846024.95	11886897.79 106.88
5250.00	91.80	270.1	3200.65	-545.20	-2237.13	0.00	2235.88	1845974.97	11886897.90 108.45
5300.00	91.80	270.1	3199.08	-545.08	-2287.10	0.00	2285.86	1845925.00	11886898.02 110.02
5350.00	91.80	270.1	3197.51	-544.97	-2337.08	0.00	2335.83	1845875.02	11886898.13 111.59
5400.00	91.80	270.1	3195.94	-544.86	-2387.05	0.00	2385.81	1845825.05	11886898.24 113.16
5450.00	91.80	270.1	3194.37	-544.74	-2437.03	0.00	2435.78	1845775.07	11886898.36 114.73

\$25 x 8 79

www.makinhole.com

Leavitt 13 7H, Plan 1

Operator	Redwood Operating LLC	Units	feet, °/100ft	11:38 Wednesday, July 20, 2022	Page 3 of 4
Field	Red Lake	County	Eddy	Vertical Section Azimuth	270.13
Well Name	Leavitt 13 7H	State	New Mexico	Survey Calculation Method	Minimum Curvature
Plan	1	Country	USA	Database	Access
Location	SL: 2528 FSL & 737 FWL Section 18-T18S-R27E BHL: 1980 FSL & 1 FWL Section 13-T18S-R26E			Map Zone	UTM
Site				Surface X	1848212.1
Slot Name		UWI		Surface Y	11887443.1
Well Number	7H	API		Surface Z	3309.1
Project		MD/TVD Ref	KB	Ground Level	3291.1
				Lat Long Ref	
				Surface Long	
				Surface Lat	
				Global Z Ref	KB
				Local North Ref	Grid

DIRECTIONAL WELL PLAN

MD*	INC*	AZI*	TVD*	N*	E*	DLS*	V. S.*	MapE*	MapN*	SysTVD*
ft	deg	deg	ft	ft	ft	°/100ft	ft	ft	ft	ft
5500.00	91.80	270.1	3192.80	-544.63	-2487.00	0.00	2485.76	1845725.10	11886898.47	116.30
5550.00	91.80	270.1	3191.23	-544.52	-2536.98	0.00	2535.74	1845675.12	11886898.58	117.87
5600.00	91.80	270.1	3189.66	-544.40	-2586.95	0.00	2585.71	1845625.15	11886898.70	119.44
5650.00	91.80	270.1	3188.09	-544.29	-2636.93	0.00	2635.69	1845575.17	11886898.81	121.01
5700.00	91.80	270.1	3186.52	-544.18	-2686.90	0.00	2685.66	1845525.20	11886898.92	122.58
5750.00	91.80	270.1	3184.95	-544.06	-2736.88	0.00	2735.64	1845475.22	11886899.04	124.15
5800.00	91.80	270.1	3183.38	-543.95	-2786.85	0.00	2785.61	1845425.25	11886899.15	125.72
5850.00	91.80	270.1	3181.81	-543.84	-2836.83	0.00	2835.59	1845375.27	11886899.26	127.29
5900.00	91.80	270.1	3180.24	-543.72	-2886.80	0.00	2885.56	1845325.30	11886899.38	128.86
5950.00	91.80	270.1	3178.67	-543.61	-2936.78	0.00	2935.54	1845275.32	11886899.49	130.43
6000.00	91.80	270.1	3177.10	-543.50	-2986.75	0.00	2985.51	1845225.35	11886899.60	132.00
6050.00	91.80	270.1	3175.53	-543.38	-3036.73	0.00	3035.49	1845175.37	11886899.72	133.57
6100.00	91.80	270.1	3173.96	-543.27	-3086.70	0.00	3085.46	1845125.40	11886899.83	135.14
6150.00	91.80	270.1	3172.38	-543.16	-3136.68	0.00	3135.44	1845075.42	11886899.94	136.72
6200.00	91.80	270.1	3170.81	-543.04	-3186.66	0.00	3185.41	1845025.45	11886900.06	138.29
6250.00	91.80	270.1	3169.24	-542.93	-3236.63	0.00	3235.39	1844975.47	11886900.17	139.86
6300.00	91.80	270.1	3167.67	-542.82	-3286.61	0.00	3285.37	1844925.49	11886900.28	141.43
6350.00	91.80	270.1	3166.10	-542.70	-3336.58	0.00	3335.34	1844875.52	11886900.40	143.00
6400.00	91.80	270.1	3164.53	-542.59	-3386.56	0.00	3385.32	1844825.54	11886900.51	144.57
6450.00	91.80	270.1	3162.96	-542.48	-3436.53	0.00	3435.29	1844775.57	11886900.62	146.14
6500.00	91.80	270.1	3161.39	-542.36	-3486.51	0.00	3485.27	1844725.59	11886900.74	147.71
6550.00	91.80	270.1	3159.82	-542.25	-3536.48	0.00	3535.24	1844675.62	11886900.85	149.28
6600.00	91.80	270.1	3158.25	-542.14	-3586.46	0.00	3585.22	1844625.64	11886900.96	150.85
6650.00	91.80	270.1	3156.68	-542.02	-3636.43	0.00	3635.19	1844575.67	11886901.08	152.42
6700.00	91.80	270.1	3155.11	-541.91	-3686.41	0.00	3685.17	1844525.69	11886901.19	153.99
6750.00	91.80	270.1	3153.54	-541.80	-3736.38	0.00	3735.14	1844475.72	11886901.30	155.56
6800.00	91.80	270.1	3151.97	-541.68	-3786.36	0.00	3785.12	1844425.74	11886901.42	157.13
6850.00	91.80	270.1	3150.40	-541.57	-3836.33	0.00	3835.09	1844375.77	11886901.53	158.70
6900.00	91.80	270.1	3148.83	-541.46	-3886.31	0.00	3885.07	1844325.79	11886901.64	160.27
6950.00	91.80	270.1	3147.26	-541.34	-3936.28	0.00	3935.04	1844275.82	11886901.76	161.84
7000.00	91.80	270.1	3145.69	-541.23	-3986.26	0.00	3985.02	1844225.84	11886901.87	163.41
7050.00	91.80	270.1	3144.11	-541.12	-4036.23	0.00	4035.00	1844175.87	11886901.98	164.99
7100.00	91.80	270.1	3142.54	-541.00	-4086.21	0.00	4084.97	1844125.89	11886902.10	166.56
7150.00	91.80	270.1	3140.97	-540.89	-4136.18	0.00	4134.95	1844075.92	11886902.21	168.13
7200.00	91.80	270.1	3139.40	-540.78	-4186.16	0.00	4184.92	1844025.94	11886902.32	169.70
7250.00	91.80	270.1	3137.83	-540.66	-4236.13	0.00	4234.90	1843975.97	11886902.44	171.27
7300.00	91.80	270.1	3136.26	-540.55	-4286.11	0.00	4284.87	1843925.99	11886902.55	172.84

Leavitt 13 7H, Plan 1

Operator	Redwood Operating LLC	Units	feet, °/100ft	11:38 Wednesday, July 20, 2022	Page 4 of 4
Field	Red Lake	County	Eddy	Vertical Section Azimuth	270.13
Well Name	Leavitt 13 7H	State	New Mexico	Survey Calculation Method	Minimum Curvature
Plan	1	Country	USA	Database	Access
Location	SL: 2528 FSL & 737 FWL Section 18-T18S-R27E BHL: 1980 FSL & 1 FWL Section 13-T18S-R26E			Map Zone	UTM
Site				Surface X	1848212.1
Slot Name		UWI		Surface Y	11887443.1
Well Number	7H	API		Surface Z	3309.1
Project		MD/TVD Ref	KB	Ground Level	3291.1
				Lat Long Ref	
				Surface Long	
				Surface Lat	
				Global Z Ref	KB
				Local North Ref	Grid

DIRECTIONAL WELL PLAN

MD*	INC*	AZI*	TVD*	N*	E*	DLS*	V. S.*	MapE*	MapN*	SysTVD*
ft	deg	deg	ft	ft	ft	%/100ft	ft	ft	ft	ft
7350.00	91.80	270.1	3134.69	-540.44	-4336.08	0.00	4334.85	1843876.02	11886902.66	174.41
7400.00	91.80	270.1	3133.12	-540.32	-4386.06	0.00	4384.82	1843826.04	11886902.78	175.98
7450.00	91.80	270.1	3131.55	-540.21	-4436.04	0.00	4434.80	1843776.07	11886902.89	177.55
7500.00	91.80	270.1	3129.98	-540.10	-4486.01	0.00	4484.77	1843726.09	11886903.00	179.12
7550.00	91.80	270.1	3128.41	-539.98	-4535.99	0.00	4534.75	1843676.11	11886903.12	180.69
7600.00	91.80	270.1	3126.84	-539.87	-4585.96	0.00	4584.72	1843626.14	11886903.23	182.26
7650.00	91.80	270.1	3125.27	-539.76	-4635.94	0.00	4634.70	1843576.16	11886903.34	183.83
7700.00	91.80	270.1	3123.70	-539.64	-4685.91	0.00	4684.67	1843526.19	11886903.46	185.40
7750.00	91.80	270.1	3122.13	-539.53	-4735.89	0.00	4734.65	1843476.21	11886903.57	186.97
7800.00	91.80	270.1	3120.56	-539.41	-4785.86	0.00	4784.63	1843426.24	11886903.69	188.54
7850.00	91.80	270.1	3118.99	-539.30	-4835.84	0.00	4834.60	1843376.26	11886903.80	190.11
7900.00	91.80	270.1	3117.42	-539.19	-4885.81	0.00	4884.58	1843326.29	11886903.91	191.68
7950.00	91.80	270.1	3115.85	-539.07	-4935.79	0.00	4934.55	1843276.31	11886904.03	193.25
8000.00	91.80	270.1	3114.27	-538.96	-4985.76	0.00	4984.53	1843226.34	11886904.14	194.83
8050.00	91.80	270.1	3112.70	-538.85	-5035.74	0.00	5034.50	1843176.36	11886904.25	196.40
8100.00	91.80	270.1	3111.13	-538.73	-5085.71	0.00	5084.48	1843126.39	11886904.37	197.97
8150.00	91.80	270.1	3109.56	-538.62	-5135.69	0.00	5134.45	1843076.41	11886904.48	199.54
8200.00	91.80	270.1	3107.99	-538.51	-5185.66	0.00	5184.43	1843026.44	11886904.59	201.11
8250.00	91.80	270.1	3106.42	-538.39	-5235.64	0.00	5234.40	1842976.46	11886904.71	202.68
8300.00	91.80	270.1	3104.85	-538.28	-5285.61	0.00	5284.38	1842926.49	11886904.82	204.25
8350.00	91.80	270.1	3103.28	-538.17	-5335.59	0.00	5334.35	1842876.51	11886904.93	205.82
8400.00	91.80	270.1	3101.71	-538.05	-5385.56	0.00	5384.33	1842826.54	11886905.05	207.39
8450.00	91.80	270.1	3100.14	-537.94	-5435.54	0.00	5434.30	1842776.56	11886905.16	208.96
8500.00	91.80	270.1	3098.57	-537.83	-5485.51	0.00	5484.28	1842726.59	11886905.27	210.53
8550.00	91.80	270.1	3097.00	-537.71	-5535.49	0.00	5534.26	1842676.61	11886905.39	212.10
8600.00	91.80	270.1	3095.43	-537.60	-5585.46	0.00	5584.23	1842626.64	11886905.50	213.67
8650.00	91.80	270.1	3093.86	-537.49	-5635.44	0.00	5634.21	1842576.66	11886905.61	215.24
8700.00	91.80	270.1	3092.29	-537.37	-5685.42	0.00	5684.18	1842526.69	11886905.73	216.81
8750.00	91.80	270.1	3090.72	-537.26	-5735.39	0.00	5734.16	1842476.71	11886905.84	218.38
8800.00	91.80	270.1	3089.15	-537.15	-5785.37	0.00	5784.13	1842426.73	11886905.95	219.95
8850.00	91.80	270.1	3087.58	-537.03	-5835.34	0.00	5834.11	1842376.76	11886906.07	221.52
8900.00	91.80	270.1	3086.01	-536.92	-5885.32	0.00	5884.08	1842326.78	11886906.18	223.10
8950.00	91.80	270.1	3084.43	-536.81	-5935.29	0.00	5934.06	1842276.81	11886906.29	224.67
9000.00	91.80	270.1	3082.86	-536.69	-5985.27	0.00	5984.03	1842226.83	11886906.41	226.24
*** TD (at MD = 9017.24)										
9017.24	91.80	270.1	3082.32	-536.65	-6002.50	0.00	6001.27	1842209.60	11886906.45	226.78

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 127838

CONDITIONS

Operator: Redwood Operating LLC PO Box 1370 Artesia, NM 88210	OGRID: 330211
	Action Number: 127838
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
kpickford	Adhere to previous NMOCD Conditions of Approval	7/22/2022