For State Use Only:

APPROVED BY:

Patricia L Martinez

## Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 320498 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** 30-025-48651 Phone:(575) 748-1283 Fax:(575) 748-9720 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS APOLLO STATE COM (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 144H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location <u>r</u> : <u>842</u> Unit Letter P feet from the S line and feet 422 from the E Township 33E NMPM 24S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3544 GR Pit or Below-grade Tank Application or Closure \_\_ Depth to Groundwater\_\_\_ \_\_\_ Distance from nearest fresh water well \_ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume\_ Pit Liner Thickness: bbls: Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 2/13/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Grade Dpth Yield Open Size Туре Size lb/ft TOC Held Drop Hole 02/14/22 Surf FreshWater 17.5 13.375 54.5 J55 0 1265 600 1.34 С 1500 0 Ν 04/09/22 Int1 Brine 12.25 9.625 40 J55 0 5332 1115 1.33 С 1550 0 Ν 04/18/22 OilBasedMud 20 P110 Prod 6.75 5.5 2530 20660 1405 1.53 Ν Н I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines $\square$ , a general permit $\square$ or an (attached) alternative OCD-approved plan $\square$ SIGNATURE TITLE DATE Electronically Signed Regulatory Manager 7/1/2022 Type or print name Christian Combs E-mail address Telephone No. 720-360-4028 ccombs@taprk.com

TITLE

DATE

8/31/2022 3:14:14 PM

Apollo State Com 144H – Intermediate and Production

4/6/2022: Test BOPS. Drill 12.25 intermediate hole to 5337 ft.

4/9/2022: Run 9.625 inch 40.00 lb J-55 intermediate casing to 5332 ft. Pump 20 bbls fresh water, followed by 795 sks of 11.0 ppg lead cmt, 320 sks of 14.8 ppg tail cmt. Drop plug and displace with 400 bbls of fresh water. 110 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1550 for 30 minutes, good test.

4/10/2022: Test BOPs. Drill 8.75 inch production hole to 9773 ft then switch to 6.75 inch to 20675 ft

4/18/2022: Run 5.5 inch 20 lb P-110 production casing to 20660 ft MD. Pump 40 bbls fresh water, then 360 sks of 10.5 ppg lead and 1045 sks of 13.2 ppg tail cmt. Drop plug and displace with 20 bbls sugar water, 437 bbls fresh water. 0 bbls returned to surface. Est TOC at 2530 ft.

Intermediate Casing Details: Casing ran: 4/9/2022, Fluid Type Brine, Hole 12.25 inch to 5337 ft, Csg Size 9.625 inch, Weight 40lbs, Grade J-55, Est TOC 0 ft, Depth set 5332 ft, Cement 1115 sks, Yield 3.29 lead/1.33 tail, Class C, Pressure Held 1550 psi, Pres Drop 0.

Production Casing details: Casing Date: 4/18/2022, Fluid Type Oil Based Mud, Hole 8.75 inch hole to 9773 ft then switch to 6.75 inch to 20675 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 20660 ft, EST TOC 2530 ft, Cement 1405 sacks, yield 4.11 lead/1.53 tail, Class C lead/ Class H tail.

4/16/2022: TD Reached at 20675 ft MD, 10486 ft TVD. Plug Back Measured depth at 20614 ft MD, 10484 ft TVD. Rig Release on 4/20/2022 at 06:00.