

Office  
 District I - (575) 393-6161  
 1625 N. French Dr., Hobbs, NM 88240  
 District II - (575) 748-1283  
 811 S. First St., Artesia, NM 88210  
 District III - (505) 334-6178  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 District IV - (505) 476-3460  
 1220 S. St. Francis Dr., Santa Fe, NM  
 87505

State of New Mexico  
 Energy, Minerals and Natural Resources

Form C-103  
 Revised July 18, 2013

OIL CONSERVATION DIVISION  
 1220 South St. Francis Dr.  
 Santa Fe, NM 87505

WELL API NO. 30-025-31085	
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Lovington Paddock Unit	
8. Well Number	97
9. OGRID Number 241333	
10. Pool name or Wildcat [40660] Lovington, Paddock	
4. Well Location Unit Letter <u>P</u> : <u>1325</u> feet from the <u>SOUTH</u> line and <u>1228</u> feet from the <u>EAST</u> line Section <u>36</u> Township <u>16S</u> Range <u>36E</u> NMPM County <u>LEA</u>	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ **PLUG AND ABANDON** ☒  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
 DOWNHOLE COMMINGLE ☐  
 CLOSED-LOOP SYSTEM ☐  
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS. ☐ P AND A ☐  
 CASING/CEMENT JOB ☐  
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

**CIPB 5994**

Spot 26 sacks Class C cement from 5994' to 5744'.  
 Spot 26 sacks Class C cement from 4524' to 4274'.  
 Spot 26 sacks Class C cement from 3867' to 3617'.  
 Spot 26 sacks Class C cement from 2099' to 1849'.  
 Spot 26 sacks Class C cement from 250' to 0'.

Cement circulated to surface in both strings. If bubble test fails, plan to run CBL to confirm TOC.

**4" Diameter 4' tall above ground marker**

**See attached conditions of approval**

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Hayes Thibodeaux TITLE Engineer DATE 8/17/2022

Type or print name Hayes Thibodeaux E-mail address: Hayes.Thibodeaux@chevron.com PHONE: 281-726-9683

**For State Use Only**


APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 9/1/22  
 Conditions of Appr

## Wellbore Diagram

Created: 04/22/19	By: _____	Well #: 97	St. Lse: _____
Updated: _____	By: _____	API 30-025-31085	
Lease: Lovington Paddock Unit		Unit Ltr.: P	Section: 36
Field: Lovington		TSHR/Rng: 16S-37E	
Surf. Loc.: 1325 FSL & 1228 FEL		Unit Ltr.: _____	Section: _____
Bot. Loc.: _____		TSHR/Rng: _____	
County: Lea	St.: NM	Directions: Lovington, NM	
Status: _____		Chevno: OM2016	

**Surface Casing**  
 Size: 8-5/8"  
 Wt., Grd.: 24#, J-55  
 Depth: 2031'  
 Sxs Cmt: 1275  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 12-1/4"

**Production Casing**  
 Size: 5-1/2"  
 Wt., Grd.: 15.5#  
 Depth: 6330'  
 Sxs Cmt: 2200  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 7-7/8"



Perfs: 6014' - 6307'

PBTD(est.): \_\_\_\_\_  
 TD: 6,330

KB: \_\_\_\_\_  
 DF: \_\_\_\_\_  
 GL: 3,822  
 Ini. Spud: 01/10/91  
 Ini. Comp.: 02/23/91

Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/28/2005	189	5914.81	12.00	5926.81
Tubing Sub - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/13/2012	1	4.10	5926.81	5930.91
Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/13/2012	2	63.00	5930.91	5993.91
Tubing Anchor/Catcher	Tubing Anchor/Catcher 2.875 W/ 18K TENSION	12/28/2005	1	2.73	5993.91	5996.64
Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/28/2005	7	217.17	5996.64	6213.81
Tubing - OD 2.875	ENDURALLOY Blast Joint 2.875 OD	12/28/2005	2	63.00	6213.81	6276.81
Seat Nipple / Shoe	Seat Nipple/Shoe - Standard (2.875) Mechanical Type	12/28/2005	1	0.90	6276.81	6277.71
Tubing Sub - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift PC ID&OD	12/13/2012	1	4.10	6277.71	6281.81
Bull Plug (Tubing)	Slotted Mud Anchor 2.875	12/28/2005	1	25.30	6281.81	6307.11
Bull Plug (Tubing)	Bull Plug (Unknown Type & Size) - Bare	12/13/2012	1	0.50	6307.11	6307.61
Polished Rod	1.250 (1 1/4 in.) C x 22 - w/Polished Rod Liner	12/08/2006	1	22.00	12.00	34.00
Rod (Sub)	0.980 (1 in.) Fiberglass x 9 Rod Sub	12/08/2006	1	9.00	34.00	43.00
Rod (Sub)	0.980 (1 in.) Fiberglass Rod Sub(s)	12/13/2012	6	12.00	43.00	55.00
Rod	0.990 (1 in.) FG x 37.5 Rod	12/08/2006	85	3187.50	55.00	3242.50
Rod	0.875 (7/8 in.) N-90 (D) x 25 Rod	12/08/2006	110	2750.00	3242.50	5992.50
Rod (Sinker Bar)	1.500 (1 1/2 in.) K x 25 Sinker Bar	12/08/2006	9	225.00	5992.50	6217.50
Shear Tool/Coupling	Shear Tool	12/08/2006	1	0.80	6217.50	6218.30
Rod (Sinker Bar)	1.500 (1 1/2 in.) K x 25 Sinker Bar	12/13/2012	1	25.00	6218.30	6243.30
Rod Pump (Insert) (NON-SERIALIZED)	Rod Pump (Insert) (NON-SERIALIZED) - 25-175-R H BM -24.5 (Bore = 1.75)	12/08/2006	1	24.00	6243.30	6267.30

**PROPOSED Wellbore Diagram**

Created:	<u>04/22/19</u>	By:	<u>                    </u>	Well #:	<u>97</u>	St. Lse:	<u>                    </u>
Updated:	<u>                    </u>	By:	<u>                    </u>	API	<u>30-025-31085</u>		
Lease:	<u>Lovington Paddock Unit</u>			Unit Ltr.:	<u>P</u>	Section:	<u>36</u>
Field:	<u>Lovington</u>			TSHP/Rng:	<u>16S-37E</u>		
Surf. Loc.:	<u>1325 FSL &amp; 1228 FEL</u>			Unit Ltr.:	<u>                    </u>	Section:	<u>                    </u>
Bot. Loc.:	<u>                    </u>			TSHP/Rng:	<u>                    </u>		
County:	<u>Lea</u>	St.:	<u>NM</u>	Directions:	<u>Lovington, NM</u>		
Status:	<u>                    </u>			Chevno:	<u>OM2016</u>		


**Surface Casing**

Size: 8-5/8"  
 Wt., Grd.: 24#, J-55  
 Depth: 2031'  
 Sxs Cmt: 1275  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 12-1/4"

KB:                       
 DF:                       
 GL: 3,822  
 Ini. Spud: 01/10/91  
 Ini. Comp.: 02/23/91

**Production Casing**

Size: 5-1/2"  
 Wt., Grd.: 15.5#  
 Depth: 6330'  
 Sxs Cmt: 2200  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 7-7/8"



PBTD(est.):                       
 TD: 6,330

**CONDITIONS OF APPROVAL  
FOR PLUGGING AND ABANDONMENT  
OCD - Southern District**

The following is a guide or checklist in preparation of a plugging program, this is not all inclusive and care must be exercised in establishing special plugging programs in unique and unusual cases, Notify NMOCD District Office I (Hobbs) at (575)-263-6633 at least 24 hours before beginning work. After MIRU rig will remain on well until it is plugged to surface. OCD is to be notified before rig down.

**Company representative will be on location during plugging procedures.**

1. A notice of intent to plug and abandon a wellbore is required to be approved before plugging operations are conducted. A cement evaluation tool is required in order to ensure isolation of producing formations, protection of water and correlative rights. A cement bond log or other accepted cement evaluation tool is to be provided to the division for evaluation if one has not been previously run or if the well did not have cement circulated to surface during the original casing cementing job or subsequent cementing jobs. Insure all bradenheads have been exposed, identified and valves are operational prior to rig up.
2. Closed loop system is to be used for entire plugging operation. Upon completion, contents of steel pits are to be hauled to a permitted disposal location.
3. Trucking companies being used to haul oilfield waste fluids to a disposal - commercial or private- shall have an approved NMOCD C-133 permit. A copy of this permit shall be available in each truck used to haul waste products. It is the responsibility of the operator as well as the contractor, to verify that this permit is in place prior to performing work. Drivers shall be able to produce a copy upon request of an NMOCD Field inspector.
4. Filing a subsequent C-103 will serve as notification that the well has been plugged.
5. A final C-103 shall be filed (and a site inspection by NMOCD Inspector to determine if the location is satisfactorily cleaned, all equipment, electric poles and trash has been removed to Meet NMOCD standards) before bonding can be released.
6. If work has not begun within 1 Year of the approval of this procedure, an extension request must be file stating the reason the well has not been plugged.
7. Squeeze pressures are not to exceed 500 psi, unless approval is given by NMOCD.
8. Produced water will not be used during any part of the plugging operation.
9. Mud laden fluids must be placed between all cement plugs mixed at 25 sacks per 100 bbls of water.
10. All cement plugs will be a minimum of 100' in length or a minimum of 25 sacks of cement, whichever is greater. 50' of calculated cement excess required for inside casing plugs and 100% calculated cement excess required on outside casing plugs.
11. Class 'C' cement will be used above 7500 feet.
12. Class 'H' cement will be used below 7500 feet.
13. A cement plug is required to be set 50' above and 50' below, casing stubs, DV tools, attempted casing cut offs, cement tops outside casing, salt sections and anywhere the casing is perforated, these plugs require a 4 hour WOC and then will be tagged
14. All Casing Shoes Will Be Perforated 50' below shoe depth and Attempted to be Squeezed, cement needs to be 50' above and 50' Below Casing Shoe inside the Production Casing.
16. When setting the top out cement plug in production, intermediate and surface casing, wellbores should remain full at least 30 minutes after plugs are set
17. A CIBP is to be set within 100' of production perforations, capped with 100' of cement, WOC 4 hours and tag.
18. A CIBP with 35' of cement may be used in lieu of the 100' plug if set with a bailer. This plug will be placed within 100' of the top perforation, (WOC 4 hrs and tag).

19. No more than 3000' is allowed between cement plugs in cased hole and 2000' in open hole.
20. Some of the Formations to be isolated with cement plugs are: These plugs to be set to isolate formation tops
- A) Fusselman
  - B) Devonian
  - C) Morrow
  - D) Wolfcamp
  - E) Bone Springs
  - F) Delaware
  - G) Any salt sections
  - H) Abo
  - I) Glorieta
  - J) Yates.
  - K) Potash---(In the R-111-P Area (Potash Mine Area),  
A solid cement plug must be set across the salt section. Fluid used to mix the cement shall be saturated with the salts that are common to the section penetrated and in suitable proportions, not more than 3% calcium chloride (by weight of cement) will be considered the desired mixture whenever possible, WOC 4 hours and tag, this plug will be 50' below the bottom and 50' above the top of the Formation.
21. If cement does not exist behind casing strings at recommended formation depths, the casing can be cut and pulled with plugs set at recommended depths. If casing is not pulled, perforations will be shot and cement squeezed behind casing, WOC and tagged. These plugs will be set 50' below formation bottom to 50' above formation top inside the casing.

### **DRY HOLE MARKER REQUIREMENTS**

The operator shall mark the exact location of the plugged and abandoned well with a steel marker not less than four inches in diameter, 3' below ground level with a plate of at least ¼" welded to the top of the casing and the dry hole marker welded on the plate with the following information welded on the dry hole marker:

1. Operator name
2. Lease and Well Number
3. API Number
4. Unit letter
5. Quarter Section (feet from the North, South, East or West)
6. Section, Township and Range
7. Plugging Date
8. County

### **SPECIAL CASES -----AGRICULTURE OR PRARIE CHICKEN BREEDING AREAS**

In these areas, a below ground marker is required with all pertinent information mentioned above on a plate, set 3' below ground level, a picture of the plate will be supplied to NMOCD for record, the exact location of the marker (longitude and latitude by GPS) will be provided to NMOCD (We typically require a current survey to verify the GPS)

### **SITE REMEDIATION DUE WITHIN ONE YEAR OF WELL PLUGGING COMPLETION**

**Lovington Well P&A Short Procedure for wells with rods and tubing.****All cement plugs are based on 1.18 yield for Class H and 1.32 yield for Class C**

1. Install casing Riser on intermediate and surface casing.
  - a. Follow the MCBU Ground Disturbance OE Standard before starting any excavations (One Call, Dig Plan)
  - b. Paint the casing valves as follow  
  
Production: Blue  
  
Intermediate: White  
  
Surface: Yellow
2. Call and notify NMOCD 24 hrs. before operations begin.
3. MIRU pulling unit.
  - a. Intrinsically safe fans and H2S scavenger required due to known H2S in the field.
4. Check well pressures, kill well as necessary following The Chevron Initial Well Kill Operating Guidelines.
  - a. Bubble test should be at least 30 minutes and follow the bubble test SOP. On all casing annuli, if bubble test fails Chevron intends to add perf/squeezes, cut and pull casing, or eliminate SCP with another means after the well is plugged to a certain point agreed upon by the NMOCD and Chevron.
  - b. Bubble tests should occur each morning, critical times are prior to pumping upper hydrocarbon plug or pumping cement to surface.
  - c. Perform a final bubble test after cement has hardened at surface.
5. Attempt to pressure test tubing to at least 1,000 psi for 15 minutes or the highest pressure expected while plugging the well.
  - a. If test passes, utilize tubing for work string.
  - b. If test fails, pick up a work string provided by Chevron.
6. Install hydraulic rod BOP and function test.
7. Pull and lay down rods.
  - a. If paraffin is encountered or rods are stuck contact engineer.
8. N/U BOPE using rubber coated hangers provided by Chevron, and pressure test, 250 psi low and 1,000 psi or MASP (per Chevron operating guidelines) for 5 minutes each.
  - a. On a chart, no bleed off allotted.
  - b. Contact engineer if unable to unset TAC, do not shear TAC without the BOP N/U first to mitigate any risks of well control events.
9. If tubing pressure tested, stand back pipe. If it failed, lay down and prepare to run a work string.
10. MIRU wireline and lubricator.
11. Pressure test lubricator to 500 psi or MASP (whichever is larger) for 10 minutes.
  - a. If MASP is greater than 1,000 psi, contact the engineer to discuss running grease injection.
12. Run and set CIBP within 100' of top perforation or as per approved C-103.
  - a. Skip gauge run if TAC pulled freely past setting depth.

13. Fill well with fresh water and pressure test casing to 500 psi for 15 minutes if no P&S required or 1,000 psi for 15 minutes if P&S required.
  - a. 5% bleed off allotted.
  - b. Contact the engineer if pressure test fails, document test results.
14. Perform 30-minute bubble test on surface and production casings. Record results to meet the barrier standard intent. Adjust forward plan as necessary to address SCP.
15. TIH and tag CIBP.
16. Spot MLF, subtracting cement volumes. Do not place MLF until casing pressure tests or above first Perf and Squeezes. If casing pressure test failed in step 13., Chevron requires all casing holes/damage to be covered with cement.
17. Spot 26 sacks Class C cement from 5994' to 5744'.
18. Spot 26 sacks Class C cement from 4524' to 4274'.
19. Spot 26 sacks Class C cement from 3867' to 3617'.
20. Spot 26 sacks Class C cement from 2099' to 1849'.
21. Conduct 30 minute bubble test in all annuli. If bubble test fails and with cement to surface, plan to run CBL to confirm TOC in annulus discuss contingency perforation/squeeze or casing cut/pull. Confirm forward plan with NMOCD.
22. Once a passing bubble test is achieved, Spot 26 sacks Class C cement from 250' to 0'.
23. While RDMO, perform 30-minute bubble test on surface and production casings. Record results to meet the barrier standard intent.
24. Cut all casings & anchors & remove 3' below grade. Verify cement to surface & weld on dry hole marker (4" diameter, 4' tall). Clean location.

Note: All cement plugs class "C" (<7,500') or "H" (>7,500') with closed loop system used, and MLF spotted between plugs.




## Wellbore Diagram

Created: 04/22/19	By: _____	Well #: 97	St. Lse: _____
Updated: _____	By: _____	API: 30-025-31085	
Lease: Lovington Paddock Unit		Unit Ltr.: P	Section: 36
Field: Lovington		TSHR/Rng: 16S-37E	
Surf. Loc.: 1325 FSL & 1228 FEL		Unit Ltr.: _____	Section: _____
Bot. Loc.: _____		TSHR/Rng: _____	
County: Lea	St.: NM	Directions: Lovington, NM	
Status: _____		Chevno: OM2016	

**Surface Casing**  
 Size: 8-5/8"  
 Wt., Grd.: 24#, J-55  
 Depth: 2031'  
 Sxs Cmt: 1275  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 12-1/4"

**Production Casing**  
 Size: 5-1/2"  
 Wt., Grd.: 15.5#  
 Depth: 6330'  
 Sxs Cmt: 2200  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 7-7/8"



Perfs: 6014' - 6307'

PBTD(est.): \_\_\_\_\_  
 TD: 6,330

KB: \_\_\_\_\_  
 DF: \_\_\_\_\_  
 GL: 3,822  
 Ini. Spud: 01/10/91  
 Ini. Comp.: 02/23/91

Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/28/2005	189	5914.81	12.00	5926.81
Tubing Sub - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/13/2012	1	4.10	5926.81	5930.91
Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/13/2012	2	63.00	5930.91	5993.91
Tubing Anchor/Catcher	Tubing Anchor/Catcher 2.875 W/ 18K TENSION	12/28/2005	1	2.73	5993.91	5996.64
Tubing - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift	12/28/2005	7	217.17	5996.64	6213.81
Tubing - OD 2.875	ENDURALLOY Blast Joint 2.875 OD	12/28/2005	2	63.00	6213.81	6276.81
Seat Nipple / Shoe	Seat Nipple/Shoe - Standard (2.875) Mechanical Type	12/28/2005	1	0.90	6276.81	6277.71
Tubing Sub - OD 2.875	J-55 2.875 OD/ 6.50# T&C External Upset 2.441 ID 2.347 Drift PC ID&OD	12/13/2012	1	4.10	6277.71	6281.81
Bull Plug (Tubing)	Slotted Mud Anchor 2.875	12/28/2005	1	25.30	6281.81	6307.11
Bull Plug (Tubing)	Bull Plug (Unknown Type & Size) - Bare	12/13/2012	1	0.50	6307.11	6307.61
Polished Rod	1.250 (1 1/4 in.) C x 22 - w/Polished Rod Liner	12/08/2006	1	22.00	12.00	34.00
Rod (Sub)	0.980 (1 in.) Fiberglass x 9 Rod Sub	12/08/2006	1	9.00	34.00	43.00
Rod (Sub)	0.980 (1 in.) Fiberglass Rod Sub(s)	12/13/2012	6	12.00	43.00	55.00
Rod	0.990 (1 in.) FG x 37.5 Rod	12/08/2006	85	3187.50	55.00	3242.50
Rod	0.875 (7/8 in.) N-90 (D) x 25 Rod	12/08/2006	110	2750.00	3242.50	5992.50
Rod (Sinker Bar)	1.500 (1 1/2 in.) K x 25 Sinker Bar	12/08/2006	9	225.00	5992.50	6217.50
Shear Tool/Coupling	Shear Tool	12/08/2006	1	0.80	6217.50	6218.30
Rod (Sinker Bar)	1.500 (1 1/2 in.) K x 25 Sinker Bar	12/13/2012	1	25.00	6218.30	6243.30
Rod Pump (Insert) (NON-SERIALIZED)	Rod Pump (Insert) (NON-SERIALIZED) - 25-175-R H BM -24.5 (Bore = 1.75)	12/08/2006	1	24.00	6243.30	6267.30



**PROPOSED Wellbore Diagram**

Created:	<u>04/22/19</u>	By:	<u>                    </u>	Well #:	<u>97</u>	St. Lse:	<u>                    </u>
Updated:	<u>                    </u>	By:	<u>                    </u>	API	<u>                    </u>	<u>30-025-31085</u>	<u>                    </u>
Lease:	<u>Lovington Paddock Unit</u>			Unit Ltr.:	<u>P</u>	Section:	<u>36</u>
Field:	<u>Lovington</u>			TSHP/Rng:	<u>                    </u>	<u>16S-37E</u>	<u>                    </u>
Surf. Loc.:	<u>1325 FSL &amp; 1228 FEL</u>			Unit Ltr.:	<u>                    </u>	Section:	<u>                    </u>
Bot. Loc.:	<u>                    </u>			TSHP/Rng:	<u>                    </u>	<u>                    </u>	<u>                    </u>
County:	<u>Lea</u>	St.:	<u>NM</u>	Directions:	<u>Lovington, NM</u>	<u>                    </u>	<u>                    </u>
Status:	<u>                    </u>			Chevno:	<u>OM2016</u>	<u>                    </u>	<u>                    </u>


**Surface Casing**

Size: 8-5/8"  
 Wt., Grd.: 24#, J-55  
 Depth: 2031'  
 Sxs Cmt: 1275  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 12-1/4"

KB:                       
 DF:                       
 GL: 3,822  
 Ini. Spud: 01/10/91  
 Ini. Comp.: 02/23/91

**Production Casing**

Size: 5-1/2"  
 Wt., Grd.: 15.5#  
 Depth: 6330'  
 Sxs Cmt: 2200  
 Circulate: Yes  
 TOC: Surface  
 Hole Size: 7-7/8"



PBTD(est.):                       
 TD: 6,330

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

COMMENTS  
  
Action 134806

COMMENTS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 134806
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM	9/1/2022

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 134806

CONDITIONS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 134806
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	See attached COA	9/1/2022