For State Use Only:

APPROVED BY:

Patricia L Martinez

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 314382 **District II** WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-49174 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS HAMMS STATE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 218H 2. Name of Operator 9. OGRID Number TAP ROCK OPERATING, LLC 372043 3. Address of Operator 10. Pool name or Wildcat 523 Park Point Drive, Suite 200, Golden, CO 80401 4. Well Location Unit Letter M : 996 feet from the S line and feet 497 from the W Township 34 27E NMPM 23S Range County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3189 GR Pit or Below-grade Tank Application or Closure __ Depth to Groundwater___ ___ Distance from nearest fresh water well__ _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ bbls; Construction Material Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See attached description of work for intermediate and production casing See Attached 2/6/2022 Spudded well. **Casing and Cement Program** Date String Csg Weight Dpth Yield Open Size Size lb/ft TOC Held Drop Hole 02/06/22 Surf FreshWater 17.5 13.375 54.5 J55 0 352 450 1.34 С 1500 0 Ν 02/12/22 Int1 Brine 9.875 7.625 29.7 P110 0 8225 1115 1.35 TXI 1305 0 Ν 02/26/22 OilBasedMud 20 P110 Prod 6.75 5.5 4363 13912 1.32 D Ν 483 I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square TITLE SIGNATURE DATE Electronically Signed Regulatory Manager 4/20/2022 Type or print name Christian Combs E-mail address Telephone No. 720-360-4028 ccombs@taprk.com

TITLE

DATE

10/13/2022 8:11:10 AM

Hamms State 218H – Intermediate and Production

2/8/2022: Test BOPS. Drill 9.875 intermediate hole to 8647 ft.

2/12/2022: Run 7.625 inch 29.7 lb P-110 intermediate casing to 8225 ft. Pump 20 bbls chem wash, 20 bbls vis water, followed by 821 sks of 10.5 ppg lead cmt, 294 sks of 13.2 ppg tail cmt. Drop plug and displace with 390 bbls of fresh water. 160 bbls cement to surface. EST TOC at 0 ft. Pressure test casing to 1305 for 30 minutes, good test.

2/23/2022: Drill 6.75 inch production hole to 13939 ft

2/26/2022: Run 5.5 inch 20 lb P-110 production casing to 13912 ft MD. Pump 40 bbls MPE, 92 bbls MRF, then 483 sks of 14.5 ppg tail cmt. Drop plug and displace with 10 bbls sugar water, 278 bbls brine, 20 bbls fresh water. 20 bbls MPE returned to surface. Est TOC at 4363 ft.

Intermediate Casing Details: Casing ran: 2/12/2022, Fluid Type Brine, Hole 9.875 inch to 8647 ft, Csg Size 7.625 inch, Weight 29.7 lbs, Grade P-110, Est TOC 0 ft, Depth set 8225 ft, Cement 1115 sks, Yield 3.53 lead/1.35 tail, Class TXI, Pressure Held 1305 psi, Pres Drop 0.

Production Casing details: Casing Date: 2/26/2022, Fluid Type Oil Based Mud, Hole 6.75 inch hole to 13939 ft, Csg Size, 5.5 inch, Weight 20 lbs, Grade P-110, Depth set 13912 ft, EST TOC 4363 ft, Cement 483 sacks, yield 1.32 tail, Class D.

2/25/2022: TD Reached at 13939 ft MD, 9218 ft TVD. Plug Back Measured depth at 13861 ft MD, 9218 ft TVD. Rig Release on 2/27/2022 at 10:30