

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. **NMNM122619**

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator **EOG RESOURCES INCORPORATED**

3a. Address **1111 BAGBY SKY LOBBY 2, HOUSTON, TX 770** 3b. Phone No. (include area code) **(713) 651-7000**

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)
SEC 7/T25S/R33E/NMP

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No. **DAUNTLESS 7 FED/401H**

9. API Well No. **30-025-50751**

10. Field and Pool or Exploratory Area
WC-025 G-08 S253235G; LWR BONE SPRIN

11. Country or Parish, State
LEA/NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon		
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

EOG respectfully requests an amendment to our approved APD for this well to reflect the following changes:

The original well Dauntless 7 Fed Com 401H (API: 3002550493) has been P&Aed (Sundry ID: 2698100). We request that the old well to be renamed to Dauntless 7 Fed Com 401Y. The replacement well proposed will take the name Dauntless 7 Fed Com 401H.

Change SHL from T-25-S, R-33-E, Sec 7, 370' FSL, 398' FEL, Lea Co., NM, to T-25-S, R-33-E, Sec 7, 310' FSL, 473' FEL, Lea Co., N.M.

Change BHL from T-25-S, R-33-E, Sec 6, 100' FNL, 975' FEL, Lea Co., NM, to T-25-S, R-33-E, Sec 6, 100' FNL, 890' FEL, Lea Co., N.M.

Continued on page 3 additional information

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)
STAR HARRELL / Ph: (432) 848-9161

Title **Regulatory Specialist**

Signature _____ Date **10/14/2022**

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by
CHRISTOPHER WALLS / Ph: (575) 234-2234 / Approved

Title **Petroleum Engineer** Date **10/14/2022**

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office **CARLSBAD**

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

10/18/2022

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Additional Remarks

Change target formation to Second Bone Spring Shale.

Update casing and cement program to current design.

No new surface disturbance or pad expansion is required.

Skid to replace well with collapsed conductor casing.

Location of Well

0. SHL: TR P / 310 FSL / 424 FEL / TWSP: 25S / RANGE: 33E / SECTION: 7 / LAT: 32.138873 / LONG: -103.60412 (TVD: 0 feet, MD: 0 feet)

PPP: TR P / 100 FSL / 975 FEL / TWSP: 25S / RANGE: 33E / SECTION: 7 / LAT: 32.138132 / LONG: -103.605984 (TVD: 9090 feet, MD: 9133 feet)

BHL: LOT 1 / 100 FNL / 890 FEL / TWSP: 25S / RANGE: 33E / SECTION: 6 / LAT: 32.16661 / LONG: -103.605978 (TVD: 9355 feet, MD: 19596 feet)

CONFIDENTIAL

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources
Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

FORM C-102

Revised August 1, 2011

Submit one copy to appropriate
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-025-50751		² Pool Code 97903		³ Pool Name WC-025 G-08 S253235G; LWR BONE SPRIN	
⁴ Property Code 324978		⁵ Property Name DAUNTLESS 7 FED			⁶ Well Number 401H
⁷ OGRID No. 7377		⁸ Operator Name EOG RESOURCES, INC.			⁹ Elevation 3474'

¹⁰Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	7	25-S	33-E	-	310'	SOUTH	473'	EAST	LEA

¹¹Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
1	6	25-S	33-E	-	100'	NORTH	890'	EAST	LEA

¹² Dedicated Acres 640.00	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.





Dauntless 7 Fed 401H

1. GEOLOGIC NAME OF SURFACE FORMATION:

Permian

2. ESTIMATED TOPS OF IMPORTANT GEOLOGICAL MARKERS:

Rustler	1,045'
Tamarisk	1,120'
Top of Salt	1,270'
Base of Salt	4,735'
Lamar	4,965'
Bell Canyon	4,995'
Cherry Canyon	5,990'
Brushy Canyon	7,555'
Bone Spring Lime	9,095'
Leonard (Avalon) Shale	9,175'
1st Bone Spring Sand	10,065'
2nd Bone Spring Shale	10,300'
2nd Bone Spring Sand	10,535'
3rd Bone Spring Carb	11,175'
3rd Bone Spring Sand	11,810'
TD	10,450'

3. ESTIMATED DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS:

Upper Permian Sands	0- 400'	Fresh Water
Bell Canyon	4,995'	Oil
Cherry Canyon	5,990'	Oil
Brushy Canyon	7,555'	Oil
Leonard (Avalon) Shale	9,175'	Oil
1st Bone Spring Sand	10,065'	Oil
2nd Bone Spring Shale	10,300'	Oil
2nd Bone Spring Sand	10,535'	Oil

No other Formations are expected to give up oil, gas or fresh water in measurable quantities. Surface fresh water sands will be protected by setting 13-3/8" casing at 1,150' and circulating cement back to surface.



Dauntless 7 Fed 401H

4. CASING PROGRAM

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
16"	0	1,150	0	1,150	13-3/8"	54.5#	J-55	STC
12-1/4"	0	4,015	0	4,000	9-5/8"	40#	J-55	LTC
12-1/4"	4,015	4,855	4,000	4,840	9-5/8"	40#	HCK-55	LTC
7-7/8"	0	20,671	0	10,450	5-1/2"	17#	HCP-110	LTC

Variance is requested to waive the centralizer requirements for the 9-5/8" casing in the 12-1/4" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 12-1/4" hole interval to maximize cement bond and zonal isolation.

Variance is also requested to waive any centralizer requirements for the 5-1/2" casing in the 7-7/8" hole size. An expansion additive will be utilized, in the cement slurry, for the entire length of the 7-7/8" hole interval to maximize cement bond and zonal isolation.

Cementing Program:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
1,150' 13-3/8"	350	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	100	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 950')
4,840' 9-5/8"	710	12.7	2.22	Lead: Class C + 10% NaCl + 6% Bentonite Gel + 3% MagOx (TOC @ Surface)
	310	14.8	1.32	Tail: Class C + 10% NaCl + 3% MagOx (TOC @ 3872')
20,671' 5-1/2"	1080	11.0	3.21	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 4340')
	750	13.2	1.52	Tail: Class H + 5% NEX-020 + 0.2% NAC-102 + 0.15% NAS-725 + 0.5% NFL-549 + 0.2% NFP-703 + 1% NBE-737 + 0.3% NRT-241 (TOC @ 9990')



Dauntless 7 Fed 401H

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Pre-Mag-M	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

Cement integrity tests will be performed immediately following plug bump.

Note: Cement volumes based on bit size plus at least 25% excess in the open hole plus 10% excess in the cased-hole overlap section.

5. MINIMUM SPECIFICATIONS FOR PRESSURE CONTROL:

Variance is requested to use a co-flex line between the BOP and choke manifold (instead of using a 4" OD steel line).

The minimum blowout preventer equipment (BOPE) shown in Exhibit #1 will consist of a single ram, mud cross and double ram-type (10,000 psi WP) preventer and an annular preventer (5,000-psi WP). Both units will be hydraulically operated and the ram-type will be equipped with blind rams on bottom and drill pipe rams on top. All BOPE will be tested in accordance with Onshore Oil & Gas order No. 2.

EOG will utilize wing unions on BOPE connections that can be isolated from wellbore pressure through means of a choke. All wing unions will be rated to a pressure that meets or exceeds the pressure rating of the BOPE system.

Variance is requested to use a 5,000 psi annular BOP with the 10,000 psi BOP stack.

Before drilling out of the surface casing, the ram-type BOP and accessory equipment will be tested to 10,000/ 250 psig and the annular preventer to 5,000/ 250 psig.

Pipe rams and blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

A hydraulically operated choke will be installed prior to drilling out of the intermediate casing shoe.



Dauntless 7 Fed 401H

6. TYPES AND CHARACTERISTICS OF THE PROPOSED MUD SYSTEM:

During this procedure we plan to use a Closed-Loop System and haul contents to the required disposal.

The applicable depths and properties of the drilling fluid systems are as follows:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,150'	Fresh - Gel	8.6-8.8	28-34	N/c
1,150' – 4,840'	Brine	8.6-8.8	28-34	N/c
4,640' – 20,671' Lateral	Oil Base	8.8-9.5	58-68	N/c - 6

An electronic pit volume totalizer (PVT) will be utilized on the circulating system, to monitor pit volume, flow rate, pump pressure and stroke rate.

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept at the wellsite at all times.

7. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT:

- (A) A kelly cock will be kept in the drill string at all times.
- (B) A full opening drill pipe-stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.
- (C) H2S monitoring and detection equipment will be utilized from surface casing point to TD.

8. LOGGING, TESTING AND CORING PROGRAM:

- (A) Open-hole logs are not planned for this well.
- (B) GR-CCL will be run in cased hole during completions phase of operations.

9. ABNORMAL CONDITIONS, PRESSURES, TEMPERATURES AND POTENTIAL HAZARDS:

The estimated bottom-hole temperature (BHT) at TD is 175 degrees F with an estimated maximum bottom-hole pressure (BHP) at TD of 4,891 psig and a maximum anticipated surface pressure of 2,592 psig (based on 9.0 ppg MW). No hydrogen sulfide or other hazardous gases or fluids have been encountered, reported or are known to exist at this depth in this area. Severe loss circulation is expected from 7,555' to intermediate casing point.



Dauntless 7 Fed 401H

10. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS:

The drilling operation should be finished in approximately one month. If the well is productive, an additional 60-90 days will be required for completion and testing before a decision is made to install permanent facilities.

EOG Resources requests the option to contract a Surface Rig to drill, set surface casing, and Cement on the subject well. After WOC 8 hours or 500 psi compressive strength (whichever is greater), the Surface Rig will move off so the wellhead can be installed. A welder will cut the casing to the proper height and weld on the wellhead (both "A" and "B" sections). The weld will be tested to 1,500 psi. All valves will be closed and a wellhead cap will be installed (diagram attached). If the timing between rigs is such that EOG Resources would not be able to preset the surface, the Primary Rig will MIRU and drill the well in its entirety per the APD.

11. WELLHEAD & Offline Cementing:

A multi-bowl wellhead system will be utilized.

After running the 13-3/8" surface casing, a 13-3/8" BOP/BOPE system with a minimum working pressure of 10,000 psi will be installed on the wellhead system and will be pressure tested to 250 psi low followed by a 10,000 psi pressure test. This pressure test will be repeated at least every 30 days, as per Onshore Order No. 2.

The minimum working pressure of the BOP and related BOPE required for drilling below the surface casing shoe shall be 10,000 psi.

The multi-bowl wellhead will be installed by vendor's representative(s). A copy of the installation instructions for the Cactus Multi-Bowl WH system has been sent to the NM BLM office in Carlsbad, NM.

The wellhead will be installed by a third party welder while being monitored by WH vendor's representative.

All BOP equipment will be tested utilizing a conventional test plug. Not a cup or J-packer type. EOG Resources reserves the option to conduct BOPE testing during wait on cement periods provided a test plug is utilized.

A solid steel body pack-off will be utilized after running and cementing the intermediate casing. After installation the pack-off and lower flange will be pressure tested to 5000 psi.

Casing strings will be tested as per Onshore Order No. 2 to at least 0.22 psi/ft or 1,500 psi, whichever is greater.



Dauntless 7 Fed 401H

EOG Resources Inc. (EOG) respectfully requests a variance from the minimum standards for well control equipment testing of Onshore Order No. 2 (item III.A.2.a.i) to allow a testing schedule of the blow out preventer (BOP) and blow out prevention equipment (BOPE) along with Batch Drilling & Offline cement operations to include the following:

- Full BOPE test at first installation on the pad.
- Full BOPE test every 20 days per Onshore Order No. 2.
- Function test BOP elements per Onshore Order No. 2.
- Break testing BOP and BOPE coupled with batch drilling operations and option to offline cement and/or remediate (if needed) any surface or intermediate sections, according to attached offline cementing support documentation.
- After the well section is secured, the BOP will be disconnected from the wellhead and walked with the rig to another well on the pad.
- TA cap will also be installed per Wellhead vendor procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.
- See attached "EOG BLM Variance 3a -Offline Cement Intermediate Operational Procedure"




Dauntless 7 Fed 401H

310' FSL
473' FEL
Section 7
T-25-S, R-33-E

Proposed Wellbore A

KB: 3499'
GL: 3474'

API: 30-025-*****





Dauntless 7 Fed 401H

Well Name: Dauntless 7 Fed 401H

Location: SHL: 310' FSL & 473' FEL, Section 7, T-25-S, R-33-E, Lea Co., N.M.

BHL: 100' FNL & 890' FEL, Section 6, T-25-S, R-33-E, Lea Co., N.M.

Casing Program B:

Hole Size	Interval MD		Interval TVD		Csg OD	Weight	Grade	Conn
	From (ft)	To (ft)	From (ft)	To (ft)				
13-1/2"	0	1,150	0	1,150	10-3/4"	40.5#	J-55	STC
9-7/8"	0	11,190	0	11,175	8-3/4"	38.5#	P110-EC	VAM Sprint-SF
6-3/4"	0	20,671	0	10,450	5-1/2"	17#	HCP-110	LTC

Cementing Program:

Depth	No. Sacks	Wt. ppg	Yld Ft3/sk	Slurry Description
1,150' 10-3/4"	350	13.5	1.73	Lead: Class C + 4.0% Bentonite Gel + 0.5% CaCl ₂ + 0.25 lb/sk Cello-Flake (TOC @ Surface)
	100	14.8	1.34	Tail: Class C + 0.6% FL-62 + 0.25 lb/sk Cello-Flake + 0.2% Sodium Metasilicate (TOC @ 950')
11,175' 8-3/4"	220	14.2	1.11	1st Stage (Tail): Class C + 0.6% Halad-9 + 0.45% HR-601 + 3% Microbond (TOC @ 7,560')
	1000	14.8	1.5	2nd Stage (Bradenhead squeeze): Class C + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (TOC @ surface)
20,671' 5-1/2"	140	14.2	1.31	Lead: Class H + 0.4% Halad-344 + 0.35% HR-601 + 3% Microbond (TOC @ 10,675')

As a contingency, EOG requests to pump a two stage cement job on the 8-3/4" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon (7,555') and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. If necessary, a top out consisting of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yld, 12.91 ppg) will be executed.



Dauntless 7 Fed 401H

Additive	Purpose
Bentonite Gel	Lightweight/Lost circulation prevention
Calcium Chloride	Accelerator
Cello-flake	Lost circulation prevention
Sodium Metasilicate	Accelerator
MagOx	Expansive agent
Pre-Mag-M	Expansive agent
Sodium Chloride	Accelerator
FL-62	Fluid loss control
Halad-344	Fluid loss control
Halad-9	Fluid loss control
HR-601	Retarder
Microbond	Expansive Agent

Mud Program:

Depth	Type	Weight (ppg)	Viscosity	Water Loss
0 – 1,150'	Fresh - Gel	8.6-8.8	28-34	N/c
1,150' – 4,840'	Brine	10.0-10.2	28-34	N/c
4,840' – 11,175'	Oil Base	8.7-9.4	58-68	N/c - 6
11,175' – 20,671' Lateral	Oil Base	10.0-14.0	58-68	4 - 6

Wellhead & Offline Cementing:

EOG Resources Inc. (EOG) respectfully requests a variance from the minimum standards for well control equipment testing of Onshore Order No. 2 (item III.A.2.a.i) to allow a testing schedule of the blow out preventer (BOP) and blow out prevention equipment (BOPE) along with Batch Drilling & Offline cement operations to include the following:

- Full BOPE test at first installation on the pad.
- Full BOPE test every 30 days per Onshore Order No. 2.
- Function test BOP elements per Onshore Order No. 2.
- Break testing BOP and BOPE coupled with batch drilling operations and option to offline cement and/or remediate (if needed) any surface or intermediate sections, according to attached offline cementing support documentation.
- After the well section is secured, the BOP will be disconnected from the wellhead and walked with the rig to another well on the pad.
- TA cap will also be installed per Wellhead vendor procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.
- See attached "EOG BLM Variance 3a -Offline Cement Intermediate Operational Procedure"



Dauntless 7 Fed 401H

310'

Proposed Wellbore B:

KB: 3499'


473'

GL: 3474'

Section 7

T-25-S, R-33-E

API: 30-025-*****





Cement Program

1. No changes to the cement program will take place for offline cementing.

Summarized Operational Procedure for Intermediate Casing

1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment back pressure valves.
 - a. Float equipment is equipped with two back pressure valves rated to a minimum of 5,000 psi.
2. Land production casing on mandrel hanger through BOP.
 - a. If casing is unable to be landed with a mandrel hanger, then the **casing will be cemented online.**
3. Break circulation and confirm no restrictions.
 - a. Ensure no blockage of float equipment and appropriate annular returns.
 - b. Perform flow check to confirm well is static.
4. Set pack-off
 - a. If utilizing a fluted/ported mandrel hanger, ensure well is static on the annulus and inside the casing by filling the pipe with kill weight fluid, remove landing joint, and set annular packoff through BOP. Pressure test to 5,000 psi for 10 min.
 - b. If utilizing a solid mandrel hanger, ensure well is static on the annulus and inside the casing by filling the pipe with kill weight fluid. Pressure test seals to 5,000 psi for 10 min. Remove landing joint through BOP.
5. After confirmation of both annular barriers and the two casing barriers, install TA plug and pressure test to 5,000 psi for 10 min. Notify the BLM with intent to proceed with nipple down and offline cementing.
 - a. Minimum 4 hrs notice.
6. With the well secured and BLM notified, nipple down BOP and secure on hydraulic carrier or cradle.
 - a. **Note, if any of the barriers fail to test, the BOP stack will not be nipped down until after the cement job has concluded and both lead and tail slurry have reached 500 psi.**
7. Skid/Walk rig off current well.
8. Confirm well is static before removing TA Plug.
 - a. Cementing operations will not proceed until well is under control. (If well is not static, notify BLM and proceed to kill)
 - b. Casing outlet valves will provide access to both the casing ID and annulus. Rig or third party pump truck will kill well prior to cementing.
 - c. Well control plan can be seen in Section B, Well Control Procedures.
 - d. If need be, rig can be moved back over well and BOP nipped back up for any further remediation.



Offline Intermediate Cementing Procedure

2/24/2022

- e. Diagram for rig positioning relative to offline cementing can be seen in Figure 4.
9. Rig up return lines to take returns from wellhead to pits and rig choke.
 - a. Test all connections and lines from wellhead to choke manifold to 5,000 psi high for 10 min.
 - b. If either test fails, perform corrections and retest before proceeding.
 - c. Return line schematics can be seen in Figure 3.
10. Remove TA Plug from the casing.
11. Install offline cement tool.
 - a. Current offline cement tool schematics can be seen in Figure 1 (Cameron) and Figure 2 (Cactus).
12. Rig up cement head and cementing lines.
 - a. Pressure test cement lines against cement head to 80% of casing burst for 10 min.
13. Break circulation on well to confirm no restrictions.
 - a. If gas is present on circulation, well will be shut in and returns rerouted through gas buster.
 - b. Max anticipated time before circulating with cement truck is 6 hrs.
14. Pump cement job as per plan.
 - a. At plug bump, test casing to 0.22 psi/ft or 1500 psi, whichever is greater.
 - b. If plug does not bump on calculated, shut down and wait 8 hrs or 500 psi compressive strength, whichever is greater before testing casing.
15. Confirm well is static and floats are holding after cement job.
 - a. With floats holding and backside static:
 - i. Remove cement head.
 - b. If floats are leaking:
 - i. Shut-in well and WOC (Wait on Cement) until tail slurry reaches 500 psi compressive strength and the casing is static prior to removing cement head.
 - c. If there is flow on the backside:
 - i. Shut in well and WOC until tail slurry reaches 500 psi compressive strength. Ensure that the casing is static prior to removing cement head.
16. Remove offline cement tool.
17. Install night cap with pressure gauge for monitoring.
18. Test night cap to 5,000 psi for 10 min.



Offline Intermediate Cementing Procedure

2/24/2022

Example Well Control Plan Content

A. Well Control Component Table

The table below, which covers the cementing of the **5M MASP (Maximum Allowable Surface Pressure) portion of the well**, outlines the well control component rating in use. This table, combined with the mud program, documents that two barriers to flow can be maintained at all times, independent of the BOP nipped up to the wellhead.

Intermediate hole section, 5M requirement

Component	RWP
Pack-off	10M
Casing Wellhead Valves	10M
Annular Wellhead Valves	5M
TA Plug	10M
Float Valves	5M
2" 1502 Lo-Torque Valves	15M

B. Well Control Procedures

Well control procedures are specific to the rig equipment and the operation at the time the kick occurs. Below are the minimal high-level tasks prescribed to assure a proper shut-in while circulating and cementing through the Offline Cement Adapter.

General Procedure While Circulating

1. Sound alarm (alert crew).
2. Shut down pumps.
3. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
4. Confirm shut-in.
5. Notify tool pusher/company representative.



Offline Intermediate Cementing Procedure

2/24/2022

6. Read and record the following:
 - a. SICP (Shut in Casing Pressure) and AP (Annular Pressure)
 - b. Pit gain
 - c. Time
 - d. Regroup and identify forward plan to continue circulating out kick via rig choke and mud/gas separator. Circulate and adjust mud density as needed to control well.

General Procedure While Cementing

1. Sound alarm (alert crew).
2. Shut down pumps.
3. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
4. Confirm shut-in.
5. Notify tool pusher/company representative.
6. Open rig choke and begin pumping again taking returns through choke manifold and mud/gas separator.
7. Continue to place cement until plug bumps.
8. At plug bump close rig choke and cement head.
9. Read and record the following
 - a. SICP and AP
 - b. Pit gain
 - c. Time
 - d. Shut-in annulus valves on wellhead

General Procedure After Cementing

1. Sound alarm (alert crew).
2. Shut-in Well (close valves to rig pits and open valve to rig choke line. Rig choke will already be in the closed position).
3. Confirm shut-in.
4. Notify tool pusher/company representative.
5. Read and record the following:
 - a. SICP and AP
 - b. Pit gain
 - c. Time
 - d. Shut-in annulus valves on wellhead



Figure 1: Cameron TA Plug and Offline Adapter Schematic







Figure 2: Cactus TA Plug and Offline Adapter Schematic






Offline Intermediate Cementing Procedure

2/24/2022

Figure 3: Back Yard Rig Up




*** All Lines 10M rated working pressure



Offline Intermediate Cementing Procedure

2/24/2022

Figure 4: Rig Placement Diagram





Midland

Lea County, NM (NAD 83 NME)

Dauntless 7 Fed

#401H

143473

OH

Plan: Plan #1

Standard Planning Report

13 October, 2022



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Project	Lea County, NM (NAD 83 NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Dauntless 7 Fed				
Site Position:		Northing:	414,874.00 usft	Latitude:	32.1385453°N
From:	Map	Easting:	762,795.00 usft	Longitude:	103.6178570°W
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "		

Well	#401H					
Well Position	+N/-S	0.0 usft	Northing:	414,962.00 usft	Latitude:	32.1387102°N
	+E/-W	0.0 usft	Easting:	766,970.00 usft	Longitude:	103.6043675°W
Position Uncertainty	0.0 usft		Wellhead Elevation:	usft	Ground Level:	3,474.0 usft
Grid Convergence:	0.39 °					

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	10/7/2022	6.40	59.77	47,303.02614467

Design	Plan #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	357.28

Plan Survey Tool Program	Date	10/13/2022		
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.0	20,670.6 Plan #1 (OH)	EOG MWD+IFR1	MWD + IFR1

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,180.4	3.61	237.64	2,180.3	-3.0	-4.8	2.00	2.00	0.00	237.64	
9,807.5	3.61	237.64	9,792.2	-260.0	-410.2	0.00	0.00	0.00	0.00	
9,987.9	0.00	0.00	9,972.5	-263.0	-415.0	2.00	-2.00	0.00	180.00	KOP 1 (Dauntless 7 F
10,737.9	90.00	359.63	10,450.0	214.5	-418.1	12.00	12.00	-0.05	359.63	
20,670.6	90.00	359.63	10,450.0	10,147.0	-482.0	0.00	0.00	0.00	0.00	BHL (Dauntless 7 Fec



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,100.0	2.00	237.64	2,100.0	-0.9	-1.5	-0.9	2.00	2.00	0.00
2,180.4	3.61	237.64	2,180.3	-3.0	-4.8	-2.8	2.00	2.00	0.00
2,200.0	3.61	237.64	2,199.8	-3.7	-5.8	-3.4	0.00	0.00	0.00
2,300.0	3.61	237.64	2,299.6	-7.1	-11.2	-6.5	0.00	0.00	0.00
2,400.0	3.61	237.64	2,399.4	-10.4	-16.5	-9.6	0.00	0.00	0.00
2,500.0	3.61	237.64	2,499.2	-13.8	-21.8	-12.8	0.00	0.00	0.00
2,600.0	3.61	237.64	2,599.0	-17.2	-27.1	-15.9	0.00	0.00	0.00
2,700.0	3.61	237.64	2,698.9	-20.5	-32.4	-19.0	0.00	0.00	0.00
2,800.0	3.61	237.64	2,798.7	-23.9	-37.7	-22.1	0.00	0.00	0.00
2,900.0	3.61	237.64	2,898.5	-27.3	-43.0	-25.2	0.00	0.00	0.00
3,000.0	3.61	237.64	2,998.3	-30.6	-48.4	-28.3	0.00	0.00	0.00
3,100.0	3.61	237.64	3,098.1	-34.0	-53.7	-31.4	0.00	0.00	0.00
3,200.0	3.61	237.64	3,197.9	-37.4	-59.0	-34.5	0.00	0.00	0.00
3,300.0	3.61	237.64	3,297.7	-40.8	-64.3	-37.7	0.00	0.00	0.00
3,400.0	3.61	237.64	3,397.5	-44.1	-69.6	-40.8	0.00	0.00	0.00
3,500.0	3.61	237.64	3,497.3	-47.5	-74.9	-43.9	0.00	0.00	0.00
3,600.0	3.61	237.64	3,597.1	-50.9	-80.3	-47.0	0.00	0.00	0.00
3,700.0	3.61	237.64	3,696.9	-54.2	-85.6	-50.1	0.00	0.00	0.00
3,800.0	3.61	237.64	3,796.7	-57.6	-90.9	-53.2	0.00	0.00	0.00
3,900.0	3.61	237.64	3,896.5	-61.0	-96.2	-56.3	0.00	0.00	0.00
4,000.0	3.61	237.64	3,996.3	-64.3	-101.5	-59.4	0.00	0.00	0.00
4,100.0	3.61	237.64	4,096.1	-67.7	-106.8	-62.6	0.00	0.00	0.00
4,200.0	3.61	237.64	4,195.9	-71.1	-112.1	-65.7	0.00	0.00	0.00
4,300.0	3.61	237.64	4,295.7	-74.4	-117.5	-68.8	0.00	0.00	0.00
4,400.0	3.61	237.64	4,395.5	-77.8	-122.8	-71.9	0.00	0.00	0.00
4,500.0	3.61	237.64	4,495.3	-81.2	-128.1	-75.0	0.00	0.00	0.00
4,600.0	3.61	237.64	4,595.1	-84.5	-133.4	-78.1	0.00	0.00	0.00
4,700.0	3.61	237.64	4,694.9	-87.9	-138.7	-81.2	0.00	0.00	0.00
4,800.0	3.61	237.64	4,794.7	-91.3	-144.0	-84.3	0.00	0.00	0.00
4,900.0	3.61	237.64	4,894.5	-94.7	-149.4	-87.5	0.00	0.00	0.00
5,000.0	3.61	237.64	4,994.3	-98.0	-154.7	-90.6	0.00	0.00	0.00
5,100.0	3.61	237.64	5,094.1	-101.4	-160.0	-93.7	0.00	0.00	0.00
5,200.0	3.61	237.64	5,193.9	-104.8	-165.3	-96.8	0.00	0.00	0.00



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
5,300.0	3.61	237.64	5,293.7	-108.1	-170.6	-99.9	0.00	0.00	0.00	
5,400.0	3.61	237.64	5,393.5	-111.5	-175.9	-103.0	0.00	0.00	0.00	
5,500.0	3.61	237.64	5,493.3	-114.9	-181.2	-106.1	0.00	0.00	0.00	
5,600.0	3.61	237.64	5,593.1	-118.2	-186.6	-109.2	0.00	0.00	0.00	
5,700.0	3.61	237.64	5,692.9	-121.6	-191.9	-112.4	0.00	0.00	0.00	
5,800.0	3.61	237.64	5,792.7	-125.0	-197.2	-115.5	0.00	0.00	0.00	
5,900.0	3.61	237.64	5,892.5	-128.3	-202.5	-118.6	0.00	0.00	0.00	
6,000.0	3.61	237.64	5,992.3	-131.7	-207.8	-121.7	0.00	0.00	0.00	
6,100.0	3.61	237.64	6,092.1	-135.1	-213.1	-124.8	0.00	0.00	0.00	
6,200.0	3.61	237.64	6,191.9	-138.4	-218.5	-127.9	0.00	0.00	0.00	
6,300.0	3.61	237.64	6,291.7	-141.8	-223.8	-131.0	0.00	0.00	0.00	
6,400.0	3.61	237.64	6,391.5	-145.2	-229.1	-134.1	0.00	0.00	0.00	
6,500.0	3.61	237.64	6,491.3	-148.5	-234.4	-137.3	0.00	0.00	0.00	
6,600.0	3.61	237.64	6,591.1	-151.9	-239.7	-140.4	0.00	0.00	0.00	
6,700.0	3.61	237.64	6,690.9	-155.3	-245.0	-143.5	0.00	0.00	0.00	
6,800.0	3.61	237.64	6,790.7	-158.7	-250.3	-146.6	0.00	0.00	0.00	
6,900.0	3.61	237.64	6,890.5	-162.0	-255.7	-149.7	0.00	0.00	0.00	
7,000.0	3.61	237.64	6,990.3	-165.4	-261.0	-152.8	0.00	0.00	0.00	
7,100.0	3.61	237.64	7,090.1	-168.8	-266.3	-155.9	0.00	0.00	0.00	
7,200.0	3.61	237.64	7,189.9	-172.1	-271.6	-159.0	0.00	0.00	0.00	
7,300.0	3.61	237.64	7,289.7	-175.5	-276.9	-162.2	0.00	0.00	0.00	
7,400.0	3.61	237.64	7,389.5	-178.9	-282.2	-165.3	0.00	0.00	0.00	
7,500.0	3.61	237.64	7,489.3	-182.2	-287.6	-168.4	0.00	0.00	0.00	
7,600.0	3.61	237.64	7,589.1	-185.6	-292.9	-171.5	0.00	0.00	0.00	
7,700.0	3.61	237.64	7,688.9	-189.0	-298.2	-174.6	0.00	0.00	0.00	
7,800.0	3.61	237.64	7,788.7	-192.3	-303.5	-177.7	0.00	0.00	0.00	
7,900.0	3.61	237.64	7,888.5	-195.7	-308.8	-180.8	0.00	0.00	0.00	
8,000.0	3.61	237.64	7,988.3	-199.1	-314.1	-183.9	0.00	0.00	0.00	
8,100.0	3.61	237.64	8,088.1	-202.4	-319.4	-187.1	0.00	0.00	0.00	
8,200.0	3.61	237.64	8,187.9	-205.8	-324.8	-190.2	0.00	0.00	0.00	
8,300.0	3.61	237.64	8,287.8	-209.2	-330.1	-193.3	0.00	0.00	0.00	
8,400.0	3.61	237.64	8,387.6	-212.5	-335.4	-196.4	0.00	0.00	0.00	
8,500.0	3.61	237.64	8,487.4	-215.9	-340.7	-199.5	0.00	0.00	0.00	
8,600.0	3.61	237.64	8,587.2	-219.3	-346.0	-202.6	0.00	0.00	0.00	
8,700.0	3.61	237.64	8,687.0	-222.7	-351.3	-205.7	0.00	0.00	0.00	
8,800.0	3.61	237.64	8,786.8	-226.0	-356.7	-208.8	0.00	0.00	0.00	
8,900.0	3.61	237.64	8,886.6	-229.4	-362.0	-212.0	0.00	0.00	0.00	
9,000.0	3.61	237.64	8,986.4	-232.8	-367.3	-215.1	0.00	0.00	0.00	
9,100.0	3.61	237.64	9,086.2	-236.1	-372.6	-218.2	0.00	0.00	0.00	
9,200.0	3.61	237.64	9,186.0	-239.5	-377.9	-221.3	0.00	0.00	0.00	
9,300.0	3.61	237.64	9,285.8	-242.9	-383.2	-224.4	0.00	0.00	0.00	
9,400.0	3.61	237.64	9,385.6	-246.2	-388.5	-227.5	0.00	0.00	0.00	
9,500.0	3.61	237.64	9,485.4	-249.6	-393.9	-230.6	0.00	0.00	0.00	
9,600.0	3.61	237.64	9,585.2	-253.0	-399.2	-233.7	0.00	0.00	0.00	
9,700.0	3.61	237.64	9,685.0	-256.3	-404.5	-236.9	0.00	0.00	0.00	
9,807.5	3.61	237.64	9,792.2	-260.0	-410.2	-240.2	0.00	0.00	0.00	
9,900.0	1.76	237.64	9,884.7	-262.3	-413.9	-242.3	2.00	-2.00	0.00	
9,917.1	1.42	237.64	9,901.7	-262.5	-414.3	-242.6	2.00	-2.00	0.00	
KOP (Dauntless 7 Fed 401H)										
9,987.9	0.00	0.00	9,972.5	-263.0	-415.0	-243.0	2.00	-2.00	0.00	
KOP 1 (Dauntless 7 Fed 401H)										
10,000.0	1.46	359.63	9,984.6	-262.8	-415.0	-242.9	12.00	12.00	0.00	
10,025.0	4.46	359.63	10,009.6	-261.6	-415.0	-241.6	12.00	12.00	0.00	



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,050.0	7.46	359.63	10,034.5	-259.0	-415.0	-239.0	12.00	12.00	0.00
10,075.0	10.46	359.63	10,059.2	-255.1	-415.1	-235.1	12.00	12.00	0.00
10,100.0	13.46	359.63	10,083.6	-249.9	-415.1	-229.9	12.00	12.00	0.00
10,125.0	16.46	359.63	10,107.8	-243.4	-415.1	-223.5	12.00	12.00	0.00
10,150.0	19.46	359.63	10,131.5	-235.7	-415.2	-215.8	12.00	12.00	0.00
10,175.0	22.46	359.63	10,154.9	-226.8	-415.2	-206.8	12.00	12.00	0.00
10,200.0	25.46	359.63	10,177.7	-216.6	-415.3	-196.7	12.00	12.00	0.00
10,225.0	28.46	359.63	10,200.0	-205.3	-415.4	-185.4	12.00	12.00	0.00
10,250.0	31.46	359.63	10,221.7	-192.8	-415.5	-172.9	12.00	12.00	0.00
10,275.0	34.46	359.63	10,242.6	-179.2	-415.5	-159.3	12.00	12.00	0.00
10,300.0	37.46	359.63	10,262.9	-164.6	-415.6	-144.6	12.00	12.00	0.00
10,325.0	40.46	359.63	10,282.3	-148.8	-415.7	-128.9	12.00	12.00	0.00
10,350.0	43.46	359.63	10,300.9	-132.1	-415.8	-112.2	12.00	12.00	0.00
10,375.0	46.46	359.63	10,318.6	-114.5	-416.0	-94.6	12.00	12.00	0.00
10,389.8	48.24	359.63	10,328.6	-103.6	-416.0	-83.7	12.00	12.00	0.00
FTP1 (Dauntless 7 Fed 401H)									
10,400.0	49.46	359.63	10,335.3	-95.9	-416.1	-76.0	12.00	12.00	0.00
10,425.0	52.46	359.63	10,351.1	-76.5	-416.2	-56.6	12.00	12.00	0.00
10,450.0	55.46	359.63	10,365.8	-56.3	-416.3	-36.5	12.00	12.00	0.00
10,475.0	58.46	359.63	10,379.4	-35.3	-416.5	-15.5	12.00	12.00	0.00
10,500.0	61.46	359.63	10,391.9	-13.7	-416.6	6.1	12.00	12.00	0.00
10,525.0	64.46	359.63	10,403.3	8.6	-416.7	28.3	12.00	12.00	0.00
10,550.0	67.46	359.63	10,413.5	31.4	-416.9	51.2	12.00	12.00	0.00
10,575.0	70.46	359.63	10,422.5	54.7	-417.0	74.5	12.00	12.00	0.00
10,600.0	73.46	359.63	10,430.2	78.5	-417.2	98.2	12.00	12.00	0.00
10,625.0	76.46	359.63	10,436.7	102.6	-417.4	122.3	12.00	12.00	0.00
10,650.0	79.46	359.63	10,441.9	127.1	-417.5	146.8	12.00	12.00	0.00
10,675.0	82.46	359.63	10,445.8	151.8	-417.7	171.4	12.00	12.00	0.00
10,700.0	85.46	359.63	10,448.5	176.6	-417.8	196.3	12.00	12.00	0.00
10,725.0	88.46	359.63	10,449.8	201.6	-418.0	221.2	12.00	12.00	0.00
10,737.9	90.00	359.63	10,450.0	214.5	-418.1	234.0	12.00	12.00	0.00
10,800.0	90.00	359.63	10,450.0	276.6	-418.5	296.1	0.00	0.00	0.00
10,900.0	90.00	359.63	10,450.0	376.6	-419.1	396.1	0.00	0.00	0.00
11,000.0	90.00	359.63	10,450.0	476.6	-419.8	496.0	0.00	0.00	0.00
11,100.0	90.00	359.63	10,450.0	576.6	-420.4	595.9	0.00	0.00	0.00
11,200.0	90.00	359.63	10,450.0	676.6	-421.0	695.8	0.00	0.00	0.00
11,300.0	90.00	359.63	10,450.0	776.6	-421.7	795.7	0.00	0.00	0.00
11,400.0	90.00	359.63	10,450.0	876.6	-422.3	895.6	0.00	0.00	0.00
11,500.0	90.00	359.63	10,450.0	976.6	-423.0	995.6	0.00	0.00	0.00
11,600.0	90.00	359.63	10,450.0	1,076.6	-423.6	1,095.5	0.00	0.00	0.00
11,700.0	90.00	359.63	10,450.0	1,176.6	-424.3	1,195.4	0.00	0.00	0.00
11,800.0	90.00	359.63	10,450.0	1,276.6	-424.9	1,295.3	0.00	0.00	0.00
11,900.0	90.00	359.63	10,450.0	1,376.6	-425.6	1,395.2	0.00	0.00	0.00
12,000.0	90.00	359.63	10,450.0	1,476.6	-426.2	1,495.1	0.00	0.00	0.00
12,100.0	90.00	359.63	10,450.0	1,576.6	-426.8	1,595.0	0.00	0.00	0.00
12,200.0	90.00	359.63	10,450.0	1,676.6	-427.5	1,695.0	0.00	0.00	0.00
12,300.0	90.00	359.63	10,450.0	1,776.6	-428.1	1,794.9	0.00	0.00	0.00
12,400.0	90.00	359.63	10,450.0	1,876.6	-428.8	1,894.8	0.00	0.00	0.00
12,500.0	90.00	359.63	10,450.0	1,976.6	-429.4	1,994.7	0.00	0.00	0.00
12,600.0	90.00	359.63	10,450.0	2,076.6	-430.1	2,094.6	0.00	0.00	0.00
12,700.0	90.00	359.63	10,450.0	2,176.6	-430.7	2,194.5	0.00	0.00	0.00
12,800.0	90.00	359.63	10,450.0	2,276.6	-431.3	2,294.5	0.00	0.00	0.00
12,900.0	90.00	359.63	10,450.0	2,376.6	-432.0	2,394.4	0.00	0.00	0.00
13,000.0	90.00	359.63	10,450.0	2,476.6	-432.6	2,494.3	0.00	0.00	0.00



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
13,100.0	90.00	359.63	10,450.0	2,576.6	-433.3	2,594.2	0.00	0.00	0.00	
13,200.0	90.00	359.63	10,450.0	2,676.5	-433.9	2,694.1	0.00	0.00	0.00	
13,300.0	90.00	359.63	10,450.0	2,776.5	-434.6	2,794.0	0.00	0.00	0.00	
13,400.0	90.00	359.63	10,450.0	2,876.5	-435.2	2,894.0	0.00	0.00	0.00	
13,500.0	90.00	359.63	10,450.0	2,976.5	-435.9	2,993.9	0.00	0.00	0.00	
13,600.0	90.00	359.63	10,450.0	3,076.5	-436.5	3,093.8	0.00	0.00	0.00	
13,700.0	90.00	359.63	10,450.0	3,176.5	-437.1	3,193.7	0.00	0.00	0.00	
13,800.0	90.00	359.63	10,450.0	3,276.5	-437.8	3,293.6	0.00	0.00	0.00	
13,900.0	90.00	359.63	10,450.0	3,376.5	-438.4	3,393.5	0.00	0.00	0.00	
14,000.0	90.00	359.63	10,450.0	3,476.5	-439.1	3,493.4	0.00	0.00	0.00	
14,100.0	90.00	359.63	10,450.0	3,576.5	-439.7	3,593.4	0.00	0.00	0.00	
14,200.0	90.00	359.63	10,450.0	3,676.5	-440.4	3,693.3	0.00	0.00	0.00	
14,300.0	90.00	359.63	10,450.0	3,776.5	-441.0	3,793.2	0.00	0.00	0.00	
14,400.0	90.00	359.63	10,450.0	3,876.5	-441.6	3,893.1	0.00	0.00	0.00	
14,500.0	90.00	359.63	10,450.0	3,976.5	-442.3	3,993.0	0.00	0.00	0.00	
14,600.0	90.00	359.63	10,450.0	4,076.5	-442.9	4,092.9	0.00	0.00	0.00	
14,700.0	90.00	359.63	10,450.0	4,176.5	-443.6	4,192.9	0.00	0.00	0.00	
14,800.0	90.00	359.63	10,450.0	4,276.5	-444.2	4,292.8	0.00	0.00	0.00	
14,900.0	90.00	359.63	10,450.0	4,376.5	-444.9	4,392.7	0.00	0.00	0.00	
15,000.0	90.00	359.63	10,450.0	4,476.5	-445.5	4,492.6	0.00	0.00	0.00	
15,100.0	90.00	359.63	10,450.0	4,576.5	-446.1	4,592.5	0.00	0.00	0.00	
15,200.0	90.00	359.63	10,450.0	4,676.5	-446.8	4,692.4	0.00	0.00	0.00	
15,300.0	90.00	359.63	10,450.0	4,776.5	-447.4	4,792.4	0.00	0.00	0.00	
15,400.0	90.00	359.63	10,450.0	4,876.5	-448.1	4,892.3	0.00	0.00	0.00	
15,500.0	90.00	359.63	10,450.0	4,976.5	-448.7	4,992.2	0.00	0.00	0.00	
15,600.0	90.00	359.63	10,450.0	5,076.5	-449.4	5,092.1	0.00	0.00	0.00	
15,700.0	90.00	359.63	10,450.0	5,176.5	-450.0	5,192.0	0.00	0.00	0.00	
15,800.0	90.00	359.63	10,450.0	5,276.5	-450.7	5,291.9	0.00	0.00	0.00	
15,900.0	90.00	359.63	10,450.0	5,376.5	-451.3	5,391.9	0.00	0.00	0.00	
16,000.0	90.00	359.63	10,450.0	5,476.5	-451.9	5,491.8	0.00	0.00	0.00	
16,100.0	90.00	359.63	10,450.0	5,576.5	-452.6	5,591.7	0.00	0.00	0.00	
16,200.0	90.00	359.63	10,450.0	5,676.5	-453.2	5,691.6	0.00	0.00	0.00	
16,300.0	90.00	359.63	10,450.0	5,776.5	-453.9	5,791.5	0.00	0.00	0.00	
16,400.0	90.00	359.63	10,450.0	5,876.5	-454.5	5,891.4	0.00	0.00	0.00	
16,500.0	90.00	359.63	10,450.0	5,976.5	-455.2	5,991.3	0.00	0.00	0.00	
16,600.0	90.00	359.63	10,450.0	6,076.5	-455.8	6,091.3	0.00	0.00	0.00	
16,700.0	90.00	359.63	10,450.0	6,176.5	-456.4	6,191.2	0.00	0.00	0.00	
16,800.0	90.00	359.63	10,450.0	6,276.5	-457.1	6,291.1	0.00	0.00	0.00	
16,900.0	90.00	359.63	10,450.0	6,376.5	-457.7	6,391.0	0.00	0.00	0.00	
17,000.0	90.00	359.63	10,450.0	6,476.5	-458.4	6,490.9	0.00	0.00	0.00	
17,100.0	90.00	359.63	10,450.0	6,576.5	-459.0	6,590.8	0.00	0.00	0.00	
17,200.0	90.00	359.63	10,450.0	6,676.5	-459.7	6,690.8	0.00	0.00	0.00	
17,300.0	90.00	359.63	10,450.0	6,776.5	-460.3	6,790.7	0.00	0.00	0.00	
17,364.3	90.00	359.63	10,450.0	6,840.8	-460.7	6,855.0	0.00	0.00	0.00	
TGT 1 (Dauntless 7 Fed 401H)										
17,400.0	90.00	359.63	10,450.0	6,876.5	-461.0	6,890.6	0.00	0.00	0.00	
17,500.0	90.00	359.63	10,450.0	6,976.5	-461.6	6,990.5	0.00	0.00	0.00	
17,600.0	90.00	359.63	10,450.0	7,076.5	-462.2	7,090.4	0.00	0.00	0.00	
17,700.0	90.00	359.63	10,450.0	7,176.5	-462.9	7,190.3	0.00	0.00	0.00	
17,800.0	90.00	359.63	10,450.0	7,276.5	-463.5	7,290.3	0.00	0.00	0.00	
17,900.0	90.00	359.63	10,450.0	7,376.5	-464.2	7,390.2	0.00	0.00	0.00	
18,000.0	90.00	359.63	10,450.0	7,476.4	-464.8	7,490.1	0.00	0.00	0.00	
18,100.0	90.00	359.63	10,450.0	7,576.4	-465.5	7,590.0	0.00	0.00	0.00	



Planning Report

Database:	PEDM	Local Co-ordinate Reference:	Well #401H
Company:	Midland	TVD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Project:	Lea County, NM (NAD 83 NME)	MD Reference:	KB = 30' @ 3504.0usft (ICD 301)
Site:	Dauntless 7 Fed	North Reference:	Grid
Well:	#401H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
18,200.0	90.00	359.63	10,450.0	7,676.4	-466.1	7,689.9	0.00	0.00	0.00	
18,300.0	90.00	359.63	10,450.0	7,776.4	-466.7	7,789.8	0.00	0.00	0.00	
18,400.0	90.00	359.63	10,450.0	7,876.4	-467.4	7,889.7	0.00	0.00	0.00	
18,500.0	90.00	359.63	10,450.0	7,976.4	-468.0	7,989.7	0.00	0.00	0.00	
18,600.0	90.00	359.63	10,450.0	8,076.4	-468.7	8,089.6	0.00	0.00	0.00	
18,700.0	90.00	359.63	10,450.0	8,176.4	-469.3	8,189.5	0.00	0.00	0.00	
18,800.0	90.00	359.63	10,450.0	8,276.4	-470.0	8,289.4	0.00	0.00	0.00	
18,900.0	90.00	359.63	10,450.0	8,376.4	-470.6	8,389.3	0.00	0.00	0.00	
19,000.0	90.00	359.63	10,450.0	8,476.4	-471.2	8,489.2	0.00	0.00	0.00	
19,100.0	90.00	359.63	10,450.0	8,576.4	-471.9	8,589.2	0.00	0.00	0.00	
19,200.0	90.00	359.63	10,450.0	8,676.4	-472.5	8,689.1	0.00	0.00	0.00	
19,300.0	90.00	359.63	10,450.0	8,776.4	-473.2	8,789.0	0.00	0.00	0.00	
19,400.0	90.00	359.63	10,450.0	8,876.4	-473.8	8,888.9	0.00	0.00	0.00	
19,500.0	90.00	359.63	10,450.0	8,976.4	-474.5	8,988.8	0.00	0.00	0.00	
19,600.0	90.00	359.63	10,450.0	9,076.4	-475.1	9,088.7	0.00	0.00	0.00	
19,700.0	90.00	359.63	10,450.0	9,176.4	-475.8	9,188.7	0.00	0.00	0.00	
19,800.0	90.00	359.63	10,450.0	9,276.4	-476.4	9,288.6	0.00	0.00	0.00	
19,900.0	90.00	359.63	10,450.0	9,376.4	-477.0	9,388.5	0.00	0.00	0.00	
20,000.0	90.00	359.63	10,450.0	9,476.4	-477.7	9,488.4	0.00	0.00	0.00	
20,100.0	90.00	359.63	10,450.0	9,576.4	-478.3	9,588.3	0.00	0.00	0.00	
20,200.0	90.00	359.63	10,450.0	9,676.4	-479.0	9,688.2	0.00	0.00	0.00	
20,300.0	90.00	359.63	10,450.0	9,776.4	-479.6	9,788.1	0.00	0.00	0.00	
20,400.0	90.00	359.63	10,450.0	9,876.4	-480.3	9,888.1	0.00	0.00	0.00	
20,500.0	90.00	359.63	10,450.0	9,976.4	-480.9	9,988.0	0.00	0.00	0.00	
20,600.0	90.00	359.63	10,450.0	10,076.4	-481.5	10,087.9	0.00	0.00	0.00	
20,660.6	90.00	359.63	10,450.0	10,137.0	-481.9	10,148.4	0.00	0.00	0.00	
PBHL (Dauntless 7 Fed 401H)										
20,670.6	90.00	359.63	10,450.0	10,147.0	-482.0	10,158.4	0.00	0.00	0.00	
BHL (Dauntless 7 Fed 401H)										

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
KOP 1 (Dauntless 7 Fed - plan hits target center - Point	0.00	0.00	9,972.5	-263.0	-415.0	414,699.00	766,555.00	32.1379950°N	103.6057140°W	
FTP1 (Dauntless 7 Fed - plan misses target center by 163.4usft at 10389.8usft MD (10328.6 TVD, -103.6 N, -416.0 E) - Point	0.00	0.00	10,450.0	-213.0	-415.0	414,749.00	766,555.00	32.1381324°N	103.6057129°W	
BHL (Dauntless 7 Fed 401H - plan hits target center - Point	0.00	0.00	10,450.0	10,147.0	-482.0	425,109.00	766,488.00	32.1666104°N	103.6057031°W	

Lea County, NM (NAD 83 NME)

Dauntless 7 Fed #401H

ICD 301

Plan #1



To convert a Magnetic Direction to a Grid Direction, Add 6.01°
To convert a Magnetic Direction to a True Direction, Add 6.40° East
To convert a True Direction to a Grid Direction, Subtract 0.39°

PROJECT DETAILS: Lea County, NM (NAD 83 NME)

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone
System Datum: Mean Sea Level

WELL DETAILS: #401H

KB = 30' @ 3504.0usft (ICD 301) 3474.0

Northing	Easting	Latitude	Longitude
414962.00	766970.00	32.1387102°N	103.6043675°W

SECTION DETAILS



Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.0	
2	2000.0	0.00	0.00	2000.0	0.0	0.0	0.00	0.00	0.0	
3	2180.4	3.61	237.64	2180.3	-3.0	-4.8	2.00	237.64	-240.2	
4	9807.5	3.61	237.64	9792.2	-260.0	-410.2	0.00	0.00	-242.8	
5	9987.9	0.00	0.00	9972.5	-263.0	-415.0	2.00	180.00	-243.0	KOP 1 (Dauntless 7 Fed 401H)
6	10737.9	90.00	359.63	10450.0	214.5	-418.1	12.00	359.63	234.0	
7	20670.6	90.00	359.63	10450.0	10147.0	-482.0	0.00	0.00	10158.4	BHL (Dauntless 7 Fed 401H)

CASING DETAILS

No casing data is available

WELLBORE TARGET DETAILS (MAP CO-ORDINATES)

Name	TVD	+N/-S	+E/-W	Northing	Easting
KOP 1 (Dauntless 7 Fed 401H)	9972.5	-263.0	-415.0	414699.00	766555.00
BHL (Dauntless 7 Fed 401H)	10450.0	10147.0	-482.0	425109.00	766488.00
FTP1 (Dauntless 7 Fed 401H)	10450.0	-213.0	-415.0	414749.00	766555.00



District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 151542

CONDITIONS

Operator: EOG RESOURCES INC P.O. Box 2267 Midland, TX 79702	OGRID: 7377
	Action Number: 151542
	Action Type: [C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104	10/18/2022
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	10/18/2022
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system	10/18/2022
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing	10/18/2022