

Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM
 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-28317
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator CROSS TIMBERS ENERGY LLC		6. State Oil & Gas Lease No. 312479
3. Address of Operator 400 W 7TH ST, FORT WORTH, TX 76102		7. Lease Name or Unit Agreement Name NORTH VACUUM ABO UNIT
4. Well Location Unit Letter <u>A</u> : <u>500</u> feet from the <u>N</u> line and <u>660</u> feet from the <u>E</u> line Section <u>26</u> Township <u>17 S</u> Range <u>34 E</u> NMPM County <u>LEA</u>		8. Well Number 237
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4026 GL		9. OGRID Number 298299
		10. Pool name or Wildcat VACUUM; ABO, NORTH

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
DOWNHOLE COMMINGLE <input type="checkbox"/>			
CLOSED-LOOP SYSTEM <input type="checkbox"/>			
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

MIRU 09/07/2021

PU 5 1/2" RBP, RIH, set @ 4287' and dumped 2 sx sand on top. POOH.

Ran 5 1/2", 17# tie-back liner from surface to top of current liner at 4182'; DV tool @ 3100'.

Cemented with 390 sx, circulated cmt to surface, WOC.

Drilled out cement, retrieved RBP, fished stuck tubing, POOH with fish.

RIH with 2 7/8" production string and rods/rod pump. EOT @ 8426'.

RDMO, RWTP 10/22/2021.

Spud Date:

10/22/1983

Rig Release Date:

10/22/2021

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Connie Blaylock TITLE REGULATORY ANALYST DATE 11/22/2021

Type or print name CONNIE BLAYLOCK E-mail address: cblaylock@mspartner.com PHONE: 817-334-7882

For State Use Only

APPROVED BY: Kerry Fortner TITLE Compliance Officer A DATE 10/28/22

Conditions of Approval (if any):

CROSS TIMBERS ENERGY, LLC
NORTH VACUUM ABO UNIT #237
API 30-025-28317
CURRENT WBD – 11/17/2021

17-1/2" HOLE

SFC CSG - 13-3/8", 54.5# S80 ST&C CSG. + 13-3/8", 48# H40 ST&C CSG. (5 JTS- 204') SET @ 405' W/ 400 SX. CL C + 2% CACL2 + 1/4# FC/SK. CIRC.

ELEV: GL: 4026'
DF: 4035'
KB: 4036'
ZERO- 10' AGL

Tie-back Liner: 5-1/2", 17# N80, LTC from 4,182' to surface (DV tool @ 3,100')
Cmt'd w/ 390 sx. Cmt circ to surf

4/7/2021: Casing leak isolated between 410' - 550'.

12-1/4" HOLE

INT CSG - 8-5/8", 32# S80 ST&C CSG. (14 JTS. - 620') + 8-5/8", 32# J55 ST&C CSG. (58 JTS. - 2486') + 8-5/8", 32# K55 ST&C CSG. (39 JTS. - 1808') SET @ 4918' W/ 3825 SX. CL C + 4% GEL + 15# SALT/SK + 5# GILSONITE/SK + 1/4# FC/ SK + 200 SX. CL C + 2% CACL2 + 1/4# FC/ SK. CIRC.

TOL @ 4182'

8-5/8" shoe @ 4918'

TIGHT SPOT 4290' (2006)

TIGHT SPOT 5150' (2006)

7-7/8" HOLE

2-7/8" Tubing, EOT @ 8426'
1.75" insert rod pump on steel & fiberglass rod string.

LINER - 5-1/2", 17# N80 LT&C (39 JTS. - 1616') + 5-1/2", 15.5# K55 ST&C (66 JTS- 2884') SET @ 8699' (TOL @ 4182') W/ 1000 SX. CL H + 4% GEL + .4% HALAD4 + 1/4# FC + 200 SX. CL H + .4% HALAD4 + 1/4# FC CMT. CIRC.

PBTD @ 8645'

TD @ 8700'

ABO PERFS:

8540'-43', 49'-52', 62'-65', 71'-73', 76'-84', 1 JSPF, 24 HOLES + 8425'-30', 60'-62', 82'-91', 1 JSPF, 19 HOLES. TOTAL 43 HOLES
(2/90): 8402'-8410', 8422'-8430', 8434'-62', 8468'-96', A/ 8000 GALS 15% HCL
ACIDIZE INTERVAL W/ 10000 GAL 15% HCL + 2500# ROCK SALT (5/02)

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 63053

CONDITIONS

Operator: CROSS TIMBERS ENERGY, LLC 400 West 7th Street Fort Worth, TX 76102	OGRID: 298299
	Action Number: 63053
	Action Type: [C-103] Sub. Workover (C-103R)

CONDITIONS

Created By	Condition	Condition Date
kfortner	None	10/28/2022