

Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-03178
5. Indicate Type of Lease STATE [X] FEE [ ]
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name GJ WEST COOP UNIT
8. Well Number 3
9. OGRID Number 328947
10. Pool name or Wildcat GJ; 7RVS-QN-GB-GLORIETA-YESO
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3557' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [ ] Gas Well [ ] Other [X] INJECTION
2. Name of Operator SPUR ENERGY PARTNERS LLC
3. Address of Operator 9655 KATY FREEWAY, SUITE 500, HOUSTON, TX 77024
4. Well Location Unit Letter O : 990 feet from the SOUTH line and 1650 feet from the EAST line
Section 28 Township 17S Range 29E NMPM EDDY County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [ ] PLUG AND ABANDON [ ]
TEMPORARILY ABANDON [ ] CHANGE PLANS [ ]
PULL OR ALTER CASING [ ] MULTIPLE COMPL [ ]
DOWNHOLE COMMINGLE [ ]
CLOSED-LOOP SYSTEM [ ]
OTHER: [ ]
SUBSEQUENT REPORT OF:
REMEDIAL WORK [ ] ALTERING CASING [ ]
COMMENCE DRILLING OPNS. [ ] P AND A [X]
CASING/CEMENT JOB [ ]
OTHER: [ ]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/25/22: MIRU, unflange well then NU BOP & unset TAC, POOH w/ tbg & pkr, RU WL then RIH & tag at 2456', notify OCD & SDFN.
7/26/22: PU bit sub then RIH w/ bit & bit sub to 2510', PU power swivel then RU swivel & break circulation, clean out from 2510' to 2719'- plugged off & POOH w/ tbg wet, RU WL then RIH to 2648' & notify OCD, OCD ok'd depth & set CIBP at 2648' then RD WL, SDFN.
7/27/22: Fill csg w/ FW then run CBL & RD WL, RIH w/ pkr then test plug & backside, notify & standby for orders, LD 12jts then set pkr, PLUG #1 - mix & pump 40sxs Class C cmt from eot at 2633' to toc at 2390' then displ w/ 20bbls, woc then open well & well on vacuum, RIH to tag but let cmt sit longer & SDFN.
7/28/22: RIH & tag PLUG #1 at 2382', RU WL then RIH to perf at 2290' & RD WL, RIH to circulate mud-90bbls then pulled up to 2084' & set pkr-no injection rate, notify OCD then they approved balance plug at 2330', PLUG #2 - mix & pump 50sxs Class C cmt from eot at 2330' to toc at 2040' then displ w/ 7.8bbls, woc then RIH & tag PLUG #2 at 2032', LD tbg & pkr then RIH w/ tbg to 429', SDFN.
7/29/22: PLUG #3 - mix & pump 80sxs Class C cmt from eot at 429' to surface then LD tbg, RD equipment then ND Bop & fill csg to surface, RDSU.

Well plugged 7/29/22

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

Spud Date:

[Empty box for Spud Date]

Rig Release Date:

[Empty box for Rig Release Date]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sarah Chapman TITLE REGULATORY DIRECTOR DATE 12/12/2022

Type or print name SARAH CHAPMAN E-mail address: SCHAPMAN@SPURENERGY.COM PHONE: 832-930-8613

For State Use Only

APPROVED BY: [Signature] TITLE Staff Manager DATE 12/21/22
Conditions of Approval (if any):


API #	30-015-03178	<b>GJ West Coop Unit #3</b>	County, ST	Eddy County, NM
Operator	Spur Energy Partners		Sec-Twn-Rng	28-17S-29E
Field	GJ; 7RVS-QN-GB-GLORIETA-YESO		Footage	990 FSL 1650 FEL
Spud Date	7/22/1944		Survey	32.8009644, -104.0765762

Formation (MD)	
San Andres	
Glorieta	
Yeso	
Bone Spring	
Wolfcamp	
Canyon	
Strawn	
Atoka	
Morrow	

RKB	
GL	3557

Hole Size	10"
TOC	Surface
Method	Calc


Csg Depth	355'
Size	8-5/8"
Weight	28
Grade	
Connections	
Cement	60 sx



Plug #3 80 sx of Class C cement from 429' - surface

Tubing Detail				
Jts	Size	Depth	Length	Detail

Rod Detail				
Rods	Size	Depth	Length	Detail



Plug #2 50 sx of Class C cement from 2340' - 2032'

Perforations  
OH to 3063'  
PB to 2858' w/ 20 sx

Hole Size	8"
TOC	1943'
Method	Calc

Csg Depth	2750'
Size	7"
Weight	20
Grade	
Connections	
Cement	50 sx

Last Update	8/5/2022
By	RCB

PBTD	2858
TD MD	3063
TD TVD	3063

Plug #1 40 sx of Class C cement from 2648' - 2382'  
CIBP @ 2648'

**District I**  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
 1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
 1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 165931

**CONDITIONS**

Operator: Spur Energy Partners LLC 9655 Katy Freeway Houston, TX 77024	OGRID: 328947
	Action Number: 165931
	Action Type: [C-103] Sub. Plugging (C-103P)

**CONDITIONS**

Created By	Condition	Condition Date
gcordero	None	12/21/2022