

<b>Well Name:</b> BIG EDDY UNIT 30E SKYWALKER	<b>Well Location:</b> T20S / R31E / SEC 14 / NWSW / 32.570286 / -103.846945	<b>County or Parish/State:</b> EDDY / NM
<b>Well Number:</b> 100H	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMLC063667	<b>Unit or CA Name:</b> BIG EDDY	<b>Unit or CA Number:</b> NMNM68294X
<b>US Well Number:</b> 300154619400X1	<b>Well Status:</b> Approved Application for Permit to Drill	<b>Operator:</b> XTO PERMIAN OPERATING LLC

Notice of Intent

**Sundry ID:** 2702519

**Type of Submission:** Notice of Intent

**Date Sundry Submitted:** 11/11/2022

**Date proposed operation will begin:** 12/01/2022

**Type of Action:** APD Change

**Time Sundry Submitted:** 05:44

**Procedure Description:** \*\*Surface Location Move, Bottom Hole Location, Casing/Cement, Drilling Variance Changes  
XTO Permian Operating, LLC requests permission to make the following changes to the original APD: No Additional  
Surface Disturbance Change SHL fr/1540'FSL & 465'FWL, 14-20S-31E to 1465'FSL & 480'FWL, 14-20S-31E. Well  
Stays in the Same Quarter-Quarter as Permitted Total SHL Move: 75' South & 15' East SHL change requested to  
optimize well pad layout, drilling efficiencies, and for safety purposes. Change BHL fr/660'FNL & 50'FEL to 440'FNL &  
50'FEL No change to section, township or range. Casing/Cement design per the attached drilling program.  
Attachments: C102 Drilling Program Directional Plan Multibowl Diagram Variance Requests

NOI Attachments

**Procedure Description**

BEU\_30E\_Skywalker\_100H\_Sundry\_Attachments\_20221111054406.pdf

<b>Well Name:</b> BIG EDDY UNIT 30E SKYWALKER	<b>Well Location:</b> T20S / R31E / SEC 14 / NWSW / 32.570286 / -103.846945	<b>County or Parish/State:</b> EDDY / NM
<b>Well Number:</b> 100H	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMLC063667	<b>Unit or CA Name:</b> BIG EDDY	<b>Unit or CA Number:</b> NMNM68294X
<b>US Well Number:</b> 300154619400X1	<b>Well Status:</b> Approved Application for Permit to Drill	<b>Operator:</b> XTO PERMIAN OPERATING LLC

Conditions of Approval

Additional

Sec\_14\_20S\_31E\_NMP\_Sundry\_2702520\_Big\_Eddy\_Unit\_30E\_Skywalker\_100H\_Eddy\_XTO\_COAs\_20230119154816.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

<b>Operator Electronic Signature:</b> STEPHANIE RABADUE	<b>Signed on:</b> NOV 11, 2022 05:44 AM
<b>Name:</b> XTO PERMIAN OPERATING LLC	
<b>Title:</b> Regulatory Coordinator	
<b>Street Address:</b> 500 W. Illinois St, Ste 100	
<b>City:</b> Midland	<b>State:</b> TX
<b>Phone:</b> (432) 620-6714	
<b>Email address:</b> STEPHANIE.RABADUE@EXXONMOBIL.COM	

Field

<b>Representative Name:</b>		
<b>Street Address:</b>		
<b>City:</b>	<b>State:</b>	<b>Zip:</b>
<b>Phone:</b>		
<b>Email address:</b>		

BLM Point of Contact

<b>BLM POC Name:</b> CHRISTOPHER WALLS	<b>BLM POC Title:</b> Petroleum Engineer
<b>BLM POC Phone:</b> 5752342234	<b>BLM POC Email Address:</b> cwalls@blm.gov
<b>Disposition:</b> Approved	<b>Disposition Date:</b> 01/20/2023
<b>Signature:</b> Chris Walls	

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office  
☐ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-015-46194	<sup>2</sup> Pool Code 97650	<sup>3</sup> Pool Name WC Williams Sink; Bone Spring
<sup>4</sup> Property Code 325955	<sup>5</sup> Property Name BIG EDDY UNIT 30E SKYWALKER	<sup>6</sup> Well Number 100H
<sup>7</sup> OGRID No. 373075	<sup>8</sup> Operator Name XTO PERMIAN OPERATING, LLC.	<sup>9</sup> Elevation 3,447'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	14	20 S	31 E		1,465	SOUTH	480	WEST	EDDY

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	13	20 S	31 E		440	NORTH	50	EAST	EDDY

<sup>12</sup> Dedicated Acres 320	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<sup>17</sup> OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*Stephanie Rabadue* 11/10/2022  
Signature Date

Stephanie Rabadue  
Printed Name

stephanie.rabadue@exxonmobil.com  
E-mail Address

<sup>18</sup> SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

11-10-2022

Date of Survey

Signature and Seal of  
Professional Surveyor:

MARK DILLON HARP 23786  
Certificate Number

AI

2017081252



**DRILLING PLAN: BLM COMPLIANCE**  
(Supplement to BLM 3160-3)

XTO Energy Inc.  
Big Eddy Unit 30E Skywalker 100H

**1. Geologic Name of Surface Formation**

A. Quaternary

**2. Estimated Tops of Geological Markers & Depths of Anticipated Fresh Water, Oil or Gas**

Formation	Well Depth (TVD)	Water/Oil/Gas
Rustler	686'	Water
Top of Salt	950'	Water
Base of Salt	1969'	Water
Capitan Reef	2736'	Water
Delaware	4017'	Water
Brushy Canyon	5785'	Water/Oil/Gas
Bone Spring	7371'	Water
1st Bone Spring Ss	8290'	Water/Oil/Gas
2nd Bone Spring Ss	9142'	Water/Oil/Gas
Target/Land Curve	9402'	Water/Oil/Gas

\*\*\* Hydrocarbons @ Brushy Canyon

\*\*\* Groundwater depth 40' (per NM State Engineers Office).

No other formations are expected to yield oil, gas or fresh water in measurable volumes. The surface fresh water sands will be protected by setting 18.625 inch casing @ 786' (164' above the salt) and circulating cement back to surface. The salt will be isolated by setting 13.375 inch casing at 2069' and circulating cement to surface. The second intermediate will isolate the Capitan Reef from the salt down to the next casing seat by setting 9.625 inch casing at 4067' and cemented to surface. A 8.5 inch curve and 8.5 inch lateral hole will be drilled to 21037 MD/TD and 5.5 inch production casing will be set at TD and cemented back up to 2nd intermediate (estimated TOC 2661 feet; >50' above the Capitan Reef) per Potash regulations.

**3. Casing Design**

Hole Size	Depth	OD Csg	Weight	Grade	Collar	New/Used	SF Burst	SF Collapse	SF Tension
24	0' – 786'	18.625	87.5	J-55	BTC	New	3.62	1.77	19.32
17.5	0' – 2069'	13.375	54.5	J-55	BTC	New	2.72	1.80	7.56
12.25	0' – 2169'	9.625	40	HC P-110	BTC	New	3.07	4.17	7.75
12.25	2169' – 4067'	9.625	40	HC L-80	BTC	New	2.23	3.77	12.07
8.5	0' – 3967'	5.5	20	RY P-110	Semi-Premium	New	1.05	5.66	2.24
8.5	3967' - 21037'	5.5	20	RY P-110	Semi-Flush	New	1.05	2.39	2.42

- XTO requests the option to utilize a spudder rig (Atlas Copco RD20 or Equivalent) to set and cement surface and intermediate 1 casing per this Sundry
- XTO requests to not utilize centralizers in the curve and lateral
- 13.375 Collapse analyzed using 50% evacuation based on regional experience.
- 9.625 Collapse analyzed using 50% evacuation based on regional experience.
- 5.5 Tension calculated using vertical hanging weight plus the lateral weight multiplied by a friction factor of 0.35
- Test on 2M annular & Casing will be limited to 70% burst of the casing or 1500 psi, whichever is less
- XTO requests the option to use 5" BTC Float equipment for the the production casing

**Wellhead:**

*Permanent Wellhead – Multibowl System*

A. Starting Head: 13-5/8" 10M top flange x 18-5/8" bottom

B. Tubing Head: 13-5/8" 10M bottom flange x 7-1/16" 15M top flange

- Wellhead will be installed by manufacturer's representatives.
- Manufacturer will monitor welding process to ensure appropriate temperature of seal.
- Operator will test the 9-5/8" casing per BLM Onshore Order 2
- Wellhead Manufacturer representative will not be present for BOP test plug installation

#### 4. Cement Program

##### **Surface Casing: 18.625, 87.5 New BTC, J-55 casing to be set at +/- 786'**

Lead: 850 sxs Class C (mixed at 12.8 ppg, 1.95 ft<sup>3</sup>/sx, 10.93 gal/sx water)  
 Tail: 550 sxs Class C + 2% CaCl (mixed at 14.8 ppg, 1.35 ft<sup>3</sup>/sx, 6.39 gal/sx water)  
 Top of Cement: Surface  
 Compressives:           12-hr =           250 psi           24 hr = 500 psi

Due to the high probability of not getting cement to surface during conventional top-out jobs in the area, ~10-20 ppb gravel will be added on the backside of the 1" to get cement to surface, if required.

##### **1st Intermediate Casing: 13.375, 54.5 New BTC, J-55 casing to be set at +/- 2069'**

Lead: 1260 sxs Class C (mixed at 12.9 ppg, 1.95 ft<sup>3</sup>/sx, 10.93 gal/sx water)  
 Tail: 310 sxs Class C + 2% CaCl (mixed at 14.8 ppg, 1.33 ft<sup>3</sup>/sx, 6.39 gal/sx water)  
 Top of Cement: Surface  
 Compressives:           12-hr =           900 psi           24 hr = 1500 psi

##### **2nd Intermediate Casing: 9.625, 40 New casing to be set at +/- 4067'**

###### 1st Stage

Optional Lead: 990 sxs Class C (mixed at 10.5 ppg, 2.37 ft<sup>3</sup>/sx, 12.78 gal/sx water)  
 TOC: 0  
 Tail: 140 sxs Class C (mixed at 14.8 ppg, 1.33 ft<sup>3</sup>/sx, 6.39 gal/sx water)  
 TOC: 3767  
 Compressives:           12-hr =           900 psi           24 hr = 1150 psi

###### 2nd Stage Bradenhead (if needed)

Optional Tail: 1220 sxs Class C (mixed at 14.8 ppg, 1.33 ft<sup>3</sup>/sx, 6.39 gal/sx water)  
 Top of Cement: 0  
 Compressives:           12-hr =           900 psi           24 hr = 1150 psi

XTO requests the option to pump a two stage cement job on the 9-5/8" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Capitan Reef (2736') and the second stage performed as a bradenhead squeeze with planned cement from the Capitan Reef to surface. If cement is not visually confirmed to circulate to surface, the final cement top after the second stage job will be verified by Echo-meter. If necessary, a top out consisting of 1,500 sack of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yd, 12.91 ppg) will be executed as a contingency. If cement is still unable to circulate to surface, another Echo-meter run will be performed for cement top verification.

XTO will include the Echo-meter verified fluid top and the volume of displacement fluid above the cement slurry in the annulus in all post-drill sundries on wells utilizing this cement program.

XTO will report to the BLM the volume of fluid (limited to 5 bbls) used to flush intermediate casing valves following backside cementing procedures.

XTO requests to pump an Optional Lead if well conditions dictate in an attempt to bring cement to surface. If cement reaches surface, the BLM will be notified and the second stage bradenhead squeeze and subsequent TOC verification will be negated.

XTO requests the option to conduct the bradenhead squeeze and TOC verification offline as per standard approval from BLM when unplanned remediation is needed and batch drilling is approved. In the event the bradenhead is conducted, we will ensure the first stage cement job is cemented properly and the well is static with floats holding and no pressure on the csg annulus as with all other casing strings where batch drilling operations occur before moving off the rig. The TA cap will also be installed per Cactus procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.

**Production Casing: 5.5, 20 New Semi-Flush, RY P-110 casing to be set at +/- 21037'**1st Stage

Lead: 420 sxs 50/50 POZ/Class C (mixed at 11.5 ppg, 2.6 ft<sup>3</sup>/sx, 14.84 gal/sx water) Top of Cement: 5785 feet  
Tail: 1920 sxs 50/50 POZ/Class H (mixed at 13.2 ppg, 1.51 ft<sup>3</sup>/sx, 7.21 gal/sx water) Top of Cement: 10005 feet  
Compressives: 12-hr = 1375 psi 24 hr = 2285 psi

2nd Stage Bradenhead (if needed)

Optional Tail: 1070 sxs Class C (mixed at 14.8 ppg, 1.33 ft<sup>3</sup>/sx, 6.39 gal/sx water)  
Top of Cement: 2661  
Compressives: 12-hr = 900 psi 24 hr = 1150 psi

XTO requests the option to pump a two stage cement job on the 5-1/2" production casing string with the first stage being pumped conventionally with the calculated top of cement at the Brushy Canyon (4017') and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to a depth dictated by the COA or current regulations.

A freshwater spacer will be pumped behind the cement to displace to the desired depth. A bradenhead squeeze will reduce channeling and allow for a more accurate placement of cement, while leaving an un-cemented portion of the annulus for pressure monitoring during completions operations.

XTO requests the ability to conduct the bradenhead squeeze offline.

XTO requests to pump an Optional Lead & Tail, if well conditions dictate, in an attempt to bring top of cement as dictated by the COA or current regulations. If cement reaches this depth, the BLM will be notified and the second stage bradenhead squeeze will be negated.

Lead: 1410 sxs 50/50 POZ/Class C (mixed at 11.5 ppg, 2.6 ft<sup>3</sup>/sx, 14.84 gal/sx water) Top of Cement: 2661 feet  
Tail: 1920 sxs 50/50 POZ/Class H (mixed at 13.2 ppg, 1.51 ft<sup>3</sup>/sx, 7.21 gal/sx water) Top of Cement: 10005 feet  
Compressives: 12-hr = 1375 psi 24 hr = 2285 psi

XTO requests the option to offline cement and remediate (if needed) surface and intermediate casing strings where batch drilling is approved and if unplanned remediation is needed. XTO will ensure well is static with no pressure on the csg annulus, as with all other casing strings where batch drilling operations occur before moving off the rig. The TA cap will also be installed when applicable per Cactus procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops. Offline cement operations will then be conducted after the rig is moved off the current well to the next well in the batch sequence.

## 5. Pressure Control Equipment

Once the permanent WH is installed on the 18.625 casing, the blow out preventer equipment (BOP) will consist of a 13-5/8" minimum 3M Hydriil and a 13-5/8" minimum 3M Double Ram BOP. MASP should not exceed 0 psi. In any instance where 10M BOP is required by BLM, XTO requests a variance to utilize 5M annular with 10M ram preventers (a common BOP configuration, which allows use of 10M rams in unlikely event that pressures exceed 5M).

All BOP testing will be done by an independent service company. Annular pressure tests will be limited to 50% of the working pressure. When nipping up on the 18.625, 3M bradenhead and flange, the BOP test will be limited to 3000 psi. When nipping up on the 13.375, the BOP will be tested to a minimum of 3000 psi. All BOP tests will include a low pressure test as per BLM regulations. The 3M BOP diagrams are attached. Blind rams will be functioned tested each trip, pipe rams will be functioned tested each day.

A variance is requested to allow use of a flex hose as the choke line from the BOP to the Choke Manifold. If this hose is used, a copy of the manufacturer's certification and pressure test chart will be kept on the rig. Attached is an example of a certification and pressure test chart. The manufacturer does not require anchors.

XTO requests a variance to be able to batch drill this well if necessary. In doing so, XTO will set casing and ensure that the well is cemented properly (unless approval is given for offline cementing) and the well is static. With floats holding, no pressure on the csg annulus, and the installation of a 10K TA cap as per Cactus recommendations, XTO will contact the BLM to skid the rig to drill the remaining wells on the pad. Once surface and both intermediate strings are all completed, XTO will begin drilling the production hole on each of the wells.

A variance is requested to **ONLY** test broken pressure seals on the BOP equipment when moving from wellhead to wellhead which is in compliance with API Standard 53. API standard 53 states, that for pad drilling operation, moving from one wellhead to another within 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken. Based on discussions with the BLM on February 27th 2020, we will request permission to **ONLY** retest broken pressure seals if the following conditions are met: 1. After a full BOP test is conducted on the first well on the pad 2. When skidding to drill an intermediate section that does not penetrate into the Wolfcamp.

**6. Proposed Mud Circulation System**

INTERVAL	Hole Size	Mud Type	MW (ppg)	Viscosity (sec/qt)	Fluid Loss (cc)
0' - 786'	24	FW/Native	8.7-9.2	35-40	NC
786' - 2069'	17.5	Brine	10-10.5	30-32	NC
2069' to 4067'	12.25	FW / Cut Brine	9-9.5	30-32	NC
4067' to 21037'	8.5	OBM	9.5-10	50-60	NC - 20

The necessary mud products for weight addition and fluid loss control will be on location at all times.

Spud with fresh water/native mud. Drill out from under 18-5/8" surface casing with brine solution. A 10 ppg -10.5 ppg brine mud will be used while drilling through the salt formation. Use fibrous materials as needed to control seepage and lost circulation. Pump viscous sweeps as needed for hole cleaning. Pump speed will be recorded on a daily drilling report after mudding up. A Pason or Totco will be used to detect changes in loss or gain of mud volume. A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Use available solids controls equipment to help keep mud weight down after mud up. Rig up solids control equipment to operate as a closed loop system.

**7. Auxiliary Well Control and Monitoring Equipment**

- A. A Kelly cock will be in the drill string at all times.
- B. A full opening drill pipe stabbing valve having appropriate connections will be on the rig floor at all times.
- C. H2S monitors will be on location when drilling below the 18.625 casing.

**8. Logging, Coring and Testing Program**

Mud Logger: Mud Logging Unit (2 man) below intermediate casing.

Open hole logging will not be done on this well.

**9. Abnormal Pressures and Temperatures / Potential Hazards**

None Anticipated. BHT of 160 to 180 F is anticipated. No H2S is expected but monitors will be in place to detect any H2S occurrences. Should these circumstances be encountered the operator and drilling contractor are prepared to take all necessary steps to ensure safety of all personnel and environment. Lost circulation could occur but is not expected to be a serious problem in this area and hole seepage will be compensated for by additions of small amounts of LCM in the drilling fluid. The maximum anticipated bottom hole pressure for this well is 4644 psi.

**10. Anticipated Starting Date and Duration of Operations**

Anticipated spud date will be after Remuda 25 State drilling is completed and BLM approval. Move in operations and drilling is expected to take 40 days.





## **XTO Energy**

**EDDY COUNTY, NM (NAD-27 / NME)**

**BEU 30E SKYWALKER**

**100H**

**OH**

**Plan: PERMIT**

## **Standard Survey Report**

**10 November, 2022**



Project: EDDY COUNTY, NM (NAD-27 / NME)  
Site: BEU 30E SKYWALKER  
Well: 100H  
Wellbore: OH  
Design: PERMIT

WELL DETAILS: 100H


Rig Name:		TBD	
RKB = 33' @ 3480.00usft (TBD)		3447.00	
Ground Level:	Easting	Latitude	Longitude
0.00	0.00	571408.60	650208.10
		32.5699633	-103.8457451

SECTION DETAILS



Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	2000.00	0.00	0.00	2000.00	0.00	0.00	0.00	0.00	0.00	
3	3426.21	28.52	339.36	3368.02	325.41	-122.60	2.00	339.36	-120.89	
4	9617.87	28.52	339.36	8808.11	3092.27	-1165.01	0.00	0.00	-1148.80	
5	10618.35	90.55	89.70	9402.00	3401.20	-596.70	10.00	107.79	-578.88	BEU 30E #100H: FTP/LP
6	20987.67	90.55	89.70	9302.46	3454.84	9772.00	0.00	0.00	9789.96	BEU 30E #100H: LTP
7	21037.67	90.55	89.70	9301.98	3455.10	9822.00	0.00	0.00	9839.96	BEU 30E #100H: PBHL

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
BEU 30E #100H: SHL	0.00	0.00	0.00	571408.60	650208.10	32.5699633	-103.8457451
BEU 30E #100H: PBHL	9301.98	3455.10	9822.00	574863.70	660030.10	32.5793327	-103.8138083
BEU 30E #100H: LTP	9302.46	3454.90	9772.00	574863.50	659980.10	32.5793328	-103.8139707
BEU 30E #100H: FTP/LP	9402.00	3401.20	-596.70	574809.80	649611.40	32.5793198	-103.8476315



FORMATION TOP DETAILS	
TVDPath	Formation
686.00	Rustler
950.00	Salado
1969.00	Base Salt
2736.00	Capitan
4017.00	Delaware
5785.00	Brushy Canyon
7139.00	Basal Brushy Canyon
7371.00	Bone Spring Lime
7600.00	Avalon Shale Upper SH
8080.00	Avalon Shale Lower SH
8290.00	1st Bone Spring Lime
8577.00	1st Bone Spring Sand
8811.00	2nd Bone Spring Lime
9142.00	2nd Bone Spring Sand
9382.00	Target Top
9402.00	Landing Point



PROJECT DETAILS: EDDY COUNTY, NM (NAD-27 / NME)  
Geodetic System: US State Plane 1927 (Exact solution)  
Datum: NAD 1927 (NADCON CONUS)  
Ellipsoid: Clarke 1866  
Zone: New Mexico East 3001  
System Datum: Mean Sea Level

Plan: PERMIT (100H/OH)

Created By: Matthew May Date: 10:20, November 10 2022

\*\*\*Note: this electronic file is provided for information purposes only. Prototype Well Planning LLC, its employees, and agents make no guarantee or warranty, expressed or implied, as to the accuracy of this electronic file. The data included here and may be subject to error, while corruption, change, alteration, or update without any notice to the user. Prototype Well Planning LLC, its employees, and its agents assume no responsibility, expressed or implied, for any damages incurred either directly or indirectly by the use of this electronic file. The users agree to the above specified terms of this electronic file and agrees to verify the data enclosed to ascertain its accuracy for their intended use. If these conditions are unacceptable, user shall discard this data.\*\*\*

Vertical Section at 89.70° (1500 usft/in)

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office  
☐ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-015-	<sup>2</sup> Pool Code	<sup>3</sup> Pool Name
<sup>4</sup> Property Code	<sup>5</sup> Property Name BIG EDDY UNIT 30E SKYWALKER	<sup>6</sup> Well Number 100H
<sup>7</sup> OGRID No. 373075	<sup>8</sup> Operator Name XTO PERMIAN OPERATING, LLC.	<sup>9</sup> Elevation 3,447'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
L	14	20 S	31 E		1,465	SOUTH	480	WEST	EDDY

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	13	20 S	31 E		440	NORTH	50	EAST	EDDY

<sup>12</sup> Dedicated Acres	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
-------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<sup>17</sup> OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature \_\_\_\_\_ Date \_\_\_\_\_

Printed Name \_\_\_\_\_

E-mail Address \_\_\_\_\_

<sup>18</sup> SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

11-10-2022

Date of Survey

Signature and Seal of  
Professional Surveyor:

MARK DILLON HARP 23786

Certificate Number

AI

2017081252





## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

<b>Project</b>	EDDY COUNTY, NM (NAD-27 / NME)		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	New Mexico East 3001		

<b>Site</b>	BEU 30E SKYWALKER		
<b>Site Position:</b>		<b>Northing:</b>	571,481.50 usft
<b>From:</b>	Map	<b>Easting:</b>	649,992.30 usft
<b>Position Uncertainty:</b>	0.00 usft	<b>Slot Radius:</b>	13-3/16 "
		<b>Latitude:</b>	32.5701664
		<b>Longitude:</b>	-103.8464444
		<b>Grid Convergence:</b>	0.26 °

<b>Well</b>	100H		
<b>Well Position</b>	<b>+N/-S</b>	0.00 usft	<b>Northing:</b> 571,408.60 usft
	<b>+E/-W</b>	0.00 usft	<b>Easting:</b> 650,208.10 usft
<b>Position Uncertainty</b>	0.00 usft	<b>Wellhead Elevation:</b>	0.00 usft
		<b>Latitude:</b>	32.5699633
		<b>Longitude:</b>	-103.8457450
		<b>Ground Level:</b>	3,447.00 usft

<b>Wellbore</b>	OH		
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>
	IGRF2020	11/10/22	6.54
			<b>Dip Angle (°)</b> 60.13
			<b>Field Strength (nT)</b> 47,523

<b>Design</b>	PERMIT		
<b>Audit Notes:</b>			
<b>Version:</b>	<b>Phase:</b>	PROTOTYPE	<b>Tie On Depth:</b> 0.00
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>
	0.00	0.00	0.00
			<b>Direction (°)</b> 89.70

<b>Survey Tool Program</b>	<b>Date</b>	11/10/22		
<b>From (usft)</b>	<b>To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>
0.00	21,037.67	PERMIT (OH)	MWD	MWD - Standard

<b>Planned Survey</b>									
<b>Measured Depth (usft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Vertical Section (usft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>BEU 30E #100H: SHL</b>									
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
686.00	0.00	0.00	686.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>Rustler</b>									



## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
950.00	0.00	0.00	950.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>Salado</b>									
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,969.00	0.00	0.00	1,969.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>Base Salt</b>									
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00
2,100.00	2.00	339.36	2,099.98	1.63	-0.62	-0.61	2.00	2.00	0.00
2,200.00	4.00	339.36	2,199.84	6.53	-2.46	-2.43	2.00	2.00	0.00
2,300.00	6.00	339.36	2,299.45	14.69	-5.53	-5.46	2.00	2.00	0.00
2,400.00	8.00	339.36	2,398.70	26.09	-9.83	-9.69	2.00	2.00	0.00
2,500.00	10.00	339.36	2,497.47	40.73	-15.34	-15.13	2.00	2.00	0.00
2,600.00	12.00	339.36	2,595.62	58.58	-22.07	-21.76	2.00	2.00	0.00
2,700.00	14.00	339.36	2,693.06	79.63	-30.00	-29.58	2.00	2.00	0.00
2,744.35	14.89	339.36	2,736.00	89.98	-33.90	-33.43	2.00	2.00	0.00
<b>Capitan</b>									
2,800.00	16.00	339.36	2,789.64	103.85	-39.13	-38.58	2.00	2.00	0.00
2,900.00	18.00	339.36	2,885.27	131.21	-49.43	-48.75	2.00	2.00	0.00
3,000.00	20.00	339.36	2,979.82	161.67	-60.91	-60.06	2.00	2.00	0.00
3,100.00	22.00	339.36	3,073.17	195.21	-73.54	-72.52	2.00	2.00	0.00
3,200.00	24.00	339.36	3,165.21	231.77	-87.32	-86.10	2.00	2.00	0.00
3,300.00	26.00	339.36	3,255.84	271.32	-102.22	-100.80	2.00	2.00	0.00
3,400.00	28.00	339.36	3,344.94	313.80	-118.22	-116.58	2.00	2.00	0.00
3,426.21	28.52	339.36	3,368.02	325.41	-122.60	-120.89	2.00	2.00	0.00
3,500.00	28.52	339.36	3,432.86	358.39	-135.02	-133.14	0.00	0.00	0.00
3,600.00	28.52	339.36	3,520.72	403.07	-151.86	-149.74	0.00	0.00	0.00
3,700.00	28.52	339.36	3,608.58	447.76	-168.69	-166.35	0.00	0.00	0.00
3,800.00	28.52	339.36	3,696.44	492.45	-185.53	-182.95	0.00	0.00	0.00
3,900.00	28.52	339.36	3,784.30	537.13	-202.36	-199.55	0.00	0.00	0.00
4,000.00	28.52	339.36	3,872.16	581.82	-219.20	-216.15	0.00	0.00	0.00
4,100.00	28.52	339.36	3,960.02	626.51	-236.04	-232.75	0.00	0.00	0.00
4,164.85	28.52	339.36	4,017.00	655.49	-246.95	-243.52	0.00	0.00	0.00
<b>Delaware</b>									



## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,200.00	28.52	339.36	4,047.89	671.20	-252.87	-249.35	0.00	0.00	0.00
4,300.00	28.52	339.36	4,135.75	715.88	-269.71	-265.95	0.00	0.00	0.00
4,400.00	28.52	339.36	4,223.61	760.57	-286.54	-282.56	0.00	0.00	0.00
4,500.00	28.52	339.36	4,311.47	805.26	-303.38	-299.16	0.00	0.00	0.00
4,600.00	28.52	339.36	4,399.33	849.94	-320.21	-315.76	0.00	0.00	0.00
4,700.00	28.52	339.36	4,487.19	894.63	-337.05	-332.36	0.00	0.00	0.00
4,800.00	28.52	339.36	4,575.06	939.32	-353.89	-348.96	0.00	0.00	0.00
4,900.00	28.52	339.36	4,662.92	984.00	-370.72	-365.56	0.00	0.00	0.00
5,000.00	28.52	339.36	4,750.78	1,028.69	-387.56	-382.17	0.00	0.00	0.00
5,100.00	28.52	339.36	4,838.64	1,073.38	-404.39	-398.77	0.00	0.00	0.00
5,200.00	28.52	339.36	4,926.50	1,118.06	-421.23	-415.37	0.00	0.00	0.00
5,300.00	28.52	339.36	5,014.36	1,162.75	-438.06	-431.97	0.00	0.00	0.00
5,400.00	28.52	339.36	5,102.22	1,207.44	-454.90	-448.57	0.00	0.00	0.00
5,500.00	28.52	339.36	5,190.09	1,252.12	-471.73	-465.17	0.00	0.00	0.00
5,600.00	28.52	339.36	5,277.95	1,296.81	-488.57	-481.77	0.00	0.00	0.00
5,700.00	28.52	339.36	5,365.81	1,341.50	-505.41	-498.38	0.00	0.00	0.00
5,800.00	28.52	339.36	5,453.67	1,386.19	-522.24	-514.98	0.00	0.00	0.00
5,900.00	28.52	339.36	5,541.53	1,430.87	-539.08	-531.58	0.00	0.00	0.00
6,000.00	28.52	339.36	5,629.39	1,475.56	-555.91	-548.18	0.00	0.00	0.00
6,100.00	28.52	339.36	5,717.25	1,520.25	-572.75	-564.78	0.00	0.00	0.00
6,177.10	28.52	339.36	5,785.00	1,554.70	-585.73	-577.58	0.00	0.00	0.00
<b>Brushy Canyon</b>									
6,200.00	28.52	339.36	5,805.12	1,564.93	-589.58	-581.38	0.00	0.00	0.00
6,300.00	28.52	339.36	5,892.98	1,609.62	-606.42	-597.98	0.00	0.00	0.00
6,400.00	28.52	339.36	5,980.84	1,654.31	-623.26	-614.59	0.00	0.00	0.00
6,500.00	28.52	339.36	6,068.70	1,698.99	-640.09	-631.19	0.00	0.00	0.00
6,600.00	28.52	339.36	6,156.56	1,743.68	-656.93	-647.79	0.00	0.00	0.00
6,700.00	28.52	339.36	6,244.42	1,788.37	-673.76	-664.39	0.00	0.00	0.00
6,800.00	28.52	339.36	6,332.29	1,833.05	-690.60	-680.99	0.00	0.00	0.00
6,900.00	28.52	339.36	6,420.15	1,877.74	-707.43	-697.59	0.00	0.00	0.00
7,000.00	28.52	339.36	6,508.01	1,922.43	-724.27	-714.19	0.00	0.00	0.00
7,100.00	28.52	339.36	6,595.87	1,967.11	-741.11	-730.80	0.00	0.00	0.00
7,200.00	28.52	339.36	6,683.73	2,011.80	-757.94	-747.40	0.00	0.00	0.00
7,300.00	28.52	339.36	6,771.59	2,056.49	-774.78	-764.00	0.00	0.00	0.00
7,400.00	28.52	339.36	6,859.45	2,101.17	-791.61	-780.60	0.00	0.00	0.00
7,500.00	28.52	339.36	6,947.32	2,145.86	-808.45	-797.20	0.00	0.00	0.00
7,600.00	28.52	339.36	7,035.18	2,190.55	-825.28	-813.80	0.00	0.00	0.00
7,700.00	28.52	339.36	7,123.04	2,235.24	-842.12	-830.40	0.00	0.00	0.00
7,718.17	28.52	339.36	7,139.00	2,243.35	-845.18	-833.42	0.00	0.00	0.00
<b>Basal Brushy Canyon</b>									
7,800.00	28.52	339.36	7,210.90	2,279.92	-858.96	-847.01	0.00	0.00	0.00
7,900.00	28.52	339.36	7,298.76	2,324.61	-875.79	-863.61	0.00	0.00	0.00
7,982.22	28.52	339.36	7,371.00	2,361.35	-889.63	-877.26	0.00	0.00	0.00
<b>Bone Spring Lime</b>									



## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,000.00	28.52	339.36	7,386.62	2,369.30	-892.63	-880.21	0.00	0.00	0.00
8,100.00	28.52	339.36	7,474.48	2,413.98	-909.46	-896.81	0.00	0.00	0.00
8,200.00	28.52	339.36	7,562.35	2,458.67	-926.30	-913.41	0.00	0.00	0.00
8,242.86	28.52	339.36	7,600.00	2,477.82	-933.51	-920.53	0.00	0.00	0.00
<b>Avalon Shale Upper SH</b>									
8,300.00	28.52	339.36	7,650.21	2,503.36	-943.13	-930.01	0.00	0.00	0.00
8,400.00	28.52	339.36	7,738.07	2,548.04	-959.97	-946.61	0.00	0.00	0.00
8,500.00	28.52	339.36	7,825.93	2,592.73	-976.81	-963.22	0.00	0.00	0.00
8,600.00	28.52	339.36	7,913.79	2,637.42	-993.64	-979.82	0.00	0.00	0.00
8,700.00	28.52	339.36	8,001.65	2,682.10	-1,010.48	-996.42	0.00	0.00	0.00
8,789.17	28.52	339.36	8,080.00	2,721.95	-1,025.49	-1,011.22	0.00	0.00	0.00
<b>Avalon Shale Lower SH</b>									
8,800.00	28.52	339.36	8,089.52	2,726.79	-1,027.31	-1,013.02	0.00	0.00	0.00
8,900.00	28.52	339.36	8,177.38	2,771.48	-1,044.15	-1,029.62	0.00	0.00	0.00
9,000.00	28.52	339.36	8,265.24	2,816.16	-1,060.98	-1,046.22	0.00	0.00	0.00
9,028.18	28.52	339.36	8,290.00	2,828.76	-1,065.73	-1,050.90	0.00	0.00	0.00
<b>1st Bone Spring Lime</b>									
9,100.00	28.52	339.36	8,353.10	2,860.85	-1,077.82	-1,062.82	0.00	0.00	0.00
9,200.00	28.52	339.36	8,440.96	2,905.54	-1,094.65	-1,079.43	0.00	0.00	0.00
9,300.00	28.52	339.36	8,528.82	2,950.23	-1,111.49	-1,096.03	0.00	0.00	0.00
9,354.83	28.52	339.36	8,577.00	2,974.73	-1,120.72	-1,105.13	0.00	0.00	0.00
<b>1st Bone Spring Sand</b>									
9,400.00	28.52	339.36	8,616.68	2,994.91	-1,128.33	-1,112.63	0.00	0.00	0.00
9,500.00	28.52	339.36	8,704.55	3,039.60	-1,145.16	-1,129.23	0.00	0.00	0.00
9,600.00	28.52	339.36	8,792.41	3,084.29	-1,162.00	-1,145.83	0.00	0.00	0.00
9,617.87	28.52	339.36	8,808.11	3,092.27	-1,165.01	-1,148.80	0.00	0.00	0.00
9,621.16	28.43	340.01	8,811.00	3,093.74	-1,165.55	-1,149.34	10.00	-3.01	20.00
<b>2nd Bone Spring Lime</b>									
9,650.00	27.70	345.95	8,836.45	3,106.70	-1,169.52	-1,153.24	10.00	-2.52	20.58
9,700.00	27.07	356.75	8,880.88	3,129.34	-1,172.99	-1,156.59	10.00	-1.26	21.60
9,750.00	27.29	7.70	8,925.39	3,152.07	-1,172.10	-1,155.58	10.00	0.44	21.90
9,800.00	28.33	18.19	8,969.64	3,174.72	-1,166.86	-1,150.22	10.00	2.09	20.99
9,850.00	30.12	27.77	9,013.30	3,197.10	-1,157.31	-1,140.55	10.00	3.57	19.16
9,900.00	32.52	36.22	9,056.03	3,219.06	-1,143.52	-1,126.64	10.00	4.80	16.90
9,950.00	35.41	43.53	9,097.51	3,240.42	-1,125.59	-1,108.60	10.00	5.79	14.62
10,000.00	38.68	49.81	9,137.43	3,261.02	-1,103.66	-1,086.57	10.00	6.54	12.56
10,005.87	39.09	50.49	9,142.00	3,263.38	-1,100.83	-1,083.73	10.00	6.89	11.54
<b>2nd Bone Spring Sand</b>									
10,050.00	42.25	55.22	9,175.47	3,280.70	-1,077.90	-1,060.71	10.00	7.16	10.73
10,100.00	46.03	59.92	9,211.36	3,299.32	-1,048.51	-1,031.22	10.00	7.57	9.40
10,150.00	49.98	64.04	9,244.82	3,316.73	-1,015.71	-998.33	10.00	7.91	8.25
10,200.00	54.06	67.71	9,275.58	3,332.80	-979.74	-962.28	10.00	8.17	7.33
10,250.00	58.25	71.01	9,303.43	3,347.41	-940.89	-923.35	10.00	8.37	6.60
10,300.00	62.51	74.02	9,328.14	3,360.44	-899.44	-881.83	10.00	8.52	6.02





## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,350.00	66.83	76.80	9,349.53	3,371.80	-855.72	-838.05	10.00	8.64	5.57
10,400.00	71.20	79.41	9,367.44	3,381.41	-810.05	-792.33	10.00	8.73	5.22
10,450.00	75.60	81.89	9,381.72	3,389.17	-762.78	-745.03	10.00	8.80	4.95
10,451.12	75.70	81.94	9,382.00	3,389.33	-761.71	-743.96	10.00	8.83	4.84
<b>Target Top</b>									
10,500.00	80.02	84.27	9,392.28	3,395.05	-714.28	-696.49	10.00	8.85	4.76
10,550.00	84.46	86.59	9,399.03	3,399.00	-664.91	-647.11	10.00	8.88	4.63
10,600.00	88.92	88.87	9,401.91	3,400.97	-615.05	-597.23	10.00	8.90	4.56
10,618.35	90.55	89.70	9,402.00	3,401.20	-596.70	-578.88	10.00	8.91	4.55
<b>Landing Point - BEU 30E #100H: FTP/LP</b>									
10,700.00	90.55	89.70	9,401.22	3,401.62	-515.06	-497.24	0.00	0.00	0.00
10,800.00	90.55	89.70	9,400.26	3,402.14	-415.06	-397.24	0.00	0.00	0.00
10,900.00	90.55	89.70	9,399.30	3,402.66	-315.07	-297.25	0.00	0.00	0.00
11,000.00	90.55	89.70	9,398.34	3,403.17	-215.07	-197.25	0.00	0.00	0.00
11,100.00	90.55	89.70	9,397.38	3,403.69	-115.08	-97.26	0.00	0.00	0.00
11,200.00	90.55	89.70	9,396.42	3,404.21	-15.09	2.74	0.00	0.00	0.00
11,300.00	90.55	89.70	9,395.46	3,404.73	84.91	102.73	0.00	0.00	0.00
11,400.00	90.55	89.70	9,394.50	3,405.24	184.90	202.73	0.00	0.00	0.00
11,500.00	90.55	89.70	9,393.54	3,405.76	284.90	302.72	0.00	0.00	0.00
11,600.00	90.55	89.70	9,392.58	3,406.28	384.89	402.72	0.00	0.00	0.00
11,700.00	90.55	89.70	9,391.62	3,406.80	484.88	502.71	0.00	0.00	0.00
11,800.00	90.55	89.70	9,390.66	3,407.31	584.88	602.71	0.00	0.00	0.00
11,900.00	90.55	89.70	9,389.70	3,407.83	684.87	702.71	0.00	0.00	0.00
12,000.00	90.55	89.70	9,388.74	3,408.35	784.87	802.70	0.00	0.00	0.00
12,100.00	90.55	89.70	9,387.78	3,408.86	884.86	902.70	0.00	0.00	0.00
12,200.00	90.55	89.70	9,386.82	3,409.38	984.85	1,002.69	0.00	0.00	0.00
12,300.00	90.55	89.70	9,385.86	3,409.90	1,084.85	1,102.69	0.00	0.00	0.00
12,400.00	90.55	89.70	9,384.90	3,410.42	1,184.84	1,202.68	0.00	0.00	0.00
12,500.00	90.55	89.70	9,383.94	3,410.93	1,284.84	1,302.68	0.00	0.00	0.00
12,600.00	90.55	89.70	9,382.98	3,411.45	1,384.83	1,402.67	0.00	0.00	0.00
12,700.00	90.55	89.70	9,382.02	3,411.97	1,484.82	1,502.67	0.00	0.00	0.00
12,800.00	90.55	89.70	9,381.06	3,412.49	1,584.82	1,602.66	0.00	0.00	0.00
12,900.00	90.55	89.70	9,380.10	3,413.00	1,684.81	1,702.66	0.00	0.00	0.00
13,000.00	90.55	89.70	9,379.14	3,413.52	1,784.81	1,802.65	0.00	0.00	0.00
13,100.00	90.55	89.70	9,378.18	3,414.04	1,884.80	1,902.65	0.00	0.00	0.00
13,200.00	90.55	89.70	9,377.22	3,414.56	1,984.79	2,002.65	0.00	0.00	0.00
13,300.00	90.55	89.70	9,376.26	3,415.07	2,084.79	2,102.64	0.00	0.00	0.00
13,400.00	90.55	89.70	9,375.30	3,415.59	2,184.78	2,202.64	0.00	0.00	0.00
13,500.00	90.55	89.70	9,374.34	3,416.11	2,284.78	2,302.63	0.00	0.00	0.00
13,600.00	90.55	89.70	9,373.38	3,416.62	2,384.77	2,402.63	0.00	0.00	0.00
13,700.00	90.55	89.70	9,372.42	3,417.14	2,484.76	2,502.62	0.00	0.00	0.00
13,800.00	90.55	89.70	9,371.46	3,417.66	2,584.76	2,602.62	0.00	0.00	0.00
13,900.00	90.55	89.70	9,370.50	3,418.18	2,684.75	2,702.61	0.00	0.00	0.00
14,000.00	90.55	89.70	9,369.54	3,418.69	2,784.75	2,802.61	0.00	0.00	0.00





## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
14,100.00	90.55	89.70	9,368.58	3,419.21	2,884.74	2,902.60	0.00	0.00	0.00
14,200.00	90.55	89.70	9,367.62	3,419.73	2,984.73	3,002.60	0.00	0.00	0.00
14,300.00	90.55	89.70	9,366.66	3,420.25	3,084.73	3,102.60	0.00	0.00	0.00
14,400.00	90.55	89.70	9,365.70	3,420.76	3,184.72	3,202.59	0.00	0.00	0.00
14,500.00	90.55	89.70	9,364.74	3,421.28	3,284.72	3,302.59	0.00	0.00	0.00
14,600.00	90.55	89.70	9,363.78	3,421.80	3,384.71	3,402.58	0.00	0.00	0.00
14,700.00	90.55	89.70	9,362.82	3,422.31	3,484.71	3,502.58	0.00	0.00	0.00
14,800.00	90.55	89.70	9,361.86	3,422.83	3,584.70	3,602.57	0.00	0.00	0.00
14,900.00	90.55	89.70	9,360.90	3,423.35	3,684.69	3,702.57	0.00	0.00	0.00
15,000.00	90.55	89.70	9,359.94	3,423.87	3,784.69	3,802.56	0.00	0.00	0.00
15,100.00	90.55	89.70	9,358.98	3,424.38	3,884.68	3,902.56	0.00	0.00	0.00
15,200.00	90.55	89.70	9,358.02	3,424.90	3,984.68	4,002.55	0.00	0.00	0.00
15,300.00	90.55	89.70	9,357.06	3,425.42	4,084.67	4,102.55	0.00	0.00	0.00
15,400.00	90.55	89.70	9,356.10	3,425.94	4,184.66	4,202.54	0.00	0.00	0.00
15,500.00	90.55	89.70	9,355.14	3,426.45	4,284.66	4,302.54	0.00	0.00	0.00
15,600.00	90.55	89.70	9,354.18	3,426.97	4,384.65	4,402.54	0.00	0.00	0.00
15,700.00	90.55	89.70	9,353.22	3,427.49	4,484.65	4,502.53	0.00	0.00	0.00
15,800.00	90.55	89.70	9,352.26	3,428.01	4,584.64	4,602.53	0.00	0.00	0.00
15,900.00	90.55	89.70	9,351.30	3,428.52	4,684.63	4,702.52	0.00	0.00	0.00
16,000.00	90.55	89.70	9,350.34	3,429.04	4,784.63	4,802.52	0.00	0.00	0.00
16,100.00	90.55	89.70	9,349.38	3,429.56	4,884.62	4,902.51	0.00	0.00	0.00
16,200.00	90.55	89.70	9,348.42	3,430.07	4,984.62	5,002.51	0.00	0.00	0.00
16,300.00	90.55	89.70	9,347.46	3,430.59	5,084.61	5,102.50	0.00	0.00	0.00
16,400.00	90.55	89.70	9,346.50	3,431.11	5,184.60	5,202.50	0.00	0.00	0.00
16,500.00	90.55	89.70	9,345.54	3,431.63	5,284.60	5,302.49	0.00	0.00	0.00
16,600.00	90.55	89.70	9,344.58	3,432.14	5,384.59	5,402.49	0.00	0.00	0.00
16,700.00	90.55	89.70	9,343.62	3,432.66	5,484.59	5,502.48	0.00	0.00	0.00
16,800.00	90.55	89.70	9,342.66	3,433.18	5,584.58	5,602.48	0.00	0.00	0.00
16,900.00	90.55	89.70	9,341.70	3,433.70	5,684.57	5,702.48	0.00	0.00	0.00
17,000.00	90.55	89.70	9,340.74	3,434.21	5,784.57	5,802.47	0.00	0.00	0.00
17,100.00	90.55	89.70	9,339.78	3,434.73	5,884.56	5,902.47	0.00	0.00	0.00
17,200.00	90.55	89.70	9,338.82	3,435.25	5,984.56	6,002.46	0.00	0.00	0.00
17,300.00	90.55	89.70	9,337.86	3,435.76	6,084.55	6,102.46	0.00	0.00	0.00
17,400.00	90.55	89.70	9,336.90	3,436.28	6,184.54	6,202.45	0.00	0.00	0.00
17,500.00	90.55	89.70	9,335.94	3,436.80	6,284.54	6,302.45	0.00	0.00	0.00
17,600.00	90.55	89.70	9,334.98	3,437.32	6,384.53	6,402.44	0.00	0.00	0.00
17,700.00	90.55	89.70	9,334.02	3,437.83	6,484.53	6,502.44	0.00	0.00	0.00
17,800.00	90.55	89.70	9,333.06	3,438.35	6,584.52	6,602.43	0.00	0.00	0.00
17,900.00	90.55	89.70	9,332.10	3,438.87	6,684.52	6,702.43	0.00	0.00	0.00
18,000.00	90.55	89.70	9,331.14	3,439.39	6,784.51	6,802.42	0.00	0.00	0.00
18,100.00	90.55	89.70	9,330.18	3,439.90	6,884.50	6,902.42	0.00	0.00	0.00
18,200.00	90.55	89.70	9,329.22	3,440.42	6,984.50	7,002.42	0.00	0.00	0.00
18,300.00	90.55	89.70	9,328.26	3,440.94	7,084.49	7,102.41	0.00	0.00	0.00



## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
18,400.00	90.55	89.70	9,327.30	3,441.46	7,184.49	7,202.41	0.00	0.00	0.00
18,500.00	90.55	89.70	9,326.34	3,441.97	7,284.48	7,302.40	0.00	0.00	0.00
18,600.00	90.55	89.70	9,325.38	3,442.49	7,384.47	7,402.40	0.00	0.00	0.00
18,700.00	90.55	89.70	9,324.42	3,443.01	7,484.47	7,502.39	0.00	0.00	0.00
18,800.00	90.55	89.70	9,323.46	3,443.52	7,584.46	7,602.39	0.00	0.00	0.00
18,900.00	90.55	89.70	9,322.50	3,444.04	7,684.46	7,702.38	0.00	0.00	0.00
19,000.00	90.55	89.70	9,321.54	3,444.56	7,784.45	7,802.38	0.00	0.00	0.00
19,100.00	90.55	89.70	9,320.58	3,445.08	7,884.44	7,902.37	0.00	0.00	0.00
19,200.00	90.55	89.70	9,319.62	3,445.59	7,984.44	8,002.37	0.00	0.00	0.00
19,300.00	90.55	89.70	9,318.66	3,446.11	8,084.43	8,102.36	0.00	0.00	0.00
19,400.00	90.55	89.70	9,317.70	3,446.63	8,184.43	8,202.36	0.00	0.00	0.00
19,500.00	90.55	89.70	9,316.74	3,447.15	8,284.42	8,302.36	0.00	0.00	0.00
19,600.00	90.55	89.70	9,315.78	3,447.66	8,384.41	8,402.35	0.00	0.00	0.00
19,700.00	90.55	89.70	9,314.82	3,448.18	8,484.41	8,502.35	0.00	0.00	0.00
19,800.00	90.55	89.70	9,313.86	3,448.70	8,584.40	8,602.34	0.00	0.00	0.00
19,900.00	90.55	89.70	9,312.90	3,449.21	8,684.40	8,702.34	0.00	0.00	0.00
20,000.00	90.55	89.70	9,311.94	3,449.73	8,784.39	8,802.33	0.00	0.00	0.00
20,100.00	90.55	89.70	9,310.98	3,450.25	8,884.38	8,902.33	0.00	0.00	0.00
20,200.00	90.55	89.70	9,310.02	3,450.77	8,984.38	9,002.32	0.00	0.00	0.00
20,300.00	90.55	89.70	9,309.06	3,451.28	9,084.37	9,102.32	0.00	0.00	0.00
20,400.00	90.55	89.70	9,308.10	3,451.80	9,184.37	9,202.31	0.00	0.00	0.00
20,500.00	90.55	89.70	9,307.14	3,452.32	9,284.36	9,302.31	0.00	0.00	0.00
20,600.00	90.55	89.70	9,306.18	3,452.84	9,384.35	9,402.30	0.00	0.00	0.00
20,700.00	90.55	89.70	9,305.22	3,453.35	9,484.35	9,502.30	0.00	0.00	0.00
20,800.00	90.55	89.70	9,304.26	3,453.87	9,584.34	9,602.30	0.00	0.00	0.00
20,900.00	90.55	89.70	9,303.30	3,454.39	9,684.34	9,702.29	0.00	0.00	0.00
20,987.67	90.55	89.70	9,302.46	3,454.84	9,772.00	9,789.96	0.00	0.00	0.00
<b>BEU 30E #100H: LTP</b>									
21,000.00	90.55	89.70	9,302.35	3,454.91	9,784.33	9,802.29	0.00	0.00	0.00
21,037.67	90.55	89.70	9,301.98	3,455.10	9,822.00	9,839.96	0.00	0.00	0.00
<b>BEU 30E #100H: PBHL</b>									



## Survey Report

<b>Company:</b>	XTO Energy	<b>Local Co-ordinate Reference:</b>	Well 100H
<b>Project:</b>	EDDY COUNTY, NM (NAD-27 / NME)	<b>TVD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Site:</b>	BEU 30E SKYWALKER	<b>MD Reference:</b>	RKB = 33' @ 3480.00usft (TBD)
<b>Well:</b>	100H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	OH	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	PERMIT	<b>Database:</b>	EDM 5000.1.13 Single User Db

## Design Targets

Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
BEU 30E #100H: SHL - plan hits target center - Point	0.00	0.00	0.00	0.00	0.00	571,408.60	650,208.10	32.5699633	-103.8457450
BEU 30E #100H: PBH - plan hits target center - Point	0.00	0.01	9,301.98	3,455.10	9,822.00	574,863.70	660,030.10	32.5793327	-103.8138083
BEU 30E #100H: LTP - plan misses target center by 0.06usft at 20987.67usft MD (9302.46 TVD, 3454.84 N, 9772.00 E) - Point	0.00	0.00	9,302.46	3,454.90	9,772.00	574,863.50	659,980.10	32.5793328	-103.8139707
BEU 30E #100H: FTP - plan hits target center - Point	0.00	0.00	9,402.00	3,401.20	-596.70	574,809.80	649,611.40	32.5793198	-103.8476315


## Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
686.00	686.00	Rustler			
950.00	950.00	Salado			
1,969.00	1,969.00	Base Salt			
2,744.35	2,736.00	Capitan			
4,164.85	4,017.00	Delaware			
6,177.10	5,785.00	Brushy Canyon			
7,718.17	7,139.00	Basal Brushy Canyon			
7,982.22	7,371.00	Bone Spring Lime			
8,242.86	7,600.00	Avalon Shale Upper SH			
8,789.17	8,080.00	Avalon Shale Lower SH			
9,028.18	8,290.00	1st Bone Spring Lime			
9,354.83	8,577.00	1st Bone Spring Sand			
9,621.16	8,811.00	2nd Bone Spring Lime			
10,005.87	9,142.00	2nd Bone Spring Sand			
10,451.12	9,382.00	Target Top			
10,618.35	9,402.00	Landing Point			

Checked By: \_\_\_\_\_ Approved By: \_\_\_\_\_ Date: \_\_\_\_\_



GE Oil &amp; Gas



ALL DIMENSIONS ARE APPROXIMATE

This drawing is the property of GE Oil & Gas Pressure Control LP and is considered confidential. Unless otherwise approved in writing, neither it nor its contents may be used, copied, transmitted or reproduced except for the sole purpose of GE Oil & Gas Pressure Control LP.

XTO ENERGY, INC.

13-3/8" x 9-5/8" x 5-1/2" 10M RSH-2 Wellhead  
Assembly, With T-EBS-F Tubing Head

DRAWN

VJK

16FEB17

APPRV

KN

16FEB17

FOR REFERENCE ONLY

DRAWING NO.

10012842

**Subject:** Request for a Variance Allowing break Testing of the Blowout Preventer Equipment (BOPE)

XTO Energy requests a variance to ONLY test broken pressure seals on the BOPE and function test BOP when skidding a drilling rig between multiple wells on a pad.

**Background**

Onshore Oil and Gas Order (OOGO) No. 2, Drilling Operations, Sections III.A.2.i.iv.B states that the BOP test must be performed whenever any seal subject to test pressure is broken. The current interpretation of the Bureau of Land Management (BLM) requires a complete BOP test and not just a test of the affected component. OOGO No. 2, Section I.D.2 states, "Some situation may exist either on a well-by-well basis or field-wide basis whereby it is commonly accepted practice to vary a particular minimum standard(s) established in this order. This situation can be resolved by requesting a variance...". XTO Energy feels the break testing the BOPE is such a situation. Therefore, as per OOGO No. 2, Section IV., XTO Energy submits this request for the variance.

**Supporting Documentation**

OOGO No. 2 became effective on December 19, 1988 and has remained the standard for regulating BLM onshore drilling operations for over 30 years. During this time there have been significant changes in drilling technology. BLM continues to use the variance request process to allow for the use of modern technology and acceptable engineering practices that have arisen since OOGO No. 2 was originally released. The XTO Energy drilling rig fleet has many modern upgrades that allow the intact BOP stack to be moved between well slots on a multi-well pad, as well as, wellhead designs that incorporate quick connects facilitating release of the BOP from the wellhead without breaking any BOP stack components apart. These technologies have been used extensively offshore, and other regulators, API, and many operators around the world have endorsed break testing as safe and reliable.



Figure 1: Winch System attached to BOP Stack





Figure 2: BOP Winch System

American Petroleum Institute (API) standards, specification and recommended practices are considered the industry standard and are consistently utilized and referenced by the industry. OOGO No. 2 recognizes API recommended Practices (RP) 53 in its original development. API Standard 53, *Well Control Equipment Systems for Drilling Wells* (Fifth Edition, December 2018, Annex C, Table C.4) recognizes break testing as an acceptable practice. Specifically, API Standard 53, Section 5.3.7.1 states “A pressure test of the pressure containing component shall be performed following the disconnection or repair, limited to the affected component.” See Table C.4 below for reference.

62

API STANDARD 53

Table C.4—Initial Pressure Testing, Surface BOP Stacks

Component to be Pressure Tested	Pressure Test—Low Pressure <sup>ac</sup> psig (MPa)	Pressure Test—High Pressure <sup>ac</sup>	
		Change Out of Component, Elastomer, or Ring Gasket	No Change Out of Component, Elastomer, or Ring Gasket
Annular preventer <sup>b</sup>	250 to 350 (1.72 to 2.41)	RWP of annular preventer	MASP or 70% annular RWP, whichever is lower.
Fixed pipe, variable bore, blind, and BSR preventers <sup>bd</sup>	250 to 350 (1.72 to 2.41)	RWP of ram preventer or wellhead system, whichever is lower	ITP
Choke and kill line and BOP side outlet valves below ram preventers (both sides)	250 to 350 (1.72 to 2.41)	RWP of side outlet valve or wellhead system, whichever is lower	ITP
Choke manifold—upstream of chokes <sup>e</sup>	250 to 350 (1.72 to 2.41)	RWP of ram preventers or wellhead system, whichever is lower	ITP
Choke manifold—downstream of chokes <sup>e</sup>	250 to 350 (1.72 to 2.41)	RWP of valve(s), line(s), or MASP for the well program, whichever is lower	
Kelly, kelly valves, drill pipe safety valves, IBOPs	250 to 350 (1.72 to 2.41)	MASP for the well program	

<sup>a</sup> Pressure test evaluation periods shall be a minimum of five minutes.

No visible leaks.

The pressure shall remain stable during the evaluation period. The pressure shall not decrease below the intended test pressure.

<sup>b</sup> Annular(s) and VBR(s) shall be pressure tested on the largest and smallest OD drill pipe to be used in well program.

<sup>c</sup> For pad drilling operations, moving from one wellhead to another within the 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken.

<sup>d</sup> For surface offshore operations, the ram BOPs shall be pressure tested with the ram locks engaged and the closing and locking pressure vented during the initial test. For land operations, the ram BOPs shall be pressure tested with the ram locks engaged and the closing and locking pressure vented at commissioning and annually.

<sup>e</sup> Adjustable chokes are not required to be full sealing devices. Pressure testing against a closed choke is not required.

The Bureau of Safety and Environmental Enforcement (BSEE), Department of Interior, has also utilized the API standards, specification and best practices in the development of its offshore oil and gas regulations and incorporates them by reference within its regulations.

Break testing has been approved by the BLM in the past with other operators based on the detailed information provided in this document.


XTO Energy feels break testing and our current procedures meet the intent of OOGO No. 2 and often exceed it. There has been no evidence that break testing results in more components failing than seen on full BOP tests. XTO Energy's internal standards requires complete BOPE tests more often than that of OOGO No. 2 (Every 21 days). In addition to function testing the annular, pipe rams and blind rams after each BOP nipple up, XTO Energy performs a choke drill with the rig crew prior to drilling out every casing shoe. This is additional training for the rig crew that exceeds the requirements of the OOGO No.2.

### **Procedures**

1. XTO Energy will use this document for our break testing plan for New Mexico Delaware basin. The summary below will be referenced in the APD or Sundry Notice and receive approval prior to implementing this variance.
2. XTO Energy will perform BOP break testing on multi-wells pads where multiple intermediate sections can be drilled and cased within the 21-day BOP test window.
  - a. A full BOP test will be conducted on the first well on the pad.
  - b. The first intermediate hole section drilled on the pad will be the deepest. All of the remaining hole sections will be the same depth or shallower.
    - i. Our Lower WC targets set the intermediate casing shoe no deeper than the Wolfcamp B.
    - ii. Our Upper WC targets set the intermediate casing shoe shallower than the Wolfcamp B.
  - c. A Full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
  - d. A full BOP test will be required prior to drilling any production hole.
3. After performing a complete BOP test on the first well, the intermediate hole section will be drilled and cased, two breaks would be made on the BOP equipment.
  - a. Between the HCV valve and choke line connection
  - b. Between the BOP quick connect and the wellhead
4. The BOP is then lifted and removed from the wellhead by a hydraulic system.
5. After skidding to the next well, the BOP is moved to the wellhead by the same hydraulic system and installed.
6. The connections mentioned in 3a and 3b will then be reconnected.
7. Install test plug into the wellhead using test joint or drill pipe.
8. A shell test is performed against the upper pipe rams testing the two breaks.
9. The shell test will consist of a 250 psi low test and a high test to the value submitted in the APD or Sundry (e.g. 5,000 psi or 10,000psi).
10. Function test will be performed on the following components: lower pipe rams, blind rams, and annular.

11. For a multi-well pad the same two breaks on the BOP would be made and on the next wells and steps 4 through 10 would be repeated.
12. A second break test would only be done if the intermediate hole section being drilled could not be completed within the 21 day BOP test window.

*Note: Picture below highlights BOP components that will be tested during batch operations*



### Summary

A variance is requested to **ONLY** test broken pressure seals on the BOP equipment when moving from wellhead to wellhead which is in compliance with API Standard 53. API Standard 53 states, that for pad drilling operation, moving from one wellhead to another within 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken.

The BOP will be secured by a hydraulic carrier or cradle. The BLM will be contacted if a Well Control event occurs prior to the commencement of a BOPE Break Testing operation.

Based on discussions with the BLM on February 27th 2020 and the supporting documentation submitted to the BLM, we will request permission to **ONLY** retest broken pressure seals if the following conditions are met:

1. After a full BOP test is conducted on the first well on the pad.
2. The first intermediate hole section drilled on the pad will be the deepest. All of the remaining hole sections will be the same depth or shallower.
3. Full BOP test will be required if the intermediate hole section being drilled has a MASP over 5M.
4. Full BOP test will be required prior to drilling the production hole.



Only **ONE** test will occur during each break test procedure.


All valves in red including the upper pipe rams will be shut to test the broken connections.

\*\* Each valve on choke manifold will alternate being tested against during each rig skid.



The connection between the HCV and kill line connection will **NOT** be broken on each skid and does not need to be retested.

The connection between the BOP stack / BOP Quick Connect and wellhead will be broken, as well as, the connection between the HCV and Choke Line on each skid and will be re-tested each time.



GATES E & S NORTH AMERICA, INC  
DU-TEX  
134 44TH STREET  
CORPUS CHRISTI, TEXAS 78405

PHONE: 361-887-9807  
FAX: 361-887-0812  
EMAIL: crpe@s@gates.com  
WEB: www.gates.com

### GRADE D PRESSURE TEST CERTIFICATE


Customer :	AUSTIN DISTRIBUTING	Test Date:	6/8/2014
Customer Ref. :	PENDING	Hose Serial No.:	D-060814-1
Invoice No. :	201709	Created By:	NORMA
Product Description:	FD3.042.0R41/16.5KFLGE/E LE		
End Fitting 1 :	4 1/16 in.5K FLG	End Fitting 2 :	4 1/16 in.5K FLG
Gates Part No. :	4774-6001	Assembly Code :	L33090011513D-060814-1
Working Pressure :	5,000 PSI	Test Pressure :	7,500 PSI

Gates E & S North America, Inc. certifies that the following hose assembly has been tested to the Gates Oilfield Roughneck Agreement/Specification requirements and passed the 15 minute hydrostatic test per API Spec 7K/Q1, Fifth Edition, June 2010, Test pressure 9.6.7 and per Table 9 to 7,500 psi in accordance with this product number. Hose burst pressure 9.6.7.2 exceeds the minimum of 2.5 times the working pressure per Table 9.

Quality:	QUALITY	Technical Supervisor :	PRODUCTION
Date :	6/8/2014	Date :	6/8/2014
Signature :		Signature :	

Form PTC - 01 Rev.0 2









**XTO Permian Operating, LLC Offline Cementing Variance Request**

XTO requests the option to cement the surface and intermediate casing strings offline as a prudent batch drilling efficiency of acreage development.

**1. Cement Program**

No changes to the cement program will take place for offline cementing.

**2. Offline Cementing Procedure**

The operational sequence will be as follows. If a well control event occurs, the BLM will be contacted for approval prior to conducting offline cementing operations.

1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment (float collar and shoe)
2. Land casing with mandrel
3. Fill pipe with kill weight fluid, do not circulate through floats and confirm well is static
4. Set annular packoff shown below and pressure test to confirm integrity of the seal. Pressure ratings of wellhead components and valves is 5,000 psi.
5. After confirmation of both annular barriers and internal barriers, nipple down BOP and install cap flange.
  - a. If any barrier fails to test, the BOP stack will not be nippedled down until after the cement job is completed with cement 500ft above the highest formation capable of flow with kill weight mud above or after it has achieved 50-psi compressive strength if kill weight fluid cannot be verified.



Annular packoff with both external and internal seals

## XTO Permian Operating, LLC Offline Cementing Variance Request



Wellhead diagram during skidding operations

6. Skid rig to next well on pad.
7. Confirm well is static before removing cap flange, flange will not be removed and offline cementing operations will not commence until well is under control. If well is not static, casing outlet valves will provide access to both the casing ID and annulus. Rig or third party pump truck will kill well prior to cementing or nipping up for further remediation.
  - a. Well Control Plan
    - i. The Drillers Method will be the primary well control method to regain control of the wellbore prior to cementing, if wellbore conditions do not permit the drillers method other methods of well control may be used
    - ii. Rig pumps or a 3<sup>rd</sup> party pump will be tied into the upper casing valve to pump down the casing ID
    - iii. A high pressure return line will be rigged up to lower casing valve and run to choke manifold to control annular pressure
    - iv. Once influx is circulated out of the hole, kill weight mud will be circulated
    - v. Well will be confirmed static
    - vi. Once confirmed static, cap flange will be removed to allow for offline cementing operations to commence
8. Install offline cement tool
9. Rig up cement equipment

**XTO Permian Operating, LLC Offline Cementing Variance Request**

Wellhead diagram during offline cementing operations

10. Circulate bottoms up with cement truck
  - a. If gas is present on bottoms up, well will be shut in and returns rerouted through gas buster to handle entrained gas
  - b. Max anticipated time before circulating with cement truck is 6 hrs
11. Perform cement job taking returns from the annulus wellhead valve
12. Confirm well is static and floats are holding after cement job
13. Remove cement equipment, offline cement tools and install night cap with pressure gauge for monitoring.

XTO respectfully requests approval to utilize a spudder rig to pre-set surface casing.

Description of Operations:

1. Spudder rig will move in to drill the surface hole and pre-set surface casing on the well.
  - a. After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
  - b. The spudder rig will utilize fresh water-based mud to drill the surface hole to TD. Solids control will be handled entirely on a closed loop basis. No earth pits will be used.
2. The wellhead will be installed and tested as soon as the surface casing is cut off and WOC time has been reached.
3. A blind flange at the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wing valves.
  - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. Spudder rig operations are expected to take 2-3 days per well on the pad.
5. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
6. Drilling Operations will begin with a larger rig and a BOP stack equal to or greater than the pressure rating that was permitted will be nipped up and tested on the wellhead before drilling operations resume on each well.
  - a. The larger rig will move back onto the location within 180 days from the point at which the wells are secured and the spudder rig is moved off location.
  - b. The BLM will be notified 24 hours before the larger rig moves back on the pre-set locations
7. XTO will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
8. Once the rig is removed, XTO will secure the wellhead area by placing a guard rail around the cellar area.



## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	XTO Permian Operating LLC
<b>WELL NAME &amp; NO.:</b>	Big Eddy Unit 30E Skywalker 100H
<b>LOCATION:</b>	Sec 14-20S-31E-NMP
<b>COUNTY:</b>	Eddy County, New Mexico

*Changes approved through engineering via Sundry 2702519 on 01/19/2023. Any previous COAs not addressed within the updated COAs still apply.*

**IMPORTANT NOTE FROM BLM GEOLOGIST REGARDING WELL:** Located in a depth restrictive area, TVD should not exceed approximately 9,665', or 50' into the top of the 3rd Bone Spring Limestone. Cooperative work between BLM Geologist responsible for Potash management and BLM Geologist responsible for authoring this report identified a shallower 3rd Bone Spring Limestone top depth than originally predicted. Revised 04/02/2019 to include the shallower 3rd Bone Spring Limestone formation top depth, from 9,750' TVD to 9,615' TVD, based on best available data in the area.

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input type="radio"/> None	<input type="radio"/> Secretary	<input checked="" type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input checked="" type="checkbox"/> 4 String Area	<input checked="" type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input checked="" type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input checked="" type="checkbox"/> Unit

### A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

**B. CASING**

1. The **18-5/8** inch surface casing shall be set at approximately 849 feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite and above the salt) and cemented to the surface. ***Surface casing set depth adjusted per BLM geologist.***
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **24 hours in the Potash Area** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

**Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.**

2. The minimum required fill of cement behind the **13-3/8** inch intermediate casing is:
  - Cement to surface. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
  - ❖ In R111 Potash Areas if cement does not circulate to surface on the first two salt protection casing strings, the cement on the 3rd casing string must come to surface.
  - ❖ In Capitan Reef Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
  - ❖ Ensure freshwater based mud is used across the Capitan interval

**Operator has proposed to pump down 13-3/8" X 9-5/8" annulus. Operator must run a CBL from TD of the 9-5/8" casing to surface. Submit results to BLM.**

3. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
  - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, potash or capitan reef.**

**Operator has proposed to pump down 9-5/8" X 5-1/2" annulus. Operator must run a CBL from TD of the 5-1/2" casing to surface. Submit results to BLM.**

4. The minimum required fill of cement behind the **5-1/2** inch production casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
  - Cement should tie-back at least **50 feet** on top of Capitan Reef top **or 200 feet** into the previous casing, whichever is greater. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, potash or capitan reef.**

## **C. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M)** psi.
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

#### **D. SPECIAL REQUIREMENT (S)**

##### **Unit Wells**

The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number when the sign is replaced.

##### **Commercial Well Determination**

A commercial well determination shall be submitted after production has been established for at least six months.

##### **Break Testing**

**BOP Break Testing Variance** (Note: Shell testing is not approved for any portion of the hole with a MASP of 5000 psi or greater)

- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer prior to the commencement of any BOP Break Testing operations.

A full BOP test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOP test will be required.

## **GENERAL REQUIREMENTS**

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e.

changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
  - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-



off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### C. DRILLING MUD



Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS  
  
Action 181853

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 181853
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
kpickford	Adhere to previous NMOCD Conditions of Approval	2/2/2023