

<b>Well Name:</b> BETONNIE TSOSIE WASH UNIT	<b>Well Location:</b> T23N / R8W / SEC 15 / SESW / 36.221991 / -107.672361	<b>County or Parish/State:</b> SAN JUAN / NM
<b>Well Number:</b> 211H	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM50999	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b> NMNM135219a
<b>US Well Number:</b> 3004538248	<b>Well Status:</b> Drilling Well	<b>Operator:</b> DJR OPERATING LLC

Subsequent Report

<b>Sundry ID:</b> 2704438	
<b>Type of Submission:</b> Subsequent Report	<b>Type of Action:</b> Drilling Operations
<b>Date Sundry Submitted:</b> 11/28/2022	<b>Time Sundry Submitted:</b> 08:23
<b>Date Operation Actually Began:</b> 11/20/2022	

**Actual Procedure:** Intermediate Casing & Cement. Depths adjusted for 26' KB of production rig. -11/20/22: NU BOPE full function PT L250 (5min) H1500 (10min). PT pre-set 9.625" 36# J55 STC casing 1500 (30min). All test good & recorded on chart. No regulatory agencies onsite to witness. Drill 8.75" hole from 395' to 5446' MD. TOH -11/24/22. RU CRTs. Run 125 jts of 7" 26# J55 LTC casing set from surface to 5437'. RU to cement. 5k test on lines, test good. Lead: Type G, 187 bbls (449 sx), 12.3 ppg, 2.34 yield, 13.13 gps. Tail: Type G, 38 bbls (143 sx) 13.5 ppg, 1.47 yield, 7.01 gps. Total sx: 592. Bump plug 910 FCP, pressure up to 1910 psi & hold for 5 min. Check floats, floats held. Circulate. No cement back to surface. RD CRTs. Install 7" packoff, secure & test to 5k, test good. ND BOP & cap well. Please note: PT of 7" casing will be provided in next report. -11/25/22: Run CBL. TOC called at 400'. BOC at 5437'. CBL uploaded to BLM & NMOCD on 11/28/22.

SR Attachments

**PActual Procedure**  
BETONNIE\_TSOSIE\_WASH\_UNIT\_211H\_20221128082334.pdf

<b>Well Name:</b> BETONNIE TSOSIE WASH UNIT	<b>Well Location:</b> T23N / R8W / SEC 15 / SESW / 36.221991 / -107.672361	<b>County or Parish/State:</b> SAN JUAN / NM
<b>Well Number:</b> 211H	<b>Type of Well:</b> OIL WELL	<b>Allottee or Tribe Name:</b>
<b>Lease Number:</b> NMNM50999	<b>Unit or CA Name:</b>	<b>Unit or CA Number:</b> NMNM135219a
<b>US Well Number:</b> 3004538248	<b>Well Status:</b> Drilling Well	<b>Operator:</b> DJR OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

<b>Operator Electronic Signature:</b> SHAW-MARIE FORD	<b>Signed on:</b> NOV 28, 2022 08:23 AM
<b>Name:</b> DJR OPERATING LLC	
<b>Title:</b> Regulatory Specialist	
<b>Street Address:</b> 1 Road 3263	
<b>City:</b> Aztec	<b>State:</b> NM
<b>Phone:</b> (505) 632-3476	
<b>Email address:</b> sford@djrlc.com	

Field

<b>Representative Name:</b>		
<b>Street Address:</b>		
<b>City:</b>	<b>State:</b>	<b>Zip:</b>
<b>Phone:</b>		
<b>Email address:</b>		

BLM Point of Contact

<b>BLM POC Name:</b> KENNETH G RENNICK	<b>BLM POC Title:</b> Petroleum Engineer
<b>BLM POC Phone:</b> 5055647742	<b>BLM POC Email Address:</b> krennick@blm.gov
<b>Disposition:</b> Accepted	<b>Disposition Date:</b> 11/29/2022
<b>Signature:</b> Kenneth Rennick	

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS

Action 162116

CONDITIONS

Operator: DJR OPERATING, LLC 1 Road 3263 Aztec, NM 87410	OGRID: 371838
	Action Number: 162116
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
gramirez	Cement is required to circulate on both surface and intermediate1 strings of casing. Perform a top down job.	2/7/2023