

Form 3160-3
(June 2015)

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: DRILL REENTER
1b. Type of Well: Oil Well Gas Well Other
1c. Type of Completion: Hydraulic Fracturing Single Zone Multiple Zone

5. Lease Serial No.
6. If Indian, Allottee or Tribe Name
7. If Unit or CA Agreement, Name and No.
8. Lease Name and Well No.

[316707]

2. Name of Operator
[12361]

9. API Well No. 30-025-51095

3a. Address 3b. Phone No. (include area code)

10. Field and Pool, or Exploratory [98259]

4. Location of Well (Report location clearly and in accordance with any State requirements. *)
At surface
At proposed prod. zone

11. Sec., T. R. M. or Blk. and Survey or Area

14. Distance in miles and direction from nearest town or post office*

12. County or Parish 13. State

15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)

16. No of acres in lease

17. Spacing Unit dedicated to this well

18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.

19. Proposed Depth

20. BLM/BIA Bond No. in file

21. Elevations (Show whether DF, KDB, RT, GL, etc.)

22. Approximate date work will start*

23. Estimated duration

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- 1. Well plat certified by a registered surveyor.
- 2. A Drilling Plan.
- 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).

- 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- 5. Operator certification.
- 6. Such other site specific information and/or plans as may be requested by the BLM.

25. Signature Name (Printed/Typed) Date

Title

Approved by (Signature) Name (Printed/Typed) Date

Title Office

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NGMP Rec 02/13/2023

SL

KZ
02/14/2023



(Continued on page 2)

*(Instructions on page 2)

State of New Mexico
 Energy, Minerals and Natural Resources Department

Submit Electronically
 Via E-permitting

Oil Conservation Division
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description Effective May 25, 2021

I. Operator: Kaiser-Francis Oil Company OGRID: 12361 Date: 01/30/2023

II. Type: Original Amendment due to 19.15.27.9.D(6)(a) NMAC 19.15.27.9.D(6)(b) NMAC Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Bell Lake Unit North 135H		I-Sec5-T23S-34E	1925 FSL 1275 FEL	1800	3000	2000

IV. Central Delivery Point Name: pad site [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Bell Lake Unit North 135H		TBD	TBD	TBD	TBD	TBD

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Kaiser-Francis Oil Company Natural Gas Management Plan

Plan Description

VI. Separation Equipment

Separation equipment will be designed for maximum anticipated throughput and pressure to minimize waste.

VII. Operational Practices

A. VENTING AND FLARING OF NATURAL GAS

Kaiser-Francis Oil Company (KFOC) will maximize the recovery of natural gas by minimizing the waste of natural gas through venting and flaring during drilling, completion, and production operations as outlined in 19.15.27.8 NMAC. KFOC will flare rather than vent natural gas except when flaring is technically infeasible or would pose a safety risk and venting is a safer alternative than flaring. KFOC will ensure well(s) are connected to a natural gas gathering system with sufficient capacity to transport natural gas.

B. Venting and flaring during drilling operations

KFOC will combust natural gas brought to the surface during drilling operations. A properly sized flare stack will be located at a minimum of 100 feet from the nearest surface hole location. In case of emergency or malfunction, KFOC will report natural gas volumes, vented or flared.

C. Venting and flaring during completion or recompletion operations

During completion operations, KFOC will flare natural gas brought to the surface and commence operation of a separator once technically feasible. Produced natural gas from separation equipment will be sold. If natural gas does not meet gathering pipeline quality specifications, KFOC will flare for no more than 60 days or until the natural gas meets the pipeline quality specifications, whichever is sooner.

D. Venting and flaring during production operations

KFOC will not vent or flare natural gas during production, except for provisions defined by 19.15.27.8.D (1) through (4). KFOC will report natural gas volumes, vented or flared, appropriately.

E. Performance Standards

KFOC will comply with performance standards outlined in 19.15.27.8.E to minimize waste. Separation equipment will be designed for maximum anticipated throughput and pressure to minimize waste. Any permanent storage tank associated with production operations that is

routed to a flare or control device will be equipped with an automatic gauging system that reduces the venting of natural gas. KFOC will combust natural gas in a flare stack that is properly sized and designed to ensure proper combustion efficiency. Flare stacks will be equipped with an automatic ignitor or continuous pilot. KFOC will conduct an AVO inspection on the frequency specified in Subsection D of 19.15.27.8 NMAC. All emergencies will be resolved as quickly and safely as feasible.

F. Measurement or estimation of vented or flared natural gas

KFOC will measure or estimate natural gas that is vented, flared, or beneficially used during drilling, completion, and production operations. Equipment will be installed to measure the volume of natural gas flared from existing piping or a flowline piped from equipment such as high-pressure separators, heater treaters, or vapor recovery units associated with a well or facility, authorized by an APD issued after May 25, 2021, that has an average daily production greater than 60,000 cubic feet of natural gas. Measuring equipment will conform to an industry standard. Where measuring is not feasible, volumes will be estimated.

VIII. Best Management Practices

During active and planned maintenance, venting will be limited to the depressurization of the equipment to ensure safe working conditions. For maintenance of production and compression equipment the associated producing wells will be shut-in to eliminate venting. During VRU maintenance, gas normally routed to the VRU will be flared.

Section 2 – Enhanced Plan

EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system will will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator does does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

Attach Operator’s plan to manage production in response to the increased line pressure.

XIV. Confidentiality: Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications

Effective May 25, 2021

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: 
Printed Name: Aaron Daniels
Title: EHS Manager
E-mail Address: aarond@kfoc.net
Date: 1/30/2023
Phone: 918-491-4352

OIL CONSERVATION DIVISION
(Only applicable when submitted as a standalone form)

Approved By:
Title:
Approval Date:
Conditions of Approval:



Kaiser Francis

Bell Lake Unit North 135H
Bell Lake Unit North 135H
Bell Lake Unit North 135H
Bell Lake Unit North 135H

Plan: 190621 Bell Lake Unit North 135H

Morcor Standard Plan

21 June, 2019

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Project	Bell Lake Unit North 135H		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Bell Lake Unit North 135H				
Site Position:		Northing:	485,427.38 usft	Latitude:	32° 19' 54.041 N
From:	Map	Easting:	802,519.29 usft	Longitude:	103° 29' 15.842 W
Position Uncertainty:	1.0 usft	Slot Radius:	17-1/2 "	Grid Convergence:	0.45 °

Well	Bell Lake Unit North 135H					
Well Position	+N/-S	0.0 usft	Northing:	485,427.38 usft	Latitude:	32° 19' 54.041 N
	+E/-W	0.0 usft	Easting:	802,519.29 usft	Longitude:	103° 29' 15.842 W
Position Uncertainty		1.0 usft	Wellhead Elevation:	usft	Ground Level:	3,423.1 usft

Wellbore	Bell Lake Unit North 135H				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	6/21/2019	6.56	60.09	47,887

Design	190621 Bell Lake Unit North 135H				
Audit Notes:					
Version:	Phase:	PLAN	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	358.63	

Survey Tool Program	Date	6/21/2019			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
0.0	17,783.2	190621 Bell Lake Unit North 135H (Bell La	MWD	MWD - Standard	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
0.0	0.00	0.00	0.0	-3,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
100.0	0.00	0.00	100.0	-3,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
120.0	0.00	0.00	120.0	-3,325.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
20" Conductor											
200.0	0.00	0.00	200.0	-3,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
300.0	0.00	0.00	300.0	-3,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
400.0	0.00	0.00	400.0	-3,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
500.0	0.00	0.00	500.0	-2,945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
600.0	0.00	0.00	600.0	-2,845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
700.0	0.00	0.00	700.0	-2,745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
800.0	0.00	0.00	800.0	-2,645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
900.0	0.00	0.00	900.0	-2,545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	-2,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	-2,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	-2,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,222.0	0.00	0.00	1,222.0	-2,223.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Rustler											
1,247.0	0.00	0.00	1,247.0	-2,198.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
13 3/8" Surface Casing											
1,300.0	0.00	0.00	1,300.0	-2,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,400.0	0.00	0.00	1,400.0	-2,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,500.0	0.00	0.00	1,500.0	-1,945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,600.0	0.00	0.00	1,600.0	-1,845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,622.0	0.00	0.00	1,622.0	-1,823.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Salado											
1,700.0	0.00	0.00	1,700.0	-1,745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,800.0	0.00	0.00	1,800.0	-1,645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	

Morcor Engineering

Morcor Standard Plan



Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
1,822.0	0.00	0.00	1,822.0	-1,623.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Top of Salt											
1,900.0	0.00	0.00	1,900.0	-1,545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	-1,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,100.0	0.00	0.00	2,100.0	-1,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,200.0	0.00	0.00	2,200.0	-1,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,300.0	0.00	0.00	2,300.0	-1,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,400.0	0.00	0.00	2,400.0	-1,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,500.0	0.00	0.00	2,500.0	-945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,600.0	0.00	0.00	2,600.0	-845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,700.0	0.00	0.00	2,700.0	-745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,800.0	0.00	0.00	2,800.0	-645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,900.0	0.00	0.00	2,900.0	-545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,000.0	0.00	0.00	3,000.0	-445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,100.0	0.00	0.00	3,100.0	-345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,200.0	0.00	0.00	3,200.0	-245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,300.0	0.00	0.00	3,300.0	-145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,400.0	0.00	0.00	3,400.0	-45.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,500.0	0.00	0.00	3,500.0	54.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,600.0	0.00	0.00	3,600.0	154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,700.0	0.00	0.00	3,700.0	254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,800.0	0.00	0.00	3,800.0	354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,900.0	0.00	0.00	3,900.0	454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,000.0	0.00	0.00	4,000.0	554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,100.0	0.00	0.00	4,100.0	654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,200.0	0.00	0.00	4,200.0	754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,300.0	0.00	0.00	4,300.0	854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
4,400.0	0.00	0.00	4,400.0	954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,500.0	0.00	0.00	4,500.0	1,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,600.0	0.00	0.00	4,600.0	1,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,700.0	0.00	0.00	4,700.0	1,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,722.0	0.00	0.00	4,722.0	1,276.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Base of Salt										
4,800.0	0.00	0.00	4,800.0	1,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,900.0	0.00	0.00	4,900.0	1,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,972.0	0.00	0.00	4,972.0	1,526.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Lamar										
5,000.0	0.00	0.00	5,000.0	1,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,072.0	0.00	0.00	5,072.0	1,626.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
9 5/8" Intermediate Casing										
5,100.0	0.00	0.00	5,100.0	1,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,172.0	0.00	0.00	5,172.0	1,726.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Bell Canyon										
5,200.0	0.00	0.00	5,200.0	1,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,300.0	0.00	0.00	5,300.0	1,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,400.0	0.00	0.00	5,400.0	1,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,500.0	0.00	0.00	5,500.0	2,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,600.0	0.00	0.00	5,600.0	2,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,700.0	0.00	0.00	5,700.0	2,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,800.0	0.00	0.00	5,800.0	2,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,900.0	0.00	0.00	5,900.0	2,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,000.0	0.00	0.00	6,000.0	2,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,100.0	0.00	0.00	6,100.0	2,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,197.0	0.00	0.00	6,197.0	2,751.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Cherry Canyon										

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
6,200.0	0.00	0.00	6,200.0	2,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,300.0	0.00	0.00	6,300.0	2,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,400.0	0.00	0.00	6,400.0	2,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,500.0	0.00	0.00	6,500.0	3,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,600.0	0.00	0.00	6,600.0	3,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,700.0	0.00	0.00	6,700.0	3,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,800.0	0.00	0.00	6,800.0	3,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,900.0	0.00	0.00	6,900.0	3,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,000.0	0.00	0.00	7,000.0	3,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,100.0	0.00	0.00	7,100.0	3,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,200.0	0.00	0.00	7,200.0	3,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,300.0	0.00	0.00	7,300.0	3,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,400.0	0.00	0.00	7,400.0	3,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,500.0	0.00	0.00	7,500.0	4,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,522.0	0.00	0.00	7,522.0	4,076.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Brushy Canyon										
7,600.0	0.00	0.00	7,600.0	4,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,700.0	0.00	0.00	7,700.0	4,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,800.0	0.00	0.00	7,800.0	4,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,900.0	0.00	0.00	7,900.0	4,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,000.0	0.00	0.00	8,000.0	4,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,100.0	0.00	0.00	8,100.0	4,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,200.0	0.00	0.00	8,200.0	4,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,300.0	0.00	0.00	8,300.0	4,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,400.0	0.00	0.00	8,400.0	4,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,500.0	0.00	0.00	8,500.0	5,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,600.0	0.00	0.00	8,600.0	5,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
8,622.0	0.00	0.00	8,622.0	5,176.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Bone Spring										
8,700.0	0.00	0.00	8,700.0	5,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,717.0	0.00	0.00	8,717.0	5,271.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Avalon										
8,800.0	0.00	0.00	8,800.0	5,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,900.0	0.00	0.00	8,900.0	5,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
9,000.0	0.00	0.00	9,000.0	5,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
9,100.0	0.00	0.00	9,100.0	5,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
9,147.0	0.00	0.00	9,147.0	5,701.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Start Build 10.00										
9,150.0	0.30	1.78	9,150.0	5,704.9	0.0	0.0	802,519.29	485,427.39	0.01	10.00
9,200.0	5.30	1.78	9,199.9	5,754.8	2.4	0.1	802,519.37	485,429.83	2.45	10.00
9,250.0	10.30	1.78	9,249.4	5,804.3	9.2	0.3	802,519.58	485,436.61	9.22	10.00
9,300.0	15.30	1.78	9,298.2	5,853.1	20.3	0.6	802,519.92	485,447.68	20.27	10.00
9,350.0	20.30	1.78	9,345.8	5,900.7	35.6	1.1	802,520.40	485,462.95	35.53	10.00
9,400.0	25.30	1.78	9,391.9	5,946.8	54.9	1.7	802,521.00	485,482.30	54.87	10.00
9,450.0	30.30	1.78	9,436.1	5,991.0	78.2	2.4	802,521.73	485,505.60	78.14	10.00
9,500.0	35.30	1.78	9,478.1	6,033.0	105.3	3.3	802,522.57	485,532.66	105.18	10.00
9,550.0	40.30	1.78	9,517.6	6,072.5	135.9	4.2	802,523.52	485,563.28	135.76	10.00
9,555.8	40.88	1.78	9,522.0	6,076.9	139.7	4.4	802,523.64	485,567.06	139.54	10.00
1st Bone Spring Sand										
9,600.0	45.30	1.78	9,554.3	6,109.2	169.8	5.3	802,524.58	485,597.23	169.67	10.00
9,650.0	50.30	1.78	9,587.8	6,142.7	206.9	6.4	802,525.74	485,634.23	206.64	10.00
9,700.0	55.29	1.78	9,618.1	6,173.0	246.6	7.7	802,526.97	485,674.03	246.39	10.00
9,750.0	60.29	1.78	9,644.7	6,199.6	288.9	9.0	802,528.29	485,716.30	288.62	10.00
9,800.0	65.29	1.78	9,667.6	6,222.5	333.4	10.4	802,529.68	485,760.73	333.01	10.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
9,850.0	70.29	1.78	9,686.5	6,241.4	379.6	11.8	802,531.12	485,806.99	379.21	10.00
9,900.0	75.29	1.78	9,701.2	6,256.1	427.3	13.3	802,532.60	485,854.71	426.89	10.00
9,950.0	80.29	1.78	9,711.8	6,266.7	476.2	14.8	802,534.13	485,903.54	475.67	10.00
10,000.0	85.29	1.78	9,718.1	6,273.0	525.7	16.4	802,535.67	485,953.10	525.18	10.00
10,034.8	88.77	1.78	9,719.9	6,274.8	560.5	17.5	802,536.75	485,987.85	559.89	10.00
Start DLS 1.84 TFO -70.33										
10,100.0	89.18	0.66	9,721.0	6,275.9	625.6	18.9	802,538.14	486,053.01	625.00	1.84
10,200.0	89.80	358.92	9,721.9	6,276.8	725.6	18.5	802,537.77	486,153.00	724.97	1.84
10,232.7	90.00	358.36	9,722.0	6,276.9	758.3	17.7	802,537.00	486,185.66	757.64	1.84
Start 7550.6 hold at 10232.7 MD										
10,300.0	90.00	358.36	9,722.0	6,276.9	825.6	15.8	802,535.07	486,252.96	824.97	0.00
10,400.0	90.00	358.36	9,722.0	6,276.9	925.5	12.9	802,532.20	486,352.92	924.97	0.00
10,500.0	90.00	358.36	9,722.0	6,276.9	1,025.5	10.0	802,529.33	486,452.88	1,024.97	0.00
10,600.0	90.00	358.36	9,722.0	6,276.9	1,125.5	7.2	802,526.46	486,552.84	1,124.97	0.00
10,700.0	90.00	358.36	9,722.0	6,276.9	1,225.4	4.3	802,523.60	486,652.80	1,224.96	0.00
10,800.0	90.00	358.36	9,722.0	6,276.9	1,325.4	1.4	802,520.73	486,752.76	1,324.96	0.00
10,900.0	90.00	358.36	9,722.0	6,276.9	1,425.3	-1.4	802,517.86	486,852.72	1,424.96	0.00
11,000.0	90.00	358.36	9,722.0	6,276.9	1,525.3	-4.3	802,515.00	486,952.68	1,524.96	0.00
11,100.0	90.00	358.36	9,722.0	6,276.9	1,625.3	-7.2	802,512.13	487,052.63	1,624.96	0.00
11,200.0	90.00	358.36	9,722.0	6,276.9	1,725.2	-10.0	802,509.26	487,152.59	1,724.96	0.00
11,300.0	90.00	358.36	9,722.0	6,276.9	1,825.2	-12.9	802,506.39	487,252.55	1,824.96	0.00
11,400.0	90.00	358.36	9,722.0	6,276.9	1,925.1	-15.8	802,503.53	487,352.51	1,924.96	0.00
11,500.0	90.00	358.36	9,722.0	6,276.9	2,025.1	-18.6	802,500.66	487,452.47	2,024.96	0.00
11,600.0	90.00	358.36	9,722.0	6,276.9	2,125.0	-21.5	802,497.79	487,552.43	2,124.95	0.00
11,700.0	90.00	358.36	9,722.0	6,276.9	2,225.0	-24.4	802,494.92	487,652.39	2,224.95	0.00
11,800.0	90.00	358.36	9,722.0	6,276.9	2,325.0	-27.2	802,492.06	487,752.35	2,324.95	0.00
11,900.0	90.00	358.36	9,722.0	6,276.9	2,424.9	-30.1	802,489.19	487,852.31	2,424.95	0.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
12,000.0	90.00	358.36	9,722.0	6,276.9	2,524.9	-33.0	802,486.32	487,952.26	2,524.95	0.00	
12,100.0	90.00	358.36	9,722.0	6,276.9	2,624.8	-35.8	802,483.46	488,052.22	2,624.95	0.00	
12,200.0	90.00	358.36	9,722.0	6,276.9	2,724.8	-38.7	802,480.59	488,152.18	2,724.95	0.00	
12,300.0	90.00	358.36	9,722.0	6,276.9	2,824.8	-41.6	802,477.72	488,252.14	2,824.95	0.00	
12,400.0	90.00	358.36	9,722.0	6,276.9	2,924.7	-44.4	802,474.85	488,352.10	2,924.95	0.00	
12,500.0	90.00	358.36	9,722.0	6,276.9	3,024.7	-47.3	802,471.99	488,452.06	3,024.94	0.00	
12,600.0	90.00	358.36	9,722.0	6,276.9	3,124.6	-50.2	802,469.12	488,552.02	3,124.94	0.00	
12,700.0	90.00	358.36	9,722.0	6,276.9	3,224.6	-53.0	802,466.25	488,651.98	3,224.94	0.00	
12,800.0	90.00	358.36	9,722.0	6,276.9	3,324.6	-55.9	802,463.38	488,751.94	3,324.94	0.00	
12,900.0	90.00	358.36	9,722.0	6,276.9	3,424.5	-58.8	802,460.52	488,851.89	3,424.94	0.00	
13,000.0	90.00	358.36	9,722.0	6,276.9	3,524.5	-61.6	802,457.65	488,951.85	3,524.94	0.00	
13,100.0	90.00	358.36	9,722.0	6,276.9	3,624.4	-64.5	802,454.78	489,051.81	3,624.94	0.00	
13,200.0	90.00	358.36	9,722.0	6,276.9	3,724.4	-67.4	802,451.91	489,151.77	3,724.94	0.00	
13,300.0	90.00	358.36	9,722.0	6,276.9	3,824.3	-70.2	802,449.05	489,251.73	3,824.94	0.00	
13,400.0	90.00	358.36	9,722.0	6,276.9	3,924.3	-73.1	802,446.18	489,351.69	3,924.93	0.00	
13,500.0	90.00	358.36	9,722.0	6,276.9	4,024.3	-76.0	802,443.31	489,451.65	4,024.93	0.00	
13,600.0	90.00	358.36	9,722.0	6,276.9	4,124.2	-78.8	802,440.45	489,551.61	4,124.93	0.00	
13,700.0	90.00	358.36	9,722.0	6,276.9	4,224.2	-81.7	802,437.58	489,651.57	4,224.93	0.00	
13,800.0	90.00	358.36	9,722.0	6,276.9	4,324.1	-84.6	802,434.71	489,751.52	4,324.93	0.00	
13,900.0	90.00	358.36	9,722.0	6,276.9	4,424.1	-87.4	802,431.84	489,851.48	4,424.93	0.00	
14,000.0	90.00	358.36	9,722.0	6,276.9	4,524.1	-90.3	802,428.98	489,951.44	4,524.93	0.00	
14,100.0	90.00	358.36	9,722.0	6,276.9	4,624.0	-93.2	802,426.11	490,051.40	4,624.93	0.00	
14,200.0	90.00	358.36	9,722.0	6,276.9	4,724.0	-96.0	802,423.24	490,151.36	4,724.93	0.00	
14,300.0	90.00	358.36	9,722.0	6,276.9	4,823.9	-98.9	802,420.37	490,251.32	4,824.92	0.00	
14,400.0	90.00	358.36	9,722.0	6,276.9	4,923.9	-101.8	802,417.51	490,351.28	4,924.92	0.00	
14,500.0	90.00	358.36	9,722.0	6,276.9	5,023.9	-104.7	802,414.64	490,451.24	5,024.92	0.00	
14,600.0	90.00	358.36	9,722.0	6,276.9	5,123.8	-107.5	802,411.77	490,551.20	5,124.92	0.00	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
14,700.0	90.00	358.36	9,722.0	6,276.9	5,223.8	-110.4	802,408.91	490,651.15	5,224.92	0.00
14,800.0	90.00	358.36	9,722.0	6,276.9	5,323.7	-113.3	802,406.04	490,751.11	5,324.92	0.00
14,900.0	90.00	358.36	9,722.0	6,276.9	5,423.7	-116.1	802,403.17	490,851.07	5,424.92	0.00
15,000.0	90.00	358.36	9,722.0	6,276.9	5,523.7	-119.0	802,400.30	490,951.03	5,524.92	0.00
15,100.0	90.00	358.36	9,722.0	6,276.9	5,623.6	-121.9	802,397.44	491,050.99	5,624.92	0.00
15,200.0	90.00	358.36	9,722.0	6,276.9	5,723.6	-124.7	802,394.57	491,150.95	5,724.91	0.00
15,300.0	90.00	358.36	9,722.0	6,276.9	5,823.5	-127.6	802,391.70	491,250.91	5,824.91	0.00
15,400.0	90.00	358.36	9,722.0	6,276.9	5,923.5	-130.5	802,388.83	491,350.87	5,924.91	0.00
15,500.0	90.00	358.36	9,722.0	6,276.9	6,023.4	-133.3	802,385.97	491,450.83	6,024.91	0.00
15,600.0	90.00	358.36	9,722.0	6,276.9	6,123.4	-136.2	802,383.10	491,550.78	6,124.91	0.00
15,700.0	90.00	358.36	9,722.0	6,276.9	6,223.4	-139.1	802,380.23	491,650.74	6,224.91	0.00
15,800.0	90.00	358.36	9,722.0	6,276.9	6,323.3	-141.9	802,377.37	491,750.70	6,324.91	0.00
15,900.0	90.00	358.36	9,722.0	6,276.9	6,423.3	-144.8	802,374.50	491,850.66	6,424.91	0.00
16,000.0	90.00	358.36	9,722.0	6,276.9	6,523.2	-147.7	802,371.63	491,950.62	6,524.91	0.00
16,100.0	90.00	358.36	9,722.0	6,276.9	6,623.2	-150.5	802,368.76	492,050.58	6,624.90	0.00
16,200.0	90.00	358.36	9,722.0	6,276.9	6,723.2	-153.4	802,365.90	492,150.54	6,724.90	0.00
16,300.0	90.00	358.36	9,722.0	6,276.9	6,823.1	-156.3	802,363.03	492,250.50	6,824.90	0.00
16,400.0	90.00	358.36	9,722.0	6,276.9	6,923.1	-159.1	802,360.16	492,350.46	6,924.90	0.00
16,500.0	90.00	358.36	9,722.0	6,276.9	7,023.0	-162.0	802,357.29	492,450.41	7,024.90	0.00
16,600.0	90.00	358.36	9,722.0	6,276.9	7,123.0	-164.9	802,354.43	492,550.37	7,124.90	0.00
16,700.0	90.00	358.36	9,722.0	6,276.9	7,223.0	-167.7	802,351.56	492,650.33	7,224.90	0.00
16,800.0	90.00	358.36	9,722.0	6,276.9	7,322.9	-170.6	802,348.69	492,750.29	7,324.90	0.00
16,900.0	90.00	358.36	9,722.0	6,276.9	7,422.9	-173.5	802,345.82	492,850.25	7,424.89	0.00
17,000.0	90.00	358.36	9,722.0	6,276.9	7,522.8	-176.3	802,342.96	492,950.21	7,524.89	0.00
17,100.0	90.00	358.36	9,722.0	6,276.9	7,622.8	-179.2	802,340.09	493,050.17	7,624.89	0.00
17,200.0	90.00	358.36	9,722.0	6,276.9	7,722.7	-182.1	802,337.22	493,150.13	7,724.89	0.00
17,300.0	90.00	358.36	9,722.0	6,276.9	7,822.7	-184.9	802,334.36	493,250.09	7,824.89	0.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
17,400.0	90.00	358.36	9,722.0	6,276.9	7,922.7	-187.8	802,331.49	493,350.04	7,924.89	0.00	
17,500.0	90.00	358.36	9,722.0	6,276.9	8,022.6	-190.7	802,328.62	493,450.00	8,024.89	0.00	
17,600.0	90.00	358.36	9,722.0	6,276.9	8,122.6	-193.5	802,325.75	493,549.96	8,124.89	0.00	
17,700.0	90.00	358.36	9,722.0	6,276.9	8,222.5	-196.4	802,322.89	493,649.92	8,224.89	0.00	
17,783.2	90.00	358.36	9,722.0	6,276.9	8,305.7	-198.8	802,320.50	493,733.09	8,308.08	0.00	
TD at 17783.2 - 5 1/2" Production Casing											

Casing Points						
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")		
1,247.0	1,247.0	13 3/8" Surface Casing	13-3/8	17-1/2		
17,783.2	9,722.0	5 1/2" Production Casing	5-1/2	8-3/4		
5,072.0	5,072.0	9 5/8" Intermediate Casing	9-5/8	12-1/4		
120.0	120.0	20" Conductor	20	26		

Morcor Engineering

Morcor Standard Plan



Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
7,522.0	7,522.0	Brushy Canyon		0.00		
8,717.0	8,717.0	Avalon		0.00		
1,822.0	1,822.0	Top of Salt		0.00		
1,222.0	1,222.0	Rustler		0.00		
4,722.0	4,722.0	Base of Salt		0.00		
9,555.8	9,522.0	1st Bone Spring Sand		0.00		
8,622.0	8,622.0	Bone Spring		0.00		
5,172.0	5,172.0	Bell Canyon		0.00		
6,197.0	6,197.0	Cherry Canyon		0.00		
4,972.0	4,972.0	Lamar		0.00		
1,622.0	1,622.0	Salado		0.00		

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
9,147.0	9,147.0	0.0	0.0	Start Build 10.00	
10,034.8	9,719.9	560.5	17.5	Start DLS 1.84 TFO -70.33	
10,232.7	9,722.0	758.3	17.7	Start 7550.6 hold at 10232.7 MD	
17,783.2	9,722.0	8,305.7	-198.8	TD at 17783.2	

Checked By: _____ Approved By: _____ Date: _____



Kaiser Francis

Bell Lake Unit North 135H
Bell Lake Unit North 135H
Bell Lake Unit North 135H
Bell Lake Unit North 135H

Plan: 190621 Bell Lake Unit North 135H

Morcor Standard Plan

21 June, 2019

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Project	Bell Lake Unit North 135H		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Bell Lake Unit North 135H				
Site Position:		Northing:	485,427.38 usft	Latitude:	32° 19' 54.041 N
From:	Map	Easting:	802,519.29 usft	Longitude:	103° 29' 15.842 W
Position Uncertainty:	1.0 usft	Slot Radius:	17-1/2 "	Grid Convergence:	0.45 °

Well	Bell Lake Unit North 135H					
Well Position	+N/-S	0.0 usft	Northing:	485,427.38 usft	Latitude:	32° 19' 54.041 N
	+E/-W	0.0 usft	Easting:	802,519.29 usft	Longitude:	103° 29' 15.842 W
Position Uncertainty	1.0 usft		Wellhead Elevation:	usft	Ground Level:	3,423.1 usft

Wellbore	Bell Lake Unit North 135H				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	6/21/2019	6.56	60.09	47,887

Design	190621 Bell Lake Unit North 135H				
Audit Notes:					
Version:	Phase:	PLAN	Tie On Depth:	0.0	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	358.63	

Survey Tool Program	Date	6/21/2019			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
0.0	17,783.2	190621 Bell Lake Unit North 135H (Bell La	MWD	MWD - Standard	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
0.0	0.00	0.00	0.0	-3,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
100.0	0.00	0.00	100.0	-3,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
120.0	0.00	0.00	120.0	-3,325.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
20" Conductor											
200.0	0.00	0.00	200.0	-3,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
300.0	0.00	0.00	300.0	-3,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
400.0	0.00	0.00	400.0	-3,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
500.0	0.00	0.00	500.0	-2,945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
600.0	0.00	0.00	600.0	-2,845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
700.0	0.00	0.00	700.0	-2,745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
800.0	0.00	0.00	800.0	-2,645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
900.0	0.00	0.00	900.0	-2,545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,000.0	0.00	0.00	1,000.0	-2,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,100.0	0.00	0.00	1,100.0	-2,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,200.0	0.00	0.00	1,200.0	-2,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,222.0	0.00	0.00	1,222.0	-2,223.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Rustler											
1,247.0	0.00	0.00	1,247.0	-2,198.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
13 3/8" Surface Casing											
1,300.0	0.00	0.00	1,300.0	-2,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,400.0	0.00	0.00	1,400.0	-2,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,500.0	0.00	0.00	1,500.0	-1,945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,600.0	0.00	0.00	1,600.0	-1,845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,622.0	0.00	0.00	1,622.0	-1,823.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Salado											
1,700.0	0.00	0.00	1,700.0	-1,745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
1,800.0	0.00	0.00	1,800.0	-1,645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	

Morcor Engineering

Morcor Standard Plan



Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
1,822.0	0.00	0.00	1,822.0	-1,623.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Top of Salt											
1,900.0	0.00	0.00	1,900.0	-1,545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	-1,445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,100.0	0.00	0.00	2,100.0	-1,345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,200.0	0.00	0.00	2,200.0	-1,245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,300.0	0.00	0.00	2,300.0	-1,145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,400.0	0.00	0.00	2,400.0	-1,045.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,500.0	0.00	0.00	2,500.0	-945.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,600.0	0.00	0.00	2,600.0	-845.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,700.0	0.00	0.00	2,700.0	-745.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,800.0	0.00	0.00	2,800.0	-645.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
2,900.0	0.00	0.00	2,900.0	-545.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,000.0	0.00	0.00	3,000.0	-445.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,100.0	0.00	0.00	3,100.0	-345.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,200.0	0.00	0.00	3,200.0	-245.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,300.0	0.00	0.00	3,300.0	-145.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,400.0	0.00	0.00	3,400.0	-45.1	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,500.0	0.00	0.00	3,500.0	54.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,600.0	0.00	0.00	3,600.0	154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,700.0	0.00	0.00	3,700.0	254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,800.0	0.00	0.00	3,800.0	354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
3,900.0	0.00	0.00	3,900.0	454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,000.0	0.00	0.00	4,000.0	554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,100.0	0.00	0.00	4,100.0	654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,200.0	0.00	0.00	4,200.0	754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
4,300.0	0.00	0.00	4,300.0	854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	

Morcor Engineering

Morcor Standard Plan



Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
4,400.0	0.00	0.00	4,400.0	954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,500.0	0.00	0.00	4,500.0	1,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,600.0	0.00	0.00	4,600.0	1,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,700.0	0.00	0.00	4,700.0	1,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,722.0	0.00	0.00	4,722.0	1,276.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Base of Salt										
4,800.0	0.00	0.00	4,800.0	1,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,900.0	0.00	0.00	4,900.0	1,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
4,972.0	0.00	0.00	4,972.0	1,526.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Lamar										
5,000.0	0.00	0.00	5,000.0	1,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,072.0	0.00	0.00	5,072.0	1,626.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
9 5/8" Intermediate Casing										
5,100.0	0.00	0.00	5,100.0	1,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,172.0	0.00	0.00	5,172.0	1,726.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Bell Canyon										
5,200.0	0.00	0.00	5,200.0	1,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,300.0	0.00	0.00	5,300.0	1,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,400.0	0.00	0.00	5,400.0	1,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,500.0	0.00	0.00	5,500.0	2,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,600.0	0.00	0.00	5,600.0	2,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,700.0	0.00	0.00	5,700.0	2,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,800.0	0.00	0.00	5,800.0	2,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
5,900.0	0.00	0.00	5,900.0	2,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,000.0	0.00	0.00	6,000.0	2,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,100.0	0.00	0.00	6,100.0	2,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,197.0	0.00	0.00	6,197.0	2,751.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Cherry Canyon										

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
6,200.0	0.00	0.00	6,200.0	2,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,300.0	0.00	0.00	6,300.0	2,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,400.0	0.00	0.00	6,400.0	2,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,500.0	0.00	0.00	6,500.0	3,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,600.0	0.00	0.00	6,600.0	3,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,700.0	0.00	0.00	6,700.0	3,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,800.0	0.00	0.00	6,800.0	3,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
6,900.0	0.00	0.00	6,900.0	3,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,000.0	0.00	0.00	7,000.0	3,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,100.0	0.00	0.00	7,100.0	3,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,200.0	0.00	0.00	7,200.0	3,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,300.0	0.00	0.00	7,300.0	3,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,400.0	0.00	0.00	7,400.0	3,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,500.0	0.00	0.00	7,500.0	4,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,522.0	0.00	0.00	7,522.0	4,076.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
Brushy Canyon										
7,600.0	0.00	0.00	7,600.0	4,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,700.0	0.00	0.00	7,700.0	4,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,800.0	0.00	0.00	7,800.0	4,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
7,900.0	0.00	0.00	7,900.0	4,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,000.0	0.00	0.00	8,000.0	4,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,100.0	0.00	0.00	8,100.0	4,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,200.0	0.00	0.00	8,200.0	4,754.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,300.0	0.00	0.00	8,300.0	4,854.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,400.0	0.00	0.00	8,400.0	4,954.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,500.0	0.00	0.00	8,500.0	5,054.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00
8,600.0	0.00	0.00	8,600.0	5,154.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
8,622.0	0.00	0.00	8,622.0	5,176.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Bone Spring											
8,700.0	0.00	0.00	8,700.0	5,254.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
8,717.0	0.00	0.00	8,717.0	5,271.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Avalon											
8,800.0	0.00	0.00	8,800.0	5,354.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
8,900.0	0.00	0.00	8,900.0	5,454.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
9,000.0	0.00	0.00	9,000.0	5,554.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
9,100.0	0.00	0.00	9,100.0	5,654.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
9,147.0	0.00	0.00	9,147.0	5,701.9	0.0	0.0	802,519.29	485,427.38	0.00	0.00	
Start Build 10.00											
9,150.0	0.30	1.78	9,150.0	5,704.9	0.0	0.0	802,519.29	485,427.39	0.01	10.00	
9,200.0	5.30	1.78	9,199.9	5,754.8	2.4	0.1	802,519.37	485,429.83	2.45	10.00	
9,250.0	10.30	1.78	9,249.4	5,804.3	9.2	0.3	802,519.58	485,436.61	9.22	10.00	
9,300.0	15.30	1.78	9,298.2	5,853.1	20.3	0.6	802,519.92	485,447.68	20.27	10.00	
9,350.0	20.30	1.78	9,345.8	5,900.7	35.6	1.1	802,520.40	485,462.95	35.53	10.00	
9,400.0	25.30	1.78	9,391.9	5,946.8	54.9	1.7	802,521.00	485,482.30	54.87	10.00	
9,450.0	30.30	1.78	9,436.1	5,991.0	78.2	2.4	802,521.73	485,505.60	78.14	10.00	
9,500.0	35.30	1.78	9,478.1	6,033.0	105.3	3.3	802,522.57	485,532.66	105.18	10.00	
9,550.0	40.30	1.78	9,517.6	6,072.5	135.9	4.2	802,523.52	485,563.28	135.76	10.00	
9,555.8	40.88	1.78	9,522.0	6,076.9	139.7	4.4	802,523.64	485,567.06	139.54	10.00	
1st Bone Spring Sand											
9,600.0	45.30	1.78	9,554.3	6,109.2	169.8	5.3	802,524.58	485,597.23	169.67	10.00	
9,650.0	50.30	1.78	9,587.8	6,142.7	206.9	6.4	802,525.74	485,634.23	206.64	10.00	
9,700.0	55.29	1.78	9,618.1	6,173.0	246.6	7.7	802,526.97	485,674.03	246.39	10.00	
9,750.0	60.29	1.78	9,644.7	6,199.6	288.9	9.0	802,528.29	485,716.30	288.62	10.00	
9,800.0	65.29	1.78	9,667.6	6,222.5	333.4	10.4	802,529.68	485,760.73	333.01	10.00	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
9,850.0	70.29	1.78	9,686.5	6,241.4	379.6	11.8	802,531.12	485,806.99	379.21	10.00
9,900.0	75.29	1.78	9,701.2	6,256.1	427.3	13.3	802,532.60	485,854.71	426.89	10.00
9,950.0	80.29	1.78	9,711.8	6,266.7	476.2	14.8	802,534.13	485,903.54	475.67	10.00
10,000.0	85.29	1.78	9,718.1	6,273.0	525.7	16.4	802,535.67	485,953.10	525.18	10.00
10,034.8	88.77	1.78	9,719.9	6,274.8	560.5	17.5	802,536.75	485,987.85	559.89	10.00
Start DLS 1.84 TFO -70.33										
10,100.0	89.18	0.66	9,721.0	6,275.9	625.6	18.9	802,538.14	486,053.01	625.00	1.84
10,200.0	89.80	358.92	9,721.9	6,276.8	725.6	18.5	802,537.77	486,153.00	724.97	1.84
10,232.7	90.00	358.36	9,722.0	6,276.9	758.3	17.7	802,537.00	486,185.66	757.64	1.84
Start 7550.6 hold at 10232.7 MD										
10,300.0	90.00	358.36	9,722.0	6,276.9	825.6	15.8	802,535.07	486,252.96	824.97	0.00
10,400.0	90.00	358.36	9,722.0	6,276.9	925.5	12.9	802,532.20	486,352.92	924.97	0.00
10,500.0	90.00	358.36	9,722.0	6,276.9	1,025.5	10.0	802,529.33	486,452.88	1,024.97	0.00
10,600.0	90.00	358.36	9,722.0	6,276.9	1,125.5	7.2	802,526.46	486,552.84	1,124.97	0.00
10,700.0	90.00	358.36	9,722.0	6,276.9	1,225.4	4.3	802,523.60	486,652.80	1,224.96	0.00
10,800.0	90.00	358.36	9,722.0	6,276.9	1,325.4	1.4	802,520.73	486,752.76	1,324.96	0.00
10,900.0	90.00	358.36	9,722.0	6,276.9	1,425.3	-1.4	802,517.86	486,852.72	1,424.96	0.00
11,000.0	90.00	358.36	9,722.0	6,276.9	1,525.3	-4.3	802,515.00	486,952.68	1,524.96	0.00
11,100.0	90.00	358.36	9,722.0	6,276.9	1,625.3	-7.2	802,512.13	487,052.63	1,624.96	0.00
11,200.0	90.00	358.36	9,722.0	6,276.9	1,725.2	-10.0	802,509.26	487,152.59	1,724.96	0.00
11,300.0	90.00	358.36	9,722.0	6,276.9	1,825.2	-12.9	802,506.39	487,252.55	1,824.96	0.00
11,400.0	90.00	358.36	9,722.0	6,276.9	1,925.1	-15.8	802,503.53	487,352.51	1,924.96	0.00
11,500.0	90.00	358.36	9,722.0	6,276.9	2,025.1	-18.6	802,500.66	487,452.47	2,024.96	0.00
11,600.0	90.00	358.36	9,722.0	6,276.9	2,125.0	-21.5	802,497.79	487,552.43	2,124.95	0.00
11,700.0	90.00	358.36	9,722.0	6,276.9	2,225.0	-24.4	802,494.92	487,652.39	2,224.95	0.00
11,800.0	90.00	358.36	9,722.0	6,276.9	2,325.0	-27.2	802,492.06	487,752.35	2,324.95	0.00
11,900.0	90.00	358.36	9,722.0	6,276.9	2,424.9	-30.1	802,489.19	487,852.31	2,424.95	0.00

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
12,000.0	90.00	358.36	9,722.0	6,276.9	2,524.9	-33.0	802,486.32	487,952.26	2,524.95	0.00	
12,100.0	90.00	358.36	9,722.0	6,276.9	2,624.8	-35.8	802,483.46	488,052.22	2,624.95	0.00	
12,200.0	90.00	358.36	9,722.0	6,276.9	2,724.8	-38.7	802,480.59	488,152.18	2,724.95	0.00	
12,300.0	90.00	358.36	9,722.0	6,276.9	2,824.8	-41.6	802,477.72	488,252.14	2,824.95	0.00	
12,400.0	90.00	358.36	9,722.0	6,276.9	2,924.7	-44.4	802,474.85	488,352.10	2,924.95	0.00	
12,500.0	90.00	358.36	9,722.0	6,276.9	3,024.7	-47.3	802,471.99	488,452.06	3,024.94	0.00	
12,600.0	90.00	358.36	9,722.0	6,276.9	3,124.6	-50.2	802,469.12	488,552.02	3,124.94	0.00	
12,700.0	90.00	358.36	9,722.0	6,276.9	3,224.6	-53.0	802,466.25	488,651.98	3,224.94	0.00	
12,800.0	90.00	358.36	9,722.0	6,276.9	3,324.6	-55.9	802,463.38	488,751.94	3,324.94	0.00	
12,900.0	90.00	358.36	9,722.0	6,276.9	3,424.5	-58.8	802,460.52	488,851.89	3,424.94	0.00	
13,000.0	90.00	358.36	9,722.0	6,276.9	3,524.5	-61.6	802,457.65	488,951.85	3,524.94	0.00	
13,100.0	90.00	358.36	9,722.0	6,276.9	3,624.4	-64.5	802,454.78	489,051.81	3,624.94	0.00	
13,200.0	90.00	358.36	9,722.0	6,276.9	3,724.4	-67.4	802,451.91	489,151.77	3,724.94	0.00	
13,300.0	90.00	358.36	9,722.0	6,276.9	3,824.3	-70.2	802,449.05	489,251.73	3,824.94	0.00	
13,400.0	90.00	358.36	9,722.0	6,276.9	3,924.3	-73.1	802,446.18	489,351.69	3,924.93	0.00	
13,500.0	90.00	358.36	9,722.0	6,276.9	4,024.3	-76.0	802,443.31	489,451.65	4,024.93	0.00	
13,600.0	90.00	358.36	9,722.0	6,276.9	4,124.2	-78.8	802,440.45	489,551.61	4,124.93	0.00	
13,700.0	90.00	358.36	9,722.0	6,276.9	4,224.2	-81.7	802,437.58	489,651.57	4,224.93	0.00	
13,800.0	90.00	358.36	9,722.0	6,276.9	4,324.1	-84.6	802,434.71	489,751.52	4,324.93	0.00	
13,900.0	90.00	358.36	9,722.0	6,276.9	4,424.1	-87.4	802,431.84	489,851.48	4,424.93	0.00	
14,000.0	90.00	358.36	9,722.0	6,276.9	4,524.1	-90.3	802,428.98	489,951.44	4,524.93	0.00	
14,100.0	90.00	358.36	9,722.0	6,276.9	4,624.0	-93.2	802,426.11	490,051.40	4,624.93	0.00	
14,200.0	90.00	358.36	9,722.0	6,276.9	4,724.0	-96.0	802,423.24	490,151.36	4,724.93	0.00	
14,300.0	90.00	358.36	9,722.0	6,276.9	4,823.9	-98.9	802,420.37	490,251.32	4,824.92	0.00	
14,400.0	90.00	358.36	9,722.0	6,276.9	4,923.9	-101.8	802,417.51	490,351.28	4,924.92	0.00	
14,500.0	90.00	358.36	9,722.0	6,276.9	5,023.9	-104.7	802,414.64	490,451.24	5,024.92	0.00	
14,600.0	90.00	358.36	9,722.0	6,276.9	5,123.8	-107.5	802,411.77	490,551.20	5,124.92	0.00	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
14,700.0	90.00	358.36	9,722.0	6,276.9	5,223.8	-110.4	802,408.91	490,651.15	5,224.92	0.00	
14,800.0	90.00	358.36	9,722.0	6,276.9	5,323.7	-113.3	802,406.04	490,751.11	5,324.92	0.00	
14,900.0	90.00	358.36	9,722.0	6,276.9	5,423.7	-116.1	802,403.17	490,851.07	5,424.92	0.00	
15,000.0	90.00	358.36	9,722.0	6,276.9	5,523.7	-119.0	802,400.30	490,951.03	5,524.92	0.00	
15,100.0	90.00	358.36	9,722.0	6,276.9	5,623.6	-121.9	802,397.44	491,050.99	5,624.92	0.00	
15,200.0	90.00	358.36	9,722.0	6,276.9	5,723.6	-124.7	802,394.57	491,150.95	5,724.91	0.00	
15,300.0	90.00	358.36	9,722.0	6,276.9	5,823.5	-127.6	802,391.70	491,250.91	5,824.91	0.00	
15,400.0	90.00	358.36	9,722.0	6,276.9	5,923.5	-130.5	802,388.83	491,350.87	5,924.91	0.00	
15,500.0	90.00	358.36	9,722.0	6,276.9	6,023.4	-133.3	802,385.97	491,450.83	6,024.91	0.00	
15,600.0	90.00	358.36	9,722.0	6,276.9	6,123.4	-136.2	802,383.10	491,550.78	6,124.91	0.00	
15,700.0	90.00	358.36	9,722.0	6,276.9	6,223.4	-139.1	802,380.23	491,650.74	6,224.91	0.00	
15,800.0	90.00	358.36	9,722.0	6,276.9	6,323.3	-141.9	802,377.37	491,750.70	6,324.91	0.00	
15,900.0	90.00	358.36	9,722.0	6,276.9	6,423.3	-144.8	802,374.50	491,850.66	6,424.91	0.00	
16,000.0	90.00	358.36	9,722.0	6,276.9	6,523.2	-147.7	802,371.63	491,950.62	6,524.91	0.00	
16,100.0	90.00	358.36	9,722.0	6,276.9	6,623.2	-150.5	802,368.76	492,050.58	6,624.90	0.00	
16,200.0	90.00	358.36	9,722.0	6,276.9	6,723.2	-153.4	802,365.90	492,150.54	6,724.90	0.00	
16,300.0	90.00	358.36	9,722.0	6,276.9	6,823.1	-156.3	802,363.03	492,250.50	6,824.90	0.00	
16,400.0	90.00	358.36	9,722.0	6,276.9	6,923.1	-159.1	802,360.16	492,350.46	6,924.90	0.00	
16,500.0	90.00	358.36	9,722.0	6,276.9	7,023.0	-162.0	802,357.29	492,450.41	7,024.90	0.00	
16,600.0	90.00	358.36	9,722.0	6,276.9	7,123.0	-164.9	802,354.43	492,550.37	7,124.90	0.00	
16,700.0	90.00	358.36	9,722.0	6,276.9	7,223.0	-167.7	802,351.56	492,650.33	7,224.90	0.00	
16,800.0	90.00	358.36	9,722.0	6,276.9	7,322.9	-170.6	802,348.69	492,750.29	7,324.90	0.00	
16,900.0	90.00	358.36	9,722.0	6,276.9	7,422.9	-173.5	802,345.82	492,850.25	7,424.89	0.00	
17,000.0	90.00	358.36	9,722.0	6,276.9	7,522.8	-176.3	802,342.96	492,950.21	7,524.89	0.00	
17,100.0	90.00	358.36	9,722.0	6,276.9	7,622.8	-179.2	802,340.09	493,050.17	7,624.89	0.00	
17,200.0	90.00	358.36	9,722.0	6,276.9	7,722.7	-182.1	802,337.22	493,150.13	7,724.89	0.00	
17,300.0	90.00	358.36	9,722.0	6,276.9	7,822.7	-184.9	802,334.36	493,250.09	7,824.89	0.00	

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
17,400.0	90.00	358.36	9,722.0	6,276.9	7,922.7	-187.8	802,331.49	493,350.04	7,924.89	0.00
17,500.0	90.00	358.36	9,722.0	6,276.9	8,022.6	-190.7	802,328.62	493,450.00	8,024.89	0.00
17,600.0	90.00	358.36	9,722.0	6,276.9	8,122.6	-193.5	802,325.75	493,549.96	8,124.89	0.00
17,700.0	90.00	358.36	9,722.0	6,276.9	8,222.5	-196.4	802,322.89	493,649.92	8,224.89	0.00
17,783.2	90.00	358.36	9,722.0	6,276.9	8,305.7	-198.8	802,320.50	493,733.09	8,308.08	0.00

TD at 17783.2 - 5 1/2" Production Casing

Casing Points

Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")
1,247.0	1,247.0	13 3/8" Surface Casing	13-3/8	17-1/2
17,783.2	9,722.0	5 1/2" Production Casing	5-1/2	8-3/4
5,072.0	5,072.0	9 5/8" Intermediate Casing	9-5/8	12-1/4
120.0	120.0	20" Conductor	20	26

Morcor Engineering

Morcor Standard Plan

Kaiser-Francis Oil Company

Company:	Kaiser Francis	Local Co-ordinate Reference:	Well Bell Lake Unit North 135H
Project:	Bell Lake Unit North 135H	TVD Reference:	WELL @ 3445.1usft (Original Well Elev)
Site:	Bell Lake Unit North 135H	MD Reference:	WELL @ 3445.1usft (Original Well Elev)
Well:	Bell Lake Unit North 135H	North Reference:	Grid
Wellbore:	Bell Lake Unit North 135H	Survey Calculation Method:	Minimum Curvature
Design:	190621 Bell Lake Unit North 135H	Database:	EDM 5000.1 Single User Db

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
7,522.0	7,522.0	Brushy Canyon		0.00		
8,717.0	8,717.0	Avalon		0.00		
1,822.0	1,822.0	Top of Salt		0.00		
1,222.0	1,222.0	Rustler		0.00		
4,722.0	4,722.0	Base of Salt		0.00		
9,555.8	9,522.0	1st Bone Spring Sand		0.00		
8,622.0	8,622.0	Bone Spring		0.00		
5,172.0	5,172.0	Bell Canyon		0.00		
6,197.0	6,197.0	Cherry Canyon		0.00		
4,972.0	4,972.0	Lamar		0.00		
1,622.0	1,622.0	Salado		0.00		

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
9,147.0	9,147.0	0.0	0.0	Start Build 10.00	
10,034.8	9,719.9	560.5	17.5	Start DLS 1.84 TFO -70.33	
10,232.7	9,722.0	758.3	17.7	Start 7550.6 hold at 10232.7 MD	
17,783.2	9,722.0	8,305.7	-198.8	TD at 17783.2	

Checked By: _____ Approved By: _____ Date: _____

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	KAISER FRANCIS OIL COMPANY
LEASE NO.:	NMNM0000587
WELL NAME & NO.:	BELL LAKE UNIT NORTH 135H
SURFACE HOLE FOOTAGE:	1925'/S & 1275'/E
BOTTOM HOLE FOOTAGE:	330'/N & 1410'/E
LOCATION:	Section 5, T.23 S., R.34 E., NMPM
COUNTY:	Lea County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input checked="" type="checkbox"/> Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

1. The **13-3/8** inch surface casing shall be set at approximately **1700 feet** (a minimum of 25 feet (Lea County) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8**

hours or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)

- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The **9-5/8** inch intermediate casing shall be set at **5072 feet**. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.

3. The minimum required fill of cement behind the **5-1/2** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).

2. BOP Requirements

Option 1

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M)** psi.

- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **3000 (3M)** psi.

Option 2

Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **10,000 (10M)** psi. **Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.**

- a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
- b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- c. Manufacturer representative shall install the test plug for the initial BOP test.
- d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Unit Wells

The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number when the sign is replaced.

Commercial Well Determination

A commercial well determination shall be submitted after production has been established for at least six months. (This is not necessary for secondary recovery unit wells)

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.

7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.

- a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

RI12222020

**KAISER-FRANCIS OIL COMPANY
HYDROGEN SULFIDE (H₂S) CONTINGENCY PLAN
FOR DRILLING/COMPLETION WORKOVER/FACILITY**

**Bell Lake Unit North
SECTION 1 -T23S-R33E
SECTION 6 -T23S-R34E
SECTION 5 -T23S-R34E**

LEA COUNTY, NM

This well/facility is not expected to have H₂S, but due to the sensitive location, the following is submitted as requested.

TABLE OF CONTENTS

Emergency Response Activation and General Responsibilities	3
Individual Responsibilities During An H ₂ S Release	4
Procedure For Igniting An Uncontrollable Condition	5
Emergency Phone Numbers	6
Protection Of The General Public/Roe	7
Characteristics Of H ₂ S And SO ₂	8
Training	8
Public Relations	8
Maps	

EMERGENCY RESPONSE ACTIVATION AND GENERAL RESPONSIBILITIES

Activation of the Emergency Action Plan

In the event of any emergency situation, all personnel on location should first ensure that the following items are initiated. After that, they should refer to the appropriate Specific Emergency Guidance sections below for further responsibilities:

1. Notify the senior ranking contract representative on site.
2. Notify Kaiser-Francis representative in charge.
3. Notify civil authorities if the Kaiser-Francis Representative cannot be contacted and the situation dictates.
4. Perform rescue and first aid as required (without jeopardizing additional personnel).

General Responsibilities

In the event of an H₂S emergency, the following plan will be initiated.

- 1) All personnel will immediately evacuate to an up-wind and if possible up-hill "safe area".
- 2) If for any reason a person must enter the hazardous area, they must wear a SCBA (Self contained breathing apparatus).
- 3) Always use the "buddy system".
- 4) Isolate the well/problem if possible.
- 5) Account for all personnel
- 6) Display the proper colors, warning all unsuspecting personnel of the danger at hand
- 7) Contact the Company personnel as soon as possible if not at the location. (use the enclosed call list as instructed)

At this point the company representative will evaluate the situation and coordinate the necessary duties to bring the situation under control, and if necessary, the notification of emergency response agencies and residents.

INDIVIDUAL RESPONSIBILITIES DURING AN H₂S RELEASE

The following procedures and responsibilities will be implemented on activation of the H₂S siren and lights.

All Personnel:

1. On alarm, don escape unit (if available) and report to upwind briefing area.

Rig Manager/Tool Pusher:

1. Check that all personnel are accounted for and their condition.
2. Administer or arrange for first aid treatment, and/or call EMTs as needed.
3. Identify two people best suited to secure well and perform rescue, and instruct them to don SCBA.
4. Notify Contract management and Kaiser-Francis Representative.
5. Remain at the briefing area, assess and monitor personnel and overall situation for hazards or conditions that might warrant a change in the action plan.

Two People Responsible for Shut-in and Rescue:

1. Don SCBA and acquire tools to secure well and perform rescue, i.e., wrenches, retrieval ropes, etc.
2. Utilize the buddy system to secure well and perform rescue(s).
3. Return to the briefing area and stand by for further instructions.

All Other Personnel:

1. Isolate the area and prevent entry by other persons into the 100 ppm ROE. Additionally the first responder(s) must evacuate any public places encompassed by the 100 ppm ROE. First responder(s) must take care not to injure themselves during this operation. Company and/or local officials must be contacted to aid in this operation. Evacuation of the public should be beyond the 100 ppm ROE.

Kaiser-Francis Oil Company Representative:

1. Remain at the briefing area, assess and monitor personnel and overall situation for hazards or conditions that might warrant a change in the action plan.
2. Notify company management or Local Incident Commander, and Police, Fire Department, or other local emergency services as required.

PROCEDURE FOR IGNITING AN UNCONTROLLABLE CONDITION:

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police shall be the Incident Command of any major release.

The decision to ignite a well should be a last resort and one if not both of the following pertain.

- 1) Human life and/or property are in danger.
- 2) There is no hope of bringing the situation under control with the prevailing conditions at the site.

INSTRUCTIONS FOR IGNITION:

- 1) Two people are required. They must be equipped with positive pressure; self contained breathing apparatus and a "D"-ring style, full body, OSHA approved safety harness. Non-flammable rope will be attached.
- 2) One of the people will be a qualified safety person who will test the atmosphere for H₂S, Oxygen, & LFL. The other person will be the company supervisor; he is responsible for igniting the well.
- 3) Ignite up-wind from a distance no closer than necessary. Make sure that where you ignite from has the maximum escape avenue available. A 25mm flare gun shall be used, with a +/-500' range to ignite the gas.
- 4) Prior to ignition, make a final check for combustible gases.
- 5) Following ignition, continue with the emergency actions & procedures as before.

CONTACTING AUTHORITIES

Kaiser-Francis personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. This response plan must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER).

EMERGENCY CALL LIST: (Start and continue until ONE of these people have been reached)

	<u>OFFICE</u>	<u>MOBILE</u>
Kaiser-Francis Oil Co.	918/494-0000	
Bill Wilkinson	580/668-2335	580/221-4637
David Zerger	918/491-4350	918/557-6708
Charles Lock	918/491-4337	918/671-6510
Stuart Blake	918/491-4347	918/510-4126
Robert Sanford	918/491-4201	918/770-2682
Eric Hansen	918/491-4339	918/527-5260

EMERGENCY RESPONSE NUMBERS: Lea County, New Mexico

State Police – Artesia	575/748-9718
State Police – Hobbs	575/392-5580
State Police – Carlsbad	575/885-3138
Lea County Sheriff - Lovington	575/396-3611
Local Emergency Planning Center – Lea County	575/396-8607
Local Emergency Planning Center – Eddy County	575/885-3581
Fire Fighting, Rescue & Ambulance – Carlsbad	911 or 575/885-3125
Fire Fighting, Rescue & Ambulance – Hobbs	911 or 575/397-9308
Fire Fighting – Jal Volunteer Fire Department	911 or 505/395-2221
New Mexico Oil & Gas Commission – Artesia	575/748-1283
New Mexico Oil & Gas Commission – Hobbs	575/393-6161
Air Medical Transport Services – Hobbs	800/550-1025
Med Flight Air Ambulance – Albuquerque	505/842-4433
Angel MedFlight	844/553-9033
DXP	432/580-3770
BJ Services	575/392-5556
Halliburton	575/392-6531 800/844-8451

CHARACTERISTICS OF H₂S AND SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air = 1	10 ppm	100 ppm	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air = 1	2 ppm	N/A	1000 ppm

TRAINING:

All responders must have training in the detection of H₂S measures for protection against the gas, equipment used for protection and emergency response. Weekly drills by all crews will be conducted and recorded in the IADC daily log. Additionally, responders must be equipped with H₂S monitors at all times.

PUBLIC RELATIONS

Kaiser-Francis recognizes that the news media have a legitimate interest in incidents at Kaiser-Francis facilities that could affect the public. It is to the company's benefit to cooperate with the news media when incidents occur because these media are our best liaison with the public.

Our objective is to see that all reports of any emergency are factual and represent the company's position fairly and accurately. Cooperation with news media representatives is the most reliable guarantee that this objective will be met.

All contract and Kaiser-Francis employees are instructed **NOT** to make any statement to the media concerning the emergency incident. If a media representative contacts any employee, they should refer them to the designated Emergency Command Center where they should contact the Incident Commander or his designated relief for any information concerning the incident.

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 185480

CONDITIONS

Operator: KAISER-FRANCIS OIL CO PO Box 21468 Tulsa, OK 74121146	OGRID:	12361
	Action Number:	185480
	Action Type:	[C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104	2/14/2023
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	2/14/2023
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system	2/14/2023
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing	2/14/2023