SIGNATURE

Type or print name

For State Use Only:

APPROVED BY:

Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 327871 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** Phone:(575) 748-1283 Fax:(575) 748-9720 30-025-49741 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS NORTH HOBBS G/SA UNIT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 979 2. Name of Operator 9. OGRID Number OCCIDENTAL PERMIAN LTD 157984 3. Address of Operator 10. Pool name or Wildcat P.O. Box 4294, Houston, TX 772104294 4. Well Location Section <u>A</u> : <u>740</u> feet from the N line and feet 328 from the E 38E NMPM Township 18S Range County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3640 GR Pit or Below-grade Tank Application or Closure ___ Distance from nearest fresh water well_ ___ Depth to Groundwater____ _ Distance from nearest surface water Pit Type mil Below-Grade Tank: Volume_ __ bbls; Construction Material_ Pit Liner Thickness: 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. see comments9/16/2022 Spudded well. **Casing and Cement Program** Date Strina Fluid Hole Weight Fst Dpth Sacks Class Pres Pres Open Type Size Size lb/ft TOC Set Dpth Held Drop Hole 09/17/22 Surf 13.5 9.625 36 J55 0 1485 895 1.9 C 09/21/22 Prod 8.75 29 L80 0 4639 1100 1.28 С I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square

Manager Regulatory

Petroleum Specialist - A

kelley_montgomery@oxy.com

DATE

DATE

Telephone No.

10/25/2022

713-366-5716

2/28/2023 2:42:52 PM

TITLE

E-mail address

Electronically Signed

Sarah K McGrath

KELLEY MONTGOMERY

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 327871

COMMENTS

Operator:	OGRID:
OCCIDENTAL PERMIAN LTD	157984
P.O. Box 4294	Action Number:
Houston, TX 772104294	327871
	Action Type:
	[C-103] EP Drilling / Cement

Comments

Created By	Comment	Comment Date
	Spud 13-1/2" hole 09/16/22, drill to 1505' 09/17/22. RIH & set 9-5/8" 36# J-55 LTC csg @ 1485', pump 30bbl gel spacer then cmt w/ 515sx (174bbl) Class C w/ additives 12.9ppg 1.9 yield, followed by 380sx (91bbl) Class C w/ additives 14.8ppg 1.35 yield, full returns throughout job, circ 210sx (71bbl) cmt to surface, WOC.	10/25/2022
	09/18/22 RU BOP, test @ 250# low 3000# high, test 9-5/8" casing to 1800# for 30 min, good test. RIH & drill new formation to 1622'. 09/19/22 drill 8-3/4" hole to 4664'MD, 09/20/22. RIH & set 7" 29# L-80 LTC csg @ 4639', DVT @ 3896', pump 40bbl gel spacer then lead cmt w/ 140sx (32bbl) Class C w/ additives 14.5ppg 1.28 yield, followed by 2nd stage cmt w/ 870sx (279bbl) Class C w/ additives 12ppg 1.8 yield, followed by 90sx (21bbl) Class C w/ additives 14.5ppg 1.28 yield, circ 280sx (90bbl) cmt to surf, WOC. ND BOP, RD Rel Rig 09/22/22.	10/25/2022