Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 330620 District II WELL APLNIIMBER 811 S. First St., Artesia, NM 88210 **Oil Conservation Division** 30-025-49767 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS NORTH HOBBS G/SA UNIT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 978 2. Name of Operator 9. OGRID Number OCCIDENTAL PERMIAN LTD 157984 3. Address of Operator 10. Pool name or Wildcat P.O. Box 4294, Houston, TX 772104294 4. Well Location Unit Letter I : 1662 feet from the S Section 31 Township line and feet 901 from the E Township 18S Range 38E NMPM County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3634 GR Pit or Below-grade Tank Application or Closure ___ Distance from nearest fresh water well__ _ Distance from nearest surface water ___ Depth to Groundwater____ Pit Type ___ bbls; Construction Material_ Pit Liner Thickness: mil Below-Grade Tank: Volume 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ ALTER CASING REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. See comments10/16/2022 Spudded well. **Casing and Cement Program**

Date	String	Fluid Type	Hole Size	Csg Size	Weight lb/ft	Grade	Est TOC	Dpth Set	Sacks	Yield	Class	1" Dpth	Pres Held	Pres Drop	Open Hole
10/17/22	Surf		13.5	9.625	36	J-55	0	1517	895	1.9	С				
10/19/22	Prod		8.75	7	29	L-80	0	4520	1115	1.28	С				
I hereby certify tha NMOCD guidelines							ef. I further	certify that ar	y pit or below	-grade tank	has been/wi	II be constru	ucted or clo	sed accord	ing to

SIGNATURE <u>Electronically Signed</u> TITLE <u>Manager Regulatory</u> DATE <u>1/5/2023</u>

Type or print name KELLEY MONTGOMERY E-mail address kelley_montgomery@oxy.com Telephone No. 713-366-5716

For State Use Only:

 APPROVED BY:
 Sarah K McGrath
 TITLE
 Petroleum Specialist - A
 DATE
 2/28/2023 1:56:11 PM

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 330620

COMMENTS

Operator:	OGRID:
OCCIDENTAL PERMIAN LTD	157984
P.O. Box 4294	Action Number:
Houston, TX 772104294	330620
	Action Type:
	[C-103] EP Drilling / Cement

Comments

Created By	Comment	Comment Date
	Spud 13-1/2" hole 10/16/22, drill to 1532' 10/17/22. RIH & set 9-5/8" 36# J-55 LTC csg @ 1517', pump 30bbl gel spacer then cmt w/ 520sx (176bbl) Class C w/ additives 12.9ppg 1.9 yield, followed by 375sx (90bbl) Class C w/ additives 14.8ppg 1.35 yield, full returns throughout job, circ 233sx (90bbl) cmt to surface, WOC.	1/4/2023
ronimathew	10/17/22 RU BOP, test @ 250# low 3000# high, test 9-5/8" casing to 1800# for 30 min, good test. RIH & drill new formation to 1594'. 10/19/22 drill 8-3/4" hole to 4619'MD, 10/19/22. RIH & set 7" 29# L-80 LTC csg @ 4520', DVT @ 3834', pump 40bbl gel spacer then lead cmt w/ 140sx (32bbl) Class C w/ additives 14.5ppg 1.28 yield, followed by 2nd stage cmt w/ 885sx (284bbl) Class C w/ additives 12ppg 1.8 yield, followed by 90sx (21bbl) Class C w/ additives 14.5ppg 1.28 yield, circ 436sx (140bbl) cmt to surf, WOC. ND BOP, RD Rel Rig 10/21/22.	