U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Sundry Print Report

Well Name: DOME NAVAJO 21-27-13

Well Location: T27N / R13W / SEC 21 / SWSW / 36.556519 / -108.229034

County or Parish/State: SAN

JUAN / NM

Well Number: 3

Type of Well: CONVENTIONAL GAS

WELL

Allottee or Tribe Name: EASTERN NAVAJO

Lease Number: N00C14207481

Unit or CA Name:

Unit or CA Number:

US Well Number: 300452384700S1

Well Status: Gas Well Shut In

Operator: DUGAN PRODUCTION CORPORATION

Notice of Intent

Sundry ID: 2724121

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 04/03/2023

Time Sundry Submitted: 02:33

Date proposed operation will begin: 05/08/2023

Procedure Description: Dugan Production Corp. requests permission to plug and abandon the well per the following procedure: 1) TOOH w/1½" tubing. RU wireline services. Set 2-7/8" bridge plug @ 1272'. Perforations @ 1322'-1338'. Load hole. Pressure test casing to 600 psi. 2) Spot & circulate cement to surface from 1272' w/38 sks (43.7 cu ft) Class G cement (1.15 cu ft/sk, 15.8#/gal). WOC 4 hrs. Plug I, inside 2-7/8", 38 sks, 43.7 cu ft, Pictured Cliffs-Fruitland-Kirtland-Ojo Alamo-surface, 0-1272'. 3) Cut wellhead off. Tag TOC @ surface inside 2-7/8" casing and in 5½"-2-7/8" annulus. Top off cement if needed. 4) Install below ground plate for dry hole marker as it is in NAPI surface. 5) Clean location and move.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Dome_Navajo_21_27_13_3_PA_Reclamation_Plan_20230403142627.pdf

 $Dome_Navajo_21_27_13_3_PA_formation_tops_20230403142558.pdf$

Dome_Navajo_21_27_13_3_PA_planned_wellbore_schematic_20230403142540.pdf

Dome_Navajo_21_27_13_3_PA_wellbore_schematic_current_20230403142514.pdf

Dome_Navajo_21_27_13_3_PA_Plan_20230403142227.pdf

Accepted for record – NMOCD

JRH

04/17/23

Well Name: DOME NAVAJO 21-27-13

Well Location: T27N / R13W / SEC 21 / SWSW / 36.556519 / -108.229034

/ County or Parish/State: SAN JUAN / NM

Well Number: 3

Type of Well: CONVENTIONAL GAS WELL

Allottee or Tribe Name: EASTERN NAVAJO

Lease Number: N00C14207481

Unit or CA Name:

Unit or CA Number:

US Well Number: 300452384700S1

Well Status: Gas Well Shut In

Operator: DUGAN PRODUCTION CORPORATION

Conditions of Approval

Specialist Review

2724121_NOIA_21_27_13_3_3004523847_KR_04032023_20230403170745.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: TYRA FEIL

Signed on: APR 03, 2023 01:58 PM

Name: DUGAN PRODUCTION CORPORATION

Title: Authorized Representative **Street Address:** PO Box 420

City: Farmington

State: NM

Phone: (505) 325-1821

Email address: tyrafeil@duganproduction.com

Field

Representative Name: ALIPH REENA

Street Address: PO BOX 420

City: FARMINGTON

State: NM

Zip: 87499-0420

Phone: (505)325-1821

Email address: Aliph.Reena@duganproduction.com

BLM Point of Contact

BLM POC Name: KENNETH G RENNICK

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5055647742

BLM POC Email Address: krennick@blm.gov

Disposition: Approved

Disposition Date: 04/03/2023

Signature: Kenneth Rennick


Dugan Production Corp. request permission to Plug and Abandon the well per the following procedure.

- TOOH w/1¼" tubing. RU WL services. Set 2-7/8" bridge plug @ 1272'. Perforations @ 1322'-1338'. Load hole. Pressure test casing to 600 psi.
- Spot and circulate cement to surface from 1272' w/38 sks (43.7 cu ft) Class G cement (1.15 cu ft/sk, 15.8 #/gal). WOC 4 hrs. Plug I, Inside 2-7/8", 38 sks, 43.7 cu ft, Pictured Cliffs-Fruitland-Kirtland-Ojo Alamo-Surface, 0-1272'.
- Cut wellhead off. Tag TOC @ surface inside 2-7/8" casing and in 5½"-2-7/8" annulus. Top off cement if needed.
- Install below ground plate for dry hole marker as it is NAPI surface.
- Clean location and move.

Current Wellbore Schematic

Dome Navajo 21-27-13 # 3
API: 30-045-23847
1120' FSL & 1120' FWL
Sec 21, T27N R13W
San Juan County, NM
126 FF6F087 Long: 108 220682

Lat: 36.5565987, Long: -108.2296829



5 ½", 15.5# Casing Set @ 107'. Cemented w/ 35 sks Cement. Circulate cement to surface. Hole size 8-3/4"

2-7/8" 6.5# J-55 Casing Set @ 1473' GL.
Cemented w/ 125 sks 6% 65/35 cement, & 50 sks Class B.
Circulated cement to surface. Hole size: 4-3/4"


1-1/4" tubing @ 1330

Pictured cliffs Perfs @ 1322'-1338'

TD @ 1484', PBTD @ 1444'

Planned P & A Schematic

Dome Navajo 21-27-13 # 3 API: 30-045-23847 1120' FSL & 1120' FWL Sec 21, T27N R13W San Juan County, NM Lat: 36.5565987, Long: -108.2296829



5 ½", 15.5# Casing Set @ 107'. Cemented w/ 35 sks Cement. Circulate cement to surface. Hole size 8-3/4"

2-7/8" 6.5# J-55 Casing Set @ 1473' GL. Cemented w/ 125 sks 6% 65/35 cement, & 50 sks Class B. Circulated cement to surface. Hole size: 4-3/4"

Spot Plug I from above BP @ 1272' to surface w/ 38 sks Class G neat cement (43.7 Cu.ft).

Pictured Cliffs-Fruitland-Kirtland-Ojo Alamo-Surface. 0-1272'

Pictured cliffs Perfs @ 1322'-1338'

TD @ 1484', PBTD @ 1444'

Formation Tops

- Ojo Alamo Surface
- Kirtland 240
- Fruitland 870
- Pictured Cliffs 1280

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FARMINGTON DISTRICT OFFICE

6251 COLLEGE BLVD. FARMINGTON, NEW MEXICO 87402

AFMSS 2 Sundry ID 2724121

Attachment to notice of Intention to Abandon

Well: Dome Navajo 21-27-13 3

BLM Geology Report not completed. Complete wellbore fill up is proposed.

CONDITIONS OF APPROVAL

- Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal and Indian Lease."
- 2. Farmington Office is to be notified at least 24 hours before the plugging operations commence at (505) 564-7750.

You are also required to place cement excesses per 4.2 and 4.4 of the attached General Requirements.

Office Hours: 7:45 a.m. to 4:30 p.m.

K. Rennick 4/3/2023

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 203782

CONDITIONS

Operator:	OGRID:
DUGAN PRODUCTION CORP	6515
PO Box 420	Action Number:
Farmington, NM 87499	203782
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By		Condition Date
john.harrisc	n None	4/17/2023