<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 **District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form C-101 August 1, 2011

Permit 339830

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZON	ΙE
---	----

AT LICATION FOR ENAMED TO BRIEF, RE-ENTER, DEEL EN, T ECOBACIT, OR ADD A ZONE								
Operator Name and Address	2. OGRID Number							
AMEREDEV OPERATING, LLC	AMEREDEV OPERATING, LLC							
2901 Via Fortuna	3. API Number							
Austin, TX 78746	30-025-51474							
4. Property Code	5. Property Name	6. Well No.						
331807	AZALEA 26 36 28 STATE COM	383H						

7 Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	28	26S	36E	В	330	N	1960	E	Lea

8. Proposed Bottom Hole Location

ſ	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	G	33	26S	36E	2	50	S	1650	E	Lea

9. Pool Information

WC-025 G-08 S263620C;LWR BONE SPRIN	98150

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lease Type	15. Ground Level Elevation
New Well	OIL		State	2906
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
N 18780		3rd Bone Spring Carbonate		1/1/2024
Depth to Ground water		Distance from nearest fresh water well	Distance to nearest surface water	

■ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Туре	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC	
Surf	17.5	7.5 13.375		1856	1512	0	
Int1	9.875	7.625	29.7	10947	2399	0	
Prod	6.75	5.5	23	18780	1462	0	

Casing/Cement Program: Additional Comments

22. Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
Double Ram	5000	5000	TBD

knowledge and be I further certify I	pelief. have complied with 19.15.14.9 (A	is true and complete to the best of my NMAC ⊠ and/or 19.15.14.9 (B) NMAC		OIL CONSERVATION	ON DIVISION	
Signature: Printed Name:	Electronically filed by Christie	Hanna	Approved By:	Paul F Kautz		
Title:	Regulatory		Title:	Geologist		
Email Address:	channa@ameredev.com		Approved Date:	5/19/2023	Expiration Date: 5/19/2025	
Date:	5/9/2023	Conditions of Approval Attached				

District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720 Phone: (3/5) /48-1283 hax; (3/5) /48-9/20 District III 1000 Rio Brazos Road, Aztec, NM 87410 Phone: (505) 334-6178 Fax; (505) 334-6170 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3460 Fax; (505) 476-3462

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

FORM C-102 Revised August 1, 2011 Submit one copy to appropriate **District Office**

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number		² Pool Code	³ Pool Name				
30-025- 51474		98150	98150 WC-025 G-08 S263620C; LWR E				
⁴ Property Code		⁵ Pr	operty Name	⁶ Well Number			
331807		AZALEA 26 3	36 28 STATE COM	383H			
⁷ OGRID N₀.		⁸ O _I	perator Name	⁹ Elevation			
372224		AMEREDEV	OPERATING, LLC.	2906'			
100							


¹⁰Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
В	28	26-S	36-E	_	330'	NORTH	1960'	EAST	LEA
11D W TILL C TEDIES AD C C									

¹¹Bottom Hole Location If Different From Surface

UL or lot no.	Section	Section Township		Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
2	33	26-S	26-S 36-E		50'	SOUTH	1650'	EAST	LEA
¹² Dedicated Acres 233.72	¹³ Joint or I	Infill ¹⁴ Co	nsolidation Co	de ¹⁵ Ord	er No.				

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

Form APD Conditions

Permit 339830

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
AMEREDEV OPERATING, LLC [372224]	30-025-51474
2901 Via Fortuna	Well:
Austin, TX 78746	AZALEA 26 36 28 STATE COM #383H

OCD Reviewer	Condition
pkautz	Notify OCD 24 hours prior to casing & cement
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
pkautz	Cement is required to circulate on both surface and intermediate1 strings of casing
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud



Wellbore Schematic

Well: Azalea 26 36 28 State Com 383H
SHL: Sec. 28 26S-36E 330' FNL & 1960' FEL
BHL: Sec. 33 26S-36E 50' FSL & 1650' FEL

Lea, NM

Wellhead: A - 13-5/8" 10M x 13-5/8" SOW

B - 13-5/8" 10M x 13-5/8" 10M C - 13-5/8" 10M x 13-5/8" 10M

Tubing Spool - 7-1/16" 15M x 13-3/8" 10M

Xmas Tree: 2-9/16" 10M

Tubing: 2-7/8" L-80 6.5# 8rd EUE

Co. Well ID: XXXXXX

AFE No.: XXXX-XXX

API No.: XXXXXXXXXXXX

GL: 2,906' Field: Delaware

Objective: Third Bone Spring

TVD: 10,900' **MD:** 18,780'

Rig: TBD KB 27'

E-Mail: Wellsite2@ameredev.com

Hole Size	Formation Tops	Logs Cement	Mud Weight
17.5"	Rustler 1,731' 13.375" 68# J-55 BTC 1,856'	1,512 Sacks TOC 0' 100% Excess	8.4-8.6 ppg WBM
	Salado 2,100' DV Tool with ACP 3,239'	819 Sacks TOC 0' 50% Excess	
12.25"	Tansill 3,239'		
12.23	Capitan Reef 3,726'		디
	Lamar 4,925'		ulsic
	Bell Canyon 5,095'		Εm
	No Casing 5,050']	3rine
	Brushy Canyon 7,024'		7.5-9.4 Diesel Brine Emulsion
	Bone Spring Lime 8,010'		.5-9.
9.875"	First Bone Spring 9,554'		7
	Second Bone Spring 10,171'		
	Third Bone Spring Carbonate 10,822'	2,399 Sacks TOC 0' 50% Excess	
	7.625" 29.7# L-80HC BTC 10,947'	2,399 S TOC 0' 50% Ex	
6.75"			ОВМ
12° Build @ 10,468' MD			
thru 11,218' MD	5.5" 23# P-110 USS-Eagle SFH 18,780' arget Third Bone Spring 10900 TVD // 18780 MD	1,462 Sacks TOC 0' 25% Excess	10.5-12.5 ppg
		+	



Ameredev Operating

Lea County, NM (N83-NME)
Camelia_Azalea
AZALEA STATE COM 26-36-28 383H

OWB

Plan: PWP0

Standard Planning Report - Geographic

02 May, 2023



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

176.99

Grid

Minimum Curvature

Project Lea County, NM (N83-NME)

Map System: U Geo Datum: N

Map Zone:

US State Plane 1983 North American Datum 1983 New Mexico Eastern Zone System Datum:

Mean Sea Level

Site Camelia Azalea

 Site Position:
 Northing:
 372,956.73 usft
 Latitude:
 32.0208919

 From:
 Lat/Long
 Easting:
 870,464.84 usft
 Longitude:
 -103.2713773

Position Uncertainty: 0.0 usft Slot Radius: 13-3/16 "

Well AZALEA STATE COM 26-36-28 383H

Well Position +N/-S 0.0 usft **Northing**: 372,868.67 usfl **Latitude**: 32.0206204

+E/-W 0.0 usft **Easting:** 871,554.49 usft **Longitude:** -103.2678648

0.0

Position Uncertainty 3.0 usft Wellhead Elevation: usfl Ground Level: 2,906.0 usfl

Grid Convergence: 0.57 °

Wellbore OWB

 Magnetics
 Model Name
 Sample Date (°)
 Declination (°)
 Dip Angle (°)
 Field Strength (nT)

 IGRF2020
 5/1/2023
 6.17
 59.69
 47,211.50955992

0.0

MWD

Design PWP0

Audit Notes:

Version: Phase: PLAN Tie On Depth: 0.0

Vertical Section: Depth From (TVD) +N/-S +E/-W Direction (usft) (usft) (usft) (°)

Plan Survey Tool Program Date 5/2/2023

Depth From Depth To

0.0

(usft) (usft) Survey (Wellbore) Tool Name Remarks

(uots) Currey (tronsort)

18,779.3 PWP0 (OWB)

OWSG MWD - Standard

0.0

OWOO WWD - Standar

Plan Section	IS									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,700.0	7.00	23.23	2,698.3	39.2	16.8	1.00	1.00	0.00	23.23	
8,303.2	7.00	23.23	8,259.7	666.8	286.2	0.00	0.00	0.00	0.00	
9,003.2	0.00	0.00	8,958.0	706.0	303.0	1.00	-1.00	0.00	180.00	
10,467.7	0.00	0.00	10,422.5	706.0	303.0	0.00	0.00	0.00	0.00	
11,217.7	90.00	179.41	10,900.0	228.6	307.9	12.00	12.00	23.92	179.41	
18,779.5	90.00	179.41	10,900.0	-7,332.8	385.1	0.00	0.00	0.00	0.00 B	HL (ASC 383H)



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Planned Surv	еу								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
100.0	0.00	0.00	100.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
200.0		0.00	200.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
300.0	0.00	0.00	300.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
400.0	0.00	0.00	400.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
500.0	0.00	0.00	500.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
600.0	0.00	0.00	600.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
700.0 800.0	0.00 0.00	0.00 0.00	700.0 800.0	0.0 0.0	0.0 0.0	372,868.67 372,868.67	871,554.49 871,554.49	32.0206204 32.0206204	-103.2678648 -103.2678648
900.0	0.00	0.00	900.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,000.0	0.00	0.00	1,000.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,100.0	0.00	0.00	1,100.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,200.0	0.00	0.00	1,200.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,300.0	0.00	0.00	1,300.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,400.0	0.00	0.00	1.400.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,500.0	0.00	0.00	1,500.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,600.0	0.00	0.00	1,600.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,700.0	0.00	0.00	1,700.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,731.0	0.00	0.00	1,731.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
Rustler									
1,800.0		0.00	1,800.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
1,900.0	0.00	0.00	1,900.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
2,000.0	0.00	0.00	2,000.0	0.0	0.0	372,868.67	871,554.49	32.0206204	-103.2678648
	uild 1.00								
2,100.0	1.00	23.23	2,100.0	0.8	0.3	372,869.48	871,554.83	32.0206226	-103.2678637
Salado						0=0.0=4.00			400 00=000
2,200.0	2.00	23.23	2,200.0	3.2	1.4	372,871.88	871,555.86	32.0206292	-103.2678603
2,300.0	3.00	23.23	2,299.9	7.2	3.1 5.5	372,875.89	871,557.58	32.0206402	-103.2678546
2,400.0 2,500.0	4.00 5.00	23.23 23.23	2,399.7 2,499.4	12.8 20.0	8.6	372,881.50 372,888.71	871,559.99 871,563.09	32.0206555 32.0206753	-103.2678466 -103.2678364
2,600.0	6.00	23.23	2,598.9	28.8	12.4	372,897.52	871,566.87	32.0206793	-103.2678239
2,700.0	7.00	23.23	2,698.3	39.2	16.8	372,907.92	871,571.33	32.0207278	-103.2678092
1	603.2 hold a			00.2	10.0	012,001.02	07 1,07 1.00	02.0207270	100.2070002
2,800.0	7.00	23.23	2,797.5	50.4	21.6	372,919.12	871,576.14	32.0207585	-103.2677933
2,900.0	7.00	23.23	2,896.8	61.6	26.5	372,930.32	871,580.94	32.0207891	-103.2677775
3,000.0	7.00	23.23	2,996.0	72.8	31.3	372,941.52	871,585.75	32.0208198	-103.2677616
3,100.0	7.00	23.23	3,095.3	84.0	36.1	372,952.72	871,590.56	32.0208504	-103.2677458
3,200.0	7.00	23.23	3,194.5	95.2	40.9	372,963.91	871,595.36	32.0208811	-103.2677299
3,244.8	7.00	23.23	3,239.0	100.3	43.0	372,968.93	871,597.52	32.0208948	-103.2677228
Tansill									
3,300.0	7.00	23.23	3,293.8	106.4	45.7	372,975.11	871,600.17	32.0209117	-103.2677140
3,400.0		23.23	3,393.0	117.6	50.5	372,986.31	871,604.98	32.0209424	-103.2676982
3,500.0		23.23	3,492.3	128.8	55.3	372,997.51	871,609.78	32.0209730	-103.2676823
3,600.0	7.00	23.23	3,591.6	140.0	60.1	373,008.71	871,614.59	32.0210037	-103.2676664
3,700.0		23.23 23.23	3,690.8 3,726.0	151.2 155.2	64.9 66.6	373,019.91 373,023.88	871,619.39 871,621.10	32.0210343	-103.2676506
3,735.5		23.23	3,720.0	100.2	00.0	373,023.00	071,021.10	32.0210452	-103.2676450
Capitar 3,800.0		23.23	3,790.1	162.4	69.7	373,031.11	871,624.20	32.0210650	-103.2676347
3,900.0		23.23	3,889.3	173.6	74.5	373,042.31	871,629.01	32.0210050	-103.2676189
4,000.0	7.00	23.23	3,988.6	184.8	79.3	373,053.51	871,633.81	32.0211263	-103.2676030
4,100.0	7.00	23.23	4,087.8	196.0	84.1	373,064.71	871,638.62	32.0211569	-103.2675871
4,200.0	7.00	23.23	4,187.1	207.2	88.9	373,075.91	871,643.43	32.0211876	-103.2675713
4,300.0		23.23	4,286.3	218.4	93.7	373,087.10	871,648.23	32.0212182	-103.2675554
4,400.0	7.00	23.23	4,385.6	229.6	98.6	373,098.30	871,653.04	32.0212489	-103.2675395



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Diamad Cum									
Planned Sur	vey								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
4,500.0		23.23	4,484.8	240.8	103.4	373,109.50	871,657.85	32.0212795	-103.2675237
4,600.0		23.23	4,584.1	252.0	108.2	373,120.70	871,662.65	32.0213102	-103.2675078
4,700.0		23.23	4,683.4	263.2	113.0	373,131.90	871,667.46	32.0213408	-103.2674920
4,800.0		23.23 23.23	4,782.6	274.4	117.8	373,143.10 373,154.30	871,672.26	32.0213715	-103.2674761
4,900.0 4,943.5		23.23	4,881.9 4,925.0	285.6 290.5	122.6 124.7	373,154.30 373,159.17	871,677.07 871,679.16	32.0214022 32.0214155	-103.2674602 -103.2674533
Lamar		23.23	4,923.0	290.5	124.7	373,139.17	07 1,079.10	32.0214133	-103.2074333
5,000.0		23.23	4,981.1	296.8	127.4	373,165.50	871,681.88	32.0214328	-103.2674444
5,100.0		23.23	5,080.4	308.0	132.2	373,176.70	871,686.68	32.0214635	-103.2674285
5,114.7	7.00	23.23	5,095.0	309.7	132.9	373,178.35	871,687.39	32.0214680	-103.2674262
Bell Ca	anyon								
5,200.0		23.23	5,179.6	319.2	137.0	373,187.90	871,691.49	32.0214941	-103.2674126
5,275.0		23.23	5,254.1	327.6	140.6	373,196.29	871,695.09	32.0215171	-103.2674008
	105464695 E			000.4	444.0	070 400 40	074 000 00	00.0045040	400 0070000
5,300.0 5,400.0		23.23 23.23	5,278.9 5,378.1	330.4 341.6	141.8 146.6	373,199.10 373,210.29	871,696.30 871,701.10	32.0215248 32.0215554	-103.2673968 -103.2673809
5,500.0		23.23	5,376.1 5,477.4	352.8	151.4	373,210.29	871,701.10 871,705.91	32.0215861	-103.2673651
5,600.0		23.23	5,576.6	364.0	156.2	373,232.69	871,710.72	32.0216167	-103.2673492
5,700.0		23.23	5,675.9	375.2	161.0	373,243.89	871,715.52	32.0216474	-103.2673333
5,800.0		23.23	5,775.2	386.4	165.8	373,255.09	871,720.33	32.0216780	-103.2673175
5,900.0		23.23	5,874.4	397.6	170.6	373,266.29	871,725.14	32.0217087	-103.2673016
6,000.0		23.23	5,973.7	408.8	175.5	373,277.49	871,729.94	32.0217393	-103.2672857
6,100.0		23.23	6,072.9	420.0	180.3	373,288.69	871,734.75	32.0217700	-103.2672699
6,200.0		23.23	6,172.2	431.2	185.1	373,299.89	871,739.55	32.0218006	-103.2672540
6,300.0 6,400.0		23.23 23.23	6,271.4 6,370.7	442.4 453.6	189.9 194.7	373,311.09 373,322.29	871,744.36 871,749.17	32.0218313 32.0218619	-103.2672382 -103.2672223
6,500.0		23.23	6,469.9	464.8	194.7	373,322.29	871,753.97	32.0218926	-103.2672264
6,600.0		23.23	6,569.2	476.0	204.3	373,344.68	871,758.78	32.0219232	-103.2671906
6,700.0		23.23	6,668.4	487.2	209.1	373,355.88	871,763.59	32.0219539	-103.2671747
6,800.0		23.23	6,767.7	498.4	213.9	373,367.08	871,768.39	32.0219845	-103.2671588
6,900.0		23.23	6,867.0	509.6	218.7	373,378.28	871,773.20	32.0220152	-103.2671430
7,000.0		23.23	6,966.2	520.8	223.5	373,389.48	871,778.01	32.0220458	-103.2671271
7,058.2		23.23	7,024.0	527.3	226.3	373,396.00	871,780.80	32.0220637	-103.2671179
	y Canyon	00.00	7.005.5	F20.0	220.2	272 400 00	074 700 04	20.0000705	400 0074440
7,100.0 7,200.0		23.23 23.23	7,065.5 7,164.7	532.0 543.2	228.3 233.1	373,400.68 373,411.88	871,782.81 871,787.62	32.0220765 32.0221071	-103.2671113 -103.2670954
7,200.0		23.23	7,104.7	554.4	237.9	373,423.08	871,792.43	32.0221071	-103.2670795
7,400.0		23.23	7,363.2	565.6	242.7	373,434.28	871,797.23	32.0221684	-103.2670637
7,500.0		23.23	7,462.5	576.8	247.6	373,445.48	871,802.04	32.0221991	-103.2670478
7,600.0	7.00	23.23	7,561.7	588.0	252.4	373,456.67	871,806.84	32.0222297	-103.2670319
7,700.0		23.23	7,661.0	599.2	257.2	373,467.87	871,811.65	32.0222604	-103.2670161
7,800.0		23.23	7,760.2	610.4	262.0	373,479.07	871,816.46	32.0222910	-103.2670002
7,900.0		23.23	7,859.5	621.6	266.8	373,490.27	871,821.26	32.0223217	-103.2669844
8,000.0		23.23	7,958.8	632.8	271.6	373,501.47 373,507.25	871,826.07	32.0223523	-103.2669685
8,051.6	7.00 Spring Lime	23.23	8,010.0	638.6	274.1	313,301.23	871,828.55	32.0223681	-103.2669603
8,100.0		23.23	8,058.0	644.0	276.4	373,512.67	871,830.88	32.0223830	-103.2669526
8,200.0		23.23	8,157.3	655.2	281.2	373,523.87	871,835.68	32.0224136	-103.2669368
8,303.2		23.23	8,259.7	666.8	286.2	373,535.43	871,840.64	32.0224453	-103.2669204
	rop -1.00								
8,400.0		23.23	8,355.9	676.8	290.5	373,545.52	871,844.98	32.0224729	-103.2669061
8,500.0		23.23	8,455.4	685.7	294.3	373,554.38	871,848.78	32.0224971	-103.2668935
8,600.0		23.23	8,555.1	693.0	297.4	373,561.64	871,851.89	32.0225170	-103.2668833
8,700.0	3.03	23.23	8,654.9	698.6	299.8	373,567.30	871,854.32	32.0225325	-103.2668752



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Planned Surv	rey								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
8,800.0	2.03	23.23	8,754.8	702.7	301.6	373,571.36	871,856.07	32.0225436	-103.2668695
8,900.0		23.23	8,854.8	705.1	302.6	373,573.82	871,857.12	32.0225503	-103.2668660
9,003.2		0.00	8,958.0	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,100.0	464.5 hold a 0.00	0.00	9,054.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,100.0		0.00	9,054.6 9,154.8	706.0	303.0	373,574.67 373.574.67	871,857.49 871,857.49	32.0225527 32.0225527	-103.2668648
9,300.0		0.00	9,254.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,400.0		0.00	9,354.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,500.0		0.00	9,454.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,599.2	0.00	0.00	9,554.0	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
	one Spring								
9,600.0		0.00	9,554.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,700.0		0.00	9,654.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
9,800.0 9,900.0		0.00 0.00	9,754.8 9,854.8	706.0 706.0	303.0 303.0	373,574.67 373,574.67	871,857.49 871.857.49	32.0225527 32.0225527	-103.2668648 -103.2668648
10,000.0		0.00	9,954.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
10,100.0		0.00	10,054.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
10,200.0		0.00	10,154.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
10,216.2	0.00	0.00	10,171.0	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
	d Bone Sprir								
10,300.0		0.00	10,254.8	706.0	303.0	373,574.67	871,857.49	32.0225527	-103.2668648
10,400.0		0.00	10,354.8 10,422.5	706.0	303.0	373,574.67 373,574.67	871,857.49	32.0225527	-103.2668648
10,467.7	0.00 tart DLS 12.0	0.00	,	706.0	303.0	3/3,5/4.0/	871,857.49	32.0225527	-103.2668648
10,475.0		179.41	10,429.8	705.9	303.0	373,574.62	871,857.49	32.0225525	-103.2668648
10,500.0		179.41	10,454.7	704.9	303.0	373,573.58	871,857.50	32.0225497	-103.2668648
10,525.0		179.41	10,479.6	702.6	303.0	373,571.24	871,857.52	32.0225432	-103.2668648
10,550.0		179.41	10,504.3	698.9	303.1	373,567.61	871,857.56	32.0225332	-103.2668648
10,575.0		179.41	10,528.9	694.0	303.1	373,562.68	871,857.61	32.0225197	-103.2668648
10,600.0		179.41	10,553.1	687.8	303.2	373,556.47	871,857.67	32.0225026	-103.2668648
10,625.0 10,650.0		179.41 179.41	10,576.9 10,600.4	680.3 671.6	303.3 303.4	373,549.01 373,540.31	871,857.75 871,857.84	32.0224821 32.0224582	-103.2668648 -103.2668648
10,675.0		179.41	10,623.3	661.7	303.5	373,530.40	871,857.94	32.0224310	-103.2668648
10,700.0		179.41	10,645.7	650.6	303.6	373,519.29	871,858.05	32.0224004	-103.2668647
10,725.0		179.41	10,667.5	638.4	303.7	373,507.03	871,858.18	32.0223667	-103.2668647
10,750.0		179.41	10,688.6	625.0	303.8	373,493.65	871,858.31	32.0223300	-103.2668647
10,775.0		179.41	10,709.0	610.5	304.0	373,479.18	871,858.46	32.0222902	-103.2668647
10,800.0		179.41	10,728.6	595.0	304.1	373,463.67	871,858.62	32.0222475	-103.2668647
10,825.0 10,850.0		179.41 179.41	10,747.3 10,765.2	578.5 561.0	304.3 304.5	373,447.15 373,429.67	871,858.79 871,858.97	32.0222021 32.0221541	-103.2668647 -103.2668646
10,830.0		179.41	10,782.1	542.6	304.7	373,411.28	871,859.16	32.0221035	-103.2668646
10,900.0		179.41	10,798.1	523.4	304.9	373,392.02	871,859.35	32.0220506	-103.2668646
10,925.0		179.41	10,813.0	503.3	305.1	373,371.96	871,859.56	32.0219955	-103.2668646
10,941.0	56.79	179.41	10,822.0	490.0	305.2	373,358.70	871,859.69	32.0219590	-103.2668646
	Bone Spring						0=1 0		
10,950.0		179.41	10,826.8	482.5	305.3	373,351.15	871,859.77	32.0219382	-103.2668646
10,975.0 11,000.0		179.41 179.41	10,839.6 10,851.2	461.0 438.8	305.5 305.7	373,329.64 373,307.50	871,859.99 871,860.22	32.0218791 32.0218183	-103.2668645 -103.2668645
11,000.0		179.41	10,861.6	436.6 416.1	305.7 306.0	373,284.78	871,860.22 871,860.45	32.0217558	-103.2668645
11,050.0		179.41	10,870.8	392.9	306.2	373,261.54	871,860.69	32.0216919	-103.2668645
11,075.0		179.41	10,878.8	369.2	306.4	373,237.85	871,860.93	32.0216268	-103.2668644
11,100.0		179.41	10,885.5	345.1	306.7	373,213.78	871,861.17	32.0215606	-103.2668644
11,117.0		179.41	10,889.4	328.6	306.9	373,197.25	871,861.34	32.0215152	-103.2668644
NMNM	105464695 E	xit at 11117	.0 MD						



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Design.		-							
Planned Surv	ey								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
11,125.0	78.87	179.41	10,891.0	320.7	306.9	373,189.39	871,861.42	32.0214936	-103.2668644
11,150.0	81.87	179.41	10,895.2	296.1	307.2	373,164.75	871,861.67	32.0214259	-103.2668643
11,175.0	84.87	179.41	10,898.1	271.2	307.4	373,139.92	871,861.93	32.0213576	-103.2668643
11,200.0	87.87	179.41	10,899.6	246.3	307.7	373,114.97	871,862.18	32.0212890	-103.2668643
11,217.7	90.00	179.41	10,900.0	228.6	307.9	373,097.24	871,862.36	32.0212403	-103.2668643
	t 7561.8 hol		•				,		
11,300.0	90.00	179.41	10,900.0	146.3	308.7	373,014.98	871,863.20	32.0210142	-103.2668642
11,400.0	90.00	179.41	10,900.0	46.3	309.7	372,914.99	871,864.23	32.0207393	-103.2668641
11,500.0	90.00	179.41	10,900.0	-53.7	310.8	372,814.99	871,865.25	32.0204645	-103.2668640
11,600.0	90.00	179.41	10,900.0	-153.7	311.8	372,715.00	871,866.27	32.0201896	-103.2668638
11,700.0	90.00	179.41	10,900.0	-253.7	312.8	372,615.00	871,867.29	32.0199147	-103.2668637
11,800.0	90.00	179.41	10,900.0	-353.7	313.8	372,515.01	871,868.31	32.0196399	-103.2668636
11,900.0	90.00	179.41	10,900.0	-453.7	314.8	372,415.01	871,869.33	32.0193650	-103.2668635
12,000.0	90.00	179.41	10,900.0	-553.7	315.9	372,315.02	871,870.35	32.0190901	-103.2668634
12,100.0	90.00	179.41	10,900.0	-653.6	316.9	372,215.03	871,871.38	32.0188153	-103.2668633
12,200.0	90.00	179.41	10,900.0	-753.6	317.9	372,115.03	871,872.40	32.0185404	-103.2668632
12,300.0	90.00	179.41	10,900.0	-853.6	318.9	372,015.04	871,873.42	32.0182655	-103.2668631
12,400.0	90.00	179.41	10,900.0	-953.6	320.0	371,915.04	871,874.44	32.0179907	-103.2668630
12,500.0	90.00	179.41	10,900.0	-1,053.6	321.0	371,815.05	871,875.46	32.0177158	-103.2668628
12,600.0 12,700.0	90.00 90.00	179.41 179.41	10,900.0 10,900.0	-1,153.6 -1,253.6	322.0 323.0	371,715.05 371,615.06	871,876.48 871,877.51	32.0174409 32.0171661	-103.2668627 -103.2668626
12,700.0	90.00	179.41	10,900.0	-1,253.6 -1,353.6	323.0 324.0	371,515.06	871,878.53	32.0168912	-103.2668625
12,900.0	90.00	179.41	10,900.0	-1,353.6 -1,453.6	325.1	371,415.07	871,879.55	32.0166163	-103.2668624
13,000.0	90.00	179.41	10,900.0	-1,553.6	326.1	371,315.07	871,880.57	32.0163415	-103.2668623
13,100.0	90.00	179.41	10,900.0	-1,653.6	327.1	371,215.08	871,881.59	32.0160666	-103.2668622
13,200.0	90.00	179.41	10,900.0	-1,753.6	328.1	371,115.08	871,882.61	32.0157918	-103.2668621
13,300.0	90.00	179.41	10,900.0	-1,853.6	329.1	371,015.09	871,883.63	32.0155169	-103.2668620
13,400.0	90.00	179.41	10,900.0	-1,953.6	330.2	370,915.09	871,884.66	32.0152420	-103.2668618
13,500.0	90.00	179.41	10,900.0	-2,053.6	331.2	370,815.10	871,885.68	32.0149672	-103.2668617
13,600.0	90.00	179.41	10,900.0	-2,153.6	332.2	370,715.10	871,886.70	32.0146923	-103.2668616
13,700.0	90.00	179.41	10,900.0	-2,253.6	333.2	370,615.11	871,887.72	32.0144174	-103.2668615
13,800.0	90.00	179.41	10,900.0	-2,353.6	334.3	370,515.11	871,888.74	32.0141426	-103.2668614
13,900.0	90.00	179.41	10,900.0	-2,453.6	335.3	370,415.12	871,889.76	32.0138677	-103.2668613
14,000.0	90.00	179.41	10,900.0	-2,553.5	336.3	370,315.12	871,890.78	32.0135928	-103.2668612
14,100.0	90.00	179.41	10,900.0	-2,653.5	337.3	370,215.13	871,891.81	32.0133180	-103.2668611
14,200.0	90.00	179.41	10,900.0	-2,753.5	338.3	370,115.13	871,892.83	32.0130431	-103.2668609
14,300.0	90.00	179.41	10,900.0	-2,853.5	339.4	370,015.14	871,893.85	32.0127682	-103.2668608
14,400.0	90.00	179.41	10,900.0	-2,953.5	340.4	369,915.15	871,894.87	32.0124934	-103.2668607
14,500.0	90.00	179.41	10,900.0	-3,053.5	341.4	369,815.15	871,895.89	32.0122185	-103.2668606
14,600.0	90.00	179.41	10,900.0	-3,153.5	342.4	369,715.16	871,896.91	32.0119436	-103.2668605
14,700.0	90.00	179.41	10,900.0	-3,253.5	343.4	369,615.16	871,897.94	32.0116688	-103.2668604
14,800.0 14,900.0	90.00 90.00	179.41 179.41	10,900.0 10,900.0	-3,353.5 -3,453.5	344.5 345.5	369,515.17 369,415.17	871,898.96 871,899.98	32.0113939 32.0111190	-103.2668603 -103.2668602
15,000.0	90.00	179.41	10,900.0	-3,553.5	346.5	369,315.18	871,901.00	32.0108442	-103.2668600
15,100.0	90.00	179.41	10,900.0	-3,653.5	347.5	369,215.18	871,902.02	32.0105693	-103.2668599
15,200.0	90.00	179.41	10,900.0	-3,753.5	348.6	369,115.19	871,903.04	32.0102944	-103.2668598
15,300.0	90.00	179.41	10,900.0	-3,853.5	349.6	369,015.19	871,904.06	32.0100196	-103.2668597
15,400.0	90.00	179.41	10,900.0	-3,953.5	350.6	368,915.20	871,905.09	32.0097447	-103.2668596
15,500.0	90.00	179.41	10,900.0	-4,053.5	351.6	368,815.20	871,906.11	32.0094698	-103.2668595
15,600.0	90.00	179.41	10,900.0	-4,153.5	352.6	368,715.21	871,907.13	32.0091950	-103.2668594
15,700.0	90.00	179.41	10,900.0	-4,253.5	353.7	368,615.21	871,908.15	32.0089201	-103.2668593
15,800.0	90.00	179.41	10,900.0	-4,353.5	354.7	368,515.22	871,909.17	32.0086452	-103.2668592
15,900.0	90.00	179.41	10,900.0	-4,453.4	355.7	368,415.22	871,910.19	32.0083704	-103.2668590
16,000.0	90.00	179.41	10,900.0	-4,553.4	356.7	368,315.23	871,911.21	32.0080955	-103.2668589



Database: AUS-COMPASS - EDM_15 - 32bit Ameredev Operating

Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Planned Surv	ey								
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
16,100.0		179.41	10,900.0	-4,653.4	357.7	368,215.23	871,912.24	32.0078207	-103.2668588
16,200.0		179.41	10,900.0	-4,753.4	358.8	368,115.24	871,913.26	32.0075458	-103.2668587
16,300.0		179.41	10,900.0	-4,853.4	359.8	368,015.24	871,914.28	32.0072709	-103.2668586
16,400.0		179.41	10,900.0	-4,953.4	360.8	367,915.25	871,915.30	32.0069961	-103.2668585
16,500.0		179.41	10,900.0	-5,053.4	361.8	367,815.25	871,916.32	32.0067212	-103.2668584
16,600.0		179.41	10,900.0	-5,153.4	362.9	367,715.26	871,917.34	32.0064463	-103.2668583
16,700.0		179.41	10,900.0	-5,253.4	363.9	367,615.27	871,918.37	32.0061715	-103.2668581
16,800.0		179.41	10,900.0	-5,353.4	364.9	367,515.27	871,919.39	32.0058966	-103.2668580
16,900.0		179.41	10,900.0	-5,453.4	365.9	367,415.28	871,920.41	32.0056217	-103.2668579
17,000.0		179.41	10,900.0	-5,553.4	366.9	367,315.28	871,921.43	32.0053469	-103.2668578
17,100.0		179.41	10,900.0	-5,653.4	368.0	367,215.29	871,922.45	32.0050720	-103.2668577
17,200.0		179.41	10,900.0	-5,753.4	369.0	367,115.29	871,923.47	32.0047971	-103.2668576
17,300.0		179.41	10,900.0	-5,853.4	370.0	367,015.30	871,924.49	32.0045223	-103.2668575
17,400.0		179.41	10,900.0	-5,953.4	371.0	366,915.30	871,925.52	32.0042474	-103.2668574
17,500.0	90.00	179.41	10,900.0	-6,053.4	372.1	366,815.31	871,926.54	32.0039725	-103.2668572
17,600.0	90.00	179.41	10,900.0	-6,153.4	373.1	366,715.31	871,927.56	32.0036977	-103.2668571
17,700.0	90.00	179.41	10,900.0	-6,253.4	374.1	366,615.32	871,928.58	32.0034228	-103.2668570
17,800.0		179.41	10,900.0	-6,353.4	375.1	366,515.32	871,929.60	32.0031479	-103.2668569
17,900.0	90.00	179.41	10,900.0	-6,453.3	376.1	366,415.33	871,930.62	32.0028731	-103.2668568
18,000.0	90.00	179.41	10,900.0	-6,553.3	377.2	366,315.33	871,931.64	32.0025982	-103.2668567
18,100.0	90.00	179.41	10,900.0	-6,653.3	378.2	366,215.34	871,932.67	32.0023233	-103.2668566
18,200.0		179.41	10,900.0	-6,753.3	379.2	366,115.34	871,933.69	32.0020485	-103.2668564
18,300.0		179.41	10,900.0	-6,853.3	380.2	366,015.35	871,934.71	32.0017736	-103.2668563
18,400.0		179.41	10,900.0	-6,953.3	381.2	365,915.35	871,935.73	32.0014987	-103.2668562
18,500.0		179.41	10,900.0	-7,053.3	382.3	365,815.36	871,936.75	32.0012239	-103.2668561
18,600.0		179.41	10,900.0	-7,153.3	383.3	365,715.36	871,937.77	32.0009490	-103.2668560
18,700.0		179.41	10,900.0	-7,253.3	384.3	365,615.37	871,938.80	32.0006741	-103.2668559
18,779.5	90.00	179.41	10,900.0	-7,332.8	385.1	365,535.88	871,939.61	32.0004556	-103.2668558
TD at 1	8779.5								

Design Targets									
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
FTP (ASC 383H) - plan misses targe - Point	0.00 t center by		10,900.0 1212.9usft	233.4 MD (10899.9	307.7 9 TVD, 233.4	373,102.09 N, 307.8 E)	871,862.16	32.0212536	-103.2668648
LTP (ASC 383H) - plan misses targe - Point	0.00 t center by		10,900.0 18700.0us	-7,282.8 ft MD (10900	384.6 0.0 TVD, -725	365,585.86 53.3 N, 384.3 E)	871,939.08	32.0005930	-103.2668559
BHL (ASC 383H) - plan hits target ce - Point	0.00 enter	0.00	10,900.0	-7,332.8	385.1	365,535.88	871,939.61	32.0004556	-103.2668558



Database: AUS-COMPASS - EDM_15 - 32bit

Company: Ameredev Operating
Project: Lea County, NM (N83-NME)

Site: Camelia_Azalea

Well: AZALEA STATE COM 26-36-28 383H

Wellbore: OWB Design: PWP0 Local Co-ordinate Reference:

TVD Reference: MD Reference: North Reference:

Survey Calculation Method:

Well AZALEA STATE COM26-36-28 383H

KB=27' @ 2933.0usft KB=27' @ 2933.0usft

Grid

Formations							
	Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
	1,731.0	1,731.0	Rustler				
	2,100.0	2,100.0	Salado				
	3,244.8	3,239.0	Tansill				
	3,735.5	3,726.0	Capitan				
	4,943.5	4,925.0	Lamar				
	5,114.7	5,095.0	Bell Canyon				
	7,058.2	7,024.0	Brushy Canyon				
	8,051.6	8,010.0	Bone Spring Lime				
	9,599.2	9,554.0	First Bone Spring				
	10,216.2	10,171.0	Second Bone Spring				
	10,941.0	10,822.0	Third Bone Spring Carb				

Plan Annotation	s				
Ti-	easured Depth (usft)	Vertical Depth (usft)	Local Coord +N/-S (usft)	dinates +E/-W (usft)	Comment
	2,000.0	2,000.0	0.0	0.0	Start Build 1.00
	2,700.0	2,698.3	39.2	16.8	Start 5603.2 hold at 2700.0 MD
	5,275.0	5,254.1	327.6	140.6	NMNM105464695 Entry at 5275.0 MD
	8,303.2	8,259.7	666.8	286.2	Start Drop -1.00
	9,003.2	8,958.0	706.0	303.0	Start 1464.5 hold at 9003.2 MD
	10,467.7	10,422.5	706.0	303.0	KOP-Start DLS 12.00 TFO 179.41
	11,117.0	10,889.4	328.6	306.9	NMNM105464695 Exit at 11117.0 MD
	11,217.7	10,900.0	228.6	307.9	LP-Start 7561.8 hold at 11217.7 MD
	18,779.5	10,900.0	-7,332.8	385.1	TD at 18779.5

State of New Mexico Energy, Minerals and Natural Resources Department

Submit Electronically Via E-permitting

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description Effective May 25, 2021

Operator:	Ameredev II, I	LC	OGRID: _	372224	Date:	<u> </u>
Type: ⊠ Original □	l Amendment due t	to 🗆 19.15.27	9.D(6)(a) NMAC	□ 19.15.27.9.1	D(6)(b) NMAC □ O	ther.
Other, please describe:	:					
Well(s): Provide the recompleted from a si					of wells proposed to	be drilled or propose
Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Azalea 26 36 28 State Com 383H	30-025-		330' FNL & 1960' FEL	600	11,977	1,971
Central Delivery Po	oint Name:				[See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Azalea 26 36 28 State Com 383H	30-025-	05/04/2024	05/29/2024	08/23/2024	09/16/2024	09/19/2024

VI. Separation Equipment:
☐ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: ⊠ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices:

Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

 \boxtimes Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF	

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. \square Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the
production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity or
the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural	gas gathering system \square	will □ will not have	capacity to gather	100% of the anticipate	d natural gas
production volume from the well	prior to the date of first p	production.			

XIII.	Line Pressure. Operator \square does \square does not anticipate that its existing well(s) confidence of the confidence of th	nected to the same segment, or portion,	of the
natura	al gas gathering system(s) described above will continue to meet anticipated increase	s in line pressure caused by the new wo	ell(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

XIV. Confidentiality: Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided	in
Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information	on
for which confidentiality is asserted and the basis for such assertion.	

(i)

Section 3 - Certifications Effective May 25, 2021

Operator certifies that, a	fter reasonable inquiry and based on the available information at the time of submittal:		
one hundred percent of	Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, aking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or		
hundred percent of the a into account the current	able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system. box, Operator will select one of the following:		
Well Shut-In. □ Opera D of 19.15.27.9 NMAC	tor will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection ; or		
Venting and Flaring P	lan. □ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential		
alternative beneficial us	es for the natural gas until a natural gas gathering system is available, including:		
(a)	power generation on lease;		
(b)	power generation for grid;		
(c)	compression on lease;		
(d)	liquids removal on lease;		
(e)	reinjection for underground storage;		
(f)	reinjection for temporary storage;		
(g)	reinjection for enhanced oil recovery;		
(h)	fuel cell production: and		

Section 4 - Notices

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

other alternative beneficial uses approved by the division.

- (a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or
- (b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.
- 2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: Casca Gu
Printed Name: Cesca Yu
Title: Engineer
E-mail Address: cyu@ameredev.com
Date: 05/08/2023
Phone: 512-775-1417
OIL CONSERVATION DIVISION
(Only applicable when submitted as a standalone form)
Approved By:
Title:
Approval Date:
Conditions of Approval:

Natural Gas Management Plan

VI. Separation Equipment: Attach a complete description of how Operator will size separation equipment to optimize gas capture.

- Separation equipment is sized to allow for retention time and velocity to adequately separate oil, gas, and water at anticipated peak rates.
- All central tank battery equipment is designed to efficiently capture the remaining gas from the liquid phase.
- Valves and meters are designed to service without flow interruption or venting of gas.

VII. <u>Operational Practices: Attach a complete description of the actions Operator will</u> take to comply with the requirements of Subsection A through F 19.15.27.8 NMAC.

19.15.27.8 (A)

Ameredev's field operations are designed with the goal of minimizing flaring and preventing venting of natural gas. If capturing the gas is not possible then the gas is combusted/flared using properly sized flares or combustors in accordance with state air permit rules.

19.15.27.8 (B) Venting and Flaring during drilling operations

- A properly-sized flare stack will be located at a minimum 100' from the nearest surface hole location on the pad.
- All natural gas produced during drilling operations will be flared. Venting will only occur if there is an equipment malfunction and/or to avoid risk of an immediate and substantial adverse impact on safety, public health, or the environment.

19.15.27.8 (C) Venting and Flaring during completions or recompletions operations.

- During all phases of flowback, wells will flow through a sand separator, or other appropriate flowback separation equipment, and the well stream will be directed to a central tank battery (CTB) through properly sized flowlines
- The CTB will have properly sized separation equipment for maximum anticipated flowrates
- Multiple stages of separation will be used to separate gas from liquids. All gas will be routed to a sales outlet. Fluids will be routed to tanks equipped with a closed loop system that will recover any residual gas from the tanks and route such gas to a sales outlet.

19.15.27.8 (D) Venting and Flaring during production operations.

• During production, the well stream will be routed to the CTB where multiple stages of separation will separate gas from liquids. All gas will be routed to a sales outlet. Fluids will be routed to tanks with a closed

loop system that will recover any residual gas from the tanks and route such gas to a sales outlet, minimizing tank emissions.

- Flares are equipped with auto-ignition systems and continuous pilot operations.
- Automatic gauging equipment is installed on all tanks.

19.15.27.8 (E) Performance Standards

- Production equipment will be designed to handle maximum anticipated rates and pressure.
- Automatic gauging equipment is installed on all tanks to minimize venting
- All flared gas will be combusted in a flare stack that is properly sized and designed to ensure proper combustion.
- •Flares are equipped with continuous pilots and auto-ignitors along with remote monitoring of the pilot status
- Weekly AVOs and monthly LDAR inspections will be performed on all wells and facilities that produce more than 60 Mcfd.
- Gas/H2S detectors will be installed throughout the facilities and wellheads to detect leaks and enable timely repairs.

19.15.27.8 (F) Measurement or estimation of vented and flared natural gas

- All high pressure flared gas is measured by equipment conforming to API 14.10.
- No meter bypasses are installed.
- When metering is not practical due to low pressure/low rate, the vented or flared volume will be estimated through flare flow curves with the assistance of air emissions consultants, as necessary.

VIII. <u>Best Management Practices: Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.</u>

- Ameredev will use best management practices to vent as minimally as possible during well intervention operations and downhole well maintenance
- All natural gas is routed into the gas gathering system and directed to one of Ameredev's multiple gas sales outlets.
- All venting events will be recorded and all start-up, shutdown, maintenance logs will be kept for control equipment
- All control equipment will be maintained to provide highest run-time possible
- All procedures are drafted to keep venting and flaring to the absolute minimum