					n .
Pa	aa	0	1	nt	1
	45		1	\boldsymbol{v}	-

.

Received by OCD: 3	/16/2023 1:38:47 PM							
	UNITED STATES PARTMENT OF THE INTERIOR			FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021				
BUI	REAU OF LAND MANAGEMENT		5. Lease Serial No. NMNM36949					
Do not use this	NOTICES AND REPORTS ON V form for proposals to drill or to Use Form 3160-3 (APD) for su	,	6. If Indian, Allottee or	Tribe Name				
SUBMIT IN	ITRIPLICATE - Other instructions on pag	je 2		7. If Unit of CA/Agreer	nent, Name a	and/or No.		
1. Type of Well	Well V Other			8. Well Name and No.,		24N FEDERAL SWD/001		
2. Name of Operator ENDURING R				9. API Well No. 30045	NLU 2309 2	24N FEDERAL SWD/001		
	SUITE 2500, DENVER, CO 3b. Phone No.	(include area cod		30045 10. Field and Pool or E		rea		
1050 TITH STREET	(303) 573-12		~/	WEST LYBROOK L	JNIT			
4. Location of Well (Footage, Sec., T. SEC 24/T23N/R9W/NMP	R.,M., or Survey Description)			11. Country or Parish, S SAN JUAN/NM	State			
12. CH	ECK THE APPROPRIATE BOX(ES) TO IN	DICATE NATUR	E OF NOTI	CE, REPORT OR OTH	ER DATA			
TYPE OF SUBMISSION		TY	TPE OF ACT	TION				
Notice of Intent	Acidize Deep	oen raulic Fracturing	\equiv	uction (Start/Resume) mation		Shut-Off integrity		
✓ Subsequent Report		Construction	_	mplete	✔ Other			
Final Abandonment Notice		and Abandon Back		oorarily Abandon r Disposal				
is ready for final inspection.) Conversion from a water sup EOT: 6798 MD Packer Depth Top: 6790 MD Job Start: 2/9/2023 Job End: 2/21/2023	ply well to a salt water disposal well. Upd	lated wellbore so	chematic at	tached.				
14. I hereby certify that the foregoing HEATHER HUNTINGTON / Ph: (is true and correct. Name (Printed/Typed) 505) 636-9751	Permitting	Permitting Technician Title					
Signature		Date	Date 03/08/2023					
	THE SPACE FOR FED	ERAL OR ST	TATE OF	ICE USE				
Approved by								
KENNETH G RENNICK / Ph: (50	5) 564-7742 / Accepted	Title Petr	oleum Eng	ineer D	03/09/2023 Date			
	ched. Approval of this notice does not warrar equitable title to those rights in the subject lo onduct operations thereon.	t or ease Office FA	ARMINGTC	DN				
	43 U.S.C Section 1212, make it a crime for a nents or representations as to any matter with			fully to make to any dep	partment or a	gency of the United States		

(Instructions on page 2)

WellView[®]

Wellbore Schematic - Components and Cement

352.0 353.3 362.0 353.3 365.7 Tubing YB lined tubing 3.4* 4.159.1 Tubing YB lined tubing 3.4* 4.159.1 Tubing Strings Tubing - Injection Str 395.5 402.9 Tubing YB lined tubing 3.4* 4.159.1 Tubing YB lined tubing 3.4* 4.159.1 Tubing YB lined tubing 3.4* 6.787.1 4.159.1 G.787.1 6.787.1 Casing yoints: 6.787.1 Casing yoints: 6.787.1 Tubing YB lined drift 6.713.9 Full Casing yoints: 6.788.1 Casing yoints: 6.788.0 Casing yoints: 6.788.1 Casing Strings Production Casing, Casing Joints Casing Joints Casing Joints Casing Joints Casing Joints Float Collar Casing Joints Float Collar Casing Joints Float Collar Float Shoe 7.129.9 7.259.8 Bridge Pug Bridge Pug Bridge Pug String Casing, 397			:	County SAN JL				IEXICO		SE/	ace Legal Locatio 4, SW/4, Se	ection									
MD (MC) Vertical achematic (adual) Dimp Description 14.8 16.1 Tubing TB is 0.5 is 0.5 i		On Pr	Produ	ction Date		Abandon D	ate		ft)					h (All) (ftKB) Hole - 7				All) (ftKB) al Hole -	7,26	0.0	
MD (MG) Vertical achematic (actual) Vertical achematic (actual) Vertical achematic (actual) Thing Vertical achematic						•															
14.8 14.8 15.1 Tubing Plug - Perman 15.4 15.7 15.7 Tubing Velocities 15.7 Tubing Velocities 15.7 Tubing Velocities 16.7 Tu		V	Vertic						Oth	ner St	trings										
14.8 Image: Description 15.1 Image: Description 14.8 Image: Description 15.1 Image: Description 15.7 Image: Description 15.7 Image: Description 365.7 Image: Description 15.1 Image: Description 365.7 Image: Description 16.8 Image: Description 37.3 Image: Description 16.8 Image: Description 36.7 Image: Description 16.8 Image: Description 17.8 Image: Description 18.8 Image: Description 19.7				Ver	tical s	chematic (ac	tual)		String	ig Desci	ription				String L	.ength (ft) Set De	epth (ftKB)	Rur	n Date	
15.1 Hunger									Oth	ner In	Hole										
15.1 Hanger, 14.9-15.4 Fill 15.4 Is.7 General Gen									Bric	dae P		nent	Pr	Strin oduction			p (ftKB) .260.0	Btm (ftKB) 7,262.0		Run E	
14.3-7.4 BCB 1										5	5		7,3	397.8ftKE	3		,	,	00:	00	
15.7 15.0-15.8] Woo Strings 952.0 Similar Similar Similar 953.3 Similar Similar Similar Similar 953.3 Similar Similar Similar Similar Similar 967.7 Image Similar Simil	.4	4 🛛 🕅			Ŀ				Fill					oduction 397.8ftKE		, 7	,130.0	7,260.0	2/2: 12:0	2/202 00	20
15.7 35.0 35.0 35.3 36.7 1 1 1 1 1 1 1 1 1 1 1 1 1											<u> </u>										
352.0 353.3 366.7 Integer Integ												>			String L	.ength (ft) Set D	epth (ftKB)	Rur	n Date	
352.0 Single								15.0-351.9	lte			Item De	20		OD (ir	<u></u>	Len (ft)	Top (ft	KB)	Btm	n (ftKB)
333.3 Junct Junct <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Collar; / 351.9-</td><td>018</td><td>5</td><td></td><td>Item De</td><td>55</td><td></td><td>00 (1</td><td>1)</td><td>Len (it)</td><td>TOP (II</td><td>ND)</td><td>Dui</td><td>(IIXD)</td></t<>								Collar; / 351.9-	018	5		Item De	55		00 (1	1)	Len (it)	TOP (II	ND)	Dui	(IIXD)
385.7 Tubing Yelling 34 thing								Casing													
338.7 Iubing 34 dots induing 34 drift Iubing 15 dots induing 34 drift Iubing 15 dots induing 34 drift Iubing 15 dots induing 34 drift Iubing 15 dots induing 15 dots induing 34 drift Iubing 15 dots induing 15 dots	_	_ 🖄						353.2-				string	- SWD	set at 6,7 Len (ft)			. Run Date) Pull Dat	te D	epth C
397.3 4199.0 402.9 Tubing YB 402.9 Ubing 34 4159.1 6.787.1 6.692.9 6.787.1 6.787.1 6.788.0 6.787.1 6.788.1 6.787.1 6.786.0 6.787.1 0.753.0 6.787.1 0.780.0 6.787.1 0.780.0 6.787.1 0.730.7 6.787.1 0.780.0 6.787.1 0.780.0 6.787.1 0.780.0 6.787.1 0.780.0 6.787.1 0.730.7 7.129.9 7.300.7 7.307.7 7.307.6 7.307.7 7.307.6 7.307.7 7.307.6 7.307.7 7.307.6	ed 4"	! 🕅						Float Shoe;	Tub		Injection Str		SWD	6,783.12	2 6,79	8.0	2/20/20	023			Wt
402.9 Tubing YB lined drift 4.159.1 2 drift 4.159.1 4.159.1 Grant 4.159.1 Grant 6.787.1 Grant 6.787.1 6.692.9 6.787.1 6.788.0 Grant 6.788.1 Grant 6.788.1 6.787.1 FUE 00001 Grant 1001 Table YB lined drift 1001 Table YB lined drift 11 6.787.1 FUE 00001 Grant 1001 Table YB lined drift 11 Table YB lined drift 11 6.787.1 FUE 00001 Grant 1001 Grant 1001 Table YB lined drift 11 Table YB lined drift 11 6.780.1 FUE 6.780.0 Grant 1001 Grant 1001 Table YB lined drift 11 Table YB lined drift 11 6.780.1 FUE 6.790.1 Grant 6.790.1 Grant 1001 Table YB lined drift 11 Table YB lined drift 11 7.129.9 Fue 6.790.1 Fue 7.190.0 Grant 7.190.0 Grant 7.190.0 Grant 7.190.0 7.282.1 Fue 7.393.4 Fue 7.393.4 Grant 7.393.7 Grant 7.393.7 Grant 7.393.7 7.394.7 Fuel 7.397.6 Fuel 7.397.6 Grant 7.397.6 Grant 7.397.6 Grant 7.397.6	.0	o 🔪							Jts 1		ing Hanger			OD (in) 7		ft) .55	Top (ftKB) 14.9	Btm (ftKB	4	rade	(lb/ft
4.159.1 Gasing Gasing 15.8 Gasing 15.8 6.002.9 6.787.1 Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Gasing Casing Gasing Gasing Casing Casing Gasing Joints Gasing Joints Float Collar Casing Joints Float Collar Gasing Joints Float Collar Gasing Joints Float Collar Gasing Joints Float Collar Gasing Joints Float Collar Casing Joints Float Shoe Casing Joints Float Shoe Casing Joints Float Collar Casing Joints Float Shoe Casing Joints Float Shoe C	′B	3 \ 🕅										tubing	g 3.4"	4 1/2	4,14	3.5 6	15.4	4,159.	0 J-(55	11.6
4,159.1 6,787.1 10,783.5 11,773.3,57 12,773.5 17,773.5 19,773.5 19,773.5 19,774.5 <t< td=""><td>ift;</td><td>։հ Լ</td><td>0.0.0</td><td></td><td></td><td></td><td></td><td></td><td>74</td><td></td><td></td><td>tubing</td><td>g 3.4"</td><td>4 1/2</td><td>2,628</td><td>.11</td><td>4,159.0</td><td>6,787.</td><td>1 J-(</td><td>55</td><td>11.6</td></t<>	ift;	։հ Լ	0.0.0						74			tubing	g 3.4"	4 1/2	2,628	.11	4,159.0	6,787.	1 J-(55	11.6
6.692.9	΄.1 (Β	1						15.8-	1	-		0.5		4 1/2			6,787.1	6,788.			
6.713.9 6.787.1 6.787.1 6.787.1 6.788.1 6.788.1 6.780.0 6.790.0 7.259.8 7.259.8 7.307.7 7.307.6 7.307.7 7.307.7 7.307.7 7.307.7 7.307.7 7.307.7 7.307.6 7.307.7 7.307.6 7.307.7 7.307.6 7.307.7 7.307.6 7.307.7 7.7	er; 1-	; -h						Casing		w/2.	81" profile			7			6,788.0	6,790.			
6,787.1 EUE OnOff Casing Strings 6,787.1 W2.81* Production Casing, 6,786.1 6,780.0 FRHR Casing Description 6,790.0 ASXRHS Casing Joints Casing Joints 6,797.9 6,798.0 FRHR Casing Joints Casing Joints 6,797.9 6,790.1- Fill: Fill: Casing Joints 7,129.9 Fill: Fill: Fill: Casing Joints 7,259.8 Fill: Fill: Fill: Casing Joints 7,307.7 Casing Joints Casing Joints Casing Joints 7,307.7 Filoat Collar Casing Joints 7,307.7 Filoat Collar Casing Joints 7,307.7 Casing Joints Casing Joints Casing Joints 7,307.7 Filoat Collar Casing Joints Casing Joints 7,307.7 Casing Joints Float Collar Casing Joints 7,307.7 Filoat Float Collar Casing Joints 7,308.7 Float Float Collar Casing Joints	КB	3						6,693.0-				HS-R	HK	7	/	.90	6,790.1	6,798.	J		
6,787.1 w2.81* casing Description 6,788.1 rotation rotation rotation 6,780.0 RHR rotation rotation 6,790.0 RHR rotation rotation 6,797.9 6,790.1 rotation rotation 7,129.9 rotation rotation rotation 7,259.8 rotation rotation rotation 7,307.7 rotation rotation rotation 7,307.7 rotation rotation rotation 7,307.7 rotation rotation rotation 7,307.7 rotation rotation rotation 7,308.7 rotation rotation rotation 7,307.6 rotation rotation rotation	JE	= \									<u>~</u>	7 207									
6,788.1 Production Casing (6,780.0) 6,780.0	1"	"H I							Casir	ing Des	cription	OD (in) W	/Len (lb/ft)					Depth		
6.786.1 0.790.1 fttB Packer ASX1RHS -RHR	0-	-11			-						0	/ S	20	6.00	L-80	1:	5.0 7,	397.8		ť	5.28
6,790.0 ASX1RHS -RHR Nickel coated; 6,797.9 Casing Joints G.790.1- 6,798.0 ftKB Casing Joints G.798.0 ftKB Casing Joints Fili; 7,129.9 7,129.9 Fili; 7,260.0 T,259.8 Casing Joints Fili; 7,260.0 T,262.1 Fili; 7,260.0 T,262.0 Casing Joints Fili; 7,307.6 Casing Joints Fili; 7,307.6 7,307.7 Fili; 7,307.7 Casing Joints Fili; 7,308.6 T,393.6 Surface Casing, 397 Casing Description Surface Casing Casing Joints Fili; 7,308.6 T,393.6 Surface Casing, 397 Casing Description Surface Casing Casing Joints Fili; 7,308.6 T,393.6 7,307.7 Fili; 7,307.6 Fili; 7,307.6 Collar; 7,308.6 T,393.6 Casing Joints Fili; 7,393.6 7,393.7 Fili; 7,394.7 Fili; 7,397.6 Collar; 7,397.6 Casing Joints Fili; 7,397.8	КB	<u>의</u> \									Item Des	-	Jt	6 OD (ii) (in)	Wt (lb/ft	,	е	Lei	n (ft)
Nickel coated; 6,797.9 Image: Control of the second se	IS	S								•	0		15	8	7 7	6.37 6.28	1	0 L-80 0 L-80		6.6	0.8 677.2
6,797.9 Coaled: 6,790.01- 6,798.0 ntkB Casing (6,790.01- 6,798.0) ntkB Casing Joints (6,714.0- 7,307.6 Casing Joints Float Collar Casing Joints Float Collar Float Shoe 7,129.9 7,259.8 Pittig Plug- Permanen t, 7,260.0 7,262.0 Surface Casing, 397 Casing Description Surface Casing Casing Joints Float Collar; 7,308.8 Surface Casing, 397 Casing Description Surface Casing Casing Joints Float Collar; 7,308.8 7,308.7 Float Collar; 7,308.7 Float Collar; 7,308.8 Collar; 7,308.8 7,304.7 Float Casing Joints Float Collar; 7,393.6 7,397.6 T,397.6 Top (ftKB) 1	el	el												1	7	6.28		0 L-80			20.9
ftKB 6,714.0- 7,307.6 7,307.6 7,259.8 Filit 7,130.0- 7,262.1 Filit 7,130.0- 7,262.0 Filit 7,130.0- 7,262.0 Filit 7,130.0- 7,262.0 Filit 7,130.0- 7,262.0 Filit 7,130.0- 7,262.0 Filit 7,130.0- 7,262.0 Filit 7,262.0 Filit 7,308.6 Filit 7,308.6 Filit 7,308.6 Filit 7,393.6 Filit 7,	1-	-							11	•			1	4	7	6.28		0 L-80		5	593.5
7,129.9 - Fill; - Fill; - Fill; - Float Collar Float Shoe 7,259.8 - - - - - Float Shoe Surface Casing, 397 - Casing Description Surface Casing -								6,714.0-						1 2	7 7	6.28 6.28		0 L-80 0 L-80			1.2 84.8
 7,259.8 - 7,262.1 - 7,307.7 - 7,307.7 - 7,308.7 - 7,393.7 - 7,394.7 - 7,397.6 - 7,397.6 - 7,397.6 - 7,259.8 - 7,260.0 Bridge Plug - Permanen t; 7,260.0 Plug - Permanen t; 7,260.0 T,262.0 Plug - Permanen t; 7,260.0 T,262.0 Plug - Permanen t; 7,200.0 T,262.0 Plug - Permanen t; 7,308.8 T,200.0 T,200.0 Plug - Permanen t; 7,308.8 T								Fill;	11	-				2	7	6.28		0 L-80			1.2
7,262.1 - </td <td></td> <td></td> <td></td> <td></td> <td></td> <td>****</td> <td></td> <td>7,260.0</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1</td> <td>7</td> <td>6.28</td> <td>26.0</td> <td>0 L-80</td> <td></td> <td></td> <td>3.0</td>						****		7,260.0						1	7	6.28	26.0	0 L-80			3.0
7,262.1 t; 7,260.0 Surface Casing 7,307.7 - Float Collar; 7,308.7 - 7,307.6 - 7,393.7 - - - 7,393.7 - - - 7,393.7 - - - 7,394.7 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - -								Plug -				7.2ftK		// op (lb/ft)	String Gr			t Depth	Dopth		D (in)
7,307.7 - Float Collar; 7,307.6 Casing Component: Item Des Casing Joints 7,307.7 - <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>t; 7,260.0-</td> <td>Sur</td> <td>face (</td> <td>Casing</td> <td>13 3/</td> <td>/8 54</td> <td></td> <td>J-55</td> <td></td> <td></td> <td>97.2</td> <td>Deptil</td> <td>101</td> <td>12.62</td>								t; 7,260.0-	Sur	face (Casing	13 3/	/8 54		J-55			97.2	Deptil	101	12.62
7,307.7 - Collar; 7,307.6- 7,308.7 Casing Joints 7,308.7 - - - 7,393.7 - - - 7,394.7 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - 7,397.6 - - - - 7,397.6 - - - - 7,397.6 - - - - 7,397.6 - - - - 7,397.6 - -									Cas	sing (S	Jt	6 OD (ii	n) [[D (in)	Wt (lb/ft) Grad	e	Lei	n (ft)
7,308.7 7,308.8 Float Collar 7,308.7 Casing Joints 7,393.7 Float Shoe 7,394.7 Float Collar 7,397.6 7,397.6								Collar;		0	oints			8 13 3	3/8	12.62	54.5	0 J-55			336.9
7,308.7 Joints; 7,308.8- 7,393.7 - Float 7,394.7 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.7 - - 7,397.8 - - 7,397.6 - - 7,397.6 - - 7,397.6 - - 7,397.7 - - 7,397.8 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>7,308.8</td><td></td><td></td><td></td><td></td><td></td><td>13 3</td><td></td><td>12.62</td><td>1</td><td>0 J-55</td><td></td><td></td><td>1.2</td></td<>								7,308.8						13 3		12.62	1	0 J-55			1.2
7,393.7 - 7,393.7 - 7,393.7 - 7,394.7 - 7,397.6 - 7,397.6 -								Joints;	11	-				1 13 3 13 3		12.62 12.62		0 J-55 0 J-55			42.3 1.6
Collar; Collar; 7,394.7 7,393.6- 7,397.6 7,397.8 Collar; Surface Cement, Ca 0 7,394.8- 7,397.6 7,397.8								7,393.6								12.02	01.0	0 0 00			1.0
7,397.6								Collar; 7,393.6-					1/5/20 ⁻	19 11:45		Cemen	ting Start D	ate Cer	mentin	a End	Date
7,397.6								Float	Sur	face (Cement Su		Casing,	397.2ftK	B		019 11:4		5/201		
								7,394.8-		g #	Top (ftKB)	Btm (140 sx (9	2.5 hbl	s) Tvn	Com e G cmt				
7,408.1 -										<u>'</u>	10.0					-, י, ארי	S S Ont				
Released to Imaging: 7/10/2023 9:03:14 AM			_	14.0.10		00.55	1		Pa	age 1	1/2						Rep	ort Print	ed:	3/1/2	2023

WellView[®]

Wellbore Schematic - Components and Cement

Well Name: W LYBROOK 2309-24N SWD 001



District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone: (505) 476-3470 Fax: (505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator: (OGRID:
ENDURING RESOURCES, LLC	372286
6300 S Syracuse Way, Suite 525	Action Number:
Centennial, CO 80111	198021
	Action Type:
	[C-103] Sub. Workover (C-103R)
CONDITIONS	

	-	
Created By		Condition Date
dmcclure	Accepted for Record	7/10/2023

Page 4 of 4

.

Action 198021