

Well Name: POKER LAKE UNIT	Well Location: T24S / R29E / SEC 13 / SWNE /	County or Parish/State: EDDY / NM
Well Number: 276	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM05912	Unit or CA Name: POKER LAKE DELAWARE C	Unit or CA Number: NMNM71016G
US Well Number: 3001535137	Well Status: Producing Oil Well	Operator: XTO PERMIAN OPERATING LLC

Notice of Intent

Sundry ID: 2737916

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 06/26/2023

Time Sundry Submitted: 10:40

Date proposed operation will begin: 06/26/2023

Procedure Description: XTO Permian Operating respectfully submits the NOI to PA well well above. attached is the procedure for your review along with the current and proposed WBD.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

PLU_276_NOI_to_PA_20230626103918.pdf

Well Name: POKER LAKE UNIT

Well Location: T24S / R29E / SEC 13 / SWNE /

County or Parish/State: EDDY / NM

Well Number: 276

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM05912

Unit or CA Name: POKER LAKE DELAWARE C

Unit or CA Number: NMNM71016G

US Well Number: 3001535137

Well Status: Producing Oil Well

Operator: XTO PERMIAN OPERATING LLC

Conditions of Approval

Specialist Review

Poker_Lake_Unit_276_Sundry_ID_2737916_P_A_20230719103310.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CASSIE EVANS

Signed on: JUN 26, 2023 10:39 AM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland

State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: LONG VO

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

BLM POC Email Address: LVO@BLM.GOV

Disposition: Approved

Disposition Date: 07/19/2023


Signature: Long Vo



Downhole Well Profile - with Schematic

Well Name: **POKER LAKE UNIT 276**

API/UWI 3001535137	SAP Cost Center ID 1138401001	Permit Number	State/Province New Mexico	County Eddy	
Surface Location T24S-R29E-S13	Spud Date 3/30/2008 08:00	Original KB Elevation (ft) 3,120.60	Ground Elevation (ft) 3,101.14	KB-Ground Distance (ft) 19.46	Surface Casing Flange Elevation (ft)




Wellbores							
Wellbore Name	Parent Wellbore	Wellbore API/UWI					
Original Hole							
Start Depth (ftKB)	Profile Type						
Section Des	Hole Sz (in)	Act Top (ftKB)	Act Btm (ftKB)				
Conductor	20	19.5	77.0				
Surface	12 1/4	77.0	537.0				
Production	7 7/8	537.0	9,280.0				
Zones							
Zone Name	Top (ftKB)	Btm (ftKB)	Current Status				
JRU 13							
Lwr Brushy Canyon W							
Bone Spring							
Del/BS							
Casing Strings							
Csg Des	Set Depth (ftKB)	OD (in)	Wt/Len (lb/ft)	Grade			
Conductor	77.0	14	36.00				
Surface	536.0	8 5/8	32.00	J-55			
Production	9,279.0	5 1/2	15.50	J-55			
Cement							
Des	Type	Start Date	Top (ftKB)	Btm (ftKB)			
Conductor Cement	Casing	3/15/2008	19.5	77.0			
Surface Casing Cement	Casing	3/31/2008	19.5	537.0			
Production Casing Cement	Casing	4/16/2008	5,014.0	9,280.0			
Production Casing Cement	Casing	4/16/2008	19.5	5,014.0			
Tubing Strings							
Tubing Description	Run Date	Set Depth (ftKB)					
Tubing - Production	10/7/2016	9,202.7					
Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	275	8,668.85	19.5	8,688.4
2-7/8" x 5-1/2" Baker Model "B" TAC	4.892			1	2.85	8,688.4	8,691.2
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	15	476.31	8,691.2	9,167.6
2-7/8" SS Mech SN w/ 1-1/4" x 16' Gas Anchor	2 7/8			1	1.00	9,167.6	9,168.6
2-7/8" x 4' EUE 8rd 6.5 ppf J-55 Perf Tbg Sub	2 7/8		J-55	1	4.10	9,168.6	9,172.7
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	1	29.23	9,172.7	9,201.9
Bull Plug	2 7/8			1	0.80	9,201.9	9,202.7
Rod Strings							
Rod Description	Run Date	Set Depth (ftKB)					
Rod String	8/12/2020	9,295.0					



Downhole Well Profile - with Schematic

Well Name: POKER LAKE UNIT 276

API/UWI 3001535137	SAP Cost Center ID 1138401001	Permit Number	State/Province New Mexico	County Eddy	
Surface Location T24S-R29E-S13	Spud Date 3/30/2008 08:00	Original KB Elevation (ft) 3,120.60	Ground Elevation (ft) 3,101.14	KB-Ground Distance (ft) 19.46	Surface Casing Flange Elevation (ft)



Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)
Polished Rod	1 1/2		SM	1	26.00	0.0	26.0
Pony Rod	7/8			1	8.00	26.0	34.0
Pony Rod	7/8			1	8.00	34.0	42.0
Sucker Rod	7/8		96	129	3,225.00	42.0	3,267.0
Sucker Rod	3/4		96	228	5,700.00	3,267.0	8,967.0
Sinker Bar	1 1/2		C	12	300.00	8,967.0	9,267.0
Rod Centralizer	7/8			1	4.00	9,267.0	9,271.0
Rod Insert Pump	1 1/2			1	24.00	9,271.0	9,295.0

Other In Hole

Run Date	Des	OD (in)	Top (ftKB)	Btm (ftKB)
9/13/2013	PBTD		9,230.0	9,231.0

Perforations

Date	Top (ftKB)	Btm (ftKB)	Linked Zone
12/2/2008	5,965.0	5,970.0	
12/2/2008	6,025.0	6,040.0	
11/27/2008	6,918.0	6,928.0	
5/10/2008	8,127.0	8,132.0	
5/10/2008	8,173.0	8,178.0	
5/10/2008	8,200.0	8,205.0	
5/10/2008	8,233.0	8,238.0	
5/7/2008	8,820.0	8,830.0	
5/7/2008	9,137.0	9,147.0	

Stimulation Intervals

Interval Number	Top (ftKB)	Btm (ftKB)	AIR (bbl/min)	MIR (bbl/min)	Proppant Total (lb)
1	8,820.0	9,147.0			0.0
1	8,820.0	9,147.0			0.0
2	8,127.0	8,238.0			0.0
2	8,127.0	8,238.0			0.0
3	6,918.0	6,928.0			0.0
3	6,918.0	6,928.0			0.0
4	5,965.0	6,040.0			0.0
4	5,965.0	6,040.0			0.0

PLU 276 - Proposed WBD

536' Surface Casing Shoe


3301' T/Delaware

5015' DV Tool

5965' T/ Delaware Perfs

7070' T/Bone Spring

8127' T/Bone Spring Perfs



Circulate Class C cement: 100' to surface.

Spot 25 SKS Class C: 586' to 339'. WOC and tag.

Spot 25 SKS Class C: 3351' to 3104'.

Spot 25 SKS Class C: 5065' to 4818'. WOC and tag.

Spot 25 SKS Class C atop CIBP: 5890' to 5643'. PT CIBP to 500 PSIG for 30 min. WOC and Tag.

Spot 140 SKS **Class H** atop CIBP: 8050' to 8017'. WOC and Tag.

U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Well Name: POKER LAKE UNIT

Well Location: T24S / R29E / SEC 13 / SWNE /

County or Parish/State: EDDY / NM

Well Number: 276

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM05912

Unit or CA Name: POKER LAKE DELAWARE C

Unit or CA Number: NMNM71016G

US Well Number: 3001535137

Well Status: Producing Oil Well

Operator: XTO PERMIAN OPERATING LLC

LONG VO

Digitally signed by
LONG VO
Date: 2023.07.19
11:26:49 -05'00'

Notice of Intent

Sundry ID: 2737916

Type of Submission: Notice of Intent

Type of Action: Plug and Abandonment

Date Sundry Submitted: 06/26/2023

Time Sundry Submitted: 10:40

Date proposed operation will begin: 06/26/2023

Procedure Description: XTO Permian Operating respectfully submits the NOI to PA well well above. attached is the procedure for your review along with the current and proposed WBD.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

PLU_276_NOI_to_PA_20230626103918.pdf

Well Name: POKER LAKE UNIT

Well Location: T24S / R29E / SEC 13 / SWNE /

County or Parish/State: EDDY / NM

Well Number: 276

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM05912

Unit or CA Name: POKER LAKE DELAWARE C

Unit or CA Number: NMNM71016G

US Well Number: 3001535137

Well Status: Producing Oil Well

Operator: XTO PERMIAN OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CASSIE EVANS

Signed on: JUN 26, 2023 10:39 AM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland

State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

PLUG AND ABANDON WELLBORE
POKER LAKE UNIT 276
EDDY COUNTY, NEW MEXICO
Class II

MASIP	MAOP	MAWP	Surface Csg Yield
1,000 psi	1,000 psi	3,000 psi	3930 PSI

SUMMARY: Plug and abandon wellbore according to BLM regulations.


- 1) MIRU plugging company. Set open top steel pit for plugging.
- 2) POOH LD rods and pump.
- 3) ND WH and NU 3K manual BOP. Function test BOP.
- 4) Unset the TAC at 9168.3'. POOH tbq.
- 5) MIRU WLU, RIH GR to 8080'; RIH set CIBP at 8050'; spot 140 SKS **Class H** cement from 8050' to 8017'. WOC and tag to verify TOC. (T/Bone Spring Perf, T/Bone Spring)
- 6) RIH set CIBP at 5890', pressure test to 500 PSI for 30 minutes; spot 25 SKS Class C cement from 5890' to 5643'. WOC and tag to verify TOC. (T/ Delaware Perfs)
- 7) Spot 25 SKS Class C cement from 5065' to 4818'. WOC and tag to verify TOC. (DV Tool)
- 8) Spot 123 SKS Class C cement from 4257' to 3011'. (T/Delaware, Base of Salt) WOC and Tag.
- 9) Spot 25 SKS Class C cement from 586' to 339'. WOC and tag to verify TOC. (Surface Casing Shoe)
- 10) Spot Class C cement from 100' to surface. (~10 SKS) Verify at surface.
- 11) ND BOP and cut off wellhead 5' below surface. RDMO PU, transport trucks, and pump truck.
- 12) Set P&A marker.
- 13) Pull fluid from steel tank and haul to disposal. Release steel tank.



Downhole Well Profile - with Schematic

Well Name: **POKER LAKE UNIT 276**

API/UWI 3001535137	SAP Cost Center ID 1138401001	Permit Number	State/Province New Mexico	County Eddy	
Surface Location T24S-R29E-S13	Spud Date 3/30/2008 08:00	Original KB Elevation (ft) 3,120.60	Ground Elevation (ft) 3,101.14	KB-Ground Distance (ft) 19.46	Surface Casing Flange Elevation (ft)




Wellbores							
Wellbore Name	Parent Wellbore	Wellbore API/UWI					
Original Hole							
Start Depth (ftKB)	Profile Type						
Section Des	Hole Sz (in)	Act Top (ftKB)	Act Btm (ftKB)				
Conductor	20	19.5	77.0				
Surface	12 1/4	77.0	537.0				
Production	7 7/8	537.0	9,280.0				
Zones							
Zone Name	Top (ftKB)	Btm (ftKB)	Current Status				
JRU 13							
Lwr Brushy Canyon W							
Bone Spring							
Del/BS							
Casing Strings							
Csg Des	Set Depth (ftKB)	OD (in)	Wt/Len (lb/ft)	Grade			
Conductor	77.0	14	36.00				
Surface	536.0	8 5/8	32.00	J-55			
Production	9,279.0	5 1/2	15.50	J-55			
Cement							
Des	Type	Start Date	Top (ftKB)	Btm (ftKB)			
Conductor Cement	Casing	3/15/2008	19.5	77.0			
Surface Casing Cement	Casing	3/31/2008	19.5	537.0			
Production Casing Cement	Casing	4/16/2008	5,014.0	9,280.0			
Production Casing Cement	Casing	4/16/2008	19.5	5,014.0			
Tubing Strings							
Tubing Description	Run Date	Set Depth (ftKB)					
Tubing - Production	10/7/2016	9,202.7					
Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	275	8,668.85	19.5	8,688.4
2-7/8" x 5-1/2" Baker Model "B" TAC	4.892			1	2.85	8,688.4	8,691.2
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	15	476.31	8,691.2	9,167.6
2-7/8" SS Mech SN w/ 1-1/4" x 16' Gas Anchor	2 7/8			1	1.00	9,167.6	9,168.6
2-7/8" x 4' EUE 8rd 6.5 ppf J-55 Perf Tbg Sub	2 7/8		J-55	1	4.10	9,168.6	9,172.7
2-7/8" EUE 8rd 6.5 ppf J-55 Tbg	2 7/8	6.50	J-55	1	29.23	9,172.7	9,201.9
Bull Plug	2 7/8			1	0.80	9,201.9	9,202.7
Rod Strings							
Rod Description	Run Date	Set Depth (ftKB)					
Rod String	8/12/2020	9,295.0					



Downhole Well Profile - with Schematic

Well Name: **POKER LAKE UNIT 276**

API/UWI 3001535137	SAP Cost Center ID 1138401001	Permit Number	State/Province New Mexico	County Eddy	
Surface Location T24S-R29E-S13	Spud Date 3/30/2008 08:00	Original KB Elevation (ft) 3,120.60	Ground Elevation (ft) 3,101.14	KB-Ground Distance (ft) 19.46	Surface Casing Flange Elevation (ft)



Item Des	OD (in)	Wt (lb/ft)	Grade	Jts	Len (ft)	Top (ftKB)	Btm (ftKB)
Polished Rod	1 1/2		SM	1	26.00	0.0	26.0
Pony Rod	7/8			1	8.00	26.0	34.0
Pony Rod	7/8			1	8.00	34.0	42.0
Sucker Rod	7/8		96	129	3,225.00	42.0	3,267.0
Sucker Rod	3/4		96	228	5,700.00	3,267.0	8,967.0
Sinker Bar	1 1/2		C	12	300.00	8,967.0	9,267.0
Rod Centralizer	7/8			1	4.00	9,267.0	9,271.0
Rod Insert Pump	1 1/2			1	24.00	9,271.0	9,295.0

Other In Hole				
Run Date	Des	OD (in)	Top (ftKB)	Btm (ftKB)
9/13/2013	PBTD		9,230.0	9,231.0

Perforations			
Date	Top (ftKB)	Btm (ftKB)	Linked Zone
12/2/2008	5,965.0	5,970.0	
12/2/2008	6,025.0	6,040.0	
11/27/2008	6,918.0	6,928.0	
5/10/2008	8,127.0	8,132.0	
5/10/2008	8,173.0	8,178.0	
5/10/2008	8,200.0	8,205.0	
5/10/2008	8,233.0	8,238.0	
5/7/2008	8,820.0	8,830.0	
5/7/2008	9,137.0	9,147.0	

Stimulation Intervals					
Interval Number	Top (ftKB)	Btm (ftKB)	AIR (bbl/min)	MIR (bbl/min)	Proppant Total (lb)
1	8,820.0	9,147.0			0.0
1	8,820.0	9,147.0			0.0
2	8,127.0	8,238.0			0.0
2	8,127.0	8,238.0			0.0
3	6,918.0	6,928.0			0.0
3	6,918.0	6,928.0			0.0
4	5,965.0	6,040.0			0.0
4	5,965.0	6,040.0			0.0

PLU 276 - Proposed WBD

536' Surface Casing Shoe


3301' T/Delaware

5015' DV Tool

5965' T/ Delaware Perfs

7070' T/Bone Spring

8127' T/Bone Spring Perfs



Approval Subject to

General Requirements and

Special Stipulations

Attached

Circulate Class C cement: 100' to surface.

Spot 25 SKS Class C: 586' to 339'. WOC and tag.

Spot 25 SKS Class C: 3351' to 3104'.

Spot 25 SKS Class C: 5065' to 4818'. WOC and tag.

Spot 25 SKS Class C atop CIBP: 5890' to 5643'. PT CIBP to 500 PSIG for 30 min. WOC and Tag.

Spot 140 SKS **Class H** atop CIBP: 8050' to 8017'. WOC and Tag.

**BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972**

**Permanent Abandonment of Federal Wells
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of brine water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines **(Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure)**. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias
Environmental Protection Specialist
575-234-6230

Crisha Morgan
Environmental Protection Specialist
575-234-5987

Jose Martinez-Colon
Environmental Protection Specialist
575-234-5951

Mark Mattozzi
Environmental Protection Specialist
575-234-5713

Robert Duenas
Environmental Protection Specialist
575-234-2229

Sundry ID		2737916					
Plug Type	Top	Bottom	Length	Tag	Sacks	Cement Class	Notes
Surface Plug	0.00	100.00	100.00	Tag/Verify	25.00	C	Spot cement from 100' to surface.
Shoe Plug	481.63	587.00	105.37	Tag/Verify			
Top of Salt @ 548	492.52	598.00	105.48	Tag/Verify	25.00		Spot cement from 598' to 481'. WOC and Tag.
Base of Salt @ 3092	3011.08	3142.00	130.92	Tag/Verify			
Delaware @ 4207	4114.93	4257.00	142.07	If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations	123.00	C	Spot cement from 4257' to 3011'. WOC and Tag.
DV tool plug	4914.85	5065.00	150.15	Tag/Verify	25.00	C	Spot cement from 5065' to 4914'. WOC and Tag.
CIBP Plug	5855.00	5890.00	35.00	If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations	25.00	C	Set CIBP at 5890'. Leak test CIBP. Spot 25 sxs on top.
Perforations Plug (If No CIBP)	5915.00	6978.00	1063.00	Tag/Verify			
Bonesprings @ 7070	6949.30	7120.00	170.70	If solid			
Shoe Plug	7266.10	7440.00	173.90	Tag/Verify			

				If solid base no need to Tag (CIBP present and/or Mechanical Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforations			
CIBP Plug	8015.00	8050.00	35.00		136.00	C	Tag TD. Set CIBP at 8050'. Spot cement from 8050' to 6949'. WOC and Tag.
Perforations Plug (If No CIBP)	8077.00	9197.00	1120.00	Tag/Verify			

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole.

Class H >7500'

Class C <7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater
R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft³/sx

Class H: 1.06 ft³/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement	Low		
Shoe @	537.00		
Shoe @	7390.00		
Perforatons Top @	5965.00	Perforations	6928.00
Perforatons Top @	8127.00	Perforations	9147.00
DV Tool @	5015.00	CIBP @	8050.00
		CIBP @	5890.00

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 243287

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 243287
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
john.harrison	Accepted for record - NMOCD JRH 7/25/23. BLM approved P&A 7/19/23	7/25/2023