

Submit 1 Copy To Appropriate District Office
 District I – (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II – (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III – (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV – (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

Form C-103
 Revised August 1, 2011

WELL API NO. 30-015-47572	
5. Indicate Type of Lease STATE ☐ FEE ☒	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Spud Muffin 31-30	
8. Well Number 235H	
9. OGRID Number 6137	
10. Pool name or Wildcat CEDAR CANYON; BONE SPRING	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐ 2. Name of Operator Devon Energy Production Company, L.P. 3. Address of Operator 333 West Sheridan, Oklahoma City, OK 73102 4. Well Location Unit Letter <u>O</u> : <u>775</u> feet from the <u>South</u> line and <u>1785</u> feet from the <u>East</u> line Section <u>31</u> Township <u>23S</u> Range <u>29E</u> NMPM County <u>Eddy</u> 11. Elevation (Show whether DR, RKB, RT, GR, etc.) GL: 2959'	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐ DOWNHOLE COMMINGLE ☐ OTHER: BHL change ☒		SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ P AND A ☐ CASING/CEMENT JOB ☐ OTHER: ☐	
--	--	--	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Devon Energy Production Co., L.P. (Devon) respectfully requests to move the BHL on the subject well.
 Please see attached revised C102, drill plan, and directional plan.
 Proposed BHL: NENE, 20 FNL, 375 FEL, 30-23S-29E

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shayda Omoumi TITLE Regulatory Compliance Professional DATE 7/27/2023
 Type or print name Shayda Omoumi E-mail address: shayda.omoumi@devon.com PHONE: 405-552-3513
For State Use Only

APPROVED BY: Ward Rikala TITLE Petroleum Specialist A DATE 09/05/2023
 Conditions of Approval (if any):

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015-47572	² Pool Code 11520	³ Pool Name CEDAR CANYON; BONE SPRING
⁴ Property Code 320827	⁵ Property Name SPUD MUFFIN 31 30	⁶ Well Number 235H
⁷ OGRID No. 6137	⁸ Operator Name DEVON ENERGY PRODUCTION COMPANY, L.P.	⁹ Elevation 2959.2

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
O	31	23 S	29 E		775	SOUTH	1785	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
A	30	23 S	29 E		20	NORTH	375	EAST	EDDY

¹² Dedicated Acres 320	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

	SPUD MUFFIN 31-30 235H EL. = 2959.2 GEODETTIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION N. = 457136.14 E. = 637870.09 LAT. = 32.2563565°N LONG. = 104.0210546°W KICK OFF POINT CALLS 60' FSL 376' FEL N. = 456410.8 E. = 639293.6 LAT. = 32.2542577°N LONG. = 104.01653838°W FIRST TAKE POINT 100' FSL, 375' FEL N. = 456451.26 E. = 639293.63 LAT. = 32.2544624°N LONG. = 104.0164561°W LAST TAKE POINT 100' FNL, 375' FEL N. = 466800.33 E. = 639175.04 LAT. = 32.2829114°N LONG. = 104.0167409°W BOTTOM OF HOLE 20' FNL, 375' FEL N. = 466880.35 E. = 639174.79 LAT. = 32.2831314°N LONG. = 104.0167410°W CORNER COORDINATES TABLE NAD 83 NMSP EAST <table border="1"> <tr><td>A</td><td>N. = 466889.85</td><td>E. = 639549.68</td></tr> <tr><td>B</td><td>N. = 466963.00</td><td>E. = 636940.42</td></tr> <tr><td>C</td><td>N. = 464302.93</td><td>E. = 636926.75</td></tr> <tr><td>D</td><td>N. = 461649.00</td><td>E. = 636913.10</td></tr> <tr><td>E</td><td>N. = 458998.36</td><td>E. = 636967.53</td></tr> <tr><td>F</td><td>N. = 456367.27</td><td>E. = 637021.56</td></tr> <tr><td>G</td><td>N. = 456348.63</td><td>E. = 639670.65</td></tr> <tr><td>H</td><td>N. = 458974.88</td><td>E. = 639618.59</td></tr> <tr><td>I</td><td>N. = 461601.10</td><td>E. = 639566.56</td></tr> <tr><td>J</td><td>N. = 464237.89</td><td>E. = 639558.14</td></tr> </table> LEGEND --- SECTION LINE --- QUARTER LINE --- LEASE LINE --- WELL PATH	A	N. = 466889.85	E. = 639549.68	B	N. = 466963.00	E. = 636940.42	C	N. = 464302.93	E. = 636926.75	D	N. = 461649.00	E. = 636913.10	E	N. = 458998.36	E. = 636967.53	F	N. = 456367.27	E. = 637021.56	G	N. = 456348.63	E. = 639670.65	H	N. = 458974.88	E. = 639618.59	I	N. = 461601.10	E. = 639566.56	J	N. = 464237.89	E. = 639558.14	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Shayda Omoumi</i> 7/25/2023 Signature Date Shayda Omoumi Printed Name <i>shayda.omoumi@dm.com</i> E-mail Address ¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JULY 12, 2023 Date of Survey <i>Shayda Omoumi</i> Signature and Seal of Professional Surveyor Certificate Number: 12797 SURV. NO. 8479B
A	N. = 466889.85	E. = 639549.68																														
B	N. = 466963.00	E. = 636940.42																														
C	N. = 464302.93	E. = 636926.75																														
D	N. = 461649.00	E. = 636913.10																														
E	N. = 458998.36	E. = 636967.53																														
F	N. = 456367.27	E. = 637021.56																														
G	N. = 456348.63	E. = 639670.65																														
H	N. = 458974.88	E. = 639618.59																														
I	N. = 461601.10	E. = 639566.56																														
J	N. = 464237.89	E. = 639558.14																														

Intent ☒ As Drilled ☐

API #		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, L.P.	Property Name: SPUD MUFFIN 31 30	Well Number 235H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
P	31	23S	29E		60	SOUTH	376	EAST	EDDY
Latitude 32.25425771					Longitude -104.01653838				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
P	31	23S	29E		100	SOUTH	375	EAST	EDDY
Latitude 32.2544624					Longitude 104.0164561				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
A	30	23S	29E		100	NORTH	375	EAST	EDDY
Latitude 32.2829114					Longitude 104.0167409				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?

☐ N

Is this well an infill well?

☐ Y

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-45303		
Operator Name: DEVON ENERGY PRODUCTION COMPANY, L.P.	Property Name: SPUD MUFFIN 31 30	Well Number 334H

KZ 06/29/2018


SPUD MUFFIN 31-30 235H



Well: SPUD MUFFIN 31-30 235H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	117.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
3000.00	20.00	117.00	2979.82	-78.43	153.94	-57.31	2.00	Hold Tangent
6660.81	20.00	117.00	6419.85	-646.86	1269.54	-472.65	0.00	Drop to Vertical
7660.81	0.00	117.00	7399.67	-725.30	1423.48	-529.96	2.00	Hold Vertical
8203.19	0.00	359.35	7942.05	-725.30	1423.48	-529.96	0.00	KOP
9101.34	89.81	359.35	8515.00	-154.23	1417.00	35.19	10.00	Landing Point
19000.46	89.81	359.35	8547.00	9744.21	1304.70	9831.17	0.00	BHL

**Key Depths**

	MD (ft)	TVD (ft)
Rustler	114.00	114.00
Top of Salt	469.00	469.00
Base of Salt	2547.32	2544.00
Lamar	2794.13	2784.00
Bell Canyon	2794.13	2784.00
Cherry Canyon	3738.74	3674.00
Brushy Canyon	5388.21	5224.00
1st Bone Spring Lime	6728.79	6484.00
1st Bone Spring Sand	7730.14	7469.00
Bone Spring 2nd / Point of Penetration	8551.14	8269.00
Exit	18920.46	8546.75

SHL
KOP
Point of Penetration
Exit
BHL

MD (ft)	TVD (ft)	Lat (°)	Long (°)	Section Footages
0.00	0.00	32.2563	-104.0211	775' FSL, 1785' FEL of Sec 31 in T23S, R29E
8203.19	7942.05	32.2543	-104.0165	60' FSL, 376' FEL of Sec 31 in T23S, R29E
8551.14	8269.00	32.2545	-104.0165	100' FSL, 375' FEL of Sec 31 in T23S, R29E
18920.46	8546.75	32.2829	-104.0167	100' FNL, 375' FEL of Sec 30 in T23S, R29E
19000.46	8547.00	32.2830	-104.0168	20' FNL, 375' FEL of Sec 30 in T23S, R29E

SPUD MUFFIN 31-30 235H



Well: SPUD MUFFIN 31-30 235H
 County: Eddy
 Wellbore: Permit Plan
 Design: Permit Plan #1

Geodetic System: US State Plane 1983
 Datum: North American Datum 1927
 Ellipsoid: Clarke 1866
 Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	117.00	100.00	0.00	0.00	0.00	0.00	
114.00	0.00	117.00	114.00	0.00	0.00	0.00	0.00	Rustler
200.00	0.00	117.00	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	117.00	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	117.00	400.00	0.00	0.00	0.00	0.00	
469.00	0.00	117.00	469.00	0.00	0.00	0.00	0.00	Top of Salt
500.00	0.00	117.00	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	117.00	600.00	0.00	0.00	0.00	0.00	
700.00	0.00	117.00	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	117.00	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	117.00	900.00	0.00	0.00	0.00	0.00	
1000.00	0.00	117.00	1000.00	0.00	0.00	0.00	0.00	
1100.00	0.00	117.00	1100.00	0.00	0.00	0.00	0.00	
1200.00	0.00	117.00	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	117.00	1300.00	0.00	0.00	0.00	0.00	
1400.00	0.00	117.00	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	117.00	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	117.00	1600.00	0.00	0.00	0.00	0.00	
1700.00	0.00	117.00	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	117.00	1800.00	0.00	0.00	0.00	0.00	
1900.00	0.00	117.00	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	117.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2100.00	2.00	117.00	2099.98	-0.79	1.55	-0.58	2.00	
2200.00	4.00	117.00	2199.84	-3.17	6.22	-2.31	2.00	
2300.00	6.00	117.00	2299.45	-7.12	13.98	-5.21	2.00	
2400.00	8.00	117.00	2398.70	-12.66	24.84	-9.25	2.00	
2500.00	10.00	117.00	2497.47	-19.76	38.78	-14.44	2.00	
2547.32	10.95	117.00	2544.00	-23.66	46.44	-17.29	2.00	Base of Salt
2600.00	12.00	117.00	2595.62	-28.42	55.78	-20.77	2.00	
2700.00	14.00	117.00	2693.06	-38.63	75.82	-28.23	2.00	
2794.13	15.88	117.00	2784.00	-49.65	97.45	-36.28	2.00	Lamar, Bell Canyon
2800.00	16.00	117.00	2789.64	-50.38	98.88	-36.81	2.00	
2900.00	18.00	117.00	2885.27	-63.65	124.93	-46.51	2.00	
3000.00	20.00	117.00	2979.82	-78.43	153.94	-57.31	2.00	Hold Tangent
3100.00	20.00	117.00	3073.78	-93.96	184.41	-68.66	0.00	
3200.00	20.00	117.00	3167.75	-109.49	214.89	-80.00	0.00	
3300.00	20.00	117.00	3261.72	-125.02	245.36	-91.35	0.00	
3400.00	20.00	117.00	3355.69	-140.54	275.83	-102.69	0.00	
3500.00	20.00	117.00	3449.66	-156.07	306.31	-114.04	0.00	
3600.00	20.00	117.00	3543.63	-171.60	336.78	-125.39	0.00	
3700.00	20.00	117.00	3637.60	-187.13	367.26	-136.73	0.00	
3738.74	20.00	117.00	3674.00	-193.14	379.06	-141.13	0.00	Cherry Canyon
3800.00	20.00	117.00	3731.57	-202.65	397.73	-148.08	0.00	
3900.00	20.00	117.00	3825.54	-218.18	428.21	-159.42	0.00	
4000.00	20.00	117.00	3919.51	-233.71	458.68	-170.77	0.00	
4100.00	20.00	117.00	4013.48	-249.24	489.15	-182.11	0.00	
4200.00	20.00	117.00	4107.45	-264.76	519.63	-193.46	0.00	
4300.00	20.00	117.00	4201.42	-280.29	550.10	-204.81	0.00	
4400.00	20.00	117.00	4295.39	-295.82	580.58	-216.15	0.00	
4500.00	20.00	117.00	4389.35	-311.34	611.05	-227.50	0.00	
4600.00	20.00	117.00	4483.32	-326.87	641.52	-238.84	0.00	
4700.00	20.00	117.00	4577.29	-342.40	672.00	-250.19	0.00	
4800.00	20.00	117.00	4671.26	-357.93	702.47	-261.53	0.00	
4900.00	20.00	117.00	4765.23	-373.45	732.95	-272.88	0.00	
5000.00	20.00	117.00	4859.20	-388.98	763.42	-284.23	0.00	
5100.00	20.00	117.00	4953.17	-404.51	793.90	-295.57	0.00	
5200.00	20.00	117.00	5047.14	-420.04	824.37	-306.92	0.00	
5300.00	20.00	117.00	5141.11	-435.56	854.84	-318.26	0.00	
5388.21	20.00	117.00	5224.00	-449.26	881.73	-328.27	0.00	Brushy Canyon
5400.00	20.00	117.00	5235.08	-451.09	885.32	-329.61	0.00	
5500.00	20.00	117.00	5329.05	-466.62	915.79	-340.95	0.00	
5600.00	20.00	117.00	5423.02	-482.15	946.27	-352.30	0.00	
5700.00	20.00	117.00	5516.99	-497.67	976.74	-363.65	0.00	
5800.00	20.00	117.00	5610.96	-513.20	1007.22	-374.99	0.00	
5900.00	20.00	117.00	5704.92	-528.73	1037.69	-386.34	0.00	
6000.00	20.00	117.00	5798.89	-544.25	1068.16	-397.68	0.00	
6100.00	20.00	117.00	5892.86	-559.78	1098.64	-409.03	0.00	
6200.00	20.00	117.00	5986.83	-575.31	1129.11	-420.37	0.00	
6300.00	20.00	117.00	6080.80	-590.84	1159.59	-431.72	0.00	



Well: SPUD MUFFIN 31-30 235H
County: Eddy
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6400.00	20.00	117.00	6174.77	-606.36	1190.06	-443.07	0.00	
6500.00	20.00	117.00	6268.74	-621.89	1220.54	-454.41	0.00	
6600.00	20.00	117.00	6362.71	-637.42	1251.01	-465.76	0.00	
6660.81	20.00	117.00	6419.85	-646.86	1269.54	-472.65	0.00	Drop to Vertical
6700.00	19.22	117.00	6456.77	-652.83	1281.26	-477.02	2.00	
6728.79	18.64	117.00	6484.00	-657.07	1289.58	-480.12	2.00	1st Bone Spring Lime
6800.00	17.22	117.00	6551.75	-667.02	1309.11	-487.39	2.00	
6900.00	15.22	117.00	6647.77	-679.70	1333.99	-496.65	2.00	
7000.00	13.22	117.00	6744.70	-690.85	1355.87	-504.80	2.00	
7100.00	11.22	117.00	6842.43	-700.46	1374.72	-511.82	2.00	
7200.00	9.22	117.00	6940.84	-708.51	1390.53	-517.70	2.00	
7300.00	7.22	117.00	7039.81	-715.00	1403.26	-522.44	2.00	
7400.00	5.22	117.00	7139.22	-719.91	1412.91	-526.03	2.00	
7500.00	3.22	117.00	7238.94	-723.25	1419.46	-528.47	2.00	
7600.00	1.22	117.00	7338.86	-725.00	1422.90	-529.76	2.00	
7660.81	0.00	117.00	7399.67	-725.30	1423.48	-529.96	2.00	Hold Vertical
7700.00	0.00	359.35	7438.86	-725.30	1423.48	-529.97	0.00	
7730.14	0.00	359.35	7469.00	-725.30	1423.48	-529.97	0.00	1st Bone Spring Sand
7800.00	0.00	359.35	7538.86	-725.30	1423.48	-529.97	0.00	
7900.00	0.00	359.35	7638.86	-725.30	1423.48	-529.97	0.00	
8000.00	0.00	359.35	7738.86	-725.30	1423.48	-529.97	0.00	
8100.00	0.00	359.35	7838.86	-725.30	1423.48	-529.97	0.00	
8200.00	0.00	359.35	7938.86	-725.30	1423.48	-529.97	0.00	
8203.19	0.00	359.35	7942.05	-725.30	1423.48	-529.96	0.00	KOP
8300.00	9.68	359.35	8038.40	-717.14	1423.39	-521.90	10.00	
8400.00	19.68	359.35	8135.01	-691.83	1423.10	-496.85	10.00	
8500.00	29.68	359.35	8225.76	-650.13	1422.62	-455.58	10.00	
8551.14	34.80	359.35	8269.00	-622.86	1422.32	-428.59	10.00	Bone Spring 2nd / Point of Penetration
8600.00	39.68	359.35	8307.89	-593.30	1421.98	-399.34	10.00	
8700.00	49.68	359.35	8378.90	-523.08	1421.18	-329.85	10.00	
8800.00	59.68	359.35	8436.64	-441.59	1420.26	-249.20	10.00	
8900.00	69.68	359.35	8479.35	-351.32	1419.23	-159.86	10.00	
9000.00	79.68	359.35	8505.74	-255.00	1418.14	-64.54	10.00	
9100.00	89.68	359.35	8515.00	-155.57	1417.01	33.86	10.00	
9101.34	89.81	359.35	8515.00	-154.23	1417.00	35.19	10.00	Landing Point
9200.00	89.81	359.35	8515.32	-55.57	1415.88	132.82	0.00	
9300.00	89.81	359.35	8515.64	44.42	1414.74	231.78	0.00	
9400.00	89.81	359.35	8515.97	144.41	1413.61	330.74	0.00	
9500.00	89.81	359.35	8516.29	244.41	1412.47	429.70	0.00	
9600.00	89.81	359.35	8516.61	344.40	1411.34	528.66	0.00	
9700.00	89.81	359.35	8516.94	444.39	1410.20	627.61	0.00	
9800.00	89.81	359.35	8517.26	544.39	1409.07	726.57	0.00	
9900.00	89.81	359.35	8517.58	644.38	1407.93	825.53	0.00	
10000.00	89.81	359.35	8517.91	744.37	1406.80	924.49	0.00	
10100.00	89.81	359.35	8518.23	844.37	1405.66	1023.44	0.00	
10200.00	89.81	359.35	8518.55	944.36	1404.53	1122.40	0.00	
10300.00	89.81	359.35	8518.88	1044.35	1403.39	1221.36	0.00	
10400.00	89.81	359.35	8519.20	1144.34	1402.26	1320.32	0.00	
10500.00	89.81	359.35	8519.52	1244.34	1401.12	1419.28	0.00	
10600.00	89.81	359.35	8519.85	1344.33	1399.99	1518.23	0.00	
10700.00	89.81	359.35	8520.17	1444.32	1398.85	1617.19	0.00	
10800.00	89.81	359.35	8520.49	1544.32	1397.72	1716.15	0.00	
10900.00	89.81	359.35	8520.82	1644.31	1396.58	1815.11	0.00	
11000.00	89.81	359.35	8521.14	1744.30	1395.45	1914.07	0.00	
11100.00	89.81	359.35	8521.46	1844.30	1394.31	2013.02	0.00	
11200.00	89.81	359.35	8521.79	1944.29	1393.18	2111.98	0.00	
11300.00	89.81	359.35	8522.11	2044.28	1392.05	2210.94	0.00	
11400.00	89.81	359.35	8522.43	2144.27	1390.91	2309.90	0.00	
11500.00	89.81	359.35	8522.76	2244.27	1389.78	2408.86	0.00	
11600.00	89.81	359.35	8523.08	2344.26	1388.64	2507.81	0.00	
11700.00	89.81	359.35	8523.40	2444.25	1387.51	2606.77	0.00	
11800.00	89.81	359.35	8523.73	2544.25	1386.37	2705.73	0.00	
11900.00	89.81	359.35	8524.05	2644.24	1385.24	2804.69	0.00	
12000.00	89.81	359.35	8524.37	2744.23	1384.10	2903.65	0.00	
12100.00	89.81	359.35	8524.70	2844.23	1382.97	3002.60	0.00	
12200.00	89.81	359.35	8525.02	2944.22	1381.83	3101.56	0.00	
12300.00	89.81	359.35	8525.34	3044.21	1380.70	3200.52	0.00	
12400.00	89.81	359.35	8525.67	3144.21	1379.56	3299.48	0.00	
12500.00	89.81	359.35	8525.99	3244.20	1378.43	3398.44	0.00	
12600.00	89.81	359.35	8526.31	3344.19	1377.29	3497.39	0.00	

SPUD MUFFIN 31-30 235H



Well: SPUD MUFFIN 31-30 235H

County: Eddy

Wellbore: Permit Plan

Design: Permit Plan #1

Geodetic System: US State Plane 1983

Datum: North American Datum 1927

Ellipsoid: Clarke 1866

Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
12700.00	89.81	359.35	8526.64	3444.18	1376.16	3596.35	0.00	
12800.00	89.81	359.35	8526.96	3544.18	1375.02	3695.31	0.00	
12900.00	89.81	359.35	8527.28	3644.17	1373.89	3794.27	0.00	
13000.00	89.81	359.35	8527.61	3744.16	1372.75	3893.23	0.00	
13100.00	89.81	359.35	8527.93	3844.16	1371.62	3992.18	0.00	
13200.00	89.81	359.35	8528.25	3944.15	1370.48	4091.14	0.00	
13300.00	89.81	359.35	8528.58	4044.14	1369.35	4190.10	0.00	
13400.00	89.81	359.35	8528.90	4144.14	1368.21	4289.06	0.00	
13500.00	89.81	359.35	8529.23	4244.13	1367.08	4388.02	0.00	
13600.00	89.81	359.35	8529.55	4344.12	1365.94	4486.97	0.00	
13700.00	89.81	359.35	8529.87	4444.11	1364.81	4585.93	0.00	
13800.00	89.81	359.35	8530.20	4544.11	1363.67	4684.89	0.00	
13900.00	89.81	359.35	8530.52	4644.10	1362.54	4783.85	0.00	
14000.00	89.81	359.35	8530.84	4744.09	1361.40	4882.80	0.00	
14100.00	89.81	359.35	8531.17	4844.09	1360.27	4981.76	0.00	
14200.00	89.81	359.35	8531.49	4944.08	1359.13	5080.72	0.00	
14300.00	89.81	359.35	8531.81	5044.07	1358.00	5179.68	0.00	
14400.00	89.81	359.35	8532.14	5144.07	1356.86	5278.64	0.00	
14500.00	89.81	359.35	8532.46	5244.06	1355.73	5377.59	0.00	
14600.00	89.81	359.35	8532.78	5344.05	1354.59	5476.55	0.00	
14700.00	89.81	359.35	8533.11	5444.05	1353.46	5575.51	0.00	
14800.00	89.81	359.35	8533.43	5544.04	1352.32	5674.47	0.00	
14900.00	89.81	359.35	8533.75	5644.03	1351.19	5773.43	0.00	
15000.00	89.81	359.35	8534.08	5744.02	1350.05	5872.38	0.00	
15100.00	89.81	359.35	8534.40	5844.02	1348.92	5971.34	0.00	
15200.00	89.81	359.35	8534.72	5944.01	1347.78	6070.30	0.00	
15300.00	89.81	359.35	8535.05	6044.00	1346.65	6169.26	0.00	
15400.00	89.81	359.35	8535.37	6144.00	1345.51	6268.22	0.00	
15500.00	89.81	359.35	8535.69	6243.99	1344.38	6367.17	0.00	
15600.00	89.81	359.35	8536.02	6343.98	1343.24	6466.13	0.00	
15700.00	89.81	359.35	8536.34	6443.98	1342.11	6565.09	0.00	
15800.00	89.81	359.35	8536.66	6543.97	1340.97	6664.05	0.00	
15900.00	89.81	359.35	8536.99	6643.96	1339.84	6763.01	0.00	
16000.00	89.81	359.35	8537.31	6743.95	1338.70	6861.96	0.00	
16100.00	89.81	359.35	8537.63	6843.95	1337.57	6960.92	0.00	
16200.00	89.81	359.35	8537.96	6943.94	1336.43	7059.88	0.00	
16300.00	89.81	359.35	8538.28	7043.93	1335.30	7158.84	0.00	
16400.00	89.81	359.35	8538.60	7143.93	1334.16	7257.80	0.00	
16500.00	89.81	359.35	8538.93	7243.92	1333.03	7356.75	0.00	
16600.00	89.81	359.35	8539.25	7343.91	1331.89	7455.71	0.00	
16700.00	89.81	359.35	8539.57	7443.91	1330.76	7554.67	0.00	
16800.00	89.81	359.35	8539.90	7543.90	1329.62	7653.63	0.00	
16900.00	89.81	359.35	8540.22	7643.89	1328.49	7752.59	0.00	
17000.00	89.81	359.35	8540.54	7743.88	1327.35	7851.54	0.00	
17100.00	89.81	359.35	8540.87	7843.88	1326.22	7950.50	0.00	
17200.00	89.81	359.35	8541.19	7943.87	1325.08	8049.46	0.00	
17300.00	89.81	359.35	8541.51	8043.86	1323.95	8148.42	0.00	
17400.00	89.81	359.35	8541.84	8143.86	1322.81	8247.37	0.00	
17500.00	89.81	359.35	8542.16	8243.85	1321.68	8346.33	0.00	
17600.00	89.81	359.35	8542.48	8343.84	1320.54	8445.29	0.00	
17700.00	89.81	359.35	8542.81	8443.84	1319.41	8544.25	0.00	
17800.00	89.81	359.35	8543.13	8543.83	1318.27	8643.21	0.00	
17900.00	89.81	359.35	8543.45	8643.82	1317.14	8742.16	0.00	
18000.00	89.81	359.35	8543.78	8743.82	1316.00	8841.12	0.00	
18100.00	89.81	359.35	8544.10	8843.81	1314.87	8940.08	0.00	
18200.00	89.81	359.35	8544.42	8943.80	1313.73	9039.04	0.00	
18300.00	89.81	359.35	8544.75	9043.79	1312.60	9138.00	0.00	
18400.00	89.81	359.35	8545.07	9143.79	1311.46	9236.95	0.00	
18500.00	89.81	359.35	8545.39	9243.78	1310.33	9335.91	0.00	
18600.00	89.81	359.35	8545.72	9343.77	1309.19	9434.87	0.00	
18700.00	89.81	359.35	8546.04	9443.77	1308.06	9533.83	0.00	
18800.00	89.81	359.35	8546.36	9543.76	1306.92	9632.79	0.00	
18900.00	89.81	359.35	8546.69	9643.75	1305.79	9731.74	0.00	
18920.46	89.81	359.35	8546.75	9664.21	1305.56	9751.99	0.00	Exit
19000.00	89.81	359.35	8547.01	9743.75	1304.65	9830.70	0.00	
19000.46	89.81	359.35	8547.00	9744.21	1304.70	9831.17	0.00	BHL

SPUD MUFFIN 31-30 235H

1. Geologic Formations

TVD of target	8547	Pilot hole depth	N/A
MD at TD:	19000	Deepest expected fresh water	

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Rustler	114		
Top of Salt	469		
Base of Salt	2544		
Lamar	2784		
Bell Canyon	2784		
Cherry Canyon	3674		
Brushy Canyon	5224		
1st Bone Spring Lime	6484		
1st Bone Spring Sand	7469		
Bone Spring 2nd	8269		

*H2S, water flows, loss of circulation, abnormal pressures, etc.

SPUD MUFFIN 31-30 235H

2. Casing Program

Hole Size	Csg. Size	Wt (PPF)	Grade	Conn	Casing Interval		Casing Interval	
					From (MD)	To (MD)	From (TVD)	To (TVD)
17 1/2	13 3/8	48	H40	BTC	0	139	0	139
12 1/4	9 5/8	40	J-55	BTC	0	2644	0	2644
8 3/4	5 1/2	17	P110	BTC	0	19000	0	8547

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.

SPUD MUFFIN 31-30 235H

3. Cementing Program (3-String Primary Design)

Casing	# Sks	TOC	Wt. (lb/gal)	Yld (ft ³ /sack)	Slurry Description
Surface	139	Surf	13.2	1.4	Lead: Class C Cement + additives
Int 1	266	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	2144	13.2	1.4	Tail: Class H / C + additives
Int 1 Intermediate Squeeze	345	Surf	9.0	3.3	Squeeze Lead: Class C Cement + additives
	266	Surf	9.0	3.3	Lead: Class C Cement + additives
	154	2144	13.2	1.4	Tail: Class H / C + additives
Production	516	2144	9.0	3.3	Lead: Class H / C + additives
	2083	8203	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate	30%
Production	10%

SPUD MUFFIN 31-30 235H

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-5/8"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
Production	13-5/8"	5M	Annular	X	50% of rated working pressure
			Blind Ram	X	5M
			Pipe Ram		
			Double Ram	X	
			Other*		
			Annular (5M)		
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		

SPUD MUFFIN 31-30 235H

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	Brine	10-10.5
Production	WBM	8.5-9

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned		Interval
	Resistivity	
	Density	
X	CBL	Production casing
X	Mud log	KOP to TD
	PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH pressure at deepest TVD	4000
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H ₂ S is present
Y	H ₂ S plan attached.

SPUD MUFFIN 31-30 235H

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pad.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments

X Directional Plan

 Other, describe

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 244984

CONDITIONS

Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102	OGRID: 6137
	Action Number: 244984
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	Original COA's still apply.	9/5/2023