Form C-103 State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 **Energy, Minerals and Natural Resources** Permit 339402 District II 811 S. First St., Artesia, NM 88210 WELL APLNIIMBER Oil Conservation Division Phone:(575) 748-1283 Fax:(575) 748-9720 30-015-53495 **District III** 5. Indicate Type of Lease 1220 S. St Francis Dr. 1000 Rio Brazos Rd., Aztec, NM 87410 Private Phone:(505) 334-6178 Fax:(505) 334-6170 6 State Oil & Gas Lease No. District IV **Santa Fe, NM 87505** 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS STROS 29 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number Oil 021H 2. Name of Operator 9. OGRID Number Spur Energy Partners LLC 328947 3. Address of Operator 10. Pool name or Wildcat 9655 Katy Freeway, Suite 500, Houston, TX 77024 4. Well Location : 1875 feet from the N Unit Letter H line and feet 285 from the E Section Township 18S Range 26E NMPM County Eddy 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3439 GR Pit or Below-grade Tank Application or Closure Pit Type Depth to Groundwater \_\_ Distance from nearest fresh water well\_ Distance from nearest surface water Pit Liner Thickness: bbls: Construction Material \_\_\_\_ mil Below-Grade Tank: Volume\_ 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data SUBSEQUENT REPORT OF NOTICE OF INTENTION TO: PLUG AND ABANDON ALTER CASING PERFORM REMEDIAL WORK REMEDIAL WORK TEMPORARILY ABANDON CHANGE OF PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON CASING/CEMENT JOB PULL OR ALTER CASING MULTIPLE COMPL X Other: Other: Drilling/Cement 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 04/26/2023 Spud well. Drill 12-1/4" hole to 1055'. 04/27/23 RIH & set 9-5/8" 36# J-55 BTC csg @ 1055', pump 40bbl FWS, then cmt w/ 385 sxs class C w/ additives 12.4ppg 1.77 yield followed by 160 sxs class C w/ additives 14.8ppg 1.32 yield. Full returns throughout job, circ 230 sxs cmt to surface. Will test casing and BOP with big rig moves in. Rig release 04/27/2023.4/26/2023 Spudded well. **Casing and Cement Program** Pres Date String Fluid Hole Csq Weight Grade Est Dpth Sacks Yield Class Pres Open Size Size TOC Set Dpth Held Drop . Hole Type 12.25 9.625 0 1055 C 2055 Ν 04/27/23 Surf FreshWater 36 J-55 545 0 0 06/25/23 Prod Brine 8.75 L-80 С 7272 0 Ν 06/25/23 L-80 8155 С 0 Prod Brine 8.75 5.5 0 1540 2.38 0 7352 N I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines  $\square$ , a general permit  $\square$  or an (attached) alternative OCD-approved plan  $\square$ SIGNATURE DATE Electronically Signed Regulatory Director 6/28/2023 Type or print name Sarah Chapman E-mail address schapman@spurenergy.com Telephone No. 832-930-8613

DATE

9/20/2023 9:09:46 AM

For State Use Only:

APPROVED BY:

Patricia L Martinez

TITLE

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505** 

COMMENTS

Action 339402

## **COMMENTS**

Operator:	OGRID:
Spur Energy Partners LLC	328947
9655 Katy Freeway	Action Number:
Houston, TX 77024	339402
	Action Type:
	[C-103] EP Drilling / Cement

## Comments

Created By	Comment	Comment Date
· ·	06/22/2023 test to 250# low 2500# high, good test. Test 9-5/8" csg to 1500# for 30 minutes, good test. Drill 8-3/4" hole 8155'M/2763'V – TD reached on 06/25/2023. RIH & set 7" 32#L-80 BK-HT csg @ 2945' then crossover and set 5-1/2" 20# L-80 @ 8155', pump 50bbl FWS, then cmt w/ 255 sxs class C w/ additives 11.4ppg 2.38 yield followed by tail job w/ 1285 sxs class C w/ additives 13.2ppg 1.4 yield. Full returns throughout job, circ 100 sxs cmt to surface Pressure test csg to 6000# for 30 minutes, good test. 06/26/2023 RD and rig release.	6/28/2023