

Well Name: WEST TEAS UNIT	Well Location: T20S / R33E / SEC 9 / NENW /	County or Parish/State: LEA / NM
Well Number: 921	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM104724	Unit or CA Name: WEST TEAS(YTES-7RVRS)UNIT	Unit or CA Number: NMNM103145X
US Well Number: 300253189600S1	Well Status: Water Injection Well	Operator: CHEVRON USA INCORPORATED

Accepted for record –NMOCD gc10/13/2023

Notice of Intent

Sundry ID: 2740464

Type of Submission: Notice of Intent

Date Sundry Submitted: 07/12/2023

Date proposed operation will begin: 08/01/2023

LONG VO

Digitally signed by LONG VO
Date: 2023.08.06 09:09:24 -05'00'

Type of Action: Plug and Abandonment

Time Sundry Submitted: 06:29

Procedure Description: Please see attached current wellbore diagram and proposed wellbore diagram showing our plugging plan.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Proposed_WBD_20230712062832.pdf

Current_WBD_20230712062819.pdf

Approval Subject to
General Requirements and
Special Stipulations
Attached

Well Name: WEST TEAS UNIT

Well Location: T20S / R33E / SEC 9 /
NENW /County or Parish/State: LEA /
NM

Well Number: 921

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM104724

Unit or CA Name: WEST TEAS(YTES-
7RVRS)UNITUnit or CA Number:
NMNM103145X

US Well Number: 300253189600S1

Well Status: Water Injection Well

Operator: CHEVRON USA
INCORPORATED**Operator**

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MARK TORRES

Signed on: JUL 12, 2023 06:29 AM

Name: CHEVRON USA INCORPORATED

Title: Well Abandonment Engineer

Street Address: 6301 DEAUVILLE BLVD

City: MIDLAND

State: TX

Phone: (989) 264-2525

Email address: MARKTORRES@CHEVRON.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

PROPOSED WELLBORE DIAGRAM

FIELD: West Teas Unit/Federal #9

API NO.: 30-025-31896

Spud Date: 5/28/1993

LEASE/UNIT: Federal #9

CHEVNO: QU2829

TD Date: 6/3/1993

WELL NO.: 921

PROD FORMATION: Yates

Comp Date: 6/11/1993

COUNTY: Lea ST: New Mexico

STATUS: SI Oil Well

GL: 3,577'

LOCATION: 330' FNL & 2,310' FWL, Sec. 9, T-20S, R-33E

KB: 3,563'

Base of Fresh Water: 200'

POTASH: YES

Surface Casing

Size: 8 5/8"
 Wt., Grd.: J-55, 24#
 Depth: 1,300'
 Sxs Cmt: 690
 Circulate: Yes, 85 sx
 TOC: Surface
 Hole Size: 12 1/4"

Production Casing

Size: 5-1/2"
 Wt., Grd.: 17# J-55
 Depth: 3,320'
 DV Tool: N/A
 Sxs Cmt: 580
 Circulate: Yes, 17 sx
 TOC: Surface
 Hole Size: 7-7/8"

Isolate to Surface (WSEA 10-C)

4 Spot 109 sx Class C f/ 1,096' - 0'

Formation	Top (MD)
Rustler	1,296'
Salt Top	1,432'
Salt Bottom	2,953'
Yates	3,146'

Isolate Entire Salt Section (R-111-P)

3 Perform CBL on 5-1/2" csg to confirm TOC
 Spot 176 sx Class C f/ 2,867' - 1,096'
 WOC, tag, pressure test plug

****WSR TO EVALUATE PUMPING PLUG IN STAGES
 WOC/TAG EACH STAGE****

**H2S Concentration >100
 PPM? YES
 NORM Present in Area? NO**

Isolate Perfs (WSEA 10-B)

2 Spot 25 sx Class C f/ 3,117' - 2,867'
 WOC, tag, pressure test plug

5 1/2" Arrowset Packer @ 3,117'

Set CIBP @ 3111' above Yates Perfs. Leak Test CIBP.

3,299' PBTD
 3,320' TD

3,161', 3,163', 3,165', 3,167', 3,169', 3,171', 3,200',
 3,202', 3,204', 3,206', 3,214', 3,216', 3,222', 3,227',
 3,229', 3,236', 3,238', 3,240', 3,248', 3,250', 3,252'

CURRENT WELLBORE DIAGRAM

FIELD: West Teas Unit/Federal #9

API NO.: 30-025-31896

Spud Date: 5/28/1993

LEASE/UNIT: Federal #9

CHEVNO: QU2829

TD Date: 6/3/1993

WELL NO.: 921

PROD FORMATION: Yates

Comp Date: 6/11/1993

COUNTY: Lea ST: New Mexico

STATUS: SI Oil Well

GL: 3,577'

LOCATION: 330' FNL & 2,310' FWL, Sec. 9, T-20S, R-33E

KB: 3,563'

Base of Fresh Water: 200'

POTASH: YES

Surface Casing

Size: 8 5/8"
 Wt., Grd.: J-55, 24#
 Depth: 1,300'
 Sxs Cmt: 690
 Circulate: Yes, 85 sx
 TOC: Surface
 Hole Size: 12 1/4"

Production Casing

Size: 5-1/2"
 Wt., Grd.: 17# J-55
 Depth: 3,320'
 DV Tool: N/A
 Sxs Cmt: 580
 Circulate: Yes, 17 sx
 TOC: Surface
 Hole Size: 7-7/8"

Formation	Top (MD)
Rustler	1,296'
Salt Top	1,432'
Salt Bottom	2,953'
Yates	3,146'

**H2S Concentration >100
 PPM? YES
 NORM Present in Area? NO**

Tubing Components (3/3/2004)

Item Des	Jts	OD (in)	Len (ft)
Tubing	100	2 3/8	3,107.00

1.5" Profile Nipple above Packer
 5 1/2" Arrowset Packer set @ 3,117'

Yates Perfs

3,161', 3,163', 3,165', 3,167', 3,169', 3,171', 3,200',
 3,202', 3,204', 3,206', 3,214', 3,216', 3,222', 3,227',
 3,229', 3,236', 3,238', 3,240', 3,248', 3,250', 3,252'

3,299' PBT
 3,320' TD

**BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972**

**Permanent Abandonment of Federal Wells
Conditions of Approval (LPC Habitat)**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.** Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing.

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:

From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines **(Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure)**. Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

- have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias
Environmental Protection Specialist
575-234-6230

Crisha Morgan
Environmental Protection Specialist
575-234-5987

Jose Martinez-Colon
Environmental Protection Specialist
575-234-5951

Mark Mattozzi
Environmental Protection Specialist
575-234-5713

Robert Duenas
Environmental Protection Specialist
575-234-2229

Sundry ID 2740464

Plug Type	Top	Bottom	Length	Tag	Sacks	Cement Class	Notes
Surface Plug	0.00	100.00	100.00	Tag/Verify			
Fresh Water @ 325	271.75	375.00	103.25	If solid			
Shoe Plug	1237.00	1350.00	113.00	Tag/Verify			
Top of Salt @ 1620	1553.80	1670.00	116.20	Tag/Verify			
Base of Salt @ 2970	2890.30	3020.00	129.70	Tag/Verify			
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio ns			Set CIBP at 3111'. Leak Test CIBP. Spot cement from 3111' to surface. Verify at surface. May run CBL and pump plugs in stages. WOC and Tag each plugs.
CIBP Plug	3076.00	3111.00	35.00		308.00	C	
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio ns			
Yates @ 3161	3079.39	3211.00	131.61				
Perforations Plug (If No CIBP)	3111.00	3302.00	191.00	Tag/Verify			
Capitan Reef @ 3305	3221.95	3355.00	133.05	If solid			
Shoe Plug	3236.80	3370.00	133.20	Tag/Verify			

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole.

Class H >7500'

Class C <7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater

R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft³/sx

Class H: 1.06 ft³/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement	R111-P	50 Feet from Base of Salt to surface
--------------------------	--------	--------------------------------------

Shoe @	1300.00
--------	---------

Shoe @	3320.00
--------	---------

Perforatons Top @	3161.00	Perforations	3252.00
-------------------	---------	--------------	---------

CIBP @	3111.00
--------	---------

Chevron USA Inc.
Mid-Continent Business Unit



P&A Procedure – West Teas Unit #921

Basic Well Info:

API: 30-025-31896

Fresh Water Depth: 200'

Potash/R-111-P: Yes

Notes:

- Additional well history available in Wellview and Electronic Well File. Contact engineer for more info.
- **Cement volumes are subject to change pending any cut/pull decisions – WSR to confirm all cement calculations. Notify BLM of all changes to cement volumes and deviations from the procedure.**
- WSR to assess crew competency and utilize SWA and contact Superintendent with any concerns.
- If program requires change of scope, do not proceed before contacting an engineer or Superintendent.
- Reference [Well Intervention Standard Procedure](#) and Business Partner SOPs for additional guidance.

Rig Work

1. Prior to rig arrival, verify well prep and confirm if any special or welded flanges are present that will require further intervention.
2. Contact **BLM at least 24 hours** prior to performing any work.
 - a. Place job number in WellView, note the time you contacted the agency and the engineer's name.
3. Perform pre-job meeting. Review JSA's, fill out PTW, review SIF hazards and mitigations, reinforce SWA, review potential well control issues and mitigation per the **phase 3 risk assessment (WSEA 2-A)**.
4. MIRU pulling unit.
5. Verify pressures and if necessary, kill well as per [Chevron Global Well Control Document](#).

- a. Bubble test intermediate and surface casings for 30 minutes each and share results in WellView under daily pressure.
6. Attempt to pressure test tubing to at least 1,000 psi for 15 minutes or the highest pressure expected while plugging the well.
 - a. If test passes, plan to utilize tubing for work string.
 - b. If test fails, pick up a work string provided by Chevron.
7. Establish bottom barrier:
 - a. Establish injection and bullhead 25 sx Class C cement, displacing cement below packer at 3,117'.
 - b. If unable to establish injection or tubing failed pressure test, plan to release on/off tool, LD production tbg, and set CIBP above packer at +/- 3,110'.
8. Perform flow check for 15 minutes (WSEA 10-A).
9. N/D tree and N/U 7-1/16" Class II BOPE: 5M pipe rams, blind rams (WSEA 8-A).
10. Pressure test BOPs to 250-350 psi low for 5 min / 2,000 psi for 5 min (WSEA 9-A).
 - a. On a chart, no bleed off allotted.
11. Release from on/off tool, circulate well clean and pressure test casing to 500 psi for 15 minutes.
12. Spot 25 sx Class C f/ 3,117' – 2,867' (WSEA 10-B).
 - a. WOC, tag plug with max 80% of available weight, pressure test plug to 1,500 psi for 15 minutes, 5% allowable pressure drop.
 - i. Contact engineer if concerned about casing integrity and wish to reduce test pressure.
 - b. Min. plug length 100' to be Chevron barrier.
13. Perform CBL to confirm TOC in production annulus.
 - a. MIRU WL unit w/ 5k lubricator and pack-off system.
 - b. Test lubricator to 2,000 psi.
 - c. Perform 0 psi pass and 1,500 psi pressure pass and confirm TOC.
 - d. Confirm results with engineer and discuss with BLM prior to confirm whether R-111-P plug should be spotted or perf/squeezed.
 - e. RDMO WL unit.
14. Continue to isolate entire salt section per R-111-P (Potash and Int. csg shoe).
 - a. Spot 176 sx Class C f/ 2,867' – 1,096'.
 - i. Adjust cement volumes and perform perf/squeezes pending CBL results as per discussion with engineer and BLM.
 - b. WSR to evaluate pumping plug in multiple perf/circulations pending crew competency, equipment limitations, etc.
 - c. For each stage: WOC, tag plug with max 80% of available weight.
15. Conduct bubble test for 30 minutes on all casing annuli.
 - a. If bubble test fails, contact engineer to discuss running a CBL to confirm cement quality behind pipe and/or adjusting forward plan for a perforate and squeeze contingency, cement plug or identify any opportunity to cut & pull casing, or R/D and monitor well.
 - b. Goal is to address failed test prior to freshwater depths.
 - c. Confirm forward plan with engineer and request forward plan approval from the agency.
16. If bubble test passes, proceed to isolate to surface.

17. Spot 109 sx Class C f/ 1,096' – 0' (WSEA 10-C).
 - a. Visually confirm cement to surface.
18. RDMO.
 - a. While RDMO, perform final 30-minute bubble test on surface and production casings.

Procedure for Cutting/Pulling Casing Strings

1. MIRU WL unit w/ 5k lubricator system w/ pack-off and pressure test lubricator to MASP + 500 psi for 5 minutes.
 - a. Check for visible leaks of lubricator.
2. RIH w/ jet cutter and cut casing at depth agreed upon with engineer and agency.
3. RDMO WL unit.
4. Establish circulation and clean up annulus.
 - a. If circulation is not established, contact the engineer.
5. N/D BOPs.
6. Spear casing and pull free.
 - a. If casing does not pull free, rig up casing jacks and pull free.
 - b. Contact engineer if unable to pull free with casing jacks.
7. Set casing back down on stub.
8. N/U 3k Class II BOPs to next wellhead section (WSEA 8-B Contingent).
 - a. Pipe rams required for size of casing to be laid down and blind rams.
 - b. NOTE: For WellSafe certified wells, reference EAR checklist and/or well folder for BOP schematic. Document in WellView per EAR checklist.
9. Pressure test BOP to 250-350 psi low for 5 min / 2,000 psi for 5 min. Perform full accumulator drawdown test (WSEA 9-B Contingent).
10. Spear and L/D casing.
 - a. Ensure swage joint w/ crossover to TIW is present w/ sling and ready to shut in.
11. Isolate casing stump.
 - a. RIH and set CIBP above casing stump pending approval from agency.
 - b. Alternatively, TIH and set cement plug min. 50' above and below stump and WOC/tag plug.
 - c. Pressure test CIBP or cement plug to 1,000 psi.
12. Continue to plug well out per procedure adjusting cement calculations as necessary to achieve desired plug lengths.

WSEA	Component	Description
2-A	Pre-Spud	Review JSAs, fill out PTW, review SIF hazards and mitigations, reinforce SWA, review potential well control issues and mitigation per the phase 3 RA.
8-A	BOP Configuration	7-1/16" 5M BOPE: 2-7/8" pipe rams, blind rams

8-B	BOP Configuration (Contingent)	XX" 3M BOPE: 5-1/2" pipe rams, blind rams
9-A	BOP Test	Pressure test BOP to 250-350 psi low for 5 min / 2,000 psi high for 10 min.
9-B	BOP Test (Contingent)	Pressure test BOP to 250-350 psi low for 5 min / 2,000 psi high for 10 min.
10-A	Flow Check	Perform flow check for 15 minutes.
10-B	Cement Plug (1 st barrier to perforations)	Test cement plug to 1,500 psi for 15 minutes with 5% maximum pressure drop with a decreasing rate of change. Acceptable fluid weight range 8.4 - 10 ppg. Document cement plug bottom, tag depth (must be at least 100' in length to be Chevron barrier), tag weight (maximum 80% available weight), starting pressure, ending pressure and percent decline.
10-C	Cement Plug – surface / freshwater plug	Visually confirm surface plug.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

COMMENTS

Action 273359

COMMENTS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 273359
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM.	10/13/2023

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 273359

CONDITIONS

Operator: CHEVRON U S A INC 6301 Deauville Blvd Midland, TX 79706	OGRID: 4323
	Action Number: 273359
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	10/13/2023