Submit 1 Copy To Appropriate District	State of New Me	exico	Form C-103	
Office District I – (575) 393-6161	Energy, Minerals and Nati		Revised July 18, 2013	
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	
District II – (575) 748-1283	OIL CONSERVATION	IDIVISION	30-005-20413	
811 S. First St., Artesia, NM 88210 <u>District III</u> – (505) 334-6178	1220 South St. Fran		5. Indicate Type of Lease	
1000 Rio Brazos Rd., Aztec, NM 87410			STATE FEE	
District IV – (505) 476-3460	Santa Fe, NM 8'	/505	6. State Oil & Gas Lease No.	
1220 S. St. Francis Dr., Santa Fe, NM 87505			305 865	
SUNDRY NO	TICES AND REPORTS ON WELLS	3	7. Lease Name or Unit Agreement Name	
	OSALS TO DRILL OR TO DEEPEN OR PL			
PROPOSALS.)	LICATION FOR PERMIT" (FORM C-101) F	OR SUCH	NM CR State	
1. Type of Well: Oil Well	Gas Well Other SWD)	8. Well Number 2	
2. Name of Operator			9. OGRID Number	
Weslac En	Jergy LLC	, ,	260245	
3. Address of Operator		Son Antonio,	10. Pool name or Wildcat	
8620 N. New 1	Brantels Ave. Ste. 603 =	Texas 78217	SWD: Son Andres	
4. Well Location		4		
Unit Letter € 🕅	: 660 feet from the Sout	L line and	660 feet from the West line	
Section 32	•	ange ZOE	NMPM ClovesCounty	
	11. Elevation (Show whether DR			
12. Check	Appropriate Box to Indicate N	lature of Notice,	Report or Other Data	
	NTENTION TO:		SEQUENT REPORT OF:	
PERFORM REMEDIAL WORK		REMEDIAL WOR		
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRI		
PULL OR ALTER CASING	MULTIPLE COMPL	CASING/CEMENT	TJOB PNR	
DOWNHOLE COMMINGLE				
CLOSED-LOOP SYSTEM	, –	OTLIED.		
OTHER:	nleted operations (Clearly state all	OTHER:	d give pertinent dates, including estimated date	
			npletions: Attach wellbore diagram of	
proposed completion or re		c. Tor manipic cor	* **	
		Papa	_ _ _ _ _ _	
See Attach	rens.	nd webo	,	
		He alon	tic	
See Attachments: Plugging Report As-built schematic				

Spud Date: 7/15/2021 Rig Release Date: 7/26/2021	23 1:16:06 PM
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	/20
SIGNATURE MANGERS MANGERS 9/15/2013	Released to Imaging: 10/31.

Plugging Report NM "CR" State API 30-005-20413

7/15/2021 Move in equipment and rig up. Dug out cellar and repaired surface connections. Installed BOP and POOH with 78 joints of IPC tubing. Split collar on the end of the last joint. Shut down.

7/19/2021 Moved in workstring and RIH with overshot. Caught fish at 2478'. POOH with workstring, 27 joints IPC tubing and an AD-1 packer. Picked up 4 ¾" bit and started in the hole with the workstring. SION

7/20/2021 Tagged up at 3319'. Installed stripping head, caught circulation and worked down to 3405' and stopped making progress. POOH with bit and shut down.

7/21/2021 Moved in reverse unit. Picked up 4 ¾" bit and 6 collars. RIH with workstring and tagged up at 3405′. Caught circulation and began to rotate down. Broke through at 3456′. Continued washing down with swivel to 3579′. Circulated clean and laid down swivel. RIH to 6985′ and tagged up hard. Picked up swivel and began to rotate down. Hard and slow. Returns began with cement and turned to metal shavings. Current depth 6987′. Believe to be cement retainer. SION

7/22/2021 Spot 25 sx Class H cement at 6987' as per NMOCD. WOC and tagged at 6764'. Circulate MLF. POOH to 6423' and spot 25 sx Class H cement. POOH with workstring and laid down the collars. Set 5 ½" CIBP on wireline at 3334'. Tagged CIBP with tubing and spot 25 sx Class C cement on top of the CIBP. POOH and SION.

7/23/2021 Tagged cement at 3095'. POOH and perforate casing at 2526'. Squeezed with 50 sx cement with CaCl. WOC and tagged at 2414'. Perforated at 1503' and squeezed with 50 sx cement. Left packer set and shut down.

7/26/2021 Tagged cement at 1367'. Perforated at 200'. Pumped cement down the 5 ½" casing to perfs at 200' and up the annulus to surface. Took 55 sx to get good cement to the pit. Rigged down, dug out cellar and removed the wellhead. Filled up both strings of casing with 15 sx cement. Installed BGM and removed the anchors.

Wespac Energy, LLC NM "CR" State #2 API 30-005-20413 WBD After PA Perforate at 200' and circulate cement to surface. Used 55 sx Class C 8 5/8" 24# & 32# casing set at 1453' Cemented w/570 sx TOC @ Surface Top Salt 1552' Perforate @ 1503' And squeeze with 50 sx cement. WOC and tag @ 1367' Top salt & Surface Shoe Perforate @ 2526' And squeeze with Base Salt 2476' 50 sx cement. WOC and tag @ 2414' Base Salt Set 5 1/2" CIBP @ 3334' 25 sx cement on top. Tagged @ 3095'. San Andres Perforations 3384' to 3432' 25 sx cement across the Abo from 6423'. TOC at 6171'. Perforations 7287'-7298' Cement retainer at 6987'. Top of cement at 7184' 25 sx Class H on top. Tagged cement at 6764'. Perforations 7310-7317' Squeezed with 50 sx Retainer @ 7304' 5 1/2" 14#, 15.5#, & 17# casing set at 7454' Cemented w/775 sx cement ETOC @ 2650'

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 200733

COMMENTS

Operator:	OGRID:
WESPAC ENERGY, LLC	260245
8620 North New Braunfels Ave.	Action Number:
San Antonio, TX 78217	200733
	Action Type:
	[C-103] Sub. Plugging (C-103P)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM.	10/31/2023

District III

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 200733

CONDITIONS

Operator:	OGRID:
WESPAC ENERGY, LLC	260245
8620 North New Braunfels Ave.	Action Number:
San Antonio, TX 78217	200733
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Create By	d Condition	Condition Date
kfort	Need C103Q and marker photo to release	10/31/2023