DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well X Gas Well Other 2. Name of Operator Northern Pacific Oil and Gas Incorporated 3. Address of Operator 530b Harkle Road, Santa Fe, NM 87505 New Mexico BA State 8. Well Number 004 9. OGRID Number 330352 10. Pool name or Wildcat Siete; San Andres				
4. Well Location Unit Letter K: 2310 feet from the South line and 1980 feet from the West line				
Section 16 Township 8S Range 31E NMPM County Chaves	1			
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A XX CASING/CEMENT JOB OTHER: OTHER: OTHER: OTHER: Approved for plugging of well bore only. Liability under bond is retained pending to cation cleanup & receipt of the complete of the completion of the compl				
C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE				
Type or print nameBobby Stearns E-mail address:bobbystearns1@yahoo.com_ PHONE:575-760-2482_ For State Use Only				
APPROVED BY:				

Plugging Report Northern Pacific Oil and Gas Incorporated New Mexico BA State #4 API 30-005-21023

10/18/2023 MIRU, unseat pump and lay down rods. 150 3/4" rods

10/19/2023 Install BOP. POOH with tubing and made gauge ring run. Set 5.5" CIBP at 3640'. RIH with tubing and tagged CIBP. Circulated MLF and tested casing to 500#. Good. POOH with tubing and top off casing in preparation for CBL.

10/23/2023 Ran CBL. TOC at 2120'. RIH with tubing and spot 25 sx cement on top of CIBP. Had small amount of watered down cement in the returns while displacing. Finished displacing, POOH 10 stands and circulated clean. Laid down tubing from the wellbore and began to pick up workstring. SION.

10/24/2023 Finish picking up work string and tagged cement at 3457'. POOH to 2192' and spot 25 sx cement. Perforated at 1810'. Set packer and squeezed with 40 sx cement. Good communication with surface head. WOC and tagged at 1687'. Perforated at 1354', set packer, and squeezed with 40 sx cement. Left packer set and shut down.

10/25/2023 Tagged cement at 1193'. Perforated at 250'. Circulated in/out 5.5" to surface with 65 sx cement.

10/26/2023 Dig out and remove wellhead. Filled up both strings with less than 2 sx. Install BG marker and removed the anchors.

Northern Pacific NM BA State #4 API 30-005-21023 WBD After Plugging Perforate at 250' and circulate cement to surface. 65 sx 8 5/8" 24# casing set at 1304' Cemented w/650 sx Perforate at 1354' and squeeze TOC at Surface with 40 sx. WOC and tag above 1254'. Top Salt/Surface Shoe Tagged at 1193' Perforate at 1810' and squeeze with 40 sx. WOC and tag. Top Yates/Base Salt Tagged at 1687' Spot 25 sx at 2192'

Perforations 3740' to 3784'

5 1/2" 14# casing set at 3875' Cemented w/450 sx cement

TOC @ 2120'

5 1/2" CIBP @ 3640' with 25 sx

cement on top

District III

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 284759

CONDITIONS

Operator:	OGRID:
NORTHERN PACIFIC OIL AND GAS INCORPORATED	330352
150 S. Rodeo Drive 250	Action Number:
Beverly Hills, CA 90210	284759
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By	Condition	Condition Date
gcordero	None	11/22/2023