

Submit a Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| | | |
|---|--|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | | WELL API NO. 30-015-25108 |
| 1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> | | 5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 2. Name of Operator SILVERBACK OPERATING II, LLC | | 6. State Oil & Gas Lease No. |
| 3. Address of Operator 19707 West IH 10, Suite 201 San Antonio, TX 78257 | | 7. Lease Name or Unit Agreement Name Lattion |
| 4. Well Location Unit Letter P: 660 feet from the South line and 660 feet from the East line Section 23 Township 18S Range 26E NMPM County Eddy | | 8. Well Number 2 |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3301' GR | | 9. OGRID Number 330968 |
| | | 10. Pool name or Wildcat ATOKA; GLORITA-YESO |

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

| NOTICE OF INTENTION TO: | | SUBSEQUENT REPORT OF: | |
|--|---|--|---|
| PERFORM REMEDIAL WORK <input type="checkbox"/> | PLUG AND ABANDON <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> | ALTERING CASING <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | CHANGE PLANS <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> | P AND A <input checked="" type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | MULTIPLE COMPL <input type="checkbox"/> | CASING/CEMENT JOB <input type="checkbox"/> | |
| DOWNHOLE COMMINGLE <input type="checkbox"/> | | | |
| CLOSED-LOOP SYSTEM <input type="checkbox"/> | | | |
| OTHER: <input type="checkbox"/> | | OTHER: <input type="checkbox"/> | |

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Silverback Operating II, LLC has plugged and abandoned this well. Please see attached plugging report and wellbore schematics.

Plugged 10/10/23

Spud Date:

Rig Release Date:

Approved for plugging of well bore only. Liability under bond is retained pending Location cleanup & receipt of C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @ www.emnrd.state.nm.us

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE *Heather Treffert*

TITLE Field Operations Analyst

DATE 11/8/2023

Type or print name Heather Treffert

E-mail address: htreffert@silverbackexp.com

PHONE: 575-689-5332

For State Use Only

APPROVED BY: *[Signature]*

TITLE

Staff Manager

DATE

12/5/23

Conditions of Approval (if any):

Lattion #2

30-015-25108

API

Silverback Operating II, LLC has completed the plug and abandon on this well as follows:

1. MIRU workover rig. Loaded tbg and csg with water as needed. POOH with rods and pump. ND pumping tee. NU BOP
2. POOH with 2 7/8" tbg
3. GIH with CIBP on tbg and set at 2,785'. Spot 35 sk cement plug on CIBP from 2,785'-2,431'. WO
4. Perf and checked injection @ 960. No injection observed. Spot 25sx class C cmt plug 1,010'-750
5. PU and spot 25 sk cmt plug from 0-250'.
6. Cut off wellhead and installed dry hole marker. Cleaned location as regulated.

Wellbore schematics attached.

C. Tag cmt plug
'l. WOC and tag.

| Lattion #2 Actual | | | | Sec-TWN-RNG: 23-18S-26E-Unit P | | 30-015-25108 | | | | | | | | | |
|---|------|-------|--|----------------------------------|-----------|---------------|----------|--|-----|-------------------------------------|-----------|--|-----|--|--|
| | | | | Footage Calls: 660' FSL 660' FEL | | Elev 3301' GR | | | | | | | | | |
| COMMENTS | | | | Lat/Long (NAD83): | | | | | | | | | | | |
| Surface plug CI C cmt: 0-250' | | | | | | | | | | | | | | | |
| <div><div></div><div><div>A</div><div>50'</div><div>B</div></div></div> | | | | CASING DETAIL | | | | | | | | | | | |
| | | | | # | HOLE | CSG | WGHT | GRADE | Top | Depth | TOC | SX | | | |
| | | | | A | 10 3/4 | 8 5/8 | 24 | J-55 | 0 | 913 | Circ | 700 sx cl- C | | | |
| | | | | B | 7 7/8 | 5 1/2 | 15.5 | J-55 | 0 | 3,666 | | 420 sx lt. wt. 250 sx cl- C | | | |
| | | | | C | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | FORMATION TOPS | | | | | | | | | | | |
| | | | | FORMATION | | | TOP (FT) | | | | FORMATION | | TOP | | |
| | | | | San Andres | | | 1,100 | | | | | | | | |
| | | | | Glorieta | | | 2,690 | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| | | | | TUBING DETAIL | | | | | | | | | | | |
| | | | | OD | | GRADE | | WGHT | | TOP | | BASE | | | |
| | | | | 2 7/8 | | | | | | | | 3,424 | | | |
| | | | | | | | | | | | | | | | |
| | | | | PERFORATION DETAIL | | | | | | | | | | | |
| | | | | | FORMATION | | | TOP | | BASE | | TREATMENT | | | |
| | | | | A | Yeso | | | 3,203 | | 3,540 | | Spot acid, fraced w/1790 bbl fluid, 900 sks. 20/40 sand, 200sks 12/20 sand | | | |
| B | Yeso | | | 2,835 | | 3,082 | | Spot acid, fraced w/86100 gal fluid, 1280 sks. 20/40 sand, 750sks 12/20 sand | | | | | | | |
| C | | | | | | | | | | | | | | | |
| D | | | | | | | | | | | | | | | |
| E | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | |
| PLUGS | | | | | | | | | | | | | | | |
| # | sx | Class | | Top | | Bottom | | Ht | | Notes | | Tag | | | |
| 1 | 35 | C | | 2500 | | 2785 | | 285 | | CIBP & cmt plug to cover yeso perfs | | Y | | | |
| 2 | 25 | C | | 750 | | 1,010 | | 260 | | Cmt plug across surface shoe | | Y | | | |
| 3 | 25 | C | | 0 | | 250 | | 250 | | Surface plug | | | | | |
| 4 | | | | | | | | | | | | | | | |
| 5 | | | | | | | | | | | | | | | |
| 6 | | | | | | | | | | | | | | | |
| 7 | | | | | | | | | | | | | | | |
| PBTD: MD | | | | | | | | | | | | | | | |
| TD: 3.666 MD | | | | | | | | | | | | | | | |

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 288903

CONDITIONS

| | |
|--|--|
| Operator: Silverback Operating II, LLC 19707 IH10 West, Suite 201 San Antonio, TX 78256 | OGRID: 330968 |
| | Action Number: 288903 |
| | Action Type: [C-103] Sub. Plugging (C-103P) |

CONDITIONS

| | | |
|------------|-----------|----------------|
| Created By | Condition | Condition Date |
| gcordero | None | 12/5/2023 |