

Sundry Print Repo

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: SPEYSIDE 18 FEDERAL Well Location: T22S / R34E / SEC 18 / County or Parish/State: LEA /

NENE / 32.3985624 / -103.5025312

Well Number: 301H Type of Well: OIL WELL Allottee or Tribe Name:

Lease Number: NMNM140721 Unit or CA Name: Unit or CA Number:

US Well Number: 3002551301 Well Status: Drilling Well Operator: AVANT OPERATING

LLC

Subsequent Report

Sundry ID: 2748806

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 08/30/2023 Time Sundry Submitted: 05:42

Date Operation Actually Began: 04/15/2023

Actual Procedure: Spud 17 ¬1/2 surface hole on 4/15/23 @5:00 AM. 4/16/23 TD 17-1/2 hole @1,733'. Ran 41 jts 13-3/8, 54.5 lb, J-55 STC csg @ 1,723'. Cmt lead w/ 770sx Class C, 1.9 yield, tail w/ 250sx Class C, 1.34 yield. Circ 70 bbls cmt to surface. Test surface csg to 1,500 psi for 10 mins, good test. 4/21/23 Test BOP 250 psi low / 5000psi high for 10 mins, good tests. 4/22/23 TD 12-1/4 int hole @ 4,997'. Ran 115 jts 9-5/8, 40#, HCL-80 BTC csg @ 4,987'. Cmt lead w/1310 sx Class C 1.9 yield, tail w/ 230 sx Class C, 1.27 yield. 113 bbls cement back to surface. Test csg to 5000 PSI for 10 mins, good test. 5/9/23 Test BOP 250 psi low / 5000psi high for 10 mins, good tests. 5/11/23 TD 8-3/4 prod hole @10,178' (EOC). KOP @ 9,393. 5/13/23 TD 8-3/4 @14,810' MD, 10,770' TVD. Ran 336 jts 5-1/2, 20#, HCP-110 @14,795'. Cmt lead w/865 sx Class C, yield 3.39, tail w/1255 Class H, yield 1.21. Circ 120 bbls cmt to surf. 5/14/23 RR. Will test casing on completions.

County or Parish/State: LEA? eceived by OCD: 9/6/2023 7:38:18 AM. Well Name: SPEYSIDE 18 FEDERAL Well Location: T22S / R34E / SEC 18 / NM

NENE / 32.3985624 / -103.5025312

Well Number: 301H Type of Well: OIL WELL **Allottee or Tribe Name:**

Unit or CA Number: Lease Number: NMNM140721 **Unit or CA Name:**

US Well Number: 3002551301 Well Status: Drilling Well **Operator: AVANT OPERATING**

LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: MEGHAN TWELE Signed on: AUG 30, 2023 05:42 PM

Name: AVANT OPERATING LLC Title: Contract Regulatory Analyst

Street Address: 1515 WYNKOOP ST SUITE 700

City: DENVER State: CO

Phone: (720) 339-6880

Email address: MTWELE@OUTLOOK.COM

Field

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972 BLM POC Email Address: jshepard@blm.gov

Disposition: Accepted Disposition Date: 09/05/2023

Signature: Jonathon Shepard

Page 2 of 2

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 262219

CONDITIONS

Operator:	OGRID:
Avant Operating, LLC	330396
1515 Wynkoop Street	Action Number:
Denver, CO 80202	262219
	Action Type:
	[C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	Please note for future reference that pressure tests for casing strings shall be conducted with a pressure that is approximately one-third of the manufacturer's rated internal yield pressure except that the test pressure shall not be less than 600 psi and need not be greater than 1500 psi. The Operator shall apply test pressures for a period of 30 minutes in accordance with 19.15.16.10 l. (1) NMAC.	1/4/2024