U.S. Department of the Interior BUREAU OF LAND MANAGEMENT Sundry Print Report

Well Name: ANTELOPE RIDGE UNIT

Well Location: T24S / R34E / SEC 4 /

NWNE /

County or Parish/State: LEA /

Well Number: 02

Type of Well: CONVENTIONAL GAS

WELL

Allottee or Tribe Name:

Lease Number: NMNM021422

Unit or CA Name: ANTELOPE RIDGE **DEEP MORRO**

Unit or CA Number:

NMNM68289C

US Well Number: 300252044400S1

Well Status: Producing Gas Well

Operator: OXY USA INCORPORATED

Accepted for Record Only

SUBJECT TO LIKE APPROVAL BY BLA

NMOCD 2/23/24



Notice of Intent

Sundry ID: 2776396

Type of Submission: Notice of Intent

Date Sundry Submitted: 02/22/2024

Type of Action: Plug and Abandonment

Time Sundry Submitted: 03:00

Date proposed operation will begin: 02/24/2024

Procedure Description: OXY USA Inc. respectfully requests approval to plug the subject well. The planned procedure and current/proposed wellbore is attached for reference.

Surface Disturbance

Is any additional surface disturbance proposed?: No

Approval Subject to General Requirements

and Special Stipulations Attached

NOI Attachments

Procedure Description

current_proposedwbd_20240222150028.pdf

ARU002_PA_Procedure_20240222145546.pdf

Received by OCD: Was Rand: ANTE OF PENEIDGE UNIT

Well Location: T24S / R34E / SEC 4 / NWNE /

County or Parish/State: LEA /

Well Number: 02

Type of Well: CONVENTIONAL GAS

Allottee or Tribe Name:

Page 2 of 20

Lease Number: NMNM021422

Unit or CA Name: ANTELOPE RIDGE **DEEP MORRO**

Unit or CA Number:

NMNM68289C

US Well Number: 300252044400S1

Well Status: Producing Gas Well

Operator: OXY USA INCORPORATED

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: LESLIE REEVES Signed on: FEB 22, 2024 03:00 PM

Name: OXY USA INCORPORATED

Title: Advisor Regulatory

Street Address: 5 GREENWAY PLAZA, SUITE 110

City: HOUSTON State: TX

Phone: (713) 497-2492

Email address: LESLIE_REEVES@OXY.COM

Field

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

PLUG AND ABANDONMENT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	OXY USA Incorporated
LEASE NO.:	NMNM021422
WELL NAME & NO.:	Antelope Ridge Unit 2
US Well Number:	3002520444
LOCATION:	Section 4, T.24 S., R.34 E., NMPM
COUNTY:	Lea County, New Mexico
Sundry ID:	2776396
Karst:	⊠Low □Medium □High □Critical
Potash:	☐Secretary ☐R111P
Special Area:	□ Prairie Chicken □ Capitan Reef

- 1) 10# MLF between plugs. Utilize above ground steel tanks.
- 2) POOH with production equipment.
- 3) Set CIBP @ 12795'. Spot cement from 12795' to 11770'. Leak test CIBP. WOC and Tag. 242 Sacks Class H.
- 4) Spot cement from 11561' to 11257'. WOC and Tag. 71 Sacks, Class H.
- 5) Spot cement from 9053' to 8589'. WOC and Tag. 105 Sacks, Class H.
- 6) Spot cement from 7651' to 7475'. WOC and Tag. 40 Sacks, Class H.
- 7) Spot cement from 5402' to 4405'. WOC and Tag. 181 Sacks, Class C.
- 8) Spot cement from 1775' to 1657'. WOC and Tag. 22 Sacks, Class C.
- 9) Perf and squeeze between the 13 3/8" x 20" casing from 962' to 852'. WOC and Tag. (In 20 sxs/Out 73 sxs)
- 10) Perf and squeeze across all casing strings to surface. (In 19 sxs/Out 28 sxs/Out 78 sxs) Verity at surface.

Approval Subject to General Requirements and Special Stipulations Attached

- No more than 3000 feet between cement plugs in cased hole.
- Wait on Cement and Tag Top of Cement Requirement:
 - 1. Shoe, Top of Salt, Base of Salt, DV tool, Perforate and Squeeze, Open Perforation.
 - 2. Formation plug is optional if a solid base is established and confirmed.

Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 202

DEI	dictivities of the hyperdox		·	•
BURI	EAU OF LAND MANAGEMENT		5. Lease Serial No.	MNM021422
Do not use this f	OTICES AND REPORTS ON Worm for proposals to drill or to Use Form 3160-3 (APD) for suc	o re-enter an	6. If Indian, Allottee of	or Tribe Name
SUBMIT IN 1	TRIPLICATE - Other instructions on pag	ge 2	_	ement, Name and/or No.
1. Type of Well				E DEEP MORRO/NMNM68289C
Oil Well Gas W			8. Well Ivallie and Ivo	ANTELOPE RIDGE UNIT/02
2. Name of Operator OXY USA INCO	RPORATED		9. API Well No. 3002	2520444
3a. Address 5 Greenway Plaza, Suit	e 110, Houston, TX 7704(3b. Phone No.		10. Field and Pool or	
4. Location of Well (Footage, Sec., T.,R	(713) 366-57	10	11. Country or Parish	E-BONE SPRING, W/ANTELOPE RI . State
SEC 4/T24S/R34E/NMP	,,,n., or survey Bescriptiony		LEA/NM	,
12. CHE	CK THE APPROPRIATE BOX(ES) TO IN	DICATE NATURE OF NO	TICE, REPORT OR OT	HER DATA
TYPE OF SUBMISSION		TYPE OF A	CTION	
Notice of Intent	Acidize Deep		oduction (Start/Resume)	Water Shut-Off
Notice of Intent	Alter Casing Hydr	raulic Fracturing Re	eclamation	Well Integrity
Subsequent Report		=	complete	Other
Final Abandonment Notice		_	mporarily Abandon ater Disposal	
OXY USA Inc. respectfully req reference.		The planned procedure a bject to General Requirem Stipulations Attached	, ,	wellbore is attached for
14. I hereby certify that the foregoing is	true and correct. Name (Printed/Typed)			
LESLIE REEVES / Ph: (713) 497-2	492	Advisor Regulator	ту	
Signature (Electronic Submissio	n)	Date	02/22/2	2024
	THE SPACE FOR FED	ERAL OR STATE C	FICE USE	
Approved by				
		Title		Date
	ned. Approval of this notice does not warran quitable title to those rights in the subject le duct operations thereon.		,	
	B U.S.C Section 1212, make it a crime for an ents or representations as to any matter with		rillfully to make to any d	epartment or agency of the United States

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

(Form 3160-5, page 2)

Additional Information


Location of Well


 $0. \ SHL: \ NWNE \ / \ 660 \ FNL \ / \ 1650 \ FEL \ / \ TWSP: \ 24S \ / \ RANGE: \ 34E \ / \ SECTION: \ 4 \ / \ LAT: \ 0.0 \ / \ LONG: \ 0.0 \ (\ TVD: \ 0 \ feet, \ MD: \ 0 \ feet)$ BHL: \ \ NWNE \ / \ 660 \ FNL \ / \ 1650 \ FEL \ / \ TWSP: \ 24S \ / \ SECTION: \ / \ LAT: \ 0.0 \ / \ LONG: \ 0.0 \ (\ TVD: \ 0 \ feet, \ MD: \ 0 \ feet)

OCD-HORRS

Form 3160-5 (Aprıl 2004)	UNITED STAT DEPARTMENT OF TH	IE INTERIOR		FORM APPROVED OM B No 1004-0137 Expires March 31, 2007
c	BUREAU OF LAND MA			5 Lease Serial No NM012422
	SUNDRY NOTICES AND R ot use this form for proposals			6 If Indian, Allottee or Tribe Name
aban	doned well. Use Form 3160 - 3	(APD) for such pr	oposals.	N/A
	IT IN TRIPLICATE- Other in	structions on reve	rse side.	7 If Unit or CA/Agreement, Name and/or No Antelope Ridge Unit 891008492A
1 Type of Well Oil W	ell 🗆 🔽 Gas Well 🗆 🔲 Other			8 Well Name and No.
2 Name of Operator	BOLD ENERGY, LP		/	Antelope Ridge Unit #2 9. API Well No
3a Address 415 W. Wall Street	, Suite 500 Midland, TX 79701 /	3b Phone No (included 432-686-1100	le area code)	30-025-20444 10 Field and Pool, or Exploratory Area
4 Location of Well (F	ootage, Sec , T , R., M., or Survey Description	1)		Antelope Ridge Morrow
660' FNL & 1650'	FEL; Section 4 - T24S - R34E			11 County or Parish, State Lea County, New Mexico
12. (CHECK APPROPRIATE BOX(ES)	TO INDICATE NATU	RE OF NOTICE,	REPORT, OR OTHER DATA
TYPE OF SUBM	**		PE OF ACTION	
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (S	Start/Resume)
Subsequent Repo	rt Casing Repair	New Construction	Recomplete	Other Current Wellbore
Final Abandonme	ent Notice Convert to Injection	Plug and Abandon Plug Back	Temporarily A	
testing has been or determined that th	hat the foregoing is true and correct Typed) hat the foregoing is true and correct Typed)	be filed only after all require or record.	ACCEP	TED FOR RECORD OEC 18 2007 OEXIS C. SWOBODA ROLEUM ENGINEER
14 I hereby certify t Name (Printed)	hat the foregoing is true and correct			
	non L. Klier	Title C	perations Engineer	ring Manager
Signature	Seklin	Date	11/14/0	7
	THIS SPACE FOR	R FEDERAL OR S	TATE OFFICE	E USE
Approved by		7	itle	Date
Conditions of approval certify that the applicate which would entitle the	, if any, are attached Approval of this notinat holds legal or equitable title to those right applicant to conduct operations thereon.	ce does not warrant or s in the subject lease	Office	
Title 18 USC Section States any false, fictitio	1001 and Title 43 USC Section 1212, make us or fraudulent statements or representatio	t a crime for any person kins as to any matter within it	nowingly and willfully s jurisdiction	y to make to any department or agency of the United
(Instructions on pa	ge 2)		1	


Released to Imaging: 2/26/2024 1:47:42 PM





Approval Subject to General Requirements

and Special Stipulations Attached



Approval Subject to General Requirements and Special Stipulations Attached

NOTICE OF INTENT TO PLUG AND ABANDON 2/22/2024 ANTELOPE RIDGE 02 30-025-20444-0000 PE: Michael Heinz

PLUGGING PROCEDURE:

- 1. 10# MLF between plugs. Utilize above ground steel tanks.
- 2. POOH with production equipment.
- 3. Set CIBP @ 11510' and dump 230 SX of Class H cement with TOC @ 10839'
- 4. Spot 90 SX of Class H cement @ 9103' with TOC @ 8841'.
- 5. Spot 90 SX of Class C cement @ 5452' with TOC @ 5190'.
- 6. Perf @ 912' with 695 SX of Class C cement to surface.
- 7. Approximate total: 1105 SX of cmt

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications) minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds). A weep hole shall be left if a metal plate is welded in place.

- 7. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you

have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Mark Mattozzi Environmental Protection Specialist 575-234-5713

Robert Duenas Environmental Protection Specialist 575-234-2229

Doris Lauger Martinez Environmental Protection Specialist 575-234-5926

Jaden Johnston Environmental Protection Asst. (Intern) 575-234-6252

Sundry ID	2776396						
Plug Type	Тор	Bottom	Length	Tag	Sacks	Cement Class	Notes
							Perf and squeeze across all casing strings to surface. Verify at surface. (In
Surface Plug	0.00	100.00	100.00	Tag/Verify	125.00	С	19 sxs/Out 28 sxs/Out 78 sxs)
20 inch- Shoe Plug	852.88	962.00	109.12	Tag/Verify	93.00	С	Perf and squeeze between the 13 3/8" x 20" casing from 962' to 852'. WOC and Tag. (In 20 sxs/Out 73 sxs)
<u> </u>				Ŭ ,			Spot cement from
Ton of Calt @ 4725	1057.75	1775 00	117.05	Tan A /anifi	22.00		1775' to 1657'.
Top of Salt @ 1725 Casing Leak @ 4500	1657.75 4405.00	1775.00 4550.00		Tag/Verify If solid	22.00	C	WOC and Tag.
Base of Salt @ 5080	4979.20	5130.00		Tag/Verify			
Delaware @ 5131	5029.69	5181.00		If solid			
13.375 inch- Shoe Plug	5248.48	5402.00	153.52	Tag/Verify	181.00	С	Spot cement from 5402' to 4405'. WOC and Tag.
Casing Leak @ 7601	7474.99	7651.00	176.01	If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio	40.00	н	Spot cement from 7651' to 7475'. WOC and Tag.
Bonesprings @ 8727	8589.73	8777.00			40.00	11	vvoc anu ray.
							Spot cement from 9053' to 8589'.
DV tool plug	8862.97	9053.00		Tag/Verify	105.00	H	WOC and Tag.
Liner Top @ 11422	11257.78	11472.00		If solid			
7.625 inch- Shoe Plug	11258.77	11473.00	214.23	Tag/Verify			

				1		1	
Wolfcamp @ 11511 Strawn @ 11940 9.625 inch- Shoe Plug	11345.89 11770.60 11834.95	11561.00 11990.00 12055.00	215.11 219.40		71.00	Н	Spot cement from 11561' to 11257'. WOC and Tag.
Atoka @ 12092 Morrow @ 12762	11921.08 12584.38	12142.00 12812.00	220.92 227.62				
				If solid base no need to Tag (CIBP present and/or Mechanic al Integrity Test), If Perf & Sqz then Tag, Leak Test all CIBP if no Open Perforatio			Set CIBP at 12795'. Spot cement from 12795' to 11770'. Leak Test CIBP.
CIBP Plug	12760.00	12795.00	35.00	ns	242.00	Н	WOC and Tag.
Perforations Plug (If No CIBP)	12795.00	13048.00	253.00	Tag/Verify			
CIBP Plug	13055.00	13090.00	35.00	If solid			
7.625 inch- Shoe Plug	13989.19	14231.00	241.81	Tag/Verify			

No more than 2000' is to be allowed between plugs in open hole, and no more than 3000' between plugs in cased hole. Class H >7500' Class C<7500'

Fluid used to mix the cement in R111P shall be saturated with the salts common to the section penetrated, and in suitable proportions, but not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

Medium, Secretary: Top of salt to surface If no salt take the deepest fresh water or Karst Depth

High, Critical: Bottom of Karst to surface or Deepest fresh water, whichever is greater R111P: 50 Feet from Base of Salt to surface.

Class C: 1.32 ft^3/sx Class H: 1.06 ft^3/sx

Onshore Order 2.III.G Drilling Abandonment Requirements: "All formations bearing usable-quality water, oil, gas, or geothermal resources, and/or a prospectively valuable deposit of minerals shall be protected.

Cave Karst/Potash Cement Requirement:	Low		
20 inch- Shoe Plug @ 13.375 inch- Shoe Plug @ 9.625 inch- Shoe Plug @	912.00 5352.00 12005.00	TOC @ TOC @	1500.00 700.00
			(11423 to 9900) and (7601 to
7.625 inch- Shoe Plug @ 7.625 inch- Shoe Plug @	11423.00 14181.00	TOC @ TOC @	surface) 11900.00
Perforatons Top @	12845.00	Perforations	12998.00
DV Tool @	9003.00	CIBP @ CIBP @	13090.00 12795.00

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

COMMENTS

Action 317116

COMMENTS

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	317116
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

COMMENTS

Created By	Comment	Comment Date
plmartinez	DATA ENTRY PM.	2/26/2024

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 317116

CONDITIONS

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	317116
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
kfortner	Like approval from BLM	2/23/2024