Sundry Print Report 02/12/2024

Page 1 of 30

Well Name: POKER LAKE UNIT 29-20

BUREAU OF LAND MANAGEMENT

Well Location: T25S / R31E / SEC 29 /

NWNW /

Well Number: 151H Type of Well: CONVENTIONAL GAS

Allottee or Tribe Name:

County or Parish/State:

WELL

Unit or CA Name: Lease Number: NMLC061634A

Unit or CA Number: NMNM71016X

US Well Number: 3001554265

Well Status: Approved Application for

Permit to Drill

Operator: XTO PERMIAN

OPERATING LLC

Notice of Intent

Sundry ID: 2765094

Type of Submission: Notice of Intent Type of Action: APD Change Date Sundry Submitted: 12/07/2023 Time Sundry Submitted: 02:56

Date proposed operation will begin: 01/05/2024

Procedure Description: Pool Change, First and Last Take Point Changes, Bottom Hole Location Change, Drilling Plan Change, Directional Plan Change, Casing/Cement Change. POOL: FROM: (98220) Purple Sage; Wolfcamp (gas) TO: WC; Big Sinks; Bone Spring (96654) SHL: Fr/ 530' FNL & 1115' FWL To: 531' FNL & 1605' FWL of Sec 29-T25S-31E FTP: FROM: 2310' FNL & 680' FEL TO: 2115' FNL & 1645' FWL of Section 28-T25S-R31E PPP1: 0' FNL & 531' FEL LTP: FROM: 100' FSL & 680' FEL TO: 2570' FSL & 545' FWL of Section 16-T25S-R31E BHL: FROM: 50' FNL & 680' FEL TO: 2660' FSL & 545' FWL of Section 16-T25S-R31E HOLE AND CASING SIZES: surface, intermediate and production hole, casing and cement will be downsized based on the attached drilling program. Due to the downsize in these strings, the wellhead configuration has also changed based on the attached drilling program. Casing/Cement design per the attached drilling program. Attachments: C102 Drilling Program Directional Plan MBS

NOI Attachments

Procedure Description

Poker_Lake_Unit_29_20_BS_151H_Sundry_Attachments_20231207145534.pdf

Received by OCD: WIRARAS POWERS AND UNIT 29-20

Well Location: T25S / R31E / SEC 29 / NWNW /

County or Parish/State:

Allottee or Tribe Name:

Page 2 of 30

Well Number: 151H

Type of Well: CONVENTIONAL GAS

Unit or CA Number:

Lease Number: NMLC061634A

Unit or CA Name:

NMNM71016X

US Well Number: 3001554265 Well Status: Approved Application for

Permit to Drill

Operator: XTO PERMIAN OPERATING LLC

Conditions of Approval

Additional

Sec_29_25S_31E_NMP_Sundry_2765094_Poker_Lake_Unit_29_20_BS_151H_COAs_20240126091803.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: CASSIE EVANS Signed on: FEB 02, 2024 02:14 PM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5 City: Midland State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field

Representative Name:

Street Address:

City: State: Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: CHRISTOPHER WALLS BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752342234 BLM POC Email Address: cwalls@blm.gov

Disposition: Approved Disposition Date: 02/09/2024

Signature: Chris Walls

Page 2 of 2

Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 202

BURE	AU OF LAND MANAGEMENT		5. Lease Serial No.	NMLC061634A				
Do not use this fo	OTICES AND REPORTS ON Worm for proposals to drill or to se Form 3160-3 (APD) for suc	re-enter an	6. If Indian, Allottee	or Tribe Name				
SUBMIT IN TR	RIPLICATE - Other instructions on pag	e 2	_	eement, Name and/or No.				
1. Type of Well			NMNM71016X					
Oil Well Gas We	—		8. Well Name and No	^{0.} POKER LAKE UNIT 29-20 BS/151H				
2. Name of Operator XTO PERMIAN C	PERATING LLC		9. API Well No. 300	1554265				
3a. Address 6401 HOLIDAY HILL RO.	AD BLDG 5, MIDLAND, 3b. Phone No. (432) 683-22	(include area code) 77	10. Field and Pool of WC-025 G-08 S2	r Exploratory Area 13304D/WOLFCAMP (GAS)				
4. Location of Well (Footage, Sec., T.,R.,, SEC 29/T25S/R31E/NMP	M., or Survey Description)		11. Country or Parisl EDDY/NM	h, State				
12. CHEC	K THE APPROPRIATE BOX(ES) TO INI	DICATE NATURE (OF NOTICE, REPORT OR OT	THER DATA				
TYPE OF SUBMISSION		TYPE	E OF ACTION					
✓ Notice of Intent	Acidize Deep Alter Casing Hydr	en [aulic Fracturing [Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity				
Subsequent Report		Construction [and Abandon [Recomplete Temporarily Abandon	Other				
Final Abandonment Notice	Convert to Injection Plug	Back [Water Disposal					
completed. Final Abandonment Notice is ready for final inspection.) Pool Change, First and Last Take Casing/Cement Change. POOL: FROM: (98220) Purple States States From From From From From From From From	Ree Point Changes, Bottom Hole Location Sage; Wolfcamp (gas) TO: WC; Big Sir To: 531' FNL & 1605' FWL of Sec 29- FEL TO: 2115 FNL & 1645 FWL of Section TO: 2660 FSL & 545 FWL of Section To: 2660 FSL & 545 FWL of Section Trace, intermediate and production hole In these strings, the wellhead configural Information	on Change, Drilling onks; Bone Spring (9) T25S-31E tion 28-T25S-R31E on 16-T25S-R31E 16-T25S-R31E	tion, have been completed and Plan Change, Directional F96654)	Plan Change,				
CASSIE EVANS / Ph: (432) 218-367		Regulatory	Analyst					
Signature (Electronic Submission		Title Date	02/02/	2024				
	THE SPACE FOR FED	ERAL OR STA	TE OFICE USE					
Approved by								
CHRISTOPHER WALLS / Ph: (575)	234-2234 / Approved	Petrole Title	eum Engineer	02/09/2024 Date				
	ed. Approval of this notice does not warran uitable title to those rights in the subject le uct operations thereon.	t or	<u> </u>					

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

(Form 3160-5, page 2)

Additional Information

Additional Remarks

Casing/Cement design per the attached drilling program.

Attachments:

C102

Drilling Program

Directional Plan

MBS

Location of Well

0. SHL: NWNW / 530 FNL / 1115 FWL / TWSP: 25S / RANGE: 31E / SECTION: 29 / LAT: 32.107095 / LONG: -103.805237 (TVD: 0 feet, MD: 0 feet) PPP: SWNW / 2310 FNL / 680 FWL / TWSP: 25S / RANGE: 31E / SECTION: 29 / LAT: 32.102201 / LONG: -103.806689 (TVD: 12454 feet, MD: 13075 feet) BHL: NWNW / 50 FNL / 680 FWL / TWSP: 25S / RANGE: 31E / SECTION: 20 / LAT: 32.123019 / LONG: -103.806501 (TVD: 12454 feet, MD: 20648 feet)

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME: XTO Permian Operating LLC
WELL NAME & NO.: Poker Lake Unit 29-20 BS 151H
LOCATION: Sec 29-25S-31E-NMP
COUNTY: Eddy County, New Mexico

Changes approved through engineering via **Sundry 2765094** on 01/26/2024. Any previous COAs not addressed within the updated COAs still apply.

COA

H ₂ S	No	C Yes		
Potash / WIPP	None	 Secretary 	C R-111-P	■ WIPP
Cave / Karst	C Low	Medium	🛚 High	Critical
Wellhead	Conventional	• Multibowl	© Both	Diverter
Cementing	Primary Squeeze		EchoMeter	DV Tool
Special Req	Break Testing	Water Disposal	COM	Unit
Variance	▼ Flex Hose	Casing Clearance	Pilot Hole	Capitan Reef
Variance	Four-String	Offline Cementing	Fluid-Filled	Open Annulus
		Batch APD / Sundry		

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet 43 CFR 3176 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

- 1. The 9-5/8 inch surface casing shall be set at approximately 866 feet (a minimum of 70 feet (Eddy County) into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface. NOTE: This area has a high dissolution of salt, so the operator may need to make adjustments to their surface set depths to find a competent set point.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead

cement)

- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.
- 2. The minimum required fill of cement behind the 7-5/8 inch intermediate casing is:

Operator has proposed to cement in two stages by conventionally cementing the first stage and performing a bradenhead squeeze on the second stage, contingent upon no returns to surface.

- a. First stage: Operator will cement with intent to reach the top of the **Brushy Canyon** at 6879'
- b. Second stage:
 - Operator will perform bradenhead squeeze and top-out. Cement to surface. If cement does not reach surface, the appropriate BLM office shall be notified.
 Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, Capitan Reef, or potash.
- ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

Operator has proposed to pump down 9-5/8" X 7-5/8" annulus after primary cementing stage. Operator must run Echo-meter to verify Cement Slurry/Fluid top in the annulus OR operator shall run a CBL from TD of the 7-5/8" casing to surface after the second stage BH to verify TOC.

Submit results to the BLM. No displacement fluid/wash out shall be utilized at the top of the cement slurry between second stage BH and top out. Operator must use a limited flush fluid volume of 1 bbl following backside cementing procedures.

- 3. The minimum required fill of cement behind the 5-1/2 inch production casing is:
 - Cement should tie-back at least 300 feet into previous casing string (due to not meeting the 0.422" clearance requirement.) Operator shall provide method of verification. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst, Capitan Reef, or potash.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'

- 2. Operator has proposed a multi-bowl wellhead assembly. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR 3172 must be followed.

D. SPECIAL REQUIREMENT (S)

Unit Wells

The well sign for a unit well shall include the unit number in addition to the surface and bottom hole lease numbers. This also applies to participating area numbers. If a participating area has not been established, the operator can use the general unit designation, but will replace the unit number with the participating area number when the sign is replaced.

Commercial Well Determination

A commercial well determination shall be submitted after production has been established for at least six months. (This is not necessary for secondary recovery unit wells)

(Note: For a minimum 5M BOPE or less (Utilizing a 10M BOPE system) BOPE Break Testing Variance

- BOPE Break Testing is ONLY permitted for 5M BOPE or less. (Annular preventer must be tested to a minimum of 70% of BOPE working pressure and shall be higher than the MASP)
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer (575-706-2779) prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- The BLM is to be contacted (575-361-2822 Eddy County) 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at 21-day intervals.

- In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per Onshore Oil and Gas Order No. 2.
- If in the event break testing is not utilized, then a full BOPE test would be conducted.

Offline Cementing

Contact the BLM prior to the commencement of any offline cementing procedure.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)
 - Eddy County (API No. / US Well No. contains 30-015-####)
 Email or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,

 BLM_NM_CFO_DrillingNotifications@BLM.GOV
 (575) 361-2822
 - Lea County (API No. / US Well No. contains 30-025-####)
 Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575) 689-5981
- 1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per **43 CFR part 3170 Subpart 3172** as soon as 2nd Rig is rigged up on well.
- 2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

- 1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
- 2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing intergrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
- 4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
- 5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
- 6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.

- 7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
- 8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in 43 CFR part 3170 Subpart 3172 and API STD 53 Sec. 5.3.
- 2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
- 3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in 43 CFR part 3170 Subpart 3172 must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
- 5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The

casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR part 3170 Subpart 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per 43 CFR part 3170 Subpart 3172.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

12 Dedicated Acres

¹³ Joint or Infill

14 Consolidation Code

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office


☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1	API Number	r		² Pool Code			³ Pool Na	me				
	30-015-54	4265		96654			WC; Big S	inks; Bone	e Spring			
⁴ Property	Code				⁵ Property	Name			6 ,	Well Number		
				P	OKER LAKE U	NIT 29-20 BS				151H		
7 OGRID	No.				8 Operator	Name				⁹ Elevation		
373075					XTO Permian	Operating, LLC.				3,365'		
					¹⁰ Surface	Location						
UL or lot no.	UL or lot no. Section Township Range Lot Idn Feet from the North/South line Feet from the I											
C	29	25 S	31 E		531	NORTH	1,605	WE	EST EDDY			
			11 Bot	tom Hol	e Location It	Different From	n Surface					
UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	Eas	t/West line	County		
I.	16	25 S	31 E		2.663	SOUTH	545	WE	ST	EDDY		

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division

⁵ Order No.



DRILLING PLAN: BLM COMPLIANCE (Supplement to BLM 3160-3)

XTO Energy Inc.

Poker Lake Unit 29-20 BS 151H Projected TD: 22350.61' MD / 10030' TVD SHL: 531' FNL & 1605' FWL , Section 29, T25S, R31E BHL: 2663' FSL & 545' FWL , Section 16, T25S, R31E Eddy County, NM

1. Geologic Name of Surface Formation

Quaternary

2. Estimated Tops of Geological Markers & Depths of Anticipated Fresh Water, Oil or Gas

Formation	Well Depth (TVD)	Water/Oil/Gas
Rustler	766'	Water
Top of Salt	1142'	Water
Base of Salt	3995'	Water
Delaware	4202'	Water
Brushy Canyon	6879'	Water/Oil/Gas
Bone Spring	8152'	Water
1st Bone Spring	8973'	Water/Oil/Gas
2nd Bone Spring	9612'	Water/Oil/Gas
Target/Land Curve	10030'	Water/Oil/Gas

^{***} Hydrocarbons @ Brushy Canyon

No other formations are expected to yield oil, gas or fresh water in measurable volumes. The surface fresh water sands will be protected by setting 9.625 inch casing @ 866' (276' above the salt) and circulating cement back to surface. The intermediate will isolate from the top of salt down to the next casing seat by setting 7.625 inch casing at 10952.56' and cemented to surface. A 6.75 inch curve and 6.75 inch lateral hole will be drilled to 22350.61 MD/TD and 5.5 inch production casing will be set at TD and cemented back up in the intermediate shoe (estimated TOC 10652.56 feet).

3. Casing Design

Hole Size	Depth	OD Csg	Weight	Grade	Collar	New/Used	SF Burst	SF Collapse	SF Tension
12.25	0' – 866'	9.625	40	J-55	втс	New	1.32	7.27	18.19
8.75	0' – 4000'	7.625	29.7	RY P-110	Flush Joint	New	2.89	2.71	1.72
8.75	4000' – 10952.56'	7.625	29.7	HC L-80	Flush Joint	New	2.10	1.90	1.97
6.75	0' - 10852.56'	5.5	20	RY P-110	Semi-Premium	New	1.26	1.87	2.03
6.75	10852.56' - 22350.61'	5.5	20	RY P-110	Semi-Flush	New	1.26	2.03	2.03

[•] XTO requests the option to utilize a spudder rig (Atlas Copco RD20 or Equivalent) to set and cement surface casing per this Sundry

- · XTO requests to not utilize centralizers in the curve and lateral
- 7.625 Collapse analyzed using 50% evacuation based on regional experience.
- 5.5 Tension calculated using vertical hanging weight plus the lateral weight multiplied by a friction factor of 0.35
- Test on Casing will be limited to 70% burst of the casing or 1500 psi, whichever is less
- XTO requests the option to use 5" BTC Float equipment for the the production casing

^{***} Groundwater depth 40' (per NM State Engineers Office).

Wellhead:

Permanent Wellhead - Multibowl System

- A. Starting Head: 11" 10M top flange x 9-5/8" bottom
 B. Tubing Head: 11" 10M bottom flange x 7-1/16" 15M top flange
 - · Wellhead will be installed by manufacturer's representatives.
 - · Manufacturer will monitor welding process to ensure appropriate temperature of seal.
 - · Operator will test the 7-5/8" casing per BLM Onshore Order 2
 - · Wellhead Manufacturer representative will not be present for BOP test plug installation

4. Cement Program

Surface Casing: 9.625, 40 New BTC, J-55 casing to be set at +/- 866'

Lead: 180 sxs EconoCem-HLTRRC (mixed at 10.5 ppg, 1.87 ft3/sx, 10.13 gal/sx water)
Tail: 130 sxs Class C + 2% CaCl (mixed at 14.8 ppg, 1.35 ft3/sx, 6.39 gal/sx water)

Top of Cement: Surface

Compressives: 12-hr = 900 psi 24 hr = 1500 psi

2nd Intermediate Casing: 7.625, 29.7 New casing to be set at +/- 10952.56'

st Stage

Optional Lead: 370 sxs Class C (mixed at 10.5 ppg, 2.77 ft3/sx, 15.59 gal/sx water)

TOC: Surface

Tail: 370 sxs Class C (mixed at 14.8 ppg, 1.35 ft3/sx, 6.39 gal/sx water)

TOC: Brushy Canyon @ 6879

Compressives: 12-hr = 900 psi 24 hr = 1150 psi

2nd Stage

Lead: 0 sxs Class C (mixed at 12.9 ppg, 2.16 ft3/sx, 9.61 gal/sx water) Tail: 770 sxs Class C (mixed at 14.8 ppg, 1.33 ft3/sx, 6.39 gal/sx water)

Top of Cement: 0

Compressives: 12-hr = 900 psi 24 hr = 1150 psi

XTO requests to pump a two stage cement job on the 7-5/8" intermediate casing string with the first stage being pumped conventionally with the calculated top of cement at the Brush Canyon (6879') and the second stage performed as a bradenhead squeeze with planned cement from the Brushy Canyon to surface. If cement is not visually confirmed to circulate to surface, the final cement top after the second stage job will be verified by Echo-meter. If necessary, a top out consisting of 1,500 sack of Class C cement + 3% Salt + 1% PreMag-M + 6% Bentonite Gel (2.30 yld, 12.91 ppg) will be executed as a contingency. If cement is still unable to circulate to surface, another Echo-meter run will be performed for cement top verification.

XTO will report to the BLM the volume of fluid (limited to 5 bbls) used to flush intermediate casing valves following backside cementing procedures.

XTO requests to pump an Optional Lead if well conditions dictate in an attempt to bring cement inside the first intermediate casing. If cement reaches the desired height, the BLM will be notified and the second stage bradenhead squeeze and subsequent TOC verification will be negated.

XTO requests the option to conduct the bradenhead squeeze and TOC verification offline as per standard approval from BLM when unplanned remediation is needed and batch drilling is approved. In the event the bradenhead is conducted, we will ensure the first stage cement job is cemented properly and the well is static with floats holding and no pressure on the csg annulus as with all other casing strings where batch drilling operations occur before moving off the rig. The TA cap will also be installed per Cactus procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops.

Production Casing: 5.5, 20 New Semi-Flush, RY P-110 casing to be set at +/- 22350.61'

Lead: 20 sxs NeoCem (mixed at 11.5 ppg, 2.69 ft3/sx, 15.00 gal/sx water) Top of Cement: 10652.56 feet
Tail: 800 sxs VersaCem (mixed at 13.2 ppg, 1.51 ft3/sx, 8.38 gal/sx water) Top of Cement: 11152.56 feet
Compressives: 12-hr = 800 psi 24 hr = 1500 psi

XTO requests the option to offline cement and remediate (if needed) surface and intermediate casing strings where batch drilling is approved and if unplanned remediation is needed. XTO will ensure well is static with no pressure on the csg annulus, as with all other casing strings where batch drilling operations occur before moving off the rig. The TA cap will also be installed when applicable per Cactus procedure and pressure inside the casing will be monitored via the valve on the TA cap as per standard batch drilling ops. Offline cement operations will then be conducted after the rig is moved off the current well to the next well in the batch sequence.

5. Pressure Control Equipment

Once the permanent WH is installed on the 9.625 casing, the blow out preventer equipment (BOP) will consist of a 13-5/8" minimum 5M Hydril and a 13-5/8" minimum 5M Double Ram BOP. MASP should not exceed 3270 psi. In any instance where 10M BOP is required by BLM, XTO requests a variance to utilize 5M annular with 10M ram preventers (a common BOP configuration, which allows use of 10M rams in unlikely event that pressures exceed 5M).

All BOP testing will be done by an independent service company. Annular pressure tests will be limited to 50% of the working pressure. When nippling up on the 9.625, 5M bradenhead and flange, the BOP test will be limited to 5000 psi. When nippling up on the 7.625, the BOP will be tested to a minimum of 5000 psi. All BOP tests will include a low pressure test as per BLM regulations. The 5M BOP diagrams are attached. Blind rams will be functioned tested each trip, pipe rams will be functioned tested each day.

A variance is requested to allow use of a flex hose as the choke line from the BOP to the Choke Manifold. If this hose is used, a copy of the manufacturer's certification and pressure test chart will be kept on the rig. Attached is an example of a certification and pressure test chart. The manufacturer does not require anchors.

XTO requests a variance to be able to batch drill this well if necessary. In doing so, XTO will set casing and ensure that the well is cemented properly (unless approval is given for offline cementing) and the well is static. With floats holding, no pressure on the csg annulus, and the installation of a 10K TA cap as per Cactus recommendations, XTO will contact the BLM to skid the rig to drill the remaining wells on the pad. Once surface and both intermediate strings are all completed, XTO will begin drilling the production

hole on each of the wells.

A variance is requested to **ONLY** test broken pressure seals on the BOP equipment when moving from wellhead to wellhead which is in compliance with API Standard 53. API standard 53 states, that for pad drilling operation, moving from one wellhead to another within 21 days, pressure testing is required for pressure-containing and pressure-controlling connections when the integrity of a pressure seal is broken. Based on discussions with the BLM on February 27th 2020, we will request permission to **ONLY** retest broken pressure seals if the following conditions are met: 1. After a full BOP test is conducted on the first well on the pad 2. When skidding to drill an intermediate section that does not penetrate into the Wolfcamp.

6. Proposed Mud Circulation System

INTERVAL	Hole Size	Mud Type	MW	Viscosity	Fluid Loss
INTERVAL	Fiole Size	Muu Type	(ppg)	(sec/qt)	(cc)
0' - 866'	12.25	FW/Native	8.4-8.9	35-40	NC
866' - 10952.56'	8.75	FW / Cut Brine / Direct Emulsion	9.5-10	30-32	NC
10952.56' - 22350.61'	6.75	ОВМ	10.5-11	50-60	NC - 20

The necessary mud products for weight addition and fluid loss control will be on location at all times.

Spud with fresh water/native mud. Drill out from under 9-5/8" surface casing with brine solution. A 9.7 ppg - 10.2 ppg cut brine mud will be used while drilling through the salt formation. Use fibrous materials as needed to control seepage and lost circulation. Pump viscous sweeps as needed for hole cleaning. Pump speed will be recorded on a daily drilling report after mudding up. A Pason or Totco will be used to detect changes in loss or gain of mud volume. A mud test will be performed every 24 hours to determine: density, viscosity, strength, filtration and pH as necessary. Use available solids controls equipment to help keep mud weight down after mud up. Rig up solids control equipment to operate as a closed loop system.

7. Auxiliary Well Control and Monitoring Equipment

- A. A Kelly cock will be in the drill string at all times.
- B. A full opening drill pipe stabbing valve having appropriate connections will be on the rig floor at all times.
- C. H2S monitors will be on location when drilling below the 9.625 casing.

8. Logging, Coring and Testing Program

Mud Logger: Mud Logging Unit (2 man) below intermediate casing.

Open hole logging will not be done on this well.

9. Abnormal Pressures and Temperatures / Potential Hazards

None Anticipated. BHT of 165 to 185 F is anticipated. No H2S is expected but monitors will be in place to detect any H2S occurrences. Should these circumstances be encountered the operator and drilling contractor are prepared to take all necessary steps to ensure safety of all personnel and environment. Lost circulation could occur but is not expected to be a serious problem in this area and hole seepage will be compensated for by additions of small amounts of LCM in the drilling fluid. The maximum anticipated bottom hole pressure for this well is 5476 psi.

10. Anticipated Starting Date and Duration of Operations

Anticipated spud date will be after BLM approval. Move in operations and drilling is expected to take 40 days.

Magnitude Semi-major Semi-minor Semi-minor Tool

Well Plan Report - PLU 29-20 151H

Well Plan Report	Site:	Slot: PLU 29-20 151H								
PLU 29-20 151H	22350.61 ft	10030.00 ft		New Mexico East - NAD 27	403042.60 ft	664156.00 ft	3397.00 ft	3365.00 ft	Grid	0.28 Deg
T1/2/23, 12:10 PM Seport - PLU 29-20 151H of page 151H	Measured Depth:	TVD RKB:	Location	Cartographic Reference System:	Northing:	60: Easting:	RKB:	Ground Level:	North Reference:	Convergence Angle:

Plan Sections	PLI	PLU 29-20 151H						
Measured			TVD			Build	Turn	Dogleg
Depth	Inclination	Azimuth	RKB	Y Offset	X Offset	Rate	Rate	Rate
(ft)	(Deg)	(Deg)	(#)	(ft)	(ft)	(Deg/100ft)	(Deg/100ft)	(Deg/100ft) Target
00:00	00.00	00.00	00.00	00.00	00.00	0.00	0.00	0.00
1100.00	00.00	00.00	1100.00	00.00	00.00	0.00	0.00	0.00
3493.59	47.87	118.17	3224.66	-445.17	831.43	2.00	0.00	2.00
7445.16	47.87	118.17	5875.34	-1828.52	3415.07	0.00	0.00	0.00
9838.76	00.00	00.00	8000.00	-2273 70	4246.50	-2.00	0.00	2.00
11152.56	00.00	00.00	9313.80	-2273.70	4246.50	0.00	0.00	0.00
12277.56	00'06	359.94	10030.00	-1557.50	4245.80	8.00	0.00	8.00 FTP 4
22251.86	90.00	359.94	10030.00	8416.80	4236.00	0.00	0.00	0.00 LTP 4
22350.61	00.06	359.94	10030.00	8515.55	4235.90	00.00	00.00	0.00 BHL 4

Vertical	
Lateral	
TVD Highside	
2	
Measured	

PLU 29-20 151H

Position Uncertainty

'23, 12:10 PM								We	Well Plan Report	t			
Depth	Inclination	Azimuth	RKB	Error	Bias	Error	Bias	Error	Bias	of Bias	Error	Error	Azimuth Used
(#)	©	(0)	(#)	(#)	(£	(£)	(£	(#	(#)	(#)	(L	(#)	(,)
0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000 MWD+IFR1+MS
100.000	0.000	0.000	100.000	0 200 0	0.000	0.350	0.000	2.300	0.000	0.000	0.751	0.220	112.264 MWD+IFR1+MS
200.000	0.000	0.000	200.000	1.112 0	0.000	0.861	0.000	2.310	0.000	0.000	1.259	0.627	122.711 MWD+IFR1+MS
300.000	0.000	0.000	300 000	1 497 0	0.000	1.271	0.000	2.325	0.000	0.000	1.698	0 986	125.469 MWD+IFR1+MS
400.000	0.000	0.000	400.000	1.871 0	0.000	1.658	0.000	2.347	0.000	0.000	2.108	1 344	126.713 MWD+IFR1+MS
500.000	0.000	0.000	200.000	2.240 0.	0.000	2.034	0.000	2.374	0.000	0.000	2.503	1.701	127.419 MWD+IFR1+MS
000.009	0.000	0.000	000.009	2.607 0	0.000	2.405	0.000	2.407	0.000	0.000	2.888	2.059	127.873 MWD+IFR1+MS
700.000	0.000	0.000	700.000	2.971 0.	0.000	2.773	0.000	2.444	0.000	0.000	3.267	2.417	128.190 MWD+IFR1+MS
800.000	0.000	0.000	800.000	3.334 0.	0.000	3.138	0.000	2.485	0.000	0.000	3.642	2.775	128.423 MWD+IFR1+MS
900.006	0.000	0.000	000.006	3.696 0.	0.000	3.502	0.000	2.531	0.000	0.000	4.014	3.133	128.602 MWD+IFR1+MS
1000.000	0.000	0.000	1000.000	4.058 0	0.000	3.865	0.000	2.581	0.000	0.000	4.384	3.491	128.744 MWD+IFR1+MS
1100.000	0.000	0.000	1100.000	4 419 0	0.000	4.228	0.000	2.634	0.000	0.000	4.752	3 849	128.859 MWD+IFR1+MS
1200.000	2.000	118 166	1199 980	4 413 0	0.000	5.015	-0.000	2.691	0.000	0.000	5.052	4 372	132.131 MWD+IFR1+MS
1300.000	4 000	118 166	1299 838	5.267 0	0.000	5.337	-0.000	2.751	0.000	0.000	5.337	5.274	121.963 MWD+IFR1+MS
1400.000	00009	118 166	1399 452	6.015 0	0.000	5.665	-0.000	2.816	0.000	0.000	990'9	5.628	44.854 MWD+IFR1+MS
1500.000	8.000	118 166	1498 702	6 693 0	0.000	- 666'9	-0.000	2.889	0.000	0.000	6.781	5 930	44.146 MWD+IFR1+MS
1600.000	10.000	118 166	1597 465	7.318 0	0.000	6.339	-0.000	2.972	0.000	0.000	7.441	6.242	43.985 MWD+IFR1+MS
1700.000	12.000	118 166	1695.623	7 901 0	0.000	6.685	-0.000	3.067	0.000	000'0	8.060	6.563	43.961 MWD+IFR1+MS
1800.000	14.000	118 166	1793 055	8.451 0	0.000	7.039	-0.000	3.175	0.000	0.000	8.646	6.893	44.003 MWD+IFR1+MS
1900.000	16.000	118 166	1889 643	8 974 0	0.000	7.401	-0.000	3.298	0.000	000'0	9.205	7 234	44.092 MWD+IFR1+MS
2000.000	18.000	118.166	1985.268	9.472 0	0.000	7.772	-0.000	3.438	0.000	0.000	9.742	7.586	44.221 MWD+IFR1+MS
2100.000	20.000	118.166	2079.816	9 950 0	0.000	8.155 -	-0.000	3.596	0.000	0.000	10.259	7 951	44.394 MWD+IFR1+MS
2200.000	22.000	118.166	2173.169	10.410 0.	0.000	8.551	-0.000	3.773	0.000	0.000	10.760	8.330	44.615 MWD+IFR1+MS
2300.000	24 000	118 166	2265.215	10 855 0	0.000	8.960	-0.000	3.969	0.000	0.000	11.246	8.725	44.894 MWD+IFR1+MS
2400.000	26.000	118 166	2355 841	11 286 0	0.000	9.387	-0.000	4.187	0.000	0.000	11.720	9 136	45.242 MWD+IFR1+MS
2500.000	28.000	118.166	2444.937	11.704 0.	0.000	9.831	-0.000	4.426	0.000	0.000	12.183	9.565	45.677 MWD+IFR1+MS
2600.000	30.000	118.166	2532.394	12.112 0.	0.000	10.296 -	-0.000	4.687	0.000	0.000	12.636	10.015	46.222 MWD+IFR1+MS
2700.000	32.000	118.166	2618.107	12.511 0.	0.000.0	10.782 -	-0.000	4.970	0.000	0.000	13.080	10.485	46.908 MWD+IFR1+MS
2800.000	34.000	118.166	2701.970	12.901 0.	0.000.0	11.293 -	-0.000	5.276	0.000	0.000	13.518	10.978	47.776 MWD+IFR1+MS
2900.000	36.000	118 166	2783.881	13.284 0	0.000	11.829 -	-0.000	5.605	0.000	0.000	13.949	11 493	48.887 MWD+IFR1+MS
3000.000	38.000	118.166	2863.740	13.660 0.	0.000	12.392 -	-0.000	5.957	0.000	0.000	14.376	12.032	50.324 MWD+IFR1+MS

	52.206 MWD+IFR1+MS	54.708 MWD+IFR1+MS	58.069 MWD+IFR1+MS	62.587 MWD+IFR1+MS	68.193 MWD+IFR1+MS	68.629 MWD+IFR1+MS	77.007 MWD+IFR1+MS	85.545 MWD+IFR1+MS	92.784 MWD+IFR1+MS	98.297 MWD+IFR1+MS	102.337 MWD+IFR1+MS	105.304 MWD+IFR1+MS	107.522 MWD+IFR1+MS	109.220 MWD+IFR1+MS	110.548 MWD+IFR1+MS	111.609 MWD+IFR1+MS	112.471 MWD+IFR1+MS	113.183 MWD+IFR1+MS	113.779 MWD+IFR1+MS	114,284 MWD+IFR1+MS	114.716 MWD+IFR1+MS	115.090 MWD+IFR1+MS	115.415 MWD+IFR1+MS	115.701 MWD+IFR1+MS	115.953 MWD+IFR1+MS	116.177 MWD+IFR1+MS	116.377 MWD+IFR1+MS	116.557 MWD+IFR1+MS	116.720 MWD+IFR1+MS	116.867 MWD+IFR1+MS	117.000 MWD+IFR1+MS	117.122 MWD+IFR1+MS	117.234 MWD+IFR1+MS
	12.592	13.171	13.765	14.365	14.917	14.954	15.495	15.975	16.400	16.786	17.147	17.496	17.838	18.177	18.516	18.855	19.196	19.539	19.884	20.231	20.581	20.934	21.290	21 647	22.008	22.371	22.736	23.104	23.474	23.846	24.220	24.596	24.974
	14.801	15.228	15.662	16.112	16.552	16.580	17.048	17.610	18.248	18.942	19.676	20.438	21.220	22.016	22.825	23.643	24.469	25.301	26.140	26.983	27.831	28.682	29.537	30.395	31.256	32.120	32.986	33.854	34.724	35.596	36.469	37.344	38.220
oort	0.000	000'0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	000'0	0.000	000'0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Well Plan Report	6.332 0.000	6.731 0.000	7.152 0.000	7.598 0.000	8.014 0.000	8.028 0.000	8.345 0.000	8.685 0.000	9.036 0.000	9.399 0.000	9.772 0.000	10.153 0.000	10.542 0.000	10.938 0.000	11.340 0.000	11.748 0.000	12.161 0.000	12.578 0.000	13.000 0.000	13.425 0.000	13.854 0.000	14.286 0.000	14.721 0.000	15.158 0.000	15.598 0.000	16.040 0.000	16.484 0.000	16.930 0.000	17.377 0.000	17.827 0.000	18.278 0.000	18.730 0.000	19.184 0.000
	12.984 -0.000	13.607 -0.000	14.260 -0.000	14.945 -0.000	15.614 -0.000	15.660 -0.000	16.394 -0.000	17.151 -0.000	17.923 -0.000	18.706 -0.000	19.499 -0.000	20.302 -0.000	21.113 -0.000	21.931 -0.000	22.756 -0.000	23.587 -0.000	24.422 -0.000	25.263 -0.000	26.107 -0.000	26.956 -0.000	27.808 -0.000	28.663 -0.000	29.521 -0.000	30.382 -0.000	31.245 -0.000	32.110 -0.000	32.977 -0.000	33.847 -0.000	34.718 -0.000	35.591 -0.000	36.465 -0.000	37.340 -0.000	38.217 -0.000
	14.030 0.000	14.395 0.000	14.756 0.000	15.112 0.000	15.422 0.000	15.448 0.000	15.868 0.000	16.309 0.000	16.762 0.000	17.227 0.000	17.702 0.000	18.187 0.000	18.681 0.000	19.183 0.000	19.692 0.000	20.209 0.000	20.732 0.000	21.261 0.000	21.795 0.000	22.335 0.000	22.880 0.000	23.429 0.000	23.982 0.000	24.539 0.000	25.099 0.000	25.663 0.000	26.230 0.000	26.800 0.000	27.373 0.000	27.949 0.000	28.527 0.000	29.107 0.000	29.689 0.000
	2941.451	3016.918	3090.050	3160.757	3224.660	3228.958	3296.038	3363.117	3430.196	3497.275	3564.354	3631,433	3698.512	3765.591	3832.670	3899.750	3966.829	4033,908	4100.987	4168.066	4235.145	4302.224	4369.303	4436.383	4503.462	4570.541	4637.620	4704.699	4771.778	4838.857	4905.936	4973.016	5040.095
	118.166	118.166	118.166	118 166	118 166	118 166	118.166	118.166	118.166	118.166	118 166	118.166	118 166	118.166	118.166	118.166	118.166	118.166	118 166	118.166	118.166	118.166	118 166	118 166	118.166	118 166	118 166	118 166	118 166	118 166	118.166	118.166	118.166
	40.000	42.000	44.000	46.000	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872	47.872
11/2/23, 12:10 PM	3100.000	3200.000	3300.000	3400,000	3493.592	3500,000	3600.000	3700.000	3800.000	3900.000	4000.000	4100.000	4200.000	4300.000	4400.000	4500.000	4600.000	4700.000	4800.000	4900.000	2000.000	5100.000	5200.000	5300.000	5400.000	5500,000	2600.000	5700.000	5800.000	2900.000	000.0009	6100,000	6200.000
	eleas	ed t	o In	iagi	ng:	2/29	202	24 1	2:47	7:00	PM																						

4/9


	118.164 MWD+IFR1+MS	118.146 MWD+IFR1+MS	118.126 MWD+IFR1+MS	118.105 MWD+IFR1+MS	118.104 MWD+IFR1+MS	118.091 MWD+IFR1+MS	118.074 MWD+IFR1+MS	118.059 MWD+IFR1+MS	118.044 MWD+IFR1+MS	118.029 MWD+IFR1+MS	118.014 MWD+IFR1+MS	117.999 MWD+IFR1+MS	117.984 MWD+IFR1+MS	117.970 MWD+IFR1+MS	117.955 MWD+IFR1+MS	117.940 MWD+IFR1+MS	117.926 MWD+IFR1+MS	117.911 MWD+IFR1+MS	117.902 MWD+IFR1+MS	117.883 MWD+IFR1+MS	117.443 MWD+IFR1+MS	116.724 MWD+IFR1+MS	116.121 MWD+IFR1+MS	115.636 MWD+IFR1+MS	115.258 MWD+IFR1+MS	114.972 MWD+IFR1+MS	114.754 MWD+IFR1+MS	114.577 MWD+IFR1+MS	114.411 MWD+IFR1+MS	114.222 MWD+IFR1+MS	114.034 MWD+IFR1+MS	113.973 MWD+IFR1+MS	113.709 MWD+IFR1+MS
	38.866	39 199	39.515	39.811	39.895	40.018	40.222	40.428	40.636	40.847	41.059	41.273	41.490	41.708	41.929	42.151	42.375	42.601	42.720	42.825	43.104	43.400	43.637	43.818	43.949	44.040	44.102	44.147	44.187	44.232	44.275	44.288	44.359
	909.09	60.839	61.051	61.243	61 309	61.410	61.576	61.746	61.918	62.091	62.266	62.443	62 620	62.800	62.981	63.164	63.348	63.533	63.630	63.723	64.188	64.857	65.449	65 947	66.340	66.624	008.99	66.881	66.883	66.827	66.761	66.740	66.651
oort	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Well Plan Report	30.568 0.000	30.656 0.000	30.737 0.000	30.812 0.000	30.840 0.000	30.885 0.000	30.959 0.000	31.036 0.000	31.115 0.000	31.197 0.000	31.281 0.000	31.368 0.000	31.458 0.000	31,551 0.000	31.646 0.000	31.744 0.000	31.845 0.000	31.948 0.000	32.004 0.000	32.055 0.000	32.186 0.000	32.421 0.000	32.812 0.000	33.404 0.000	34.219 0.000	35.259 0.000	36.501 0.000	37.907 0.000	39.426 0.000	41.001 0.000	41.916 0.000	42.047 0.000	42.598 0.000
	-0.000	-0.000	-0.000	-0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	909.09	60.839	61.051	61.243	45.525	45.635	45.818	46.004	46.192	46.383	46.575	46.769	46.966	47.164	47.364	47.566	47.770	47.975	48.083	48.195	48.376	48.530	48.655	48.750	48.816	48.855	48.870	48.862	48.835	48.792	48.746	48.731	48.679
	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	41.668	41.220	40.714	40.153	57.253	57.359	57.534	57.712	57.891	58.072	58.255	58.440	58.626	58.813	59.002	59.193	59.385	59.579	59.681	59.143	57.817	56.106	53.804	51.082	48.161	45.317	42.872	41.166	40.493	41.014	41.916	42.047	42.598
	7662.032	7761,520	7861.298	7961.245	8000.000	8061.243	8161.243	8261.243	8361.243	8461.243	8561.243	8661.243	8761.243	8861.243	8961.243	9061.243	9161.243	9261.243	9313.803	9361,209	9460.204	9556,350	9647.775	9732.700	9809.471	9876.595	9932.764	988.9266	10008.102	10025.805	10030.000	10030.000	10030.000
	118 166	118.166	118 166	118.166	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	359.944	359.944	359.944	359.944	359 944	359.944	359 944	359.944	359.944	359.944	359.944	359.944	359.944	359.944
	6.775	4.775	2.775	0.775	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	3.795	11.795	19.795	27.795	35.795	43.795	51.795	59.795	67.795	75.795	83.795	90.000	90.000	000'06
11/2/23, 12:10 PM	9500.000	9600.000	9700.000	9800.000	9838.757	000.0066	10000.000	10100.000	10200.000	10300.000	10400.000	10500.000	10600.000	10700.000	10800.000	10900.000	11000.000	11100.000	11152.559	11200.000	11300.000	11400.000	11500.000	11600.000	11700.000	11800.000	11900.000	12000.000	12100.000	12200.000	12277.559	12300.000	12400.000
Re	leas	ed t	o In	agi	ng:	2/29	/202	24 1.	2:47	7:00	PM																						

	113.456 MWD+IFR1+MS	113.213 MWD+IFR1+MS	112.978 MWD+IFR1+MS	112.751 MWD+IFR1+MS	112.534 MWD+IFR1+MS	112.325 MWD+IFR1+MS	112.126 MWD+IFR1+MS	111.934 MWD+IFR1+MS	111.752 MWD+IFR1+MS	111.579 MWD+IFR1+MS	111.414 MWD+IFR1+MS	111.259 MWD+IFR1+MS	111.113 MWD+IFR1+MS	110.976 MWD+IFR1+MS	110.849 MWD+IFR1+MS	110.732 MWD+IFR1+MS	110.625 MWD+IFR1+MS	110.528 MWD+IFR1+MS	110.443 MWD+IFR1+MS	110.368 MWD+IFR1+MS	110.306 MWD+IFR1+MS	110,257 MWD+IFR1+MS	110.221 MWD+IFR1+MS	110.199 MWD+IFR1+MS	110.193 MWD+IFR1+MS	110.204 MWD+IFR1+MS	110.232 MWD+IFR1+MS	110.280 MWD+IFR1+MS	110.350 MWD+IFR1+MS	110.444 MWD+IFR1+MS	110.564 MWD+IFR1+MS	110,715 MWD+IFR1+MS	110.899 MWD+IFR1+MS
	44.447	44.547	44.662	44.789	44.931	45.086	45.255	45.437	45.632	45.841	46.063	46.298	46.547	46.808	47.082	47.368	47.667	47.978	48.301	48.636	48.983	49.341	49.710	20.090	50.481	50.882	51.294	51.715	52.146	52.587	53.037	53,495	53.963
	66.565	66.481	66.400	66.322	66.246	66.173	66.102	66.034	65.967	65.903	65.841	65.781	65.723	65.667	65.613	65,561	65.511	65.462	65.416	65,371	65.328	65.287	65.247	62.209	65.173	65.139	65.106	65.075	65.046	62.019	64.993	64.970	64.948
ort	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Well Plan Report	43.159 0.000	43.727 0.000	44.302 0.000	44.883 0.000	45.470 0.000	46.063 0.000	46.662 0.000	47.266 0.000	47.875 0.000	48.490 0.000	49.109 0.000	49.733 0.000	50.361 0.000	50.994 0.000	51.631 0.000	52.272 0.000	52.917 0.000	53.565 0.000	54.218 0.000	54.873 0.000	55.532 0.000	56.195 0.000	56.860 0.000	57.528 0.000	58.200 0.000	58.874 0.000	59.550 0.000	60.230 0.000	60.912 0.000	61.596 0.000	62.283 0.000	62.972 0.000	63.663 0.000
	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
	48.645	48.626	48.624	48 638	48.667	48.713	48.774	48.851	48.944	49.052	49 176	49.316	49.471	49.641	49.826	50.025	50.240	50.469	50.712	50.969	51.240	51.525	51 823	52 134	52 458	52.795	53.145	53.506	53 880	54.265	54.662	55.070	55.489
	43.159 0.000	43.727 0.000	44.302 0.000	44.883 0.000	45.470 0.000	46.063 0.000	46.662 0.000	47.266 0.000	47.875 0.000	48.490 0.000	49.109 0.000	49.733 0.000	50.361 0.000	50.994 0.000	51.631 0.000	52.272 0.000	52.917 0.000	53.565 0.000	54.218 0.000	54.873 0.000	55.532 0.000	56.195 0.000	56.860 0.000	57.528 0.000	58.200 0.000	58.874 0.000	59.550 0.000	60.230 0.000	60.912 0.000	61.596 0.000	62.283 0.000	62.972 0.000	63.663 0.000
	10030.000	10030.000	10030.000	10030 000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030 000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030 000	10030.000	10030.000	10030.000	10030 000	10030.000	10030.000	10030.000	10030.000	10030 000	10030 000	10030.000	10030 000	10030.000
	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944
	90.000	90.000	90.000	000 06	90.000	90.000	90.000	90.000	90.000	90.000	000 06	90.000	90.000	90.000	90.000	90.000	90.000	90.000	90.000	000.06	90.000	90.000	000 06	000 06	000 06	90.000	90.000	90.000	000 06	000 06	90.000	000.06	90.000
11/2/23, 12:10 PM	12500.000	12600,000	12700.000	12800.000	12900.000	13000,000	13100.000	13200.000	13300.000	13400.000	13500.000	13600,000	13700.000	13800.000	13900.000	14000.000	14100.000	14200.000	14300.000	14400,000	14500.000	14600,000	14700.000	14800,000	14900.000	15000,000	15100.000	15200.000	15300.000	15400.000	15500.000	15600,000	15700.000
-	eleas	ed t	o In	iagi	ng:	2/29	0/202	24 1	2:47	7:00	PM	r																					

	111.123 MWD+IFR1+MS	111.391 MWD+IFR1+MS	111.711 MWD+IFR1+MS	112.091 MWD+IFR1+MS	112.544 MWD+IFR1+MS	113.083 MWD+IFR1+MS	113.725 MWD+IFR1+MS	114.496 MWD+IFR1+MS	115.425 MWD+IFR1+MS	116.552 MWD+IFR1+MS	117.932 MWD+IFR1+MS	119.637 MWD+IFR1+MS	121.761 MWD+IFR1+MS	124.428 MWD+IFR1+MS	127.782 MWD+IFR1+MS	131.966 MWD+IFR1+MS	-42.955 MWD+IFR1+MS	-37.112 MWD+IFR1+MS	-30.914 MWD+IFR1+MS	-24.937 MWD+IFR1+MS	-19.648 MWD+IFR1+MS	-15.242 MWD+IFR1+MS	-11.688 MWD+IFR1+MS	-8.854 MWD+IFR1+MS	-6.592 MWD+IFR1+MS	-4.772 MWD+IFR1+MS	-3.293 MWD+IFR1+MS	-2.079 MWD+IFR1+MS	-1.070 MWD+IFR1+MS	-0.225 MWD+IFR1+MS	0.490 MWD+IFR1+MS	1.099 MWD+IFR1+MS	1.623 MWD+IFR1+MS
	54.438	54.921	55.411	55.909	56.413	56.922	57.437	27.957	58.479	59.004	59.528	090'09	995.09	61.071	61.559	62.019	62.439	62.806	63.111	63,351	63.532	63,668	63.769	63.845	63.903	63.949	63.985	64.015	64.040	64.061	64.080	64.096	64.111
	64.928	64.911	64.896	64.884	64.874	64.868	64.865	64.867	64.874	64.888	64.909	64.941	64.986	65.050	65.139	65.262	65.432	65.662	65.961	66.332	29.799	67.254	67.782	68.340	68.922	69.522	70.136	70.763	71.400	72.045	72.698	73,358	74.025
oort	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Well Plan Report	64.357 0.000	65.052 0.000	65.750 0.000	66.449 0.000	67.150 0.000	67.854 0.000	68.559 0.000	69.265 0.000	69.974 0.000	70.683 0.000	71.395 0.000	72.108 0.000	72.823 0.000	73.538 0.000	74.256 0.000	74.974 0.000	75.694 0.000	76.416 0.000	77.138 0.000	77.862 0.000	78.587 0.000	79.313 0.000	80.040 0.000	80.768 0.000	81.497 0.000	82.228 0.000	82.959 0.000	83.691 0.000	84.424 0.000	85.159 0.000	85.894 0.000	86.629 0.000	87.366 0.000
	0.000	000'0	0.000	000'0	0.000	0.000	0.000	0.000	0.000	0.000	000.0	000'0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	000'0	0.000	0.000	0.000	000.0	0.000	0.000	0.000
	55.919	56,359	56.810	57.270	57.740	58.220	58.709	59.207	59.714	60.230	60.754	61.286	61.827	62.374	62.930	63.493	64.063	64.640	65.224	65.814	66.411	67.014	67.623	68.238	68.829	69.486	70.118	70.755	71.398	72.045	72.698	73.355	74.017
	64.357 0.000	65.052 0.000	65.750 0.000	66.449 0.000	67.150 0.000	67.854 0.000	68.559 0.000	69.265 0.000	69.974 0.000	70.683 0.000	71.395 0.000	72.108 0.000	72.823 0.000	73.538 0.000	74.256 0.000	74.974 0.000	75.694 0.000	76.416 0.000	77.138 0.000	77.862 0.000	78.587 0.000	79.313 0.000	80.040 0.000	80.768 0.000	81.497 0.000	82.228 0.000	82.959 0.000	83.691 0.000	84.424 0.000	85.159 0.000	85.894 0.000	86.629 0.000	87.366 0.000
	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030,000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030,000	10030.000
	359.944	359 944	359.944	359 944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359 944	359.944	359.944	359.944	359.944	359 944	359 944	359.944	359.944	359.944	359 944	359.944	359 944	359.944	359 944	359.944	359.944	359 944	359.944	359.944	359.944	359.944
	000 06	000 06	90.000	000 06	90.000	90.000	90.000	000 06	90.000	000.06	90.000	000 06	000 06	000'06	000.06	90.000	000 06	000 06	90.000	000'06	90.000	000 06	90.000	000 06	90.000	000 06	90.000	90.000	000 06	90.000	90.000	000 06	90.000
11/2/23, 12:10 PM	15800.000	15900.000	16000.000	16100.000	16200.000	16300.000	16400.000	16500.000	16600.000	16700.000	16800.000	16900.000	17000.000	17100.000	17200.000	17300.000	17400.000	17500.000	17600.000	17700.000	17800.000	17900,000	18000.000	18100.000	18200.000	18300.000	18400.000	18500.000	18600.000	18700.000	18800.000	18900,000	19000.000
	eleas	ed t	o In	agi	ng:	2/29	0/202	24 1.	2:47	7:00	PM	,																					

	2.075 MWD+IFR1+MS	2.468 MWD+IFR1+MS	2.811 MWD+IFR1+MS	3.112 MWD+IFR1+MS	3.378 MWD+IFR1+MS	3.612 MWD+IFR1+MS	3.819 MWD+IFR1+MS	4.004 MWD+IFR1+MS	4.168 MWD+IFR1+MS	4.314 MWD+IFR1+MS	4.444 MWD+IFR1+MS	4.561 MWD+IFR1+MS	4.665 MWD+IFR1+MS	4.759 MWD+IFR1+MS	4.842 MWD+IFR1+MS	4.917 MWD+IFR1+MS	4.984 MWD+IFR1+MS	5.043 MWD+IFR1+MS	5.097 MWD+IFR1+MS	5.144 MWD+IFR1+MS	5.186 MWD+IFR1+MS	5.223 MWD+IFR1+MS	5.256 MWD+IFR1+MS	5.285 MWD+IFR1+MS	5.310 MWD+IFR1+MS	5.332 MWD+IFR1+MS	5.351 MWD+IFR1+MS	5.367 MWD+IFR1+MS	5.380 MWD+IFR1+MS	5.391 MWD+IFR1+MS	5.400 MWD+IFR1+MS	5.406 MWD+IFR1+MS	5.409 MWD+IFR1+MS
	64.125	64.137	64.149	64 161	64 173	64 184	64.195	64.206	64.217	64.229	64.241	64.252	64.265	64.277	64.290	64.303	64.316	64.330	64.345	64.359	64.374	64.390	64.406	64.422	64.439	64.456	64.474	64.492	64.511	64.530	64.549	64.569	64.580
	74 697	75 374	76.056	76 743	77 435	78 131	78.831	79.534	80.242	80.952	81.667	82.385	83 105	83.829	84.556	85 286	86.019	86.754	87.492	88.233	88.976	89.722	90.470	91.220	91.973	92.728	93 484	94 243	95.004	95.767	96.532	97.299	969.76
oort	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Well Plan Report	88.104 0.000	88.842 0.000	89.581 0.000	90.321 0.000	91.062 0.000	91.803 0.000	92.545 0.000	93.288 0.000	94.032 0.000	94.776 0.000	95.521 0.000	96.266 0.000	97.012 0.000	97.759 0.000	98.506 0.000	99.254 0.000	100.003 0.000	100.751 0.000	101.501 0.000	102.251 0.000	103.002 0.000	103.753 0.000	104.504 0.000	105.256 0.000	106.009 0.000	106.762 0.000	107.515 0.000	108.269 0.000	109.024 0.000	109.778 0.000	110.533 0.000	111.289 0.000	111.680 0.000
	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0000	0.000
	74.683	75,354	76.029	76.708	77.391	78.079	78.770	79.465	80.163	80.865	81.571	82.280	82.992	83.708	84.426	85.148	85.872	86.600	87.330	88.063	88.799	89.537	90.278	91.022	91.768	92.516	93.267	94.019	94.774	95.532	96.291	97.052	97.447
	88.104 0.000	88.842 0.000	89.581 0.000	90.321 0.000	91.062 0.000	91.803 0.000	92.545 0.000	93.288 0.000	94.032 0.000	94.776 0.000	95.521 0.000	96.266 0.000	97.012 0.000	97.759 0.000	98.506 0.000	99.254 0.000	100.003 0.000	100.751 0.000	101.501 0.000	102.251 0.000	103.002 0.000	103.753 0.000	104.504 0.000	105.256 0.000	106.009 0.000	106.762 0.000	107.515 0.000	108.269 0.000	109.024 0.000	109.778 0.000	110.533 0.000	111.289 0.000	111.680 0.000
	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000	10030.000
	359.944	359 944	359.944	359 944	359 944	359 944	359.944	359.944	359.944	359.944	359.944	359.944	359 944	359.944	359.944	359 944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359.944	359 944	359 944	359.944	359 944	359.944	359.944	359 944	359.944
	000 06	000 06	90.000	000 06	000 06	000 06	90.000	90.000	90.000	000 06	90.000	000.06	000 06	90.000	000.06	000 06	90.000	90.000	90.000	000'06	90.000	000.06	90.000	000.06	90.000	000 06	000 06	000 06	000 06	000.06	000 06	000'06	90.000
11/2/23, 12:10 PM	19100.000	19200.000	19300.000	19400.000	19500.000	19600.000	19700.000	19800.000	19900.000	20000.000	20100.000	20200,000	20300.000	20400.000	20500,000	20600.000	20700.000	20800.000	20900.000	21000,000	21100.000	21200.000	21300.000	21400.000	21500.000	21600.000	21700.000	21800.000	21900.000	22000.000	22100.000	22200.000	22251.864
	leas	ed t	o In	agi	ng:	2/29	0/202	24 1	2:47	7:00	PM																						

'23, 12:10 PM								We	Well Plan Report	+-			
22300.000	90.000		359.944 10030.000	112.044 0.000		97.813	0.000	112.044 0.000	0.000	0.000	98.065	64.589	5.412 MWD+IFR1+MS
22350.611	900'06		359.944 10030.000	112.426 0.000		98.198	0.000	0.000 112.426 0.000	0.000	0.000	98.454	64.600	5.414 MWD+IFR1+MS
lan Targets		_	PLU 29-20 151H	Ŧ									
			Me	Measured Depth	Ë		Grid	Grid Northing	_	Grid Easting	sting	TVD MSL Target Shape	rget Shape
arget Name				#)	(£)			(ft)	-		(ft)	(ft)	
TP 4				12277.52	25		4	401485.10		668401.80	01.80	6633.00 RECTANGLE	CTANGLE
TP 4				22251.86	92		4	411459.40		668392.00	92.00	6633.00 RECTANGLE	CTANGLE
HL 4				22351.17			4	411558.40	-	668391.40	91.40	6633.00 RECTANGLE	CTANGLE



District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 313469

CONDITIONS

Operator:	OGRID:
XTO PERMIAN OPERATING LLC.	373075
6401 HOLIDAY HILL ROAD	Action Number:
MIDLAND, TX 79707	313469
	Action Type:
	[C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By		Condition Date
ward.rikala	All original COA's still apply. Additionally, if cement is not circulated to surface during cementing operations, then a CBL is required.	2/29/2024