

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
August 1, 2011

Permit 359736

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

1. Operator Name and Address Silverback Operating II, LLC 19707 IH10 West, Suite 201 San Antonio, TX 78256		2. OGRID Number 330968
		3. API Number 30-015-54796
4. Property Code 332021	5. Property Name State K Com	6. Well No. 102H

**7. Surface Location**

UL - Lot M	Section 27	Township 19S	Range 25E	Lot Idn	Feet From 1117	N/S Line S	Feet From 517	E/W Line W	County Eddy
---------------	---------------	-----------------	--------------	---------	-------------------	---------------	------------------	---------------	----------------

**8. Proposed Bottom Hole Location**

UL - Lot M	Section 28	Township 19S	Range 25E	Lot Idn M	Feet From 1320	N/S Line S	Feet From 100	E/W Line W	County Eddy
---------------	---------------	-----------------	--------------	--------------	-------------------	---------------	------------------	---------------	----------------

**9. Pool Information**

N. SEVEN RIVERS; GLORIETA-YESO	97565
--------------------------------	-------

**Additional Well Information**

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3465
16. Multiple N	17. Proposed Depth 8438	18. Formation Yeso	19. Contractor	20. Spud Date 3/5/2024
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	12.25	9.625	36	1209	269	0
Prod	8.75	7	32	3316	160	0
Prod	8.75	5.5	20	8438	1598	2000

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	5000	5000	Shaffer

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief. <b>I further certify I have complied with 19.15.14.9 (A) NMAC <input checked="" type="checkbox"/> and/or 19.15.14.9 (B) NMAC <input checked="" type="checkbox"/> if applicable.</b>  Signature: Printed Name: Electronically filed by Matthew Alley Title: Chief Financial Officer Email Address: malley@silverbackexp.com Date: 2/15/2024	<b>OIL CONSERVATION DIVISION</b>  Approved By: Ward Rikala Title: Approved Date: 2/29/2024 Expiration Date: 2/28/2026 Conditions of Approval Attached
Phone: 303-513-0990	

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office  
☐ AMENDED REPORT

## WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-015 -54796	<sup>2</sup> Pool Code 97565	<sup>3</sup> Pool Name N. SEVEN RIVERS, GLORIETA-YESO
<sup>4</sup> Property Code 332021	<sup>5</sup> Property Name STATE K COM	<sup>6</sup> Well Number 102H
<sup>7</sup> OGRID No. 330968	<sup>8</sup> Operator Name SILVERBACK OPERATING II, LLC	<sup>9</sup> Elevation 3,465'

<sup>10</sup> Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	27	19-S	25-E		1,117'	SOUTH	517'	WEST	EDDY

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	28	19-S	25-E		1,320'	SOUTH	100'	WEST	EDDY

<sup>12</sup> Dedicated Acres 320	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<sup>17</sup> OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Fatma Abdallah

02/08/2024

Signature

Date

Fatma Abdallah

Printed Name

fabdallah@silverbackexp.com

E-mail Address

<sup>18</sup> SURVEYOR  
CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.


2/8/24

Date of Survey

Signature and Seal of Professional Surveyor

20450

Certificate Number



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

Form APD Conditions  
Permit 359736

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address: Silverback Operating II, LLC [330968] 19707 IH10 West, Suite 201 San Antonio, TX 78256	API Number: 30-015-54796
	Well: State K Com #102H

OCD Reviewer	Condition
ward.rikala	Notify OCD 24 hours prior to casing & cement
ward.rikala	Will require a File As Drilled C-102 and a Directional Survey with the C-104
ward.rikala	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
ward.rikala	Cement is required to circulate on both surface and intermediate1 strings of casing
ward.rikala	If cement does not circulate on any string, a CBL is required for that string of casing
ward.rikala	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
ward.rikala	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud

State of New Mexico  
Energy, Minerals and Natural Resources Department

Submit Electronically  
Via E-permitting

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

## NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

### **Section 1 – Plan Description**

**Effective May 25, 2021**

**I. Operator:** Silverback Operating II, LLC. **OGRID:** 330968 **Date:** 02 / 14 / 2024

**II. Type:** ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: \_\_\_\_\_

**III. Well(s):** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
See attached						

**IV. Central Delivery Point Name:** State K Com CTB [See 19.15.27.9(D)(1) NMAC]

**V. Anticipated Schedule:** Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
See attached						

**VI. Separation Equipment:** ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

**VII. Operational Practices:** ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

**VIII. Best Management Practices:** ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

**Section 2 – Enhanced Plan****EFFECTIVE APRIL 1, 2022**

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☐ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

**IX. Anticipated Natural Gas Production:**

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF
See attached			

**X. Natural Gas Gathering System (NGGS):**

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in
See attached				

**XI. Map.** ☒ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

**XII. Line Capacity.** The natural gas gathering system ☒ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

**XIII. Line Pressure.** Operator ☒ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

**XIV. Confidentiality:** ☒ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

### **Section 3 - Certifications**

**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

***If Operator checks this box, Operator will select one of the following:***

**Well Shut-In.** ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

**Venting and Flaring Plan.** ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

### **Section 4 - Notices**

1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.


Signature: <i>Fatma Abdallah</i>
Printed Name: Fatma Abdallah
Title: Regulatory Manager
E-mail Address: fabdallah@silverbackexp.com
Date: 02/14/2024
Phone: 210-585-3316
<b>OIL CONSERVATION DIVISION</b> <b>(Only applicable when submitted as a standalone form)</b>
Approved By:
Title:
Approval Date:
Conditions of Approval:

### Section 1-Plan Description -III. Wells

[illegible]




# Silverback Exploration: State K



## Legend

- State K
- Enterprise Sweet
- P66 Gas Line
- Durango Gas Line
- Centurion Oil Pipeline
- Water Line



## Separation Equipment

Silverback Operating II (LLC) has sampled existing producing wells and performed laboratory testing to determine composition. Performance of existing producing wells was analyzed to predict expected production volumes including a low probably, high volume production case (approximately 75% higher than type curve or most likely amount of production). Production composition and the volumes were utilized as inputs to a process model which predicts relative amounts of gas, oil and water throughout the process. The high volume case was used to size equipment, piping and instrumentation. Equipment sizing is based on drop settlement and limits the amount of carry over to the gas phase.

Each well has a dedicated 3 phase separator and gas from that separator is taken directly to gas sales. Facility piping and pipeline were sized to allow peak volumes to flow with minimal pressure loss and deliver to midstream gatherer at an acceptable pressure. Water is conveyed directly to tankage.

Oil from 3 phase separators is comingled and conveyed to a heated separator for enhanced liquid-liquid separation and degassing. Vapors from the heater treater are routed to flare. Oil and water storage tanks vapor outlets are common and utilize a closed vent vapor system to ensure all working & breathing and flashing losses are routed to the flare which is sized to accommodate peak expected production volume. Flash volumes were estimated using the high volume case and process modeling software.

## Operational Practices

Silverback Operating II, LLC will ensure pipeline connectivity before producing hydrocarbons and will operate a closed vent vapor capture system that is designed to capture all associated and evolved gas during normal operation. Venting will only occur during maintenance activities or equipment failure or upset. Silverback may utilize the following from list A-I of Section 3 for its operations to minimize flaring:

- Power generation on lease – Natural gas driven gen set to produce power required to run supply well pad electrical loads
- Compression on lease – gas lift or gas compression as required
- Liquids removal on lease – gas pressure will be used to convey fluids as needed

## **Best Management Practices**

Silverback utilizes automate engineering controls included in facility design to minimize venting and flaring. Additionally, operational best practices support minimization of flare and venting as described below.

If the main gas outlet becomes unavailable and pressure increases on the outlet sales line, produced gas will be routed directly to the facility flare. The facility control system will alert personnel to the need for maintenance and appropriate response to the temporary flaring event.


The facility design includes a closed vent vapor capture system to route flash or evolved from the heater treater and tanks to the flare.

For maintenance activities, Silverback will utilize the facility flare to blowdown equipment and piping whenever practical to minimize venting





Project: EDDY COUNTY, NM (NAD 83 - NME)  
Site: State K Com  
Well: 102H  
Wellbore: OH  
Design: Plan 1r0



WELL DETAILS: 102H

Rig Name:		TBD	RKB = 20' @ 3485.00usft (TBD)		Ground Level: 3465.00	
+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	
0.00	0.00	592058.70	496356.61	32.6275342	-104.4794424	

SECTION DETAILS





Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	Vsect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	
3	871.61	11.15	52.72	869.27	21.83	28.68	3.00	-28.65	
4	1998.77	11.15	52.72	1975.16	153.83	202.09	0.00	-201.93	
5	2766.07	60.00	270.06	2623.90	205.52	-109.85	9.00	110.07	
6	2966.07	60.00	270.06	2723.90	205.70	-283.06	0.00	283.27	
7	3314.94	91.40	270.06	2809.00	206.05	-616.90	9.00	617.12	STATE K 102H FTP
8	8437.37	91.40	270.06	2684.00	211.40	-5737.80	0.00	5738.02	STATE K 102H LTP/BHL

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
STATE K 102H SHL	0.00	0.00	0.00	592058.70	496356.61	32.6275342	-104.4794424
STATE K 102H KOP @ 1998.77' MD	1975.16	153.83	202.09	592212.53	496558.70	32.6279578	-104.4787866
STATE K 102H MAX BACKBUILD	2075.35	165.28	209.68	592223.98	496566.29	32.6279893	-104.4787620
STATE K 102H LTP/BHL	2684.00	211.40	-5737.80	592270.10	490618.81	32.6280922	-104.4980812
STATE K 102H FTP	2809.00	206.05	-616.90	592264.75	495739.71	32.6280982	-104.4814472

PROJECT DETAILS: EDDY COUNTY, NM (NAD 83 - NME)

Geodetic System: US State Plane 1983  
Datum: North American Datum 1983  
Ellipsoid: GRS 1980  
Zone: New Mexico Eastern Zone  
System Datum: Mean Sea Level



\*\*\*Note: this document is provided for information purposes only. Prototype Well Planning LLC, it's employees, and agents make no guarantee or warranty, expressed or implied, as to the accuracy of this electronic file. The data included here and may be subject to error, while corruption, change, alteration, or update without any notice to the user. Prototype Well Planning LLC, it's employees, and it's agents assume no responsibility, expressed or implied, for any damages incurred either directly or indirectly by the use of this document. The users agree to the above specified terms of this document and agrees to verify the data enclosed to ascertain its accuracy for their intended use. If these conditions are unacceptable, user shall discard this document.\*\*\*



# **SILVERBACK EXPLORATION**

**EDDY COUNTY, NM (NAD 83 - NME)**

**State K Com**

**102H**

**OH**

**Plan: Plan 1r0**

## **Standard Planning Report**

**08 February, 2024**





Planning Report

Database:	EDM 5000.1.13 Single User Db	Local Co-ordinate Reference:	Well 102H
Company:	SILVERBACK EXPLORATION	TVD Reference:	RKB = 20' @ 3485.00usft (TBD)
Project:	EDDY COUNTY, NM (NAD 83 - NME)	MD Reference:	RKB = 20' @ 3485.00usft (TBD)
Site:	State K Com	North Reference:	Grid
Well:	102H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan 1r0		

Project	EDDY COUNTY, NM (NAD 83 - NME)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site		State K Com				
Site Position:		Northing:	592,018.70 usft	Latitude:	32.6274243	
From:	Map	Easting:	496,356.59 usft	Longitude:	-104.4794422	
Position Uncertainty:		0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-0.079 °

Well	102H					
Well Position	+N/-S	40.00 usft	Northing:	592,058.70 usft	Latitude:	32.6275342
	+E/-W	0.02 usft	Easting:	496,356.61 usft	Longitude:	-104.4794424
Position Uncertainty		0.00 usft	Wellhead Elevation:	0.00 usft	Ground Level:	3,465.00 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	02/05/24	6.686	60.047	47,363

Design	Plan 1r0			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	270.06

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.000	
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.000	
871.61	11.15	52.72	869.27	21.83	28.68	3.00	3.00	0.00	52.721	
1,998.77	11.15	52.72	1,975.16	153.83	202.09	0.00	0.00	0.00	0.000	
2,766.07	60.00	270.06	2,623.90	205.52	-109.85	9.00	6.37	-18.59	-145.777	
2,966.07	60.00	270.06	2,723.90	205.70	-283.06	0.00	0.00	0.00	0.000	
3,314.94	91.40	270.06	2,809.00	206.05	-616.90	9.00	9.00	0.00	0.000	STATE K 102H FTF
8,437.37	91.40	270.06	2,684.00	211.40	-5,737.80	0.00	0.00	0.00	0.000	STATE K 102H LTP



## Planning Report

<b>Database:</b>	EDM 5000.1.13 Single User Db	<b>Local Co-ordinate Reference:</b>	Well 102H
<b>Company:</b>	SILVERBACK EXPLORATION	<b>TVD Reference:</b>	RKB = 20' @ 3485.00usft (TBD)
<b>Project:</b>	EDDY COUNTY, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3485.00usft (TBD)
<b>Site:</b>	State K Com	<b>North Reference:</b>	Grid
<b>Well:</b>	102H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OH		
<b>Design:</b>	Plan 1r0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
<b>STATE K 102H SHL</b>									
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	3.00	52.72	599.95	1.59	2.08	-2.08	3.00	3.00	0.00
700.00	6.00	52.72	699.63	6.34	8.32	-8.32	3.00	3.00	0.00
800.00	9.00	52.72	798.77	14.24	18.71	-18.69	3.00	3.00	0.00
871.61	11.15	52.72	869.27	21.83	28.68	-28.65	3.00	3.00	0.00
900.00	11.15	52.72	897.12	25.15	33.04	-33.02	0.00	0.00	0.00
1,000.00	11.15	52.72	995.24	36.86	48.43	-48.39	0.00	0.00	0.00
1,100.00	11.15	52.72	1,093.35	48.58	63.81	-63.76	0.00	0.00	0.00
1,200.00	11.15	52.72	1,191.46	60.29	79.20	-79.14	0.00	0.00	0.00
1,300.00	11.15	52.72	1,289.58	72.00	94.58	-94.51	0.00	0.00	0.00
1,400.00	11.15	52.72	1,387.69	83.71	109.97	-109.88	0.00	0.00	0.00
1,500.00	11.15	52.72	1,485.80	95.42	125.35	-125.25	0.00	0.00	0.00
1,600.00	11.15	52.72	1,583.91	107.13	140.74	-140.63	0.00	0.00	0.00
1,700.00	11.15	52.72	1,682.03	118.84	156.12	-156.00	0.00	0.00	0.00
1,800.00	11.15	52.72	1,780.14	130.55	171.51	-171.37	0.00	0.00	0.00
1,900.00	11.15	52.72	1,878.25	142.26	186.89	-186.74	0.00	0.00	0.00
1,998.77	11.15	52.72	1,975.16	153.83	202.09	-201.93	0.00	0.00	0.00
<b>STATE K 102H KOP @ 1998.77' MD</b>									
2,000.00	11.06	52.40	1,976.37	153.97	202.28	-202.11	9.00	-7.43	-26.39
2,050.00	7.78	33.20	2,025.70	159.73	207.93	-207.76	9.00	-6.56	-38.40
2,100.00	6.24	357.76	2,075.35	165.28	209.68	-209.50	9.00	-3.06	-70.87
<b>STATE K 102H MAX BACKBUILD</b>									
2,150.00	7.61	321.43	2,125.00	170.59	207.50	-207.33	9.00	2.73	-72.67
2,200.00	10.82	301.35	2,174.36	175.62	201.43	-201.24	9.00	6.43	-40.15
2,250.00	14.72	291.05	2,223.12	180.35	191.49	-191.30	9.00	7.80	-20.61
2,300.00	18.88	285.09	2,270.98	184.74	177.74	-177.55	9.00	8.33	-11.91
2,350.00	23.17	281.25	2,317.65	188.76	160.27	-160.07	9.00	8.57	-7.68
2,400.00	27.52	278.56	2,362.82	192.40	139.19	-138.99	9.00	8.70	-5.38
2,450.00	31.91	276.56	2,406.24	195.63	114.63	-114.42	9.00	8.78	-4.00
2,500.00	36.32	275.00	2,447.62	198.43	86.73	-86.53	9.00	8.83	-3.12
2,550.00	40.75	273.73	2,486.72	200.79	55.68	-55.47	9.00	8.86	-2.53
2,600.00	45.20	272.68	2,523.30	202.68	21.66	-21.45	9.00	8.88	-2.11
2,650.00	49.65	271.77	2,557.12	204.10	-15.12	15.34	9.00	8.90	-1.81
2,700.00	54.10	270.98	2,587.98	205.03	-54.44	54.65	9.00	8.91	-1.58
2,750.00	58.57	270.27	2,615.69	205.48	-96.04	96.25	9.00	8.92	-1.41
2,766.07	60.00	270.06	2,623.90	205.52	-109.85	110.07	9.00	8.93	-1.32
2,800.00	60.00	270.06	2,640.86	205.55	-139.24	139.45	0.00	0.00	0.00
2,900.00	60.00	270.06	2,690.86	205.64	-225.84	226.05	0.00	0.00	0.00
2,966.07	60.00	270.06	2,723.90	205.70	-283.06	283.27	0.00	0.00	0.00
3,000.00	63.05	270.06	2,740.07	205.73	-312.88	313.09	9.00	9.00	0.00
3,050.00	67.55	270.06	2,760.96	205.78	-358.29	358.51	9.00	9.00	0.00
3,100.00	72.05	270.06	2,778.22	205.83	-405.21	405.42	9.00	9.00	0.00
3,150.00	76.55	270.06	2,791.74	205.88	-453.33	453.55	9.00	9.00	0.00
3,200.00	81.05	270.06	2,801.45	205.93	-502.37	502.58	9.00	9.00	0.00
3,250.00	85.55	270.06	2,807.27	205.98	-552.01	552.23	9.00	9.00	0.00
3,300.00	90.05	270.06	2,809.19	206.03	-601.96	602.18	9.00	9.00	0.00
3,314.94	91.40	270.06	2,809.00	206.05	-616.90	617.12	9.00	9.00	0.00
<b>STATE K 102H FTP</b>									



## Planning Report

<b>Database:</b>	EDM 5000.1.13 Single User Db	<b>Local Co-ordinate Reference:</b>	Well 102H
<b>Company:</b>	SILVERBACK EXPLORATION	<b>TVD Reference:</b>	RKB = 20' @ 3485.00usft (TBD)
<b>Project:</b>	EDDY COUNTY, NM (NAD 83 - NME)	<b>MD Reference:</b>	RKB = 20' @ 3485.00usft (TBD)
<b>Site:</b>	State K Com	<b>North Reference:</b>	Grid
<b>Well:</b>	102H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	OH		
<b>Design:</b>	Plan 1r0		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,400.00	91.40	270.06	2,806.92	206.14	-701.94	702.15	0.00	0.00	0.00
3,500.00	91.40	270.06	2,804.48	206.24	-801.91	802.12	0.00	0.00	0.00
3,600.00	91.40	270.06	2,802.04	206.35	-901.88	902.09	0.00	0.00	0.00
3,700.00	91.40	270.06	2,799.60	206.45	-1,001.85	1,002.06	0.00	0.00	0.00
3,800.00	91.40	270.06	2,797.16	206.56	-1,101.82	1,102.03	0.00	0.00	0.00
3,900.00	91.40	270.06	2,794.72	206.66	-1,201.79	1,202.00	0.00	0.00	0.00
4,000.00	91.40	270.06	2,792.28	206.77	-1,301.76	1,301.97	0.00	0.00	0.00
4,100.00	91.40	270.06	2,789.84	206.87	-1,401.73	1,401.94	0.00	0.00	0.00
4,200.00	91.40	270.06	2,787.40	206.97	-1,501.70	1,501.91	0.00	0.00	0.00
4,300.00	91.40	270.06	2,784.96	207.08	-1,601.67	1,601.88	0.00	0.00	0.00
4,400.00	91.40	270.06	2,782.52	207.18	-1,701.64	1,701.85	0.00	0.00	0.00
4,500.00	91.40	270.06	2,780.08	207.29	-1,801.61	1,801.82	0.00	0.00	0.00
4,600.00	91.40	270.06	2,777.64	207.39	-1,901.58	1,901.79	0.00	0.00	0.00
4,700.00	91.40	270.06	2,775.20	207.50	-2,001.55	2,001.76	0.00	0.00	0.00
4,800.00	91.40	270.06	2,772.76	207.60	-2,101.52	2,101.73	0.00	0.00	0.00
4,900.00	91.40	270.06	2,770.32	207.71	-2,201.49	2,201.70	0.00	0.00	0.00
5,000.00	91.40	270.06	2,767.88	207.81	-2,301.46	2,301.67	0.00	0.00	0.00
5,100.00	91.40	270.06	2,765.44	207.91	-2,401.43	2,401.65	0.00	0.00	0.00
5,200.00	91.40	270.06	2,763.00	208.02	-2,501.40	2,501.62	0.00	0.00	0.00
5,300.00	91.40	270.06	2,760.56	208.12	-2,601.37	2,601.59	0.00	0.00	0.00
5,400.00	91.40	270.06	2,758.12	208.23	-2,701.34	2,701.56	0.00	0.00	0.00
5,500.00	91.40	270.06	2,755.68	208.33	-2,801.31	2,801.53	0.00	0.00	0.00
5,600.00	91.40	270.06	2,753.24	208.44	-2,901.28	2,901.50	0.00	0.00	0.00
5,700.00	91.40	270.06	2,750.80	208.54	-3,001.25	3,001.47	0.00	0.00	0.00
5,800.00	91.40	270.06	2,748.36	208.65	-3,101.22	3,101.44	0.00	0.00	0.00
5,900.00	91.40	270.06	2,745.92	208.75	-3,201.19	3,201.41	0.00	0.00	0.00
6,000.00	91.40	270.06	2,743.48	208.85	-3,301.16	3,301.38	0.00	0.00	0.00
6,100.00	91.40	270.06	2,741.04	208.96	-3,401.13	3,401.35	0.00	0.00	0.00
6,200.00	91.40	270.06	2,738.60	209.06	-3,501.10	3,501.32	0.00	0.00	0.00
6,300.00	91.40	270.06	2,736.16	209.17	-3,601.07	3,601.29	0.00	0.00	0.00
6,400.00	91.40	270.06	2,733.72	209.27	-3,701.04	3,701.26	0.00	0.00	0.00
6,500.00	91.40	270.06	2,731.28	209.38	-3,801.01	3,801.23	0.00	0.00	0.00
6,600.00	91.40	270.06	2,728.84	209.48	-3,900.98	3,901.20	0.00	0.00	0.00
6,700.00	91.40	270.06	2,726.40	209.59	-4,000.95	4,001.17	0.00	0.00	0.00
6,800.00	91.40	270.06	2,723.96	209.69	-4,100.92	4,101.14	0.00	0.00	0.00
6,900.00	91.40	270.06	2,721.52	209.79	-4,200.89	4,201.11	0.00	0.00	0.00
7,000.00	91.40	270.06	2,719.08	209.90	-4,300.86	4,301.08	0.00	0.00	0.00
7,100.00	91.40	270.06	2,716.64	210.00	-4,400.83	4,401.05	0.00	0.00	0.00
7,200.00	91.40	270.06	2,714.19	210.11	-4,500.80	4,501.02	0.00	0.00	0.00
7,300.00	91.40	270.06	2,711.75	210.21	-4,600.77	4,600.99	0.00	0.00	0.00
7,400.00	91.40	270.06	2,709.31	210.32	-4,700.74	4,700.96	0.00	0.00	0.00
7,500.00	91.40	270.06	2,706.87	210.42	-4,800.71	4,800.93	0.00	0.00	0.00
7,600.00	91.40	270.06	2,704.43	210.53	-4,900.68	4,900.90	0.00	0.00	0.00
7,700.00	91.40	270.06	2,701.99	210.63	-5,000.65	5,000.87	0.00	0.00	0.00
7,800.00	91.40	270.06	2,699.55	210.73	-5,100.62	5,100.84	0.00	0.00	0.00
7,900.00	91.40	270.06	2,697.11	210.84	-5,200.59	5,200.81	0.00	0.00	0.00
8,000.00	91.40	270.06	2,694.67	210.94	-5,300.56	5,300.78	0.00	0.00	0.00
8,100.00	91.40	270.06	2,692.23	211.05	-5,400.53	5,400.75	0.00	0.00	0.00
8,200.00	91.40	270.06	2,689.79	211.15	-5,500.50	5,500.72	0.00	0.00	0.00
8,300.00	91.40	270.06	2,687.35	211.26	-5,600.47	5,600.69	0.00	0.00	0.00
8,400.00	91.40	270.06	2,684.91	211.36	-5,700.44	5,700.66	0.00	0.00	0.00
8,437.37	91.40	270.06	2,684.00	211.40	-5,737.80	5,738.02	0.00	0.00	0.00
STATE K 102H LTP/BHL									





Planning Report

Database:	EDM 5000.1.13 Single User Db	Local Co-ordinate Reference:	Well 102H
Company:	SILVERBACK EXPLORATION	TVD Reference:	RKB = 20' @ 3485.00usft (TBD)
Project:	EDDY COUNTY, NM (NAD 83 - NME)	MD Reference:	RKB = 20' @ 3485.00usft (TBD)
Site:	State K Com	North Reference:	Grid
Well:	102H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan 1r0		

Design Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
STATE K 102H SHL - plan hits target center - Point	0.00	360.00	0.00	0.00	0.00	592,058.70	496,356.61	32.6275342	-104.4794424
STATE K 102H KOP (C - plan hits target center - Point	0.00	360.00	1,975.16	153.83	202.09	592,212.53	496,558.70	32.6279578	-104.4787866
STATE K 102H MAX E - plan hits target center - Point	0.00	0.00	2,075.35	165.28	209.68	592,223.99	496,566.29	32.6279893	-104.4787620
STATE K 102H LTP/B - plan hits target center - Point	0.00	360.00	2,684.00	211.40	-5,737.80	592,270.10	490,618.81	32.6280922	-104.4980812
STATE K 102H FTP - plan hits target center - Point	0.00	360.00	2,809.00	206.05	-616.90	592,264.75	495,739.71	32.6280982	-104.4814471