ecenter by Copy to Appropriate District 4:13 PM	State of New Mexico	Form C-103 ¹ 6
Office District I – (575) 393-6161 Enc	ergy, Minerals and Natural Resources	Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240		WELL API NO.
District II – (575) 748-1283	L CONSERVATION DIVISION	30-015-40796
811 S. First St., Artesia, NM 88210 District III – (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410		STATE FEE
<u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
SUNDRY NOTICES AN	O REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO D		Kaiser 18 A
DIFFERENT RESERVOIR. USE "APPLICATION FO	OR PERMIT" (FORM C-101) FOR SUCH	8. Well Number
PROPOSALS.)		#15
1. Type of Well: Oil Well Gas Well	Other	
2. Name of Operator		9. OGRID Number
Riley Permian Operating Company LLC		372290 10. Pool name or Wildcat
3. Address of Operator 29 E. Reno Avenue Suite 500, Oklahoma (Site: OV 72104	Yeso
	ліу, ОК 73104 	Teso
4. Well Location		
Unit Letter A : 330	feet from the Nline and800	feet from the <u>E</u> line
Section 18 Tov	wnship 18S Range 27E	NMPM County Eddy
11. Ele	vation (Show whether DR, RKB, RT, GR, etc.	
	3292'	
		_
12 Check Appropri	ate Box to Indicate Nature of Notice,	Report or Other Data
12. Check Appropri	ate box to indicate Nature of Notice,	Report of Other Data
NOTICE OF INTENTION	ON TO: SUB	SEQUENT REPORT OF:
	AND ABANDON REMEDIAL WOR	
	GE PLANS COMMENCE DR	<u> </u>
	PLE COMPL CASING/CEMEN	
DOWNHOLE COMMINGLE	2.2 3 3 1 1 1 3 7 1 3 1 1 1 1 1 1 1 1 1 1 1	. 005
CLOSED-LOOP SYSTEM		
OTHER:	□ OTHER:	
		d give pertinent dates, including estimated date
	RULE 19.15.7.14 NMAC. For Multiple Con	
proposed completion or recompletion		inproved in the second or agrain of
respective semi-		
01/05/24 MIRU plugging equipment. 01/08/	24 Beld down well. Pumped 145 bbls brine	e H20 down csg, could not kill well. 01/09/24
Bled down well. Pumped 30 bbls Brine H20		
Circ'd hole w/ 60 bbls Brine H20. Pressure		
		v/ 20 bbls MLF. Spotted 25 sx class C cmt @
		igged down & moved off. 01/16/24 Moved in
backhoe and welder. Cut off well head & an		
		t. Backfilled cellar, cut off deadmen, cleaned
location, and moved off.		,
	F	
		Approved for plugging of well bore only. Liability under
	le de la companya de	ond is retained pending Location cleanup & receipt of
		C-103Q (Subsequent Report of Well Plugging) which may be found at OCD Web Page, OCD Permitting @
Spud Date:		vww.emnrd.state.nm.us
I hereby certify that the information above is t	rue and complete to the best of my knowledge	re and belief
Thereby certify that the information above is t	rue and complete to the best of my knowledg	e and benen.
SIGNATURE Spance Laird	TITLE EHS&R Manager	DATE_1/19/2024
- Justin Linder		
Type or print nameSpence Laird	E-mail address: spencelaird@ri	leypermian.com PHONE: 1-405-543-1411
For State Use Only		
APPROVED BY:	TITLE Staff Manager	DATE 3/8/24
Conditions of Approval (if any):		

an Operating Comp	any	Plugged
Abby @ BCM		
Kaiser 18 A	Well No.	#15
Red Lake; GL Yeso	API#:	30-015-40796
Eddy	Location:	Sec 18, T18S, R27E
NM	_	330 FNL & 800 FEL
10/27/2012	GL:	3292
	Abby @ BCM Kaiser 18 A Red Lake; GL Yeso Eddy NM	Kaiser 18 A Well No. Red Lake; GL Yeso API #: Eddy Location: NM

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surface Csg	8 5/8	J55	24#	424	12 1/4	300	0
Prod Csg	5 1/2	J55	17#	4,422	7 7/8	875	360

2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 1/2" CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 2800-3996	ate _	10/27/2012	GL: <u>32</u>	292				-	
Grbg 938 San Andres 1368 San Andres 2688 Yeso 2827 Tubb 4679 8 5/8 24# CSG @ 424 Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 475' to surface. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 '%" CIBP @ 2750', Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 ■ 104.3116837								Formation	Тор
San Andres 1168 Glorieta 2688 Yeso 2827 Tubb 4679 8 5/8 24# CSG @ 424 Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 475' to surface. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 ½" CIBP @ 2750', Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509', WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 28030-3400 1-04-3116837	_		_						
Spotted 25 sx class C cmt @ 988-735'.									
8 5/8 24# CSG @ 424 Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 988-735'. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 %" CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 3030-3400 32.4750855 Perfs @ 3030-3400									
8 5/8 24# CSG @ 424 Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 475' to surface. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 ½' CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 2800-2996 Perfs @ 3303-3400 - 104.3116837									
8 5/8 24# CSG @ 424 Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 475' to surface. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 ½" CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 3030-3400 32.4750855 -104.3116837									
Hole Size: 12 1/4 3. Spotted 75 sx class C cmt @ 475' to surface. 2. Spotted 25 sx class C cmt @ 988-735'. 1. Set 5 1/4" CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 3030-3400 1. Set 5 1/4" CIBP @ 2750'. Circ'd hole w/ 60 bbls Brine H20. Pressure tested csg, held 500 PSI. Spotted 25 sx class C cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 3030-3400	- 1							Tubb	4679
cmt @ 2750-2509'. WOC. RU 3rd party wireline. Tagged plug @ 2586'. Ran CBL, found TOC @ 360'. Perfs @ 2800-2996 Perfs @ 3030-3400 -104.3116837	4		Hole Size:	12 1/4 C cmt @ 475' to					
TDPB @ 4365 Hole Size: 7 7/8 TD @ 4425			cmt @ 2750-2509'. WOO Perfs @ 2800-2996 Perfs @ 3030-3400 2 7/8 @ 4143'.	C. RU 3rd party v	r/ 60 bbls Brine H2 wireline. Tagged p	20. Pressure teste llug @ 2586'. Rai	d csg, held 500 PSI. S n CBL, found TOC @	360'. 32.4750855	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 305568

CONDITIONS

Operator:	OGRID:
RILEY PERMIAN OPERATING COMPANY, LLC	372290
29 E Reno Avenue, Suite 500	Action Number:
Oklahoma City, OK 73104	305568
	Action Type:
	[C-103] Sub. Plugging (C-103P)

CONDITIONS

Created By		Condition Date
gcordero	None	3/8/2024