

Well Name: LOST TANK 30-19 FEDERAL COM	Well Location: T22S / R32E / SEC 19 / NENW / 32.3832396 / -103.7174375	County or Parish/State: LEA / NM
Well Number: 22H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM90587	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002547543	Well Status: Approved Application for Permit to Drill	Operator: OXY USA INCORPORATED

Notice of Intent

Sundry ID: 2759009

Type of Submission: Notice of Intent

Type of Action: APD Change

Date Sundry Submitted: 11/01/2023

Time Sundry Submitted: 08:33

Date proposed operation will begin: 12/01/2023

Procedure Description: OXY USA INC. Respectfully requests approval to make changes to our approved APD, see the following change requests below: Update Surface Hole: from Sec 19, T22S, R32E, 373' From the North and 1701' From the West, to the new location of Sec 19, T22S, R32E, 353' From the North and 2049' from the West. Update Bottom Hole: from Section 30 T22S, R32E, 20' from the South and 1340' from the West, to the new location of Section 30, T22S, R32E, 20' From the South and 1640' From the West. Changes to our 3 string casing design. Please see the attached updated drill plans, along with specs for the casing strings.

NOI Attachments

Procedure Description

- LostTank30_19FedCom22H_ProdCsgAnnClearanceVariance_20240205124414.pdf
- LostTank30_19FedCom22H_OfflineCementVariance_20240205124405.pdf
- LostTank30_19FedCom22H_BradenheadCBLVariance_20240205124357.pdf
- LostTank30_19FedCom22H_BOPBreakTestingVariance_20240205124350.pdf
- LostTank30_19FedCom22H_13inADAPT_13.375in_9.625in_10x10_20240205124336.pdf
- LostTank30_19FedCom22H_DrillPlan_20240205124324.pdf
- LostTank30_19FedCom22H_DirectPlan_20240205124316.pdf
- LostTank30_19FedCom22H_TNSWedge461_5.500in_20.00ppf_P110CY_20240205124303.pdf

Well Name: LOST TANK 30-19
FEDERAL COM

Well Location: T22S / R32E / SEC 19 /
NENW / 32.3832396 / -103.7174375

County or Parish/State: LEA /
NM

Well Number: 22H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM90587

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002547543

Well Status: Approved Application for
Permit to Drill

Operator: OXY USA
INCORPORATED

I105015WEL01NM_LOST_TANK_30_19_FED_COM_22H_C_102_20231101083330.pdf

Conditions of Approval

Additional

LOST_TANK_30_19_FEDERAL_COM_22H__COA_20240309102916.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: LESLIE REEVES

Signed on: FEB 05, 2024 12:43 PM

Name: OXY USA INCORPORATED

Title: Advisor Regulatory

Street Address: 5 GREENWAY PLAZA, SUITE 110

City: HOUSTON

State: TX

Phone: (713) 497-2492

Email address: LESLIE_REEVES@OXY.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: KEITH P IMMATTY

BLM POC Title: ENGINEER

BLM POC Phone: 5759884722

BLM POC Email Address: KIMMATTY@BLM.GOV

Disposition: Approved

Disposition Date: 03/22/2024

Signature: Chris Walls

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well

Oil Well Gas Well Other

8. Well Name and No.

2. Name of Operator

9. API Well No.

3a. Address

3b. Phone No. (include area code)

10. Field and Pool or Exploratory Area

4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)

11. Country or Parish, State

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon		
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Title

Signature

Date

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: NENW / 373 FNL / 1701 FWL / TWSP: 22S / RANGE: 32E / SECTION: 19 / LAT: 32.3832396 / LONG: -103.7174375 (TVD: 0 feet, MD: 0 feet)
PPP: LOT 1 / 100 FNL / 1340 FWL / TWSP: 22S / RANGE: 32E / SECTION: 19 / LAT: 32.3839863 / LONG: -103.718607 (TVD: 10530 feet, MD: 10935 feet)
PPP: LOT 1 / 1315 FNL / 1341 FWL / TWSP: 22S / RANGE: 32E / SECTION: 19 / LAT: 32.380648 / LONG: -103.718605 (TVD: 10531 feet, MD: 12155 feet)
PPP: LOT 1 / 7 FNL / 1344 FWL / TWSP: 22S / RANGE: 32E / SECTION: 30 / LAT: 32.369765 / LONG: -103.718598 (TVD: 10531 feet, MD: 16114 feet)
PPP: LOT 3 / 2635 FNL / 1342 FWL / TWSP: 22S / RANGE: 32E / SECTION: 19 / LAT: 32.37702 / LONG: -103.718603 (TVD: 10531 feet, MD: 13475 feet)
BHL: LOT 4 / 20 FSL / 1340 FWL / TWSP: 22S / RANGE: 32E / SECTION: 30 / LAT: 32.3552778 / LONG: -103.718589 (TVD: 10531 feet, MD: 21386 feet)

CONFIDENTIAL

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	OXY USA INC.
WELL NAME & NO.:	LOST TANK 30 19 FEDERAL COM 22H
SURFACE HOLE FOOTAGE:	353'/N & 2049'/W
BOTTOM HOLE FOOTAGE:	20'/S & 1640'/W
LOCATION:	Section 19, T.22 S., R.32 E.
COUNTY:	Lea County, New Mexico

All previous COAs still apply

COA

H2S	<input checked="" type="radio"/> Yes	<input type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Wellhead Variance	<input type="radio"/> Diverter		
Other	<input type="checkbox"/> 4 String	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Pilot Hole	<input type="checkbox"/> Open Annulus
Cementing	<input type="checkbox"/> Contingency Cement Squeeze	<input type="checkbox"/> EchoMeter	<input checked="" type="checkbox"/> Primary Cement Squeeze
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit
Special Requirements	<input type="checkbox"/> Batch Sundry		
Special Requirements Variance	<input checked="" type="checkbox"/> Break Testing	<input checked="" type="checkbox"/> Offline Cementing	<input checked="" type="checkbox"/> Casing Clearance

A. CASING

Primary Casing Design:

1. The **13-3/8** inch surface casing shall be set at approximately **913** feet (a minimum of 25 feet (Lea County) into the Rustler Anhydrite, above the salt, and below usable fresh water) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8**

- hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The **7-5/8** inch intermediate casing shall be set at approximately **9760** feet. The minimum required fill of cement behind the **7-5/8** inch intermediate casing is:

Option 1 (Single Stage):

- Cement to surface. If cement does not circulate see B.1.a, c-d above.

Option 2:

Operator has proposed to cement in two stages by conventionally cementing the first stage and performing a bradenhead squeeze on the second stage, contingent upon no returns to surface.

- a. First stage: Operator will cement with intent to reach the top of the **Brushy Canyon**
- b. Second stage:
 - Operator will perform bradenhead squeeze and top-out. Cement to surface. If cement does not reach surface, the appropriate BLM office shall be notified.

Operator has proposed to pump down 7-5/8" X 13-3/8" annulus. Operator must top out cement after the bradenhead squeeze and verify cement to surface. Operator can also check TOC with Echo-meter. CBL must be run from TD of the 7-5/8" casing to surface if confidence is lacking on the quality of the bradenhead squeeze cement job. Submit results to BLM.

3. The **5.5** inch production casing shall be set at approximately **21,080** feet. The minimum required fill of cement behind the **5.5** inch production casing is:

Option 1 (Single Stage):

- Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

B. SPECIAL REQUIREMENT (S)

(Note: For a minimum 5M BOPE or less (Utilizing a 10M BOPE system)

BOPE Break Testing Variance

- BOPE Break Testing is ONLY permitted for 5M BOPE or less. **(Annular preventer must be tested to a minimum of 70% of BOPE working pressure and shall be higher than the MASP)**
- BOPE Break Testing is NOT permitted to drilling the production hole section.
- Variance only pertains to the intermediate hole-sections and no deeper than the Bone Springs formation.
- While in transfer between wells, the BOPE shall be secured by the hydraulic carrier or cradle.
- Any well control event while drilling require notification to the BLM Petroleum Engineer **(575-706-2779)** prior to the commencement of any BOPE Break Testing operations.
- A full BOPE test is required prior to drilling the first deep intermediate hole section. If any subsequent hole interval is deeper than the first, a full BOPE test will be required. (200' TVD tolerance between intermediate shoes is allowable).
- The BLM is to be contacted (575-689-5981 Lea County) 4 hours prior to BOPE tests.
- As a minimum, a full BOPE test shall be performed at 21-day intervals.
- In the event any repairs or replacement of the BOPE is required, the BOPE shall test as per 43 CFR part 3170 Subpart 3172.
- If in the event break testing is not utilized, then a full BOPE test would be conducted.

Offline Cementing

OK for surface and intermediate intervals. Notify the BLM prior to the commencement of any offline cementing procedure.

Casing Clearance:

Overlap clearance in production interval OK

Operator shall clean up cycles until wellbore is clear of cuttings and any large debris, ensure cutting sizes are adequate “coffee ground or less” before cementing.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

EMAIL or call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,

BLM_NM_CFO_DrillingNotifications@BLM.GOV

(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240,

(575) 689-5981

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per **43 CFR part 3170 Subpart 3172** as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or

if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in **43 CFR part 3170 Subpart 3172 and API STD 53 Sec. 5.3.**

2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in **43 CFR part 3170 Subpart 3172** must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead cement), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been

done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the cement plug. The BOPE test can be initiated after bumping the cement plug with the casing valve open. (only applies to single stage cement jobs, prior to the cement setting up.)

- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer and can be initiated immediately with the casing valve open. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to **43 CFR part 3170 Subpart 3172** with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per **43 CFR part 3170 Subpart 3172**.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

KPI 3/9/2024

Production Casing Annular Clearance Variance Request

As per the agreement reached in the Oxy/BLM face-to-face meeting on Feb 22, 2018, Oxy requests permission to allow deviation from the 0.422" annular clearance requirement from 43 CFR part 3170 Subpart 3172 under the following conditions:

1. Annular clearance to meet or exceed 0.422" between intermediate casing ID and production casing coupling only on the first 500' overlap between both casings.
2. Annular clearance less than 0.422" is acceptable for the curve and lateral portions of the production open hole section.

Offline Cementing Variance Request

Oxy requests a variance to cement the 9.625” and/or 7.625” intermediate casing strings offline in accordance to the approved variance, EC Tran 461365.

1. Cement Program

No changes to the cement program will take place for offline cementing.


2. Offline Cementing Procedure

The operational sequence will be as follows:


1. Run casing as per normal operations. While running casing, conduct negative pressure test and confirm integrity of the float equipment (float collar and shoe)
2. Land casing with mandrel
3. Fill pipe with kill weight fluid, do not circulate through floats and confirm well is static
4. Set annular packoff shown below and pressure test to confirm integrity of the seal.
Pressure ratings of wellhead components and valves is 5,000 psi

Annular packoff with both external and internal seals





5. After confirmation of both annular barriers and internal barriers, nipple down BOP and install cap flange.
 - a. If any barrier fails to test, the BOP stack will not be nipped down until after the cement job is completed with cement 500ft above the highest formation capable of flow with kill weight mud above or after it has achieved 50 psi compressive strength if cannot be verified.
6. Skid rig to next well on pad.
7. Confirm well is static before removing cap flange, flange will not be removed and offline cementing operations will not commence until well is under control. If well is not static, casing outlet valves will provide access to both the casing ID and annulus. Rig or third party pump truck will kill well prior to cementing or nipping up for further remediation.
 - a. Well Control Plan
 - i. The Drillers Method will be the primary well control method to regain control of the wellbore prior to cementing, if wellbore conditions do not permit the drillers method other methods of well control may be used
 - ii. Rig pumps or a 3rd party pump will be tied into the upper casing valve to pump down the casing ID
 - iii. A high pressure return line will be rigged up to lower casing valve and run to choke manifold to control annular pressure
 - iv. Once influx is circulated out of the hole, kill weight mud will be circulated
 - v. Well will be confirmed static
 - vi. Once confirmed static, cap flange will be removed to allow for offline cementing operations to commence
8. Install offline cement tool
9. Rig up cement equipment



Wellhead diagram during offline cementing operations

10. Circulate bottoms up with cement truck
 - a. If gas is present on bottoms up, well will be shut in and returns rerouted through gas buster to handle entrained gas
 - b. Max anticipated time before circulating with cement truck is 6 hrs
11. Perform cement job taking returns from the annulus wellhead valve
12. Confirm well is static and floats are holding after cement job
13. Remove cement equipment, offline cement tools and install night cap with pressure gauge for monitoring.

Bradenhead Cement CBL Variance Request

Oxy requests permission to adjust the CBL requirement after bradenhead cement jobs, on 7-5/8” intermediate casings, as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

Three string wells:

- CBL will be required on one well per pad
- If the pumped volume of cement is less than permitted in the APD, BLM will be notified and a CBL may be run
- Echometer will be used after bradenhead cement job to determine TOC before pumping top-out cement

Four string wells:

- CBL is not required
- If the pumped volume of cement is less than permitted in the APD, BLM will be notified and a CBL may be run
- Echometer will be used after bradenhead cement job to determine TOC before pumping top-out cement

BOP Break Testing Request

Oxy requests permission to adjust the BOP break testing requirements as per the agreement reached in the OXY/BLM meeting on September 5, 2019.

BOP break test under the following conditions:

- After a full BOP test is conducted
- When skidding to drill an intermediate section where ICP is set into the third Bone Spring or shallower.
- When skidding to drill a production section that does not penetrate into the third Bone Spring or deeper.

If the kill line is broken prior to skid, two tests will be performed.

- 1) Wellhead flange, co-flex hose, kill line connections and upper pipe rams
- 2) Wellhead flange, HCR valve, check valve, upper pipe rams

If the kill line is not broken prior to skid, only one test will be performed.

- 1) Wellhead flange, co-flex hose, check valve, upper pipe rams

See supporting information below:

Subject: Request for a Variance Allowing Break Testing of a Blowout Preventer Stack

OXY USA Inc. (OXY) requests a variance to allow break testing of the Blowout Preventer (BOP) stack when skidding a drilling rig between wells on multi-well pads. This practice entails retesting only the connections of the **BOP** stack that have been disconnected during this operation and not a complete **BOP** test.

Background

43 CFR part 3170 Subpart 3172 states that a **BOP** test must be performed whenever any seal subject to test pressure is broken. The current interpretation of the Bureau of Land Management (BLM) is this requires a complete **BOP** test and not just a test of the affected component. 43 CFR part 3170 Subpart 3172, Section I.D.2. states, "Some situations may exist either on a well-by-well basis or field-wide basis whereby it is commonly accepted practice to vary a particular minimum standard(s) established in this Order. This situation can be resolved by requesting a variance...". OXY feels the practice of break testing the **BOP** stack is such a situation. Therefore, as per 43 CFR part 3170 Subpart 3172, Section IV., OXY submits this request for the variance.

Supporting Rationale

43 CFR part 3170 Subpart 3172 became effective on December 19, 1988, and has remained the standard for regulating BLM onshore drilling operations for almost 30 years. During this time there have been significant changes in drilling technology. **BLM** continues to use the variance request process to allow for the use of modern technology and acceptable engineering practices that have arisen since 43 CFR part 3170 Subpart 3172 was originally released. The drilling rig fleet OXY utilizes in New Mexico was built with many modern upgrades. One of which allows the rigs to skid between wells on multi-well pads. A part of this rig package is a hydraulic winch system which safely installs and removes the BOP from the wellhead and carries it during skidding operations. This technology has made break testing a safe and reliable procedure.

American Petroleum Institute (API) standards, specifications and recommended practices are considered industry standards and are consistently utilized and referenced by the industry. 43 CFR part 3170 Subpart 3172 recognized API Recommended Practices (RP) 53 in its original development. API Standard 53,

Blowout Prevention Equipment Systems for Drilling Wells (Fourth Edition, November 2012, Addendum 1, July 2016) recognizes break testing as an acceptable practice. Specifically, API Standard 53, Section 6.5.3.4.1.b states "Pressure tests on the well control equipment shall be conducted after the disconnection or repair of any pressure containment seal in the **BOP** stack, choke line, kill line, choke manifold, or wellhead assembly but limited to the affected component."

The Bureau of Safety and Environmental Enforcement (BSEE), Department of Interior, has also utilized the API standards, specifications and best practices in the development of its offshore oil and gas regulations and incorporates them by reference within its regulations. BSEE issued new offshore regulations under 30 CFR Part 250, *Oil and Gas and Sulphur Operations in the Outer Continental Shelf - Blowout Preventer Systems and Well Control*, which became effective on July 28, 2016. Section 250.737(d.1) states "Follow the testing requirements of API Standard 53". In addition, Section 250.737(d.8) has adopted language from **API** Standard 53 as it states "Pressure test affected **BOP** components following the disconnection or repair of any well-pressure containment seal in the wellhead or **BOP** stack assembly".

Break testing has been approved by the BLM in the past. See the Appendix for a Sundry Notice that was approved in 2015 by the Farmington Field Office. This approval granted permission for the operator to break test when skidding its Aztec 1000 rig on multi-well pads.

Oxy feels break testing and our current procedures meet the intent of 43 CFR part 3170 Subpart 3172 and often exceed it. We have not seen any evidence that break testing results in more components failing tests than seen on full BOP tests. As skidding operations take place within the 30-day full BOPE test window, the BOP shell and components such as the pipe rams and check valve get tested to the full rated working pressure more often. Therefore, there are more opportunities to ensure components are in good working order. Also, Oxy's standard requires complete BOP tests more often than that of 43 CFR part 3170 Subpart 3172. In addition to function testing the annular at least weekly and the pipe and blind rams on each trip, Oxy also performs a choke drill prior to drilling out every casing shoe. As a crew's training is a vital part of well control, this procedure to simulate step one of the Driller's Method exceeds the requirements of 43 CFR part 3170 Subpart 3172.

Procedures

- 1) OXY to submit the break testing plan in the APD or Sundry Notice (SN) and receive approval prior to implementing (See Appendix for examples)
- 2) OXY would perform BOP break testing on multi-well pads where multiple intermediate sections can be drilled and cased within the 30-day BOP test window
- 3) After performing a complete BOP test on the first well and drilling and casing the hole section, three breaks would be made on the BOP.
 - Between the check valve and the kill line
 - Between the HCR valve and the co-flex hose or the co-flex hose and the manifold
 - Between the BOP flange and the wellhead
- 4) The BOP is then lifted and removed from the wellhead by the hydraulic winch system
- 5) After skidding to the next well, the BOP is moved to the wellhead by the hydraulic winch system and installed
- 6) The choke line and kill line are reconnected
- 7) A test plug is installed in the wellhead with a joint of drill pipe and the internal parts of the check valve are removed
- 8) A shell test is performed against the upper pipe rams testing all three breaks
- 9) The internal parts of the check valve are reinstalled and the HCR valve is closed. A second test is performed on them
- 10) These tests consist of a 250 psi low test and a high test to the value submitted in the APD or SN (e.g., 5000 psi)
- 11) Perform a function test of components not pressure tested to include the lower pipe rams, the blind rams and the annular
- 12) If this were a three well pad, the same three breaks on the BOP would be made and steps 4 through 11 would be repeated
- 13) A second break test would only be done if the third hole section could be completed within the 30-day BOP test window
- 14) If a second break test is performed, additional components that were not tested on the initial break test will be tested on this break test

Notes:


- a. If any parts of the BOP are changed out or any additional breaks are made during the skidding operation, these affected components would also be tested as in step 10.
- b. As the choke manifold remains stationary during the skidding operation and the only break to the manifold is tested in step 8 above, no further testing of the manifold is done until the next full BOP test.

Summary

OXY requests a variance to allow break testing of the BOP stack when skidding drilling rigs between wells on multi-well pads. API standards, specifications and recommended practices are considered industry standards and are consistently utilized and referenced by the industry and the BLM. API Standard 53 recognizes break testing as an acceptable practice and BSEE adopted language from this standard into its newly created 30 CFR Part 250 which also supports break testing. Due to this, OXY feels this request meets the intent of 43 CFR part 3170

REQUEST FOR A VARIANCE TO BREAK TEST THE BOP

Permian Resources New Mexico



Request for Variance

OXY USA Inc. (OXY) requests a variance to allow break testing of the Blowout Preventer (BOP) stack when skidding a drilling rig between wells on multi-well pads

- This practice entails retesting only the connections of the BOP stack that have been disconnected during this operation and not a complete BOP test.
- As the choke manifold remains stationary during the skidding operation and the only break to the manifold is tested, no further testing of the manifold is done until the next full BOP test.
- This request is being made as per Section IV of the *Onshore Oil and Gas Order (OOGO) No. 2*

Rationale for Allowing BOP Break Testing

American Petroleum Institute (API) standards, specifications and recommended practices are considered industry standards and are consistently utilized and referenced by the industry

- API Standard 53, *Blowout Prevention Equipment Systems for Drilling Wells* (Fourth Edition, November 2012, Addendum 1, July 2016) recognizes break testing as an acceptable practice.
- Specifically, API Standard 53, Section 6.5.3.4.1.b states “Pressure tests on the well control equipment shall be conducted after the disconnection or repair of any pressure containment seal in the BOP stack, choke line, kill line, choke manifold, or wellhead assembly but limited to the affected component.”



Rationale for Allowing BOP Break Testing

The Bureau of Safety and Environmental Enforcement (BSEE), Department of Interior, has also utilized the API standards, specifications and best practices in the development of its offshore oil and gas regulations and incorporates them by reference within its regulations.

- BSEE issued new offshore regulations in July 2016 under 30 CFR Part 250, *Oil and Gas and Sulphur Operations in the Outer Continental Shelf - Blowout Preventer Systems and Well Control*. Within these regulations is language adopted from API Standard 53 which also supports break testing.
- Specifically, Section 250.737(d.8) states “Pressure test affected BOP components following the disconnection or repair of any well-pressure containment seal in the wellhead or BOP stack assembly.”



Rationale for Allowing BOP Break Testing

Break testing has been approved by the BLM in the past

- The Farmington Field Office approved a Sundry Notice (SN) to allow break testing in 2015
- This SN granted permission for the operator to break test when skidding its Aztec 1000 rig on multi-well pads

Oxy feels break testing and our current procedures meet or exceed the intent of OOGO No. 2

- As skidding operations take place within the 30-day full BOPE test window, the BOP shell and components such as the pipe rams and check valve get tested to the full rated working pressure more often
- Oxy's standard requires complete BOP tests more often than that of OOGO No. 2
- Oxy performs a choke drill prior to drilling out every casing shoe. As a crew's training is a vital part of well control, this procedure to simulate step one of the Driller's Method exceeds the requirements of OOGO No. 2



Break Testing Procedures

- 1) OXY to submit the break testing plan in the APD or Sundry Notice (SN) and receive approval prior to implementing
- 2) OXY would perform BOP break testing on multi-well pads where multiple intermediate sections can be drilled and cased within the full BOP test window
- 3) After performing a complete BOP test on the first well and drilling and casing the hole section, three breaks would be made on the BOP.
 - Between the check valve and the kill line
 - Between the HCR valve and the co-flex hose or the co-flex hose and the manifold
 - Between the BOP flange and the wellhead
- 4) The BOP is then lifted and removed from the wellhead by the hydraulic winch system
- 5) After skidding to the next well, the BOP is moved to the wellhead by the hydraulic winch system and installed
- 6) The choke line and kill line are reconnected
- 7) A test plug is installed in the wellhead with a joint of drill pipe and the internal parts of the check valve are removed



Break Testing Procedures


- 8) A shell test is performed against the upper pipe rams testing all three breaks
- 9) The internal parts of the check valve are reinstalled and the HCR valve is closed. A second test is performed on them
- 10) These tests consist of a 250 psi low test and a high test to the value submitted in the APD or SN (e.g., 5000 psi)
- 11) Perform a function test of components not pressure tested to include the lower pipe rams, the blind rams and the annular
- 12) If this were a three well pad, the same three breaks on the BOP would be made and steps 4 through 11 would be repeated
- 13) A second break test would only be done if the third hole section could be completed within the 30-day BOP test window
- 14) If a second break test is performed, additional components that were not tested on the first break test will be tested



Break Testing Procedures and Tests


1. After performing a complete BOP test on the first well, the BOP is removed, the rig is skidded and the BOP is installed on the second well

2. A test plug is installed in the wellhead on drill pipe and the inner components of the check valve are removed



Break Testing Procedures and Tests

3. After Test #1, the inner components of the check valve are reinstalled and the HCR valve is closed




Test #2
BOP-Wellhead flange, HCR valve, check valve and upper pipe rams

- Items in red are in the closed position
- Items in green are in the open position
- Items in blue are the breaks
- Items in yellow were previously tested

Second Break Testing Procedures and Tests

Procedures 1 and 2 and Test #1 will be completed as in the first break test (see slide 8)

3. After Test #1, the inner components of the check valve are reinstalled and the inside choke line valve is closed



Test #2
BOP-Wellhead flange, inside choke line valve, check valve and upper pipe rams

- Items in red are in the closed position
- Items in green are in the open position
- Items in blue are the breaks
- Items in yellow were previously tested

BOP Handling System



Hydraulic winch system which moves the BOP from its carrier to the wellhead

BOP standing in its carrier



BOP Handling System



Hydraulic winch system moving the BOP over to the wellhead


Wellhead



Summary for Variance Request for Break Testing

- API standards, specifications and recommended practices are considered industry standards
 - OOGO No. 2 recognized API Recommended Practices (RP) 53 in its original development
 - API Standard 53 recognizes break testing as an acceptable practice
 - The Bureau of Safety and Environmental Enforcement has utilized API standards, specifications and best practices in the development of its offshore oil and gas regulations
 - API Standard 53 recognizes break testing as an acceptable practice
- OXY feels break testing meets the intent of OOGO No. 2 to protect public health and safety and the environment





Notes:

1. THIS IS A PROPOSAL DRAWING AND DIMENSIONS SHOWN ARE SUBJECT TO CHANGE DURING THE FINAL DESIGN PROCESS.
2. DIGITALLY ENABLED SOLUTIONS, CHOKES AND ESD'S AVAILABLE ON REQUEST

CONFIDENTIAL			
SURFACE TREATMENT	DO NOT SCALE		SURFACE SYSTEMS
DRAWN BY: D. GOTTUNG	DATE 18 Feb 22	 A Schlumberger Company	OXY 13-5/8" 10K ADAPT 16" X 10-3/4" X 7-5/8" X 5-1/2"
CHECKED BY: D. GOTTUNG	DATE 18 Feb 22		
MATERIAL & HEAT TREAT	APPROVED BY: D. GOTTUNG	DATE 18 Feb 22	ESTIMATED WEIGHT: 6115.068 LBS 2773.748 KG
INITIAL USE B/M:		SHEET 1 of 1	REV: 01
SD-053434-94-12			INVENTOR: B

Oxy USA Inc. - Lost Tank 30_19 Fed Com 22H Drill Plan

1. Geologic Formations

TVD of Target (ft):	10452	Pilot Hole Depth (ft):	
Total Measured Depth (ft):	21080	Deepest Expected Fresh Water (ft):	853

Delaware Basin

Formation	MD-RKB (ft)	TVD-RKB (ft)	Expected Fluids
Rustler	853	853	
Salado	1145	1145	Salt
Castile	2852	2852	Salt
Delaware	4599	4599	Oil/Gas/Brine
Bell Canyon	4675	4675	Oil/Gas/Brine
Cherry Canyon	5521	5515	Oil/Gas/Brine
Brushy Canyon	6762	6743	Losses
Bone Spring	8536	8500	Oil/Gas
Bone Spring 1st	9630	9583	Oil/Gas
Bone Spring 2nd	10294	10219	Oil/Gas
Bone Spring 3rd			Oil/Gas
Wolfcamp			Oil/Gas
Penn			Oil/Gas
Strawn			Oil/Gas

*H2S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program

Section	Hole Size (in)	MD		TVD		Csg. OD (in)	Csg. Wt. (ppf)	Grade	Conn.
		From (ft)	To (ft)	From (ft)	To (ft)				
Surface	17.5	0	913	0	913	13.375	54.5	J-55	BTC
Intermediate	9.875	0	9760	0	9711	7.625	26.4	L-80 HC	BTC
Production	6.75	0	21080	0	10452	5.5	20	P-110	Wedge 461

All casing strings will be tested in accordance with 43 CFR part 3170 Subpart 3172

All Casing SF Values will meet or exceed those below			
SF Collapse	SF Burst	Body SF Tension	Joint SF Tension
1.00	1.100	1.4	1.4

Annular Clearance Variance Request

As per the agreement reached in the Oxy/BLM face-to-face meeting on Feb 22, 2018, Oxy requests permission to allow deviation from the 0.422" annular clearance requirement. Please see Annular Clearance Variance attachment for further details.

	Y or N
Is casing new? If used, attach certification as required in 43 CFR 3160	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	Y
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Section	Stage	Slurry:	Sacks	Yield (ft ³ /ft)	Density (lb/gal)	Excess:	TOC	Placement	Description
Surface	1	Surface - Tail	954	1.33	14.8	100%	-	Circulate	Class C+Accel.
Int.	1	Intermediate 1S - Tail	376	1.65	13.2	5%	7,012	Circulate	Class H+Accel., Disper., Salt
Int.	2	Intermediate 2S - Tail BH	1252	1.71	13.3	25%	-	Bradenhead	Class C+Accel.
Prod.	1	Production - Tail	893	1.38	13.2	25%	9,260	Circulate	Class H+Ret., Disper., Salt

Offline Cementing Request

Oxy requests a variance to cement the 9.625" and/or 7.625" intermediate casing strings offline in accordance to the approved variance, EC Tran 461365. Please see Offline Cementing Variance attachment for further details.

Bradenhead CBL Request

Oxy requests permission to adjust the CBL requirement after bradenhead cement jobs, on 7-5/8" intermediate casings, as per the agreement reached in the OXY/BLM meeting on September 5, 2019. Please see Bradenhead CBL Variance attachment for further details.

4. Pressure Control Equipment

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:	Deepest TVD Depth (ft) per Section:
9.875" Hole	13-5/8"	5M	Annular	✓	70% of working pressure	9711
		5M	Blind Ram	✓	250 psi / 5000 psi	
			Pipe Ram			
			Double Ram	✓		
Other*						
6.75" Hole	13-5/8"	5M	Annular	✓	70% of working pressure	10452
		5M	Blind Ram	✓	250 psi / 5000 psi	
			Pipe Ram			
			Double Ram	✓		
Other*						

*Specify if additional ram is utilized

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per 43 CFR part 3170 Subpart 3172 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

	<p>Formation integrity test will be performed per 43 CFR part 3170 Subpart 3172.</p> <p>On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with 43 CFR part 3170 Subpart 3172.</p>
	<p>A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.</p>
Y	<p>Are anchors required by manufacturer?</p>
	<p>A multibowl or a unionized multibowl wellhead system will be employed. The wellhead and connection to the BOPE will meet all API 6A requirements. The BOP will be tested per 43 CFR part 3170 Subpart 3172 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. We will test the flange connection of the wellhead with a test port that is directly in the flange. We are proposing that we will run the wellhead through the rotary prior to cementing surface casing as discussed with the BLM on October 8, 2015.</p> <p>See attached schematics.</p>

BOP Break Testing Request

Oxy requests permission to adjust the BOP break testing requirements as per the agreement reached in the OXY/BLM meeting on September 5, 2019. Please see BOP Break Testing Variance attachment for further details.

Oxy will use Cameron ADAPT wellhead system that uses an OEC top flange connection. This connection has been fully vetted and verified by API to Spec 6A and carries an API monogram.

5. Mud Program

Section	Depth - MD		Depth - TVD		Type	Weight (ppg)	Viscosity	Water Loss
	From (ft)	To (ft)	From (ft)	To (ft)				
Surface	0	913	0	913	Water-Based Mud	8.6 - 8.8	40-60	N/C
Intermediate	913	9760	913	9711	Saturated Brine-Based or Oil-Based Mud	8.0 - 10.0	35-45	N/C
Production	9760	21080	9711	10452	Water-Based or Oil-Based Mud	8.0 - 9.6	38-50	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times. The following is a general list of products: Barite, Bentonite, Gypsum, Lime, Soda Ash, Caustic Soda, Nut Plug, Cedar Fiber, Cotton Seed Hulls, Drilling Paper, Salt Water Clay, CACL2. Oxy will use a closed mud system.

What will be used to monitor the loss or gain of fluid?	PVT/MD Totco/Visual Monitoring
---	--------------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
Yes	Will run GR from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
No	Logs are planned based on well control or offset log information.
No	Drill stem test? If yes, explain
No	Coring? If yes, explain
Additional logs planned	Interval
No	Resistivity
No	Density
Yes	CBL Production string
Yes	Mud log Bone Spring – TD
No	PEX

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	5218 psi
Abnormal Temperature	No
BH Temperature at deepest TVD	164°F

Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of 43 CFR part 3170 Subpart 3172. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H2S is present
Y	H2S Plan attached

8. Other facets of operation

	Yes/No
Will the well be drilled with a walking/skidding operation? If yes, describe. We plan to drill the 2 well pad in batch by section: all surface sections, intermediate sections and production sections. The wellhead will be secured with a night cap whenever the rig is not over the well.	Yes
Will more than one drilling rig be used for drilling operations? If yes, describe. Oxy requests the option to contract a Surface Rig to drill, set surface casing, and cement for this well. If the timing between rigs is such that Oxy would not be able to preset surface, the Primary Rig will MIRU and drill the well in its entirety per the APD. Please see the attached document for information on the spudder rig.	Yes

Total Estimated Cuttings Volume: 1611 bbls

OXY

PRD NM DIRECTIONAL PLANS (NAD 1983)

LOST TANK 30-19 FED

Lost Tank 30_19 Fed Com 22H

Wellbore #1

Plan: Permitting Plan

Standard Planning Report

24 October, 2023

OXY Planning Report

Database:	HOPSPP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Project PRD NM DIRECTIONAL PLANS (NAD 1983)			
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		Using geodetic scale factor

Site LOST TANK 30-19 FED			
Site Position:		Northing:	503,826.03 usft
From:	Lat/Long	Easting:	0.00 usft
Position Uncertainty:	44.72 ft	Slot Radius:	13.200 in
		Latitude:	32.372894
		Longitude:	-106.086667

Well Lost Tank 30_19 Fed Com 22H			
Well Position	+N/-S	0.00 ft	Northing:
	+E/-W	0.00 ft	503,726.49 usf
			Latitude:
			32.383303
Position Uncertainty		1.79 ft	Easting:
			731,808.38 usf
			Longitude:
			-103.716312
Grid Convergence:		0.33 °	Wellhead Elevation:
			0.00 ft
			Ground Level:
			3,619.70 ft

Wellbore Wellbore #1					
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM_FILE	10/24/2023	6.37	59.98	47,606.80000000

Design Permitting Plan				
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (ft)	+N/-S (ft)	+E/-W (ft)	Direction (°)
	0.00	0.00	0.00	181.94

Plan Survey Tool Program		Date 10/24/2023		
Depth From (ft)	Depth To (ft)	Survey (Wellbore)	Tool Name	Remarks
1	0.00	21,080.34 Permitting Plan (Wellbore #1)	B001Mb_MWD+HRGM OWSG MWD + HRGM	

Plan Sections										
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
4,305.00	0.00	0.00	4,305.00	0.00	0.00	0.00	0.00	0.00	0.00	
5,112.95	8.08	329.55	5,110.27	49.02	-28.83	1.00	1.00	0.00	329.55	
9,860.49	8.08	329.55	9,810.69	624.22	-367.02	0.00	0.00	0.00	0.00	
10,830.34	90.00	179.64	10,451.70	55.24	-409.09	10.00	8.45	-15.46	-149.66	
21,080.34	90.00	179.64	10,451.70	-10,194.56	-344.92	0.00	0.00	0.00	0.00	PBHL (Lost Tank

OXY

Planning Report

Database:	HOPSPP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	0.00	0.00
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00
2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00	0.00	0.00
2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00	0.00	0.00
2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00	0.00	0.00
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	0.00	0.00
2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00	0.00	0.00
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00	0.00	0.00
2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00	0.00	0.00
2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00	0.00	0.00
2,900.00	0.00	0.00	2,900.00	0.00	0.00	0.00	0.00	0.00	0.00
3,000.00	0.00	0.00	3,000.00	0.00	0.00	0.00	0.00	0.00	0.00
3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00	0.00	0.00
3,200.00	0.00	0.00	3,200.00	0.00	0.00	0.00	0.00	0.00	0.00
3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00	0.00	0.00
3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00	0.00	0.00
3,500.00	0.00	0.00	3,500.00	0.00	0.00	0.00	0.00	0.00	0.00
3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00	0.00	0.00
3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00	0.00	0.00
3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00	0.00	0.00
3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00	0.00	0.00
4,000.00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00	0.00	0.00
4,100.00	0.00	0.00	4,100.00	0.00	0.00	0.00	0.00	0.00	0.00
4,200.00	0.00	0.00	4,200.00	0.00	0.00	0.00	0.00	0.00	0.00
4,300.00	0.00	0.00	4,300.00	0.00	0.00	0.00	0.00	0.00	0.00
4,305.00	0.00	0.00	4,305.00	0.00	0.00	0.00	0.00	0.00	0.00
4,400.00	0.95	329.55	4,400.00	0.68	-0.40	-0.67	1.00	1.00	0.00
4,500.00	1.95	329.55	4,499.96	2.86	-1.68	-2.80	1.00	1.00	0.00
4,600.00	2.95	329.55	4,599.87	6.55	-3.85	-6.41	1.00	1.00	0.00
4,700.00	3.95	329.55	4,699.69	11.73	-6.90	-11.49	1.00	1.00	0.00
4,800.00	4.95	329.55	4,799.38	18.42	-10.83	-18.04	1.00	1.00	0.00
4,900.00	5.95	329.55	4,898.93	26.61	-15.64	-26.06	1.00	1.00	0.00
5,000.00	6.95	329.55	4,998.30	36.29	-21.34	-35.55	1.00	1.00	0.00
5,100.00	7.95	329.55	5,097.45	47.47	-27.91	-46.50	1.00	1.00	0.00
5,112.95	8.08	329.55	5,110.27	49.02	-28.83	-48.02	1.00	1.00	0.00
5,200.00	8.08	329.55	5,196.46	59.57	-35.03	-58.35	0.00	0.00	0.00

OXY

Planning Report

Database:	HOPSPP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
5,300.00	8.08	329.55	5,295.47	71.69	-42.15	-70.22	0.00	0.00	0.00
5,400.00	8.08	329.55	5,394.48	83.80	-49.27	-82.09	0.00	0.00	0.00
5,500.00	8.08	329.55	5,493.48	95.92	-56.40	-93.96	0.00	0.00	0.00
5,600.00	8.08	329.55	5,592.49	108.03	-63.52	-105.82	0.00	0.00	0.00
5,700.00	8.08	329.55	5,691.50	120.15	-70.65	-117.69	0.00	0.00	0.00
5,800.00	8.08	329.55	5,790.51	132.27	-77.77	-129.56	0.00	0.00	0.00
5,900.00	8.08	329.55	5,889.51	144.38	-84.89	-141.43	0.00	0.00	0.00
6,000.00	8.08	329.55	5,988.52	156.50	-92.02	-153.30	0.00	0.00	0.00
6,100.00	8.08	329.55	6,087.53	168.61	-99.14	-165.16	0.00	0.00	0.00
6,200.00	8.08	329.55	6,186.54	180.73	-106.26	-177.03	0.00	0.00	0.00
6,300.00	8.08	329.55	6,285.54	192.84	-113.39	-188.90	0.00	0.00	0.00
6,400.00	8.08	329.55	6,384.55	204.96	-120.51	-200.77	0.00	0.00	0.00
6,500.00	8.08	329.55	6,483.56	217.07	-127.63	-212.63	0.00	0.00	0.00
6,600.00	8.08	329.55	6,582.56	229.19	-134.76	-224.50	0.00	0.00	0.00
6,700.00	8.08	329.55	6,681.57	241.31	-141.88	-236.37	0.00	0.00	0.00
6,800.00	8.08	329.55	6,780.58	253.42	-149.01	-248.24	0.00	0.00	0.00
6,900.00	8.08	329.55	6,879.59	265.54	-156.13	-260.11	0.00	0.00	0.00
7,000.00	8.08	329.55	6,978.59	277.65	-163.25	-271.97	0.00	0.00	0.00
7,100.00	8.08	329.55	7,077.60	289.77	-170.38	-283.84	0.00	0.00	0.00
7,200.00	8.08	329.55	7,176.61	301.88	-177.50	-295.71	0.00	0.00	0.00
7,300.00	8.08	329.55	7,275.62	314.00	-184.62	-307.58	0.00	0.00	0.00
7,400.00	8.08	329.55	7,374.62	326.11	-191.75	-319.44	0.00	0.00	0.00
7,500.00	8.08	329.55	7,473.63	338.23	-198.87	-331.31	0.00	0.00	0.00
7,600.00	8.08	329.55	7,572.64	350.35	-205.99	-343.18	0.00	0.00	0.00
7,700.00	8.08	329.55	7,671.65	362.46	-213.12	-355.05	0.00	0.00	0.00
7,800.00	8.08	329.55	7,770.65	374.58	-220.24	-366.91	0.00	0.00	0.00
7,900.00	8.08	329.55	7,869.66	386.69	-227.37	-378.78	0.00	0.00	0.00
8,000.00	8.08	329.55	7,968.67	398.81	-234.49	-390.65	0.00	0.00	0.00
8,100.00	8.08	329.55	8,067.68	410.92	-241.61	-402.52	0.00	0.00	0.00
8,200.00	8.08	329.55	8,166.68	423.04	-248.74	-414.39	0.00	0.00	0.00
8,300.00	8.08	329.55	8,265.69	435.15	-255.86	-426.25	0.00	0.00	0.00
8,400.00	8.08	329.55	8,364.70	447.27	-262.98	-438.12	0.00	0.00	0.00
8,500.00	8.08	329.55	8,463.71	459.39	-270.11	-449.99	0.00	0.00	0.00
8,600.00	8.08	329.55	8,562.71	471.50	-277.23	-461.86	0.00	0.00	0.00
8,700.00	8.08	329.55	8,661.72	483.62	-284.35	-473.72	0.00	0.00	0.00
8,800.00	8.08	329.55	8,760.73	495.73	-291.48	-485.59	0.00	0.00	0.00
8,900.00	8.08	329.55	8,859.74	507.85	-298.60	-497.46	0.00	0.00	0.00
9,000.00	8.08	329.55	8,958.74	519.96	-305.73	-509.33	0.00	0.00	0.00
9,100.00	8.08	329.55	9,057.75	532.08	-312.85	-521.20	0.00	0.00	0.00
9,200.00	8.08	329.55	9,156.76	544.19	-319.97	-533.06	0.00	0.00	0.00
9,300.00	8.08	329.55	9,255.76	556.31	-327.10	-544.93	0.00	0.00	0.00
9,400.00	8.08	329.55	9,354.77	568.42	-334.22	-556.80	0.00	0.00	0.00
9,500.00	8.08	329.55	9,453.78	580.54	-341.34	-568.67	0.00	0.00	0.00
9,600.00	8.08	329.55	9,552.79	592.66	-348.47	-580.53	0.00	0.00	0.00
9,700.00	8.08	329.55	9,651.79	604.77	-355.59	-592.40	0.00	0.00	0.00
9,800.00	8.08	329.55	9,750.80	616.89	-362.71	-604.27	0.00	0.00	0.00
9,860.49	8.08	329.55	9,810.69	624.22	-367.02	-611.45	0.00	0.00	0.00
9,900.00	5.08	306.38	9,849.94	627.65	-369.84	-614.78	10.00	-7.60	-58.64
10,000.00	8.06	209.80	9,949.51	624.18	-376.91	-611.07	10.00	2.99	-96.58
10,100.00	17.43	192.74	10,046.96	603.43	-383.71	-590.11	10.00	9.37	-17.06
10,200.00	27.25	187.59	10,139.35	566.03	-390.06	-552.51	10.00	9.82	-5.16
10,300.00	37.16	185.03	10,223.87	513.11	-395.74	-499.44	10.00	9.91	-2.56
10,400.00	47.10	183.43	10,297.94	446.30	-400.59	-432.50	10.00	9.94	-1.60
10,500.00	57.06	182.28	10,359.32	367.61	-404.47	-353.72	10.00	9.96	-1.15
10,600.00	67.03	181.37	10,406.14	279.43	-407.25	-265.50	10.00	9.97	-0.91

OXY Planning Report

Database:	HOPSPP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
10,700.00	77.00	180.58	10,436.98	184.45	-408.85	-170.52	10.00	9.97	-0.79
10,800.00	86.97	179.86	10,450.90	85.56	-409.22	-71.67	10.00	9.97	-0.73
10,830.34	90.00	179.64	10,451.70	55.24	-409.09	-41.37	10.00	9.97	-0.71
10,900.00	90.00	179.64	10,451.70	-14.43	-408.66	28.24	0.00	0.00	0.00
11,000.00	90.00	179.64	10,451.70	-114.43	-408.03	128.16	0.00	0.00	0.00
11,100.00	90.00	179.64	10,451.70	-214.42	-407.40	228.08	0.00	0.00	0.00
11,200.00	90.00	179.64	10,451.70	-314.42	-406.78	328.00	0.00	0.00	0.00
11,300.00	90.00	179.64	10,451.70	-414.42	-406.15	427.92	0.00	0.00	0.00
11,400.00	90.00	179.64	10,451.70	-514.42	-405.52	527.84	0.00	0.00	0.00
11,500.00	90.00	179.64	10,451.70	-614.42	-404.90	627.76	0.00	0.00	0.00
11,600.00	90.00	179.64	10,451.70	-714.41	-404.27	727.68	0.00	0.00	0.00
11,700.00	90.00	179.64	10,451.70	-814.41	-403.65	827.59	0.00	0.00	0.00
11,800.00	90.00	179.64	10,451.70	-914.41	-403.02	927.51	0.00	0.00	0.00
11,900.00	90.00	179.64	10,451.70	-1,014.41	-402.39	1,027.43	0.00	0.00	0.00
12,000.00	90.00	179.64	10,451.70	-1,114.41	-401.77	1,127.35	0.00	0.00	0.00
12,100.00	90.00	179.64	10,451.70	-1,214.40	-401.14	1,227.27	0.00	0.00	0.00
12,200.00	90.00	179.64	10,451.70	-1,314.40	-400.52	1,327.19	0.00	0.00	0.00
12,300.00	90.00	179.64	10,451.70	-1,414.40	-399.89	1,427.11	0.00	0.00	0.00
12,400.00	90.00	179.64	10,451.70	-1,514.40	-399.26	1,527.03	0.00	0.00	0.00
12,500.00	90.00	179.64	10,451.70	-1,614.40	-398.64	1,626.95	0.00	0.00	0.00
12,600.00	90.00	179.64	10,451.70	-1,714.39	-398.01	1,726.87	0.00	0.00	0.00
12,700.00	90.00	179.64	10,451.70	-1,814.39	-397.39	1,826.79	0.00	0.00	0.00
12,800.00	90.00	179.64	10,451.70	-1,914.39	-396.76	1,926.71	0.00	0.00	0.00
12,900.00	90.00	179.64	10,451.70	-2,014.39	-396.13	2,026.63	0.00	0.00	0.00
13,000.00	90.00	179.64	10,451.70	-2,114.39	-395.51	2,126.55	0.00	0.00	0.00
13,100.00	90.00	179.64	10,451.70	-2,214.38	-394.88	2,226.47	0.00	0.00	0.00
13,200.00	90.00	179.64	10,451.70	-2,314.38	-394.26	2,326.39	0.00	0.00	0.00
13,300.00	90.00	179.64	10,451.70	-2,414.38	-393.63	2,426.31	0.00	0.00	0.00
13,400.00	90.00	179.64	10,451.70	-2,514.38	-393.00	2,526.23	0.00	0.00	0.00
13,500.00	90.00	179.64	10,451.70	-2,614.38	-392.38	2,626.15	0.00	0.00	0.00
13,600.00	90.00	179.64	10,451.70	-2,714.37	-391.75	2,726.07	0.00	0.00	0.00
13,700.00	90.00	179.64	10,451.70	-2,814.37	-391.12	2,825.99	0.00	0.00	0.00
13,800.00	90.00	179.64	10,451.70	-2,914.37	-390.50	2,925.91	0.00	0.00	0.00
13,900.00	90.00	179.64	10,451.70	-3,014.37	-389.87	3,025.83	0.00	0.00	0.00
14,000.00	90.00	179.64	10,451.70	-3,114.37	-389.25	3,125.75	0.00	0.00	0.00
14,100.00	90.00	179.64	10,451.70	-3,214.36	-388.62	3,225.67	0.00	0.00	0.00
14,200.00	90.00	179.64	10,451.70	-3,314.36	-387.99	3,325.59	0.00	0.00	0.00
14,300.00	90.00	179.64	10,451.70	-3,414.36	-387.37	3,425.51	0.00	0.00	0.00
14,400.00	90.00	179.64	10,451.70	-3,514.36	-386.74	3,525.43	0.00	0.00	0.00
14,500.00	90.00	179.64	10,451.70	-3,614.36	-386.12	3,625.35	0.00	0.00	0.00
14,600.00	90.00	179.64	10,451.70	-3,714.35	-385.49	3,725.27	0.00	0.00	0.00
14,700.00	90.00	179.64	10,451.70	-3,814.35	-384.86	3,825.19	0.00	0.00	0.00
14,800.00	90.00	179.64	10,451.70	-3,914.35	-384.24	3,925.11	0.00	0.00	0.00
14,900.00	90.00	179.64	10,451.70	-4,014.35	-383.61	4,025.02	0.00	0.00	0.00
15,000.00	90.00	179.64	10,451.70	-4,114.35	-382.99	4,124.94	0.00	0.00	0.00
15,100.00	90.00	179.64	10,451.70	-4,214.35	-382.36	4,224.86	0.00	0.00	0.00
15,200.00	90.00	179.64	10,451.70	-4,314.34	-381.73	4,324.78	0.00	0.00	0.00
15,300.00	90.00	179.64	10,451.70	-4,414.34	-381.11	4,424.70	0.00	0.00	0.00
15,400.00	90.00	179.64	10,451.70	-4,514.34	-380.48	4,524.62	0.00	0.00	0.00
15,500.00	90.00	179.64	10,451.70	-4,614.34	-379.86	4,624.54	0.00	0.00	0.00
15,600.00	90.00	179.64	10,451.70	-4,714.34	-379.23	4,724.46	0.00	0.00	0.00
15,700.00	90.00	179.64	10,451.70	-4,814.33	-378.60	4,824.38	0.00	0.00	0.00
15,800.00	90.00	179.64	10,451.70	-4,914.33	-377.98	4,924.30	0.00	0.00	0.00
15,900.00	90.00	179.64	10,451.70	-5,014.33	-377.35	5,024.22	0.00	0.00	0.00
16,000.00	90.00	179.64	10,451.70	-5,114.33	-376.72	5,124.14	0.00	0.00	0.00

OXY Planning Report

Database:	HOPSPP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Planned Survey									
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
16,100.00	90.00	179.64	10,451.70	-5,214.33	-376.10	5,224.06	0.00	0.00	0.00
16,200.00	90.00	179.64	10,451.70	-5,314.32	-375.47	5,323.98	0.00	0.00	0.00
16,300.00	90.00	179.64	10,451.70	-5,414.32	-374.85	5,423.90	0.00	0.00	0.00
16,400.00	90.00	179.64	10,451.70	-5,514.32	-374.22	5,523.82	0.00	0.00	0.00
16,500.00	90.00	179.64	10,451.70	-5,614.32	-373.59	5,623.74	0.00	0.00	0.00
16,600.00	90.00	179.64	10,451.70	-5,714.32	-372.97	5,723.66	0.00	0.00	0.00
16,700.00	90.00	179.64	10,451.70	-5,814.31	-372.34	5,823.58	0.00	0.00	0.00
16,800.00	90.00	179.64	10,451.70	-5,914.31	-371.72	5,923.50	0.00	0.00	0.00
16,900.00	90.00	179.64	10,451.70	-6,014.31	-371.09	6,023.42	0.00	0.00	0.00
17,000.00	90.00	179.64	10,451.70	-6,114.31	-370.46	6,123.34	0.00	0.00	0.00
17,100.00	90.00	179.64	10,451.70	-6,214.31	-369.84	6,223.26	0.00	0.00	0.00
17,200.00	90.00	179.64	10,451.70	-6,314.30	-369.21	6,323.18	0.00	0.00	0.00
17,300.00	90.00	179.64	10,451.70	-6,414.30	-368.59	6,423.10	0.00	0.00	0.00
17,400.00	90.00	179.64	10,451.70	-6,514.30	-367.96	6,523.02	0.00	0.00	0.00
17,500.00	90.00	179.64	10,451.70	-6,614.30	-367.33	6,622.94	0.00	0.00	0.00
17,600.00	90.00	179.64	10,451.70	-6,714.30	-366.71	6,722.86	0.00	0.00	0.00
17,700.00	90.00	179.64	10,451.70	-6,814.29	-366.08	6,822.78	0.00	0.00	0.00
17,800.00	90.00	179.64	10,451.70	-6,914.29	-365.46	6,922.70	0.00	0.00	0.00
17,900.00	90.00	179.64	10,451.70	-7,014.29	-364.83	7,022.62	0.00	0.00	0.00
18,000.00	90.00	179.64	10,451.70	-7,114.29	-364.20	7,122.54	0.00	0.00	0.00
18,100.00	90.00	179.64	10,451.70	-7,214.29	-363.58	7,222.45	0.00	0.00	0.00
18,200.00	90.00	179.64	10,451.70	-7,314.28	-362.95	7,322.37	0.00	0.00	0.00
18,300.00	90.00	179.64	10,451.70	-7,414.28	-362.32	7,422.29	0.00	0.00	0.00
18,400.00	90.00	179.64	10,451.70	-7,514.28	-361.70	7,522.21	0.00	0.00	0.00
18,500.00	90.00	179.64	10,451.70	-7,614.28	-361.07	7,622.13	0.00	0.00	0.00
18,600.00	90.00	179.64	10,451.70	-7,714.28	-360.45	7,722.05	0.00	0.00	0.00
18,700.00	90.00	179.64	10,451.70	-7,814.27	-359.82	7,821.97	0.00	0.00	0.00
18,800.00	90.00	179.64	10,451.70	-7,914.27	-359.19	7,921.89	0.00	0.00	0.00
18,900.00	90.00	179.64	10,451.70	-8,014.27	-358.57	8,021.81	0.00	0.00	0.00
19,000.00	90.00	179.64	10,451.70	-8,114.27	-357.94	8,121.73	0.00	0.00	0.00
19,100.00	90.00	179.64	10,451.70	-8,214.27	-357.32	8,221.65	0.00	0.00	0.00
19,200.00	90.00	179.64	10,451.70	-8,314.26	-356.69	8,321.57	0.00	0.00	0.00
19,300.00	90.00	179.64	10,451.70	-8,414.26	-356.06	8,421.49	0.00	0.00	0.00
19,400.00	90.00	179.64	10,451.70	-8,514.26	-355.44	8,521.41	0.00	0.00	0.00
19,500.00	90.00	179.64	10,451.70	-8,614.26	-354.81	8,621.33	0.00	0.00	0.00
19,600.00	90.00	179.64	10,451.70	-8,714.26	-354.19	8,721.25	0.00	0.00	0.00
19,700.00	90.00	179.64	10,451.70	-8,814.26	-353.56	8,821.17	0.00	0.00	0.00
19,800.00	90.00	179.64	10,451.70	-8,914.25	-352.93	8,921.09	0.00	0.00	0.00
19,900.00	90.00	179.64	10,451.70	-9,014.25	-352.31	9,021.01	0.00	0.00	0.00
20,000.00	90.00	179.64	10,451.70	-9,114.25	-351.68	9,120.93	0.00	0.00	0.00
20,100.00	90.00	179.64	10,451.70	-9,214.25	-351.06	9,220.85	0.00	0.00	0.00
20,200.00	90.00	179.64	10,451.70	-9,314.25	-350.43	9,320.77	0.00	0.00	0.00
20,300.00	90.00	179.64	10,451.70	-9,414.24	-349.80	9,420.69	0.00	0.00	0.00
20,400.00	90.00	179.64	10,451.70	-9,514.24	-349.18	9,520.61	0.00	0.00	0.00
20,500.00	90.00	179.64	10,451.70	-9,614.24	-348.55	9,620.53	0.00	0.00	0.00
20,600.00	90.00	179.64	10,451.70	-9,714.24	-347.93	9,720.45	0.00	0.00	0.00
20,700.00	90.00	179.64	10,451.70	-9,814.24	-347.30	9,820.37	0.00	0.00	0.00
20,800.00	90.00	179.64	10,451.70	-9,914.23	-346.67	9,920.29	0.00	0.00	0.00
20,900.00	90.00	179.64	10,451.70	-10,014.23	-346.05	10,020.21	0.00	0.00	0.00
21,000.00	90.00	179.64	10,451.70	-10,114.23	-345.42	10,120.13	0.00	0.00	0.00
21,080.34	90.00	179.64	10,451.70	-10,194.56	-344.92	10,200.40	0.00	0.00	0.00

OXY Planning Report

Database:	HOPSP	Local Co-ordinate Reference:	Well Lost Tank 30_19 Fed Com 22H
Company:	ENGINEERING DESIGNS	TVD Reference:	25' RKB @ 3644.70ft
Project:	PRD NM DIRECTIONAL PLANS (NAD 1983)	MD Reference:	25' RKB @ 3644.70ft
Site:	LOST TANK 30-19 FED	North Reference:	Grid
Well:	Lost Tank 30_19 Fed Com 22H	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Permitting Plan		

Design Targets									
Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(ft)	(ft)	(ft)	(usft)	(usft)		
- Shape									
FTP (Lost Tank 30_19 - plan misses target center by 31.70ft at 10643.65ft MD (10421.63 TVD, 238.64 N, -408.10 E) - Point	0.00	0.00	10,451.70	248.43	-410.30	503,974.91	731,398.10	32.383993	-103.717637
PBHL (Lost Tank - plan hits target center - Point	0.00	0.00	10,451.70	-10,194.56	-344.92	493,532.45	731,463.48	32.355288	-103.717619

Formations						
Measured Depth	Vertical Depth	Name	Lithology	Dip	Dip Direction	
(ft)	(ft)			(°)	(°)	
852.70	852.70	RUSTLER				
1,144.70	1,144.70	SALADO				
2,851.70	2,851.70	CASTILE				
4,598.83	4,598.70	DELAWARE				
4,674.96	4,674.70	BELL CANYON				
5,521.43	5,514.70	CHERRY CANYON				
6,761.74	6,742.70	BRUSHY CANYON				
8,536.36	8,499.70	BONE SPRING				
9,630.21	9,582.70	BONE SPRING 1ST				
10,293.55	10,218.70	BONE SPRING 2ND				

Plan Annotations					
Measured Depth	Vertical Depth	Local Coordinates		Comment	
(ft)	(ft)	+N/-S	+E/-W		
		(ft)	(ft)		
4,305.00	4,305.00	0.00	0.00	Build 1°/100'	
5,112.95	5,110.27	49.02	-28.83	Hold 8° Tangent	
9,860.49	9,810.69	624.22	-367.02	KOP, Build & Turn 10°/100'	
10,830.34	10,451.70	55.24	-409.09	Landing Point	
21,080.34	10,451.70	-10,194.56	-344.92	TD at 21080.34' MD	



Special Data Sheet

TH DS-20.0359
12 August 2020
Rev 00

**5.500" 20.00 lb/ft P110-CY
TenarisHydril Wedge 461™ Matched
Strength**

Nominal OD	5.500 in.	Wall Thickness	0.361 in.	Grade	P110-CY
Min Wall Thickness	87.5%	Type	CASING	Connection OD Option	MATCHED STRENGTH

Pipe Body Data

Geometry			Performance		
Nominal OD	5.500 in.	Nominal ID	4.778 in.	Body Yield Strength	641 x 1000 lbs
Nominal Weight	20.00 lbs/ft	Wall Thickness	0.361 in.	Internal Yield	12640 psi
Standard Drift Diameter	4.653 in.	Plain End Weight	19.83 lbs/ft	SMYS	110000 psi
Special Drift Diameter	N/A	OD Tolerance	API	Collapse Pressure	11110 psi

Connection Data

Geometry		Performance		Make-up Torques	
Matched Strength OD	6.050 in.	Tension Efficiency	100%	Minimum	17000 ft-lbs
Make-up Loss	3.775 in.	Joint Yield Strength	641 x 1000 lbs	Optimum	18000 ft-lbs
Threads per in.	3.40	Internal Yield	12640 psi	Maximum	21600 ft-lbs
Connection OD Option	MATCHED STRENGTH	Compression Efficiency	100%	Operational Limit Torques	
Coupling Length	7.714 in.	Compression Strength	641 x 1000 lbs	Operating Torque	32000 ft-lbs
		Bending	92 °/100 ft	Yield Torque	38000 ft-lbs
		Collapse	11110 psi	Buck-On Torques	
				Minimum	21600 ft-lbs
				Maximum	23100 ft-lbs

Notes

*If you need to use torque values that are higher than the maximum indicated, please contact a local Tenaris technical sales representative

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
11 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

AMENDED REPORT


WELL LOCATION AND ACREAGE DEDICATION PLAT

Table with 3 columns: 1 API Number (30-025-47543), 2 Pool Code (97366), 3 Pool Name (Bilbrey Basin; Bone Spring), 4 Property Code (322423), 5 Property Name (LOST TANK 30-19 FED COM), 6 Well Number (22H), 7 OGRID No. (16696), 8 Operator Name (OXY USA INC.), 9 Elevation (3619.7')

10 Surface Location table with columns: UL or lot no. (C), Section (19), Township (22S), Range (32E), Lot Idn, Feet from the (353), North/South line (NORTH), Feet from the (2049), East/West line (WEST), County (LEA)

11 Bottom Hole Location If Different From Surface table with columns: UL or lot no. (N), Section (30), Township (22S), Range (32E), Lot Idn, Feet from the (20), North/South line (SOUTH), Feet from the (1640), East/West line (WEST), County (LEA). Includes 12 Dedicated Acres (640), 13 Joint or Infill, 14 Consolidation Code, 15 Order No.

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.




HSU COORDINATES table with columns: POINT, NORTHING, EASTING (NAD 27 N.M. STATE PLANE, EAST ZONE), NORTHING, EASTING (NAD 83 N.M. STATE PLANE, EAST ZONE). Rows A through H.




SCALE
DRAWN BY: D.J.S. 08-01-23
REV: 1 D.J.S. 08-09-23
(UPDATED DISTANCE LABEL)

Detail "A" No Scale



Detail "B" No Scale



LINE TABLE with columns: LINE, DIRECTION, LENGTH. Lists lines L1 through L20 with their respective bearings and lengths.

17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Sarah McKinney 10/24/23
Signature Date


Sarah McKinney
Printed Name

sarah_mckinney@oxy.com
E-mail Address

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

July 18, 2023
Date of Survey
Signature and Seal of Professional Surveyor:



Certificate Number:

- = SURFACE HOLE LOCATION
- ◆ = KICK OFF POINT/TAKE POINTS
- ◇ = LEASE CROSSING
- = BOTTOM HOLE LOCATION
- ▲ = SECTION CORNER LOCATED
- = LEASE LINE
- = HORIZONTAL SPACING UNIT
- N.O.W. = NORTH OF WELL.
- S.O.W. = SOUTH OF WELL.
- W.O.W. = WEST OF WELL.

NAD 83 (SURFACE HOLE LOCATION)
LATITUDE = 32°22'59.89" (32.383303°)
LONGITUDE = -103°42'58.72" (-103.716312°)
NAD 27 (SURFACE HOLE LOCATION)
LATITUDE = 32°22'59.45" (32.383180°)
LONGITUDE = -103°42'56.96" (-103.715824°)
STATE PLANE NAD 83 (N.M. EAST)
N: 503726.49' E: 731808.38'
STATE PLANE NAD 27 (N.M. EAST)
N: 503666.08' E: 690625.98'

NAD 83 (KICK OFF POINT)
LATITUDE = 32°22'11.11" (32.369751°)
LONGITUDE = -103°43'03.46" (-103.717628°)
NAD 27 (KICK OFF POINT)
LATITUDE = 32°22'10.66" (32.369629°)
LONGITUDE = -103°43'01.70" (-103.717140°)
STATE PLANE NAD 83 (N.M. EAST)
N: 504374.83' E: 731395.89'
STATE PLANE NAD 27 (N.M. EAST)
N: 504314.40' E: 690213.51'

NAD 83 (LEASE CROSSING 1)
LATITUDE = 32°23'03.36" (32.384267°)
LONGITUDE = -103°43'03.49" (-103.717636°)
NAD 27 (LEASE CROSSING 1)
LATITUDE = 32°23'02.92" (32.384145°)
LONGITUDE = -103°43'01.73" (-103.717148°)
STATE PLANE NAD 83 (N.M. EAST)
N: 504074.89' E: 731397.55'
STATE PLANE NAD 27 (N.M. EAST)
N: 504014.47' E: 690215.16'

NAD 83 (FIRST TAKE POINT)
LATITUDE = 32°23'02.37" (32.383992°)
LONGITUDE = -103°43'03.49" (-103.717636°)
NAD 27 (FIRST TAKE POINT)
LATITUDE = 32°23'01.93" (32.383870°)
LONGITUDE = -103°43'01.73" (-103.717148°)
STATE PLANE NAD 83 (N.M. EAST)
N: 503974.91' E: 731398.10'
STATE PLANE NAD 27 (N.M. EAST)
N: 503914.49' E: 690215.71'

NAD 83 (LEASE CROSSING 2)
LATITUDE = 32°22'37.23" (32.377007°)
LONGITUDE = -103°43'03.48" (-103.717632°)
NAD 27 (LEASE CROSSING 2)
LATITUDE = 32°22'36.78" (32.376884°)
LONGITUDE = -103°43'01.72" (-103.717144°)
STATE PLANE NAD 83 (N.M. EAST)
N: 501433.63' E: 731413.97'
STATE PLANE NAD 27 (N.M. EAST)
N: 501373.28' E: 690231.51'

NAD 83 (LEASE CROSSING 3)
LATITUDE = 32°22'11.11" (32.369751°)
LONGITUDE = -103°43'03.46" (-103.717628°)
NAD 27 (LEASE CROSSING 3)
LATITUDE = 32°22'10.66" (32.369629°)
LONGITUDE = -103°43'01.70" (-103.717140°)
STATE PLANE NAD 83 (N.M. EAST)
N: 498794.07' E: 731430.45'
STATE PLANE NAD 27 (N.M. EAST)
N: 498733.79' E: 690247.92'

NAD 83 (LAST TAKE POINT)
LATITUDE = 32°21'19.83" (32.355508°)
LONGITUDE = -103°43'03.43" (-103.717620°)
NAD 27 (LAST TAKE POINT)
LATITUDE = 32°21'19.39" (32.355385°)
LONGITUDE = -103°43'01.68" (-103.717133°)
STATE PLANE NAD 83 (N.M. EAST)
N: 493612.44' E: 731462.80'
STATE PLANE NAD 27 (N.M. EAST)
N: 493552.30' E: 690280.11'

NAD 83 (BOTTOM HOLE LOCATION)
LATITUDE = 32°21'19.04" (32.355288°)
LONGITUDE = -103°43'03.43" (-103.717619°)
NAD 27 (BOTTOM HOLE LOCATION)
LATITUDE = 32°21'18.60" (32.355166°)
LONGITUDE = -103°43'01.67" (-103.717132°)
STATE PLANE NAD 83 (N.M. EAST)
N: 493532.45' E: 731463.48'
STATE PLANE NAD 27 (N.M. EAST)
N: 493472.31' E: 690280.79'

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 326866

CONDITIONS

Operator: OXY USA INC P.O. Box 4294 Houston, TX 772104294	OGRID: 16696
	Action Number: 326866
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	4/11/2024