

District I

1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011

Permit 367107

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address MATADOR PRODUCTION COMPANY One Lincoln Centre Dallas, TX 75240		2. OGRID Number 228937
		3. API Number 30-025-53138
4. Property Code 334167	5. Property Name BARBARA 29 17S 37E State	6. Well No. 002

7. Surface Location

UL - Lot P	Section 29	Township 17S	Range 37E	Lot Idn P	Feet From 371	N/S Line S	Feet From 301	E/W Line E	County Lea
---------------	---------------	-----------------	--------------	--------------	------------------	---------------	------------------	---------------	---------------

8. Proposed Bottom Hole Location

UL - Lot P	Section 29	Township 17S	Range 37E	Lot Idn P	Feet From 330	N/S Line S	Feet From 394	E/W Line E	County Lea
---------------	---------------	-----------------	--------------	--------------	------------------	---------------	------------------	---------------	---------------

9. Pool Information

MIDWAY;STRAWN, SOUTH	96346
----------------------	-------

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3767
16. Multiple N	17. Proposed Depth 11365	18. Formation Strawn	19. Contractor	20. Spud Date 10/1/2024
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

☒ We will be using a closed-loop system in lieu of lined pits

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	14.75	9.625	36	2132	2060	0
Prod	8.75	5.5	17	11365	2175	0

Casing/Cement Program: Additional Comments

--

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	5000	3000	Cameron
Double Ram	10000	5000	Cameron
Pipe	10000	5000	Cameron

23. I hereby certify that the information given above is true and complete to the best of my knowledge and belief.
I further certify I have complied with 19.15.14.9 (A) NMAC ☒ and/or 19.15.14.9 (B) NMAC ☒ if applicable.

Signature:

Printed Name: Electronically filed by Brett A Jennings

Title: Regulatory Analyst

Email Address: brett.jennings@matadorresources.com

Date: 6/12/2024

Phone: 972-629-2160

OIL CONSERVATION DIVISION

Approved By: Paul F Kautz

Title: Geologist

Approved Date: 7/3/2024

Expiration Date: 7/3/2026

Conditions of Approval Attached

DISTRICT I
1625 N. FRENCH DR., BOBBS, NM 86240
Phone: (575) 393-6161 Fax: (575) 393-0720

DISTRICT II
611 S. FIRST ST., ARTESIA, NM 86210
Phone: (505) 748-1283 Fax: (505) 748-0720

DISTRICT III
1000 RIO BRAZOS RD., AZTEC, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number	Pool Code 96346	Pool Name Midway; Strawn, South
Property Code	Property Name BARBARA 29-17S-37E STATE	Well Number 2
OGRID No. 228937	Operator Name MATADOR PRODUCTION COMPANY	Elevation 3766.8'

Surface Location


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	29	17-S	37-E		371	SOUTH	301	EAST	LEA

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	29	17-S	37-E		330	SOUTH	394	EAST	LEA

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
40			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

		<p>NAD 27 NME <u>BOTTOM</u> <u>HOLE LOCATION</u> Y=656162.4 N X=828000.0 E LAT.=32.799330° N LONG.=103.265913° W</p>		<p>NAD 27 NME <u>SURFACE LOCATION</u> Y=656204.1 N X=828093.0 E LAT.=32.799442° N LONG.=103.265608° W</p>		<p>OPERATOR CERTIFICATION I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. Signature <u>Reece Clark</u> Date <u>5/22/24</u> Printed Name <u>Reece Clark</u> E-mail Address <u>reece.clark@msi-intelligence.com</u></p>																							
		<p>NAD 83 NME <u>BOTTOM</u> <u>HOLE LOCATION</u> Y=656224.9 N X=869179.2 E LAT.=32.799447° N LONG.=103.266403° W</p>		<p>NAD 83 NME <u>SURFACE LOCATION</u> Y=656266.6 N X=869272.3 E LAT.=32.799559° N LONG.=103.266099° W</p>			<p>SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. Date of Survey <u>MAY 3, 2024</u> Signature & Seal of Professional Surveyor  Certificate No. <u>CHAD HARCROW 17777</u> W.O. #24-498 DRAWN BY: WN</p>																						
<p>POINT LEGEND NAD 27</p> <table border="1"> <tr><td>1</td><td>Y=657157.5 N</td></tr> <tr><td>X=828390.2 E</td></tr> <tr><td>2</td><td>Y=657149.4 N</td></tr> <tr><td>X=827065.0 E</td></tr> <tr><td>3</td><td>Y=655826.5 N</td></tr> <tr><td>X=827076.3 E</td></tr> <tr><td>4</td><td>Y=655834.9 N</td></tr> <tr><td>X=828395.3 E</td></tr> </table>		1	Y=657157.5 N	X=828390.2 E	2			Y=657149.4 N	X=827065.0 E	3	Y=655826.5 N	X=827076.3 E	4	Y=655834.9 N	X=828395.3 E	<p>POINT LEGEND NAD 83</p> <table border="1"> <tr><td>1</td><td>Y=657220.1 N</td></tr> <tr><td>X=869569.4 E</td></tr> <tr><td>2</td><td>Y=657212.1 N</td></tr> <tr><td>X=868244.2 E</td></tr> <tr><td>3</td><td>Y=655889.1 N</td></tr> <tr><td>X=868255.6 E</td></tr> <tr><td>4</td><td>Y=655897.4 N</td></tr> <tr><td>X=869574.5 E</td></tr> </table>		1	Y=657220.1 N	X=869569.4 E	2	Y=657212.1 N	X=868244.2 E	3	Y=655889.1 N	X=868255.6 E	4	Y=655897.4 N	X=869574.5 E
1	Y=657157.5 N																												
X=828390.2 E																													
2	Y=657149.4 N																												
X=827065.0 E																													
3	Y=655826.5 N																												
X=827076.3 E																													
4	Y=655834.9 N																												
X=828395.3 E																													
1	Y=657220.1 N																												
X=869569.4 E																													
2	Y=657212.1 N																												
X=868244.2 E																													
3	Y=655889.1 N																												
X=868255.6 E																													
4	Y=655897.4 N																												
X=869574.5 E																													

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form APD Conditions
Permit 367107

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address: MATADOR PRODUCTION COMPANY [228937] One Lincoln Centre Dallas, TX 75240	API Number: 30-025-53138
	Well: BARBARA 29 17S 37E State #002

OCD Reviewer	Condition
pkautz	Notify OCD 24 hours prior to casing & cement
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system
pkautz	Cement is required to circulate on both surface and production strings of casing
pkautz	If cement does not circulate on any string, a CBL is required for that string of casing
pkautz	The Operator is to notify NMOCD by sundry (Form C-103) within ten (10) days of the well being spud

Addendum to Natural Gas Management Plan for Matador's

Barbara 29-17S-37E State #2

VI. Separation Equipment

Flow from the wells will be routed via a flowline through well test to either a 36"x15' three phase separator or a 72"x20' three phase heater treater. The first stage separator and heater treater are sized with input from BRE ProMax and API 12J. Expected production from the Barbara State #2 well is approximately 500 mcf/d, 250 bopd, and 80 bwpd. Liquid retention times at expected maximum rates will be >3 minutes. Hydrocarbon liquids are dumped from the first stage separator and commingled to one or more heater treaters. Gas will be routed from the heater treater to sales. The gas from the heater treater(s) could either be sent to sales or routed to a compressor if the sales line pressure is higher than the MAWP of the heater treater (125 psi). From the heater treater, hydrocarbon liquid and water will be routed to the tanks where vapor is compressed by a VRU if technically feasible to either sales or a compressor if the sales line pressure is higher than the VRU's maximum discharge pressure (~150 psi). Therefore, Matador has sized our separation equipment to optimize gas capture and our separation equipment is of sufficient size to handle the expected volumes of gas.

VII. Operation Practices

Although not a complete recitation of all our efforts to comply with a subsection A through F of 19.15.27.8 NMAC, a summary is as follows. During drilling, Matador will have a properly sized flare stack at least 100 feet from the nearest surface hole. During initial flowback we will route the flowback fluids into completion or storage tanks and, to the extent possible, flare rather than vent any gas. We will commence operation of the heater treater as soon as technically feasible, and have instructed our team that we want to connect the gas to sales as soon as possible but not later than 30 days after initial flowback.

Regarding production operations, we have designed our production facilities to be compliant with the requirements of Part E of 19.15.27.8 NMAC. We will instruct our team to perform the AVOs on the frequency required under the rules. While the well is producing, we will take steps to minimize flaring during maintenance, as set forth below, and we have a process in place for the measuring of any flared gas and the reporting of any reportable flaring events.

VII. Best Management Practices

Steps are taken to minimize venting during active or planned maintenance when technically feasible including:

- Isolating the affected component and reducing pressure through process piping
- Blowing down the equipment being maintained to a control device
- Performing preventative maintenance and minimizing the duration of maintenance activities
- Shutting in sources of supply as possible
- Other steps that are available depending on the maintenance being performed

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Electronically
Via E-permitting

NATURAL GAS MANAGEMENT PLAN

This Natural Gas Management Plan must be submitted with each Application for Permit to Drill (APD) for a new or recompleted well.

Section 1 – Plan Description

Effective May 25, 2021

I. Operator: Matador Production Company **OGRID:** 228937 **Date:** 6/5/2024

II. Type: ☒ Original ☐ Amendment due to ☐ 19.15.27.9.D(6)(a) NMAC ☐ 19.15.27.9.D(6)(b) NMAC ☐ Other.

If Other, please describe: _____

III. Well(s): Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	ULSTR	Footages	Anticipated Oil BBL/D	Anticipated Gas MCF/D	Anticipated Produced Water BBL/D
Barbara 29-17S-37 State #2	TBD	UL-P Sec 29 T17S R37E	371' FSL 301' FEL	250	500	80

IV. Central Delivery Point Name: Barbara TB [See 19.15.27.9(D)(1) NMAC]

V. Anticipated Schedule: Provide the following information for each new or recompleted well or set of wells proposed to be drilled or proposed to be recompleted from a single well pad or connected to a central delivery point.

Well Name	API	Spud Date	TD Reached Date	Completion Commencement Date	Initial Flow Back Date	First Production Date
Barbara 29-17S-37 State #2	TBD	10/1/2024	10/20/2024	11/15/2024	11/15/2024	11/15/2024

VI. Separation Equipment: ☒ Attach a complete description of how Operator will size separation equipment to optimize gas capture.

VII. Operational Practices: ☒ Attach a complete description of the actions Operator will take to comply with the requirements of Subsection A through F of 19.15.27.8 NMAC.

VIII. Best Management Practices: ☒ Attach a complete description of Operator's best management practices to minimize venting during active and planned maintenance.

Section 2 – Enhanced Plan
EFFECTIVE APRIL 1, 2022

Beginning April 1, 2022, an operator that is not in compliance with its statewide natural gas capture requirement for the applicable reporting area must complete this section.

☒ Operator certifies that it is not required to complete this section because Operator is in compliance with its statewide natural gas capture requirement for the applicable reporting area.

IX. Anticipated Natural Gas Production:

Well	API	Anticipated Average Natural Gas Rate MCF/D	Anticipated Volume of Natural Gas for the First Year MCF

X. Natural Gas Gathering System (NGGS):

Operator	System	ULSTR of Tie-in	Anticipated Gathering Start Date	Available Maximum Daily Capacity of System Segment Tie-in

XI. Map. ☐ Attach an accurate and legible map depicting the location of the well(s), the anticipated pipeline route(s) connecting the production operations to the existing or planned interconnect of the natural gas gathering system(s), and the maximum daily capacity of the segment or portion of the natural gas gathering system(s) to which the well(s) will be connected.

XII. Line Capacity. The natural gas gathering system ☐ will ☐ will not have capacity to gather 100% of the anticipated natural gas production volume from the well prior to the date of first production.

XIII. Line Pressure. Operator ☐ does ☐ does not anticipate that its existing well(s) connected to the same segment, or portion, of the natural gas gathering system(s) described above will continue to meet anticipated increases in line pressure caused by the new well(s).

☐ Attach Operator's plan to manage production in response to the increased line pressure.

XIV. Confidentiality: ☐ Operator asserts confidentiality pursuant to Section 71-2-8 NMSA 1978 for the information provided in Section 2 as provided in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and attaches a full description of the specific information for which confidentiality is asserted and the basis for such assertion.

Section 3 - Certifications**Effective May 25, 2021**

Operator certifies that, after reasonable inquiry and based on the available information at the time of submittal:

☒ Operator will be able to connect the well(s) to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system; or

☐ Operator will not be able to connect to a natural gas gathering system in the general area with sufficient capacity to transport one hundred percent of the anticipated volume of natural gas produced from the well(s) commencing on the date of first production, taking into account the current and anticipated volumes of produced natural gas from other wells connected to the pipeline gathering system.

If Operator checks this box, Operator will select one of the following:

Well Shut-In. ☐ Operator will shut-in and not produce the well until it submits the certification required by Paragraph (4) of Subsection D of 19.15.27.9 NMAC; or

Venting and Flaring Plan. ☐ Operator has attached a venting and flaring plan that evaluates and selects one or more of the potential alternative beneficial uses for the natural gas until a natural gas gathering system is available, including:

- (a) power generation on lease;
- (b) power generation for grid;
- (c) compression on lease;
- (d) liquids removal on lease;
- (e) reinjection for underground storage;
- (f) reinjection for temporary storage;
- (g) reinjection for enhanced oil recovery;
- (h) fuel cell production; and
- (i) other alternative beneficial uses approved by the division.

Section 4 - Notices


1. If, at any time after Operator submits this Natural Gas Management Plan and before the well is spud:

(a) Operator becomes aware that the natural gas gathering system it planned to connect the well(s) to has become unavailable or will not have capacity to transport one hundred percent of the production from the well(s), no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised venting and flaring plan containing the information specified in Paragraph (5) of Subsection D of 19.15.27.9 NMAC; or

(b) Operator becomes aware that it has, cumulatively for the year, become out of compliance with its baseline natural gas capture rate or natural gas capture requirement, no later than 20 days after becoming aware of such information, Operator shall submit for OCD's approval a new or revised Natural Gas Management Plan for each well it plans to spud during the next 90 days containing the information specified in Paragraph (2) of Subsection D of 19.15.27.9 NMAC, and shall file an update for each Natural Gas Management Plan until Operator is back in compliance with its baseline natural gas capture rate or natural gas capture requirement.

2. OCD may deny or conditionally approve an APD if Operator does not make a certification, fails to submit an adequate venting and flaring plan which includes alternative beneficial uses for the anticipated volume of natural gas produced, or if OCD determines that Operator will not have adequate natural gas takeaway capacity at the time a well will be spud.

I certify that, after reasonable inquiry, the statements in and attached to this Natural Gas Management Plan are true and correct to the best of my knowledge and acknowledge that a false statement may be subject to civil and criminal penalties under the Oil and Gas Act.

Signature: 
Printed Name: Mark Gonzales
Title: Facilities Engineer
E-mail Address: mark.gonzales@matadorresources.com
Date: 6/5/2024
Phone: (915) 240-3468
OIL CONSERVATION DIVISION (Only applicable when submitted as a standalone form)
Approved By:
Title:
Approval Date:
Conditions of Approval:

Matador Production Company

Twin Lakes

Barbara

Barbara State #2

Wellbore #1

Plan: State Plan #1

Standard Planning Report

03 June, 2024

Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Barbara State #2
Company:	Matador Production Company	TVD Reference:	KB @ 3795.3usft
Project:	Twin Lakes	MD Reference:	KB @ 3795.3usft
Site:	Barbara	North Reference:	Grid
Well:	Barbara State #2	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	State Plan #1		

Project	Twin Lakes		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		Using geodetic scale factor

Site	Barbara		
Site Position:		Northing:	656,204.14 usft
From:	Lat/Long	Easting:	828,093.19 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "
		Latitude:	32° 47' 57.991 N
		Longitude:	103° 15' 56.189 W
		Grid Convergence:	0.58 °

Well	Barbara State #2		
Well Position	+N/-S	0.0 usft	Northing:
	+E/-W	0.0 usft	Easting:
Position Uncertainty	0.0 usft	Wellhead Elevation:	
		Latitude:	32° 47' 57.991 N
		Longitude:	103° 15' 56.189 W
		Ground Level:	3,766.8 usft

Wellbore	Wellbore #1		
Magnetics	Model Name	Sample Date	Declination
			(°)
	IGRF2015	6/3/2024	6.08
			Dip Angle
			(°)
			60.53
			Field Strength
			(nT)
			47,584.63252766

Design	State Plan #1		
Audit Notes:			
Version:	Phase:	PROTOTYPE	Tie On Depth:
			0.0
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W
	(usft)	(usft)	(usft)
	0.0	0.0	0.0
			Direction
			(°)
			0.00

Plan Survey Tool Program	Date	6/3/2024		
Depth From	Depth To			
(usft)	(usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.0	11,365.8	State Plan #1 (Wellbore #1)	MWD
				OWSG MWD - Standard

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(usft)	(usft)	Rate	Rate	Rate	(°)	
(usft)			(usft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,600.0	2.00	245.92	2,600.0	-1.4	-3.2	1.00	1.00	0.00	245.92	
5,362.4	2.00	245.92	5,360.7	-40.8	-91.2	0.00	0.00	0.00	0.00	
5,495.8	0.00	0.00	5,494.0	-41.7	-93.3	1.50	-1.50	0.00	180.00	
9,001.8	0.00	0.00	9,000.0	-41.7	-93.3	0.00	0.00	0.00	0.00	VP - Barabara State #
11,365.8	0.00	0.00	11,364.0	-41.7	-93.3	0.00	0.00	0.00	0.00	BHL - Barbara State #

Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Barbara State #2
Company:	Matador Production Company	TVD Reference:	KB @ 3795.3usft
Project:	Twin Lakes	MD Reference:	KB @ 3795.3usft
Site:	Barbara	North Reference:	Grid
Well:	Barbara State #2	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	State Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	0.00	0.00	300.0	0.0	0.0	0.0	0.00	0.00	0.00
400.0	0.00	0.00	400.0	0.0	0.0	0.0	0.00	0.00	0.00
500.0	0.00	0.00	500.0	0.0	0.0	0.0	0.00	0.00	0.00
600.0	0.00	0.00	600.0	0.0	0.0	0.0	0.00	0.00	0.00
700.0	0.00	0.00	700.0	0.0	0.0	0.0	0.00	0.00	0.00
800.0	0.00	0.00	800.0	0.0	0.0	0.0	0.00	0.00	0.00
900.0	0.00	0.00	900.0	0.0	0.0	0.0	0.00	0.00	0.00
1,000.0	0.00	0.00	1,000.0	0.0	0.0	0.0	0.00	0.00	0.00
1,100.0	0.00	0.00	1,100.0	0.0	0.0	0.0	0.00	0.00	0.00
1,200.0	0.00	0.00	1,200.0	0.0	0.0	0.0	0.00	0.00	0.00
1,300.0	0.00	0.00	1,300.0	0.0	0.0	0.0	0.00	0.00	0.00
1,400.0	0.00	0.00	1,400.0	0.0	0.0	0.0	0.00	0.00	0.00
1,500.0	0.00	0.00	1,500.0	0.0	0.0	0.0	0.00	0.00	0.00
1,600.0	0.00	0.00	1,600.0	0.0	0.0	0.0	0.00	0.00	0.00
1,700.0	0.00	0.00	1,700.0	0.0	0.0	0.0	0.00	0.00	0.00
1,800.0	0.00	0.00	1,800.0	0.0	0.0	0.0	0.00	0.00	0.00
1,900.0	0.00	0.00	1,900.0	0.0	0.0	0.0	0.00	0.00	0.00
2,000.0	0.00	0.00	2,000.0	0.0	0.0	0.0	0.00	0.00	0.00
2,082.0	0.00	0.00	2,082.0	0.0	0.0	0.0	0.00	0.00	0.00
Rustler									
2,100.0	0.00	0.00	2,100.0	0.0	0.0	0.0	0.00	0.00	0.00
2,200.0	0.00	0.00	2,200.0	0.0	0.0	0.0	0.00	0.00	0.00
2,300.0	0.00	0.00	2,300.0	0.0	0.0	0.0	0.00	0.00	0.00
2,400.0	0.00	0.00	2,400.0	0.0	0.0	0.0	0.00	0.00	0.00
Start Build 1.00									
2,500.0	1.00	245.92	2,500.0	-0.4	-0.8	-0.4	1.00	1.00	0.00
2,600.0	2.00	245.92	2,600.0	-1.4	-3.2	-1.4	1.00	1.00	0.00
Start 2759.6 hold at 2600.0 MD									
2,700.0	2.00	245.92	2,699.9	-2.8	-6.4	-2.8	0.00	0.00	0.00
2,800.0	2.00	245.92	2,799.8	-4.3	-9.6	-4.3	0.00	0.00	0.00
2,900.0	2.00	245.92	2,899.8	-5.7	-12.7	-5.7	0.00	0.00	0.00
3,000.0	2.00	245.92	2,999.7	-7.1	-15.9	-7.1	0.00	0.00	0.00
3,100.0	2.00	245.92	3,099.7	-8.5	-19.1	-8.5	0.00	0.00	0.00
3,200.0	2.00	245.92	3,199.6	-10.0	-22.3	-10.0	0.00	0.00	0.00
3,205.4	2.00	245.92	3,205.0	-10.0	-22.5	-10.0	0.00	0.00	0.00
Base salt/Top Artesia group									
3,300.0	2.00	245.92	3,299.5	-11.4	-25.5	-11.4	0.00	0.00	0.00
3,400.0	2.00	245.92	3,399.5	-12.8	-28.7	-12.8	0.00	0.00	0.00
3,500.0	2.00	245.92	3,499.4	-14.2	-31.9	-14.2	0.00	0.00	0.00
3,600.0	2.00	245.92	3,599.4	-15.7	-35.1	-15.7	0.00	0.00	0.00
3,700.0	2.00	245.92	3,699.3	-17.1	-38.2	-17.1	0.00	0.00	0.00
3,800.0	2.00	245.92	3,799.2	-18.5	-41.4	-18.5	0.00	0.00	0.00
3,900.0	2.00	245.92	3,899.2	-19.9	-44.6	-19.9	0.00	0.00	0.00
4,000.0	2.00	245.92	3,999.1	-21.4	-47.8	-21.4	0.00	0.00	0.00
4,100.0	2.00	245.92	4,099.0	-22.8	-51.0	-22.8	0.00	0.00	0.00
4,200.0	2.00	245.92	4,199.0	-24.2	-54.2	-24.2	0.00	0.00	0.00
4,300.0	2.00	245.92	4,298.9	-25.6	-57.4	-25.6	0.00	0.00	0.00
4,400.0	2.00	245.92	4,398.9	-27.1	-60.5	-27.1	0.00	0.00	0.00
4,500.0	2.00	245.92	4,498.8	-28.5	-63.7	-28.5	0.00	0.00	0.00
4,600.0	2.00	245.92	4,598.7	-29.9	-66.9	-29.9	0.00	0.00	0.00

Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Barbara State #2
Company:	Matador Production Company	TVD Reference:	KB @ 3795.3usft
Project:	Twin Lakes	MD Reference:	KB @ 3795.3usft
Site:	Barbara	North Reference:	Grid
Well:	Barbara State #2	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	State Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,700.0	2.00	245.92	4,698.7	-31.3	-70.1	-31.3	0.00	0.00	0.00
4,800.0	2.00	245.92	4,798.6	-32.7	-73.3	-32.7	0.00	0.00	0.00
4,900.0	2.00	245.92	4,898.6	-34.2	-76.5	-34.2	0.00	0.00	0.00
5,000.0	2.00	245.92	4,998.5	-35.6	-79.7	-35.6	0.00	0.00	0.00
5,100.0	2.00	245.92	5,098.4	-37.0	-82.8	-37.0	0.00	0.00	0.00
5,200.0	2.00	245.92	5,198.4	-38.4	-86.0	-38.4	0.00	0.00	0.00
5,300.0	2.00	245.92	5,298.3	-39.9	-89.2	-39.9	0.00	0.00	0.00
5,359.6	2.00	245.92	5,357.9	-40.7	-91.1	-40.7	0.00	0.00	0.00
Start Drop -1.50									
5,362.4	2.00	245.92	5,360.7	-40.8	-91.2	-40.8	0.00	0.00	0.00
5,400.0	1.44	245.92	5,398.3	-41.2	-92.2	-41.2	1.50	-1.50	0.00
5,417.7	1.17	245.92	5,416.0	-41.4	-92.6	-41.4	1.50	-1.50	0.00
San Andres									
5,492.9	0.04	245.92	5,491.2	-41.7	-93.3	-41.7	1.50	-1.50	0.00
Start 5872.8 hold at 5492.9 MD									
5,495.8	0.00	0.00	5,494.0	-41.7	-93.3	-41.7	1.50	-1.50	0.00
5,500.0	0.00	0.00	5,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
5,600.0	0.00	0.00	5,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
5,700.0	0.00	0.00	5,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
5,800.0	0.00	0.00	5,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
5,900.0	0.00	0.00	5,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,000.0	0.00	0.00	5,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,100.0	0.00	0.00	6,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,200.0	0.00	0.00	6,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,300.0	0.00	0.00	6,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,400.0	0.00	0.00	6,398.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,500.0	0.00	0.00	6,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,600.0	0.00	0.00	6,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,700.0	0.00	0.00	6,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,800.0	0.00	0.00	6,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
6,900.0	0.00	0.00	6,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,000.0	0.00	0.00	6,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,100.0	0.00	0.00	7,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,200.0	0.00	0.00	7,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,300.0	0.00	0.00	7,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,400.0	0.00	0.00	7,398.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,500.0	0.00	0.00	7,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,600.0	0.00	0.00	7,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,638.8	0.00	0.00	7,637.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
First Bone Spring									
7,700.0	0.00	0.00	7,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,800.0	0.00	0.00	7,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
7,900.0	0.00	0.00	7,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,000.0	0.00	0.00	7,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,100.0	0.00	0.00	8,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,200.0	0.00	0.00	8,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,300.0	0.00	0.00	8,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,398.8	0.00	0.00	8,397.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Second Bone Spring									
8,400.0	0.00	0.00	8,398.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,500.0	0.00	0.00	8,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,600.0	0.00	0.00	8,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,700.0	0.00	0.00	8,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00

Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Barbara State #2
Company:	Matador Production Company	TVD Reference:	KB @ 3795.3usft
Project:	Twin Lakes	MD Reference:	KB @ 3795.3usft
Site:	Barbara	North Reference:	Grid
Well:	Barbara State #2	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	State Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,800.0	0.00	0.00	8,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
8,900.0	0.00	0.00	8,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,000.0	0.00	0.00	8,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,001.8	0.00	0.00	9,000.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
VP - Barabara State #2									
9,100.0	0.00	0.00	9,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,200.0	0.00	0.00	9,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,208.8	0.00	0.00	9,207.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Third Bone Carb									
9,300.0	0.00	0.00	9,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,400.0	0.00	0.00	9,398.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,500.0	0.00	0.00	9,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,546.8	0.00	0.00	9,545.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Third Bone Spring									
9,600.0	0.00	0.00	9,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,700.0	0.00	0.00	9,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,756.8	0.00	0.00	9,755.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Wolfcamp A									
9,800.0	0.00	0.00	9,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
9,900.0	0.00	0.00	9,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,000.0	0.00	0.00	9,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,100.0	0.00	0.00	10,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,200.0	0.00	0.00	10,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,300.0	0.00	0.00	10,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,400.0	0.00	0.00	10,398.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,500.0	0.00	0.00	10,498.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,526.8	0.00	0.00	10,525.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Penn Shale									
10,600.0	0.00	0.00	10,598.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,671.8	0.00	0.00	10,670.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Strawn									
10,700.0	0.00	0.00	10,698.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,800.0	0.00	0.00	10,798.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,900.0	0.00	0.00	10,898.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
10,915.8	0.00	0.00	10,914.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
Atoka									
11,000.0	0.00	0.00	10,998.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
11,100.0	0.00	0.00	11,098.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
11,200.0	0.00	0.00	11,198.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
11,300.0	0.00	0.00	11,298.2	-41.7	-93.3	-41.7	0.00	0.00	0.00
11,365.7	0.00	0.00	11,364.0	-41.7	-93.3	-41.7	0.00	0.00	0.00
TD at 11365.7 - BHL - Barbara State #2									

Planning Report

Database:	EDM 5000.14 Single User Db	Local Co-ordinate Reference:	Well Barbara State #2
Company:	Matador Production Company	TVD Reference:	KB @ 3795.3usft
Project:	Twin Lakes	MD Reference:	KB @ 3795.3usft
Site:	Barbara	North Reference:	Grid
Well:	Barbara State #2	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	State Plan #1		

Design Targets									
Target Name									
- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
VP - Barabara State #2	0.00	0.00	9,000.0	-41.7	-93.3	656,162.45	827,999.88	32° 47' 57.588 N	103° 15' 57.287 W
- plan hits target center									
- Point									
BHL - Barbara State #2	0.00	0.00	11,364.0	-41.7	-93.3	656,162.40	827,999.88	32° 47' 57.588 N	103° 15' 57.287 W
- plan hits target center									
- Point									

Formations					
Measured Depth	Vertical Depth	Name	Lithology	Dip	Dip Direction
(usft)	(usft)			(°)	(°)
2,082.0	2,082.0	Rustler			
3,205.4	3,205.0	Base salt/Top Artesia group			
5,417.7	5,416.0	San Andres			
7,638.8	7,637.0	First Bone Spring			
8,398.8	8,397.0	Second Bone Spring			
9,208.8	9,207.0	Third Bone Carb			
9,546.8	9,545.0	Third Bone Spring			
9,756.8	9,755.0	Wolfcamp A			
10,526.8	10,525.0	Penn Shale			
10,671.8	10,670.0	Strawn			
10,915.8	10,914.0	Atoka			

Plan Annotations				
Measured Depth	Vertical Depth	Local Coordinates		
(usft)	(usft)	+N/-S (usft)	+E/-W (usft)	Comment
2,400.0	2,400.0	0.0	0.0	Start Build 1.00
2,600.0	2,600.0	-1.4	-3.2	Start 2759.6 hold at 2600.0 MD
5,359.6	5,357.9	-40.8	-91.1	Start Drop -1.50
5,492.9	5,491.2	-41.7	-93.2	Start 5872.8 hold at 5492.9 MD
11,365.7	11,364.0	-41.7	-93.2	TD at 11365.7