

1625 N. French Dr., Hobbs, NM 88240

District II

811 S. First St., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural ResourcesForm C-104
Revised August 1, 2011Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit one copy to appropriate District Office

☐ AMENDED REPORT**I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT**

¹ Operator name and Address XTO Energy, Inc. 6401 HOLIDAY HILL ROAD BLDG 5 MIDLAND, TX 79707		² OGRID Number 373075
		³ Reason for Filing Code/ Effective Date NW
⁴ API Number 30 - 015-47099	⁵ Pool Name PURPLE SAGE; WOLFCAMP (GAS)	⁶ Pool Code 98220
⁷ Property Code 327328	⁸ Property Name POKER LAKE UNIT 30 BS	⁹ Well Number 167H

II. ¹⁰ Surface Location

Ul or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
H	30	25S	31E		2310	North	690	East	EDDY

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	6	26S	31E		230	South	1244	East	EDDY
¹² Lse Code	¹³ Producing Method Code	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number	¹⁶ C-129 Effective Date	¹⁷ C-129 Expiration Date				

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
34053	Plains/Western (PLU Pipeline)	O/W
373075	XTO Permian Midstream	G

IV. Well Completion Data

²¹ Spud Date 2/19/2021	²² Ready Date 2/4/2022	^{24906 MD} TD 11583 TVD	^{24879 MB} PBT 11583 TVD	²⁵ Perforations 11,691 TO 24,753	²⁶ DHC, MC
²⁷ Hole Size	²⁸ Casing & Tubing Size	²⁹ Depth Set	³⁰ Sacks Cement		
14.75	11.75	1,068	860		
8.75	7.625	10,840	1305		
6.75	5.0	24881/X	1195		

V. Well Test Data

³¹ Date New Oil 2/5/22	³² Gas Delivery Date 2/18/22	³³ Test Date 2/18/22	³⁴ Test Length 24 hrs	³⁵ Tbg. Pressure 0	³⁶ Csg. Pressure 1588
³⁷ Choke Size	³⁸ Oil 5590	³⁹ Water 14608	⁴⁰ Gas 20545		⁴¹ Test Method Flowing
⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Amanda Thames</i> Printed name: Amanda Thames Title: Regulatory Analyst E-mail Address: amanda.thames@exxonmobil.com Date: 3/8/2022			OIL CONSERVATION DIVISION Approved by: PATRICIA MARTINEZ Title: PETROLEUM SPECIALIST Approval Date: 11/4/2024		
Phone:					

District I

1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II

811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720

District III

1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102

Revised August 1, 2011

Submit one copy to appropriate

District Office

☒ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

AS-DRILLED PLAT

¹ API Number 30-015-47099	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 327328	⁵ Property Name POKER LAKE UNIT 30 BS	⁶ Well Number 167H
⁷ OGRID No. 373075	⁸ Operator Name XTO PERMIAN OPERATING, LLC.	⁹ Elevation 3,364'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
H	30	25 S	31 E		2,310	NORTH	690	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	6	26 S	31 E		230	SOUTH	1,244	EAST	EDDY

¹² Dedicated Acres 800	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.
--------------------------------------	-------------------------------	----------------------------------	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division. NOTE: AS-DRILLED BOTTOM HOLE PLOTTED FROM DATA FURNISHED BY XTO ENERGY

16 SHL (NAD83 NME) Y = 401,306.6 X = 703,040.6 LAT. = 32.102195° N LONG. = 103.811114° W KOP (NAD83 NME) Y = 401,385.3 X = 702,378.4 LAT. = 32.102420° N LONG. = 103.813251° W FTP (NAD83 NME) Y = 401,058.2 X = 702,394.5 LAT. = 32.101520° N LONG. = 103.813204° W CORNER COORDINATES (NAD83 NME) A - Y = 400,966.5 N , X = 703,729.5 E B - Y = 398,308.0 N , X = 703,719.7 E C - Y = 395,652.0 N , X = 703,732.0 E D - Y = 392,996.2 N , X = 703,742.0 E E - Y = 390,335.7 N , X = 703,758.2 E F - Y = 387,674.7 N , X = 703,774.6 E G - Y = 400,955.6 N , X = 702,400.1 E H - Y = 398,298.0 N , X = 702,389.1 E I - Y = 395,642.9 N , X = 702,401.5 E J - Y = 392,985.5 N , X = 702,412.9 E K - Y = 390,323.9 N , X = 702,428.8 E L - Y = 387,661.9 N , X = 702,444.8 E SHL (NAD27 NME) Y = 401,248.7 X = 661,855.0 LAT. = 32.102070° N LONG. = 103.810635° W KOP (NAD27 NME) Y = 401,327.4 X = 661,192.9 LAT. = 32.102295° N LONG. = 103.812772° W FTP (NAD27 NME) Y = 401,000.3 X = 661,208.9 LAT. = 32.101396° N LONG. = 103.812725° W CORNER COORDINATES (NAD27 NME) A - Y = 400,908.6 N , X = 662,543.9 E B - Y = 398,250.1 N , X = 662,534.0 E C - Y = 395,594.2 N , X = 662,546.2 E D - Y = 392,938.5 N , X = 662,556.1 E E - Y = 390,278.1 N , X = 662,572.2 E F - Y = 387,617.1 N , X = 662,588.6 E G - Y = 400,897.7 N , X = 661,214.5 E H - Y = 398,240.1 N , X = 661,203.4 E I - Y = 395,585.1 N , X = 661,215.8 E J - Y = 392,927.8 N , X = 661,227.0 E K - Y = 390,266.3 N , X = 661,242.8 E L - Y = 387,604.3 N , X = 661,258.8 E	17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Amanda Thames</i> 3/8/2022 Signature Date Amanda Thames Printed Name amanda.thames@exxonmobil.com E-mail Address 18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. 3-3-2022 Date of Survey Signature and Seal of Professional Surveyor: <i>Mark Dillon Harp</i> MARK DILLON HARP 23786 Certificate Number JC 2017071042
--	--

Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)

Schlumberger

April 23, 2021

XTO Permian Operating LLC
6401 Holiday Hill Road, Bldg 5
Midland, TX 79707

Re:

CLIENT: XTO Permian Operating LLC
WELL: Poker Lake Unit 30 BS 167H
FIELD: Purple Sage Wolfcamp Gas

RIG: H&P 552
COUNTY: Eddy
API NO: 30-015-47099
JOB NO: 21MLE0100

30 25S 31E Eddy NM
N 32.102070 W -103.810635

Enclosed, please find the original copy of the survey performed on the referenced well by Drilling & Measurements, a division of Schlumberger Technology Corporation (P-5 No. 754900).
Other information required by your office is as follows.

<u>Name & Title of Surveyor</u>	<u>Drainhole Number</u>	<u>Surveyed Depths</u>	<u>Dates Performed</u>	<u>Type of Survey</u>
Idris Olayinka Kazeem	Poker Lake Unit 30 BS			
FE	167H	207.00 Ft	February 19, 2021	XBOLT G2
	Original Hole	24906.00 Ft	April 22, 2021	

Schlumberger-Private

Oilfield Services, Central U.S. Land
Schlumberger Drilling and Measurements
Drilling Group
Geo Market Area: South West Texas Basin
7220 W I-H 20
Midland, Texas 79706
Phone : (432) 742-5400 (Main)
Fax : (432) 742-5606 (Shared)



Well Reference:

30 25S 31E Eddy NM
N 32.102070 W -103.810635

I, Idris Olayinka Kazeem certify that; I am employed by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I did on the day(s) of February 19, 2021 through April 22, 2021, conduct or supervise the taking of the XBOLT G2 surveys from a depth of 207.00 feet to a depth of 24906.00 feet referenced to driller's depth; that the data is true, correct, complete and within the limitations of the tool as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation; that I am authorized and qualified to make this report; that this survey was conducted at the request of XTO Permian Operating LLC for the Poker Lake Unit 30 BS 167H Well (Original Hole) API No. 30-015-47099 in New Mexico; and that I have reviewed this report and find that it conforms to the principals and procedures as set forth by Drilling & Measurements, a division of Schlumberger Technology Corporation.

By 
Idris Olayinka Kazeem
FE

Subscribed and Sworn to before me this _____ day of _____ (month) _____(yr)

My Commission expires:

_____- (signature)
Notary Public

(County State)



XTO Poker Lake Unit 30 BS 167H 0' to 24906' MD Survey Geodetic Report



(Def Survey)

Report Date: April 23, 2021 - 10:38 AM
 Client: XTO Energy
 Field: NM Eddy County (NAD 27)
 Structure / Slot: XTO Poker Lake Unit 30 BS 167H / New Slot
 Well: Poker Lake Unit 30 BS 167H
 Borehole: Poker Lake Unit 30 BS 167H
 UWI / API#: Unknown / 30-015-46944
 Survey Name: XTO Poker Lake Unit 30 BS 167H 0' to 24906' MD
 Survey Date: January 05, 2021
 Tort / AHD / DDI / ERD Ratio: 399.719' / 14465.106 ft / 7.090 / 1.237
 Coordinate Reference System: NAD27 New Mexico State Plane, Eastern Zone, US Feet
 Location Lat / Long: N 32° 6' 7.45272", W 103° 48' 38.28526"
 Location Grid N/E Y/X: N 401248.700 RUS, E 661855.000 RUS
 CRS Grid Convergence Angle: 0.2778°
 Grid Scale Factor: 0.9998391
 Version / Patch: 2.10.825.0

Survey / DLS Computation: Minimum Curvature / Lubinski
 Vertical Section Azimuth: 183.689° (Grid North)
 Vertical Section Origin: 0.000 ft, 0.000 ft
 TVD Reference Datum: RKB
 TVD Reference Elevation: 3364.000 ft above MSL
 Seabed / Ground Elevation: 3364.000 ft above MSL
 Magnetic Declination: 6.607°
 Total Gravity Field Strength: 998.420 mgn (9.80665 Based)
 Gravity Model: GARM
 Total Magnetic Field Strength: 47612.000 nT
 Magnetic Dip Angle: 59.680°
 Declination Date: January 26, 2021
 Magnetic Declination Model: IFR1+MS
 North Reference: Grid North
 North Convergence Used: 0.2780°
 Total Corr Mag North->Grid North: 6.3310°
 Local Coord Referenced To: Well Head

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (RUS)	Easting (RUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
Surface	0.00	0.00	203.86	0.00	0.00	0.00	0.00	N/A	401248.70	661855.00	32.102070	-103.810635	0.00	0.00
	207.00	1.38	352.74	206.98	-2.45	2.47	-0.32	0.67	401251.17	661854.69	32.102077	-103.810636	2.49	352.74
	299.00	1.16	349.06	298.96	-4.44	4.49	-0.63	0.25	401253.19	661854.37	32.102083	-103.810637	4.53	351.98
	392.00	1.13	346.80	391.94	-6.22	6.30	-1.02	0.06	401255.00	661853.98	32.102088	-103.810638	6.39	350.81
	484.00	1.07	349.97	483.92	-7.93	8.03	-1.38	0.09	401256.73	661853.62	32.102092	-103.810639	8.15	350.28
	576.00	1.19	7.44	575.90	-9.71	9.83	-1.40	0.39	401258.52	661853.60	32.102097	-103.810639	9.92	351.88
	667.00	1.24	346.36	666.88	-11.60	11.72	-1.51	0.49	401260.42	661853.49	32.102102	-103.810639	11.82	352.65
	759.00	1.27	344.31	758.86	-13.51	13.67	-2.02	0.06	401262.37	661852.98	32.102108	-103.810641	13.82	351.58
	851.00	1.15	356.90	850.84	-15.39	15.57	-2.35	0.32	401264.27	661852.65	32.102113	-103.810642	15.75	351.42
	942.00	0.73	22.04	941.83	-16.85	17.02	-2.18	0.64	401265.72	661852.82	32.102117	-103.810642	17.16	352.70
11-3/4" Casing	1003.00	0.69	45.52	1002.83	-17.49	17.64	-1.77	0.48	401266.34	661853.23	32.102119	-103.810640	17.73	354.26
	1088.00	1.13	47.18	1087.81	-18.48	18.57	-0.79	0.52	401267.26	661854.21	32.102121	-103.810637	18.58	357.55
	1133.00	1.36	47.63	1132.80	-19.18	19.23	-0.07	0.52	401267.93	661854.93	32.102123	-103.810635	19.23	359.78
	1262.00	1.80	46.49	1261.75	-21.77	21.65	2.53	0.34	401270.35	661857.53	32.102130	-103.810626	21.80	6.65
	1353.00	2.13	41.61	1352.70	-24.15	23.90	4.69	0.41	401272.60	661859.69	32.102136	-103.810619	24.36	11.09
	1445.00	2.69	39.50	1444.62	-27.25	26.85	7.19	0.62	401275.54	661862.19	32.102144	-103.810611	27.79	15.00
	1538.00	2.61	45.36	1537.52	-30.60	30.02	10.09	0.30	401278.72	661865.09	32.102153	-103.810602	31.67	18.58
	1630.00	4.25	36.32	1629.35	-35.04	34.24	13.60	1.87	401282.93	661868.60	32.102164	-103.810590	36.84	21.66
	1726.00	5.46	31.64	1725.01	-42.07	40.99	18.10	1.33	401289.69	661873.10	32.102183	-103.810576	44.81	23.83
	1822.00	4.94	27.12	1820.61	-49.90	48.56	22.38	0.69	401297.26	661877.38	32.102203	-103.810562	53.47	24.75
	1916.00	3.35	30.61	1914.36	-56.06	54.52	25.63	1.71	401303.22	661880.62	32.102220	-103.810551	60.25	25.17
	2013.00	2.91	12.40	2011.22	-61.02	59.37	27.60	1.11	401308.07	661882.60	32.102233	-103.810545	65.47	24.93
	2109.00	2.69	335.82	2107.11	-65.42	63.80	27.20	1.84	401312.50	661882.20	32.102245	-103.810546	69.36	23.09
	2205.00	3.59	287.09	2202.98	-68.11	66.74	23.40	2.83	401315.44	661878.40	32.102253	-103.810558	70.73	19.32
	2301.00	5.69	269.13	2298.67	-68.43	67.55	15.77	2.63	401316.25	661870.77	32.102256	-103.810583	69.37	13.14
	2397.00	7.86	263.51	2393.99	-66.89	66.74	4.49	2.36	401315.44	661859.49	32.102254	-103.810619	66.89	3.85
	2495.00	9.06	260.13	2490.93	-63.90	64.66	-9.77	1.32	401313.36	661845.23	32.102248	-103.810665	65.39	351.41
	2591.00	10.59	261.13	2585.52	-60.21	62.00	-25.94	1.60	401310.70	661829.07	32.102241	-103.810718	67.21	337.30
	2687.00	11.01	258.04	2679.82	-55.82	58.74	-43.62	0.74	401307.44	661811.38	32.102232	-103.810775	73.17	323.40
	2783.00	10.25	254.74	2774.17	-50.57	54.60	-60.83	1.01	401303.29	661794.17	32.102221	-103.810830	81.74	311.91
	2879.00	10.11	253.54	2868.66	-44.89	49.96	-77.15	0.26	401298.66	661777.85	32.102209	-103.810883	91.91	302.93
	2975.00	9.87	249.97	2963.20	-38.68	44.76	-92.96	0.69	401293.45	661762.04	32.102194	-103.810934	103.17	295.71
	3071.00	8.53	248.69	3057.97	-32.36	39.35	-107.32	1.41	401288.05	661747.68	32.102180	-103.810981	114.31	290.13
	3167.00	7.63	243.34	3153.01	-26.13	33.90	-119.65	1.22	401282.60	661735.35	32.102165	-103.810121	124.36	285.82
	3262.00	7.65	248.32	3247.17	-20.24	28.74	-131.17	0.70	401277.43	661723.84	32.102151	-103.810158	134.28	282.36
	3359.00	7.19	245.98	3343.36	-14.65	23.88	-142.71	0.57	401272.58	661712.30	32.102138	-103.810195	144.69	279.50
	3454.00	6.50	248.64	3437.68	-9.61	19.50	-153.15	0.80	401268.20	661701.86	32.102126	-103.810129	154.39	277.26
	3550.00	5.73	230.67	3533.14	-4.04	14.48	-161.92	1.43	401263.18	661693.09	32.102112	-103.810157	162.56	275.11
	3645.00	6.69	219.34	3627.59	3.70	7.20	-169.99	1.04	401255.90	661685.92	32.102092	-103.810181	169.25	272.44
	3741.00	8.36	216.78	3722.76	14.09	-2.72	-176.82	1.77	401245.98	661678.19	32.102065	-103.810206	176.84	269.12
	3837.00	10.35	213.04	3817.48	27.45	-15.54	-185.70	2.17	401233.16	661669.31	32.102030	-103.810235	186.35	265.22
	3932.00	11.87	213.22	3910.69	43.39	-30.87	-195.71	1.60	401217.84	661659.31	32.101988	-103.810267	196.12	261.04
	4028.00	10.64	214.79	4004.85	59.57	-46.40	-206.17	1.32	401202.30	661648.84	32.101945	-103.810301	211.33	257.32
	4123.00	8.25	215.50	4098.55	72.88	-59.16	-215.13	2.52	401189.55	661639.88	32.101910	-103.810330	223.12	254.62
	4219.00	6.49	225.95	4193.76	82.75	-68.54	-223.03	2.30	401180.17	661631.98	32.101885	-103.810356	233.33	252.92
	4312.00	7.56	231.71	4286.06	90.73	-75.98	-231.61	1.38	401172.72	661623.40	32.101864	-103.810384	243.76	251.84
	4408.00	8.31	240.35	4381.14	98.76	-83.33	-242.60	1.47	401165.38	661612.41	32.101844	-103.810419	256.51	251.04
	4504.00	7.95	253.83	4476.19	104.83	-88.61	-255.01	2.02	401160.10	661600.01	32.101830	-103.810460	269.96	250.84
	4599.00	8.08	258.76	4570.26	108.78	-91.74	-267.87	0.74	401156.96	661587.15	32.101822	-103.810501	283.14	251.09
	4695.00	7.67	271.69	4665.36	110.75	-92.87	-280.89	1.89	401155.84	661574.13	32.101819	-103.810543	295.84	251.71
4790.00	7.64	279.85	4759.52	110.29	-91.60	-293.45	1.14	401157.11	661561.57	32.101822	-103.810584	307.41	252.66	
4886.00	8.76	283.62	4854.54	108.34	-88.79	-306.84	1.29	401159.92	661548.18	32.101830	-103.810627	319.43	253.86	
4982.00	9.86	287.59	4949.27	105.11	-84.58	-321.78	1.33	401164.12	661533.24	32.101842	-103.810675	332.71	255.27	
5077.00	10.37	286.89	5042.80	101.20	-79.64	-337.71	0.55	401169.07	661517.31	32.101856	-103.810727	346.98	256.73	
5173.00	10.20	283.06	5137.25	97.84	-75.21	-354.26	0.73	401173.50	661500.76	32.101868	-103.810780	362.16	258.01	
5269.00	10.53	281.85	5231.69	95.21	-71.49	-371.13	0.41	401177.22	661483.90	32.101879	-103.810834	377.95	259.10	
5365.00	11.00	285.45	5326.00	92.10	-67.24	-388.54	0.85	401181.46	661466.48	32.101891	-103.810890	394.32	260.18	
5460.00	11.52	290.14	5419.17	87.57	-61.56	-406.18	1.11	401187.14	661448.84	32.101906	-103.810947	410.82	261.38	
5556.00	13.12	287.84	5512.96	82.19	-54.92	-425.56	1.74	401193.78	661429.47	32.101925	-103.810210	429.09	262.65	
5652.00	14.04	285.19	5606.27	77.20	-48.53	-447.17	1.16	401200.17	661407.86	32.101943	-103.810280	449.79	263.81	
5748.00	13.20	290.11	5699.98	71.78	-41.71	-468.70	1.49	401206.99	661386.33	32.101962	-103.810214	470.55	264.91	
5844.00	11.16	290.97	5793.41	65.92	-34.62	-487.67	2.13	401214.08	661367.36	32.101982	-103.810210	488.90	265.94	
5940.00	10.95	290.94	5887.63	60.46	-28.04	-504.86	0.22	401220.66	661350.17	32.102000	-103.810265	505.64	266.82	
6036.00	10.32	288.36	5981.98	55.58	-22.07	-521.54	0.82	401226.63	661333.50	32.102016	-103.810219	522.00	267.58	
6131.00	11.08	284.48	6075.33	51.71	-17.11	-538.45	1.10	401231.59	661316.58	32.102030	-103.810234	538.72	268.18	
6227.00	12.10	280.84	6169.37	48.73	-12.91	-557.27	1.31	401235.79	661297.77	32.102042	-103.810243	557.42	268.67	
6324.00	11.99	281.67	6264.24	47										

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	8624.00	1.08	358.52	8557.38	5.89	36.36	-655.53	1.26	401285.05	661199.51	32.102179	-103.812751	656.54	273.17
	8720.00	1.02	312.48	8653.36	4.46	37.84	-656.18	0.86	401286.53	661198.86	32.102183	-103.812753	657.27	273.30
	8816.00	1.08	297.50	8749.34	3.56	38.83	-657.62	0.29	401287.53	661197.42	32.102186	-103.812758	658.76	273.38
	8911.00	0.73	308.58	8844.33	2.85	39.62	-658.88	0.41	401288.32	661196.16	32.102188	-103.812762	660.07	273.44
	9007.00	0.84	334.51	8940.32	1.89	40.64	-659.66	0.38	401289.34	661195.38	32.102191	-103.812764	660.92	273.53
	9103.00	0.99	325.21	9036.31	0.62	41.96	-660.44	0.22	401290.65	661194.60	32.102194	-103.812767	661.77	273.63
	9199.00	1.10	313.49	9132.30	-0.62	43.27	-661.58	0.25	401291.97	661193.46	32.102198	-103.812770	663.00	273.74
	9295.00	1.13	312.23	9228.28	-1.80	44.54	-662.95	0.04	401293.24	661192.09	32.102201	-103.812775	664.45	273.84
	9390.00	1.82	5.72	9323.25	-3.89	46.67	-663.50	1.54	401295.37	661191.55	32.102207	-103.812777	665.13	274.02
	9486.00	2.75	5.50	9419.17	-7.71	50.48	-663.12	0.97	401299.18	661191.92	32.102218	-103.812775	665.04	274.35
	9582.00	2.46	1.86	9515.07	-12.08	54.83	-662.84	0.35	401303.53	661192.21	32.102230	-103.812774	665.10	274.73
	9678.00	5.25	7.35	9610.85	-18.52	61.25	-662.21	2.93	401309.95	661192.84	32.102247	-103.812772	665.03	275.28
	9773.00	5.42	10.51	9705.44	-27.31	69.97	-660.83	0.36	401318.67	661194.21	32.102271	-103.812768	664.53	276.04
	9869.00	4.77	14.33	9801.06	-35.74	78.30	-659.02	0.76	401326.99	661196.02	32.102294	-103.812762	663.65	276.78
	9965.00	3.54	8.65	9896.80	-42.61	85.09	-657.58	1.35	401333.79	661197.46	32.102313	-103.812757	663.07	277.37
	10060.00	2.51	16.08	9991.67	-47.57	89.99	-656.57	1.16	401338.69	661198.48	32.102326	-103.812754	662.70	277.80
	10156.00	1.88	32.16	10087.60	-51.00	93.35	-655.15	0.91	401342.04	661199.90	32.102335	-103.812749	661.76	278.11
	10252.00	1.26	26.46	10183.56	-53.36	95.62	-653.84	0.67	401344.32	661201.20	32.102342	-103.812745	660.79	278.32
	10348.00	0.07	274.33	10279.55	-54.33	96.57	-653.43	1.34	401345.27	661201.62	32.102344	-103.812743	660.52	278.41
	10443.00	2.54	208.28	10374.52	-52.42	94.72	-654.48	2.64	401343.42	661200.56	32.102339	-103.812747	661.30	278.24
	10538.00	2.91	204.37	10469.42	-48.25	90.67	-656.47	0.44	401339.37	661198.57	32.102328	-103.812753	662.71	277.86
	10634.00	2.29	200.41	10565.32	-44.13	86.66	-658.15	0.67	401335.35	661196.89	32.102317	-103.812759	663.83	277.50
	10730.00	1.57	213.74	10661.26	-41.16	83.78	-659.55	0.88	401332.46	661195.49	32.102309	-103.812763	664.84	277.24
	10797.00	1.29	225.49	10728.24	-39.80	82.47	-660.59	0.60	401331.17	661194.45	32.102306	-103.812767	665.72	277.12
7-58" Casing	10860.00	0.68	229.88	10791.23	-39.01	81.73	-661.39	0.97	401330.43	661193.65	32.102304	-103.812769	666.42	277.04
	10893.00	0.37	237.92	10864.23	-38.81	81.65	-661.63	0.97	401330.25	661193.41	32.102303	-103.812770	666.63	277.03
	10989.00	0.09	82.26	10920.23	-38.65	81.40	-661.82	0.47	401330.09	661193.23	32.102303	-103.812771	666.80	277.01
	11085.00	10.59	188.11	11015.69	-29.84	72.65	-662.99	11.06	401321.34	661192.05	32.102279	-103.812775	666.96	276.25
	11181.00	19.92	182.49	11108.20	-4.64	47.52	-664.95	9.83	401296.22	661190.09	32.102210	-103.812781	666.64	274.09
	11276.00	26.93	180.96	11195.32	33.08	9.79	-666.01	7.41	401258.49	661189.03	32.102106	-103.812785	666.08	270.84
	11372.00	32.43	177.55	11278.70	80.42	-37.70	-665.28	5.99	401211.00	661189.77	32.101975	-103.812784	666.34	266.76
	11468.00	37.66	175.33	11357.27	135.07	-92.69	-661.79	5.61	401156.02	661193.26	32.101824	-103.812773	668.24	262.03
	11564.00	43.80	173.94	11429.99	196.89	-155.01	-655.88	6.46	401093.69	661199.16	32.101653	-103.812755	673.95	256.79
	11659.00	49.04	173.86	11495.45	264.68	-223.42	-648.57	5.52	401025.29	661206.47	32.101465	-103.812733	685.98	250.90
	11755.00	54.68	174.86	11554.72	339.16	-298.53	-641.18	5.93	400950.19	661213.86	32.101258	-103.812710	707.27	245.03
	11851.00	60.76	173.40	11605.97	419.15	-379.22	-632.85	6.46	400869.50	661222.19	32.101036	-103.812684	737.77	239.07
	11947.00	70.17	174.97	11645.79	505.19	-466.01	-624.06	9.91	400782.72	661230.98	32.100798	-103.812657	778.85	233.25
	12043.00	81.83	175.23	11668.97	597.14	-558.66	-616.12	12.15	400690.08	661238.92	32.100543	-103.812633	831.68	227.80
FTP [350° FNL, 39° FWL]	12138.00	86.59	174.68	11678.55	690.53	-652.78	-607.81	5.04	400595.96	661247.23	32.100284	-103.812608	891.94	222.96
	12186.00	88.15	174.44	11680.76	737.87	-700.51	-603.26	3.29	400548.23	661251.78	32.100153	-103.812594	924.47	220.73
	12233.00	89.68	174.21	11681.64	784.23	-747.27	-598.62	3.29	400501.48	661256.42	32.100024	-103.812579	957.47	218.70
	12329.00	89.58	176.49	11682.26	879.21	-842.95	-590.84	2.38	400405.81	661264.20	32.099761	-103.812556	1029.39	215.03
	12425.00	89.92	176.74	11682.68	974.48	-938.78	-585.17	0.44	400309.98	661269.87	32.099498	-103.812539	1106.22	211.94
	12521.00	88.71	175.34	11683.83	1069.61	-1034.54	-578.54	1.93	400214.23	661276.50	32.099234	-103.812519	1185.32	209.21
	12617.00	89.71	177.76	11685.16	1164.85	-1130.35	-572.76	2.73	400118.43	661282.27	32.098971	-103.812502	1267.18	206.87
	12713.00	89.92	179.12	11685.47	1260.45	-1226.31	-570.15	1.43	400022.47	661284.89	32.098707	-103.812495	1352.37	204.94
	12809.00	90.19	179.54	11685.37	1356.17	-1322.30	-569.03	0.52	399926.48	661286.01	32.098443	-103.812493	1439.54	203.28
	12904.00	91.08	177.84	11684.32	1450.80	-1417.26	-566.85	2.02	3998931.52	661288.18	32.098182	-103.812487	1526.42	201.80
	13000.00	87.67	177.35	11685.37	1546.24	-1513.16	-562.83	3.59	399735.63	661292.21	32.097918	-103.812476	1614.44	200.40
	13092.00	86.96	176.65	11689.68	1637.54	-1604.94	-558.26	0.89	399643.86	661296.78	32.097686	-103.812463	1699.26	199.18
	13188.00	88.51	177.71	11693.47	1732.87	-1700.76	-553.79	1.80	399548.04	661301.24	32.097403	-103.812450	1788.65	198.04
	13284.00	90.94	178.20	11693.93	1828.38	-1796.69	-550.36	2.58	399452.12	661304.67	32.097139	-103.812440	1879.10	197.03
	13380.00	91.25	178.61	11692.10	1923.95	-1892.64	-547.69	0.54	399356.18	661307.34	32.096875	-103.812433	1970.29	196.14
	13476.00	90.23	178.93	11690.86	2019.59	-1988.61	-545.63	1.11	399260.22	661309.40	32.096611	-103.812428	2062.10	195.34
	13572.00	91.27	179.32	11689.60	2115.28	-2084.58	-544.17	1.16	399164.25	661310.87	32.096347	-103.812424	2154.44	194.63
	13668.00	92.03	179.84	11686.84	2210.99	-2180.54	-543.46	0.96	399068.30	661311.57	32.096084	-103.812424	2247.25	193.99
	13763.00	91.30	180.27	11684.08	2305.76	-2275.50	-543.55	0.89	398973.34	661311.48	32.095823	-103.812425	2339.52	193.43
	13859.00	91.31	181.14	11681.89	2401.60	-2371.47	-544.74	0.91	398877.38	661310.30	32.095559	-103.812431	2433.23	192.94
	13955.00	90.97	181.63	11679.98	2497.50	-2467.02	-547.06	0.62	398781.44	661307.98	32.095295	-103.812440	2527.34	192.50
	14051.00	90.97	182.14	11678.35	2593.44	-2563.35	-550.21	0.53	398685.51	661304.82	32.095031	-103.812451	2621.74	192.11
	14147.00	89.88	181.18	11677.64	2689.38	-2659.31	-552.99	1.51	398589.56	661302.04	32.094768	-103.812462	2716.20	191.75
	14242.00	87.99	180.04	11679.41	2784.22	-2754.28	-554.00	2.32	398494.59	661301.03	32.094507	-103.812467	2809.45	191.37
	14338.00	89.25	179.59	11684.01	2974.72	-2945.22	-553.39	0.70	398303.67	661301.65	32.093982	-103.812468	2906.76	190.64
	14529.00	90.59	181.47	11684.14	3070.57	-3041.21	-554.28	2.40	398207.68	661300.76	32.093718	-103.812472	3091.31	190.33
	14625.00	90.78	181.67	11682.99	3166.50	-3137.17	-556.91	0.29	398111.73	661298.13	32.093454	-103.812482	3186.21	190.07
	14720.00	90.27	181.92	11682.12	3261.44	-3232.12	-559.88	0.60	398016.79	661295.15	32.093193	-103.812493	3280.25	189.63
	14816.00	90.52	182.10	11681.46	3357.40	-3328.05	-563.25	0.32	397920.86	661291.79	32.092930	-103.812505	3375.38	189.81
	14912.00	91.54	182.44	11679.74	3453.35	-3423.96	-567.05	1.12	397824.95	661287.99	32.092666	-103.812519	3470.60	189.40
	15008.00	90.46	182.61	11678.06	3549.31	-3519.85	-571.28	1.14	397729.07	6				

Comments	MD (ft)	Incl (°)	Azim Grid (°)	TVD (ft)	VSEC (ft)	NS (ft)	EW (ft)	DLS (°/100ft)	Northing (ftUS)	Easting (ftUS)	Latitude (°)	Longitude (°)	Closure (ft)	Closure Azimuth (°)
	19702.00	90.32	180.02	11613.16	8231.12	-8211.99	-561.79	1.10	393037.23	661293.25	32.078905	-103.812577	8231.18	183.91
	19798.00	90.25	179.67	11612.68	8326.90	-8307.99	-561.53	0.37	392941.24	661293.51	32.079241	-103.812578	8326.94	183.87
	19893.00	89.11	178.44	11613.21	8421.59	-8402.97	-559.96	1.77	392846.26	661295.07	32.078980	-103.812574	8421.61	183.81
	19989.00	90.08	179.15	11613.89	8517.23	-8498.94	-557.94	1.25	392750.29	661297.09	32.078716	-103.812569	8517.24	183.76
	20084.00	91.16	179.73	11612.86	8611.96	-8593.93	-557.01	1.29	392655.31	661298.02	32.078455	-103.812567	8611.96	183.71
	20180.00	88.27	178.96	11613.34	8707.68	-8689.91	-555.92	3.12	392559.33	661299.12	32.078191	-103.812565	8707.68	183.66
	20276.00	90.17	179.39	11614.64	8803.36	-8785.89	-554.53	2.03	392463.36	661300.50	32.077927	-103.812562	8803.37	183.61
	20372.00	90.76	179.71	11613.87	8899.11	-8881.88	-553.78	0.70	392367.38	661301.25	32.077663	-103.812562	8899.13	183.57
	20468.00	90.42	179.06	11612.88	8994.83	-8977.87	-552.75	0.76	392271.39	661302.29	32.077399	-103.812560	8994.87	183.52
	20564.00	90.86	179.18	11611.80	9090.52	-9073.85	-551.28	0.48	392175.42	661303.76	32.077136	-103.812556	9090.59	183.48
	20660.00	90.69	178.02	11610.51	9186.13	-9169.82	-548.93	1.22	392079.46	661306.10	32.076872	-103.812550	9186.23	183.43
	20756.00	89.07	178.56	11610.71	9281.70	-9265.77	-546.07	1.78	391983.51	661308.97	32.076608	-103.812543	9281.85	183.37
	20852.00	92.16	179.50	11609.68	9377.37	-9361.74	-544.44	3.36	391887.55	661310.59	32.076344	-103.812539	9377.55	183.33
	20948.00	93.35	179.14	11605.06	9472.98	-9457.62	-543.30	1.29	391791.68	661311.73	32.076081	-103.812537	9473.21	183.29
	21043.00	93.96	180.25	11599.01	9567.55	-9552.42	-542.80	1.33	391696.88	661312.24	32.075820	-103.812536	9567.83	183.25
	21139.00	88.17	178.14	11597.22	9663.19	-9648.35	-541.45	6.42	391600.96	661313.59	32.075556	-103.812534	9663.53	183.21
	21234.00	93.07	179.24	11596.20	9757.80	-9743.29	-539.28	5.29	391506.03	661315.76	32.075295	-103.812528	9756.20	183.17
	21330.00	88.09	177.75	11595.22	9853.37	-9839.22	-536.76	5.41	391410.10	661318.28	32.075032	-103.812521	9853.85	183.12
	21425.00	89.35	179.20	11597.35	9947.94	-9934.15	-534.23	2.02	391315.17	661320.81	32.074771	-103.812515	9948.51	183.08
	21521.00	90.99	180.06	11597.06	10043.70	-10030.15	-533.61	1.93	391219.18	661321.42	32.074507	-103.812514	10044.33	183.05
	21617.00	89.56	179.49	11596.60	10139.47	-10126.14	-533.23	1.60	391123.19	661321.80	32.074243	-103.812515	10140.17	183.01
	21713.00	89.89	179.99	11597.06	10235.24	-10222.14	-532.80	0.62	391027.20	661322.24	32.073979	-103.812515	10236.02	182.98
	21808.00	91.11	179.97	11596.23	10330.04	-10317.14	-532.76	1.28	390932.21	661322.27	32.073716	-103.812516	10330.88	182.96
	21904.00	90.50	179.27	11594.88	10425.78	-10413.12	-532.13	0.97	390836.23	661322.91	32.073454	-103.812515	10426.71	182.93
	22000.00	89.84	179.68	11594.60	10521.52	-10509.12	-531.25	0.81	390740.24	661323.79	32.073190	-103.812514	10522.54	182.89
	22095.00	89.08	179.00	11595.49	10616.25	-10604.11	-530.15	1.07	390645.26	661324.88	32.072929	-103.812512	10617.35	182.86
	22192.00	90.74	178.66	11595.65	10712.89	-10701.08	-528.17	1.75	390548.29	661326.86	32.072662	-103.812507	10714.11	182.83
	22287.00	95.41	181.11	11590.55	10807.51	-10795.91	-527.98	5.55	390453.47	661327.06	32.072402	-103.812508	10808.81	182.80
	22383.00	90.96	178.85	11585.22	10903.13	-10891.73	-527.94	5.20	390357.65	661327.09	32.072138	-103.812509	10904.52	182.78
	22479.00	89.43	179.52	11584.89	10998.83	-10987.72	-526.57	1.74	390261.67	661328.46	32.071875	-103.812506	11000.33	182.74
	22577.00	90.35	180.09	11585.08	11096.61	-11085.72	-526.24	1.10	390163.68	661328.79	32.071605	-103.812507	11098.20	182.72
	22673.00	90.19	182.90	11584.63	11192.53	-11181.67	-528.74	2.93	390067.73	661326.29	32.071341	-103.812517	11194.17	182.71
	22769.00	90.00	179.50	11584.47	11288.42	-11277.64	-530.76	3.55	389971.77	661324.28	32.071078	-103.812525	11290.12	182.69
	22960.00	90.66	179.84	11583.37	11478.95	-11468.63	-529.65	0.39	389780.79	661325.38	32.070553	-103.812524	11480.85	182.64
	23056.00	90.05	180.48	11582.77	11574.76	-11564.63	-529.92	0.92	389684.80	661325.11	32.070289	-103.812526	11576.76	182.62
	23152.00	90.14	179.59	11582.61	11670.57	-11660.63	-529.98	0.93	389588.81	661325.05	32.070025	-103.812528	11672.66	182.60
	23248.00	90.39	179.46	11582.17	11766.31	-11756.62	-529.19	0.29	389492.82	661325.85	32.069761	-103.812527	11768.53	182.58
	23344.00	90.45	179.13	11581.47	11862.03	-11852.61	-528.00	0.35	389396.83	661327.03	32.069497	-103.812525	11864.37	182.55
	23440.00	90.43	179.42	11580.73	11957.74	-11948.60	-526.79	0.30	389300.85	661328.24	32.069233	-103.812522	11960.21	182.52
	23536.00	89.70	179.57	11580.62	12053.48	-12044.60	-525.94	0.78	389204.86	661329.09	32.068969	-103.812521	12056.07	182.50
	23727.00	89.95	179.08	11581.20	12243.93	-12235.58	-523.69	0.29	389013.89	661331.34	32.068444	-103.812517	12246.78	182.45
	23823.00	90.23	179.37	11581.05	12339.63	-12331.57	-522.40	0.42	388917.90	661332.64	32.068180	-103.812514	12342.63	182.43
	24015.00	91.11	179.50	11578.81	12531.09	-12523.55	-520.50	0.46	388725.94	661334.53	32.067653	-103.812511	12534.36	182.38
	24110.00	88.49	178.28	11579.14	12625.75	-12618.52	-518.66	3.04	388630.97	661336.37	32.067392	-103.812506	12629.17	182.35
	24206.00	88.86	179.14	11581.36	12721.36	-12714.47	-516.50	0.98	388535.03	661338.53	32.067128	-103.812501	12724.96	182.33
	24302.00	90.28	179.85	11582.08	12817.10	-12810.46	-515.66	1.65	388439.05	661339.38	32.066864	-103.812500	12820.83	182.31
	24398.00	90.47	179.19	11581.45	12912.84	-12906.45	-514.85	0.72	388343.06	661340.18	32.066600	-103.812499	12916.72	182.28
	24494.00	90.01	179.18	11581.05	13008.54	-13002.44	-513.49	0.48	388247.08	661341.55	32.066336	-103.812496	13012.58	182.26
	24590.00	90.04	178.86	11581.01	13104.22	-13098.43	-511.84	0.33	388151.10	661343.19	32.066072	-103.812492	13108.43	182.24
	24685.00	88.53	180.69	11582.19	13198.99	-13193.41	-511.47	2.50	388056.12	661343.56	32.065811	-103.812492	13203.32	182.22
	24781.00	90.71	180.42	11582.83	13294.84	-13289.40	-512.40	2.29	387960.13	661342.63	32.065548	-103.812497	13299.28	182.21
LTP [330° FSL,85° FWL]	24810.00	90.23	180.05	11582.59	13323.78	-13318.40	-512.52	2.07	387931.14	661342.51	32.065468	-103.812497	13328.26	182.20
Last Survey	24877.00	89.13	179.21	11582.96	13390.61	-13385.40	-512.09	2.07	387864.15	661342.94	32.065284	-103.812497	13395.19	182.19
Projection to Bit [230° FSL,86° FWL]	24906.00	89.13	179.21	11583.40	13419.52	-13414.39	-511.69	0.00	387835.15	661343.34	32.065204	-103.812496	13424.15	182.18

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 3 *** 3-D 95.000% Confidence 2.7955 sigma
Survey Program:

Description	Part	MD From (ft)	MD To (ft)	EOU Freq (ft)	Hole Size (in)	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
Schlumberger / xBolt	1	0.000	30.000	1/98.425	14.750	11.750	A008Mb_MWD+IFR1+MS-Depth Only	Poker Lake Unit 30 BS 167H / XTO Poker Lake Unit 30 BS 167H 0' to 24906' MD
Schlumberger / xBolt	1	30.000	30.000	Act Stns	14.750	11.750	A008Mb_MWD+IFR1+MS-Depth Only	Poker Lake Unit 30 BS 167H / XTO Poker Lake Unit 30 BS 167H 0' to 24906' MD
Schlumberger / xBolt	1	30.000	1088.000	Act Stns	14.750	11.750	A008Mb_MWD+IFR1+MS	Poker Lake Unit 30 BS 167H / XTO Poker Lake Unit 30 BS 167H 0' to Poker Lake Unit 30 BS 167H 0' to
Schlumberger / xBolt	1	1088.000	10860.000	Act Stns	8.750	7.625	A008Mb_MWD+IFR1+MS	Poker Lake Unit 30 BS 167H 0' to Poker Lake Unit 30 BS 167H 0' to
Schlumberger / xBolt	1	10860.000	24906.000	Act Stns	6.750	5.500	A008Mb_MWD+IFR1+MS	Poker Lake Unit 30 BS 167H / XTO Poker Lake Unit 30 BS 167H 0' to

Intent ☒ As Drilled ☐

API # 3001547099		
Operator Name: XTO PERMIAN OPERATING, LLC	Property Name: Poker Lake Unit 30 BS	Well Number 167H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
G	30	25S	31E		2227	North	1352	East	Eddy
Latitude 32.102420					Longitude -103.813251			NAD 83	

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
H	30	25S	31E		2554	North	1335	East	Eddy
Latitude 32.101520					Longitude -103.813204			NAD 83	

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
P	6	26S	31E		383	South	1243	East	Eddy
Latitude 32.065749					Longitude -103.812972			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit? ☐ NIs this well an infill well? ☐ Y

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # Undesignated		
Operator Name: XTO Permian Operating LLC.	Property Name: Poker Lake Unit 30 BS	Well Number 105H

KZ 06/29/2018

Well Name: POKER LAKE UNIT 30 BS	Well Location: T25S / R31E / SEC 30 / SENE / 32.102195 / -103.811114	County or Parish/State: EDDY / NM
Well Number: 167H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMLC0061634B, NMLC061634B	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001547099	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Subsequent Report

Sundry ID: 2655993

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 02/07/2022

Time Sundry Submitted: 03:41

Date Operation Actually Began: 10/30/2021

Actual Procedure: XTO PERMIAN OPERATING LLC respectfully submits this sundry notice to report the completion operations of the referenced well. KOP @ depth 11,019 ft. PBTD = 24,880 ft. 8/3/21 Run RCB/GR/CCL 10/7/21 Pressure test 5.5 in csg to 8,264 psi for 30min test good, open sleeve. 10/30/21 Perf and frac 65 stages, 1,560 total shots, from 11,691 to 24,753 using 639,570 bbls of fluid and 32,547,217 lbs Proppant. Tag and drill out plugs.

Well Name: POKER LAKE UNIT 30 BS	Well Location: T25S / R31E / SEC 30 / SENE / 32.102195 / -103.811114	County or Parish/State: EDDY / NM
Well Number: 167H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMLC0061634B, NMLC061634B	Unit or CA Name: POKER LAKE	Unit or CA Number: NMNM071016X, NMNM71016X
US Well Number: 3001547099	Well Status: Drilling Well	Operator: XTO PERMIAN OPERATING LLC

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: CASSIE EVANS

Signed on: FEB 07, 2022 03:41 PM

Name: XTO PERMIAN OPERATING LLC

Title: Regulatory Analyst

Street Address: 6401 Holiday Hill Road, Bldg 5

City: Midland

State: TX

Phone: (432) 218-3671

Email address: CASSIE.EVANS@EXXONMOBIL.COM

Field Representative

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: Jonathon W Shepard

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5752345972

BLM POC Email Address: jshepard@blm.gov

Disposition: Accepted

Disposition Date: 03/03/2022

Signature: Jonathon Shepard

Submit To Appropriate District Office Two Copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 811 S. First St., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017				
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name POKER LAKE UNIT 30 BS		
								6. Well Number: 167H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER										
8. Name of Operator XTO PERMIAN OPERATING LLC.						9. OGRID 373075				
10. Address of Operator 6401 HOLIDAY HILL RD BLDG #5, MIDLAND TX 79707						11. Pool name or Wildcat PURPLE SAGE;WOLFCAMP (GAS)				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	H	30	25S	31E		2310	North	690	East	Eddy
BH:	P	6	26S	31E		230	South	1244	East	Eddy
13. Date Spudded 2/19/2021	14. Date T.D. Reached 4/22/2021		15. Date Rig Released 4/25/2021		16. Date Completed (Ready to Produce) 2/4/2022			17. Elevations (DF and RKB, RT, GR, etc.) 3364' GL		
18. Total Measured Depth of Well 24,906			19. Plug Back Measured Depth 24,879		20. Was Directional Survey Made? Yes			21. Type Electric and Other Logs Run CBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 11,691 TO 24,753 PURPLE SAGE;WOLFCAMP (GAS)										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
11 3/4"		54.0		1,068'		14 3/4"		860		
7 5/8"		29.7		10,840'		8 3/4"		1305		
5"		18.0		24,881'		6 3/4"		1195		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN		SIZE	DEPTH SET		PACKER SET	
26. Perforation record (interval, size, and number) 11,691 TO 24,753 2spf, 1560 Total Shots 65 stages						27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.				
						DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED		
						11,691 TO 24,753		639,570 bbl fluid + 32,547,217 lbs proppant		
28. PRODUCTION										
Date First Production 2/5/22		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in) Producing				
Date of Test 2/18/22	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 5590	Gas - MCF 20545	Water - Bbl. 14608	Gas - Oil Ratio 3675			
Flow Tubing Press. 0	Casing Pressure 1588	Calculated 24-Hour Rate	Oil - Bbl. 5590	Gas - MCF 20545	Water - Bbl. 14608	Oil Gravity - API - (Corr.)				
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold								30. Test Witnessed By		
31. List Attachments C-104 NW, C-102 & Supplement , Directional Survey (Log uploaded to NMOCD)										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.								33. Rig Release Date:		
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude				Longitude				NAD83		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature <i>Amanda Thames</i>				Printed Name Amanda Thames		Title Regulatory Analyst		Date 3/8/2022		
E-mail Address amanda.thames@exxonmobil.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn A"
T. Salt 1,237	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt 3,987	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand 4,180	T. Morrison	
T. Drinkard	T. Bone Springs 8,032	T. Todilto	
T. Abo	T. Rustler 855	T. Entrada	
T. Wolfcamp 11,395	T.	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

No. 1, from.....to.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

From	To	Thickness In Feet	Lithology

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 88050

ACKNOWLEDGMENTS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 88050
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 88050

CONDITIONS

Operator: XTO PERMIAN OPERATING LLC. 6401 HOLIDAY HILL ROAD MIDLAND, TX 79707	OGRID: 373075
	Action Number: 88050
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	File 3160-4 Completion Report within 10 days of BLM approval.	11/4/2024