	,														
Sante Fe Main Office Phone: (505) 476-3441				Stat	te of N	ew M	exico						Au	Form C-103 gust 1, 2011	
General Information Phone: (505) 629-6116	Energy, Minerals and Natural Resources									Permit 325664					
Online Phone Directory		Oil Conservation Division								W	WELL API NUMBER 30-025-49802				
https://www.emnrd.nm.gov/ocd/c							5.	5. Indicate Type of Lease State							
										6.		& Gas Lease	e No.		
				Sai	nta Fe,	IAIAI C	7 303								
(DO NOT USE THIS FORM FOR (FORM C-101) FOR SUCH PRO	R PROPOSALS TO DR	_	FICES AND	_		_	VOIR. USE "/	APPLICATIC	N FOR PER			ame or Unit A DAKMONT			
1. Type of Well: Oil										8.	Well Nun	nber )11H			
Name of Operator     Spur Energy Partn	ers LLC									9.	OGRID N	umber 328947			
Address of Operator	y, Suite 500, Housto	on. TX 7702	4							10	. Pool na	me or Wildo	at		
4. Well Location	,,	,													
Unit Letter B : 7	770 feet from the Township 17S	Range		d feet 189 NMPM		from the I	<u> </u>	line							
	11. E		w whether DR,	KB, BT, GF	R, etc.)										
Pit or Below-grade Tank Applica	ation or Closure	4161 (	SK .												
Pit Type Depth to Gro	undwater Dis	stance from ne	earest fresh wa	ter well	Distance	from neare	st surface wat	er							
Pit Liner Thickness:	_ mil Below-Grad	de Tank: Volu	me	bbls;	Construction I	Material		_							
12. Check Appropriate Box to Ir	ndicate Nature of Notice				Ī				SUBSEQU	ENT REPO	RT OF:				
PERFORM REMEDIAL WORK		PLUG	AND ABANDO	١		REMEDIA		OPNO	OODOLQO		ALTER (				
TEMPORARILY ABANDON PULL OR ALTER CASING		=	GE OF PLANS PLE COMPL				CE DRILLING CEMENT JOB				PLUG AI	ND ABANDO	N	_	
Other:						Other: Dri	lling/Cement							×	
13. Describe proposed or compl Attach wellbore diagram of prop 09/18/2022/2022 NU BOP, test I 40bbl FWS, then cmt w/ 540 sxs rig moves back in. 09/19/2022 R	osed completion or re to 250# low 2500# high class C w/ additives 1 BD and rig release. 8/2	completion. h, good test. 7 2.0ppg 2.38 y	est 13-3/8" cs rield followed b	g to 1500# f	for 30 minutes	, good test.	Drill 12-1/4" I	nole to 3200	. 09/19/2022	RIH & set	9-5/8" 36	# J-55 BTC	csg @ 320	0', pump	
Casing and Cement Progra			0		0 1	<b>-</b> .	5.4	0.1	V: 11	01	411				
· ·	Fluid Type	Hole Size	Csg Size	Weight lb/ft	Grade	Est TOC	Dpth Set	Sacks	Yield	Class	1" Dpth	Pres Held	Pres Drop	Open Hole	
	FreshWater FreshWater	17.5 12.25	13.375 9.625	54.5 36	J-55 J-55	0 0	1533 3200	1530 735	1.77 2.38	C C	0 0	2055 2816	0 0	N N	
	Brine	8.75	7	32	L-80	0	6502	2475	2.4	C	0	7272	0	N	
10/16/22 Prod	Brine	8.75	5.5	20	L-80	0	14482	2475	2.4	С	0	7352	0	N	
I hereby certify that the inform NMOCD guidelines □, a gene						further certi	fy that any pit	or below-gr	ade tank has	s been/will	be constru	ucted or clos	ed accordi	ng to	
SIGNATURE	Electronically Signed		TITLE	TITLE		Regulatory Director DATE						10/18/2022			
Type or print name Sarah Chapman			E-mail addr	ess	schapman@spurenergy.com Telephone No				e No.	832-930-8613					
For State Use Only:															
APPROVED BY:	Keith Dziokonski		TITLE		Petroleum	Specialist	: A		DATE		12/1	6/2024 9:20	0:37 AM		
	_			•		•						•			

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

COMMENTS

Action 325664

## **COMMENTS**

Operator:	OGRID:
Spur Energy Partners LLC	328947
9655 Katy Freeway	Action Number:
Houston, TX 77024	325664
	Action Type:
	[C-103] EP Drilling / Cement

## Comments

Created By	Comment	Comment Date
schapman01	10/07/2022 NU BOP, test to 250# low 2500# high, good test. Test 9-5/8" csg top 1500# for 30min, good test. Drill 8-3/4" hole to 6237'V/14482'M – TD reached on 10/16/2022. RIH & set 7" 32# L-80 BK-HT csg @ 6502' then crossover and set 5-1/2" 20# L-80 BK-HT csg @ 14482', pump 40bbl FWS, then cmt w/ 215 sxs class C w/ additives 11.4ppg 2.40 yield followed by tail job w/ 2260 sxs class C w/ additives 13.2ppg and 1.4 yield. Full returns throughout job, circ 234 sxs cmt to surface. Pressure test csg to 6000# for 30 minutes, good test. 10/17/2022 RD and rig release.	10/18/2022