

I. REQUEST FOR ALLOWABLE AND AUTHORIZATION TO TRANSPORT

¹ Operator name and Address EARTHSTONE OPERATING, LLC 1400 WOODLOCH FOREST DR., SUITE 300 THE WOODLANDS, TX 77380		² OGRID Number 331165
		³ Reason for Filing Code/ Effective Date NW-01/06/2023
⁴ API Number 30 - 025-49709	⁵ Pool Name OJO CHISO; BONE SPRING	⁶ Pool Code 96553
⁷ Property Code 332643	⁸ Property Name SQUEEZE 2 STATE COM	⁹ Well Number 3H

II. ¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South Line	Feet from the	East/West line	County
M	2	22S	34E		380	SOUTH	1175	WEST	LEA

¹¹ Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	2	22S	34E		101	NORTH	823	WEST	LEA
¹² Lse Code S	¹³ Producing Method Code	¹⁴ Gas Connection Date	¹⁵ C-129 Permit Number		¹⁶ C-129 Effective Date		¹⁷ C-129 Expiration Date		

III. Oil and Gas Transporters

¹⁸ Transporter OGRID	¹⁹ Transporter Name and Address	²⁰ O/G/W
372603	DKL FIELD SERVICES, LLC	G
20667	SHELL PIPELINE CORPORATION	O

IV. Well Completion Data

²¹ Spud Date 08/12/2022	²² Ready Date 01/06/2023	²³ TD 15238'MD	²⁴ PBTD NA	²⁵ Perforations 10492'-15190'	²⁶ DHC, MC
²⁷ Hole Size		²⁸ Casing & Tubing Size	²⁹ Depth Set		³⁰ Sacks Cement
17.5"		13.375", 54.5#, J-55	1742' MD		1165
12.25"		9.625", 40#, J-55 & HCL-80	5623' MD		2141
7.875"		5.5", 20#, P-110	15217' MD		1455

V. Well Test Data

³¹ Date New Oil 01/06/2023	³² Gas Delivery Date 01/06/2023	³³ Test Date 01/21/2023	³⁴ Test Length 24	³⁵ Tbg. Pressure	³⁶ Csg. Pressure 425
³⁷ Choke Size 52	³⁸ Oil 1389	³⁹ Water 1528	⁴⁰ Gas 1562		⁴¹ Test Method FLOW

⁴² I hereby certify that the rules of the Oil Conservation Division have been complied with and that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>Deborah Marberry</i> Printed name: Deborah Marberry Title: SR. REGULATORY ANALYST E-mail Address: dmarberry@EARTHSTONEENERGY.COM Date: 05/10/2023	Oil Conservation Division
	Approved by: <i>PATRICIA MARTINEZ</i>
	Title: <i>PETROLEUM SPECIALIST</i>
	Approval Date: <i>1/29/2025</i>
	Phone: 281-298-4246 ext. 3091

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office
☒ AMENDED REPORT
as-drilled

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-025-49709	² Pool Code 96553	³ Pool Name OJO CHISO; BONE SPRING
⁴ Property Code 332643	⁵ Property Name SQUEEZE 2 STATE COM 2BS	
⁷ OGRID No. 331165	⁸ Operator Name EARTHSTONE OPERATING, LLC	⁶ Well Number 3H ⁹ Elevation 3571.8


¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
M	2	22 S	34 E		380	SOUTH	1175	WEST	LEA

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
D	2	22 S	34 E		101	NORTH	823	WEST	LEA
¹² Dedicated Acres 324.37	¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.						

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

SQUEEZE 2 STATE COM 2BS 3H EL. = 3571.8 <table border="0"> <tr> <td> GEODETIC COORDINATES NAD 27 NMSP EAST SURFACE LOCATION N. = 515610.67 E. = 774158.66 LAT. = 32.4143953°N LONG. = 103.4449318°W KICK OFF POINT 62' FSL, 796' FWL NAD 27 NMSP EAST N. = 515289.92 E. = 773782.34 LAT. = 32.4135223°N LONG. = 103.4461598°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 27 NMSP EAST N. = 515735.97 E. = 773755.76 LAT. = 32.4147489°N LONG. = 103.4462339°W LAST TAKE POINT 155' FNL, 824' FWL NAD 27 NMSP EAST N. = 520419.80 E. = 773777.97 LAT. = 32.4276223°N LONG. = 103.4460359°W BOTTOM OF HOLE NAD 27 NMSP EAST N. = 520474.76 E. = 773777.36 LAT. = 32.4277733°N LONG. = 103.4460364°W CORNER COORDINATES TABLE NAD 27 NMSP EAST A - N. = 520596.79 E. = 775593.03 B - N. = 520565.53 E. = 772953.50 C - N. = 517893.68 E. = 772969.93 D - N. = 515221.85 E. = 772986.38 E - N. = 515242.05 E. = 775624.41 CORNER COORDINATES TABLE NAD 83 NMSP EAST A - N. = 520657.85 E. = 816776.03 B - N. = 520626.57 E. = 814136.42 C - N. = 517954.85 E. = 814152.91 D - N. = 515282.74 E. = 814169.41 E - N. = 515302.95 E. = 816807.52 </td> <td> GEODETIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION N. = 515671.58 E. = 815341.71 LAT. = 32.4145195°N LONG. = 103.4454120°W KICK OFF POINT 62' FSL, 796' FWL NAD 83 NMSP EAST N. = 515350.82 E. = 814965.39 LAT. = 32.4136465°N LONG. = 103.446400°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 83 NMSP EAST N. = 515796.88 E. = 814938.80 LAT. = 32.4148731°N LONG. = 103.4467141°W LAST TAKE POINT 155' FNL, 824' FWL NAD 83 NMSP EAST N. = 520480.84 E. = 814960.92 LAT. = 32.4277464°N LONG. = 103.4465165°W BOTTOM OF HOLE NAD 83 NMSP EAST N. = 520535.81 E. = 814960.31 LAT. = 32.4278975°N LONG. = 103.4465170°W </td> </tr> </table>		GEODETIC COORDINATES NAD 27 NMSP EAST SURFACE LOCATION N. = 515610.67 E. = 774158.66 LAT. = 32.4143953°N LONG. = 103.4449318°W KICK OFF POINT 62' FSL, 796' FWL NAD 27 NMSP EAST N. = 515289.92 E. = 773782.34 LAT. = 32.4135223°N LONG. = 103.4461598°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 27 NMSP EAST N. = 515735.97 E. = 773755.76 LAT. = 32.4147489°N LONG. = 103.4462339°W LAST TAKE POINT 155' FNL, 824' FWL NAD 27 NMSP EAST N. = 520419.80 E. = 773777.97 LAT. = 32.4276223°N LONG. = 103.4460359°W BOTTOM OF HOLE NAD 27 NMSP EAST N. = 520474.76 E. = 773777.36 LAT. = 32.4277733°N LONG. = 103.4460364°W CORNER COORDINATES TABLE NAD 27 NMSP EAST A - N. = 520596.79 E. = 775593.03 B - N. = 520565.53 E. = 772953.50 C - N. = 517893.68 E. = 772969.93 D - N. = 515221.85 E. = 772986.38 E - N. = 515242.05 E. = 775624.41 CORNER COORDINATES TABLE NAD 83 NMSP EAST A - N. = 520657.85 E. = 816776.03 B - N. = 520626.57 E. = 814136.42 C - N. = 517954.85 E. = 814152.91 D - N. = 515282.74 E. = 814169.41 E - N. = 515302.95 E. = 816807.52	GEODETIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION N. = 515671.58 E. = 815341.71 LAT. = 32.4145195°N LONG. = 103.4454120°W KICK OFF POINT 62' FSL, 796' FWL NAD 83 NMSP EAST N. = 515350.82 E. = 814965.39 LAT. = 32.4136465°N LONG. = 103.446400°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 83 NMSP EAST N. = 515796.88 E. = 814938.80 LAT. = 32.4148731°N LONG. = 103.4467141°W LAST TAKE POINT 155' FNL, 824' FWL NAD 83 NMSP EAST N. = 520480.84 E. = 814960.92 LAT. = 32.4277464°N LONG. = 103.4465165°W BOTTOM OF HOLE NAD 83 NMSP EAST N. = 520535.81 E. = 814960.31 LAT. = 32.4278975°N LONG. = 103.4465170°W	¹⁷ OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.  01/10/2023 Signature Date JENNIFER ELROD Printed Name jelrod@earthstoneenergy.com E-mail Address ¹⁸ SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JANUARY 9, 2023 Date of Survey  Signature and Seal of Professional Surveyor: Certificate Number: 12797 SURVEY NO. 9606
GEODETIC COORDINATES NAD 27 NMSP EAST SURFACE LOCATION N. = 515610.67 E. = 774158.66 LAT. = 32.4143953°N LONG. = 103.4449318°W KICK OFF POINT 62' FSL, 796' FWL NAD 27 NMSP EAST N. = 515289.92 E. = 773782.34 LAT. = 32.4135223°N LONG. = 103.4461598°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 27 NMSP EAST N. = 515735.97 E. = 773755.76 LAT. = 32.4147489°N LONG. = 103.4462339°W LAST TAKE POINT 155' FNL, 824' FWL NAD 27 NMSP EAST N. = 520419.80 E. = 773777.97 LAT. = 32.4276223°N LONG. = 103.4460359°W BOTTOM OF HOLE NAD 27 NMSP EAST N. = 520474.76 E. = 773777.36 LAT. = 32.4277733°N LONG. = 103.4460364°W CORNER COORDINATES TABLE NAD 27 NMSP EAST A - N. = 520596.79 E. = 775593.03 B - N. = 520565.53 E. = 772953.50 C - N. = 517893.68 E. = 772969.93 D - N. = 515221.85 E. = 772986.38 E - N. = 515242.05 E. = 775624.41 CORNER COORDINATES TABLE NAD 83 NMSP EAST A - N. = 520657.85 E. = 816776.03 B - N. = 520626.57 E. = 814136.42 C - N. = 517954.85 E. = 814152.91 D - N. = 515282.74 E. = 814169.41 E - N. = 515302.95 E. = 816807.52	GEODETIC COORDINATES NAD 83 NMSP EAST SURFACE LOCATION N. = 515671.58 E. = 815341.71 LAT. = 32.4145195°N LONG. = 103.4454120°W KICK OFF POINT 62' FSL, 796' FWL NAD 83 NMSP EAST N. = 515350.82 E. = 814965.39 LAT. = 32.4136465°N LONG. = 103.446400°W FIRST TAKE POINT 508' FSL, 773' FWL NAD 83 NMSP EAST N. = 515796.88 E. = 814938.80 LAT. = 32.4148731°N LONG. = 103.4467141°W LAST TAKE POINT 155' FNL, 824' FWL NAD 83 NMSP EAST N. = 520480.84 E. = 814960.92 LAT. = 32.4277464°N LONG. = 103.4465165°W BOTTOM OF HOLE NAD 83 NMSP EAST N. = 520535.81 E. = 814960.31 LAT. = 32.4278975°N LONG. = 103.4465170°W			

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Project	Lea County, NM (NAD 27)		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Squeeze 2 State Pad				
Site Position:		Northing:	515,610.64 usft	Latitude:	32° 24' 51.82 N
From:	Map	Easting:	774,158.67 usft	Longitude:	103° 26' 41.75 W
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.48 °

Well	2BS Com 3H					
Well Position	+N/-S	0.00 usft	Northing:	515,610.64 usft	Latitude:	32° 24' 51.82 N
	+E/-W	0.00 usft	Easting:	774,158.67 usft	Longitude:	103° 26' 41.75 W
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,571.80 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM_FILE	9/22/2022	6.35	60.08	47,708.10000000

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	359.65	

Survey Program	Date	11/2/2022			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
77.00	1,697.00	Survey #1 (OH)	OWSG_Rev2_MWD	OWSG MWD - Standard	
1,771.00	15,183.00	Survey #2 (OH)	OWSG_Rev2_MWD+HRGM	OWSG MWD + HRGM	
15,238.00	15,238.00	Survey #3 (OH)	Project	Projection	

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
SHL (Squeeze 2 State 2BS Com 3H)										
77.00	0.44	69.21	77.00	0.10	0.28	0.10	0.57	0.57	0.00	
214.00	0.70	45.48	213.99	0.88	1.36	0.87	0.25	0.19	-17.32	
276.00	0.48	60.68	275.99	1.27	1.86	1.26	0.43	-0.35	24.52	
358.00	0.62	265.82	357.99	1.41	1.72	1.40	1.31	0.17	-188.85	
447.00	0.48	252.40	446.98	1.26	0.88	1.25	0.21	-0.16	-15.08	

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
535.00	0.40	303.96	534.98	1.32	0.28	1.32	0.44	-0.09	58.59	
622.00	0.79	275.31	621.98	1.54	-0.57	1.55	0.55	0.45	-32.93	
709.00	0.48	216.25	708.97	1.31	-1.39	1.31	0.78	-0.36	-67.89	
797.00	0.18	356.26	796.97	1.15	-1.61	1.16	0.71	-0.34	159.10	
884.00	0.44	167.12	883.97	0.96	-1.55	0.97	0.71	0.30	196.39	
972.00	0.66	225.00	971.97	0.27	-1.83	0.28	0.64	0.25	65.77	
1,061.00	0.66	247.45	1,060.96	-0.29	-2.67	-0.27	0.29	0.00	25.22	
1,148.00	0.40	117.91	1,147.96	-0.62	-2.86	-0.61	1.11	-0.30	-148.90	
1,237.00	0.44	234.97	1,236.96	-0.97	-2.87	-0.95	0.81	0.04	131.53	
1,324.00	0.57	264.41	1,323.95	-1.20	-3.57	-1.18	0.33	0.15	33.84	
1,414.00	0.48	308.44	1,413.95	-1.01	-4.31	-0.98	0.45	-0.10	48.92	
1,501.00	0.40	335.16	1,500.95	-0.51	-4.72	-0.48	0.25	-0.09	30.71	
1,586.00	0.57	304.66	1,585.95	0.00	-5.20	0.04	0.36	0.20	-35.88	
1,675.00	0.66	340.88	1,674.94	0.74	-5.73	0.77	0.44	0.10	40.70	
1,697.00	0.62	336.31	1,696.94	0.97	-5.82	1.00	0.29	-0.18	-20.77	
1,771.00	0.44	9.03	1,770.94	1.62	-5.93	1.65	0.47	-0.24	44.22	
1,864.00	0.79	268.31	1,863.93	1.95	-6.52	1.99	1.05	0.38	-108.30	
1,958.00	2.20	239.13	1,957.90	1.00	-8.71	1.06	1.66	1.50	-31.04	
2,052.00	4.92	228.06	2,051.71	-2.62	-13.26	-2.54	2.97	2.89	-11.78	
2,146.00	6.77	224.54	2,145.22	-9.26	-20.15	-9.14	2.00	1.97	-3.74	
2,239.00	8.71	224.54	2,237.37	-18.19	-28.93	-18.01	2.09	2.09	0.00	
2,333.00	9.50	225.60	2,330.18	-28.69	-39.47	-28.45	0.86	0.84	1.13	
2,427.00	10.02	226.48	2,422.82	-39.75	-50.94	-39.43	0.58	0.55	0.94	
2,521.00	10.20	228.23	2,515.36	-50.92	-63.08	-50.54	0.38	0.19	1.86	
2,615.00	9.50	227.53	2,607.98	-61.70	-75.01	-61.24	0.76	-0.74	-0.74	
2,709.00	9.23	229.64	2,700.72	-71.82	-86.47	-71.29	0.46	-0.29	2.24	
2,803.00	9.94	230.87	2,793.41	-81.83	-98.51	-81.22	0.79	0.76	1.31	
2,898.00	9.50	230.69	2,887.05	-91.97	-110.94	-91.29	0.46	-0.46	-0.19	
2,991.00	7.91	221.55	2,978.98	-101.62	-121.12	-100.88	2.26	-1.71	-9.83	
3,085.00	7.74	208.72	3,072.11	-112.01	-128.45	-111.22	1.86	-0.18	-13.65	
3,179.00	7.74	205.73	3,165.25	-123.26	-134.24	-122.44	0.43	0.00	-3.18	
3,273.00	8.18	216.46	3,258.35	-134.35	-140.97	-133.48	1.65	0.47	11.41	
3,366.00	8.35	225.25	3,350.39	-144.42	-149.69	-143.50	1.37	0.18	9.45	
3,460.00	8.53	225.07	3,443.37	-154.15	-159.48	-153.17	0.19	0.19	-0.19	
3,553.00	8.53	225.25	3,535.34	-163.88	-169.26	-162.84	0.03	0.00	0.19	
3,648.00	8.88	225.95	3,629.25	-173.94	-179.53	-172.84	0.38	0.37	0.74	
3,742.00	8.97	228.58	3,722.11	-183.83	-190.24	-182.66	0.44	0.10	2.80	
3,836.00	8.09	229.46	3,815.07	-192.98	-200.76	-191.75	0.95	-0.94	0.94	
3,931.00	8.09	230.17	3,909.12	-201.60	-210.98	-200.31	0.11	0.00	0.75	
4,024.00	8.27	229.29	4,001.18	-210.16	-221.07	-208.80	0.24	0.19	-0.95	
4,118.00	9.15	231.05	4,094.09	-219.26	-232.01	-217.84	0.98	0.94	1.87	
4,212.00	8.27	238.08	4,187.01	-227.54	-243.56	-226.04	1.47	-0.94	7.48	

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
4,305.00	8.71	234.21	4,278.99	-235.19	-254.95	-233.63	0.78	0.47	-4.16	
4,399.00	9.94	232.63	4,371.75	-244.28	-267.17	-242.64	1.34	1.31	-1.68	
4,493.00	7.56	251.26	4,464.67	-251.19	-279.48	-249.48	3.91	-2.53	19.82	
4,587.00	5.45	255.66	4,558.06	-254.28	-289.66	-252.51	2.30	-2.24	4.68	
4,682.00	4.22	252.84	4,652.72	-256.43	-297.37	-254.61	1.32	-1.29	-2.97	
4,776.00	3.25	254.95	4,746.52	-258.15	-303.25	-256.29	1.04	-1.03	2.24	
4,870.00	2.81	239.66	4,840.39	-260.00	-307.81	-258.12	0.97	-0.47	-16.27	
4,965.00	2.73	241.07	4,935.27	-262.27	-311.80	-260.36	0.11	-0.08	1.48	
5,059.00	2.55	245.99	5,029.17	-264.21	-315.67	-262.27	0.31	-0.19	5.23	
5,152.00	2.81	251.08	5,122.07	-265.79	-319.72	-263.83	0.38	0.28	5.47	
5,246.00	3.25	255.30	5,215.94	-267.21	-324.47	-265.22	0.52	0.47	4.49	
5,341.00	3.61	255.30	5,310.77	-268.65	-329.97	-266.63	0.38	0.38	0.00	
5,435.00	3.78	257.76	5,404.58	-270.06	-335.86	-268.00	0.25	0.18	2.62	
5,530.00	3.69	260.58	5,499.37	-271.22	-341.94	-269.13	0.22	-0.09	2.97	
5,566.00	3.87	259.17	5,535.30	-271.64	-344.27	-269.53	0.56	0.50	-3.92	
5,667.00	3.78	262.33	5,636.07	-272.73	-350.92	-270.58	0.23	-0.09	3.13	
5,761.00	4.40	218.92	5,729.85	-275.95	-356.26	-273.77	3.27	0.66	-46.18	
5,856.00	2.20	188.86	5,824.70	-280.58	-358.83	-278.39	2.87	-2.32	-31.64	
5,949.00	1.93	108.53	5,917.65	-282.85	-357.62	-280.66	2.87	-0.29	-86.38	
6,043.00	2.29	107.47	6,011.59	-283.91	-354.33	-281.74	0.39	0.38	-1.13	
6,138.00	0.79	3.94	6,106.56	-283.83	-352.47	-281.67	2.73	-1.58	-108.98	
6,232.00	0.88	2.35	6,200.55	-282.46	-352.40	-280.30	0.10	0.10	-1.69	
6,326.00	1.06	7.63	6,294.54	-280.88	-352.25	-278.72	0.21	0.19	5.62	
6,420.00	0.88	350.05	6,388.52	-279.31	-352.26	-277.15	0.37	-0.19	-18.70	
6,514.00	1.14	2.88	6,482.51	-277.66	-352.34	-275.50	0.36	0.28	13.65	
6,608.00	1.32	349.17	6,576.49	-275.66	-352.49	-273.51	0.37	0.19	-14.59	
6,701.00	1.14	1.65	6,669.47	-273.69	-352.67	-271.53	0.35	-0.19	13.42	
6,796.00	1.14	348.12	6,764.45	-271.82	-352.84	-269.66	0.28	0.00	-14.24	
6,889.00	1.14	335.99	6,857.43	-270.07	-353.40	-267.90	0.26	0.00	-13.04	
6,983.00	1.06	324.39	6,951.41	-268.51	-354.29	-266.34	0.25	-0.09	-12.34	
7,076.00	0.88	333.53	7,044.40	-267.17	-355.11	-264.99	0.25	-0.19	9.83	
7,171.00	1.23	339.33	7,139.38	-265.56	-355.79	-263.38	0.38	0.37	6.11	
7,265.00	1.06	340.21	7,233.37	-263.80	-356.45	-261.62	0.18	-0.18	0.94	
7,359.00	0.53	332.12	7,327.36	-262.60	-356.94	-260.41	0.57	-0.56	-8.61	
7,452.00	0.88	108.70	7,420.35	-262.44	-356.47	-260.26	1.42	0.38	146.86	
7,545.00	1.23	104.31	7,513.34	-262.92	-354.82	-260.75	0.39	0.38	-4.72	
7,639.00	1.85	133.14	7,607.30	-264.21	-352.74	-262.05	1.04	0.66	30.67	
7,733.00	1.67	136.48	7,701.26	-266.24	-350.69	-264.09	0.22	-0.19	3.55	
7,827.00	1.06	130.67	7,795.23	-267.80	-349.09	-265.66	0.66	-0.65	-6.18	
7,921.00	1.32	129.44	7,889.21	-269.05	-347.59	-266.92	0.28	0.28	-1.31	
8,015.00	0.97	122.24	7,983.19	-270.16	-346.08	-268.05	0.40	-0.37	-7.66	
8,109.00	1.06	244.05	8,077.19	-270.97	-346.19	-268.85	1.89	0.10	129.59	

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
8,203.00	1.06	252.14	8,171.17	-271.62	-347.80	-269.49	0.16	0.00	8.61	
8,297.00	1.14	272.88	8,265.15	-271.84	-349.56	-269.70	0.43	0.09	22.06	
8,391.00	1.32	304.35	8,359.13	-271.18	-351.39	-269.03	0.73	0.19	33.48	
8,485.00	2.55	321.75	8,453.08	-268.93	-353.58	-266.76	1.44	1.31	18.51	
8,579.00	3.17	332.65	8,546.96	-264.97	-356.07	-262.79	0.87	0.66	11.60	
8,674.00	2.81	344.25	8,641.83	-260.40	-357.90	-258.21	0.74	-0.38	12.21	
8,768.00	0.79	234.39	8,735.79	-258.56	-359.06	-256.36	3.37	-2.15	-116.87	
8,861.00	1.76	211.01	8,828.77	-260.16	-360.31	-257.95	1.16	1.04	-25.14	
8,954.00	3.61	176.91	8,921.67	-264.31	-360.89	-262.10	2.55	1.99	-36.67	
9,048.00	3.34	186.05	9,015.50	-269.98	-361.02	-267.77	0.65	-0.29	9.72	
9,142.00	2.99	198.88	9,109.36	-275.03	-362.10	-272.81	0.84	-0.37	13.65	
9,237.00	6.33	182.71	9,204.03	-282.60	-363.15	-280.38	3.74	3.52	-17.02	
9,246.14	6.33	184.22	9,213.12	-283.61	-363.21	-281.39	1.82	-0.03	16.54	
Hard Line Crossing 1 @ 9246.14' MD										
9,332.00	6.51	198.17	9,298.44	-292.95	-365.08	-290.72	1.82	0.21	16.24	
9,426.00	6.07	209.78	9,391.88	-302.33	-369.21	-300.07	1.43	-0.47	12.35	
9,520.00	4.57	198.70	9,485.48	-310.19	-372.88	-307.91	1.93	-1.60	-11.79	
9,615.00	4.75	190.09	9,580.16	-317.65	-374.78	-315.35	0.76	0.19	-9.06	
9,642.00	4.40	189.91	9,607.08	-319.77	-375.16	-317.47	1.30	-1.30	-0.67	
9,733.00	3.17	347.06	9,698.00	-320.76	-376.32	-318.45	8.16	-1.35	172.69	
9,780.00	9.85	5.87	9,744.67	-315.49	-376.20	-313.18	14.73	14.21	40.02	
9,828.00	17.15	6.22	9,791.32	-304.35	-375.01	-302.05	15.21	15.21	0.73	
9,874.00	25.15	0.77	9,834.19	-287.81	-374.15	-285.52	17.89	17.39	-11.85	
9,883.60	25.52	359.98	9,842.86	-283.70	-374.12	-281.41	5.23	3.86	-8.27	
Hard Line Crossing 2 @ 9883.60' MD										
9,921.00	27.00	357.08	9,876.40	-267.16	-374.56	-264.87	5.23	3.96	-7.74	
9,968.00	30.78	356.38	9,917.55	-244.50	-375.86	-242.20	8.07	8.04	-1.49	
10,016.00	32.27	358.66	9,958.46	-219.43	-376.93	-217.12	3.97	3.10	4.75	
10,063.00	31.57	358.49	9,998.36	-194.58	-377.55	-192.27	1.50	-1.49	-0.36	
10,110.00	36.93	359.19	10,037.19	-168.15	-378.08	-165.83	11.43	11.40	1.49	
10,157.00	37.99	358.84	10,074.50	-139.57	-378.57	-137.25	2.30	2.26	-0.74	
10,205.00	43.00	356.73	10,110.99	-108.43	-379.80	-106.11	10.82	10.44	-4.40	
10,227.77	45.29	355.49	10,127.33	-92.61	-380.88	-90.28	10.77	10.08	-5.46	
LP (Squeeze 2 State 2BS Com 3H)										
10,252.00	47.75	354.27	10,144.00	-75.10	-382.45	-72.77	10.77	10.13	-5.03	
10,299.00	52.23	354.80	10,174.21	-39.28	-385.88	-36.92	9.57	9.53	1.13	
10,346.00	52.76	354.62	10,202.83	-2.15	-389.31	0.23	1.17	1.13	-0.38	
10,394.00	58.30	353.57	10,229.98	37.19	-393.40	39.60	11.68	11.54	-2.19	
10,441.00	65.42	353.21	10,252.13	78.34	-398.17	80.77	15.16	15.15	-0.77	
10,488.00	69.56	354.80	10,270.13	121.51	-402.69	123.96	9.35	8.81	3.38	
10,535.00	74.57	359.01	10,284.60	166.13	-405.08	168.60	13.65	10.66	8.96	
10,582.00	78.70	1.12	10,295.46	211.85	-405.02	214.32	9.81	8.79	4.49	
10,676.00	86.88	0.77	10,307.25	305.01	-403.49	307.47	8.71	8.70	-0.37	

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
10,770.00	90.48	0.07	10,309.42	398.97	-402.80	401.42	3.90	3.83	-0.74
10,864.00	90.57	1.12	10,308.55	492.96	-401.82	495.40	1.12	0.10	1.12
10,958.00	90.13	0.95	10,307.98	586.94	-400.13	589.37	0.50	-0.47	-0.18
11,052.00	90.04	1.65	10,307.84	680.92	-397.99	683.33	0.75	-0.10	0.74
11,145.00	89.87	1.30	10,307.91	773.89	-395.60	776.29	0.42	-0.18	-0.38
11,240.00	89.52	1.65	10,308.42	868.85	-393.15	871.24	0.52	-0.37	0.37
11,334.00	89.09	1.65	10,309.56	962.81	-390.45	965.17	0.46	-0.46	0.00
11,428.00	91.63	1.48	10,308.97	1,056.76	-387.88	1,059.11	2.71	2.70	-0.18
11,522.00	92.42	2.00	10,305.65	1,150.66	-385.03	1,152.99	1.01	0.84	0.55
11,615.00	92.86	1.83	10,301.36	1,243.51	-381.92	1,245.82	0.51	0.47	-0.18
11,709.00	93.39	1.65	10,296.24	1,337.32	-379.07	1,339.61	0.60	0.56	-0.19
11,802.00	91.54	2.00	10,292.24	1,430.19	-376.12	1,432.46	2.02	-1.99	0.38
11,895.00	91.89	1.83	10,289.46	1,523.09	-373.01	1,525.34	0.42	0.38	-0.18
11,987.00	92.51	1.30	10,285.92	1,614.99	-370.50	1,617.22	0.89	0.67	-0.58
12,081.00	90.92	0.77	10,283.11	1,708.93	-368.80	1,711.15	1.78	-1.69	-0.56
12,175.00	90.40	0.25	10,282.03	1,802.92	-367.96	1,805.13	0.78	-0.55	-0.55
12,269.00	90.57	0.60	10,281.23	1,896.91	-367.27	1,899.12	0.41	0.18	0.37
12,362.00	91.89	0.25	10,279.24	1,989.89	-366.58	1,992.09	1.47	1.42	-0.38
12,456.00	92.33	1.30	10,275.78	2,083.81	-365.31	2,086.00	1.21	0.47	1.12
12,549.00	92.59	0.60	10,271.78	2,176.71	-363.77	2,178.89	0.80	0.28	-0.75
12,642.00	92.59	0.25	10,267.58	2,269.62	-363.08	2,271.79	0.38	0.00	-0.38
12,735.00	91.45	359.54	10,264.30	2,362.56	-363.25	2,364.73	1.44	-1.23	-0.76
12,828.00	91.98	358.49	10,261.52	2,455.50	-364.85	2,457.68	1.26	0.57	-1.13
12,923.00	92.15	358.14	10,258.10	2,550.40	-367.64	2,552.59	0.41	0.18	-0.37
13,016.00	90.13	358.31	10,256.25	2,643.33	-370.52	2,645.54	2.18	-2.17	0.18
13,110.00	91.45	358.31	10,254.95	2,737.28	-373.29	2,739.50	1.40	1.40	0.00
13,203.00	89.60	359.19	10,254.10	2,830.24	-375.32	2,832.48	2.20	-1.99	0.95
13,297.00	90.13	359.19	10,254.32	2,924.23	-376.65	2,926.48	0.56	0.56	0.00
13,391.00	90.66	358.84	10,253.67	3,018.22	-378.26	3,020.47	0.68	0.56	-0.37
13,484.00	91.80	359.19	10,251.68	3,111.18	-379.86	3,113.44	1.28	1.23	0.38
13,578.00	92.77	0.42	10,247.93	3,205.10	-380.18	3,207.37	1.67	1.03	1.31
13,672.00	90.57	0.77	10,245.19	3,299.05	-379.21	3,301.31	2.37	-2.34	0.37
13,765.00	90.84	1.65	10,244.04	3,392.02	-377.24	3,394.26	0.99	0.29	0.95
13,858.00	88.99	2.00	10,244.18	3,484.97	-374.28	3,487.19	2.02	-1.99	0.38
13,951.00	88.55	1.12	10,246.18	3,577.91	-371.75	3,580.12	1.06	-0.47	-0.95
14,045.00	88.90	0.77	10,248.27	3,671.88	-370.20	3,674.07	0.53	0.37	-0.37
14,139.00	88.81	0.95	10,250.15	3,765.85	-368.79	3,768.03	0.21	-0.10	0.19
14,232.00	88.90	1.65	10,252.01	3,858.81	-366.68	3,860.97	0.76	0.10	0.75
14,326.00	90.92	359.01	10,252.15	3,952.79	-366.14	3,954.95	3.54	2.15	-2.81
14,421.00	91.19	358.84	10,250.41	4,047.76	-367.92	4,049.93	0.34	0.28	-0.18
14,515.00	91.10	358.84	10,248.53	4,141.72	-369.82	4,143.90	0.10	-0.10	0.00
14,609.00	91.36	358.84	10,246.51	4,235.68	-371.72	4,237.87	0.28	0.28	0.00

Survey Report

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
14,703.00	92.07	358.84	10,243.70	4,329.62	-373.63	4,331.82	0.76	0.76	0.00	
14,797.00	92.77	359.01	10,239.73	4,423.52	-375.39	4,425.73	0.77	0.74	0.18	
14,891.00	92.51	358.66	10,235.40	4,517.40	-377.30	4,519.62	0.46	-0.28	-0.37	
14,984.00	91.45	359.72	10,232.18	4,610.33	-378.61	4,612.56	1.61	-1.14	1.14	
15,078.00	91.10	359.19	10,230.09	4,704.30	-379.51	4,706.53	0.68	-0.37	-0.56	
15,171.00	91.63	359.54	10,227.88	4,797.27	-380.54	4,799.50	0.68	0.57	0.38	
15,183.00	91.80	359.37	10,227.52	4,809.26	-380.65	4,811.50	2.00	1.42	-1.42	
15,237.39	91.80	359.37	10,225.81	4,863.62	-381.25	4,865.86	0.00	0.00	0.00	
Hard Line Crossing 3 @ 15237.39' MD - PBHL (Squeeze 2 State 2BS Com 3H)										
15,238.00	91.80	359.37	10,225.79	4,864.23	-381.25	4,866.47	0.00	0.00	0.00	
Projection to Bit @ 15238' MD - BHL (Squeeze 2 State 2BS Com 3H)										

Design Targets										
Target Name - hit/miss target - Shape	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
SHL (Squeeze 2 State 2 - actual wellpath hits target center - Point	0.00	0.00	0.00	0.00	0.00	515,610.64	774,158.67	32° 24' 51.82 N	103° 26' 41.75 W	
BHL (Squeeze 2 State 2 - actual wellpath hits target center - Point	0.00	0.00	10,225.79	4,864.23	-381.25	520,474.87	773,777.42	32° 25' 39.99 N	103° 26' 45.73 W	
PBHL (Squeeze 2 State - actual wellpath misses target center by 32.35usft at 15237.39usft MD (10225.81 TVD, 4863.62 N, -381.25 E) - Point	0.00	0.00	10,248.04	4,864.35	-404.74	520,474.99	773,753.93	32° 25' 39.99 N	103° 26' 46.00 W	
LP (Squeeze 2 State 2B - actual wellpath misses target center by 270.73usft at 10227.77usft MD (10127.33 TVD, -92.61 N, -380.88 E) - Point	0.00	0.00	10,319.92	-282.72	-373.07	515,327.92	773,785.60	32° 24' 49.06 N	103° 26' 46.13 W	

Design Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
9,246.14	9,213.12	-283.61	-363.21	Hard Line Crossing 1 @ 9246.14' MD	
9,883.60	9,842.86	-283.70	-374.12	Hard Line Crossing 2 @ 9883.60' MD	
15,237.39	10,225.81	4,863.62	-381.25	Hard Line Crossing 3 @ 15237.39' MD	
15,238.00	10,225.79	4,864.23	-381.25	Projection to Bit @ 15238' MD	

Checked By: _____	Approved By: _____	Date: _____
-------------------	--------------------	-------------

Survey Report - Geographic

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Project	Lea County, NM (NAD 27)		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site	Squeeze 2 State Pad				
Site Position:		Northing:	515,610.64 usft	Latitude:	32° 24' 51.82 N
From:	Map	Easting:	774,158.67 usft	Longitude:	103° 26' 41.75 W
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.48 °

Well	2BS Com 3H					
Well Position	+N/-S	0.00 usft	Northing:	515,610.64 usft	Latitude:	32° 24' 51.82 N
	+E/-W	0.00 usft	Easting:	774,158.67 usft	Longitude:	103° 26' 41.75 W
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,571.80 usft

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM_FILE	9/22/2022	6.35	60.08	47,708.10000000

Design	OH				
Audit Notes:					
Version:	1.0	Phase:	ACTUAL	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00		359.65

Survey Program	Date	11/2/2022			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
77.00	1,697.00	Survey #1 (OH)	OWSG_Rev2_MWD	OWSG MWD - Standard	
1,771.00	15,183.00	Survey #2 (OH)	OWSG_Rev2_MWD+HRGM	OWSG MWD + HRGM	
15,238.00	15,238.00	Survey #3 (OH)	Project	Projection	

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.00	0.00	0.00	0.00	0.00	0.00	515,610.64	774,158.67	32° 24' 51.82 N	103° 26' 41.75 W
SHL (Squeeze 2 State 2BS Com 3H)									
77.00	0.44	69.21	77.00	0.10	0.28	515,610.75	774,158.94	32° 24' 51.82 N	103° 26' 41.75 W
214.00	0.70	45.48	213.99	0.88	1.36	515,611.52	774,160.03	32° 24' 51.83 N	103° 26' 41.74 W
276.00	0.48	60.68	275.99	1.27	1.86	515,611.91	774,160.53	32° 24' 51.84 N	103° 26' 41.73 W
358.00	0.62	265.82	357.99	1.41	1.72	515,612.05	774,160.39	32° 24' 51.84 N	103° 26' 41.73 W
447.00	0.48	252.40	446.98	1.26	0.88	515,611.90	774,159.55	32° 24' 51.84 N	103° 26' 41.74 W
535.00	0.40	303.96	534.98	1.32	0.28	515,611.96	774,158.94	32° 24' 51.84 N	103° 26' 41.75 W

Survey Report - Geographic

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Corn 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Corn 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
622.00	0.79	275.31	621.98	1.54	-0.57	515,612.19	774,158.09	32° 24' 51.84 N	103° 26' 41.76 W
709.00	0.48	216.25	708.97	1.31	-1.39	515,611.95	774,157.28	32° 24' 51.84 N	103° 26' 41.77 W
797.00	0.18	356.26	796.97	1.15	-1.61	515,611.79	774,157.06	32° 24' 51.83 N	103° 26' 41.77 W
884.00	0.44	167.12	883.97	0.96	-1.55	515,611.60	774,157.12	32° 24' 51.83 N	103° 26' 41.77 W
972.00	0.66	225.00	971.97	0.27	-1.83	515,610.91	774,156.84	32° 24' 51.83 N	103° 26' 41.78 W
1,061.00	0.66	247.45	1,060.96	-0.29	-2.67	515,610.35	774,156.00	32° 24' 51.82 N	103° 26' 41.79 W
1,148.00	0.40	117.91	1,147.96	-0.62	-2.86	515,610.02	774,155.81	32° 24' 51.82 N	103° 26' 41.79 W
1,237.00	0.44	234.97	1,236.96	-0.97	-2.87	515,609.68	774,155.80	32° 24' 51.81 N	103° 26' 41.79 W
1,324.00	0.57	264.41	1,323.95	-1.20	-3.57	515,609.44	774,155.10	32° 24' 51.81 N	103° 26' 41.80 W
1,414.00	0.48	308.44	1,413.95	-1.01	-4.31	515,609.63	774,154.36	32° 24' 51.81 N	103° 26' 41.81 W
1,501.00	0.40	335.16	1,500.95	-0.51	-4.72	515,610.14	774,153.94	32° 24' 51.82 N	103° 26' 41.81 W
1,586.00	0.57	304.66	1,585.95	0.00	-5.20	515,610.65	774,153.47	32° 24' 51.82 N	103° 26' 41.82 W
1,675.00	0.66	340.88	1,674.94	0.74	-5.73	515,611.38	774,152.94	32° 24' 51.83 N	103° 26' 41.82 W
1,697.00	0.62	336.31	1,696.94	0.97	-5.82	515,611.61	774,152.85	32° 24' 51.83 N	103° 26' 41.82 W
1,771.00	0.44	9.03	1,770.94	1.62	-5.93	515,612.26	774,152.73	32° 24' 51.84 N	103° 26' 41.82 W
1,864.00	0.79	268.31	1,863.93	1.95	-6.52	515,612.59	774,152.15	32° 24' 51.84 N	103° 26' 41.83 W
1,958.00	2.20	239.13	1,957.90	1.00	-8.71	515,611.65	774,149.95	32° 24' 51.83 N	103° 26' 41.86 W
2,052.00	4.92	228.06	2,051.71	-2.62	-13.26	515,608.03	774,145.40	32° 24' 51.80 N	103° 26' 41.91 W
2,146.00	6.77	224.54	2,145.22	-9.26	-20.15	515,601.38	774,138.52	32° 24' 51.73 N	103° 26' 41.99 W
2,239.00	8.71	224.54	2,237.37	-18.19	-28.93	515,592.45	774,129.73	32° 24' 51.65 N	103° 26' 42.09 W
2,333.00	9.50	225.60	2,330.18	-28.69	-39.47	515,581.95	774,119.20	32° 24' 51.54 N	103° 26' 42.22 W
2,427.00	10.02	226.48	2,422.82	-39.75	-50.94	515,570.90	774,107.73	32° 24' 51.43 N	103° 26' 42.35 W
2,521.00	10.20	228.23	2,515.36	-50.92	-63.08	515,559.72	774,095.59	32° 24' 51.32 N	103° 26' 42.50 W
2,615.00	9.50	227.53	2,607.98	-61.70	-75.01	515,548.94	774,083.66	32° 24' 51.22 N	103° 26' 42.64 W
2,709.00	9.23	229.64	2,700.72	-71.82	-86.47	515,538.82	774,072.19	32° 24' 51.12 N	103° 26' 42.77 W
2,803.00	9.94	230.87	2,793.41	-81.83	-98.51	515,528.82	774,060.16	32° 24' 51.02 N	103° 26' 42.91 W
2,898.00	9.50	230.69	2,887.05	-91.97	-110.94	515,518.67	774,047.73	32° 24' 50.92 N	103° 26' 43.06 W
2,991.00	7.91	221.55	2,978.98	-101.62	-121.12	515,509.02	774,037.55	32° 24' 50.83 N	103° 26' 43.18 W
3,085.00	7.74	208.72	3,072.11	-112.01	-128.45	515,498.63	774,030.21	32° 24' 50.73 N	103° 26' 43.26 W
3,179.00	7.74	205.73	3,165.25	-123.26	-134.24	515,487.38	774,024.42	32° 24' 50.61 N	103° 26' 43.33 W
3,273.00	8.18	216.46	3,258.35	-134.35	-140.97	515,476.30	774,017.70	32° 24' 50.51 N	103° 26' 43.41 W
3,366.00	8.35	225.25	3,350.39	-144.42	-149.69	515,466.22	774,008.97	32° 24' 50.41 N	103° 26' 43.51 W
3,460.00	8.53	225.07	3,443.37	-154.15	-159.48	515,456.49	773,999.19	32° 24' 50.31 N	103° 26' 43.63 W
3,553.00	8.53	225.25	3,535.34	-163.88	-169.26	515,446.76	773,989.41	32° 24' 50.22 N	103° 26' 43.74 W
3,648.00	8.88	225.95	3,629.25	-173.94	-179.53	515,436.71	773,979.14	32° 24' 50.12 N	103° 26' 43.87 W
3,742.00	8.97	228.58	3,722.11	-183.83	-190.24	515,426.81	773,968.43	32° 24' 50.02 N	103° 26' 43.99 W
3,836.00	8.09	229.46	3,815.07	-192.98	-200.76	515,417.67	773,957.90	32° 24' 49.93 N	103° 26' 44.12 W
3,931.00	8.09	230.17	3,909.12	-201.60	-210.98	515,409.04	773,947.69	32° 24' 49.85 N	103° 26' 44.24 W
4,024.00	8.27	229.29	4,001.18	-210.16	-221.07	515,400.49	773,937.60	32° 24' 49.76 N	103° 26' 44.35 W
4,118.00	9.15	231.05	4,094.09	-219.26	-232.01	515,391.38	773,926.66	32° 24' 49.67 N	103° 26' 44.48 W
4,212.00	8.27	238.08	4,187.01	-227.54	-243.56	515,383.10	773,915.11	32° 24' 49.59 N	103° 26' 44.62 W
4,305.00	8.71	234.21	4,278.99	-235.19	-254.95	515,375.45	773,903.72	32° 24' 49.52 N	103° 26' 44.75 W
4,399.00	9.94	232.63	4,371.75	-244.28	-267.17	515,366.36	773,891.50	32° 24' 49.43 N	103° 26' 44.89 W
4,493.00	7.56	251.26	4,464.67	-251.19	-279.48	515,359.45	773,879.19	32° 24' 49.36 N	103° 26' 45.04 W
4,587.00	5.45	255.66	4,558.06	-254.28	-289.66	515,356.36	773,869.01	32° 24' 49.33 N	103° 26' 45.16 W
4,682.00	4.22	252.84	4,652.72	-256.43	-297.37	515,354.21	773,861.30	32° 24' 49.31 N	103° 26' 45.25 W
4,776.00	3.25	254.95	4,746.52	-258.15	-303.25	515,352.50	773,855.42	32° 24' 49.29 N	103° 26' 45.32 W
4,870.00	2.81	239.66	4,840.39	-260.00	-307.81	515,350.64	773,850.86	32° 24' 49.28 N	103° 26' 45.37 W
4,965.00	2.73	241.07	4,935.27	-262.27	-311.80	515,348.37	773,846.87	32° 24' 49.25 N	103° 26' 45.42 W
5,059.00	2.55	245.99	5,029.17	-264.21	-315.67	515,346.44	773,843.00	32° 24' 49.23 N	103° 26' 45.46 W
5,152.00	2.81	251.08	5,122.07	-265.79	-319.72	515,344.85	773,838.95	32° 24' 49.22 N	103° 26' 45.51 W
5,246.00	3.25	255.30	5,215.94	-267.21	-324.47	515,343.43	773,834.19	32° 24' 49.21 N	103° 26' 45.57 W
5,341.00	3.61	255.30	5,310.77	-268.65	-329.97	515,341.99	773,828.70	32° 24' 49.19 N	103° 26' 45.63 W

Survey Report - Geographic

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Corn 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Corn 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
5,435.00	3.78	257.76	5,404.58	-270.06	-335.86	515,340.58	773,822.81	32° 24' 49.18 N	103° 26' 45.70 W
5,530.00	3.69	260.58	5,499.37	-271.22	-341.94	515,339.42	773,816.73	32° 24' 49.17 N	103° 26' 45.77 W
5,566.00	3.87	259.17	5,535.30	-271.64	-344.27	515,339.00	773,814.39	32° 24' 49.16 N	103° 26' 45.80 W
5,667.00	3.78	262.33	5,636.07	-272.73	-350.92	515,337.91	773,807.75	32° 24' 49.15 N	103° 26' 45.87 W
5,761.00	4.40	218.92	5,729.85	-275.95	-356.26	515,334.69	773,802.41	32° 24' 49.12 N	103° 26' 45.94 W
5,856.00	2.20	188.86	5,824.70	-280.58	-358.83	515,330.06	773,799.84	32° 24' 49.08 N	103° 26' 45.97 W
5,949.00	1.93	108.53	5,917.65	-282.85	-357.62	515,327.80	773,801.05	32° 24' 49.05 N	103° 26' 45.95 W
6,043.00	2.29	107.47	6,011.59	-283.91	-354.33	515,326.73	773,804.34	32° 24' 49.04 N	103° 26' 45.92 W
6,138.00	0.79	3.94	6,106.56	-283.83	-352.47	515,326.81	773,806.20	32° 24' 49.04 N	103° 26' 45.89 W
6,232.00	0.88	2.35	6,200.55	-282.46	-352.40	515,328.18	773,806.27	32° 24' 49.06 N	103° 26' 45.89 W
6,326.00	1.06	7.63	6,294.54	-280.88	-352.25	515,329.76	773,806.42	32° 24' 49.07 N	103° 26' 45.89 W
6,420.00	0.88	350.05	6,388.52	-279.31	-352.26	515,331.34	773,806.41	32° 24' 49.09 N	103° 26' 45.89 W
6,514.00	1.14	2.88	6,482.51	-277.66	-352.34	515,332.98	773,806.33	32° 24' 49.10 N	103° 26' 45.89 W
6,608.00	1.32	349.17	6,576.49	-275.66	-352.49	515,334.98	773,806.17	32° 24' 49.12 N	103° 26' 45.89 W
6,701.00	1.14	1.65	6,669.47	-273.69	-352.67	515,336.95	773,806.00	32° 24' 49.14 N	103° 26' 45.89 W
6,796.00	1.14	348.12	6,764.45	-271.82	-352.84	515,338.82	773,805.83	32° 24' 49.16 N	103° 26' 45.90 W
6,889.00	1.14	335.99	6,857.43	-270.07	-353.40	515,340.57	773,805.26	32° 24' 49.18 N	103° 26' 45.90 W
6,983.00	1.06	324.39	6,951.41	-268.51	-354.29	515,342.14	773,804.38	32° 24' 49.20 N	103° 26' 45.91 W
7,076.00	0.88	333.53	7,044.40	-267.17	-355.11	515,343.47	773,803.56	32° 24' 49.21 N	103° 26' 45.92 W
7,171.00	1.23	339.33	7,139.38	-265.56	-355.79	515,345.08	773,802.87	32° 24' 49.22 N	103° 26' 45.93 W
7,265.00	1.06	340.21	7,233.37	-263.80	-356.45	515,346.84	773,802.22	32° 24' 49.24 N	103° 26' 45.94 W
7,359.00	0.53	332.12	7,327.36	-262.60	-356.94	515,348.05	773,801.72	32° 24' 49.25 N	103° 26' 45.94 W
7,452.00	0.88	108.70	7,420.35	-262.44	-356.47	515,348.20	773,802.20	32° 24' 49.26 N	103° 26' 45.94 W
7,545.00	1.23	104.31	7,513.34	-262.92	-354.82	515,347.72	773,803.84	32° 24' 49.25 N	103° 26' 45.92 W
7,639.00	1.85	133.14	7,607.30	-264.21	-352.74	515,346.43	773,805.93	32° 24' 49.24 N	103° 26' 45.89 W
7,733.00	1.67	136.48	7,701.26	-266.24	-350.69	515,344.40	773,807.98	32° 24' 49.22 N	103° 26' 45.87 W
7,827.00	1.06	130.67	7,795.23	-267.80	-349.09	515,342.84	773,809.58	32° 24' 49.20 N	103° 26' 45.85 W
7,921.00	1.32	129.44	7,889.21	-269.05	-347.59	515,341.59	773,811.08	32° 24' 49.19 N	103° 26' 45.84 W
8,015.00	0.97	122.24	7,983.19	-270.16	-346.08	515,340.48	773,812.59	32° 24' 49.18 N	103° 26' 45.82 W
8,109.00	1.06	244.05	8,077.19	-270.97	-346.19	515,339.67	773,812.48	32° 24' 49.17 N	103° 26' 45.82 W
8,203.00	1.06	252.14	8,171.17	-271.62	-347.80	515,339.02	773,810.87	32° 24' 49.16 N	103° 26' 45.84 W
8,297.00	1.14	272.88	8,265.15	-271.84	-349.56	515,338.81	773,809.11	32° 24' 49.16 N	103° 26' 45.86 W
8,391.00	1.32	304.35	8,359.13	-271.18	-351.39	515,339.46	773,807.28	32° 24' 49.17 N	103° 26' 45.88 W
8,485.00	2.55	321.75	8,453.08	-268.93	-353.58	515,341.72	773,805.09	32° 24' 49.19 N	103° 26' 45.91 W
8,579.00	3.17	332.65	8,546.96	-264.97	-356.07	515,345.67	773,802.60	32° 24' 49.23 N	103° 26' 45.93 W
8,674.00	2.81	344.25	8,641.83	-260.40	-357.90	515,350.24	773,800.76	32° 24' 49.28 N	103° 26' 45.95 W
8,768.00	0.79	234.39	8,735.79	-258.56	-359.06	515,352.08	773,799.61	32° 24' 49.29 N	103° 26' 45.97 W
8,861.00	1.76	211.01	8,828.77	-260.16	-360.31	515,350.48	773,798.35	32° 24' 49.28 N	103° 26' 45.98 W
8,954.00	3.61	176.91	8,921.67	-264.31	-360.89	515,346.34	773,797.77	32° 24' 49.24 N	103° 26' 45.99 W
9,048.00	3.34	186.05	9,015.50	-269.98	-361.02	515,340.66	773,797.65	32° 24' 49.18 N	103° 26' 45.99 W
9,142.00	2.99	198.88	9,109.36	-275.03	-362.10	515,335.62	773,796.56	32° 24' 49.13 N	103° 26' 46.01 W
9,237.00	6.33	182.71	9,204.03	-282.60	-363.15	515,328.04	773,795.51	32° 24' 49.06 N	103° 26' 46.02 W
9,246.14	6.33	184.22	9,213.12	-283.61	-363.21	515,327.03	773,795.45	32° 24' 49.05 N	103° 26' 46.02 W
Hard Line Crossing 1 @ 9246.14' MD									
9,332.00	6.51	198.17	9,298.44	-292.95	-365.08	515,317.69	773,793.59	32° 24' 48.95 N	103° 26' 46.04 W
9,426.00	6.07	209.78	9,391.88	-302.33	-369.21	515,308.31	773,789.46	32° 24' 48.86 N	103° 26' 46.09 W
9,520.00	4.57	198.70	9,485.48	-310.19	-372.88	515,300.45	773,785.79	32° 24' 48.78 N	103° 26' 46.13 W
9,615.00	4.75	190.09	9,580.16	-317.65	-374.78	515,292.99	773,783.88	32° 24' 48.71 N	103° 26' 46.16 W
9,642.00	4.40	189.91	9,607.08	-319.77	-375.16	515,290.87	773,783.51	32° 24' 48.69 N	103° 26' 46.16 W
9,733.00	3.17	347.06	9,698.00	-320.76	-376.32	515,289.88	773,782.34	32° 24' 48.68 N	103° 26' 46.18 W
9,780.00	9.85	5.87	9,744.67	-315.49	-376.20	515,295.16	773,782.47	32° 24' 48.73 N	103° 26' 46.17 W
9,828.00	17.15	6.22	9,791.32	-304.35	-375.01	515,306.29	773,783.65	32° 24' 48.84 N	103° 26' 46.16 W
9,874.00	25.15	0.77	9,834.19	-287.81	-374.15	515,322.84	773,784.52	32° 24' 49.01 N	103° 26' 46.15 W

Survey Report - Geographic

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
9,883.60	25.52	359.98	9,842.86	-283.70	-374.12	515,326.94	773,784.55	32° 24' 49.05 N	103° 26' 46.15 W	
Hard Line Crossing 2 @ 9883.60' MD										
9,921.00	27.00	357.08	9,876.40	-267.16	-374.56	515,343.48	773,784.11	32° 24' 49.21 N	103° 26' 46.15 W	
9,968.00	30.78	356.38	9,917.55	-244.50	-375.86	515,366.14	773,782.81	32° 24' 49.43 N	103° 26' 46.16 W	
10,016.00	32.27	358.66	9,958.46	-219.43	-376.93	515,391.21	773,781.73	32° 24' 49.68 N	103° 26' 46.17 W	
10,063.00	31.57	358.49	9,998.36	-194.58	-377.55	515,416.06	773,781.12	32° 24' 49.93 N	103° 26' 46.18 W	
10,110.00	36.93	359.19	10,037.19	-168.15	-378.08	515,442.49	773,780.59	32° 24' 50.19 N	103° 26' 46.18 W	
10,157.00	37.99	358.84	10,074.50	-139.57	-378.57	515,471.07	773,780.10	32° 24' 50.47 N	103° 26' 46.18 W	
10,205.00	43.00	356.73	10,110.99	-108.43	-379.80	515,502.21	773,778.87	32° 24' 50.78 N	103° 26' 46.20 W	
10,227.77	45.29	355.49	10,127.33	-92.61	-380.88	515,518.03	773,777.79	32° 24' 50.94 N	103° 26' 46.21 W	
LP (Squeeze 2 State 2BS Com 3H)										
10,252.00	47.75	354.27	10,144.00	-75.10	-382.45	515,535.54	773,776.21	32° 24' 51.11 N	103° 26' 46.22 W	
10,299.00	52.23	354.80	10,174.21	-39.28	-385.88	515,571.36	773,772.79	32° 24' 51.47 N	103° 26' 46.26 W	
10,346.00	52.76	354.62	10,202.83	-2.15	-389.31	515,608.49	773,769.35	32° 24' 51.83 N	103° 26' 46.30 W	
10,394.00	58.30	353.57	10,229.98	37.19	-393.40	515,647.84	773,765.27	32° 24' 52.22 N	103° 26' 46.34 W	
10,441.00	65.42	353.21	10,252.13	78.34	-398.17	515,688.98	773,760.50	32° 24' 52.63 N	103° 26' 46.39 W	
10,488.00	69.56	354.80	10,270.13	121.51	-402.69	515,732.15	773,755.97	32° 24' 53.06 N	103° 26' 46.44 W	
10,535.00	74.57	359.01	10,284.60	166.13	-405.08	515,776.77	773,753.59	32° 24' 53.50 N	103° 26' 46.46 W	
10,582.00	78.70	1.12	10,295.46	211.85	-405.02	515,822.49	773,753.64	32° 24' 53.95 N	103° 26' 46.46 W	
10,676.00	86.88	0.77	10,307.25	305.01	-403.49	515,915.65	773,755.18	32° 24' 54.87 N	103° 26' 46.43 W	
10,770.00	90.48	0.07	10,309.42	398.97	-402.80	516,009.61	773,755.87	32° 24' 55.80 N	103° 26' 46.41 W	
10,864.00	90.57	1.12	10,308.55	492.96	-401.82	516,103.60	773,756.84	32° 24' 56.73 N	103° 26' 46.39 W	
10,958.00	90.13	0.95	10,307.98	586.94	-400.13	516,197.58	773,758.54	32° 24' 57.66 N	103° 26' 46.37 W	
11,052.00	90.04	1.65	10,307.84	680.92	-397.99	516,291.56	773,760.67	32° 24' 58.59 N	103° 26' 46.33 W	
11,145.00	89.87	1.30	10,307.91	773.89	-395.60	516,384.53	773,763.07	32° 24' 59.51 N	103° 26' 46.29 W	
11,240.00	89.52	1.65	10,308.42	868.85	-393.15	516,479.49	773,765.51	32° 25' 0.45 N	103° 26' 46.26 W	
11,334.00	89.09	1.65	10,309.56	962.81	-390.45	516,573.45	773,768.22	32° 25' 1.38 N	103° 26' 46.22 W	
11,428.00	91.63	1.48	10,308.97	1,056.76	-387.88	516,667.40	773,770.79	32° 25' 2.31 N	103° 26' 46.18 W	
11,522.00	92.42	2.00	10,305.65	1,150.66	-385.03	516,761.30	773,773.64	32° 25' 3.24 N	103° 26' 46.13 W	
11,615.00	92.86	1.83	10,301.36	1,243.51	-381.92	516,854.15	773,776.74	32° 25' 4.16 N	103° 26' 46.09 W	
11,709.00	93.39	1.65	10,296.24	1,337.32	-379.07	516,947.97	773,779.59	32° 25' 5.09 N	103° 26' 46.05 W	
11,802.00	91.54	2.00	10,292.24	1,430.19	-376.12	517,040.83	773,782.55	32° 25' 6.01 N	103° 26' 46.00 W	
11,895.00	91.89	1.83	10,289.46	1,523.09	-373.01	517,133.73	773,785.66	32° 25' 6.92 N	103° 26' 45.96 W	
11,987.00	92.51	1.30	10,285.92	1,614.99	-370.50	517,225.63	773,788.17	32° 25' 7.83 N	103° 26' 45.92 W	
12,081.00	90.92	0.77	10,283.11	1,708.93	-368.80	517,319.57	773,789.87	32° 25' 8.76 N	103° 26' 45.89 W	
12,175.00	90.40	0.25	10,282.03	1,802.92	-367.96	517,413.56	773,790.70	32° 25' 9.69 N	103° 26' 45.87 W	
12,269.00	90.57	0.60	10,281.23	1,896.91	-367.27	517,507.55	773,791.40	32° 25' 10.62 N	103° 26' 45.85 W	
12,362.00	91.89	0.25	10,279.24	1,989.89	-366.58	517,600.53	773,792.09	32° 25' 11.54 N	103° 26' 45.84 W	
12,456.00	92.33	1.30	10,275.78	2,083.81	-365.31	517,694.45	773,793.36	32° 25' 12.47 N	103° 26' 45.81 W	
12,549.00	92.59	0.60	10,271.78	2,176.71	-363.77	517,787.35	773,794.90	32° 25' 13.39 N	103° 26' 45.79 W	
12,642.00	92.59	0.25	10,267.58	2,269.62	-363.08	517,880.26	773,795.59	32° 25' 14.31 N	103° 26' 45.77 W	
12,735.00	91.45	359.54	10,264.30	2,362.56	-363.25	517,973.20	773,795.42	32° 25' 15.23 N	103° 26' 45.76 W	
12,828.00	91.98	358.49	10,261.52	2,455.50	-364.85	518,066.14	773,793.82	32° 25' 16.15 N	103° 26' 45.77 W	
12,923.00	92.15	358.14	10,258.10	2,550.40	-367.64	518,161.04	773,791.03	32° 25' 17.09 N	103° 26' 45.80 W	
13,016.00	90.13	358.31	10,256.25	2,643.33	-370.52	518,253.97	773,788.15	32° 25' 18.01 N	103° 26' 45.82 W	
13,110.00	91.45	358.31	10,254.95	2,737.28	-373.29	518,347.92	773,785.38	32° 25' 18.94 N	103° 26' 45.84 W	
13,203.00	89.60	359.19	10,254.10	2,830.24	-375.32	518,440.89	773,783.35	32° 25' 19.86 N	103° 26' 45.86 W	
13,297.00	90.13	359.19	10,254.32	2,924.23	-376.65	518,534.88	773,782.02	32° 25' 20.79 N	103° 26' 45.86 W	
13,391.00	90.66	358.84	10,253.67	3,018.22	-378.26	518,628.86	773,780.40	32° 25' 21.72 N	103° 26' 45.87 W	
13,484.00	91.80	359.19	10,251.68	3,111.18	-379.86	518,721.82	773,778.81	32° 25' 22.64 N	103° 26' 45.88 W	
13,578.00	92.77	0.42	10,247.93	3,205.10	-380.18	518,815.74	773,778.49	32° 25' 23.57 N	103° 26' 45.88 W	
13,672.00	90.57	0.77	10,245.19	3,299.05	-379.21	518,909.69	773,779.46	32° 25' 24.50 N	103° 26' 45.86 W	
13,765.00	90.84	1.65	10,244.04	3,392.02	-377.24	519,002.66	773,781.43	32° 25' 25.42 N	103° 26' 45.83 W	

Survey Report - Geographic

Company:	Earthstone Operating, LLC	Local Co-ordinate Reference:	Well 2BS Com 3H
Project:	Lea County, NM (NAD 27)	TVD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Site:	Squeeze 2 State Pad	MD Reference:	GE 3571.8' + KB 26' @ 3597.80usft (Scan Patriot)
Well:	2BS Com 3H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	OH	Database:	LEAM Multi_User Db

Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
13,858.00	88.99	2.00	10,244.18	3,484.97	-374.28	519,095.61	773,784.39	32° 25' 26.34 N	103° 26' 45.78 W
13,951.00	88.55	1.12	10,246.18	3,577.91	-371.75	519,188.56	773,786.92	32° 25' 27.26 N	103° 26' 45.74 W
14,045.00	88.90	0.77	10,248.27	3,671.88	-370.20	519,282.52	773,788.47	32° 25' 28.19 N	103° 26' 45.72 W
14,139.00	88.81	0.95	10,250.15	3,765.85	-368.79	519,376.49	773,789.88	32° 25' 29.12 N	103° 26' 45.69 W
14,232.00	88.90	1.65	10,252.01	3,858.81	-366.68	519,469.45	773,791.99	32° 25' 30.04 N	103° 26' 45.66 W
14,326.00	90.92	359.01	10,252.15	3,952.79	-366.14	519,563.43	773,792.53	32° 25' 30.97 N	103° 26' 45.64 W
14,421.00	91.19	358.84	10,250.41	4,047.76	-367.92	519,658.40	773,790.75	32° 25' 31.91 N	103° 26' 45.65 W
14,515.00	91.10	358.84	10,248.53	4,141.72	-369.82	519,752.36	773,788.85	32° 25' 32.84 N	103° 26' 45.67 W
14,609.00	91.36	358.84	10,246.51	4,235.68	-371.72	519,846.32	773,786.94	32° 25' 33.77 N	103° 26' 45.68 W
14,703.00	92.07	358.84	10,243.70	4,329.62	-373.63	519,940.26	773,785.04	32° 25' 34.69 N	103° 26' 45.69 W
14,797.00	92.77	359.01	10,239.73	4,423.52	-375.39	520,034.16	773,783.28	32° 25' 35.62 N	103° 26' 45.70 W
14,891.00	92.51	358.66	10,235.40	4,517.40	-377.30	520,128.04	773,781.37	32° 25' 36.55 N	103° 26' 45.72 W
14,984.00	91.45	359.72	10,232.18	4,610.33	-378.61	520,220.97	773,780.06	32° 25' 37.47 N	103° 26' 45.72 W
15,078.00	91.10	359.19	10,230.09	4,704.30	-379.51	520,314.94	773,779.16	32° 25' 38.40 N	103° 26' 45.73 W
15,171.00	91.63	359.54	10,227.88	4,797.27	-380.54	520,407.91	773,778.13	32° 25' 39.32 N	103° 26' 45.73 W
15,183.00	91.80	359.37	10,227.52	4,809.26	-380.65	520,419.90	773,778.02	32° 25' 39.44 N	103° 26' 45.73 W
15,237.39	91.80	359.37	10,225.81	4,863.62	-381.25	520,474.26	773,777.42	32° 25' 39.98 N	103° 26' 45.73 W
Hard Line Crossing 3 @ 15237.39' MD - PBHL (Squeeze 2 State 2BS Com 3H)									
15,238.00	91.80	359.37	10,225.79	4,864.23	-381.25	520,474.87	773,777.41	32° 25' 39.99 N	103° 26' 45.73 W
Projection to Bit @ 15238' MD - BHL (Squeeze 2 State 2BS Com 3H)									

Design Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
9,246.14	9,213.12	-283.61	-363.21	Hard Line Crossing 1 @ 9246.14' MD	
9,883.60	9,842.86	-283.70	-374.12	Hard Line Crossing 2 @ 9883.60' MD	
15,237.39	10,225.81	4,863.62	-381.25	Hard Line Crossing 3 @ 15237.39' MD	
15,238.00	10,225.79	4,864.23	-381.25	Projection to Bit @ 15238' MD	

Intent ☐ As Drilled ☒

API # 30-025-49709		
Operator Name: EARTHSTONE OPERATING, LLC	Property Name: SQUEEZE 2 STATE COM 2BS	Well Number 3H

Kick Off Point (KOP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
M	2	22S	34E		62	SOUTH	796	WEST	LEA
Latitude 32.4136465					Longitude 103.4466400				NAD 83

First Take Point (FTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
M	2	22S	34E		508	SOUTH	773	WEST	LEA
Latitude 32.4148731					Longitude 103.4467141				NAD 83

Last Take Point (LTP)

UL	Section	Township	Range	Lot	Feet	From N/S	Feet	From E/W	County
D	2	22S	34E	4	155	NORTH	824	WEST	LEA
Latitude 32.4277464					Longitude 103.4465165				NAD 83

Is this well the defining well for the Horizontal Spacing Unit? ☐ NOIs this well an infill well? ☐ YES

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-025-49156		
Operator Name: EARTHSTONE OPERATING, LLC	Property Name: SQUEEZE 2 STATE COM 3BS	Well Number 1H

KZ 06/29/2018

Submit a Copy To Appropriate District
Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-49709
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator EARTHSTONE OPERATING, LLC		6. State Oil & Gas Lease No.
3. Address of Operator 1400 WOODLOCH FOREST DR., SUITE 300 THE WOODLANDS, TX 77380		7. Lease Name or Unit Agreement Name SQUEEZE 2 STATE COM
4. Well Location Unit Letter M : 380 feet from the SOUTH line and 1175 feet from the WEST line Section 2 Township 22S Range 34E NMPM County LEA		8. Well Number 3H
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3572'GR		9. OGRID Number 331165
		10. Pool name or Wildcat OJO CHISO; BONE SPRING (96553)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
DOWNHOLE COMMINGLE ☐	P AND A ☐
CLOSED-LOOP SYSTEM ☐	CASING/CEMENT JOB ☐
OTHER: ☐	OTHER: COMPLETIONS OPERATIONS ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/10/2022-TIH; RUN CBL W/EST TOC @ 2,470' MD

11/14/2022-SET CBP @ 15,200' MD; PRESSURE TEST 5.5" PROD CSG TO 9500 PSI, 30 MIN, GOOD TEST

11/15/2022-PERFORATE STAGE 1 @ 15,191' - 15,028'

11/16-11/30/2022-PERFORATE STAGE 2-26 @ 15,010 - 10,492

-FRACTURE ALL STAGES W/619 BBLS HCl + 236,236 BBLS SW W/7,614,743# 100 MESH + 3,454,132# 40/70 + 656,120# 30/50 SAND

-

01/06/2023-BEGIN FLOWBACK & FIRST PRODUCTION

Spud Date:

08/10/2022

Rig Release Date:

09/18/2022

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jennifer Elrod TITLE SR. REGULATORY ANALYST DATE 03/07/2023

Type or print name JENNIFER ELROD E-mail address: JELROD@EARTHSTONEENERGY.COM PHONE: 817-953-3728

For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____

Conditions of Approval (if any):

Submit To Appropriate District Office Two Copies <u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> 811 S. First St., Artesia, NM 88210 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM 87505		State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505				Form C-105 Revised April 3, 2017				
WELL COMPLETION OR RECOMPLETION REPORT AND LOG										
4. Reason for filing: ☒ COMPLETION REPORT (Fill in boxes #1 through #31 for State and Fee wells only) ☐ C-144 CLOSURE ATTACHMENT (Fill in boxes #1 through #9, #15 Date Rig Released and #32 and/or #33; attach this and the plat to the C-144 closure report in accordance with 19.15.17.13.K NMAC)								5. Lease Name or Unit Agreement Name SQUEEZE 2 STATE COM		
								6. Well Number: 3H		
7. Type of Completion: ☒ NEW WELL ☐ WORKOVER ☐ DEEPENING ☐ PLUGBACK ☐ DIFFERENT RESERVOIR ☐ OTHER _____										
8. Name of Operator Earthstone Operating, LLC						9. OGRID 331165				
10. Address of Operator 1400 WOODLOCH FOREST DR. STE. 300 ATTN: REGULATORY THE WOODLANDS, TX 77380						11. Pool name or Wildcat OJO CHISO; BONE SPRING				
12. Location	Unit Ltr	Section	Township	Range	Lot	Feet from the	N/S Line	Feet from the	E/W Line	County
Surface:	M	02	22S	34E		380	SOUTH	1175	WEST	LEA
BH:	D	02	22S	34E		101	NORTH	823	WEST	LEA
13. Date Spudded 08/12/2022	14. Date T.D. Reached 09/17/2022		15. Date Rig Released 09/18/2022		16. Date Completed (Ready to Produce) 01/06/2023			17. Elevations (DF and RKB, RT, GR, etc.) 3572		
18. Total Measured Depth of Well 15238			19. Plug Back Measured Depth NA		20. Was Directional Survey Made? YES			21. Type Electric and Other Logs Run RBL		
22. Producing Interval(s), of this completion - Top, Bottom, Name 10492 - 15190 OJO CHISO; BONE SPRING										
23. CASING RECORD (Report all strings set in well)										
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED
13.375		54.5# J-55		1742		17.5		1165 sks Class C		
9.625		40# J-55; HCL-80		5623		12.25		2141 sks Class C		
5.5		20# P-110		15217		7.875		1455 sks Class C		
24. LINER RECORD						25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET			
26. Perforation record (interval, size, and number) 10492 - 15190; size 0.42; Total Shots 17008					27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
					DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
					10492 - 15190		FRACTURE ALL STAGES W/619 BBLS HCl + 236,236			
							BBLS SW W/7,614,743# 100 MESH + 3,454,132# 40/70 +			
							656,120# 30/50 SAND			
28. PRODUCTION										
Date First Production 01/06/2023		Production Method (<i>Flowing, gas lift, pumping - Size and type pump</i>) FLOW				Well Status (<i>Prod. or Shut-in</i>) PROD				
Date of Test 01/21/2023	Hours Tested 24	Choke Size 52	Prod'n For Test Period	Oil - Bbl 1389	Gas - MCF 1562	Water - Bbl. 1528	Gas - Oil Ratio			
Flow Tubing Press.	Casing Pressure 425	Calculated 24-Hour Rate	Oil - Bbl. 1389	Gas - MCF 1562	Water - Bbl. 1528	Oil Gravity - API - (<i>Corr.</i>) 40.8				
29. Disposition of Gas (<i>Sold, used for fuel, vented, etc.</i>) SOLD							30. Test Witnessed By			
31. List Attachments										
32. If a temporary pit was used at the well, attach a plat with the location of the temporary pit.							33. Rig Release Date:			
34. If an on-site burial was used at the well, report the exact location of the on-site burial:										
Latitude _____					Longitude _____			NAD83		
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief										
Signature <i>Deborah Marberry</i>			Printed Name Deborah Marberry			Title Sr. Reg Tech			Date 05/18/2023	
E-mail Address dmarberry@earthstoneenergy.com										

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well and not later than 60 days after completion of closure. When submitted as a completion report, this shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 11, 12 and 26-31 shall be reported for each zone.

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon CHERRY 5856	T. Ojo Alamo	T. Penn A "
T. Salt	T. Strawn	T. Kirtland	T. Penn. "B"
B. Salt	T. Atoka	T. Fruitland	T. Penn. "C"
T. Yates 3797	T. Miss	T. Pictured Cliffs	T. Penn. "D"
T. 7 Rivers	T. Devonian	T. Cliff House	T. Leadville
T. Queen	T. Silurian	T. Menefee	T. Madison
T. Grayburg	T. Montoya	T. Point Lookout	T. Elbert
T. San Andres	T. Simpson	T. Mancos	T. McCracken
T. Glorieta	T. McKee	T. Gallup	T. Ignacio Otzte
T. Paddock	T. Ellenburger	Base Greenhorn	T. Granite
T. Blinebry	T. Gr. Wash	T. Dakota	
T. Tubb	T. Delaware Sand	T. Morrison	
T. Drinkard	T. Bone Springs 8440	T. Todilto	
T. Abo	T. CAPITAN REEF 4063	T. Entrada	
T. Wolfcamp	T. BRUSHY CANYON 7089	T. Wingate	
T. Penn	T.	T. Chinle	
T. Cisco (Bough C)	T.	T. Permian	

OIL OR GAS SANDS OR ZONES

No. 3, from.....to.....

No. 4, from.....to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 3. from.....to.....feet.....

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 219051

ACKNOWLEDGMENTS

Operator: Earthstone Operating, LLC 300 N. Marienfeld St Ste 1000 Midland, TX 79701	OGRID: 331165
	Action Number: 219051
	Action Type: [C-104] Completion Packet (C-104C)

ACKNOWLEDGMENTS

☒	I hereby certify that the required Water Use Report has been, or will be, submitted for this wells completion.
☒	I hereby certify that the required FracFocus disclosure has been, or will be, submitted for this wells completion.

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 219051

CONDITIONS

Operator: Earthstone Operating, LLC 300 N. Marienfeld St Ste 1000 Midland, TX 79701	OGRID: 331165
	Action Number: 219051
	Action Type: [C-104] Completion Packet (C-104C)

CONDITIONS

Created By	Condition	Condition Date
plmartinez	None	1/29/2025