Received by UCD. 5/26/2025 6:37:38 PM U.S. Department of the Interior BUREAU OF LAND MANAGEMENT		Sundry Print Report 01/26/2025
Well Name: BURCH KEELY UNIT	Well Location: T17S / R29E / SEC 13 / NESW / 32.8327272 / -104.0302161	County or Parish/State: EDDY / NM
Well Number: 372	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMLC028784C	Unit or CA Name: BURCH KEELY UNIT	Unit or CA Number: NMNM88525X
US Well Number: 3001533802	Operator: SPUR ENERGY PARTNERS LLC	

Notice of Intent

Sundry ID: 2824312

Type of Submission: Notice of Intent

Date Sundry Submitted: 11/25/2024

Date proposed operation will begin: 02/06/2025

Type of Action: Plug and Abandonment Time Sundry Submitted: 08:17

Procedure Description: Please find proposed P&A procedure, current wellbore diagram and proposed diagram attached for your review.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

BKU_372___WBD___PROPOSED_P_A_20241125081656.pdf

BKU_372___WBD___CURRENT_20241125081656.pdf

BKU_372_P_A_PROCEDURE_20241125081640.pdf

Received by OCD: 1/26/2025 6:37:38 PM Well Name: BURCH KEELY UNIT	Well Location: T17S / R29E / SEC 13 / NESW / 32.8327272 / -104.0302161	County or Parish/State: EDBY ? of NM
Well Number: 372	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMLC028784C	Unit or CA Name: BURCH KEELY UNIT	Unit or CA Number: NMNM88525X
US Well Number: 3001533802	Operator: SPUR ENERGY PARTNERS LLC	

Conditions of Approval

Specialist Review

BKU_372_BLM_Revised_P_A_Procedure_and_COA_20250125112454.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: SARAH CHAPMAN

Name: SPUR ENERGY PARTNERS LLC

Title: Regulatory Director

Street Address: 9655 KATY FREEWAY SUITE 500

City: HOUSTON

Phone: (281) 642-5503

Email address: SCHAPMAN@SPURENERGY.COM

Field

Representative Name: Street Address: City: Phone: Email address:

State:

State: TX

BLM Point of Contact

BLM POC Name: ZOTA M STEVENS BLM POC Phone: 5752345998 Disposition: Approved Signature: Zota Stevens Signed on: NOV 25, 2024 08:17 AM

Zip:

BLM POC Title: Petroleum Engineer BLM POC Email Address: ZSTEVENS@BLM.GOV

Disposition Date: 01/25/2025

Received by OCD: 1/26/2025 6:37:38 PM

<i>cectred by</i> 0 cD. 17 2 072	020 0.07.00 1 01			I uge o oj	
Form 3160-5 (June 2019)	DEPARTMENT OF THE	UNITED STATES EPARTMENT OF THE INTERIOR REAU OF LAND MANAGEMENT		RM APPROVED 1B No. 1004-0137 es: October 31, 2021	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If Indian, Allottee or Tribe Name		
	MIT IN TRIPLICATE - Other inst	ructions on page 2	7. If Unit of CA/Agreement, Na	me and/or No.	
1. Type of Well Oil Well	Gas Well Other		8. Well Name and No.		
2. Name of Operator			9. API Well No.		
3a. Address		3b. Phone No. <i>(include area code)</i>	10. Field and Pool or Explorator	ry Area	
4. Location of Well (Footage,	Sec., T.,R.,M., or Survey Description))	11. Country or Parish, State		
	12. CHECK THE APPROPRIATE F	BOX(ES) TO INDICATE NATURE (OF NOTICE, REPORT OR OTHE	ER DATA	
TYPE OF SUBMISSIO	N	TYPI	E OF ACTION		
Notice of Intent	Acidize	Deepen Hydraulic Fracturing	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair Change Plans	New Construction	Recomplete	Other	
Final Abandonment No	tice Convert to Injection	n Plug Back	Water Disposal		
the proposal is to deepen of the Bond under which the completion of the involve	irectionally or recomplete horizonta work will be perfonned or provide the operations. If the operation results ment Notices must be filed only after	lly, give subsurface locations and me he Bond No. on file with BLM/BIA. in a multiple completion or recomple	easured and true vertical depths of Required subsequent reports must etion in a new interval, a Form 316	and approximate duration thereof. If all pertinent markers and zones. Attach be filed within 30 days following 60-4 must be filed once testing has been e operator has detennined that the site	

14. I hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>)			
1	Title		
Circusture			
Signature	Date		
THE SPACE FOR FEDE	RAL OR STATE O	OFICE USE	
Approved by			
	Title	Date	
Conditions of approval, if any, are attached. Approval of this notice does not warrant of certify that the applicant holds legal or equitable title to those rights in the subject least which would entitle the applicant to conduct operations thereon.			
Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any any false, fictitious or fraudulent statements or representations as to any matter within		villfully to make to any department or agency of the United	States

(Instructions on page 2)

GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

SPECIFIC INSTRUCTIONS

Item 4 - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

Item 13: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c)and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

BURDEN HOURS STATEMENT: Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

Additional Information

Location of Well

0. SHL: NESW / 1980 FSL / 2050 FWL / TWSP: 17S / RANGE: 29E / SECTION: 13 / LAT: 32.8327272 / LONG: -104.0302161 (TVD: 0 feet, MD: 4800 feet) BHL: NESW / 1980 FSL / 2050 FWL / TWSP: 17S / RANGE: 29E / SECTION: 13 / LAT: 0.0 / LONG: 0.0 (TVD: 0 feet, MD: 4800 feet)

•

API # 30-015-33802		PROPOSED P&A		County, ST	Eddy County, NM
Operator Spur Energy Partne	ers	FROFOSEDF&A	·	Sec-Twn-Rng	13-17S-29E
Field BURCH KEELY; GLORIETA-L	JPPER YESO	BURCH KEELY UNIT 372		Footage	1980 FSL, 2050 FWL
Spud Date 2/11/2005				Survey	32.8327827,-104.0301743
				, ,	,
Formation (MD)	RKB				
TOP OF SALT 358	GL 3621				
BASE OF SALT 873					
YATES 1,602	Hole Size 12 1/4"				
QUEEN 1,930	TOC SURF				
GRAYBURG 2,333	Method CIRC				
SAN ANDRES 2,628					
GLORIETA 4,036	Csg Depth 379'		DI		1201
YESO 4,142	Size 8 5/8"		Plug #4: P&S 48 s	x class C cmt from	429' - surface
	Weight 24# Grade				
	Connections		TOP OF SALT @ 3	358'	
	Cement 300 SX				
			1		
			BASE OF SALT @	873'	
			Plug #4: P&S 25 s	x class C cmt from	973' - 773'
				4 6 9 9 1	
			TOP OF YATES @	1602	
			Plug #3. P&S 48 s	x class C cmt from	1980' - 1552'
			1 105 105 105 40 5		1500 1552
			TOP OF QUEEN @	D 1930'	
			TOP OF GRAYBU	RG @ 2333'	
			Plug #2: P&S 35 s	x class C cmt from	2678' - 2283'
			TOP OF SAN AND	JKES @ 2628	
	Hole Size 7 7/8"				
	TOC SURF				
	Method CIRC		TOP OF GLORIET	A @ 4036'	
	Csg Depth 4567'		a		
	Size 5 1/2"			cmt @ 4095' - 398	b [.]
	Weight 17#		Plug #1: CIBP @ 4		
	Grade	1 1	TOP OF YESO @ 4	4142'	
	Connections Cement 1700 SXS		8/2005: PERFS @	1115' - 1270'	
	Cement 1700 SXS		0/2003. PEKFS @	4143 - 43/8	
	PBTD 4,550				
Last Update 11/22/2024	TD MD 4,650				
By WSC	TD TVD 4,650				
·	· · · · · ·				

•

RKB Survey Pr SALT 358 OF SALT 873 TES 1,602 IEN 1,930	Eddy County, NM 13-17S-29E 1980 FSL, 2050 FWL 32.8327827,-104.0301743
BURCH KEELY; GLORIETA-UPPER YESO BORCH KEELY ONT S/2 Footage te 2/11/2005 Survey rmation (MD) FSALT 358 OF SALT 358 OF SALT 873 TES 1,602	1980 FSL, 2050 FWL
RKB GL 3621 OF SALT 358 GL 3621 OF SALT 873 Hole Size 12 1/4"	32.8327827,-104.0301743
OF SALT 358 GL 3621 OF SALT 873	
OF SALT 358 GL 3621 OF SALT 873	
DF SALT 873 TES 1,602 Hole Size 12 1/4"	
TES 1,602 Hole Size 12 1/4"	
/BURG 2,333 Method CIRC	
NDRES 2,628	
RIETA 4,036 Csg Depth 379'	
SO 4,142 Size 85/8"	
Weight 24# Grade	
Connections	
Cement 300 SX	
2 7/8" 6.5# J55 TBG	
TAC @ 4031'	
Hole Size 77/8"	
TOC SURF Method CIRC	
Csg Depth 4567'	
Size 5 1/2"	
Weight 17# SN @ 4423'	
Connections	
Connections <th< th=""> <</th<>	
Cement 1700 SXS ≤ √ ≤ 4/8/2005: PERFS @ 4145' - 4378'	

BKU 372 P&A Procedure 30-015-33802 32.8327827,-104.0301743

- 1. POOH rods and tbg. Rod and tbg details unknown.
- 2. Set 5.5" CIBP @ 4095'. Circ hole w/ MLF. Pressure test csg. 500 psi, 30 min. Run CBL from 4095 surface. Spot 25 sx class C cmt @ 4095' 3986' (Perfs / Yeso / Glorieta). WOC & Tag. (Plug 1)
- 3. Spot 35 sx class C cmt @ 2678' 2283' (San Andres / Grayburg). WOC & Tag. (Plug 2)
- 4. Spot 48 sx class C cmt @ 1980' 1552' (Queen / Yates). WOC & Tag. (Plug 3)
- 5. Spot 30 sx class C cmt @ 973' 773' (Base of Salt). WOC & Tag. (Plug 4)
- 6. Spot 48 sx class C cmt @ 429' Surface (8 5/8" shoe / Top of Salt). Verify Cmt to surface. (Plug 4)
- 7. Top off all annuli from back side.
- 8. Cut off Wellhead. Weld on below ground dry hole marker. Send picture to engineer.

Revised P&A Procedure

- 1. MIRU P&A unit. POOH rods and tubing string.
- 2. Set CIBP at 4095ft. Spot 25 sx of CI C cement from 4095' -3986'. WOC and Tag (Pressure Test).
- 3. Run CBL from 3986 ft to surface. Contact BLM after running CBL.
- 4. Perf and Sqz 35 sx of Cl C from 2678'-2236'. (T/ Grayburg, T/San Andres)
- 5. Perf and Sqz 48 sx of Cl C from 1980'- 1552'. WOC and Tag (T/Yates, T/ Queen)
- 6. Perf and Sqz 25 sx of Cl C from 973'-773'. (B/Salt)
- 7. Perf and Sqz 48 sx from 429' to surface.
- 8. Circ mud between each plug.
- 9. Cut wellhead off. Set Dry Hole marker.

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval (LPC Habitat)

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours for Class C or accelerated cement (calcium chloride) and 6 hours for Class H. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a

bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

Fluid used to mix the cement in R111Q shall be saturated with the salts common to the section penetrated, and in suitable proportions but not less than 1% and not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

6. <u>Below Ground Level Cap (Lesser Prairie-Chicken Habitat)</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified** *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¹/₄ inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. <u>Show date well was plugged.</u>

8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:

From March 1st through June 15th annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



United States Department of the Interior

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (**Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure**). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry

Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Petroleum Engineering Tech/Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias Environmental Protection Specialist 575-234-6230

Crisha Morgan Environmental Protection Specialist 575-234-5987

Jose Martinez-Colon Environmental Protection Specialist 575-234-5951

Mark Mattozzi Environmental Protection Specialist 575-234-5713

Robert Duenas Environmental Protection Specialist 575-234-2229

Doris Lauger Martinez Environmental Protection Specialist 575-234-5926

Jaden Johnston Environmental Protection Asst. (Intern) 575-234-6252 Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Operator:	OGRID:
Spur Energy Partners LLC	328947
9655 Katy Freeway	Action Number:
Houston, TX 77024	424758
	Action Type:
	[C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	A Cement Bond Log (CBL) is required to be submitted to electronic permitting.	1/30/2025
gcordero	Submit Cement Bond Logs (CBL) prior to submittal of C-103P.	1/30/2025

Page 14 of 14

Action 424758