

Well Name: FALCON FEDERAL	Well Location: T19S / R32E / SEC 9 / SWNW / 32.6776703 / -103.7777327	County or Parish/State: LEA / NM
Well Number: 01	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM13422B	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002538421	Operator: COG OPERATING LLC	

Notice of Intent

Sundry ID: 2820992

Type of Submission: Notice of Intent	Type of Action: Plug and Abandonment
Date Sundry Submitted: 11/06/2024	Time Sundry Submitted: 07:17
Date proposed operation will begin: 12/30/2024	

**Procedure Description:** 1. Hold Pre job meeting, comply with all NMOCD, BLM and environmental regulations. 2. MIRU P&A rig and equipment. 3. Check and record tubing, casing and bradenhead pressures. Remove existing piping from casing valve, RU blow lines from casing valves and blow down casing pressure. Kill well as necessary. Ensure that well is dead or on a vacuum. 4. ND WH, NU BOP, function test BOP. 5. RIH 5 1/2" CIBP and set at 9244'. TOH. 6. MIRU logging truck. Run CBL from 9244' & log TOC to surface. Hold 600 psi on casing if possible. NOTE: Results of CBL may change the following plugs. Electronic copy of CBL to be sent to BLM Representative. 7. RIH with tubing workstring. Drop ball valve down tubing and pressure test to 1000#. Pressure test casing to 500#. If casing does not test, then discuss with Regulatory for procedure change. 8. Plug #1: Bone Spring perforation: With CIBP @ 9244' mix and pump 25 sxs Class H cement from 9244' to 4044'. 9. Plug #2: 5 1/2" DV Tool: Spot 15 sxs Class H cement from 7850' to 7750'. WOC & Tag. If plug 2 is at 7750' or above, continue to next step. If cement is lower than 7750', contact BLM Representative for procedure change. 10. Plug #3: Bone Spring formation: Mix and pump 15 sxs Class C cement from 7200' to 7099'. 11. Plug #4: San Andres formation: Mix and pump 15 sxs Class C cement from 4785' to 4685'. 12. Plug #5: 9 5/8" Shoe & Queen formation: Spot 22 sxs Class C cement from 3958' to 3795'. WOC & Tag. If plug 5 is at 3795' or above, continue to next step. If cement is lower than 3795', contact BLM Representative for procedure change. 13. MIRU wireline unit. Perforate squeeze holes at 3032'. Establish injection rate. 14. Plug #6: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (107 sx outside, 31 sx inside) from 3032' to 2773'. WOC & Tag. If plug 6 is at 2773' or above, continue to next step. If cement is lower than 2773', contact BLM Representative for procedure change. 15. MIRU wireline unit. Perforate squeeze holes at 1119'. Establish injection rate. 16. Plug #7: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (96 sx outside, 28 sx inside) from 1119' to 886'. WOC & Tag. If plug 7 is at 886' or above, continue to next step. If cement is lower than 886', contact BLM Representative for procedure change. 17. MIRU wireline unit. Perforate squeeze holes at 200'. Establish injection rate. 18. Plug 4: Surface Plug: Squeeze 107 sx Class C cement (82 sx outside, 25 sx inside) from 200' to 5' and circulate good cement out casing and annulus. 19. RD cementing equipment. Cut off wellhead, fill any exposed annulus with cement, as necessary. Install DHM. 20. Record GPS coordinates for P&A marker and the Final P&A Report. Photograph the P&A marker and attach to the report. 21. Send all reports and attachments will be uploaded to NMOCD website within 30 days of completion.

Well Name: FALCON FEDERAL	Well Location: T19S / R32E / SEC 9 / SWNW / 32.6776703 / -103.7777327	County or Parish/State: LEA / NM
Well Number: 01	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM13422B	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002538421	Operator: COG OPERATING LLC	

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Falcon\_Federal\_1\_Proposed\_NOI\_20241106071655.pdf

Conditions of Approval

Specialist Review

Falcon\_Federal\_01\_\_2820992\_\_COA\_and\_Procedure\_20250116201530.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: RUTH SHOCKENCY	Signed on: NOV 06, 2024 07:17 AM
Name: COG OPERATING LLC	
Title: Regulatory Analyst	
Street Address: 600 W. ILLINOIS AVE.	
City: MIDLAND	State: TX
Phone: (575) 703-8321	
Email address: RUTH.SHOCKENCY@CONOCOPHILLIPS.COM	

Field

Representative Name:		
Street Address:		
City:	State:	Zip:
Phone:		
Email address:		

Well Name: FALCON FEDERAL

Well Location: T19S / R32E / SEC 9 /  
SWNW / 32.6776703 / -103.7777327

County or Parish/State: LEA /  
NM

Well Number: 01

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM13422B

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002538421

Operator: COG OPERATING LLC

BLM Point of Contact

BLM POC Name: KEITH P IMMATTY

BLM POC Title: ENGINEER

BLM POC Phone: 5759884722

BLM POC Email Address: KIMMATTY@BLM.GOV

Disposition: Approved

Disposition Date: 01/16/2025

Signature: Keith Immatty

Form 3160-5 (June 2019)	UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT	FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021
<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> <i>Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.</i>		5. Lease Serial No.
		6. If Indian, Allottee or Tribe Name

<b>SUBMIT IN TRIPLICATE - Other instructions on page 2</b>		7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		8. Well Name and No.
2. Name of Operator		9. API Well No.
3a. Address	3b. Phone No. (include area code)	10. Field and Pool or Exploratory Area
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)		11. Country or Parish, State

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be perfonned or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)		
	Title	
Signature	Date	

<b>THE SPACE FOR FEDERAL OR STATE OFFICE USE</b>		
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

## GENERAL INSTRUCTIONS

This form is designed for submitting proposals to perform certain well operations and reports of such operations when completed as indicated on Federal and Indian lands pursuant to applicable Federal law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local area or regional procedures and practices, are either shown below, will be issued by or may be obtained from the local Federal office.

## SPECIFIC INSTRUCTIONS

*Item 4* - Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult the local Federal office for specific instructions.

*Item 13*: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by the local Federal office. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to the top of any tubing left in the hole; method of closing top of well and date well site conditioned for final inspection looking for approval of the abandonment. If the proposal will involve **hydraulic fracturing operations**, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The privacy Act of 1974 and the regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

AUTHORITY: 30 U.S.C. 181 et seq., 351 et seq., 25 U.S.C. 396; 43 CFR 3160.

PRINCIPAL PURPOSE: The information is used to: (1) Evaluate, when appropriate, approve applications, and report completion of subsequent well operations, on a Federal or Indian lease; and (2) document for administrative use, information for the management, disposal and use of National Resource lands and resources, such as: (a) evaluating the equipment and procedures to be used during a proposed subsequent well operation and reviewing the completed well operations for compliance with the approved plan; (b) requesting and granting approval to perform those actions covered by 43 CFR 3162.3-2, 3162.3-3, and 3162.3-4; (c) reporting the beginning or resumption of production, as required by 43 CFR 3162.4-1(c) and (d) analyzing future applications to drill or modify operations in light of data obtained and methods used.

ROUTINE USES: Information from the record and/or the record will be transferred to appropriate Federal, State, local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecutions in connection with congressional inquiries or to consumer reporting agencies to facilitate collection of debts owed the Government.

EFFECT OF NOT PROVIDING THE INFORMATION: Filing of this notice and report and disclosure of the information is mandatory for those subsequent well operations specified in 43 CFR 3162.3-2, 3162.3-3, 3162.3-4.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM collects this information to evaluate proposed and/or completed subsequent well operations on Federal or Indian oil and gas leases.

Response to this request is mandatory.

The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Collection Clearance Officer (WO-630), 1849 C St., N.W., Mail Stop 401 LS, Washington, D.C. 20240

## Additional Information

### Additional Remarks

continue to next step. If cement is lower than 7750, contact BLM Representative for procedure change.

10. Plug #3: Bone Spring formation: Mix and pump 15 sxs Class C cement from 7200 to 7099.

11. Plug #4: San Andres formation: Mix and pump 15 sxs Class C cement from 4785 to 4685.

12. Plug #5: 9 5/8 Shoe & Queen formation: Spot 22 sxs Class C cement from 3958 to 3795. WOC & Tag. If plug 5 is at 3795 or above, continue to next step. If cement is lower than 3795, contact BLM Representative for procedure change.

13. MIRU wireline unit. Perforate squeeze holes at 3032. Establish injection rate.

14. Plug #6: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (107 sx outside, 31 sx inside) from 3032 to 2773. WOC & Tag. If plug 6 is at 2773 or above, continue to next step. If cement is lower than 2773, contact BLM Representative for procedure change.

15. MIRU wireline unit. Perforate squeeze holes at 1119. Establish injection rate.

16. Plug #7: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (96 sx outside, 28 sx inside) from 1119 to 886. WOC & Tag. If plug 7 is at 886 or above, continue to next step. If cement is lower than 886, contact BLM Representative for procedure change

17. MIRU wireline unit. Perforate squeeze holes at 200. Establish injection rate.

18. Plug 4: Surface Plug: Squeeze 107 sx Class C cement (82 sx outside, 25 sx inside) from 200 to 5 and circulate good cement out casing and annulus.

19. RD cementing equipment. Cut off wellhead, fill any exposed annulus with cement, as necessary. Install DHM.

20. Record GPS coordinates for P&A marker and the Final P&A Report. Photograph the P&A marker and attach to the report.

21. Send all reports and attachments will be uploaded to NMOCD website within 30 days of completion.

### Location of Well

0. SHL: SWNW / 1650 FNL / 660 FWL / TWSP: 19S / RANGE: 32E / SECTION: 9 / LAT: 32.6776703 / LONG: -103.7777327 ( TVD: 0 feet, MD: 0 feet )

BHL: SWNW / 1650 FNL / 660 FWL / TWSP: 19S / SECTION: / LAT: 0.0 / LONG: 0.0 ( TVD: 0 feet, MD: 0 feet )

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an  
abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No. NMNM13422B

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator COG Operating, LLC

3a. Address 600 W Illinois Midland TX 79701

3b. Phone No. (include area code)  
(432) 683-74434. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1650 FNL & 660 FWL Sec 9, T19S, R32E

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No. Falcon Federal #1

9. API Well No. 30-025-38421

10. Field and Pool or Exploratory Area  
Lusk; Strawn11. Country or Parish, State  
Lea County, NM

## 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon		
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

**Please see attached for the proposed P&A NOI.**

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Title

Signature

Date

**THE SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)



**Proposed P&A NOI**  
**ConocoPhillips/COG Operating, LLC**  
**Falcon Federal #1**  
**30-025-38421**

**Note: All cement is to be Class H mixed at 16.4 ppg, yield 1.06 cu ft / sx below 7500'. Class C mixed at 14.8 ppg, yield 1.32 cu ft / sx above 7500'. Cement volumes are based on inside capacities + 50' excess and outside capacities + 100% excess.**

1. Hold Pre job meeting, comply with all NMOCD, BLM and environmental regulations.
2. MIRU P&A rig and equipment.
3. Check and record tubing, casing and bradenhead pressures. Remove existing piping from casing valve, RU blow lines from casing valves and blow down casing pressure. Kill well as necessary. Ensure that well is dead or on a vacuum.
4. ND WH, NU BOP, function test BOP.
5. RIH 5 1/2" CIBP and set at 9244'. TOH.
6. MIRU logging truck. Run CBL from 9244' & log TOC to surface. Hold 600 psi on casing if possible. NOTE: Results of CBL may change the following plugs. Electronic copy of CBL to be sent to BLM Representative.
7. RIH with tubing workstring. Drop ball valve down tubing and pressure test to 1000#. Pressure test casing to 500#. If casing does not test, then discuss with Regulatory for procedure change.
8. Plug #1: Bone Spring perforation: With CIBP @ 9244' mix and pump 25 sxs Class H cement from 9244' to 4044'.
9. Plug #2: 5 1/2" DV Tool: Spot 15 sxs Class H cement from 7850' to 7750'. WOC & Tag. If plug 2 is at 7750' or above, continue to next step. If cement is lower than 7750', contact BLM Representative for procedure change.
10. Plug #3: Bone Spring formation: Mix and pump 15 sxs Class C cement from 7200' to 7099'.
11. Plug #4: San Andres formation: Mix and pump 15 sxs Class C cement from 4785' to 4685'.
12. Plug #5: 9 5/8" Shoe & Queen formation: Spot 22 sxs Class C cement from 3958' to 3795'. WOC & Tag. If plug 5 is at 3795' or above, continue to next step. If cement is lower than 3795', contact BLM Representative for procedure change.
13. MIRU wireline unit. Perforate squeeze holes at 3032'. Establish injection rate.
14. Plug #6: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (107 sx outside, 31 sx inside) from 3032' to 2773'. WOC & Tag. If plug 6 is at 2773' or above, continue to next step. If cement is lower than 2773', contact BLM Representative for procedure change.
15. MIRU wireline unit. Perforate squeeze holes at 1119'. Establish injection rate.
16. Plug #7: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (96 sx outside, 28 sx inside) from 1119' to 886'. WOC & Tag. If plug 7 is at 886' or above, continue to next step. If cement is lower than 886', contact BLM Representative for procedure change.




**Proposed P&A NOI**  
**ConocoPhillips/COG Operating, LLC**  
**Falcon Federal #1**  
**30-025-38421**

17. MIRU wireline unit. Perforate squeeze holes at 200'. Establish injection rate.
18. Plug 4: Surface Plug: Squeeze 107 sx Class C cement (82 sx outside, 25 sx inside) from 200' to 5' and circulate good cement out casing and annulus.
19. RD cementing equipment. Cut off wellhead, fill any exposed annulus with cement, as necessary. **Install DHM.**
20. Record GPS coordinates for P&A marker and the Final P&A Report. Photograph the P&A marker and attach to the report.
21. Send all reports and attachments will be uploaded to NMOCD website within 30 days of completion.

ConocoPhillips		PROPOSED	
Author:	Abby @ JMR	Well No.	1
Well Name	Falcon Federal	API #:	30-025-38421
Field/Pool	Lusk Strawn	Location:	Sec 9, T19S, R32E,
County	Lea		1650'FNL & 660'FWL
State	NM	GL:	3643'
Spud Date	9/3/2007		

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surf Csg	13.325	J55	54.5	936	17 1/2	800	Surface
Interm Csg	9.625	J-55	40#/36#	3,908	12 1/4	1,450	Surface
Prod Csg	5.5	N-80	17	11,858	7 7/8	1,465	3,600

Formation	Top
Rustler	1069
Tansill	2,827
Yates	2982
Queen	3845
San Andres	4735
DB	5,216
Bone Spring	7,149
Wolfc	10,450
Strawn	11,520



**Plug #8:** Perf & Sqz 107 sx cmt @ 200' to surface. (82 sx outside, 25 sx inside)

13.325 54.5 CSG @ 936

**Plug #7:** Perf & Sqz 124 sx cmt @ 1119-886' ( 96 sx outside, 28 sx inside). WOC & Tag (Rustler & 13 3/8" Shoe).

**DVT @ 2,823'**

**Plug #6:** Perf & Sqz 138 sx cmt @ 3032-2773' (107 sx outside, 31 sx inside). WOC & Tag (Yates, Tansill, & DV Tool)

Est TOC ~3,600' Temp survey

9.625 40&36 Csg @ 3,908

**Plug #5:** Spot 22 sx class C 14.8# cmt @ 3958-3795'. WOC & Tag (9 5/8" Shoe & Queen)

**Plug #4:** Spot 15 sx class C cmt @ 4785-4685'. (San Andres)

**Plug #3:** Spot 15 sx class C 14.8# cmt @ 7200-7099'. (Bone Spring)

**DVT @ 7,800'**

**Plug #2:** Spot 15 sx class H 16.4# cmt @ 7850-7750'. WOC & Tag (DV Tool)

**Plug #1:** Set 5 1/2" CIBP @ 9244'. Spot 25 sx class H 16.4# cmt @ 9244-4044'.

**Perfs @ 9,294' to 9,312' (38 holes 2BS)**

**Perfs @ 9,834' to 9,933' (180 holes BS)**

**CIBP @ 10,675' +35' of cement**

**Perfs @ 10,718' to 10,794' (20 holes WLFC)**

**CIBP @ 11,475' +35' of cement**

**Perfs @ 11,508' to 11,702' (20 Holes Strawn)**


5.5 17 CSG @ 11,858

PBTD @ 11,798  
TD @ 11,850

32.6776772  
-103.7776947

<b>ConocoPhillips</b>		<b>CURRENT</b>	
Author:	JJC	Well No.	1
Well Name	Falcon Federal	API #:	30-025-38421
Field/Pool	Lusk Strawn	Location:	Sec 9, T19S, R32E,
County	Lea		1650'FNL & 660'FWL
State	NM	GL:	3643'
Spud Date	9/3/2007		

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surf Csg	13.325	J55	54.5	936	17 1/2	800	Surface
Interm Csg	9.625	J-55	40#/36#	3,908	12 1/4	1,450	Surface
Prod Csg	5.5	N-80	17	11,858	7 7/8	1,465	3,600
Formation Top							
Rustler							1069
Tansill							2,827
Yates							2982
Queen							3845
San Andres							4735
DB							5,216
Bone Spring							7,149
Wolfc							10,450
Strawn							11,520



Form 3160-5  
(June 2015)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018**SUNDRY NOTICES AND REPORTS ON WELLS**  
**Do not use this form for proposals to drill or to re-enter an  
abandoned well. Use Form 3160-3 (APD) for such proposals.**

5. Lease Serial No. NMNM13422B

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE - Other instructions on page 2**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No. Falcon Federal #1

2. Name of Operator COG Operating, LLC

9. API Well No. 30-025-38421

3a. Address 600 W Illinois Midland TX 79701

3b. Phone No. (include area code)  
(432) 683-744310. Field and Pool or Exploratory Area  
Lusk; Strawn4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1650 FNL & 660 FWL Sec 9, T19S, R32E11. Country or Parish, State  
Lea County, NM

## 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off	
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Hydraulic Fracturing	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity	
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other	
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon		
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

**Please see attached for the proposed P&A NOI.**

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Title

Signature

Date

**THE SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

**Proposed P&A NOI**  
**ConocoPhillips/COG Operating, LLC**  
**Falcon Federal #1**  
**30-025-38421**

**Note: All cement is to be Class H mixed at 16.4 ppg, yield 1.06 cu ft / sx below 7500'. Class C mixed at 14.8 ppg, yield 1.32 cu ft / sx above 7500'. Cement volumes are based on inside capacities + 50' excess and outside capacities + 100% excess.**

1. Hold Pre job meeting, comply with all NMOCD, BLM and environmental regulations.
2. MIRU P&A rig and equipment.
3. Check and record tubing, casing and bradenhead pressures. Remove existing piping from casing valve, RU blow lines from casing valves and blow down casing pressure. Kill well as necessary. Ensure that well is dead or on a vacuum.
4. ND WH, NU BOP, function test BOP.
5. RIH 5 1/2" CIBP and set at 9244'. TOH.
6. MIRU logging truck. Run CBL from 9244' & log TOC to surface. Hold 600 psi on casing if possible. NOTE: Results of CBL may change the following plugs. Electronic copy of CBL to be sent to BLM Representative.
7. RIH with tubing workstring. Drop ball valve down tubing and pressure test to 1000#. Pressure test casing to 500# **30MINS**. If casing does not test, then discuss with Regulatory for procedure change.
8. Plug #1: Bone Spring perforation: With CIBP @ 9244' mix and pump 25 sxs Class H cement from 9244' to 4044'.
9. Plug #2: 5 1/2" DV Tool: Spot 15 sxs Class H cement from 7850' to **7680'**. WOC & Tag. If plug 2 is at 7750' or above, continue to next step. If cement is lower than **7680'**, contact BLM Representative for procedure change.
10. Plug #3: Bone Spring formation: Mix and pump **25** sxs Class C cement from 7200' to **7030'**.
11. Plug #4: San Andres formation: Mix and pump **25** sxs Class C cement from 4785' to **4655'**.
12. Plug #5: 9 5/8" Shoe & Queen formation: Spot **25** sxs Class C cement from 3958' to **3755'**. WOC & Tag. If plug 5 is at 3795' or above, continue to next step. If cement is lower than **3755'**, contact BLM Representative for procedure change.
13. MIRU wireline unit. Perforate squeeze holes at 3032'. Establish injection rate.
14. Plug #6: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (107 sx outside, 31 sx inside) from 3032' to 2773'. WOC & Tag. If plug 6 is at **2743'** or above, continue to next step. If cement is lower than **2743'**, contact BLM Representative for procedure change.
15. MIRU wireline unit. Perforate squeeze holes at 1119'. Establish injection rate.
16. Plug #7: DV Tool and Yates, Tansill formations: Squeeze 138 sxs Class C cement (96 sx outside, 28 sx inside) from 1119' to 886'. WOC & Tag. If plug 7 is at **876'** or above, continue to next step. If cement is lower than **876'**, contact BLM Representative for procedure change.

**Proposed P&A NOI**  
**ConocoPhillips/COG Operating, LLC**  
**Falcon Federal #1**  
**30-025-38421**


17. MIRU wireline unit. Perforate squeeze holes at 200'. Establish injection rate.
18. Plug 4: Surface Plug: Squeeze 107 sx Class C cement (82 sx outside, 25 sx inside) from 200' to 5' and circulate good cement out casing and annulus.
19. RD cementing equipment. Cut off wellhead, fill any exposed annulus with cement, as necessary. **Install DHM.**
20. Record GPS coordinates for P&A marker and the Final P&A Report. Photograph the P&A marker and attach to the report.
21. Send all reports and attachments will be uploaded to NMOCD website within 30 days of completion.

**25sks minimum when spotting. 10' excess for every 1000' of MD**

ConocoPhillips		PROPOSED	
Author:	Abby @ JMR	Well No.	1
Well Name	Falcon Federal	API #:	30-025-38421
Field/Pool	Lusk Strawn	Location:	Sec 9, T19S, R32E,
County	Lea		1650'FNL & 660'FWL
State	NM	GL:	3643'
Spud Date	9/3/2007		

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surf Csg	13.325	J55	54.5	936	17 1/2	800	Surface
Interm Csg	9.625	J-55	40#/36#	3,908	12 1/4	1,450	Surface
Prod Csg	5.5	N-80	17	11,858	7 7/8	1,465	3,600

Formation	Top
Rustler	1069
Tansill	2,827
Yates	2982
Queen	3845
San Andres	4735
DB	5,216
Bone Spring	7,149
Wolfc	10,450
Strawn	11,520



**Plug #8:** Perf & Sqz 107 sx cmt @ 200' to surface. (82 sx outside, 25 sx inside)

13.325 54.5 CSG @ 936

**Plug #7:** Perf & Sqz 124 sx cmt @ 1119-876' (96 sx outside, 28 sx inside). WOC & Tag (Rustler & 13 3/8" Shoe).  
DVT @ 2,823'

**Plug #6:** Perf & Sqz 138 sx cmt @ 3032-2743' (107 sx outside, 31 sx inside). WOC & Tag (Yates, Tansill, & DV Tool)

Est TOC ~3,600' Temp survey

9.625 40&36 Csg @ 3,908

**Plug #5:** Spot 25 sx class C 14.8# cmt @ 3958-3755'. WOC & Tag (9 5/8" Shoe & Queen)

**Plug #4:** Spot 25 sx class C cmt @ 4785-4685'. (San Andres)

**Plug #3:** Spot 25 sx class C 14.8# cmt @ 7200-7030'. (Bone Spring)

DVT @ 7,800'

**Plug #2:** Spot 25 sx class H 16.4# cmt @ 7850-7680'. WOC & Tag (DV Tool)

**Plug #1:** Set 5 1/2" CIBP @ 9244'. Spot 25 sx class H 16.4# cmt @ 9244-4044'.

Perfs @ 9,294' to 9,312' (38 holes 2BS)

Perfs @ 9,834' to 9,933' (180 holes BS)

CIBP @ 10,675' +35' of cement

Perfs @ 10,718' to 10,794' (20 holes WLFC)

CIBP @ 11,475' +35' of cement

Perfs @ 11,508' to 11,702' (20 Holes Strawn)

5.5 17 CSG @ 11,858


PBTD @ 11,798  
TD @ 11,850

32.6776772  
-103.7776947



<b>ConocoPhillips</b>		<b>CURRENT</b>	
Author:	JJC	Well No.	1
Well Name	Falcon Federal	API #:	30-025-38421
Field/Pool	Lusk Strawn	Location:	Sec 9, T19S, R32E,
County	Lea		1650'FNL & 660'FWL
State	NM	GL:	3643'
Spud Date	9/3/2007		

Description	O.D.	Grade	Weight	Depth	Hole	Cmt Sx	TOC
Surf Csg	13.325	J55	54.5	936	17 1/2	800	Surface
Interm Csg	9.625	J-55	40#/36#	3,908	12 1/4	1,450	Surface
Prod Csg	5.5	N-80	17	11,858	7 7/8	1,465	3,600
Formation Top							
Rustler							1069
Tansill							2,827
Yates							2982
Queen							3845
San Andres							4735
DB							5,216
Bone Spring							7,149
Wolfc							10,450
Strawn							11,520



**BUREAU OF LAND MANAGEMENT  
Carlsbad Field Office  
620 East Greene Street  
Carlsbad, New Mexico 88220  
575-234-5972**

**Permanent Abandonment of Federal Wells  
Conditions of Approval (LPC Habitat)**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon.

**If you are unable to plug the well by the 90<sup>th</sup> day provide this office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.**

**The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.**

2. **Notification:** Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-689-5981.

3. **Blowout Preventers:** A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. **Mud Requirement:** Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. **Cement Requirement:** Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours for Class C or accelerated cement (calcium chloride) and 6 hours for Class H. Tagging the plug means running in the hole with a string of tubing or drill pipe and placing sufficient weight on the plug to ensure its integrity. Other methods of tagging the plug may be approved by the BLM authorized officer or BLM field representative.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a

bailer is used to cap this plug, 35 feet of cement shall be sufficient. **Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.**

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

Fluid used to mix the cement in R111Q shall be saturated with the salts common to the section penetrated, and in suitable proportions but not less than 1% and not more than 3% calcium chloride by weight of cement will be considered the desired mixture whenever possible.

6. Below Ground Level Cap (Lesser Prairie-Chicken Habitat): All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). **The BLM is to be notified *BY PHONE* (numbers listed in 2. Notifications) a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10<sup>th</sup> day, the BLM is to be contacted with justification to receive an extension for completing the cut off.**

Upon the plugging and subsequent abandonment of wells that are located in lesser prairie-chicken habitat, the casings shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. A weep hole shall be left in the plate and/or casing. The following information shall be permanently inscribed on the plate: well name and number, name of operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

NMOCD also requires the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground cap was installed as required in the COA's from the BLM.

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well.

**Show date well was plugged.**

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation objectives.

**Timing Limitation Stipulation/ Condition of Approval for Lesser Prairie-Chicken:**

From March 1<sup>st</sup> through June 15<sup>th</sup> annually, abandonment activities will be allowed except between the hours from 3:00 am and 9:00 am. Normal vehicle use on existing roads will not be restricted



# United States Department of the Interior

## BUREAU OF LAND MANAGEMENT

Carlsbad Field Office  
620 E. Greene St.  
Carlsbad, New Mexico 88220-6292  
www.blm.gov/nm



In Reply Refer To: 1310

### Reclamation Objectives and Procedures

**Reclamation Objective:** Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo “interim” reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo “final” reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its pre-disturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any/all contaminants, scrap/trash, equipment, pipelines and powerlines (**Contact service companies, allowing plenty of time to have the risers and power lines and poles removed prior to reclamation, don't wait till the last day and try to get them to remove infrastructure**). Strip and remove caliche, contour the location to blend with the surrounding landscape, re-distribute the native soils, provide erosion control as needed, rip (across the slope and seed as specified in the original APD COA. **This will apply to well pads, facilities, and access roads.** Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry

Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.

5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos  
Supervisory Petroleum Engineering Tech/Environmental Protection Specialist  
575-234-5909 (Office), 575-361-2648 (Cell)

Arthur Arias  
Environmental Protection Specialist  
575-234-6230

Crisha Morgan  
Environmental Protection Specialist  
575-234-5987

Jose Martinez-Colon  
Environmental Protection Specialist  
575-234-5951

Mark Mattozzi  
Environmental Protection Specialist  
575-234-5713

Robert Duenas  
Environmental Protection Specialist  
575-234-2229

Doris Lauger Martinez  
Environmental Protection Specialist  
575-234-5926

Jaden Johnston  
Environmental Protection Asst. (Intern)  
575-234-6252

Sante Fe Main Office  
Phone: (505) 476-3441

General Information  
Phone: (505) 629-6116

Online Phone Directory  
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

CONDITIONS

Action 423017

CONDITIONS

Operator: COG OPERATING LLC 600 W Illinois Ave Midland, TX 79701	OGRID: 229137
	Action Number: 423017
	Action Type: [C-103] NOI Plug & Abandon (C-103F)

CONDITIONS

Created By	Condition	Condition Date
gcordero	Run CBL from 9244' to Surface	1/30/2025
gcordero	Spot 15 sacks cement 3360' - 3260' - T 7Rivers	1/30/2025
gcordero	A Cement Bond Log (CBL) is required to be submitted to electronic permitting.	1/30/2025
gcordero	Submit Cement Bond Logs (CBL) prior to submittal of C-103P.	1/30/2025