

Well Name: ROSA UNIT	Well Location: T31N / R5W / SEC 33 / NWSW / 36.856045 / -107.373405	County or Parish/State: RIO ARRIBA / NM
Well Number: 752H	Type of Well: CONVENTIONAL GAS WELL	Allottee or Tribe Name:
Lease Number: NMSF078773	Unit or CA Name: ROSA UNIT	Unit or CA Number: NMNM78407E
US Well Number: 300393146000X1	Operator: LOGOS OPERATING LLC	

Subsequent Report

Sundry ID: 2816882

Type of Submission: Subsequent Report

Type of Action: Drilling Operations

Date Sundry Submitted: 01/10/2025

Time Sundry Submitted: 10:55

Date Operation Actually Began: 11/27/2024

Actual Procedure: 11/22/24 - LOGOS received BLM approval for Wildlife Stipulation Exception. 11/27 - 11/28/24 - Skid rig from Rosa Unit 754H to Rosa Unit 752H, NU BOP. Function test and perform full BOP test, Good test. Pressure test casing to 1500psi/15mins. Drill out DV tool #1 @ 3801' and circulate hole clean. Pressure test casing to 1500psi/15mins. Drill out #2 @ 4954' and circulate hole clean. Pressure test casing to 1500psi/15mins. Pressure test 9-5/8" casing to 1500psi/30mins. Good test. TIH drill cement and shoe track & float collar f/6472' t/ 6575'. Drill new hole f/6575' t/6605'. Circulate. Perform FIT. POOH. 11/29 - 12/02/24 - Drill 8.5" hole f/6605' t/6678', Rotate & slide drill 8.5" lateral f/6678' t/14,387'. Circulate. Spot kill pill. TOO. TIH, drill f/14,387' t/16,888' (TD). Perform clean up cycles. POOH. 12/03 - 12/05/24 - TOO with drill pipe & BHA. PU CRT. RIH with total 404jts of 5.5" 20#, P-110, BTC csg set @ 16,868' w/FC @ 16,783'. Toe sleeves f/16,700' t/16,611'. Circulate & condition. RU cmt crew. Pump 130bbls Tuned Prime spacer. Pump Lead cmt w/140sx (45bbls, 252cf) Cap Isobond cement, 12.5 ppg, 1.80yield. Pump 650sx (209bbls, 1170cf) Cap Isobond cement, 12.5 ppg, 1.80yield. Tail w/1230sx (434bbls, 2435cf) NEOCEM, 13.2ppg, 1.98yield. Displaced w/372 bbls. Bumped plug w/2750psi. 92bbls spacer to surface. Circulate 0 bbls of cmt to surface. Top of Cap cmt @ 499', Top of Lead cmt @ 1524', Top of Tail @ 6303'. RD cmt crew. RD CRT. Set pack-off, test scale to 10,000psi, pull test 40klbs over string wt - good tests. ND BOP. Rig released 12/5/24 @ 1800hrs. 12/06 - 12/12/24 - Start rigging down operation equipment. All LOGOS equipment moved off location on 12/12/2024 @ 12:00hrs. 12/23/24 - ND tubing spool, remove BPV, NU tubing spool. Pressure test 5.5" casing 1785psi/ 30mins. Good test. Install BPV. NU night cap. SIW.

Well Name: ROSA UNIT

Well Location: T31N / R5W / SEC 33 /
NWSW / 36.856045 / -107.373405County or Parish/State: RIO
ARRIBA / NM

Well Number: 752H

Type of Well: CONVENTIONAL GAS
WELL

Allottee or Tribe Name:

Lease Number: NMSF078773

Unit or CA Name: ROSA UNIT

Unit or CA Number:
NMNM78407E

US Well Number: 300393146000X1

Operator: LOGOS OPERATING LLC

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: ETTA TRUJILLO

Signed on: JAN 10, 2025 10:56 AM

Name: LOGOS OPERATING LLC

Title: Regulatory Specialist

Street Address: 2010 AFTON PLACE

City: Farmington

State: NM

Phone: (505) 324-4154

Email address: ETRUJILLO@LOGOSRESOURCESLLC.COM

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: MATTHEW H KADE

BLM POC Title: Petroleum Engineer

BLM POC Phone: 5055647736

BLM POC Email Address: MKADE@BLM.GOV

Disposition: Accepted

Disposition Date: 01/10/2025

Signature: Matthew Kade

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 419612

CONDITIONS

Operator: LOGOS OPERATING, LLC 2010 Afton Place Farmington, NM 87401	OGRID: 289408
	Action Number: 419612
	Action Type: [C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
keith.dziokonski	• A CBL is required to be submitted for each string that does not circulate cement to the surface. Please submit a RCBL for review. Thank you	5/19/2025