

Form 3160-5
(June 2019)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2021

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No. NMNM101609	
6. If Indian, Allottee or Tribe Name	
7. If Unit of CA/Agreement, Name and/or No.	
8. Well Name and No. JUNIOR MINT FED/217H	
9. API Well No.	
10. Field and Pool or Exploratory Area Dogie Draw; Wolfcamp	
11. Country or Parish, State LEA/NM	

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well ☐ Oil Well ☒ Gas Well ☐ Other	2. Name of Operator CIVITAS PERMIAN OPERATING LLC
3a. Address 555 17TH STREET SUITE 3700, DENVER, CO 8	3b. Phone No. (include area code) (303) 293-1000
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description) SEC 15/T25S/R35E/NMP	

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION				
☒ Notice of Intent	☐ Acidize	☐ Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off	
☐ Subsequent Report	☐ Alter Casing	☐ Hydraulic Fracturing	☐ Reclamation	☐ Well Integrity	
☐ Final Abandonment Notice	☐ Casing Repair	☐ New Construction	☐ Recomplete	☐ Other	
	☒ Change Plans	☐ Plug and Abandon	☐ Temporarily Abandon		
	☐ Convert to Injection	☐ Plug Back	☐ Water Disposal		

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be perfonned or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has detennined that the site is ready for final inspection.)

Civitas Permian Operating, LLC requests the following changes to the previously approved surface hole location (SHL) and drill plan. Change SHL from 272 FNL & 1531 FWL, NENW, Sec. 15, T.25S, R.35E to 301 FNL & 1411 FWL, NENW, Sec. 15, T.25S, R.35E. Changes to the drill plan and other variance requests are detailed in the attached summary and supporting documents. Please see the attached revised C102 plat, directional plan, anticollision report, production casing spec sheets and wellhead diagram for additional information.

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) BRIAN WOOD / Ph: (505) 466-8120	Title Permitting Agent
Signature (Electronic Submission)	Date 04/18/2025

THE SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by CHRISTOPHER WALLS / Ph: (575) 234-2234 / Approved	Title Petroleum Engineer	Date 05/27/2025
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.	Office CARLSBAD	

Title 18 U.S.C Section 1001 and Title 43 U.S.C Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

Additional Information

Location of Well

0. SHL: NENW / 272 FNL / 1531 FWL / TWSP: 25S / RANGE: 35E / SECTION: 15 / LAT: 32.136889 / LONG: -103.3589871 (TVD: 0 feet, MD: 0 feet)

PPP: NENW / 114 FNL / 2359 FWL / TWSP: 25S / RANGE: 35E / SECTION: 15 / LAT: 32.1373216 / LONG: -103.3563133 (TVD: 12210 feet, MD: 12298 feet)

BHL: SESW / 5 FSL / 2361 FWL / TWSP: 25S / RANGE: 35E / SECTION: 22 / LAT: 32.1086319 / LONG: -103.3563237 (TVD: 12597 feet, MD: 22841 feet)

C-102 Submit Electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION	Revised July 9, 2024	
		Submittal Type:	☐ Initial Submittal
			☒ Amended Report
		☐ As Drilled	

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-025- 54751	Pool Code 17980	Pool Name DOGIE DRAW; WOLFCAMP
Property Code 337333	Property Name JUNIOR MINT FED	Well Number 217H
OGRID No. 332195	Operator Name CIVITAS PERMIAN OPERATING, LLC	Ground Level Elevation 3221'
Surface Owner: ☐ State ☐ Fee ☐ Tribal ☒ Federal		Mineral Owner: ☐ State ☐ Fee ☐ Tribal ☒ Federal

Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
C	15	25-S	35-E	-	301' N	1411' W	N 32.1368095	W 103.3593756	LEA

Bottom Hole Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
N	22	25-S	35-E	-	5' S	2361' W	N 32.1086319	W 103.3563237	LEA

Dedicated Acres 1280.00	Infill or Defining Well -	Defining Well API -	Overlapping Spacing Unit (Y/N) -	Consolidated Code -
Order Numbers -			Well Setbacks are under Common Ownership: ☒ Yes ☐ No	

Kick Off Point (KOP)

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
C	15	25-S	35-E	-	100' N	2361' W	N 32.1373568	W 103.3563074	LEA

First Take Point (FTP)

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
C	15	25-S	35-E	-	100' N	2361' W	N 32.1373568	W 103.3563074	LEA


Last Take Point (LTP)

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the N/S	Feet from the E/W	Latitude	Longitude	County
N	22	25-S	35-E	-	100' S	2361' W	N 32.1088930	W 103.3563230	LEA

Unitized Area or Area of Uniform Intrest -	Spacing Unity Type ☒ Horizontal ☐ Vertical	Ground Floor Elevation -
--	--	------------------------------------

OPERATOR CERTIFICATION <i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief; and, if the well is a vertical or directional well, that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of a working interest or unleased mineral interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i> <i>If this well is a horizontal well, I further certify that this organization has received The consent of at least one lessee or owner of a working interest or unleased mineral interest in each tract (in the target pool or formation) in which any part of the well's completed interval will be located or obtained a compulsory pooling order from the division.</i>  4-16-25		SURVEYORS CERTIFICATION <i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i>  2/6/2025 4:24:33 PM	
Signature Cory Walk		Signature and Seal of Professional Surveyor	
Date 4-16-25		Date	
Print Name cory@permitswest.com		Certificate Number	Date of Survey 01/30/2025
E-mail Address			

C-102 Submit Electronically Via OCD Permitting	State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION	Revised July 9, 2024	
		Submittal Type:	☐ Initial Submittal
			☒ Amended Report
Property Name and Well Number		☐ As Drilled	
JUNIOR MINT FED 217H			



Junior Mint Sundry Summary

4/3/2025

Civitas Resources is requesting sundries/variances for the upcoming Junior Mint drilling campaigns.

1. Cement Volumes and Design: Civitas Resources requests to sundry cement volumes to the following strings with comments noted below:

- Intermediate Cement: for all Junior Mint wells with deepset 7 5/8" intermediate strings, the following items are updated in the cement table:
 - i. Intermediate Lead/Tail Volumes: based of offset TapRock wells drilled in the previous two years, the lead and tail cement volumes are increased to improve assurance of cement to surface.
 - ii. Intermediate Yield: The lead cement yield for the 10.5 ppg slurry is updated to reflect recent labs from cement providers.
 - iii. Intermediate Contingency for no returns and/or lack of cement to surface: the goal is to ensure quality cement from shoe to surface
 - 1. No Returns at TD of 9 7/8" Hole: Civitas Resources requests to pump an intentional 2-stage cement job where stage 1 would be pumped to the mid/base of the Brushy Canyon and stage 2 would be pumped as a standard bradenhead squeeze to the mid/base of Brushy Canyon, thus cementing the entire string. To verify the TOC of stage 2, and Echo-meter will be used

Stage 1 Cement Details (conventional):
Single slurry: 15.6 ppg cement, Class H, Yield: 1.18 cuft/sk, 25% xs DBE Emulsion Spacer (weighted)

Stage 2 Cement Details (bradenhead):
Lead: 14.8 ppg, Class C Thixotropic + LCM, Yield: 1.44 cuft/sk, 100% xs DBE Spacer (weighted)

Tail: 14.8 ppg, Class C Thixotropic, Yield: 1.44 cuft/sk, 100% xs, shoot temp survey to determine TOC

Top Out (if necessary): 14.8 Class C Neat, Yield: 1.33 cuft/sk; if required, Civitas Resources will request BLM approval to top out after running a temp survey and report back to BLM the amount of volume to flush cement lines to wellhead.
- 2. No Cement to Surface 7 5/8" cement Job: Civitas Resources requests to pump an intentional 2-stage cement job where stage 1 would be pumped to the




mid/base of the Brushy Canyon and stage 2 would be pumped as a standard bradenhead squeeze to the mid/base of Brushy Canyon (as described above), thus cementing the entire string. To verify the TOC of stage 2, and Echo-meter will be used and with BLM approval, top out the job as needed.

- Production Cement: the production tail volume has been increased from 200' to 500' to improve the overlap between intermediate and production casing



2. **Offline Cementing Intermediate Casing Only:** In addition to the batch drilling variance submitted in the original APD, Civitas Resources requests a variance for the option to offline cement intermediate casing strings set higher than the top of the WCA during the Junior Mint drilling campaign. To execute offline cement jobs safely, the following precautions and equipment are detailed below:
- During the drilling of the 9 7/8" and 10 5/8" hole sections (all TD'd above the WCA top), hole conditions will be monitored and addressed to ensure for a successful casing run. In the event hole conditions change after running casing and/or the well is not in a static state, Civitas Resources can elect to pump the cement job online.
 - Equipment for the offline cement job will include a tested/charted 5M working pressure dual manifold cement head system will be used with a standard offline cement tool that is packed off and tested through a port between the upper valve and packoff assembly (diagram below). Returns from the manifold will be taken to an auxiliary mud-gas separator during cement job. The operational scope is described in the following steps: the casing will be landed on the mandrel, pull tested, packoff installed and tested to 80% of collapse of casing on the top and bottom seals, nipple down BOP and install offline cement tool/manifold. The offline cement tool screws into the top of the packoff assembly. During the cement job, all returns will be taken through the A-Section valve (flanged).





3. **BOPE Testing Procedure for Batch Drilling:** Civitas Resources requests a variance to adjust the BOPE testing procedure to accommodate batch drilling. Details of the request are below:
- In lieu of a full BOP test during batch intermediate drilling operations, Civitas Resources requests to "Break-Test" or only test BOP connection breaks that are separated during skids between intermediate casing strings set above 5M BOPE thresholds/Wolfcamp A top. Industry standards are adhered to in terms of timing of breaks as noted in API Standard 53 which will include test charts during each skid for the following: Top Pipe Rams or VBRs, HCR, Downstream Kill Line, QDC Adapter – wellhead quick connect, and the body/shell of the BOP stack to 5M for 10 minutes.
 - Depending on the length and position of the next batch drilled intermediate hole section, the flex hose that connects to the choke manifold might have to be broken out, at which point the break will also be tested. This is not expected with Civitas Resources' rig fleet but could occur.
 - All "Break Test" BOPE operations will follow a 14-day limit, such that, Civitas Resources can have a 7-day buffer to execute a full test as per Onshore Order 43 CFR 3172 (21-day limit).
 - After completion of batch drilling operations for all intermediate hole sections above the WCA, the BOP tests will follow Onshore Order 43 CFR 3172
 - In the event any part of the BOPE equipment is changed or fails a test, a full test BOPE test will be performed. If the "Break Test" is not performed during the proper timing interval, a full BOPE test will take place.
 - The BLM will be contacted in the event a well control event is encountered.
 - During all "Break Test" or full BOPE tests, the BLM will be notified 4 hours before the test.
 - Before drilling out intermediate shoes and commencing production hole drilling, a full BOP test will be performed for all targets requiring a 10M BOPE pressure test; this test will override a previous 14 day "Break Test" interval.
4. **Centralizer Variance:** Due to the design of the intermediate casing strings on the Third Bone Spring Sand, WCA, and WCB intervals on the Junior Mint development (11 3/4" x 7 5/8" x 5 1/2" casing design), a variance to waive the centralizers is requested due to the tight clearance between 6 3/4" hole and 5 1/2" casing and the risk of not getting casing to bottom.



- Junior Mint Fed 217, WCA Target

Estimated Tops:

Formation	TVD	MD	Lithologies	Bearing
Quaternary Deposits	0	0	Surface	None
Rustler	660	660	Salt	Salt
Top Salt	1,100	1,100	Salt	Salt
Base Salt	4,920	4,924	Salt	Salt
DMG	5,160	5,175	Sandstone	None
Lamar	5,165	5,180	Sandstone	Hydrocarbons
Bell Canyon	5,185	5,285	Sandstone	Hydrocarbons
Ramsey Sand	5,205	5,305	Sandstone	Hydrocarbons
Cherry Canyon	6,150	6,250	Limestone	Hydrocarbons
Brushy Canyon	7,620	7,720	Sandstone	Hydrocarbons
Bone Spring Lime	8,930	9,030	Carbonate	Hydrocarbons
Upper Avalon	8,955	9,055	Carbonate	Hydrocarbons
Middle Avalon	9,185	9,285	Carbonate	Hydrocarbons
1st BS Sand	10,165	10,265	Sandstone	Hydrocarbons
2nd BS Carb	10,330	10,430	Carbonate	Hydrocarbons
2nd BS Sand	10,715	10,815	Sandstone	Hydrocarbons
3rd BS Carb	11,265	11,365	Carbonate	Hydrocarbons
3rd BS Sand	11,895	11,995	Sandstone	Hydrocarbons
KOP	11937	12048	Carbonate	Hydrocarbons
TD	12596	22875	Carbonate	Hydrocarbons

Casing Design:

Section	Drilled Interval			Casing Size	Standard	Tapered	Casing Set Depths				Casing Details					
	Hole Size	Top	Btm				Top MD	Bottom MD	Top TVD	BTM TVD	Grade	Weight	Thread	Collapse	Burst	Tension
Surface	14 3/4	0	1,075	11 3/4	API	No	0	1,075	0	1,075	J-55	47	BTC	1.13	1.15	1.6
1st Intermediate	9 7/8	1,075	11,948	7 5/8	API	No	0	11,948	0	11,737	P-110	29.7	BTC	1.13	1.15	1.6
Production	6 3/4	11,948	12,048	5 1/2	NON API	No	0	12,048	0	11,937	P110RYS	23	Talon	1.13	1.15	1.6
	6 3/4	12,048	22,875	5 1/2	NON API	No	12,048	22,875	11,937	12,596	P110RY	23	Talon	1.13	1.15	1.6

Cement Volumes:

Name	Type	Top MD	Sacks	Yield	Cu. Ft	Weight	Excess	Cement	Additives
Surface	Lead	0	391	1.72	672	13.5	100%	C	Additives + LCM
	Tail	775	196	1.33	260	14.8	100%	C	Additives + LCM
Intermediate	Lead	0	1074	4.29	4610	10.5	200%	C	Contingency Bradenhead Squeeze, LCM Lead
	Tail	10948	129	1.67	215	13.2	100%	C	Additives + LCM
Production	Tail	11448	924	1.24	1145	13.2	20%	H	Fluid Loss + Dispersant + Retarder + LCM

Mud Program:

Name	Top	Bottom	Type	Mud Weight	Visc	Fluid Loss
Surface	0	1,075	FW Spud Mud	8.40	28	NC
1st Intermediate	1,075	11,948	DBE	9.20	27-30	NC
Production	11,948	22,875	OBM	12.50	55-65	<16



U. S. Steel Tubular Products

5.500" 23.00lb/ft (0.415" Wall) P110 RY USS-TALON HTQ™ RD

2/25/2025 2:43:45 PM

				
MECHANICAL PROPERTIES	Pipe	USS-TALON HTQ™ RD		[6]
Minimum Yield Strength	110,000	--	psi	--
Maximum Yield Strength	125,000	--	psi	--
Minimum Tensile Strength	125,000	--	psi	--
DIMENSIONS	Pipe	USS-TALON HTQ™ RD		--
Outside Diameter	5.500	5.900	in.	--
Wall Thickness	0.415	--	in.	--
Inside Diameter	4.670	4.670	in.	--
Standard Drift	4.545	4.545	in.	--
Alternate Drift	--	--	in.	--
Nominal Linear Weight, T&C	23.00	--	lb/ft	--
Plain End Weight	22.56	--	lb/ft	--
SECTION AREA	Pipe	USS-TALON HTQ™ RD		--
Critical Area	6.630	6.425	sq. in.	--
Joint Efficiency	--	96.9	%	[2]
PERFORMANCE	Pipe	USS-TALON HTQ™ RD		--
Minimum Collapse Pressure	14,540	14,540	psi	--
Minimum Internal Yield Pressure	14,520	14,520	psi	--
Minimum Pipe Body Yield Strength	729,000	--	lb	--
Joint Strength	--	707,000	lb	--
Compression Rating	--	707,000	lb	--
Reference Length	--	20,490	ft	[5]
Maximum Uniaxial Bend Rating	--	88.9	deg/100 ft	[3]
MAKE-UP DATA	Pipe	USS-TALON HTQ™ RD		--
Make-Up Loss	--	5.58	in.	--
Minimum Make-Up Torque	--	20,800	ft-lb	[4]
Maximum Make-Up Torque	--	23,800	ft-lb	[4]
Maximum Operating Torque	--	39,800	ft-lb	[4]

UNCONTROLLED

Notes

1. Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness, and Specified Minimum Yield Strength (SMYS).
2. Joint efficiencies are calculated by dividing the connection critical area by the pipe body area.
3. Uniaxial bend rating shown is structural only.
4. Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
5. Reference length is calculated by Joint Strength divided by Nominal Linear Weight, T&C with a 1.5 Safety factor.
6. Coupling must meet minimum mechanical properties of the pipe.

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.



U. S. Steel Tubular Products

5.500" 23.00lb/ft (0.415" Wall) USS RYS110 USS-TALON HTQ™ RD

2/25/2025 2:25:12 PM

MECHANICAL PROPERTIES	Pipe	USS-TALON HTQ™ RD		[6]
Minimum Yield Strength	110,000	--	psi	--
Maximum Yield Strength	125,000	--	psi	--
Minimum Tensile Strength	120,000	--	psi	--
DIMENSIONS	Pipe	USS-TALON HTQ™ RD		--
Outside Diameter	5.500	5.900	in.	--
Wall Thickness	0.415	--	in.	--
Inside Diameter	4.670	4.670	in.	--
Standard Drift	4.545	4.545	in.	--
Alternate Drift	--	--	in.	--
Nominal Linear Weight, T&C	23.00	--	lb/ft	--
Plain End Weight	22.56	--	lb/ft	--
SECTION AREA	Pipe	USS-TALON HTQ™ RD		--
Critical Area	6.630	6.425	sq. in.	--
Joint Efficiency	--	96.9	%	[2]
PERFORMANCE	Pipe	USS-TALON HTQ™ RD		--
Minimum Collapse Pressure	14,540	14,540	psi	--
Minimum Internal Yield Pressure	14,520	14,520	psi	--
Minimum Pipe Body Yield Strength	729,000	--	lb	--
Joint Strength	--	707,000	lb	--
Compression Rating	--	707,000	lb	--
Reference Length	--	20,490	ft	[5]
Maximum Uniaxial Bend Rating	--	88.9	deg/100 ft	[3]
MAKE-UP DATA	Pipe	USS-TALON HTQ™ RD		--
Make-Up Loss	--	5.58	in.	--
Minimum Make-Up Torque	--	20,800	ft-lb	[4]
Maximum Make-Up Torque	--	23,800	ft-lb	[4]
Maximum Operating Torque	--	39,800	ft-lb	[4]

UNCONTROLLED

Notes


1. Other than proprietary collapse and connection values, performance properties have been calculated using standard equations defined by API 5C3 and do not incorporate any additional design or safety factors. Calculations assume nominal pipe OD, nominal wall thickness, and Specified Minimum Yield Strength (SMYS).
2. Joint efficiencies are calculated by dividing the connection critical area by the pipe body area.
3. Uniaxial bend rating shown is structural only.
4. Torques have been calculated assuming a thread compound friction factor of 1.0 and are recommended only. Field make-up torques may require adjustment based on actual field conditions (e.g. make-up speed, temperature, thread compound, etc.).
5. Reference length is calculated by Joint Strength divided by Nominal Linear Weight, T&C with a 1.5 Safety factor.
6. Coupling must meet minimum mechanical properties of the pipe.

Legal Notice

All material contained in this publication is for general information only. This material should not therefore be used or relied upon for any specific application without independent competent professional examination and verification of accuracy, suitability and applicability. Anyone making use of this material does so at their own risk and assumes any and all liability resulting from such use. U. S. Steel disclaims any and all expressed or implied warranties of fitness for any general or particular application.

U. S. Steel Tubular Products
460 Wildwood Forest Drive, Suite 300S
Spring, Texas 77380

1-877-893-9461
connections@uss.com
www.usstubular.com



INFORMATION CONTAINED HEREIN IS THE PROPERTY OF CACTUS WELLHEAD, LLC. REPRODUCTION, DISCLOSURE, OR USE THEREOF IS PERMISSIBLE ONLY AS PROVIDED BY CONTRACT OR AS EXPRESSLY AUTHORIZED BY CACTUS WELLHEAD, LLC.

ALL DIMENSIONS APPROXIMATE

CACTUS WELLHEAD LLC		CIVITAS RESOURCES DELAWARE BASIN	
20" x 11-3/4" x 7-5/8" x 5-1/2" MBU-3T-SF Wellhead System With 13-5/8" 10M x 7-1/16" 15M CTH-DBLHPS Tubing Head And Quick Connect Drill Adapter & Quick Connect TA Cap	DRAWN	VJK	13FEB25
	APPR		
DRAWING NO.		REF: HBE0001444	

Project: Lea County, NM (NAD 83)
Site: Junior Mint Fed Pad
Well: Junior Mint Fed 217H
Wellbore: OH
Design: Plan 1
Rig: 26' KB



Azimuths to Grid North
True North: -0.52°
Magnetic North: 5.55°

Magnetic Field
Strength: 47069.3nT
Dip Angle: 59.57°
Date: 7/15/2025
Model: HDGM2025

Total Magnetic Correction: 5.55°

PROJECT DETAILS: Lea County, NM (NAD 83)

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone

Reference Datum: GE 3221 + 26 @ 3247.00usft (26' KB)

SHL

RKB Elevation: GE 3221 + 26 @ 3247.00usft (26' KB)






+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Slot
0.00	0.00	414870.00	842810.00	32.1368093	-103.3593755	

SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSec	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
980.00	0.00	0.00	980.00	0.00	0.00	0.00	0.00	0.00	
1313.33	5.00	92.00	1312.91	-0.51	14.53	1.50	92.00	1.97	
2203.81	5.00	92.00	2200.00	-3.22	92.09	0.00	0.00	12.49	
2898.63	15.00	72.43	2883.54	22.95	208.40	1.50	-28.64	-1.81	
6391.36	15.00	72.43	6291.32	217.77	823.49	0.00	0.00	-133.58	
6391.42	0.00	0.00	6280.00	257.07	947.58	1.50	180.00	-160.16	
12048.42	0.00	0.00	11937.00	257.07	947.58	0.00	0.00	-160.16	
12943.42	89.50	179.51	12509.94	-310.86	952.47	10.00	179.51	405.36	
22875.30	89.50	179.51	12596.70	-10242.00	1038.00	0.00	0.00	10294.46	

WELLBORE TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
Junior Mint Fed 217H KOP/FTP	11937.00	208.00	948.00	415078.00	843758.00	32.1373573	-103.3563071
Junior Mint Fed 217H LTP	12596.20	-10147.00	1037.00	404723.00	843847.00	32.1088939	-103.3563225
Junior Mint Fed 217H BHL	12596.70	-10242.00	1038.00	404628.00	843848.00	32.1086328	-103.3563225



Do Not Cross SL

Civitas Resources

Lea County, NM (NAD 83)
Junior Mint Fed Pad
Junior Mint Fed 217H

OH

Plan: Plan 1



Standard Plan Report

25 March, 2025

Total Report Version 1.70

COMPASS 5000.16 Build 97

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Project	Lea County, NM (NAD 83)	System Datum:	Mean Sea Level
Map System:	US State Plane 1983		
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	Junior Mint Fed Pad				
Site Position:		Northing:	414,635.00 usft	Latitude:	32.1361627
From:	Map	Easting:	842,835.00 usft	Longitude:	-103.3593016
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "		

Well	Junior Mint Fed 217H					
Well Position	+N/-S	0.00 usft	Northing:	414,870.00 usft	Latitude:	32.1368093
	+E/-W	0.00 usft	Easting:	842,810.00 usft	Longitude:	-103.3593755
Position Uncertainty	0.50 usft		Wellhead Elevation:	usft	Ground Level:	3,221.00 usft
Grid Convergence:	0.52 °					

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM2025	7/15/2025	6.07	59.57	47,069.30000000

Design	Plan 1				
Audit Notes:					
Version:	Phase:	PLAN	Tie On Depth:	0.00	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.00	0.00	0.00	174.21	

Survey Tool Program	Date	3/24/2025			
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description	
0.00	22,875.30	Plan 1 (OH)	MWD+HRGM+SAG+FDIF	OWSG MWD + HRGM + SAG + FDIR Correction	

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Plan Summary

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
980.00	0.00	0.00	980.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,313.33	5.00	92.00	1,312.91	-0.51	14.53	1.50	1.50	0.00	92.00	
2,203.81	5.00	92.00	2,200.00	-3.22	92.09	0.00	0.00	0.00	0.00	
2,898.63	15.00	72.43	2,883.54	22.95	208.40	1.50	1.44	-2.82	-28.64	
5,391.36	15.00	72.43	5,291.32	217.77	823.49	0.00	0.00	0.00	0.00	
6,391.42	0.00	0.00	6,280.00	257.07	947.58	1.50	-1.50	0.00	180.00	
12,048.42	0.00	0.00	11,937.00	257.07	947.58	0.00	0.00	0.00	0.00	
12,943.42	89.50	179.51	12,509.94	-310.86	952.47	10.00	10.00	20.06	179.51	
22,875.30	89.50	179.51	12,596.70	-10,242.00	1,038.00	0.00	0.00	0.00	0.00	

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates (usft)		Map Coordinates (usft)		Geo Coordinates (°)		Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude				
100.00	0.00	0.00	100.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
980.00	0.00	0.00	980.00	0.00	0.00	414,870.00	842,810.00	32.1368093	-103.3593755	0.00	0.00	0.00	0.00
1,000.00	0.30	92.00	1,000.00	0.00	0.05	414,870.00	842,810.05	32.1368093	-103.3593753	0.01	1.50	1.50	0.00
1,100.00	1.80	92.00	1,099.98	-0.07	1.88	414,869.93	842,811.88	32.1368090	-103.3593694	0.26	1.50	1.50	0.00
1,200.00	3.30	92.00	1,199.88	-0.22	6.33	414,869.78	842,816.33	32.1368085	-103.3593550	0.86	1.50	1.50	0.00
1,300.00	4.80	92.00	1,299.63	-0.47	13.39	414,869.53	842,823.39	32.1368077	-103.3593323	1.82	1.50	1.50	0.00
1,313.33	5.00	92.00	1,312.91	-0.51	14.53	414,869.49	842,824.53	32.1368075	-103.3593286	1.97	1.50	1.50	0.00
1,400.00	5.00	92.00	1,399.25	-0.77	22.08	414,869.23	842,832.08	32.1368066	-103.3593042	2.99	0.00	0.00	0.00
1,500.00	5.00	92.00	1,498.87	-1.08	30.79	414,868.92	842,840.79	32.1368056	-103.3592761	4.18	0.00	0.00	0.00
1,600.00	5.00	92.00	1,598.49	-1.38	39.50	414,868.62	842,849.50	32.1368045	-103.3592479	5.36	0.00	0.00	0.00
1,700.00	5.00	92.00	1,698.11	-1.68	48.21	414,868.32	842,858.21	32.1368035	-103.3592198	6.54	0.00	0.00	0.00
1,800.00	5.00	92.00	1,797.73	-1.99	56.92	414,868.01	842,866.92	32.1368024	-103.3591917	7.72	0.00	0.00	0.00
1,900.00	5.00	92.00	1,897.34	-2.29	65.63	414,867.71	842,875.63	32.1368013	-103.3591636	8.90	0.00	0.00	0.00
2,000.00	5.00	92.00	1,996.96	-2.60	74.34	414,867.40	842,884.34	32.1368003	-103.3591354	10.08	0.00	0.00	0.00
2,100.00	5.00	92.00	2,096.58	-2.90	83.05	414,867.10	842,893.05	32.1367992	-103.3591073	11.26	0.00	0.00	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Dogleg Section (usft)	Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
2,203.81	5.00	92.00	2,200.00	-3.22	92.09	414,866.78	842,902.09	32.1367981	-103.3590781	12.49	0.00	0.00	0.00
2,300.00	6.30	85.69	2,295.72	-2.97	101.55	414,867.03	842,911.55	32.1367986	-103.3590476	13.19	1.50	1.36	-6.56
2,400.00	7.71	81.43	2,394.97	-1.55	113.66	414,868.45	842,923.66	32.1368022	-103.3590084	13.01	1.50	1.41	-4.26
2,500.00	9.15	78.50	2,493.89	1.03	128.08	414,871.03	842,938.08	32.1368089	-103.3589617	11.89	1.50	1.44	-2.94
2,600.00	10.60	76.35	2,592.40	4.79	144.82	414,874.79	842,954.82	32.1368188	-103.3589075	9.84	1.50	1.45	-2.14
2,700.00	12.07	74.73	2,690.45	9.71	163.85	414,879.71	842,973.85	32.1368319	-103.3588459	6.86	1.50	1.47	-1.63
2,800.00	13.54	73.45	2,787.96	15.81	185.16	414,885.81	842,995.16	32.1368481	-103.3587769	2.95	1.50	1.47	-1.28
2,898.63	15.00	72.43	2,883.54	22.95	208.40	414,892.95	843,018.40	32.1368672	-103.3587016	-1.81	1.50	1.48	-1.03
2,900.00	15.00	72.43	2,884.87	23.06	208.73	414,893.06	843,018.73	32.1368675	-103.3587005	-1.88	0.00	0.00	0.00
3,000.00	15.00	72.43	2,981.46	30.87	233.41	414,900.87	843,043.41	32.1368883	-103.3586206	-7.17	0.00	0.00	0.00
3,100.00	15.00	72.43	3,078.05	38.69	258.08	414,908.69	843,068.08	32.1369092	-103.3585407	-12.46	0.00	0.00	0.00
3,200.00	15.00	72.43	3,174.64	46.50	282.76	414,916.50	843,092.76	32.1369301	-103.3584607	-17.74	0.00	0.00	0.00
3,300.00	15.00	72.43	3,271.24	54.32	307.43	414,924.32	843,117.43	32.1369509	-103.3583808	-23.03	0.00	0.00	0.00
3,400.00	15.00	72.43	3,367.83	62.13	332.11	414,932.13	843,142.11	32.1369718	-103.3583009	-28.31	0.00	0.00	0.00
3,500.00	15.00	72.43	3,464.42	69.95	356.79	414,939.95	843,166.79	32.1369927	-103.3582209	-33.60	0.00	0.00	0.00
3,600.00	15.00	72.43	3,561.01	77.77	381.46	414,947.77	843,191.46	32.1370135	-103.3581410	-38.89	0.00	0.00	0.00
3,700.00	15.00	72.43	3,657.60	85.58	406.14	414,955.58	843,216.14	32.1370344	-103.3580611	-44.17	0.00	0.00	0.00
3,800.00	15.00	72.43	3,754.20	93.40	430.81	414,963.40	843,240.81	32.1370553	-103.3579811	-49.46	0.00	0.00	0.00
3,900.00	15.00	72.43	3,850.79	101.21	455.49	414,971.21	843,265.49	32.1370761	-103.3579012	-54.74	0.00	0.00	0.00
4,000.00	15.00	72.43	3,947.38	109.03	480.16	414,979.03	843,290.16	32.1370970	-103.3578212	-60.03	0.00	0.00	0.00
4,100.00	15.00	72.43	4,043.97	116.84	504.84	414,986.84	843,314.84	32.1371179	-103.3577413	-65.32	0.00	0.00	0.00
4,200.00	15.00	72.43	4,140.56	124.66	529.51	414,994.66	843,339.51	32.1371387	-103.3576614	-70.60	0.00	0.00	0.00
4,300.00	15.00	72.43	4,237.16	132.47	554.19	415,002.47	843,364.19	32.1371596	-103.3575814	-75.89	0.00	0.00	0.00
4,400.00	15.00	72.43	4,333.75	140.29	578.86	415,010.29	843,388.86	32.1371805	-103.3575015	-81.17	0.00	0.00	0.00
4,500.00	15.00	72.43	4,430.34	148.10	603.54	415,018.10	843,413.54	32.1372013	-103.3574216	-86.46	0.00	0.00	0.00
4,600.00	15.00	72.43	4,526.93	155.92	628.21	415,025.92	843,438.21	32.1372222	-103.3573416	-91.75	0.00	0.00	0.00
4,700.00	15.00	72.43	4,623.53	163.73	652.89	415,033.73	843,462.89	32.1372431	-103.3572617	-97.03	0.00	0.00	0.00
4,800.00	15.00	72.43	4,720.12	171.55	677.57	415,041.55	843,487.57	32.1372639	-103.3571817	-102.32	0.00	0.00	0.00
4,900.00	15.00	72.43	4,816.71	179.36	702.24	415,049.36	843,512.24	32.1372848	-103.3571018	-107.61	0.00	0.00	0.00
5,000.00	15.00	72.43	4,913.30	187.18	726.92	415,057.18	843,536.92	32.1373057	-103.3570219	-112.89	0.00	0.00	0.00
5,100.00	15.00	72.43	5,009.89	195.00	751.59	415,065.00	843,561.59	32.1373265	-103.3569419	-118.18	0.00	0.00	0.00
5,200.00	15.00	72.43	5,106.49	202.81	776.27	415,072.81	843,586.27	32.1373474	-103.3568620	-123.46	0.00	0.00	0.00
5,300.00	15.00	72.43	5,203.08	210.63	800.94	415,080.63	843,610.94	32.1373683	-103.3567821	-128.75	0.00	0.00	0.00
5,391.36	15.00	72.43	5,291.32	217.77	823.49	415,087.77	843,633.49	32.1373873	-103.3567090	-133.58	0.00	0.00	0.00
5,400.00	14.87	72.43	5,299.67	218.44	825.61	415,088.44	843,635.61	32.1373891	-103.3567022	-134.03	1.50	-1.50	0.00
5,500.00	13.37	72.43	5,396.65	225.81	848.87	415,095.81	843,658.87	32.1374088	-103.3566268	-139.02	1.50	-1.50	0.00
5,600.00	11.87	72.43	5,494.23	232.40	869.70	415,102.40	843,679.70	32.1374264	-103.3565593	-143.48	1.50	-1.50	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Dogleg Section (usft)	Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,700.00	10.37	72.43	5,592.35	238.23	888.09	415,108.23	843,698.09	32.1374419	-103.3564998	-147.42	1.50	-1.50	0.00
5,800.00	8.87	72.43	5,690.94	243.27	904.02	415,113.27	843,714.02	32.1374554	-103.3564481	-150.83	1.50	-1.50	0.00
5,900.00	7.37	72.43	5,789.93	247.54	917.49	415,117.54	843,727.49	32.1374668	-103.3564045	-153.72	1.50	-1.50	0.00
6,000.00	5.87	72.43	5,889.26	251.02	928.48	415,121.02	843,738.48	32.1374761	-103.3563689	-156.07	1.50	-1.50	0.00
6,100.00	4.37	72.43	5,988.86	253.71	936.99	415,123.71	843,746.99	32.1374833	-103.3563413	-157.89	1.50	-1.50	0.00
6,200.00	2.87	72.43	6,088.66	255.62	943.01	415,125.62	843,753.01	32.1374884	-103.3563218	-159.18	1.50	-1.50	0.00
6,300.00	1.37	72.43	6,188.59	256.74	946.54	415,126.74	843,756.54	32.1374914	-103.3563104	-159.94	1.50	-1.50	0.00
6,391.42	0.00	0.00	6,280.00	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	1.50	-1.50	0.00
6,400.00	0.00	0.00	6,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
6,500.00	0.00	0.00	6,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
6,600.00	0.00	0.00	6,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
6,700.00	0.00	0.00	6,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
6,800.00	0.00	0.00	6,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
6,900.00	0.00	0.00	6,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,000.00	0.00	0.00	6,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,100.00	0.00	0.00	6,988.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,200.00	0.00	0.00	7,088.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,300.00	0.00	0.00	7,188.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,400.00	0.00	0.00	7,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,500.00	0.00	0.00	7,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,600.00	0.00	0.00	7,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,700.00	0.00	0.00	7,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,800.00	0.00	0.00	7,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
7,900.00	0.00	0.00	7,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,000.00	0.00	0.00	7,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,100.00	0.00	0.00	7,988.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,200.00	0.00	0.00	8,088.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,300.00	0.00	0.00	8,188.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,400.00	0.00	0.00	8,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,500.00	0.00	0.00	8,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,600.00	0.00	0.00	8,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,700.00	0.00	0.00	8,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,800.00	0.00	0.00	8,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
8,900.00	0.00	0.00	8,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,000.00	0.00	0.00	8,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,100.00	0.00	0.00	8,988.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,200.00	0.00	0.00	9,088.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,300.00	0.00	0.00	9,188.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,400.00	0.00	0.00	9,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,500.00	0.00	0.00	9,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,600.00	0.00	0.00	9,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,700.00	0.00	0.00	9,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,800.00	0.00	0.00	9,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
9,900.00	0.00	0.00	9,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,000.00	0.00	0.00	9,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,100.00	0.00	0.00	9,988.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,200.00	0.00	0.00	10,088.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,300.00	0.00	0.00	10,188.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,400.00	0.00	0.00	10,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,500.00	0.00	0.00	10,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,600.00	0.00	0.00	10,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,700.00	0.00	0.00	10,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,800.00	0.00	0.00	10,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
10,900.00	0.00	0.00	10,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,000.00	0.00	0.00	10,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,100.00	0.00	0.00	10,988.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,200.00	0.00	0.00	11,088.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,300.00	0.00	0.00	11,188.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,400.00	0.00	0.00	11,288.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,500.00	0.00	0.00	11,388.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,600.00	0.00	0.00	11,488.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,700.00	0.00	0.00	11,588.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,800.00	0.00	0.00	11,688.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
11,900.00	0.00	0.00	11,788.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
12,000.00	0.00	0.00	11,888.58	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
12,048.42	0.00	0.00	11,937.00	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
12,048.49	0.00	179.51	11,937.07	257.07	947.58	415,127.07	843,757.58	32.1374923	-103.3563070	-160.16	0.00	0.00	0.00
Junior Mint Fed 217H KOP/FTP													
12,050.00	0.16	179.51	11,938.58	257.07	947.58	415,127.07	843,757.58	32.1374922	-103.3563070	-160.16	10.45	10.45	0.00
12,100.00	5.16	179.51	11,988.51	254.75	947.60	415,124.75	843,757.60	32.1374859	-103.3563070	-157.85	10.00	10.00	0.00
12,150.00	10.16	179.51	12,038.05	248.09	947.66	415,118.09	843,757.66	32.1374676	-103.3563070	-151.22	10.00	10.00	0.00
12,200.00	15.16	179.51	12,086.82	237.14	947.75	415,107.14	843,757.75	32.1374375	-103.3563070	-140.32	10.00	10.00	0.00
12,250.00	20.16	179.51	12,134.45	221.98	947.88	415,091.98	843,757.88	32.1373958	-103.3563071	-125.22	10.00	10.00	0.00
12,300.00	25.16	179.51	12,180.57	202.72	948.05	415,072.72	843,758.05	32.1373429	-103.3563071	-106.05	10.00	10.00	0.00
12,350.00	30.16	179.51	12,224.85	179.52	948.25	415,049.52	843,758.25	32.1372791	-103.3563071	-82.94	10.00	10.00	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
12,400.00	35.16	179.51	12,266.93	152.55	948.48	415,022.55	843,758.48	32.1372049	-103.3563072	-56.08	10.00	10.00	0.00
12,450.00	40.16	179.51	12,306.50	122.01	948.74	414,992.01	843,758.74	32.1371210	-103.3563072	-25.68	10.00	10.00	0.00
12,500.00	45.16	179.51	12,343.26	88.14	949.03	414,958.14	843,759.03	32.1370279	-103.3563073	8.05	10.00	10.00	0.00
12,550.00	50.16	179.51	12,376.92	51.20	949.35	414,921.20	843,759.35	32.1369264	-103.3563073	44.84	10.00	10.00	0.00
12,600.00	55.16	179.51	12,407.24	11.46	949.70	414,881.46	843,759.70	32.1368171	-103.3563074	84.40	10.00	10.00	0.00
12,650.00	60.16	179.51	12,433.98	-30.77	950.06	414,839.23	843,760.06	32.1367011	-103.3563074	126.45	10.00	10.00	0.00
12,700.00	65.16	179.51	12,456.94	-75.16	950.44	414,794.84	843,760.44	32.1365790	-103.3563075	170.66	10.00	10.00	0.00
12,750.00	70.16	179.51	12,475.94	-121.39	950.84	414,748.61	843,760.84	32.1364519	-103.3563076	216.70	10.00	10.00	0.00
12,800.00	75.16	179.51	12,490.84	-169.11	951.25	414,700.89	843,761.25	32.1363208	-103.3563076	264.21	10.00	10.00	0.00
12,850.00	80.16	179.51	12,501.53	-217.93	951.67	414,652.07	843,761.67	32.1361866	-103.3563077	312.83	10.00	10.00	0.00
12,900.00	85.16	179.51	12,507.91	-267.50	952.10	414,602.50	843,762.10	32.1360503	-103.3563078	362.19	10.00	10.00	0.00
12,943.42	89.50	179.51	12,509.94	-310.86	952.47	414,559.14	843,762.47	32.1359311	-103.3563079	405.36	10.00	10.00	0.00
13,000.00	89.50	179.51	12,510.43	-367.44	952.96	414,502.56	843,762.96	32.1357756	-103.3563079	461.70	0.00	0.00	0.00
13,100.00	89.50	179.51	12,511.30	-467.43	953.82	414,402.57	843,763.82	32.1355008	-103.3563081	561.27	0.00	0.00	0.00
13,200.00	89.50	179.51	12,512.18	-567.43	954.68	414,302.57	843,764.68	32.1352259	-103.3563082	660.84	0.00	0.00	0.00
13,300.00	89.50	179.51	12,513.05	-667.42	955.54	414,202.58	843,765.54	32.1349511	-103.3563084	760.41	0.00	0.00	0.00
13,400.00	89.50	179.51	12,513.92	-767.41	956.40	414,102.59	843,766.40	32.1346762	-103.3563085	859.98	0.00	0.00	0.00
13,500.00	89.50	179.51	12,514.80	-867.40	957.26	414,002.60	843,767.26	32.1344013	-103.3563087	959.55	0.00	0.00	0.00
13,600.00	89.50	179.51	12,515.67	-967.40	958.13	413,902.60	843,768.13	32.1341265	-103.3563088	1,059.12	0.00	0.00	0.00
13,700.00	89.50	179.51	12,516.55	-1,067.39	958.99	413,802.61	843,768.99	32.1338516	-103.3563090	1,158.69	0.00	0.00	0.00
13,800.00	89.50	179.51	12,517.42	-1,167.38	959.85	413,702.62	843,769.85	32.1335768	-103.3563091	1,258.26	0.00	0.00	0.00
13,900.00	89.50	179.51	12,518.29	-1,267.37	960.71	413,602.63	843,770.71	32.1333019	-103.3563093	1,357.83	0.00	0.00	0.00
14,000.00	89.50	179.51	12,519.17	-1,367.37	961.57	413,502.63	843,771.57	32.1330271	-103.3563094	1,457.40	0.00	0.00	0.00
14,100.00	89.50	179.51	12,520.04	-1,467.36	962.43	413,402.64	843,772.43	32.1327522	-103.3563096	1,556.97	0.00	0.00	0.00
14,200.00	89.50	179.51	12,520.91	-1,567.35	963.29	413,302.65	843,773.29	32.1324774	-103.3563097	1,656.53	0.00	0.00	0.00
14,300.00	89.50	179.51	12,521.79	-1,667.34	964.15	413,202.66	843,774.15	32.1322025	-103.3563099	1,756.10	0.00	0.00	0.00
14,400.00	89.50	179.51	12,522.66	-1,767.34	965.01	413,102.66	843,775.01	32.1319276	-103.3563100	1,855.67	0.00	0.00	0.00
14,500.00	89.50	179.51	12,523.53	-1,867.33	965.88	413,002.67	843,775.88	32.1316528	-103.3563102	1,955.24	0.00	0.00	0.00
14,600.00	89.50	179.51	12,524.41	-1,967.32	966.74	412,902.68	843,776.74	32.1313779	-103.3563103	2,054.81	0.00	0.00	0.00
14,700.00	89.50	179.51	12,525.28	-2,067.31	967.60	412,802.69	843,777.60	32.1311031	-103.3563105	2,154.38	0.00	0.00	0.00
14,800.00	89.50	179.51	12,526.16	-2,167.31	968.46	412,702.69	843,778.46	32.1308282	-103.3563106	2,253.95	0.00	0.00	0.00
14,900.00	89.50	179.51	12,527.03	-2,267.30	969.32	412,602.70	843,779.32	32.1305534	-103.3563108	2,353.52	0.00	0.00	0.00
15,000.00	89.50	179.51	12,527.90	-2,367.29	970.18	412,502.71	843,780.18	32.1302785	-103.3563109	2,453.09	0.00	0.00	0.00
15,100.00	89.50	179.51	12,528.78	-2,467.28	971.04	412,402.72	843,781.04	32.1300037	-103.3563111	2,552.66	0.00	0.00	0.00
15,200.00	89.50	179.51	12,529.65	-2,567.28	971.90	412,302.72	843,781.90	32.1297288	-103.3563112	2,652.23	0.00	0.00	0.00
15,300.00	89.50	179.51	12,530.52	-2,667.27	972.76	412,202.73	843,782.76	32.1294539	-103.3563113	2,751.80	0.00	0.00	0.00
15,400.00	89.50	179.51	12,531.40	-2,767.26	973.63	412,102.74	843,783.63	32.1291791	-103.3563115	2,851.37	0.00	0.00	0.00
15,500.00	89.50	179.51	12,532.27	-2,867.25	974.49	412,002.75	843,784.49	32.1289042	-103.3563116	2,950.93	0.00	0.00	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
15,600.00	89.50	179.51	12,533.14	-2,967.25	975.35	411,902.75	843,785.35	32.1286294	-103.3563118	3,050.50	0.00	0.00	0.00
15,700.00	89.50	179.51	12,534.02	-3,067.24	976.21	411,802.76	843,786.21	32.1283545	-103.3563119	3,150.07	0.00	0.00	0.00
15,800.00	89.50	179.51	12,534.89	-3,167.23	977.07	411,702.77	843,787.07	32.1280797	-103.3563121	3,249.64	0.00	0.00	0.00
15,900.00	89.50	179.51	12,535.76	-3,267.22	977.93	411,602.78	843,787.93	32.1278048	-103.3563122	3,349.21	0.00	0.00	0.00
16,000.00	89.50	179.51	12,536.64	-3,367.22	978.79	411,502.78	843,788.79	32.1275300	-103.3563124	3,448.78	0.00	0.00	0.00
16,100.00	89.50	179.51	12,537.51	-3,467.21	979.65	411,402.79	843,789.65	32.1272551	-103.3563125	3,548.35	0.00	0.00	0.00
16,200.00	89.50	179.51	12,538.39	-3,567.20	980.52	411,302.80	843,790.52	32.1269802	-103.3563127	3,647.92	0.00	0.00	0.00
16,300.00	89.50	179.51	12,539.26	-3,667.19	981.38	411,202.81	843,791.38	32.1267054	-103.3563128	3,747.49	0.00	0.00	0.00
16,400.00	89.50	179.51	12,540.13	-3,767.19	982.24	411,102.81	843,792.24	32.1264305	-103.3563130	3,847.06	0.00	0.00	0.00
16,500.00	89.50	179.51	12,541.01	-3,867.18	983.10	411,002.82	843,793.10	32.1261557	-103.3563131	3,946.63	0.00	0.00	0.00
16,600.00	89.50	179.51	12,541.88	-3,967.17	983.96	410,902.83	843,793.96	32.1258808	-103.3563133	4,046.20	0.00	0.00	0.00
16,700.00	89.50	179.51	12,542.75	-4,067.16	984.82	410,802.84	843,794.82	32.1256060	-103.3563134	4,145.77	0.00	0.00	0.00
16,800.00	89.50	179.51	12,543.63	-4,167.16	985.68	410,702.84	843,795.68	32.1253311	-103.3563136	4,245.33	0.00	0.00	0.00
16,900.00	89.50	179.51	12,544.50	-4,267.15	986.54	410,602.85	843,796.54	32.1250563	-103.3563137	4,344.90	0.00	0.00	0.00
17,000.00	89.50	179.51	12,545.37	-4,367.14	987.40	410,502.86	843,797.40	32.1247814	-103.3563139	4,444.47	0.00	0.00	0.00
17,100.00	89.50	179.51	12,546.25	-4,467.13	988.27	410,402.87	843,798.27	32.1245065	-103.3563140	4,544.04	0.00	0.00	0.00
17,200.00	89.50	179.51	12,547.12	-4,567.13	989.13	410,302.87	843,799.13	32.1242317	-103.3563142	4,643.61	0.00	0.00	0.00
17,300.00	89.50	179.51	12,547.99	-4,667.12	989.99	410,202.88	843,799.99	32.1239568	-103.3563143	4,743.18	0.00	0.00	0.00
17,400.00	89.50	179.51	12,548.87	-4,767.11	990.85	410,102.89	843,800.85	32.1236820	-103.3563144	4,842.75	0.00	0.00	0.00
17,500.00	89.50	179.51	12,549.74	-4,867.10	991.71	410,002.90	843,801.71	32.1234071	-103.3563146	4,942.32	0.00	0.00	0.00
17,600.00	89.50	179.51	12,550.62	-4,967.10	992.57	409,902.90	843,802.57	32.1231323	-103.3563147	5,041.89	0.00	0.00	0.00
17,700.00	89.50	179.51	12,551.49	-5,067.09	993.43	409,802.91	843,803.43	32.1228574	-103.3563149	5,141.46	0.00	0.00	0.00
17,800.00	89.50	179.51	12,552.36	-5,167.08	994.29	409,702.92	843,804.29	32.1225826	-103.3563150	5,241.03	0.00	0.00	0.00
17,900.00	89.50	179.51	12,553.24	-5,267.07	995.15	409,602.93	843,805.15	32.1223077	-103.3563152	5,340.60	0.00	0.00	0.00
18,000.00	89.50	179.51	12,554.11	-5,367.07	996.02	409,502.93	843,806.02	32.1220328	-103.3563153	5,440.17	0.00	0.00	0.00
18,100.00	89.50	179.51	12,554.98	-5,467.06	996.88	409,402.94	843,806.88	32.1217580	-103.3563155	5,539.73	0.00	0.00	0.00
18,200.00	89.50	179.51	12,555.86	-5,567.05	997.74	409,302.95	843,807.74	32.1214831	-103.3563156	5,639.30	0.00	0.00	0.00
18,300.00	89.50	179.51	12,556.73	-5,667.04	998.60	409,202.96	843,808.60	32.1212083	-103.3563158	5,738.87	0.00	0.00	0.00
18,400.00	89.50	179.51	12,557.60	-5,767.04	999.46	409,102.96	843,809.46	32.1209334	-103.3563159	5,838.44	0.00	0.00	0.00
18,500.00	89.50	179.51	12,558.48	-5,867.03	1,000.32	409,002.97	843,810.32	32.1206586	-103.3563161	5,938.01	0.00	0.00	0.00
18,600.00	89.50	179.51	12,559.35	-5,967.02	1,001.18	408,902.98	843,811.18	32.1203837	-103.3563162	6,037.58	0.00	0.00	0.00
18,700.00	89.50	179.51	12,560.23	-6,067.01	1,002.04	408,802.99	843,812.04	32.1201089	-103.3563164	6,137.15	0.00	0.00	0.00
18,800.00	89.50	179.51	12,561.10	-6,167.01	1,002.91	408,703.00	843,812.91	32.1198340	-103.3563165	6,236.72	0.00	0.00	0.00
18,900.00	89.50	179.51	12,561.97	-6,267.00	1,003.77	408,603.00	843,813.77	32.1195591	-103.3563167	6,336.29	0.00	0.00	0.00
19,000.00	89.50	179.51	12,562.85	-6,366.99	1,004.63	408,503.01	843,814.63	32.1192843	-103.3563168	6,435.86	0.00	0.00	0.00
19,100.00	89.50	179.51	12,563.72	-6,466.98	1,005.49	408,403.02	843,815.49	32.1190094	-103.3563169	6,535.43	0.00	0.00	0.00
19,200.00	89.50	179.51	12,564.59	-6,566.98	1,006.35	408,303.03	843,816.35	32.1187346	-103.3563171	6,635.00	0.00	0.00	0.00

Total Directional Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured Depth (usft)	INC (°)	AZI (°)	Vertical Depth (usft)	Local Coordinates +N/-S (usft)	+E/-W (usft)	Map Coordinates Northing (usft)	Easting (usft)	Geo Coordinates Latitude (°)	Longitude (°)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
19,300.00	89.50	179.51	12,565.47	-6,666.97	1,007.21	408,203.03	843,817.21	32.1184597	-103.3563172	6,734.56	0.00	0.00	0.00
19,400.00	89.50	179.51	12,566.34	-6,766.96	1,008.07	408,103.04	843,818.07	32.1181849	-103.3563174	6,834.13	0.00	0.00	0.00
19,500.00	89.50	179.51	12,567.21	-6,866.95	1,008.93	408,003.05	843,818.93	32.1179100	-103.3563175	6,933.70	0.00	0.00	0.00
19,600.00	89.50	179.51	12,568.09	-6,966.94	1,009.79	407,903.06	843,819.79	32.1176352	-103.3563177	7,033.27	0.00	0.00	0.00
19,700.00	89.50	179.51	12,568.96	-7,066.94	1,010.66	407,803.06	843,820.66	32.1173603	-103.3563178	7,132.84	0.00	0.00	0.00
19,800.00	89.50	179.51	12,569.83	-7,166.93	1,011.52	407,703.07	843,821.52	32.1170854	-103.3563180	7,232.41	0.00	0.00	0.00
19,900.00	89.50	179.51	12,570.71	-7,266.92	1,012.38	407,603.08	843,822.38	32.1168106	-103.3563181	7,331.98	0.00	0.00	0.00
20,000.00	89.50	179.51	12,571.58	-7,366.91	1,013.24	407,503.09	843,823.24	32.1165357	-103.3563183	7,431.55	0.00	0.00	0.00
20,100.00	89.50	179.51	12,572.46	-7,466.91	1,014.10	407,403.09	843,824.10	32.1162609	-103.3563184	7,531.12	0.00	0.00	0.00
20,200.00	89.50	179.51	12,573.33	-7,566.90	1,014.96	407,303.10	843,824.96	32.1159860	-103.3563186	7,630.69	0.00	0.00	0.00
20,300.00	89.50	179.51	12,574.20	-7,666.89	1,015.82	407,203.11	843,825.82	32.1157112	-103.3563187	7,730.26	0.00	0.00	0.00
20,400.00	89.50	179.51	12,575.08	-7,766.88	1,016.68	407,103.12	843,826.68	32.1154363	-103.3563189	7,829.83	0.00	0.00	0.00
20,500.00	89.50	179.51	12,575.95	-7,866.88	1,017.55	407,003.12	843,827.54	32.1151614	-103.3563190	7,929.40	0.00	0.00	0.00
20,600.00	89.50	179.51	12,576.82	-7,966.87	1,018.41	406,903.13	843,828.41	32.1148866	-103.3563192	8,028.96	0.00	0.00	0.00
20,700.00	89.50	179.51	12,577.70	-8,066.86	1,019.27	406,803.14	843,829.27	32.1146117	-103.3563193	8,128.53	0.00	0.00	0.00
20,800.00	89.50	179.51	12,578.57	-8,166.85	1,020.13	406,703.15	843,830.13	32.1143369	-103.3563194	8,228.10	0.00	0.00	0.00
20,900.00	89.50	179.51	12,579.44	-8,266.85	1,020.99	406,603.15	843,830.99	32.1140620	-103.3563196	8,327.67	0.00	0.00	0.00
21,000.00	89.50	179.51	12,580.32	-8,366.84	1,021.85	406,503.16	843,831.85	32.1137872	-103.3563197	8,427.24	0.00	0.00	0.00
21,100.00	89.50	179.51	12,581.19	-8,466.83	1,022.71	406,403.17	843,832.71	32.1135123	-103.3563199	8,526.81	0.00	0.00	0.00
21,200.00	89.50	179.51	12,582.06	-8,566.82	1,023.57	406,303.18	843,833.57	32.1132375	-103.3563200	8,626.38	0.00	0.00	0.00
21,300.00	89.50	179.51	12,582.94	-8,666.82	1,024.43	406,203.18	843,834.43	32.1129626	-103.3563202	8,725.95	0.00	0.00	0.00
21,400.00	89.50	179.51	12,583.81	-8,766.81	1,025.30	406,103.19	843,835.30	32.1126877	-103.3563203	8,825.52	0.00	0.00	0.00
21,500.00	89.50	179.51	12,584.69	-8,866.80	1,026.16	406,003.20	843,836.16	32.1124129	-103.3563205	8,925.09	0.00	0.00	0.00
21,600.00	89.50	179.51	12,585.56	-8,966.79	1,027.02	405,903.21	843,837.02	32.1121380	-103.3563206	9,024.66	0.00	0.00	0.00
21,700.00	89.50	179.51	12,586.43	-9,066.79	1,027.88	405,803.21	843,837.88	32.1118632	-103.3563208	9,124.23	0.00	0.00	0.00
21,800.00	89.50	179.51	12,587.31	-9,166.78	1,028.74	405,703.22	843,838.74	32.1115883	-103.3563209	9,223.80	0.00	0.00	0.00
21,900.00	89.50	179.51	12,588.18	-9,266.77	1,029.60	405,603.23	843,839.60	32.1113135	-103.3563211	9,323.36	0.00	0.00	0.00
22,000.00	89.50	179.51	12,589.05	-9,366.76	1,030.46	405,503.24	843,840.46	32.1110386	-103.3563212	9,422.93	0.00	0.00	0.00
22,100.00	89.50	179.51	12,589.93	-9,466.76	1,031.32	405,403.24	843,841.32	32.1107637	-103.3563213	9,522.50	0.00	0.00	0.00
22,200.00	89.50	179.51	12,590.80	-9,566.75	1,032.18	405,303.25	843,842.18	32.1104889	-103.3563215	9,622.07	0.00	0.00	0.00
22,300.00	89.50	179.51	12,591.67	-9,666.74	1,033.05	405,203.26	843,843.05	32.1102140	-103.3563216	9,721.64	0.00	0.00	0.00
22,400.00	89.50	179.51	12,592.55	-9,766.73	1,033.91	405,103.27	843,843.91	32.1099392	-103.3563218	9,821.21	0.00	0.00	0.00
22,500.00	89.50	179.51	12,593.42	-9,866.73	1,034.77	405,003.27	843,844.77	32.1096643	-103.3563219	9,920.78	0.00	0.00	0.00
22,600.00	89.50	179.51	12,594.30	-9,966.72	1,035.63	404,903.28	843,845.63	32.1093895	-103.3563221	10,020.35	0.00	0.00	0.00
22,700.00	89.50	179.51	12,595.17	-10,066.71	1,036.49	404,803.29	843,846.49	32.1091146	-103.3563222	10,119.92	0.00	0.00	0.00
22,780.30	89.50	179.51	12,595.87	-10,147.00	1,037.18	404,723.00	843,847.18	32.1088939	-103.3563223	10,199.87	0.00	0.00	0.00
Junior Mint Fed 217H LTP													
22,800.00	89.50	179.51	12,596.04	-10,166.70	1,037.35	404,703.30	843,847.35	32.1088398	-103.3563224	10,219.49	0.00	0.00	0.00

Total Directional
Planned Survey Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Well:	Junior Mint Fed 217H	North Reference:	Grid
Wellbore:	OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan 1	Database:	.Total Directional Production DB

Planned Survey

Measured			Vertical	Local Coordinates		Map Coordinates		Geo Coordinates		Vertical Dogleg	Build	Turn
Depth	INC	AZI	Depth	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude	Section	Rate	Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)	(°)	(°)	(usft)	(°/100usft)	(°/100usft)
22,875.30	89.50	179.51	12,596.70	-10,242.00	1,038.00	404,628.00	843,848.00	32.1086328	-103.3563225	10,294.47	0.00	0.00
Junior Mint Fed 217H BHL												

Design Targets

Target Name

- hit/miss target	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting		
- Shape	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)	Latitude	Longitude
Junior Mint Fed 217H	0.00	0.00	11,937.00	208.00	948.00	415,078.00	843,758.00	32.1373574	-103.3563071
- plan misses target center by 49.07usft at 12048.42usft MD (11937.00 TVD, 257.07 N, 947.58 E)									
- Point									
Junior Mint Fed 217H	0.00	0.00	12,596.20	-10,147.00	1,037.00	404,723.00	843,847.00	32.1088939	-103.3563229
- plan misses target center by 0.38usft at 22780.30usft MD (12595.87 TVD, -10147.00 N, 1037.18 E)									
- Point									
Junior Mint Fed 217H	0.00	0.00	12,596.70	-10,242.00	1,038.00	404,628.00	843,848.00	32.1086328	-103.3563225
- plan hits target center									
- Point									

Checked By: _____

Approved By: _____

Date: _____

Civitas Resources

Lea County, NM (NAD 83)
Junior Mint Fed Pad
Junior Mint Fed 217H

OH
Plan 1



Anticollision Report

Minimum Magnetic Interference Warning level is 50' center to center

25 March, 2025

Total Report Version 1.60

COMPASS 5000.16 Build 97

Total Directional

Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Reference	Plan 1
Filter type:	NO GLOBAL FILTER: Using user defined selection & filtering criteria
Interpolation Method:	MD Interval 100.00usft
Depth Range:	Unlimited
Results Limited by:	Maximum centre distance of 2,518.44usft
Warning Levels Evaluated at:	2.00 Sigma
Error Model:	ISCWSA
Scan Method:	Closest Approach 3D
Error Surface:	Pedal Curve
Casing Method:	Not applied

Well	Junior Mint Fed 217H					
Well Position	+N/-S	0.00 usft	Northing:	414,870.00 usft	Latitude:	32.1368093
	+E/-W	0.00 usft	Easting:	842,810.00 usft	Longitude:	-103.3593755
Position Uncertainty		0.50 usft	Wellhead Elevation:	usft	Ground Level:	3,221.00 usft
Grid Convergence:		0.52 °				

Survey Tool Program		Date	3/24/2025	
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	22,875.30	Plan 1 (OH)	MWD+HRGM+SAG+FDIF	OWSG MWD + HRGM + SAG + FDIR Correction

Offset Listing								
Site Name	Ground LevelKB Height		Map Coordinates		Geographical Coordinates		Surface Uncertainty	
Offset Well			Northing	Easting	Latitude	Longitude	Site	Well
Civitas Resources - Junior Mint Fed Pad								
(O) Montera Federal 023H -	3,221.00	3,250.00	415,363.56	843,044.05	32.1381600	-103.3586050	0.00	0.00
Junior Mint Fed 131H -	3,221.00	3,247.00	414,635.00	842,835.00	32.1361627	-103.3593016	0.00	0.50
Junior Mint Fed 132H -	3,220.00	3,246.00	414,820.00	842,835.00	32.1366712	-103.3592962	0.00	0.50
Junior Mint Fed 133H -	3,223.00	3,249.00	415,726.00	845,129.00	32.1391042	-103.3518593	0.00	0.50
Junior Mint Fed 134H -	3,221.00	3,247.00	415,566.00	845,129.00	32.1386644	-103.3518640	0.00	0.50
Junior Mint Fed 135H -	3,220.00	3,246.00	414,660.00	842,835.00	32.1362315	-103.3593009	0.00	0.50
Junior Mint Fed 137H -	3,220.00	3,246.00	414,845.00	842,835.00	32.1367399	-103.3592955	0.00	0.50
Junior Mint Fed 138H -	3,220.00	3,246.00	415,541.00	845,129.00	32.1385957	-103.3518648	0.00	0.50
Junior Mint Fed 151H -	3,221.00	3,247.00	414,685.00	842,835.00	32.1363002	-103.3593001	0.00	0.50
Junior Mint Fed 152H -	3,220.00	3,246.00	414,870.00	842,835.00	32.1368087	-103.3592947	0.00	0.50
Junior Mint Fed 156H -	3,223.00	3,249.00	415,701.00	845,129.00	32.1390354	-103.3518600	0.00	0.50
Junior Mint Fed 211H -	3,221.00	3,247.00	414,660.00	842,810.00	32.1362321	-103.3593816	0.00	0.50
Junior Mint Fed 212H -	3,220.00	3,246.00	414,845.00	842,810.00	32.1367406	-103.3593762	0.00	0.50
Junior Mint Fed 213H -	3,222.00	3,248.00	415,701.00	845,154.00	32.1390348	-103.3517793	0.00	0.50
Junior Mint Fed 214H -	3,220.00	3,246.00	415,541.00	845,154.00	32.1385951	-103.3517840	0.00	0.50
Junior Mint Fed 215H -	3,220.00	3,246.00	414,685.00	842,810.00	32.1363008	-103.3593809	0.00	0.50
Junior Mint Fed 216H -	3,223.00	3,249.00	415,751.00	845,129.00	32.1391729	-103.3518586	0.00	0.50
Junior Mint Fed 221H -	3,221.00	3,247.00	414,635.00	842,810.00	32.1361634	-103.3593824	0.00	0.50
Junior Mint Fed 222H -	3,220.00	3,246.00	414,820.00	842,810.00	32.1366718	-103.3593769	0.00	0.50
Junior Mint Fed 223H -	3,223.00	3,249.00	415,751.00	845,154.00	32.1391723	-103.3517778	0.00	0.50
Junior Mint Fed 224H -	3,220.00	3,246.00	415,566.00	845,154.00	32.1386638	-103.3517833	0.00	0.50

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 2 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Summary

Site Name Offset Well - Wellbore - Design	Reference Measured Depth (usft)	Offset Measured Depth (usft)	Distance Between Centres (usft)	Between Ellipses (usft)	Separation Factor	Warning
Junior Mint Fed Pad						
(O) Montera Federal 023H - OH - OH	3,655.55	3,618.45	454.92	433.21	20.96	CC
(O) Montera Federal 023H - OH - OH	3,700.00	3,661.26	455.08	433.10	20.70	ES
(O) Montera Federal 023H - OH - OH	11,200.00	11,066.44	704.56	648.00	12.46	SF
Junior Mint Fed 131H - OH - Plan 1	1,934.10	1,937.15	229.56	218.71	21.16	CC, ES
Junior Mint Fed 131H - OH - Plan 1	22,875.30	22,485.80	1,793.50	1,518.44	6.52	SF
Junior Mint Fed 132H - OH - Plan 1	2,138.22	2,135.71	26.20	14.24	2.19	CC
Junior Mint Fed 132H - OH - Plan 1	2,200.00	2,197.41	26.38	14.19	2.16	ES
Junior Mint Fed 132H - OH - Plan 1	2,400.00	2,396.25	27.68	14.82	2.15	SF
Junior Mint Fed 133H - OH - Plan 1	11,809.52	11,757.65	968.31	933.75	28.02	CC
Junior Mint Fed 133H - OH - Plan 1	22,875.30	22,380.67	1,053.49	783.52	3.90	ES, SF
Junior Mint Fed 134H - OH - Plan 1	11,511.16	11,433.92	1,655.01	1,622.22	50.46	CC
Junior Mint Fed 134H - OH - Plan 1	22,875.30	22,335.05	1,728.10	1,445.08	6.11	ES, SF
Junior Mint Fed 135H - OH - Plan 1	2,067.73	2,077.71	137.83	126.37	12.03	CC, ES
Junior Mint Fed 135H - OH - Plan 1	22,875.30	22,411.61	1,158.00	891.52	4.35	SF
Junior Mint Fed 137H - OH - Plan 1	300.00	299.00	35.36	31.40	8.93	CC
Junior Mint Fed 137H - OH - Plan 1	400.00	398.51	36.03	31.36	7.71	ES
Junior Mint Fed 137H - OH - Plan 1	22,875.30	22,512.90	445.04	265.85	2.48	SF
Junior Mint Fed 138H - OH - Plan 1	5,765.48	5,378.24	2,140.63	2,113.57	79.11	CC
Junior Mint Fed 138H - OH - Plan 1	22,875.30	22,363.34	2,372.93	2,085.41	8.25	ES, SF
Junior Mint Fed 151H - OH - Plan 1	1,316.21	1,321.44	165.88	157.12	18.94	CC, ES
Junior Mint Fed 151H - OH - Plan 1	22,875.30	22,008.51	2,054.60	1,794.83	7.91	SF
Junior Mint Fed 152H - OH - Plan 1	300.00	299.00	25.00	21.04	6.32	CC, ES
Junior Mint Fed 152H - OH - Plan 1	500.00	497.75	29.42	24.04	5.47	SF
Junior Mint Fed 156H - OH - Plan 1	11,102.18	11,049.13	1,109.00	1,076.23	33.85	CC
Junior Mint Fed 156H - OH - Plan 1	11,200.00	11,146.51	1,109.01	1,076.13	33.73	ES
Junior Mint Fed 156H - OH - Plan 1	22,875.30	21,915.93	1,459.29	1,222.63	6.17	SF
Junior Mint Fed 211H - OH - Plan 1	1,123.58	1,127.70	195.73	187.69	24.34	CC, ES
Junior Mint Fed 211H - OH - Plan 1	22,875.30	22,894.71	2,027.10	1,746.06	7.21	SF
Junior Mint Fed 212H - OH - Plan 1	1,061.64	1,060.64	24.98	17.15	3.19	CC
Junior Mint Fed 212H - OH - Plan 1	1,100.00	1,098.98	25.01	17.02	3.13	ES
Junior Mint Fed 212H - OH - Plan 1	22,875.30	22,794.84	711.07	428.35	2.52	SF
Junior Mint Fed 213H - OH - Plan 1	11,914.36	11,917.41	615.00	579.43	17.29	CC
Junior Mint Fed 213H - OH - Plan 1	22,875.30	22,822.36	625.45	334.38	2.15	ES, SF
Junior Mint Fed 214H - OH - Plan 1	11,901.48	11,834.43	1,934.02	1,899.08	55.35	CC
Junior Mint Fed 214H - OH - Plan 1	22,875.30	22,702.95	1,943.81	1,652.52	6.67	ES, SF
Junior Mint Fed 215H - OH - Plan 1	1,365.32	1,373.26	141.86	132.82	15.69	CC, ES
Junior Mint Fed 215H - OH - Plan 1	22,875.30	22,805.11	1,320.06	1,039.14	4.70	SF
Junior Mint Fed 216H - OH - Plan 1	11,903.47	11,825.13	1,325.00	1,291.42	39.45	CC
Junior Mint Fed 216H - OH - Plan 1	22,875.30	22,713.70	1,335.03	1,041.20	4.54	ES, SF
Junior Mint Fed 221H - OH - Plan 1	1,649.36	1,657.61	201.13	191.16	20.17	CC
Junior Mint Fed 221H - OH - Plan 1	1,700.00	1,707.61	201.29	191.14	19.83	ES
Junior Mint Fed 221H - OH - Plan 1	22,875.30	23,188.08	1,735.81	1,460.04	6.29	SF
Junior Mint Fed 222H - OH - Plan 1	1,095.46	1,094.44	49.97	42.00	6.27	CC
Junior Mint Fed 222H - OH - Plan 1	1,200.00	1,198.88	50.18	41.81	6.00	ES
Junior Mint Fed 222H - OH - Plan 1	22,875.30	23,180.03	516.35	291.26	2.29	SF
Junior Mint Fed 223H - OH - Plan 1	12,053.96	12,018.29	843.99	808.62	23.86	CC
Junior Mint Fed 223H - OH - Plan 1	22,875.30	23,128.47	981.76	696.16	3.44	ES, SF
Junior Mint Fed 224H - OH - Plan 1	5,881.13	5,553.34	2,066.06	2,038.59	75.19	CC
Junior Mint Fed 224H - OH - Plan 1	22,875.30	23,060.36	2,277.75	1,987.14	7.84	ES, SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 3 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - (O) Monter Federal 023H - OH - OH

Offset Site Error: 0.00 usft

Offset Well Error: 0.00 usft

Survey Program: 100-3_Gyro-NS-CT_OWGS, 11638-3_MWD						Rule Assigned:					Offset Well Error:		0.00 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
0.00	0.00	3.07	0.07	0.50	0.00	25.37	493.56	234.06	546.24				
100.00	100.00	105.42	102.42	0.98	0.14	25.37	493.34	233.96	546.01	544.88	1.12	485.497	
200.00	200.00	205.28	202.28	1.56	0.49	25.38	492.98	233.86	545.65	543.59	2.05	265.568	
300.00	300.00	306.35	303.35	1.98	0.85	25.38	492.52	233.65	545.14	542.31	2.83	192.692	
400.00	400.00	406.83	403.82	2.33	1.20	25.38	491.91	233.32	544.45	540.92	3.53	154.255	
500.00	500.00	507.56	504.55	2.63	1.55	25.32	491.46	232.55	543.73	539.54	4.19	129.846	
600.00	600.00	608.10	605.08	2.91	1.91	25.22	491.05	231.29	542.82	538.00	4.82	112.732	
700.00	700.00	707.32	704.29	3.16	2.25	25.12	490.63	230.08	541.91	536.49	5.42	100.050	
800.00	800.00	803.64	800.60	3.40	2.59	25.03	490.65	229.07	541.49	535.50	5.99	90.400	
810.16	810.16	813.19	810.16	3.42	2.62	25.01	490.69	228.97	541.48	535.43	6.05	89.563	
900.00	900.00	900.58	897.54	3.62	2.93	24.91	491.36	228.19	541.77	535.22	6.55	82.708	
1,000.00	1,000.00	1,000.34	997.29	3.76	3.28	-67.20	492.18	227.51	542.21	535.17	7.03	77.088	
1,100.00	1,099.98	1,101.54	1,098.49	4.00	3.63	-67.49	492.94	226.75	541.87	534.28	7.58	71.447	
1,200.00	1,199.88	1,201.76	1,198.71	4.24	3.98	-68.06	493.64	225.86	540.46	532.33	8.12	66.518	
1,300.00	1,299.63	1,302.04	1,298.98	4.46	4.33	-68.91	494.20	224.89	537.99	529.33	8.66	62.114	
1,400.00	1,399.25	1,400.69	1,397.62	4.60	4.68	-69.88	494.84	224.13	535.22	526.08	9.14	58.577	
1,500.00	1,498.87	1,500.00	1,496.93	4.78	5.02	-70.84	495.43	223.46	532.59	522.93	9.66	55.134	
1,600.00	1,598.49	1,599.11	1,596.03	4.96	5.37	-71.80	496.04	222.96	530.18	520.00	10.18	52.082	
1,700.00	1,698.11	1,697.70	1,694.62	5.14	5.72	-72.74	496.79	222.68	528.14	517.44	10.70	49.379	
1,800.00	1,797.73	1,796.84	1,793.76	5.32	6.06	-73.67	497.58	222.68	526.37	515.16	11.21	46.949	
1,900.00	1,897.34	1,896.13	1,893.04	5.49	6.41	-74.58	498.34	222.82	524.75	513.02	11.73	44.749	
2,000.00	1,996.96	1,995.83	1,992.74	5.67	6.75	-75.49	499.08	223.20	523.32	511.08	12.24	42.750	
2,100.00	2,096.58	2,094.92	2,091.83	5.85	7.10	-76.38	499.78	223.68	522.00	509.25	12.75	40.932	
2,200.00	2,196.20	2,195.31	2,192.21	6.04	7.45	-77.28	500.47	224.20	520.81	507.53	13.28	39.232	
2,300.00	2,295.72	2,293.67	2,290.57	6.23	7.79	-71.96	501.09	225.13	519.01	505.23	13.78	37.661	
2,400.00	2,394.97	2,392.07	2,388.96	6.43	8.14	-68.90	501.82	226.39	515.88	501.58	14.30	36.070	
2,500.00	2,493.89	2,490.04	2,486.91	6.64	8.48	-67.38	502.72	227.99	511.58	496.75	14.83	34.495	
2,600.00	2,592.40	2,586.16	2,583.00	6.85	8.82	-66.84	503.94	230.06	506.47	491.11	15.36	32.971	
2,700.00	2,690.45	2,682.40	2,679.20	7.07	9.16	-67.06	505.58	232.45	500.71	484.81	15.90	31.484	
2,800.00	2,787.96	2,800.00	2,796.74	7.28	9.57	-68.39	507.21	235.42	494.04	477.51	16.53	29.883	
2,900.00	2,884.87	2,873.94	2,870.63	7.49	9.83	-69.28	508.41	237.54	486.41	469.39	17.02	28.572	
3,000.00	2,981.46	2,970.99	2,967.59	7.68	10.18	-71.73	511.19	240.75	480.57	462.96	17.61	27.287	
3,100.00	3,078.05	3,078.51	3,075.01	7.87	10.56	-74.47	513.09	244.71	474.60	456.35	18.25	26.004	
3,200.00	3,174.64	3,175.00	3,171.43	8.06	10.90	-76.98	513.93	248.30	468.70	449.85	18.86	24.855	
3,300.00	3,271.24	3,271.78	3,268.14	8.26	11.24	-79.56	514.98	251.90	464.01	444.54	19.47	23.827	
3,400.00	3,367.83	3,373.40	3,369.71	8.51	11.60	-82.43	515.59	254.74	460.01	439.90	20.11	22.873	
3,500.00	3,464.42	3,469.22	3,465.52	8.80	11.94	-85.33	515.65	256.30	456.89	436.15	20.73	22.037	
3,600.00	3,561.01	3,565.47	3,561.76	9.09	12.27	-88.35	515.65	257.21	455.17	433.82	21.36	21.312	
3,655.55	3,614.66	3,618.45	3,614.74	9.25	12.46	-90.04	515.70	257.52	454.92	433.21	21.70	20.960	CC
3,700.00	3,657.60	3,661.26	3,657.55	9.38	12.61	-91.41	515.78	257.75	455.08	433.10	21.98	20.703	ES
3,800.00	3,754.20	3,758.99	3,755.28	9.68	12.95	-94.54	515.84	258.10	456.39	433.78	22.61	20.184	
3,900.00	3,850.79	3,855.37	3,851.66	9.98	13.28	-97.57	515.94	258.78	459.01	435.77	23.23	19.756	
4,000.00	3,947.38	3,962.11	3,958.34	10.28	13.66	-100.60	516.07	262.06	461.93	438.03	23.89	19.332	
4,100.00	4,043.97	4,066.00	4,062.04	10.59	14.03	-103.22	515.71	268.32	464.07	439.53	24.54	18.907	
4,200.00	4,140.56	4,176.10	4,171.85	10.90	14.43	-105.90	514.44	276.28	465.87	440.67	25.20	18.488	
4,300.00	4,237.16	4,276.93	4,272.32	11.21	14.79	-108.52	510.36	283.60	466.10	440.28	25.82	18.052	
4,400.00	4,333.75	4,362.82	4,358.00	11.52	15.09	-111.18	505.22	286.56	468.19	441.79	26.40	17.735	
4,500.00	4,430.34	4,437.31	4,432.35	11.84	15.35	-113.78	501.21	285.20	475.42	448.51	26.91	17.667	
4,600.00	4,526.93	4,511.70	4,506.64	12.16	15.62	-116.28	499.92	281.62	488.75	461.39	27.36	17.862	
4,700.00	4,623.53	4,599.15	4,593.96	12.48	15.93	-118.72	502.55	277.67	506.41	478.55	27.87	18.173	
4,800.00	4,720.12	4,749.53	4,744.04	12.80	16.47	-121.69	508.75	281.90	520.41	491.67	28.74	18.109	
4,900.00	4,816.71	4,868.72	4,862.59	13.12	16.92	-123.62	509.88	293.96	527.29	497.90	29.39	17.940	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - (O) Monter Federal 023H - OH - OH

Offset Site Error: 0.00 usft

Offset Well Error: 0.00 usft

Survey Program: 100-3_Gyro-NS-CT_OWSG, 11638-3_MWD												Rule Assigned:			
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
5,000.00	4,913.30	4,958.85	4,952.40	13.45	17.25	-125.53	506.64	300.70	534.08	504.13	29.95	17.834			
5,100.00	5,009.89	5,040.96	5,034.36	13.78	17.54	-127.45	503.06	304.29	543.68	513.22	30.46	17.850			
5,200.00	5,106.49	5,127.92	5,121.22	14.10	17.84	-129.52	499.52	305.84	556.37	525.41	30.96	17.969			
5,300.00	5,203.08	5,210.14	5,203.40	14.43	18.12	-131.43	496.89	305.34	572.33	540.90	31.43	18.209			
5,400.00	5,299.67	5,294.13	5,287.35	14.75	18.42	-133.28	495.50	303.24	591.42	559.54	31.88	18.550			
5,500.00	5,396.65	5,389.78	5,382.96	15.07	18.76	-135.31	494.62	300.52	610.85	578.44	32.41	18.848			
5,600.00	5,494.23	5,486.69	5,479.82	15.36	19.10	-137.06	493.82	297.73	629.04	596.10	32.94	19.099			
5,700.00	5,592.35	5,586.92	5,580.01	15.62	19.46	-138.57	493.04	295.06	645.57	612.10	33.48	19.285			
5,800.00	5,690.94	5,688.17	5,681.24	15.86	19.81	-139.83	492.28	292.92	659.96	625.95	34.01	19.403			
5,900.00	5,789.93	5,788.64	5,781.69	16.07	20.16	-140.85	491.55	291.18	672.22	637.68	34.54	19.463			
6,000.00	5,889.26	5,888.57	5,881.60	16.25	20.51	-141.66	490.85	289.61	682.44	647.39	35.05	19.470			
6,100.00	5,988.86	5,988.15	5,981.17	16.41	20.86	-142.29	490.21	288.13	690.65	655.10	35.55	19.426			
6,200.00	6,088.66	6,089.39	6,082.41	16.53	21.22	-142.75	489.64	286.67	696.84	660.78	36.05	19.327			
6,300.00	6,188.59	6,189.76	6,182.76	16.64	21.57	-143.08	488.64	285.48	700.58	664.04	36.54	19.174			
6,400.00	6,288.58	6,292.31	6,285.29	16.71	21.93	-70.84	487.53	284.39	702.10	665.12	36.98	18.988			
6,500.00	6,388.58	6,392.25	6,385.23	16.76	22.27	-70.94	486.46	283.61	702.49	665.11	37.38	18.794			
6,600.00	6,488.58	6,493.05	6,486.02	16.82	22.62	-71.03	485.57	282.88	702.88	665.10	37.79	18.601			
6,700.00	6,588.58	6,593.11	6,586.08	16.88	22.97	-71.10	484.80	282.28	703.20	665.01	38.19	18.412			
6,800.00	6,688.58	6,693.92	6,686.88	16.94	23.32	-71.17	484.06	281.78	703.44	664.84	38.60	18.223			
6,900.00	6,788.58	6,793.84	6,786.80	17.00	23.67	-71.25	483.30	281.22	703.71	664.71	39.01	18.041			
7,000.00	6,888.58	6,895.19	6,888.14	17.05	24.02	-71.31	482.61	280.75	703.94	664.52	39.42	17.858			
7,100.00	6,988.58	6,996.35	6,989.31	17.11	24.37	-71.37	482.00	280.52	703.96	664.13	39.83	17.674			
7,115.74	7,004.32	7,011.36	7,004.32	17.12	24.42	-71.37	481.92	280.50	703.95	664.06	39.89	17.647			
7,200.00	7,088.58	7,096.61	7,089.56	17.17	24.72	-71.41	481.47	280.34	703.97	663.73	40.24	17.495			
7,300.00	7,188.58	7,197.27	7,190.22	17.23	25.07	-71.47	480.79	280.18	703.90	663.25	40.65	17.317			
7,400.00	7,288.58	7,298.01	7,290.95	17.29	25.42	-71.52	480.16	280.22	703.66	662.61	41.06	17.138			
7,500.00	7,388.58	7,397.16	7,390.11	17.35	25.76	-71.55	479.72	280.32	703.43	661.97	41.46	16.967			
7,600.00	7,488.58	7,499.30	7,492.25	17.41	26.12	-71.56	479.43	280.55	703.13	661.25	41.88	16.790			
7,700.00	7,588.58	7,596.57	7,589.52	17.47	26.45	-71.57	479.29	280.86	702.78	660.51	42.27	16.625			
7,800.00	7,688.58	7,697.80	7,690.74	17.53	26.80	-71.56	479.27	281.11	702.54	659.85	42.69	16.458			
7,900.00	7,788.58	7,798.05	7,790.99	17.59	27.15	-71.54	479.40	281.44	702.27	659.17	43.10	16.295			
8,000.00	7,888.58	7,896.66	7,889.60	17.65	27.50	-71.49	479.91	281.90	701.99	658.49	43.50	16.137			
8,100.00	7,988.58	7,999.06	7,992.00	17.71	27.85	-71.44	480.39	282.36	701.71	657.79	43.92	15.975			
8,200.00	8,088.58	8,099.02	8,091.96	17.77	28.20	-71.37	481.12	283.08	701.26	656.92	44.34	15.816			
8,300.00	8,188.58	8,198.70	8,191.63	17.83	28.55	-71.29	481.85	283.83	700.79	656.04	44.75	15.660			
8,400.00	8,288.58	8,299.06	8,291.98	17.89	28.90	-71.21	482.65	284.59	700.32	655.16	45.16	15.506			
8,500.00	8,388.58	8,400.21	8,393.13	17.95	29.25	-71.11	483.57	285.47	699.80	654.21	45.58	15.352			
8,600.00	8,488.58	8,499.10	8,492.00	18.02	29.60	-71.02	484.53	286.36	699.26	653.26	45.99	15.203			
8,700.00	8,588.58	8,600.00	8,592.89	18.08	29.95	-70.91	485.60	287.37	698.66	652.25	46.41	15.053			
8,800.00	8,688.58	8,699.33	8,692.22	18.14	30.30	-70.81	486.49	288.36	698.01	651.19	46.83	14.907			
8,900.00	8,788.58	8,800.00	8,792.88	18.20	30.65	-70.73	487.20	289.31	697.36	650.11	47.24	14.761			
9,000.00	8,888.58	8,901.57	8,894.43	18.26	31.00	-70.62	488.21	290.38	696.69	649.02	47.67	14.616			
9,100.00	8,988.58	9,008.42	9,001.27	18.32	31.38	-70.51	489.02	292.11	695.41	647.30	48.11	14.455			
9,200.00	9,088.58	9,116.67	9,109.48	18.39	31.76	-70.43	489.09	294.94	692.98	644.42	48.55	14.272			
9,300.00	9,188.58	9,216.03	9,208.80	18.45	32.11	-70.36	488.88	297.94	690.06	641.09	48.97	14.092			
9,400.00	9,288.58	9,315.96	9,308.68	18.51	32.47	-70.31	488.52	300.87	687.17	637.79	49.38	13.916			
9,500.00	9,388.58	9,416.39	9,409.07	18.57	32.82	-70.28	487.88	303.79	684.22	634.43	49.79	13.741			
9,600.00	9,488.58	9,511.72	9,504.37	18.64	33.15	-70.32	486.60	305.94	681.64	631.45	50.19	13.582			
9,697.30	9,585.88	9,593.26	9,585.88	18.70	33.44	-70.44	484.91	306.32	680.53	630.01	50.52	13.470			
9,700.00	9,588.58	9,595.56	9,588.18	18.70	33.45	-70.44	484.87	306.30	680.54	630.00	50.53	13.468			
9,800.00	9,688.58	9,693.16	9,685.76	18.76	33.79	-70.63	482.86	305.29	680.83	629.90	50.93	13.368			
9,900.00	9,788.58	9,792.21	9,784.78	18.83	34.13	-70.82	480.85	304.10	681.29	629.96	51.33	13.272			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 5 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - (O) Monter Federal 023H - OH - OH

Offset Site Error: 0.00 usft

Offset Well Error: 0.00 usft

Survey Program: 100-3_Gyro-NS-CT_OWSG, 11638-3_MWD												Rule Assigned:			
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
10,000.00	9,888.58	9,891.51	9,884.04	18.89	34.48	-71.03	478.69	302.68	681.93	630.19	51.74	13.180			
10,100.00	9,988.58	9,990.62	9,983.11	18.95	34.83	-71.28	476.23	301.03	682.70	630.56	52.14	13.093			
10,200.00	10,088.58	10,086.07	10,078.52	19.02	35.17	-71.51	473.91	299.24	683.71	631.18	52.53	13.016			
10,300.00	10,188.58	10,181.72	10,174.12	19.08	35.50	-71.70	472.27	296.85	685.54	632.62	52.92	12.954			
10,400.00	10,288.58	10,280.17	10,272.53	19.15	35.85	-71.83	471.46	294.19	687.85	634.53	53.32	12.900			
10,500.00	10,388.58	10,382.42	10,374.75	19.21	36.21	-71.95	470.79	291.69	689.97	636.23	53.74	12.838			
10,600.00	10,488.58	10,485.34	10,477.65	19.27	36.58	-72.04	470.39	289.62	691.76	637.59	54.17	12.771			
10,700.00	10,588.58	10,585.61	10,577.91	19.34	36.93	-72.05	470.68	288.18	693.22	638.63	54.58	12.700			
10,800.00	10,688.58	10,683.28	10,675.56	19.40	37.27	-72.05	471.21	286.68	694.85	639.86	54.99	12.637			
10,900.00	10,788.58	10,781.81	10,774.07	19.47	37.61	-72.09	471.37	284.59	696.91	641.52	55.39	12.582			
11,000.00	10,888.58	10,881.31	10,873.55	19.53	37.96	-72.13	471.46	282.45	698.99	643.19	55.80	12.526			
11,100.00	10,988.58	10,978.15	10,970.35	19.60	38.31	-72.18	471.59	280.12	701.32	645.12	56.20	12.479			
11,200.00	11,088.58	11,066.44	11,058.60	19.66	38.62	-72.22	471.98	277.26	704.56	648.00	56.56	12.456	SF		
11,300.00	11,188.58	11,150.00	11,142.03	19.73	38.92	-72.20	473.59	273.03	709.98	653.08	56.90	12.478			
11,400.00	11,288.58	11,238.17	11,229.92	19.79	39.23	-72.03	477.73	267.37	717.51	660.25	57.26	12.530			
11,500.00	11,388.58	11,351.23	11,342.59	19.86	39.63	-71.72	484.05	260.56	725.00	667.25	57.75	12.554			
11,600.00	11,488.58	11,451.38	11,442.49	19.92	39.98	-71.45	489.32	255.64	731.33	673.15	58.18	12.570			
11,700.00	11,588.58	11,554.30	11,545.15	19.99	40.34	-71.17	494.73	250.76	737.51	678.89	58.62	12.581			
11,800.00	11,688.58	11,665.40	11,656.06	20.05	40.54	-70.93	499.45	246.29	742.71	683.81	58.90	12.611			
11,900.00	11,788.58	11,778.40	11,768.95	20.12	40.55	-70.71	503.46	243.58	746.13	687.15	58.98	12.650			
12,000.00	11,888.58	11,873.92	11,864.22	20.19	40.56	-70.24	510.02	243.60	748.44	689.37	59.07	12.670			
12,100.00	11,988.51	11,935.29	11,924.64	20.25	40.56	110.70	520.51	243.93	754.89	695.79	59.10	12.773			
12,200.00	12,086.82	11,992.00	11,978.79	20.31	40.58	110.87	537.26	243.95	772.71	713.60	59.11	13.073			
12,300.00	12,180.57	12,040.84	12,023.93	20.35	40.59	110.25	555.89	244.11	802.99	743.90	59.09	13.589			
12,400.00	12,266.93	12,069.85	12,049.88	20.39	40.59	107.46	568.83	244.44	846.22	787.18	59.03	14.335			
12,500.00	12,343.26	12,086.00	12,063.95	20.44	40.60	102.15	576.75	244.54	901.69	842.73	58.97	15.292			
12,600.00	12,407.24	12,086.00	12,063.95	20.52	40.60	93.65	576.75	244.54	966.76	907.87	58.89	16.415			
12,700.00	12,456.94	12,086.00	12,063.95	20.67	40.60	83.47	576.75	244.54	1,038.13	979.27	58.87	17.635			
12,800.00	12,490.84	12,086.00	12,063.95	20.88	40.60	72.56	576.75	244.54	1,112.64	1,053.76	58.87	18.899			
12,900.00	12,507.91	12,073.72	12,053.28	21.18	40.60	61.41	570.68	244.47	1,187.43	1,128.55	58.88	20.168			
13,000.00	12,510.43	12,055.00	12,036.69	21.56	40.59	56.40	562.01	244.27	1,261.17	1,202.29	58.87	21.422			
13,100.00	12,511.30	12,055.00	12,036.69	22.01	40.59	56.40	562.01	244.27	1,337.34	1,278.43	58.91	22.701			
13,200.00	12,512.18	12,023.00	12,007.61	22.52	40.58	54.79	548.67	244.00	1,416.09	1,357.15	58.94	24.027			
13,300.00	12,513.05	12,023.00	12,007.61	23.10	40.58	54.79	548.67	244.00	1,496.87	1,437.88	58.99	25.374			
13,400.00	12,513.92	12,008.51	11,994.20	23.73	40.58	54.06	543.17	243.97	1,579.65	1,520.60	59.05	26.752			
13,500.00	12,514.80	11,992.00	11,978.79	24.41	40.58	53.25	537.26	243.95	1,664.09	1,604.97	59.12	28.150			
13,600.00	12,515.67	11,992.00	11,978.79	25.15	40.58	53.25	537.26	243.95	1,749.93	1,690.75	59.18	29.570			
13,700.00	12,516.55	11,979.35	11,966.87	25.93	40.57	52.63	533.01	243.95	1,837.03	1,777.78	59.25	31.003			
13,800.00	12,517.42	11,960.00	11,948.47	26.76	40.57	51.69	527.05	243.95	1,925.44	1,866.10	59.34	32.447			
13,900.00	12,518.29	11,960.00	11,948.47	27.63	40.57	51.69	527.05	243.95	2,014.55	1,955.14	59.41	33.908			
14,000.00	12,519.17	11,960.00	11,948.47	28.53	40.57	51.69	527.05	243.95	2,104.64	2,045.15	59.48	35.383			
14,100.00	12,520.04	11,960.00	11,948.47	29.47	40.57	51.69	527.05	243.95	2,195.58	2,136.03	59.55	36.868			
14,200.00	12,520.91	11,960.00	11,948.47	30.44	40.57	51.69	527.05	243.95	2,287.28	2,227.66	59.62	38.361			
14,300.00	12,521.79	11,945.19	11,934.23	31.44	40.57	50.98	522.98	243.94	2,379.38	2,319.66	59.72	39.841			
14,400.00	12,522.66	11,929.00	11,918.52	32.46	40.56	50.21	519.06	243.91	2,472.36	2,412.53	59.83	41.326			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 6 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 131H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Separation		Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	
0.00	0.00	0.00	0.00	0.50	0.50	173.93	-235.00	25.00	236.33				
100.00	100.00	100.00	100.00	0.98	0.98	173.93	-235.00	25.00	236.33	234.36	1.96	120.440	
200.00	200.00	200.00	200.00	1.56	1.56	173.93	-235.00	25.00	236.33	233.20	3.12	75.691	
300.00	300.00	300.00	300.00	1.98	1.98	173.93	-235.00	25.00	236.33	232.36	3.96	59.643	
400.00	400.00	400.00	400.00	2.33	2.33	173.93	-235.00	25.00	236.33	231.67	4.66	50.726	
500.00	500.00	500.00	500.00	2.63	2.63	173.93	-235.00	25.00	236.33	231.06	5.27	44.852	
600.00	600.00	600.00	600.00	2.91	2.91	173.93	-235.00	25.00	236.33	230.51	5.82	40.605	
700.00	700.00	700.00	700.00	3.16	3.16	173.93	-235.00	25.00	236.33	230.00	6.33	37.348	
800.00	800.00	800.00	800.00	3.40	3.40	173.93	-235.00	25.00	236.33	229.52	6.80	34.748	
900.00	900.00	900.00	900.00	3.62	3.62	173.93	-235.00	25.00	236.33	229.08	7.25	32.608	
1,000.00	1,000.00	1,000.00	1,000.00	3.76	3.84	81.94	-235.00	25.00	236.32	228.72	7.60	31.113	
1,100.00	1,099.98	1,099.98	1,099.98	4.00	4.04	82.38	-235.00	25.00	236.07	228.08	7.99	29.549	
1,200.00	1,199.88	1,199.88	1,199.88	4.24	4.23	83.46	-235.00	25.00	235.52	227.15	8.37	28.146	
1,300.00	1,299.63	1,299.63	1,299.63	4.46	4.42	85.18	-235.00	25.00	234.82	226.09	8.73	26.884	
1,400.00	1,399.25	1,399.25	1,399.25	4.60	4.60	87.29	-235.00	25.00	234.25	225.20	9.05	25.893	
1,500.00	1,498.87	1,500.83	1,500.83	4.78	4.77	89.65	-234.56	24.23	233.58	224.18	9.40	24.856	
1,600.00	1,598.49	1,602.09	1,602.05	4.96	4.94	92.40	-233.21	21.92	232.53	222.79	9.74	23.882	
1,700.00	1,698.11	1,702.95	1,702.81	5.14	5.10	95.57	-230.99	18.07	231.32	221.25	10.07	22.968	
1,800.00	1,797.73	1,803.34	1,803.01	5.32	5.27	99.15	-227.89	12.72	230.25	219.84	10.40	22.130	
1,900.00	1,897.34	1,903.22	1,902.57	5.49	5.43	103.15	-223.94	5.89	229.61	218.88	10.74	21.387	
1,934.10	1,931.32	1,937.15	1,936.36	5.56	5.49	104.60	-222.39	3.23	229.56	218.71	10.85	21.160	CC, ES
2,000.00	1,996.96	2,002.52	2,001.41	5.67	5.60	107.54	-219.14	-2.39	229.78	218.71	11.07	20.760	
2,100.00	2,096.58	2,101.19	2,099.44	5.85	5.76	112.29	-213.53	-12.09	231.14	219.73	11.40	20.268	
2,200.00	2,196.20	2,199.17	2,196.58	6.04	5.93	117.32	-207.12	-23.16	234.07	222.32	11.75	19.919	
2,300.00	2,295.72	2,296.22	2,292.57	6.23	6.09	128.91	-199.95	-35.54	240.01	227.91	12.10	19.834	
2,400.00	2,394.97	2,391.97	2,387.03	6.43	6.26	138.66	-192.09	-49.13	250.73	238.25	12.48	20.094	
2,500.00	2,493.89	2,486.26	2,479.76	6.64	6.43	147.02	-183.57	-63.85	266.67	253.81	12.87	20.726	
2,600.00	2,592.40	2,578.91	2,570.61	6.85	6.59	154.30	-174.45	-79.60	288.03	274.77	13.26	21.723	
2,700.00	2,690.45	2,669.79	2,659.43	7.07	6.77	160.63	-164.79	-96.28	314.77	301.12	13.65	23.061	
2,800.00	2,787.96	2,759.81	2,747.10	7.28	6.91	166.13	-154.59	-113.91	346.62	332.61	14.00	24.752	
2,900.00	2,884.87	2,850.29	2,835.17	7.49	7.09	170.80	-144.19	-131.86	382.69	368.31	14.38	26.614	
3,000.00	2,981.46	2,940.31	2,922.79	7.68	7.29	173.88	-133.85	-149.73	421.15	406.41	14.74	28.570	
3,100.00	3,078.05	3,030.33	3,010.42	7.87	7.50	176.46	-123.51	-167.59	460.52	445.42	15.10	30.491	
3,200.00	3,174.64	3,120.35	3,098.04	8.06	7.71	178.64	-113.17	-185.45	500.58	485.12	15.47	32.363	
3,300.00	3,271.24	3,210.37	3,185.66	8.26	7.93	-179.49	-102.83	-203.31	541.19	525.35	15.83	34.177	
3,400.00	3,367.83	3,300.39	3,273.28	8.51	8.15	-177.88	-92.49	-221.18	582.21	566.01	16.20	35.929	
3,500.00	3,464.42	3,390.41	3,360.91	8.80	8.37	-176.47	-82.15	-239.04	623.58	607.01	16.58	37.616	
3,600.00	3,561.01	3,480.43	3,448.53	9.09	8.60	-175.24	-71.81	-256.90	665.23	648.28	16.95	39.237	
3,700.00	3,657.60	3,570.45	3,536.15	9.38	8.83	-174.15	-61.47	-274.76	707.11	689.77	17.33	40.793	
3,800.00	3,754.20	3,660.47	3,623.77	9.68	9.07	-173.18	-51.13	-292.63	749.17	731.46	17.72	42.285	
3,900.00	3,850.79	3,750.49	3,711.39	9.98	9.30	-172.31	-40.79	-310.49	791.40	773.30	18.10	43.716	
4,000.00	3,947.38	3,840.51	3,799.02	10.28	9.54	-171.53	-30.45	-328.35	833.76	815.27	18.49	45.086	
4,100.00	4,043.97	3,930.53	3,886.64	10.59	9.78	-170.83	-20.10	-346.21	876.24	857.36	18.88	46.400	
4,200.00	4,140.56	4,020.55	3,974.26	10.90	10.03	-170.19	-9.76	-364.08	918.82	899.54	19.28	47.658	
4,300.00	4,237.16	4,110.57	4,061.88	11.21	10.27	-169.60	0.58	-381.94	961.48	941.81	19.68	48.863	
4,400.00	4,333.75	4,200.59	4,149.51	11.52	10.52	-169.07	10.92	-399.80	1,004.23	984.15	20.08	50.018	
4,500.00	4,430.34	4,290.61	4,237.13	11.84	10.77	-168.57	21.26	-417.66	1,047.03	1,026.55	20.48	51.124	
4,600.00	4,526.93	4,380.63	4,324.75	12.16	11.02	-168.12	31.60	-435.53	1,089.90	1,069.01	20.89	52.185	
4,700.00	4,623.53	4,470.66	4,412.37	12.48	11.27	-167.70	41.94	-453.39	1,132.82	1,111.53	21.29	53.203	
4,800.00	4,720.12	4,560.68	4,500.00	12.80	11.53	-167.31	52.28	-471.25	1,175.78	1,154.08	21.70	54.179	
4,900.00	4,816.71	4,650.70	4,587.62	13.12	11.78	-166.95	62.62	-489.12	1,218.79	1,196.67	22.11	55.116	
5,000.00	4,913.30	4,740.72	4,675.24	13.45	12.04	-166.61	72.96	-506.98	1,261.83	1,239.30	22.53	56.015	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 7 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 131H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Reference (usft)	Major Axis Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
5,100.00	5,009.89	4,830.74	4,762.86	13.78	12.30	-166.30	83.30	-524.84	1,304.91	1,281.96	22.94	56.879					
5,200.00	5,106.49	4,920.76	4,850.49	14.10	12.55	-166.00	93.64	-542.70	1,348.01	1,324.65	23.36	57.708					
5,300.00	5,203.08	5,010.78	4,938.11	14.43	12.81	-165.73	103.98	-560.57	1,391.15	1,367.37	23.78	58.506					
5,400.00	5,299.67	5,100.80	5,025.73	14.75	13.07	-165.48	114.32	-578.43	1,434.30	1,410.11	24.19	59.295					
5,500.00	5,396.65	5,191.43	5,113.94	15.07	13.34	-165.39	124.73	-596.41	1,476.13	1,451.51	24.62	59.954					
5,600.00	5,494.23	5,283.03	5,203.11	15.36	13.60	-165.28	135.26	-614.59	1,515.68	1,490.63	25.05	60.504					
5,700.00	5,592.35	5,375.56	5,293.17	15.62	13.87	-165.15	145.89	-632.95	1,552.93	1,527.45	25.48	60.949					
5,800.00	5,690.94	5,468.94	5,384.06	15.86	14.15	-164.99	156.61	-651.48	1,587.84	1,561.94	25.90	61.296					
5,900.00	5,789.93	5,563.11	5,475.73	16.07	14.41	-164.81	167.43	-670.17	1,620.42	1,594.11	26.31	61.580					
6,000.00	5,889.26	5,685.19	5,594.79	16.25	14.75	-164.54	180.93	-693.48	1,649.96	1,623.13	26.83	61.492					
6,100.00	5,988.86	5,813.14	5,720.17	16.41	15.09	-164.27	193.71	-715.56	1,675.32	1,647.96	27.36	61.228					
6,200.00	6,088.66	5,943.22	5,848.19	16.53	15.41	-164.01	205.26	-735.52	1,696.41	1,668.55	27.87	60.872					
6,300.00	6,188.59	6,075.08	5,978.46	16.64	15.70	-163.76	215.49	-753.18	1,713.15	1,684.81	28.35	60.437					
6,400.00	6,288.58	6,208.35	6,110.56	16.71	15.96	-91.09	224.29	-768.39	1,725.49	1,696.76	28.73	60.054					
6,500.00	6,388.58	6,342.54	6,243.95	16.76	16.20	-90.84	231.60	-781.01	1,734.82	1,705.75	29.07	59.678					
6,600.00	6,488.58	6,477.34	6,378.25	16.82	16.40	-90.65	237.36	-790.97	1,742.16	1,712.77	29.39	59.284					
6,700.00	6,588.58	6,612.61	6,513.26	16.88	16.57	-90.51	241.55	-798.21	1,747.48	1,717.80	29.68	58.876					
6,800.00	6,688.58	6,748.20	6,648.75	16.94	16.71	-90.42	244.15	-802.69	1,750.77	1,720.83	29.94	58.469					
6,900.00	6,788.58	6,883.96	6,784.49	17.00	16.82	-90.39	245.14	-804.40	1,752.03	1,721.87	30.16	58.092					
7,000.00	6,888.58	6,988.04	6,888.58	17.05	16.89	-90.39	245.15	-804.42	1,752.04	1,721.75	30.29	57.838					
7,100.00	6,988.58	7,088.04	6,988.58	17.11	16.95	-90.39	245.15	-804.42	1,752.04	1,721.62	30.42	57.601					
7,200.00	7,088.58	7,188.04	7,088.58	17.17	17.02	-90.39	245.15	-804.42	1,752.04	1,721.50	30.54	57.365					
7,300.00	7,188.58	7,288.04	7,188.58	17.23	17.08	-90.39	245.15	-804.42	1,752.04	1,721.37	30.67	57.131					
7,400.00	7,288.58	7,388.04	7,288.58	17.29	17.14	-90.39	245.15	-804.42	1,752.04	1,721.25	30.79	56.898					
7,500.00	7,388.58	7,488.04	7,388.58	17.35	17.21	-90.39	245.15	-804.42	1,752.04	1,721.12	30.92	56.666					
7,600.00	7,488.58	7,588.04	7,488.58	17.41	17.27	-90.39	245.15	-804.42	1,752.04	1,721.00	31.05	56.435					
7,700.00	7,588.58	7,688.04	7,588.58	17.47	17.34	-90.39	245.15	-804.42	1,752.04	1,720.87	31.17	56.205					
7,800.00	7,688.58	7,788.04	7,688.58	17.53	17.40	-90.39	245.15	-804.42	1,752.04	1,720.74	31.30	55.977					
7,900.00	7,788.58	7,888.04	7,788.58	17.59	17.47	-90.39	245.15	-804.42	1,752.04	1,720.61	31.43	55.750					
8,000.00	7,888.58	7,988.04	7,888.58	17.65	17.53	-90.39	245.15	-804.42	1,752.04	1,720.49	31.55	55.524					
8,100.00	7,988.58	8,088.04	7,988.58	17.71	17.60	-90.39	245.15	-804.42	1,752.04	1,720.36	31.68	55.300					
8,200.00	8,088.58	8,188.04	8,088.58	17.77	17.67	-90.39	245.15	-804.42	1,752.04	1,720.23	31.81	55.077					
8,300.00	8,188.58	8,288.04	8,188.58	17.83	17.73	-90.39	245.15	-804.42	1,752.04	1,720.10	31.94	54.855					
8,400.00	8,288.58	8,388.04	8,288.58	17.89	17.80	-90.39	245.15	-804.42	1,752.04	1,719.97	32.07	54.634					
8,500.00	8,388.58	8,488.04	8,388.58	17.95	17.86	-90.39	245.15	-804.42	1,752.04	1,719.84	32.20	54.415					
8,600.00	8,488.58	8,588.04	8,488.58	18.02	17.93	-90.39	245.15	-804.42	1,752.04	1,719.71	32.33	54.196					
8,700.00	8,588.58	8,688.04	8,588.58	18.08	18.00	-90.39	245.15	-804.42	1,752.04	1,719.58	32.46	53.979					
8,800.00	8,688.58	8,788.04	8,688.58	18.14	18.06	-90.39	245.15	-804.42	1,752.04	1,719.45	32.59	53.764					
8,900.00	8,788.58	8,888.04	8,788.58	18.20	18.13	-90.39	245.15	-804.42	1,752.04	1,719.32	32.72	53.549					
9,000.00	8,888.58	8,988.04	8,888.58	18.26	18.19	-90.39	245.15	-804.42	1,752.04	1,719.19	32.85	53.336					
9,100.00	8,988.58	9,088.04	8,988.58	18.32	18.26	-90.39	245.15	-804.42	1,752.04	1,719.06	32.98	53.124					
9,200.00	9,088.58	9,188.04	9,088.58	18.39	18.33	-90.39	245.15	-804.42	1,752.04	1,718.93	33.11	52.913					
9,300.00	9,188.58	9,288.04	9,188.58	18.45	18.40	-90.39	245.15	-804.42	1,752.04	1,718.80	33.24	52.703					
9,400.00	9,288.58	9,388.04	9,288.58	18.51	18.46	-90.39	245.15	-804.42	1,752.04	1,718.67	33.38	52.495					
9,500.00	9,388.58	9,488.04	9,388.58	18.57	18.53	-90.39	245.15	-804.42	1,752.04	1,718.53	33.51	52.288					
9,600.00	9,488.58	9,588.04	9,488.58	18.64	18.60	-90.39	245.15	-804.42	1,752.04	1,718.40	33.64	52.082					
9,700.00	9,588.58	9,688.04	9,588.58	18.70	18.66	-90.39	245.15	-804.42	1,752.04	1,718.27	33.77	51.877					
9,800.00	9,688.58	9,788.04	9,688.58	18.76	18.73	-90.39	245.15	-804.42	1,752.04	1,718.13	33.91	51.673					
9,900.00	9,788.58	9,888.04	9,788.58	18.83	18.80	-90.39	245.15	-804.42	1,752.04	1,718.00	34.04	51.471					
10,000.00	9,888.58	9,988.04	9,888.58	18.89	18.87	-90.39	245.15	-804.42	1,752.04	1,717.87	34.17	51.270					
10,100.00	9,988.58	10,088.04	9,988.58	18.95	18.94	-90.39	245.15	-804.42	1,752.04	1,717.73	34.31	51.070					
10,200.00	10,088.58	10,188.04	10,088.58	19.02	19.00	-90.39	245.15	-804.42	1,752.04	1,717.60	34.44	50.871					

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 8 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 131H - OH - Plan 1														Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance			Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
10,300.00	10,188.58	10,288.04	10,188.58	19.08	19.07	-90.39	245.15	-804.42	1,752.04	1,717.47	34.58	50.673			
10,400.00	10,288.58	10,388.04	10,288.58	19.15	19.14	-90.39	245.15	-804.42	1,752.04	1,717.33	34.71	50.477			
10,500.00	10,388.58	10,488.04	10,388.58	19.21	19.21	-90.39	245.15	-804.42	1,752.04	1,717.20	34.84	50.282			
10,600.00	10,488.58	10,588.04	10,488.58	19.27	19.28	-90.39	245.15	-804.42	1,752.04	1,717.06	34.98	50.087			
10,700.00	10,588.58	10,688.04	10,588.58	19.34	19.35	-90.39	245.15	-804.42	1,752.04	1,716.93	35.11	49.894			
10,800.00	10,688.58	10,788.04	10,688.58	19.40	19.41	-90.39	245.15	-804.42	1,752.04	1,716.79	35.25	49.703			
10,900.00	10,788.58	10,888.04	10,788.58	19.47	19.48	-90.39	245.15	-804.42	1,752.04	1,716.65	35.39	49.512			
11,000.00	10,888.58	10,988.04	10,888.58	19.53	19.55	-90.39	245.15	-804.42	1,752.04	1,716.52	35.52	49.322			
11,100.00	10,988.58	11,088.04	10,988.58	19.60	19.62	-90.39	245.15	-804.42	1,752.04	1,716.38	35.66	49.134			
11,200.00	11,088.58	11,188.04	11,088.58	19.66	19.69	-90.39	245.15	-804.42	1,752.04	1,716.25	35.79	48.947			
11,300.00	11,188.58	11,288.04	11,188.58	19.73	19.76	-90.39	245.15	-804.42	1,752.04	1,716.11	35.93	48.760			
11,400.00	11,288.58	11,388.04	11,288.58	19.79	19.83	-90.39	245.15	-804.42	1,752.04	1,715.97	36.07	48.575			
11,500.00	11,388.58	11,488.04	11,388.58	19.86	19.90	-90.39	245.15	-804.42	1,752.04	1,715.83	36.21	48.391			
11,600.00	11,488.58	11,588.04	11,488.58	19.92	19.97	-90.39	245.15	-804.42	1,752.04	1,715.70	36.34	48.208			
11,700.00	11,588.58	11,688.19	11,588.71	19.99	20.03	-90.42	244.10	-804.41	1,752.04	1,715.60	36.44	48.076			
11,725.52	11,614.10	11,713.68	11,614.10	20.01	20.04	-90.49	241.99	-804.39	1,752.04	1,715.59	36.45	48.066			
11,800.00	11,688.58	11,786.36	11,685.70	20.05	20.05	-90.89	229.81	-804.29	1,752.08	1,715.65	36.44	48.085			
11,900.00	11,788.58	11,877.23	11,772.12	20.12	20.03	-91.80	202.01	-804.05	1,752.57	1,716.20	36.38	48.179			
12,000.00	11,888.58	11,957.68	11,844.12	20.19	20.00	-92.97	166.27	-803.74	1,754.24	1,717.94	36.30	48.325			
12,100.00	11,988.51	12,027.87	11,902.32	20.25	19.96	86.09	127.11	-803.40	1,757.76	1,721.58	36.19	48.572			
12,200.00	12,086.82	12,100.00	11,956.69	20.31	19.93	84.41	79.78	-803.00	1,762.62	1,726.59	36.03	48.925			
12,300.00	12,180.57	12,159.04	11,996.48	20.35	19.91	82.99	36.20	-802.62	1,768.18	1,732.26	35.92	49.223			
12,400.00	12,266.93	12,222.17	12,033.82	20.39	19.90	81.60	-14.66	-802.18	1,774.01	1,738.16	35.85	49.486			
12,500.00	12,343.26	12,284.21	12,064.84	20.44	19.92	80.38	-68.34	-801.72	1,779.65	1,743.81	35.83	49.663			
12,600.00	12,407.24	12,350.00	12,091.21	20.52	19.96	79.31	-128.58	-801.20	1,784.69	1,748.81	35.89	49.731			
12,700.00	12,456.94	12,400.00	12,106.53	20.67	20.00	78.57	-176.16	-800.79	1,788.80	1,752.74	36.06	49.609			
12,800.00	12,490.84	12,466.32	12,120.34	20.88	20.09	77.99	-240.98	-800.24	1,791.69	1,755.40	36.29	49.377			
12,900.00	12,507.91	12,526.34	12,126.32	21.18	20.20	77.71	-300.67	-799.72	1,793.21	1,756.61	36.59	49.003			
13,000.00	12,510.43	12,611.54	12,127.49	21.56	20.40	77.67	-385.86	-798.99	1,793.41	1,756.38	37.03	48.436			
13,100.00	12,511.30	12,711.54	12,128.36	22.01	20.70	77.67	-485.85	-798.13	1,793.41	1,755.73	37.68	47.602			
13,200.00	12,512.18	12,811.54	12,129.23	22.52	21.05	77.67	-585.84	-797.27	1,793.41	1,754.91	38.50	46.582			
13,300.00	12,513.05	12,911.54	12,130.10	23.10	21.47	77.67	-685.84	-796.41	1,793.41	1,753.92	39.49	45.413			
13,400.00	12,513.92	13,011.54	12,130.97	23.73	21.95	77.67	-785.83	-795.55	1,793.41	1,752.77	40.63	44.135			
13,500.00	12,514.80	13,111.54	12,131.84	24.41	22.49	77.67	-885.82	-794.68	1,793.41	1,751.49	41.92	42.782			
13,600.00	12,515.67	13,211.54	12,132.71	25.15	23.09	77.67	-985.81	-793.82	1,793.41	1,750.08	43.33	41.387			
13,700.00	12,516.55	13,311.54	12,133.58	25.93	23.75	77.67	-1,085.81	-792.96	1,793.41	1,748.55	44.86	39.976			
13,800.00	12,517.42	13,411.54	12,134.45	26.76	24.47	77.67	-1,185.80	-792.10	1,793.41	1,746.92	46.50	38.571			
13,900.00	12,518.29	13,511.54	12,135.33	27.63	25.23	77.67	-1,285.79	-791.24	1,793.41	1,745.19	48.22	37.189			
14,000.00	12,519.17	13,611.54	12,136.20	28.53	26.05	77.67	-1,385.78	-790.38	1,793.41	1,743.38	50.04	35.841			
14,100.00	12,520.04	13,711.54	12,137.07	29.47	26.91	77.67	-1,485.78	-789.52	1,793.42	1,741.49	51.93	34.538			
14,200.00	12,520.91	13,811.54	12,137.94	30.44	27.81	77.67	-1,585.77	-788.66	1,793.42	1,739.53	53.88	33.284			
14,300.00	12,521.79	13,911.54	12,138.81	31.44	28.75	77.67	-1,685.76	-787.80	1,793.42	1,737.52	55.90	32.084			
14,400.00	12,522.66	14,011.54	12,139.68	32.46	29.72	77.67	-1,785.75	-786.94	1,793.42	1,735.45	57.97	30.938			
14,500.00	12,523.53	14,111.54	12,140.55	33.51	30.72	77.67	-1,885.75	-786.08	1,793.42	1,733.33	60.09	29.847			
14,600.00	12,524.41	14,211.54	12,141.42	34.58	31.75	77.67	-1,985.74	-785.22	1,793.42	1,731.17	62.25	28.810			
14,700.00	12,525.28	14,311.54	12,142.29	35.67	32.81	77.67	-2,085.73	-784.36	1,793.42	1,728.97	64.45	27.825			
14,800.00	12,526.16	14,411.54	12,143.17	36.78	33.89	77.67	-2,185.72	-783.49	1,793.42	1,726.73	66.69	26.892			
14,900.00	12,527.03	14,511.54	12,144.04	37.90	34.99	77.67	-2,285.72	-782.63	1,793.42	1,724.46	68.96	26.007			
15,000.00	12,527.90	14,611.54	12,144.91	39.04	36.11	77.67	-2,385.71	-781.77	1,793.42	1,722.17	71.26	25.169			
15,100.00	12,528.78	14,711.54	12,145.78	40.20	37.25	77.67	-2,485.70	-780.91	1,793.43	1,719.84	73.58	24.374			
15,200.00	12,529.65	14,811.54	12,146.65	41.37	38.40	77.67	-2,585.69	-780.05	1,793.43	1,717.50	75.93	23.620			
15,300.00	12,530.52	14,911.54	12,147.52	42.55	39.56	77.67	-2,685.69	-779.19	1,793.43	1,715.13	78.30	22.905			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 9 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 131H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:			Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning			
15,400.00	12,531.40	15,011.54	12,148.39	43.74	40.74	77.67	-2,785.68	-778.33	1,793.43	1,712.74	80.69	22.227				
15,500.00	12,532.27	15,111.54	12,149.26	44.94	41.93	77.67	-2,885.67	-777.47	1,793.43	1,710.34	83.09	21.583				
15,600.00	12,533.14	15,211.54	12,150.14	46.15	43.14	77.67	-2,985.66	-776.61	1,793.43	1,707.91	85.52	20.972				
15,700.00	12,534.02	15,311.54	12,151.01	47.37	44.35	77.67	-3,085.66	-775.75	1,793.43	1,705.48	87.96	20.390				
15,800.00	12,534.89	15,411.54	12,151.88	48.59	45.57	77.67	-3,185.65	-774.89	1,793.43	1,703.02	90.41	19.837				
15,900.00	12,535.76	15,511.54	12,152.75	49.83	46.80	77.67	-3,285.64	-774.03	1,793.43	1,700.56	92.87	19.311				
16,000.00	12,536.64	15,611.54	12,153.62	51.07	48.04	77.67	-3,385.63	-773.17	1,793.43	1,698.08	95.35	18.809				
16,100.00	12,537.51	15,711.54	12,154.49	52.32	49.28	77.67	-3,485.63	-772.31	1,793.43	1,695.60	97.84	18.331				
16,200.00	12,538.39	15,811.54	12,155.36	53.57	50.53	77.67	-3,585.62	-771.44	1,793.44	1,693.10	100.33	17.875				
16,300.00	12,539.26	15,911.54	12,156.23	54.83	51.79	77.67	-3,685.61	-770.58	1,793.44	1,690.59	102.84	17.439				
16,400.00	12,540.13	16,011.54	12,157.10	56.09	53.05	77.67	-3,785.60	-769.72	1,793.44	1,688.08	105.36	17.022				
16,500.00	12,541.01	16,111.54	12,157.98	57.36	54.32	77.67	-3,885.60	-768.86	1,793.44	1,685.56	107.88	16.624				
16,600.00	12,541.88	16,211.54	12,158.85	58.64	55.60	77.67	-3,985.59	-768.00	1,793.44	1,683.03	110.41	16.243				
16,700.00	12,542.75	16,311.54	12,159.72	59.91	56.87	77.67	-4,085.58	-767.14	1,793.44	1,680.49	112.95	15.878				
16,800.00	12,543.63	16,411.54	12,160.59	61.20	58.16	77.67	-4,185.57	-766.28	1,793.44	1,677.94	115.50	15.528				
16,900.00	12,544.50	16,511.54	12,161.46	62.48	59.44	77.67	-4,285.57	-765.42	1,793.44	1,675.39	118.05	15.193				
17,000.00	12,545.37	16,611.54	12,162.33	63.77	60.73	77.67	-4,385.56	-764.56	1,793.44	1,672.84	120.60	14.871				
17,100.00	12,546.25	16,711.54	12,163.20	65.06	62.03	77.67	-4,485.55	-763.70	1,793.44	1,670.28	123.17	14.561				
17,200.00	12,547.12	16,811.54	12,164.07	66.36	63.32	77.67	-4,585.54	-762.84	1,793.44	1,667.71	125.73	14.264				
17,300.00	12,547.99	16,911.54	12,164.94	67.66	64.62	77.67	-4,685.54	-761.98	1,793.45	1,665.14	128.31	13.978				
17,400.00	12,548.87	17,011.54	12,165.82	68.96	65.92	77.67	-4,785.53	-761.12	1,793.45	1,662.56	130.88	13.703				
17,500.00	12,549.74	17,111.54	12,166.69	70.26	67.23	77.67	-4,885.52	-760.26	1,793.45	1,659.99	133.46	13.438				
17,600.00	12,550.62	17,211.54	12,167.56	71.57	68.54	77.67	-4,985.51	-759.39	1,793.45	1,657.40	136.05	13.183				
17,700.00	12,551.49	17,311.54	12,168.43	72.88	69.85	77.67	-5,085.51	-758.53	1,793.45	1,654.81	138.64	12.936				
17,800.00	12,552.36	17,411.54	12,169.30	74.19	71.16	77.67	-5,185.50	-757.67	1,793.45	1,652.22	141.23	12.699				
17,900.00	12,553.24	17,511.54	12,170.17	75.50	72.48	77.67	-5,285.49	-756.81	1,793.45	1,649.63	143.82	12.470				
18,000.00	12,554.11	17,611.54	12,171.04	76.81	73.79	77.67	-5,385.48	-755.95	1,793.45	1,647.03	146.42	12.249				
18,100.00	12,554.98	17,711.54	12,171.91	78.13	75.11	77.67	-5,485.48	-755.09	1,793.45	1,644.43	149.02	12.035				
18,200.00	12,555.86	17,811.54	12,172.78	79.45	76.43	77.67	-5,585.47	-754.23	1,793.45	1,641.83	151.63	11.828				
18,300.00	12,556.73	17,911.54	12,173.66	80.77	77.75	77.67	-5,685.46	-753.37	1,793.45	1,639.22	154.23	11.628				
18,400.00	12,557.60	18,011.54	12,174.53	82.09	79.08	77.67	-5,785.45	-752.51	1,793.46	1,636.61	156.84	11.435				
18,500.00	12,558.48	18,111.54	12,175.40	83.42	80.40	77.67	-5,885.45	-751.65	1,793.46	1,634.00	159.45	11.247				
18,600.00	12,559.35	18,211.54	12,176.27	84.74	81.73	77.67	-5,985.44	-750.79	1,793.46	1,631.39	162.07	11.066				
18,700.00	12,560.23	18,311.54	12,177.14	86.07	83.06	77.67	-6,085.43	-749.93	1,793.46	1,628.77	164.68	10.890				
18,800.00	12,561.10	18,411.54	12,178.01	87.40	84.39	77.67	-6,185.42	-749.07	1,793.46	1,626.16	167.30	10.720				
18,900.00	12,561.97	18,511.54	12,178.88	88.72	85.72	77.67	-6,285.42	-748.20	1,793.46	1,623.54	169.92	10.554				
19,000.00	12,562.85	18,611.54	12,179.75	90.05	87.05	77.67	-6,385.41	-747.34	1,793.46	1,620.92	172.55	10.394				
19,100.00	12,563.72	18,711.54	12,180.62	91.39	88.38	77.67	-6,485.40	-746.48	1,793.46	1,618.29	175.17	10.238				
19,200.00	12,564.59	18,811.54	12,181.50	92.72	89.72	77.67	-6,585.39	-745.62	1,793.46	1,615.67	177.80	10.087				
19,300.00	12,565.47	18,911.54	12,182.37	94.05	91.05	77.67	-6,685.39	-744.76	1,793.46	1,613.04	180.42	9.940				
19,400.00	12,566.34	19,011.54	12,183.24	95.39	92.39	77.67	-6,785.38	-743.90	1,793.47	1,610.41	183.05	9.797				
19,500.00	12,567.21	19,111.54	12,184.11	96.72	93.73	77.67	-6,885.37	-743.04	1,793.47	1,607.78	185.68	9.659				
19,600.00	12,568.09	19,211.54	12,184.98	98.06	95.07	77.67	-6,985.36	-742.18	1,793.47	1,605.15	188.32	9.524				
19,700.00	12,568.96	19,311.54	12,185.85	99.40	96.41	77.67	-7,085.36	-741.32	1,793.47	1,602.52	190.95	9.392				
19,800.00	12,569.83	19,411.54	12,186.72	100.73	97.75	77.67	-7,185.35	-740.46	1,793.47	1,599.88	193.59	9.264				
19,900.00	12,570.71	19,511.54	12,187.59	102.07	99.09	77.67	-7,285.34	-739.60	1,793.47	1,597.25	196.22	9.140				
20,000.00	12,571.58	19,611.54	12,188.46	103.41	100.43	77.67	-7,385.33	-738.74	1,793.47	1,594.61	198.86	9.019				
20,100.00	12,572.46	19,711.54	12,189.34	104.75	101.77	77.67	-7,485.33	-737.88	1,793.47	1,591.97	201.50	8.901				
20,200.00	12,573.33	19,811.54	12,190.21	106.10	103.12	77.66	-7,585.32	-737.02	1,793.47	1,589.33	204.14	8.786				
20,300.00	12,574.20	19,911.54	12,191.08	107.44	104.46	77.66	-7,685.31	-736.15	1,793.47	1,586.69	206.78	8.673				
20,400.00	12,575.08	20,011.54	12,191.95	108.78	105.80	77.66	-7,785.30	-735.29	1,793.47	1,584.05	209.42	8.564				
20,500.00	12,575.95	20,111.54	12,192.82	110.12	107.15	77.66	-7,885.30	-734.43	1,793.48	1,581.41	212.07	8.457				

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 131H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:			Offset Well Error:		0.50 usft		
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
20,600.00	12,576.82	20,211.54	12,193.69	111.47	108.50	77.66	-7,985.29	-733.57	1,793.48	1,578.77	214.71	8.353	
20,700.00	12,577.70	20,311.54	12,194.56	112.81	109.84	77.66	-8,085.28	-732.71	1,793.48	1,576.12	217.35	8.251	
20,800.00	12,578.57	20,411.54	12,195.43	114.16	111.19	77.66	-8,185.27	-731.85	1,793.48	1,573.48	220.00	8.152	
20,900.00	12,579.44	20,511.54	12,196.31	115.51	112.54	77.66	-8,285.27	-730.99	1,793.48	1,570.83	222.65	8.055	
21,000.00	12,580.32	20,611.54	12,197.18	116.85	113.89	77.66	-8,385.26	-730.13	1,793.48	1,568.18	225.30	7.961	
21,100.00	12,581.19	20,711.54	12,198.05	118.20	115.23	77.66	-8,485.25	-729.27	1,793.48	1,565.54	227.94	7.868	
21,200.00	12,582.06	20,811.54	12,198.92	119.55	116.58	77.66	-8,585.24	-728.41	1,793.48	1,562.89	230.59	7.778	
21,300.00	12,582.94	20,911.54	12,199.79	120.89	117.93	77.66	-8,685.24	-727.55	1,793.48	1,560.24	233.24	7.689	
21,400.00	12,583.81	21,011.54	12,200.66	122.24	119.28	77.66	-8,785.23	-726.69	1,793.48	1,557.59	235.89	7.603	
21,500.00	12,584.69	21,111.54	12,201.53	123.59	120.63	77.66	-8,885.22	-725.83	1,793.48	1,554.94	238.55	7.518	
21,600.00	12,585.56	21,211.54	12,202.40	124.94	121.98	77.66	-8,985.21	-724.96	1,793.49	1,552.29	241.20	7.436	
21,700.00	12,586.43	21,311.54	12,203.27	126.29	123.34	77.66	-9,085.21	-724.10	1,793.49	1,549.64	243.85	7.355	
21,800.00	12,587.31	21,411.54	12,204.15	127.64	124.69	77.66	-9,185.20	-723.24	1,793.49	1,546.98	246.50	7.276	
21,900.00	12,588.18	21,511.54	12,205.02	128.99	126.04	77.66	-9,285.19	-722.38	1,793.49	1,544.33	249.16	7.198	
22,000.00	12,589.05	21,611.54	12,205.89	130.34	127.39	77.66	-9,385.18	-721.52	1,793.49	1,541.68	251.81	7.122	
22,100.00	12,589.93	21,711.54	12,206.76	131.70	128.75	77.66	-9,485.18	-720.66	1,793.49	1,539.02	254.47	7.048	
22,200.00	12,590.80	21,811.54	12,207.63	133.05	130.10	77.66	-9,585.17	-719.80	1,793.49	1,536.37	257.13	6.975	
22,300.00	12,591.67	21,911.54	12,208.50	134.40	131.45	77.66	-9,685.16	-718.94	1,793.49	1,533.71	259.78	6.904	
22,400.00	12,592.55	22,011.54	12,209.37	135.75	132.81	77.66	-9,785.15	-718.08	1,793.49	1,531.05	262.44	6.834	
22,500.00	12,593.42	22,111.54	12,210.24	137.11	134.16	77.66	-9,885.15	-717.22	1,793.49	1,528.40	265.10	6.765	
22,600.00	12,594.30	22,211.54	12,211.11	138.46	135.52	77.66	-9,985.14	-716.36	1,793.49	1,525.74	267.75	6.698	
22,700.00	12,595.17	22,311.54	12,211.99	139.81	136.87	77.66	-10,085.13	-715.50	1,793.50	1,523.08	270.41	6.632	
22,800.00	12,596.04	22,411.54	12,212.86	141.17	138.23	77.66	-10,185.12	-714.64	1,793.50	1,520.42	273.07	6.568	
22,807.43	12,596.11	22,418.97	12,212.92	141.27	138.33	77.66	-10,192.56	-714.57	1,793.50	1,520.23	273.27	6.563	
22,875.30	12,596.70	22,485.80	12,213.50	142.19	139.26	77.66	-10,259.37	-714.00	1,793.50	1,518.44	275.06	6.520	SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 132H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
0.00	0.00	0.00	1.00	0.50	0.50	153.43	-50.00	25.00	55.91				
100.00	100.00	99.00	100.00	0.98	0.97	153.43	-50.00	25.00	55.90	53.95	1.95	28.595	
200.00	200.00	199.00	200.00	1.56	1.56	153.43	-50.00	25.00	55.90	52.79	3.12	17.939	
300.00	300.00	299.00	300.00	1.98	1.98	153.43	-50.00	25.00	55.90	51.94	3.96	14.123	
400.00	400.00	399.00	400.00	2.33	2.33	153.43	-50.00	25.00	55.90	51.25	4.66	12.008	
500.00	500.00	499.00	500.00	2.63	2.63	153.43	-50.00	25.00	55.90	50.64	5.27	10.616	
600.00	600.00	599.00	600.00	2.91	2.91	153.43	-50.00	25.00	55.90	50.08	5.82	9.609	
700.00	700.00	699.00	700.00	3.16	3.16	153.43	-50.00	25.00	55.90	49.58	6.33	8.838	
800.00	800.00	799.00	800.00	3.40	3.40	153.43	-50.00	25.00	55.90	49.10	6.80	8.222	
900.00	900.00	899.11	900.10	3.62	3.67	152.12	-49.32	26.09	55.80	48.56	7.24	7.704	
1,000.00	1,000.00	999.09	1,000.00	3.76	3.93	56.16	-47.27	29.41	55.64	48.06	7.58	7.336	
1,100.00	1,099.98	1,098.89	1,099.59	4.00	4.18	50.95	-43.84	34.93	54.85	46.86	7.99	6.862	
1,200.00	1,199.88	1,198.69	1,199.02	4.24	4.29	45.49	-39.34	42.19	53.08	44.76	8.31	6.385	
1,300.00	1,299.63	1,298.57	1,298.51	4.46	4.49	41.47	-34.75	49.59	49.87	41.15	8.72	5.718	
1,400.00	1,399.25	1,398.44	1,398.01	4.60	4.68	38.12	-30.17	56.99	45.66	36.60	9.06	5.040	
1,500.00	1,498.87	1,498.31	1,497.50	4.78	4.87	34.11	-25.58	64.39	41.61	32.17	9.44	4.408	
1,600.00	1,598.49	1,598.18	1,596.99	4.96	5.06	29.27	-20.99	71.79	37.81	27.99	9.82	3.850	
1,700.00	1,698.11	1,698.05	1,696.48	5.14	5.25	23.40	-16.40	79.18	34.34	24.13	10.21	3.363	
1,800.00	1,797.73	1,797.92	1,795.97	5.32	5.44	16.31	-11.82	86.58	31.30	20.70	10.60	2.952	
1,900.00	1,897.34	1,897.80	1,895.46	5.49	5.63	7.87	-7.23	93.98	28.84	17.84	11.00	2.621	
2,000.00	1,996.96	1,997.67	1,994.96	5.67	5.82	-1.89	-2.64	101.38	27.11	15.71	11.41	2.377	
2,100.00	2,096.58	2,097.54	2,094.45	5.85	6.01	-12.62	1.94	108.78	26.27	14.46	11.80	2.225	
2,138.22	2,134.66	2,135.71	2,132.47	5.92	6.08	-16.84	3.70	111.60	26.20	14.24	11.95	2.191	CC
2,200.00	2,196.20	2,197.41	2,193.94	6.04	6.20	-23.64	6.53	116.17	26.38	14.19	12.19	2.164	ES
2,300.00	2,295.72	2,296.85	2,292.93	6.23	6.38	-28.10	11.49	124.17	26.99	14.46	12.53	2.154	
2,400.00	2,394.97	2,396.25	2,391.70	6.43	6.57	-34.59	17.34	133.62	27.68	14.82	12.86	2.153	SF
2,500.00	2,493.89	2,495.63	2,490.26	6.64	6.76	-42.60	24.10	144.52	28.55	15.40	13.16	2.170	
2,600.00	2,592.40	2,595.02	2,588.57	6.85	6.95	-51.67	31.76	156.87	29.79	16.34	13.45	2.215	
2,700.00	2,690.45	2,694.41	2,686.62	7.07	7.14	-61.39	40.31	170.67	31.58	17.84	13.74	2.298	
2,800.00	2,787.96	2,793.81	2,784.39	7.28	7.34	-71.30	49.76	185.91	34.15	20.08	14.08	2.426	
2,900.00	2,884.87	2,893.23	2,881.85	7.49	7.54	-80.92	60.11	202.60	37.68	23.20	14.47	2.603	
3,000.00	2,981.46	2,992.90	2,979.35	7.68	7.74	-89.88	71.02	220.20	42.32	27.39	14.92	2.836	
3,100.00	3,078.05	3,092.60	3,076.87	7.87	7.94	-96.93	81.94	237.81	47.78	32.38	15.40	3.103	
3,200.00	3,174.64	3,192.29	3,174.39	8.06	8.14	-102.47	92.85	255.42	53.81	37.93	15.89	3.387	
3,300.00	3,271.24	3,291.99	3,271.91	8.26	8.34	-106.86	103.77	273.03	60.25	43.87	16.38	3.678	
3,400.00	3,367.83	3,391.69	3,369.43	8.51	8.55	-110.39	114.69	290.64	66.96	50.09	16.88	3.968	
3,500.00	3,464.42	3,491.39	3,466.95	8.80	8.76	-113.27	125.60	308.25	73.89	56.52	17.37	4.253	
3,600.00	3,561.01	3,591.08	3,564.47	9.09	8.97	-115.65	136.52	325.86	80.97	63.10	17.87	4.531	
3,700.00	3,657.60	3,690.78	3,662.00	9.38	9.19	-117.64	147.44	343.47	88.16	69.80	18.37	4.800	
3,800.00	3,754.20	3,790.48	3,759.52	9.68	9.42	-119.34	158.36	361.08	95.45	76.58	18.86	5.060	
3,900.00	3,850.79	3,890.18	3,857.04	9.98	9.65	-120.79	169.27	378.70	102.80	83.44	19.36	5.309	
4,000.00	3,947.38	3,989.87	3,954.56	10.28	9.89	-122.05	180.19	396.31	110.22	90.35	19.86	5.549	
4,100.00	4,043.97	4,089.39	4,051.92	10.59	10.10	-123.17	191.06	413.84	117.70	97.37	20.33	5.789	
4,200.00	4,140.56	4,188.30	4,148.92	10.90	10.33	-124.69	201.21	430.22	125.66	104.85	20.81	6.039	
4,300.00	4,237.16	4,286.98	4,246.03	11.21	10.56	-126.70	210.47	445.14	134.36	113.09	21.27	6.318	
4,400.00	4,333.75	4,385.37	4,343.14	11.52	10.77	-129.08	218.81	458.61	143.93	122.23	21.70	6.633	
4,500.00	4,430.34	4,483.43	4,440.17	11.84	10.97	-131.70	226.25	470.61	154.51	132.41	22.10	6.991	
4,600.00	4,526.93	4,581.09	4,537.03	12.16	11.16	-134.49	232.80	481.16	166.24	143.76	22.48	7.394	
4,700.00	4,623.53	4,678.29	4,633.64	12.48	11.34	-137.34	238.44	490.27	179.24	156.40	22.84	7.848	
4,800.00	4,720.12	4,774.99	4,729.92	12.80	11.50	-140.19	243.20	497.95	193.63	170.45	23.18	8.355	
4,900.00	4,816.71	4,871.14	4,825.79	13.12	11.65	-142.99	247.08	504.22	209.48	185.99	23.49	8.916	
5,000.00	4,913.30	4,966.69	4,921.16	13.45	11.79	-145.69	250.10	509.08	226.87	203.08	23.80	9.533	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 12 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 132H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:					Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
5,100.00	5,009.89	5,061.59	5,015.97	13.78	11.91	-148.26	252.27	512.58	245.85	221.76	24.10	10.203	
5,200.00	5,106.49	5,155.79	5,110.13	14.10	12.03	-150.69	253.60	514.73	266.45	242.07	24.37	10.932	
5,300.00	5,203.08	5,249.25	5,203.59	14.43	12.12	-152.98	254.12	515.57	288.67	264.05	24.62	11.726	
5,400.00	5,299.67	5,345.33	5,299.67	14.75	12.18	-155.12	254.13	515.58	312.08	287.23	24.85	12.561	
5,500.00	5,396.65	5,442.31	5,396.65	15.07	12.26	-157.01	254.13	515.58	334.49	309.37	25.12	13.316	
5,600.00	5,494.23	5,539.89	5,494.23	15.36	12.34	-158.50	254.13	515.58	354.78	329.39	25.40	13.970	
5,700.00	5,592.35	5,638.01	5,592.35	15.62	12.42	-159.68	254.13	515.58	372.84	347.17	25.67	14.523	
5,800.00	5,690.94	5,736.60	5,690.94	15.86	12.50	-160.61	254.13	515.58	388.59	362.64	25.95	14.976	
5,900.00	5,789.93	5,835.59	5,789.93	16.07	12.58	-161.34	254.13	515.58	401.96	375.74	26.22	15.330	
6,000.00	5,889.26	5,934.92	5,889.26	16.25	12.66	-161.91	254.13	515.58	412.91	386.42	26.49	15.589	
6,100.00	5,988.86	6,034.52	5,988.86	16.41	12.74	-162.32	254.13	515.58	421.41	394.66	26.75	15.756	
6,200.00	6,088.66	6,134.32	6,088.66	16.53	12.82	-162.61	254.13	515.58	427.43	400.43	27.00	15.833	
6,300.00	6,188.59	6,234.25	6,188.59	16.64	12.90	-162.77	254.13	515.58	430.96	403.73	27.23	15.824	
6,400.00	6,288.58	6,334.24	6,288.58	16.71	12.98	-90.39	254.13	515.58	432.01	404.61	27.40	15.768	
6,500.00	6,388.58	6,434.24	6,388.58	16.76	13.06	-90.39	254.13	515.58	432.01	404.48	27.53	15.690	
6,600.00	6,488.58	6,534.24	6,488.58	16.82	13.14	-90.39	254.13	515.58	432.01	404.34	27.67	15.612	
6,700.00	6,588.58	6,634.24	6,588.58	16.88	13.22	-90.39	254.13	515.58	432.01	404.20	27.81	15.536	
6,800.00	6,688.58	6,734.24	6,688.58	16.94	13.31	-90.39	254.13	515.58	432.01	404.07	27.94	15.459	
6,900.00	6,788.58	6,834.24	6,788.58	17.00	13.39	-90.39	254.13	515.58	432.01	403.93	28.08	15.384	
7,000.00	6,888.58	6,934.24	6,888.58	17.05	13.47	-90.39	254.13	515.58	432.01	403.79	28.22	15.309	
7,100.00	6,988.58	7,034.24	6,988.58	17.11	13.55	-90.39	254.13	515.58	432.01	403.65	28.36	15.234	
7,200.00	7,088.58	7,134.24	7,088.58	17.17	13.63	-90.39	254.13	515.58	432.01	403.51	28.50	15.160	
7,300.00	7,188.58	7,234.24	7,188.58	17.23	13.71	-90.39	254.13	515.58	432.01	403.38	28.63	15.087	
7,400.00	7,288.58	7,334.24	7,288.58	17.29	13.79	-90.39	254.13	515.58	432.01	403.24	28.77	15.015	
7,500.00	7,388.58	7,434.24	7,388.58	17.35	13.87	-90.39	254.13	515.58	432.01	403.10	28.91	14.942	
7,600.00	7,488.58	7,534.24	7,488.58	17.41	13.95	-90.39	254.13	515.58	432.01	402.96	29.05	14.871	
7,700.00	7,588.58	7,634.24	7,588.58	17.47	14.03	-90.39	254.13	515.58	432.01	402.82	29.19	14.800	
7,800.00	7,688.58	7,734.24	7,688.58	17.53	14.11	-90.39	254.13	515.58	432.01	402.68	29.33	14.730	
7,900.00	7,788.58	7,834.24	7,788.58	17.59	14.20	-90.39	254.13	515.58	432.01	402.54	29.47	14.660	
8,000.00	7,888.58	7,934.24	7,888.58	17.65	14.28	-90.39	254.13	515.58	432.01	402.40	29.61	14.590	
8,100.00	7,988.58	8,034.24	7,988.58	17.71	14.36	-90.39	254.13	515.58	432.01	402.26	29.75	14.522	
8,200.00	8,088.58	8,134.24	8,088.58	17.77	14.44	-90.39	254.13	515.58	432.01	402.12	29.89	14.453	
8,300.00	8,188.58	8,234.24	8,188.58	17.83	14.52	-90.39	254.13	515.58	432.01	401.98	30.03	14.386	
8,400.00	8,288.58	8,334.24	8,288.58	17.89	14.60	-90.39	254.13	515.58	432.01	401.84	30.17	14.319	
8,500.00	8,388.58	8,434.24	8,388.58	17.95	14.68	-90.39	254.13	515.58	432.01	401.70	30.31	14.252	
8,600.00	8,488.58	8,534.24	8,488.58	18.02	14.76	-90.39	254.13	515.58	432.01	401.56	30.45	14.186	
8,700.00	8,588.58	8,634.24	8,588.58	18.08	14.84	-90.39	254.13	515.58	432.01	401.41	30.60	14.120	
8,800.00	8,688.58	8,734.24	8,688.58	18.14	14.93	-90.39	254.13	515.58	432.01	401.27	30.74	14.055	
8,900.00	8,788.58	8,834.24	8,788.58	18.20	15.01	-90.39	254.13	515.58	432.01	401.13	30.88	13.991	
9,000.00	8,888.58	8,934.24	8,888.58	18.26	15.09	-90.39	254.13	515.58	432.01	400.99	31.02	13.927	
9,100.00	8,988.58	9,034.24	8,988.58	18.32	15.17	-90.39	254.13	515.58	432.01	400.85	31.16	13.863	
9,200.00	9,088.58	9,134.24	9,088.58	18.39	15.25	-90.39	254.13	515.58	432.01	400.70	31.31	13.800	
9,300.00	9,188.58	9,234.24	9,188.58	18.45	15.33	-90.39	254.13	515.58	432.01	400.56	31.45	13.737	
9,400.00	9,288.58	9,334.24	9,288.58	18.51	15.41	-90.39	254.13	515.58	432.01	400.42	31.59	13.675	
9,500.00	9,388.58	9,434.24	9,388.58	18.57	15.49	-90.39	254.13	515.58	432.01	400.28	31.73	13.614	
9,600.00	9,488.58	9,534.24	9,488.58	18.64	15.57	-90.39	254.13	515.58	432.01	400.13	31.88	13.552	
9,700.00	9,588.58	9,634.24	9,588.58	18.70	15.66	-90.39	254.13	515.58	432.01	399.99	32.02	13.492	
9,800.00	9,688.58	9,734.24	9,688.58	18.76	15.74	-90.39	254.13	515.58	432.01	399.85	32.16	13.432	
9,900.00	9,788.58	9,834.24	9,788.58	18.83	15.82	-90.39	254.13	515.58	432.01	399.70	32.31	13.372	
10,000.00	9,888.58	9,934.24	9,888.58	18.89	15.90	-90.39	254.13	515.58	432.01	399.56	32.45	13.313	
10,100.00	9,988.58	10,034.24	9,988.58	18.95	15.98	-90.39	254.13	515.58	432.01	399.41	32.60	13.254	
10,200.00	10,088.58	10,134.24	10,088.58	19.02	16.06	-90.39	254.13	515.58	432.01	399.27	32.74	13.195	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 13 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 132H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:			Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning			
10,300.00	10,188.58	10,234.24	10,188.58	19.08	16.14	-90.39	254.13	515.58	432.01	399.13	32.88	13.137				
10,400.00	10,288.58	10,334.24	10,288.58	19.15	16.22	-90.39	254.13	515.58	432.01	398.98	33.03	13.080				
10,500.00	10,388.58	10,434.24	10,388.58	19.21	16.30	-90.39	254.13	515.58	432.01	398.84	33.17	13.023				
10,600.00	10,488.58	10,534.24	10,488.58	19.27	16.39	-90.39	254.13	515.58	432.01	398.69	33.32	12.966				
10,700.00	10,588.58	10,634.24	10,588.58	19.34	16.47	-90.39	254.13	515.58	432.01	398.55	33.46	12.910				
10,800.00	10,688.58	10,734.24	10,688.58	19.40	16.55	-90.39	254.13	515.58	432.01	398.40	33.61	12.854				
10,900.00	10,788.58	10,834.24	10,788.58	19.47	16.63	-90.39	254.13	515.58	432.01	398.26	33.75	12.799				
11,000.00	10,888.58	10,934.24	10,888.58	19.53	16.71	-90.39	254.13	515.58	432.01	398.11	33.90	12.744				
11,100.00	10,988.58	11,034.24	10,988.58	19.60	16.79	-90.39	254.13	515.58	432.01	397.97	34.04	12.689				
11,200.00	11,088.58	11,134.24	11,088.58	19.66	16.87	-90.39	254.13	515.58	432.01	397.82	34.19	12.635				
11,300.00	11,188.58	11,234.24	11,188.58	19.73	16.95	-90.39	254.13	515.58	432.01	397.67	34.34	12.582				
11,400.00	11,288.58	11,334.24	11,288.58	19.79	17.04	-90.39	254.13	515.58	432.01	397.53	34.48	12.528				
11,500.00	11,388.58	11,434.24	11,388.58	19.86	17.12	-90.39	254.13	515.58	432.01	397.38	34.63	12.475				
11,600.00	11,488.58	11,534.24	11,488.58	19.92	17.20	-90.39	254.13	515.58	432.01	397.23	34.78	12.423				
11,695.30	11,583.88	11,629.55	11,583.88	19.99	17.29	-90.49	253.35	515.59	432.01	397.12	34.89	12.382				
11,700.00	11,588.58	11,634.25	11,588.56	19.99	17.29	-90.53	253.09	515.59	432.01	397.12	34.89	12.381				
11,800.00	11,688.58	11,732.02	11,685.18	20.05	17.36	-92.41	238.91	515.71	432.26	397.38	34.89	12.391				
11,900.00	11,788.58	11,822.59	11,771.34	20.12	17.42	-96.05	211.31	515.95	434.39	399.52	34.87	12.456				
12,000.00	11,888.58	11,900.00	11,840.77	20.19	17.46	-100.49	177.20	516.24	441.27	406.19	35.07	12.581				
12,100.00	11,988.51	11,972.91	11,901.41	20.25	17.51	74.28	136.80	516.59	455.27	419.68	35.59	12.792				
12,200.00	12,086.82	12,039.40	11,951.82	20.31	17.56	68.48	93.51	516.96	473.74	437.22	36.52	12.973				
12,300.00	12,180.57	12,100.00	11,993.13	20.35	17.61	63.51	49.21	517.34	494.17	456.35	37.82	13.065				
12,400.00	12,266.93	12,167.03	12,033.08	20.39	17.68	58.95	-4.56	517.81	514.63	475.47	39.16	13.143				
12,500.00	12,343.26	12,229.03	12,064.22	20.44	17.76	55.37	-58.14	518.27	533.68	493.11	40.57	13.155				
12,600.00	12,407.24	12,290.23	12,089.11	20.52	17.86	52.57	-114.01	518.75	550.15	508.29	41.87	13.140				
12,700.00	12,456.94	12,350.00	12,107.52	20.67	17.97	50.53	-170.85	519.24	563.19	520.23	42.96	13.109				
12,800.00	12,490.84	12,411.09	12,120.13	20.88	18.10	49.18	-230.59	519.75	572.19	528.42	43.77	13.072				
12,900.00	12,507.91	12,471.10	12,126.25	21.18	18.26	48.52	-290.26	520.27	576.77	532.51	44.26	13.031				
13,000.00	12,510.43	12,555.36	12,127.47	21.56	18.53	48.44	-374.50	520.99	577.33	532.82	44.51	12.971				
13,100.00	12,511.30	12,655.36	12,128.34	22.01	18.91	48.44	-474.49	521.85	577.33	532.48	44.85	12.873				
13,200.00	12,512.18	12,755.36	12,129.21	22.52	19.36	48.44	-574.48	522.71	577.33	532.05	45.28	12.749				
13,300.00	12,513.05	12,855.36	12,130.08	23.10	19.90	48.44	-674.48	523.58	577.33	531.52	45.82	12.601				
13,400.00	12,513.92	12,955.36	12,130.95	23.73	20.50	48.44	-774.47	524.44	577.33	530.89	46.44	12.432				
13,500.00	12,514.80	13,055.36	12,131.82	24.41	21.18	48.44	-874.46	525.30	577.34	530.18	47.15	12.244				
13,600.00	12,515.67	13,155.36	12,132.69	25.15	21.93	48.44	-974.45	526.16	577.34	529.38	47.95	12.040				
13,700.00	12,516.55	13,255.36	12,133.56	25.93	22.73	48.44	-1,074.45	527.02	577.34	528.51	48.83	11.823				
13,800.00	12,517.42	13,355.36	12,134.44	26.76	23.59	48.44	-1,174.44	527.88	577.34	527.56	49.78	11.597				
13,900.00	12,518.29	13,455.36	12,135.31	27.63	24.50	48.44	-1,274.43	528.74	577.34	526.53	50.81	11.362				
14,000.00	12,519.17	13,555.36	12,136.18	28.53	25.45	48.44	-1,374.42	529.60	577.34	525.44	51.91	11.123				
14,100.00	12,520.04	13,655.36	12,137.05	29.47	26.44	48.44	-1,474.42	530.46	577.34	524.28	53.06	10.880				
14,200.00	12,520.91	13,755.36	12,137.92	30.44	27.47	48.44	-1,574.41	531.32	577.35	523.07	54.28	10.636				
14,300.00	12,521.79	13,855.36	12,138.79	31.44	28.52	48.44	-1,674.40	532.19	577.35	521.80	55.55	10.393				
14,400.00	12,522.66	13,955.36	12,139.66	32.46	29.60	48.44	-1,774.39	533.05	577.35	520.47	56.88	10.151				
14,500.00	12,523.53	14,055.36	12,140.54	33.51	30.71	48.44	-1,874.39	533.91	577.35	519.10	58.25	9.912				
14,600.00	12,524.41	14,155.36	12,141.41	34.58	31.84	48.44	-1,974.38	534.77	577.35	517.69	59.67	9.676				
14,700.00	12,525.28	14,255.36	12,142.28	35.67	32.98	48.44	-2,074.37	535.63	577.35	516.23	61.13	9.445				
14,800.00	12,526.16	14,355.36	12,143.15	36.78	34.15	48.44	-2,174.36	536.49	577.36	514.73	62.62	9.220				
14,900.00	12,527.03	14,455.36	12,144.02	37.90	35.32	48.44	-2,274.36	537.35	577.36	513.20	64.16	8.999				
15,000.00	12,527.90	14,555.36	12,144.89	39.04	36.52	48.44	-2,374.35	538.21	577.36	511.63	65.72	8.785				
15,100.00	12,528.78	14,655.36	12,145.76	40.20	37.72	48.44	-2,474.34	539.07	577.36	510.04	67.32	8.576				
15,200.00	12,529.65	14,755.36	12,146.64	41.37	38.94	48.44	-2,574.33	539.93	577.36	508.41	68.95	8.373				
15,300.00	12,530.52	14,855.36	12,147.51	42.55	40.16	48.44	-2,674.33	540.80	577.36	506.76	70.61	8.177				

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 132H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5) Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre			Rule Assigned: Distance		Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,400.00	12,531.40	14,955.36	12,148.38	43.74	41.40	48.44	-2,774.32	541.66	577.37	505.08	72.29	7.987	
15,500.00	12,532.27	15,055.36	12,149.25	44.94	42.64	48.44	-2,874.31	542.52	577.37	503.38	73.99	7.803	
15,600.00	12,533.14	15,155.36	12,150.12	46.15	43.89	48.44	-2,974.30	543.38	577.37	501.65	75.72	7.626	
15,700.00	12,534.02	15,255.36	12,150.99	47.37	45.15	48.44	-3,074.30	544.24	577.37	499.91	77.46	7.454	
15,800.00	12,534.89	15,355.36	12,151.86	48.59	46.41	48.44	-3,174.29	545.10	577.37	498.15	79.23	7.288	
15,900.00	12,535.76	15,455.36	12,152.74	49.83	47.69	48.44	-3,274.28	545.96	577.37	496.36	81.01	7.127	
16,000.00	12,536.64	15,555.36	12,153.61	51.07	48.96	48.44	-3,374.27	546.82	577.37	494.57	82.81	6.972	
16,100.00	12,537.51	15,655.36	12,154.48	52.32	50.24	48.44	-3,474.27	547.68	577.38	492.75	84.62	6.823	
16,200.00	12,538.39	15,755.36	12,155.35	53.57	51.53	48.44	-3,574.26	548.54	577.38	490.92	86.45	6.679	
16,300.00	12,539.26	15,855.36	12,156.22	54.83	52.82	48.44	-3,674.25	549.41	577.38	489.08	88.30	6.539	
16,400.00	12,540.13	15,955.36	12,157.09	56.09	54.11	48.44	-3,774.24	550.27	577.38	487.23	90.15	6.404	
16,500.00	12,541.01	16,055.36	12,157.96	57.36	55.41	48.44	-3,874.24	551.13	577.38	485.36	92.02	6.274	
16,600.00	12,541.88	16,155.36	12,158.84	58.64	56.71	48.44	-3,974.23	551.99	577.38	483.48	93.90	6.149	
16,700.00	12,542.75	16,255.36	12,159.71	59.91	58.02	48.44	-4,074.22	552.85	577.39	481.59	95.79	6.028	
16,800.00	12,543.63	16,355.36	12,160.58	61.20	59.32	48.44	-4,174.21	553.71	577.39	479.70	97.69	5.910	
16,900.00	12,544.50	16,455.36	12,161.45	62.48	60.63	48.44	-4,274.21	554.57	577.39	477.79	99.60	5.797	
17,000.00	12,545.37	16,555.36	12,162.32	63.77	61.95	48.44	-4,374.20	555.43	577.39	475.87	101.52	5.687	
17,100.00	12,546.25	16,655.36	12,163.19	65.06	63.26	48.44	-4,474.19	556.29	577.39	473.94	103.45	5.581	
17,200.00	12,547.12	16,755.36	12,164.06	66.36	64.58	48.44	-4,574.18	557.15	577.39	472.01	105.38	5.479	
17,300.00	12,547.99	16,855.36	12,164.94	67.66	65.90	48.44	-4,674.18	558.02	577.40	470.07	107.33	5.380	
17,400.00	12,548.87	16,955.36	12,165.81	68.96	67.22	48.44	-4,774.17	558.88	577.40	468.12	109.28	5.284	
17,500.00	12,549.74	17,055.36	12,166.68	70.26	68.54	48.44	-4,874.16	559.74	577.40	466.16	111.23	5.191	
17,600.00	12,550.62	17,155.36	12,167.55	71.57	69.87	48.44	-4,974.15	560.60	577.40	464.20	113.20	5.101	
17,700.00	12,551.49	17,255.36	12,168.42	72.88	71.20	48.44	-5,074.15	561.46	577.40	462.23	115.17	5.014	
17,800.00	12,552.36	17,355.36	12,169.29	74.19	72.53	48.44	-5,174.14	562.32	577.40	460.26	117.14	4.929	
17,900.00	12,553.24	17,455.36	12,170.16	75.50	73.86	48.44	-5,274.13	563.18	577.40	458.28	119.12	4.847	
18,000.00	12,554.11	17,555.36	12,171.03	76.81	75.19	48.44	-5,374.12	564.04	577.41	456.30	121.11	4.768	
18,100.00	12,554.98	17,655.36	12,171.91	78.13	76.52	48.44	-5,474.12	564.90	577.41	454.31	123.10	4.691	
18,200.00	12,555.86	17,755.36	12,172.78	79.45	77.85	48.43	-5,574.11	565.76	577.41	452.31	125.10	4.616	
18,300.00	12,556.73	17,855.36	12,173.65	80.77	79.19	48.43	-5,674.10	566.63	577.41	450.31	127.10	4.543	
18,400.00	12,557.60	17,955.36	12,174.52	82.09	80.53	48.43	-5,774.09	567.49	577.41	448.31	129.10	4.473	
18,500.00	12,558.48	18,055.36	12,175.39	83.42	81.87	48.43	-5,874.09	568.35	577.41	446.30	131.11	4.404	
18,600.00	12,559.35	18,155.36	12,176.26	84.74	83.20	48.43	-5,974.08	569.21	577.42	444.29	133.12	4.337	
18,700.00	12,560.23	18,255.36	12,177.13	86.07	84.54	48.43	-6,074.07	570.07	577.42	442.28	135.14	4.273	
18,800.00	12,561.10	18,355.36	12,178.01	87.40	85.88	48.43	-6,174.06	570.93	577.42	440.26	137.16	4.210	
18,900.00	12,561.97	18,455.36	12,178.88	88.72	87.23	48.43	-6,274.06	571.79	577.42	438.24	139.18	4.149	
19,000.00	12,562.85	18,555.36	12,179.75	90.05	88.57	48.43	-6,374.05	572.65	577.42	436.21	141.21	4.089	
19,100.00	12,563.72	18,655.36	12,180.62	91.39	89.91	48.43	-6,474.04	573.51	577.42	434.18	143.24	4.031	
19,200.00	12,564.59	18,755.36	12,181.49	92.72	91.26	48.43	-6,574.03	574.37	577.43	432.15	145.27	3.975	
19,300.00	12,565.47	18,855.36	12,182.36	94.05	92.60	48.43	-6,674.03	575.23	577.43	430.12	147.31	3.920	
19,400.00	12,566.34	18,955.36	12,183.23	95.39	93.95	48.43	-6,774.02	576.10	577.43	428.08	149.35	3.866	
19,500.00	12,567.21	19,055.36	12,184.11	96.72	95.29	48.43	-6,874.01	576.96	577.43	426.04	151.39	3.814	
19,600.00	12,568.09	19,155.36	12,184.98	98.06	96.64	48.43	-6,974.00	577.82	577.43	424.00	153.43	3.763	
19,700.00	12,568.96	19,255.36	12,185.85	99.40	97.99	48.43	-7,074.00	578.68	577.43	421.95	155.48	3.714	
19,800.00	12,569.83	19,355.36	12,186.72	100.73	99.34	48.43	-7,173.99	579.54	577.43	419.91	157.53	3.666	
19,900.00	12,570.71	19,455.36	12,187.59	102.07	100.69	48.43	-7,273.98	580.40	577.44	417.86	159.58	3.619	
20,000.00	12,571.58	19,555.36	12,188.46	103.41	102.04	48.43	-7,373.97	581.26	577.44	415.81	161.63	3.573	
20,100.00	12,572.46	19,655.36	12,189.33	104.75	103.39	48.43	-7,473.97	582.12	577.44	413.75	163.69	3.528	
20,200.00	12,573.33	19,755.36	12,190.21	106.10	104.74	48.43	-7,573.96	582.98	577.44	411.70	165.74	3.484	
20,300.00	12,574.20	19,855.36	12,191.08	107.44	106.09	48.43	-7,673.95	583.84	577.44	409.64	167.80	3.441	
20,400.00	12,575.08	19,955.36	12,191.95	108.78	107.44	48.43	-7,773.94	584.71	577.44	407.58	169.86	3.399	
20,500.00	12,575.95	20,055.36	12,192.82	110.12	108.79	48.43	-7,873.94	585.57	577.45	405.52	171.93	3.359	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 15 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 132H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)		
20,600.00	12,576.82	20,155.36	12,193.69	111.47	110.14	48.43	-7,973.93	586.43	577.45	403.46	173.99	3.319
20,700.00	12,577.70	20,255.36	12,194.56	112.81	111.50	48.43	-8,073.92	587.29	577.45	401.39	176.06	3.280
20,800.00	12,578.57	20,355.36	12,195.43	114.16	112.85	48.43	-8,173.91	588.15	577.45	399.33	178.12	3.242
20,900.00	12,579.44	20,455.36	12,196.31	115.51	114.20	48.43	-8,273.91	589.01	577.45	397.26	180.19	3.205
21,000.00	12,580.32	20,555.36	12,197.18	116.85	115.56	48.43	-8,373.90	589.87	577.45	395.19	182.26	3.168
21,100.00	12,581.19	20,655.36	12,198.05	118.20	116.91	48.43	-8,473.89	590.73	577.46	393.12	184.34	3.133
21,200.00	12,582.06	20,755.36	12,198.92	119.55	118.27	48.43	-8,573.88	591.59	577.46	391.05	186.41	3.098
21,300.00	12,582.94	20,855.36	12,199.79	120.89	119.62	48.43	-8,673.88	592.45	577.46	388.97	188.49	3.064
21,400.00	12,583.81	20,955.36	12,200.66	122.24	120.98	48.43	-8,773.87	593.32	577.46	386.90	190.56	3.030
21,500.00	12,584.69	21,055.36	12,201.53	123.59	122.33	48.43	-8,873.86	594.18	577.46	384.82	192.64	2.998
21,600.00	12,585.56	21,155.36	12,202.41	124.94	123.69	48.43	-8,973.85	595.04	577.46	382.74	194.72	2.966
21,700.00	12,586.43	21,255.36	12,203.28	126.29	125.04	48.43	-9,073.85	595.90	577.46	380.67	196.80	2.934
21,800.00	12,587.31	21,355.36	12,204.15	127.64	126.40	48.43	-9,173.84	596.76	577.47	378.59	198.88	2.904
21,900.00	12,588.18	21,455.36	12,205.02	128.99	127.76	48.43	-9,273.83	597.62	577.47	376.51	200.96	2.874
22,000.00	12,589.05	21,555.36	12,205.89	130.34	129.12	48.43	-9,373.82	598.48	577.47	374.42	203.05	2.844
22,100.00	12,589.93	21,655.36	12,206.76	131.70	130.47	48.43	-9,473.82	599.34	577.47	372.34	205.13	2.815
22,200.00	12,590.80	21,755.36	12,207.63	133.05	131.83	48.43	-9,573.81	600.20	577.47	370.26	207.22	2.787
22,300.00	12,591.67	21,855.36	12,208.51	134.40	133.19	48.43	-9,673.80	601.06	577.47	368.17	209.30	2.759
22,400.00	12,592.55	21,955.36	12,209.38	135.75	134.55	48.43	-9,773.79	601.93	577.48	366.09	211.39	2.732
22,500.00	12,593.42	22,055.36	12,210.25	137.11	135.91	48.43	-9,873.79	602.79	577.48	364.00	213.48	2.705
22,600.00	12,594.30	22,155.36	12,211.12	138.46	137.26	48.43	-9,973.78	603.65	577.48	361.91	215.57	2.679
22,700.00	12,595.17	22,255.36	12,211.99	139.81	138.62	48.43	-10,073.77	604.51	577.48	359.82	217.66	2.653
22,800.00	12,596.04	22,355.36	12,212.86	141.17	139.98	48.43	-10,173.76	605.37	577.48	357.73	219.75	2.628
22,807.53	12,596.11	22,362.89	12,212.93	141.27	140.08	48.43	-10,181.29	605.43	577.48	357.58	219.91	2.626
22,875.30	12,596.70	22,428.60	12,213.50	142.19	140.98	48.43	-10,247.00	606.00	577.49	356.22	221.27	2.610

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 16 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 133H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance				Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
0.00	0.00	2.00	0.00	0.50	0.50	69.74	856.00	2,319.00	2,471.94								
100.00	100.00	102.00	100.00	0.98	0.99	69.74	856.00	2,319.00	2,471.94	2,469.97	1.97	1,252.804					
200.00	200.00	202.00	200.00	1.56	1.57	69.74	856.00	2,319.00	2,471.94	2,468.81	3.13	789.618					
300.00	300.00	302.00	300.00	1.98	1.99	69.74	856.00	2,319.00	2,471.94	2,467.97	3.97	622.773					
400.00	400.00	402.00	400.00	2.33	2.34	69.74	856.00	2,319.00	2,471.94	2,467.28	4.66	529.900					
500.00	500.00	502.00	500.00	2.63	2.64	69.74	856.00	2,319.00	2,471.94	2,466.67	5.27	468.656					
600.00	600.00	602.00	600.00	2.91	2.92	69.74	856.00	2,319.00	2,471.94	2,466.12	5.83	424.353					
700.00	700.00	704.23	702.23	3.16	3.17	69.74	856.00	2,319.00	2,471.94	2,465.60	6.34	390.020					
800.00	800.00	915.26	913.15	3.40	3.74	69.82	850.99	2,315.59	2,469.60	2,462.51	7.10	348.027					
900.00	900.00	1,076.99	1,074.40	3.62	4.02	69.99	840.83	2,308.69	2,463.22	2,455.65	7.57	325.347					
1,000.00	1,000.00	1,176.60	1,173.63	3.76	4.19	-21.90	833.65	2,303.81	2,456.10	2,448.22	7.88	311.689					
1,100.00	1,099.98	1,302.94	1,299.46	4.00	4.34	-21.82	824.26	2,297.42	2,447.20	2,438.95	8.25	296.493					
1,200.00	1,199.88	1,507.46	1,502.29	4.24	4.82	-21.61	802.74	2,282.80	2,432.80	2,423.89	8.91	273.163					
1,300.00	1,299.63	1,610.65	1,604.22	4.46	4.97	-21.55	789.41	2,273.73	2,413.68	2,404.39	9.29	259.897					
1,400.00	1,399.25	1,708.32	1,700.69	4.60	5.16	-21.42	776.78	2,265.15	2,393.08	2,383.46	9.62	248.791					
1,500.00	1,498.87	1,805.99	1,797.15	4.78	5.35	-21.28	764.15	2,256.56	2,372.47	2,362.48	9.99	237.437					
1,600.00	1,598.49	1,903.66	1,893.62	4.96	5.54	-21.13	751.52	2,247.97	2,351.88	2,341.51	10.37	226.887					
1,700.00	1,698.11	2,001.33	1,990.09	5.14	5.73	-20.97	738.89	2,239.39	2,331.30	2,320.56	10.74	217.060					
1,800.00	1,797.73	2,098.99	2,086.55	5.32	5.92	-20.82	726.25	2,230.80	2,310.75	2,299.63	11.12	207.886					
1,900.00	1,897.34	2,196.66	2,183.02	5.49	6.11	-20.66	713.62	2,222.22	2,290.20	2,278.71	11.49	199.303					
2,000.00	1,996.96	2,294.33	2,279.49	5.67	6.30	-20.50	700.99	2,213.63	2,269.68	2,257.81	11.87	191.255					
2,100.00	2,096.58	2,392.00	2,375.95	5.85	6.50	-20.33	688.36	2,205.05	2,249.17	2,236.93	12.24	183.696					
2,200.00	2,196.20	2,489.67	2,472.42	6.04	6.69	-20.16	675.73	2,196.46	2,228.68	2,216.06	12.63	176.488					
2,300.00	2,295.72	2,587.07	2,568.62	6.23	6.88	-13.66	663.14	2,187.90	2,207.04	2,194.02	13.02	169.523					
2,400.00	2,394.97	2,683.85	2,664.21	6.43	7.07	-9.19	650.62	2,179.39	2,182.91	2,169.48	13.43	162.583					
2,500.00	2,493.89	2,779.95	2,759.13	6.64	7.26	-6.01	638.19	2,170.94	2,156.29	2,142.46	13.84	155.851					
2,600.00	2,592.40	2,875.29	2,853.30	6.85	7.45	-3.61	625.86	2,162.56	2,127.23	2,112.98	14.24	149.336					
2,700.00	2,690.45	2,969.82	2,946.67	7.07	7.65	-1.68	613.64	2,154.25	2,095.73	2,081.08	14.65	143.007					
2,800.00	2,787.96	3,063.47	3,039.17	7.28	7.86	-0.08	601.52	2,146.02	2,061.84	2,046.77	15.06	136.901					
2,900.00	2,884.87	3,156.18	3,130.73	7.49	8.07	1.29	589.54	2,137.87	2,025.57	2,010.10	15.47	130.977					
3,000.00	2,981.46	3,248.40	3,221.82	7.68	8.27	1.60	577.61	2,129.77	1,988.18	1,972.34	15.84	125.496					
3,100.00	3,078.05	3,340.63	3,312.91	7.87	8.48	1.91	565.68	2,121.66	1,950.84	1,934.62	16.22	120.253					
3,200.00	3,174.64	3,432.85	3,404.00	8.06	8.68	2.23	553.75	2,113.55	1,913.56	1,896.95	16.61	115.235					
3,300.00	3,271.24	3,525.07	3,495.09	8.26	8.89	2.57	541.83	2,105.44	1,876.33	1,859.34	16.99	110.431					
3,400.00	3,367.83	3,617.30	3,586.18	8.51	9.10	2.92	529.90	2,097.34	1,839.16	1,821.78	17.38	105.829					
3,500.00	3,464.42	3,709.52	3,677.27	8.80	9.31	3.29	517.97	2,089.23	1,802.05	1,784.29	17.77	101.419					
3,600.00	3,561.01	3,801.75	3,768.36	9.09	9.51	3.67	506.05	2,081.12	1,765.01	1,746.85	18.16	97.190					
3,700.00	3,657.60	3,893.97	3,859.45	9.38	9.72	4.06	494.12	2,073.02	1,728.04	1,709.49	18.55	93.133					
3,800.00	3,754.20	3,986.20	3,950.54	9.68	9.93	4.48	482.19	2,064.91	1,691.15	1,672.20	18.95	89.238					
3,900.00	3,850.79	4,078.42	4,041.63	9.98	10.14	4.91	470.27	2,056.80	1,654.34	1,634.99	19.35	85.498					
4,000.00	3,947.38	4,170.64	4,132.72	10.28	10.35	5.36	458.34	2,048.70	1,617.61	1,597.86	19.75	81.904					
4,100.00	4,043.97	4,262.87	4,223.81	10.59	10.56	5.83	446.41	2,040.59	1,580.98	1,560.82	20.15	78.450					
4,200.00	4,140.56	4,355.09	4,314.90	10.90	10.76	6.33	434.49	2,032.48	1,544.44	1,523.88	20.56	75.128					
4,300.00	4,237.16	4,447.32	4,405.99	11.21	10.97	6.84	422.56	2,024.37	1,508.01	1,487.05	20.96	71.931					
4,400.00	4,333.75	4,539.54	4,497.08	11.52	11.18	7.38	410.63	2,016.27	1,471.70	1,450.32	21.37	68.854					
4,500.00	4,430.34	4,631.76	4,588.16	11.84	11.39	7.95	398.71	2,008.16	1,435.50	1,413.72	21.79	65.892					
4,600.00	4,526.93	4,723.99	4,679.25	12.16	11.60	8.55	386.78	2,000.05	1,399.44	1,377.24	22.20	63.037					
4,700.00	4,623.53	4,816.21	4,770.34	12.48	11.81	9.18	374.85	1,991.95	1,363.52	1,340.91	22.62	60.287					
4,800.00	4,720.12	4,908.44	4,861.43	12.80	12.02	9.84	362.93	1,983.84	1,327.76	1,304.72	23.04	57.635					
4,900.00	4,816.71	5,000.66	4,952.52	13.12	12.23	10.54	351.00	1,975.73	1,292.16	1,268.70	23.46	55.079					
5,000.00	4,913.30	5,092.88	5,043.61	13.45	12.44	11.27	339.07	1,967.63	1,256.75	1,232.86	23.89	52.612					
5,100.00	5,009.89	5,185.11	5,134.70	13.78	12.65	12.05	327.15	1,959.52	1,221.53	1,197.21	24.32	50.233					

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 17 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 133H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5) Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
5,200.00	5,106.49	5,277.33	5,225.79	14.10	12.86	12.87	315.22	1,951.41	1,186.52	1,161.77	24.75	47.937	
5,300.00	5,203.08	5,369.56	5,316.88	14.43	13.06	13.74	303.29	1,943.31	1,151.75	1,126.57	25.18	45.746	
5,400.00	5,299.67	5,448.21	5,394.68	14.75	13.21	14.48	293.72	1,936.80	1,117.78	1,092.19	25.59	43.683	
5,500.00	5,396.65	5,527.85	5,473.67	15.07	13.37	15.06	285.38	1,931.13	1,086.63	1,060.60	26.03	41.749	
5,600.00	5,494.23	5,609.25	5,554.62	15.36	13.52	15.59	278.26	1,926.29	1,059.31	1,032.86	26.45	40.049	
5,700.00	5,592.35	5,692.21	5,637.28	15.62	13.66	16.05	272.47	1,922.36	1,035.81	1,008.96	26.85	38.574	
5,800.00	5,690.94	5,776.51	5,721.41	15.86	13.77	16.43	268.12	1,919.40	1,016.14	988.91	27.23	37.316	
5,900.00	5,789.93	5,861.91	5,806.74	16.07	13.87	16.72	265.27	1,917.46	1,000.27	972.69	27.58	36.266	
6,000.00	5,889.26	5,948.16	5,892.97	16.25	13.94	16.91	264.00	1,916.60	988.21	960.33	27.88	35.449	
6,100.00	5,988.86	6,044.05	5,988.86	16.41	13.96	17.02	263.93	1,916.55	979.62	951.52	28.10	34.863	
6,200.00	6,088.66	6,143.84	6,088.66	16.53	13.99	17.11	263.93	1,916.55	973.58	945.27	28.31	34.388	
6,300.00	6,188.59	6,243.77	6,188.59	16.64	14.03	17.15	263.93	1,916.55	970.04	941.53	28.51	34.027	
6,400.00	6,288.58	6,343.76	6,288.58	16.71	14.06	89.59	263.93	1,916.55	968.99	940.37	28.63	33.848	
6,500.00	6,388.58	6,443.76	6,388.58	16.76	14.09	89.59	263.93	1,916.55	968.99	940.27	28.72	33.740	
6,600.00	6,488.58	6,543.76	6,488.58	16.82	14.13	89.59	263.93	1,916.55	968.99	940.18	28.81	33.632	
6,700.00	6,588.58	6,643.76	6,588.58	16.88	14.16	89.59	263.93	1,916.55	968.99	940.09	28.91	33.523	
6,800.00	6,688.58	6,743.76	6,688.58	16.94	14.20	89.59	263.93	1,916.55	968.99	940.00	29.00	33.415	
6,900.00	6,788.58	6,843.76	6,788.58	17.00	14.24	89.59	263.93	1,916.55	968.99	939.90	29.09	33.306	
7,000.00	6,888.58	6,943.76	6,888.58	17.05	14.27	89.59	263.93	1,916.55	968.99	939.81	29.19	33.198	
7,100.00	6,988.58	7,043.76	6,988.58	17.11	14.31	89.59	263.93	1,916.55	968.99	939.71	29.28	33.089	
7,200.00	7,088.58	7,143.76	7,088.58	17.17	14.35	89.59	263.93	1,916.55	968.99	939.61	29.38	32.981	
7,300.00	7,188.58	7,243.76	7,188.58	17.23	14.38	89.59	263.93	1,916.55	968.99	939.52	29.48	32.873	
7,400.00	7,288.58	7,343.76	7,288.58	17.29	14.42	89.59	263.93	1,916.55	968.99	939.42	29.57	32.765	
7,500.00	7,388.58	7,443.76	7,388.58	17.35	14.46	89.59	263.93	1,916.55	968.99	939.32	29.67	32.657	
7,600.00	7,488.58	7,543.76	7,488.58	17.41	14.50	89.59	263.93	1,916.55	968.99	939.22	29.77	32.549	
7,700.00	7,588.58	7,643.76	7,588.58	17.47	14.54	89.59	263.93	1,916.55	968.99	939.12	29.87	32.441	
7,800.00	7,688.58	7,743.76	7,688.58	17.53	14.58	89.59	263.93	1,916.55	968.99	939.03	29.97	32.333	
7,900.00	7,788.58	7,843.76	7,788.58	17.59	14.62	89.59	263.93	1,916.55	968.99	938.92	30.07	32.225	
8,000.00	7,888.58	7,943.76	7,888.58	17.65	14.66	89.59	263.93	1,916.55	968.99	938.82	30.17	32.118	
8,100.00	7,988.58	8,043.76	7,988.58	17.71	14.70	89.59	263.93	1,916.55	968.99	938.72	30.27	32.010	
8,200.00	8,088.58	8,143.76	8,088.58	17.77	14.74	89.59	263.93	1,916.55	968.99	938.62	30.37	31.903	
8,300.00	8,188.58	8,243.76	8,188.58	17.83	14.78	89.59	263.93	1,916.55	968.99	938.52	30.48	31.796	
8,400.00	8,288.58	8,343.76	8,288.58	17.89	14.82	89.59	263.93	1,916.55	968.99	938.42	30.58	31.689	
8,500.00	8,388.58	8,443.76	8,388.58	17.95	14.86	89.59	263.93	1,916.55	968.99	938.31	30.68	31.583	
8,600.00	8,488.58	8,543.76	8,488.58	18.02	14.90	89.59	263.93	1,916.55	968.99	938.21	30.78	31.476	
8,700.00	8,588.58	8,643.76	8,588.58	18.08	14.95	89.59	263.93	1,916.55	968.99	938.11	30.89	31.370	
8,800.00	8,688.58	8,743.76	8,688.58	18.14	14.99	89.59	263.93	1,916.55	968.99	938.00	30.99	31.264	
8,900.00	8,788.58	8,843.76	8,788.58	18.20	15.03	89.59	263.93	1,916.55	968.99	937.90	31.10	31.158	
9,000.00	8,888.58	8,943.76	8,888.58	18.26	15.08	89.59	263.93	1,916.55	968.99	937.79	31.20	31.053	
9,100.00	8,988.58	9,043.76	8,988.58	18.32	15.12	89.59	263.93	1,916.55	968.99	937.68	31.31	30.947	
9,200.00	9,088.58	9,143.76	9,088.58	18.39	15.17	89.59	263.93	1,916.55	968.99	937.58	31.42	30.842	
9,300.00	9,188.58	9,243.76	9,188.58	18.45	15.21	89.59	263.93	1,916.55	968.99	937.47	31.53	30.737	
9,400.00	9,288.58	9,343.76	9,288.58	18.51	15.26	89.59	263.93	1,916.55	968.99	937.36	31.63	30.633	
9,500.00	9,388.58	9,443.76	9,388.58	18.57	15.30	89.59	263.93	1,916.55	968.99	937.25	31.74	30.528	
9,600.00	9,488.58	9,543.76	9,488.58	18.64	15.35	89.59	263.93	1,916.55	968.99	937.14	31.85	30.424	
9,700.00	9,588.58	9,643.76	9,588.58	18.70	15.39	89.59	263.93	1,916.55	968.99	937.04	31.96	30.320	
9,800.00	9,688.58	9,743.76	9,688.58	18.76	15.44	89.59	263.93	1,916.55	968.99	936.93	32.07	30.217	
9,900.00	9,788.58	9,843.76	9,788.58	18.83	15.49	89.59	263.93	1,916.55	968.99	936.82	32.18	30.114	
10,000.00	9,888.58	9,943.76	9,888.58	18.89	15.53	89.59	263.93	1,916.55	968.99	936.71	32.29	30.011	
10,100.00	9,988.58	10,043.76	9,988.58	18.95	15.58	89.59	263.93	1,916.55	968.99	936.60	32.40	29.908	
10,200.00	10,088.58	10,143.76	10,088.58	19.02	15.63	89.59	263.93	1,916.55	968.99	936.48	32.51	29.805	
10,300.00	10,188.58	10,243.76	10,188.58	19.08	15.68	89.59	263.93	1,916.55	968.99	936.37	32.62	29.703	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 18 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 133H - OH - Plan 1													Offset Site Error:	0.00 usft
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Rule Assigned:					Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Distance Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,400.00	10,288.58	10,343.76	10,288.58	19.15	15.73	89.59	263.93	1,916.55	968.99	936.26	32.73	29.602		
10,500.00	10,388.58	10,443.76	10,388.58	19.21	15.77	89.59	263.93	1,916.55	968.99	936.15	32.85	29.500		
10,600.00	10,488.58	10,543.76	10,488.58	19.27	15.82	89.59	263.93	1,916.55	968.99	936.03	32.96	29.399		
10,700.00	10,588.58	10,643.76	10,588.58	19.34	15.87	89.59	263.93	1,916.55	968.99	935.92	33.07	29.298		
10,800.00	10,688.58	10,743.76	10,688.58	19.40	15.92	89.59	263.93	1,916.55	968.99	935.81	33.19	29.198		
10,900.00	10,788.58	10,843.76	10,788.58	19.47	15.97	89.59	263.93	1,916.55	968.99	935.69	33.30	29.098		
11,000.00	10,888.58	10,943.76	10,888.58	19.53	16.02	89.59	263.93	1,916.55	968.99	935.58	33.42	28.998		
11,100.00	10,988.58	11,043.76	10,988.58	19.60	16.07	89.59	263.93	1,916.55	968.99	935.46	33.53	28.898		
11,200.00	11,088.58	11,143.76	11,088.58	19.66	16.12	89.59	263.93	1,916.55	968.99	935.35	33.65	28.799		
11,300.00	11,188.58	11,243.76	11,188.58	19.73	16.18	89.59	263.93	1,916.55	968.99	935.23	33.76	28.700		
11,400.00	11,288.58	11,343.76	11,288.58	19.79	16.23	89.59	263.93	1,916.55	968.99	935.12	33.88	28.602		
11,500.00	11,388.58	11,443.76	11,388.58	19.86	16.28	89.59	263.93	1,916.55	968.99	935.00	34.00	28.504		
11,600.00	11,488.58	11,543.76	11,488.58	19.92	16.32	89.59	263.93	1,916.55	968.99	934.89	34.10	28.416		
11,700.00	11,588.58	11,649.05	11,593.41	19.99	16.47	90.08	255.76	1,916.30	968.73	934.49	34.25	28.286		
11,800.00	11,688.58	11,748.69	11,689.68	20.05	16.71	91.57	230.58	1,915.53	968.31	933.79	34.52	28.047		
11,809.52	11,698.09	11,757.65	11,698.09	20.06	16.74	91.75	227.50	1,915.44	968.31	933.75	34.56	28.019	CC	
11,900.00	11,788.58	11,837.41	11,770.59	20.12	16.98	93.71	194.42	1,914.43	969.04	934.13	34.91	27.756		
12,000.00	11,888.58	11,913.43	11,834.78	20.19	17.27	96.10	153.82	1,913.19	972.60	937.20	35.40	27.474		
12,100.00	11,988.51	11,978.36	11,884.95	20.25	17.57	-80.62	112.68	1,911.93	980.22	944.27	35.95	27.264		
12,200.00	12,086.82	12,040.05	11,928.01	20.31	17.91	-77.55	68.57	1,910.58	990.29	953.72	36.57	27.077		
12,300.00	12,180.57	12,100.00	11,965.08	20.35	18.29	-74.67	21.51	1,909.14	1,001.49	964.22	37.27	26.872		
12,400.00	12,266.93	12,159.18	11,996.66	20.39	18.73	-72.04	-28.50	1,907.62	1,012.80	974.76	38.04	26.625		
12,500.00	12,343.26	12,217.33	12,022.50	20.44	19.20	-69.77	-80.53	1,906.03	1,023.31	984.45	38.87	26.328		
12,600.00	12,407.24	12,274.85	12,042.73	20.52	19.70	-67.90	-134.33	1,904.38	1,032.25	992.51	39.74	25.974		
12,700.00	12,456.94	12,331.91	12,057.38	20.67	20.23	-66.48	-189.43	1,902.70	1,038.99	998.34	40.65	25.560		
12,800.00	12,490.84	12,388.66	12,066.44	20.88	20.78	-65.53	-245.39	1,900.99	1,043.04	1,001.47	41.57	25.090		
12,900.00	12,507.91	12,448.18	12,069.94	21.18	21.38	-65.06	-304.76	1,899.17	1,044.11	1,001.60	42.51	24.561		
13,000.00	12,510.43	12,519.34	12,070.44	21.56	22.12	-65.02	-375.90	1,897.89	1,042.38	998.89	43.48	23.973		
13,055.07	12,510.91	12,561.66	12,070.74	21.80	22.57	-65.01	-418.22	1,897.96	1,042.06	997.99	44.08	23.641		
13,100.00	12,511.30	12,605.38	12,071.04	22.01	23.03	-65.01	-461.94	1,898.35	1,042.12	997.49	44.63	23.352		
13,200.00	12,512.18	12,705.38	12,071.74	22.52	24.12	-65.00	-561.94	1,899.26	1,042.23	996.27	45.96	22.678		
13,300.00	12,513.05	12,805.38	12,072.44	23.10	25.23	-64.99	-661.93	1,900.17	1,042.35	994.96	47.38	21.998		
13,400.00	12,513.92	12,905.38	12,073.14	23.73	26.37	-64.99	-761.92	1,901.07	1,042.46	993.57	48.89	21.320		
13,500.00	12,514.80	13,005.38	12,073.83	24.41	27.53	-64.98	-861.92	1,901.98	1,042.58	992.09	50.49	20.651		
13,600.00	12,515.67	13,105.38	12,074.53	25.15	28.71	-64.97	-961.91	1,902.89	1,042.69	990.54	52.15	19.995		
13,700.00	12,516.55	13,205.38	12,075.23	25.93	29.90	-64.96	-1,061.90	1,903.79	1,042.81	988.93	53.88	19.355		
13,800.00	12,517.42	13,305.38	12,075.93	26.76	31.11	-64.96	-1,161.90	1,904.70	1,042.92	987.26	55.67	18.735		
13,900.00	12,518.29	13,405.38	12,076.63	27.63	32.33	-64.95	-1,261.89	1,905.61	1,043.04	985.53	57.51	18.137		
14,000.00	12,519.17	13,505.38	12,077.33	28.53	33.56	-64.94	-1,361.88	1,906.51	1,043.16	983.76	59.40	17.562		
14,100.00	12,520.04	13,605.38	12,078.02	29.47	34.80	-64.93	-1,461.88	1,907.42	1,043.27	981.93	61.34	17.009		
14,200.00	12,520.91	13,705.38	12,078.72	30.44	36.05	-64.92	-1,561.87	1,908.33	1,043.39	980.07	63.31	16.480		
14,300.00	12,521.79	13,805.38	12,079.42	31.44	37.30	-64.92	-1,661.86	1,909.23	1,043.50	978.17	65.33	15.973		
14,400.00	12,522.66	13,905.38	12,080.12	32.46	38.57	-64.91	-1,761.86	1,910.14	1,043.62	976.24	67.38	15.490		
14,500.00	12,523.53	14,005.38	12,080.82	33.51	39.84	-64.90	-1,861.85	1,911.05	1,043.73	974.28	69.45	15.028		
14,600.00	12,524.41	14,105.38	12,081.52	34.58	41.12	-64.89	-1,961.84	1,911.96	1,043.85	972.29	71.56	14.587		
14,700.00	12,525.28	14,205.38	12,082.21	35.67	42.40	-64.89	-2,061.84	1,912.86	1,043.97	970.27	73.69	14.167		
14,800.00	12,526.16	14,305.38	12,082.91	36.78	43.69	-64.88	-2,161.83	1,913.77	1,044.08	968.23	75.85	13.766		
14,900.00	12,527.03	14,405.38	12,083.61	37.90	44.98	-64.87	-2,261.82	1,914.68	1,044.20	966.17	78.02	13.383		
15,000.00	12,527.90	14,505.38	12,084.31	39.04	46.28	-64.86	-2,361.81	1,915.58	1,044.31	964.09	80.22	13.018		
15,100.00	12,528.78	14,605.38	12,085.01	40.20	47.58	-64.86	-2,461.81	1,916.49	1,044.43	962.00	82.43	12.670		
15,200.00	12,529.65	14,705.38	12,085.70	41.37	48.88	-64.85	-2,561.80	1,917.40	1,044.54	959.88	84.66	12.338		
15,300.00	12,530.52	14,805.38	12,086.40	42.55	50.19	-64.84	-2,661.79	1,918.30	1,044.66	957.75	86.91	12.020		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 133H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:						Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Offset Wellbore Centre				Distance		Separation		Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
15,400.00	12,531.40	14,905.38	12,087.10	43.74	51.50	-64.83	-2,761.79	1,919.21	1,044.78	955.61	89.17	11.717		
15,500.00	12,532.27	15,005.38	12,087.80	44.94	52.82	-64.83	-2,861.78	1,920.12	1,044.89	953.45	91.44	11.427		
15,600.00	12,533.14	15,105.38	12,088.50	46.15	54.13	-64.82	-2,961.77	1,921.02	1,045.01	951.29	93.72	11.150		
15,700.00	12,534.02	15,205.38	12,089.20	47.37	55.45	-64.81	-3,061.77	1,921.93	1,045.12	949.11	96.02	10.885		
15,800.00	12,534.89	15,305.38	12,089.89	48.59	56.77	-64.80	-3,161.76	1,922.84	1,045.24	946.92	98.32	10.631		
15,900.00	12,535.76	15,405.38	12,090.59	49.83	58.10	-64.79	-3,261.75	1,923.74	1,045.36	944.72	100.64	10.387		
16,000.00	12,536.64	15,505.38	12,091.29	51.07	59.42	-64.79	-3,361.75	1,924.65	1,045.47	942.51	102.96	10.154		
16,100.00	12,537.51	15,605.38	12,091.99	52.32	60.75	-64.78	-3,461.74	1,925.56	1,045.59	940.30	105.29	9.930		
16,200.00	12,538.39	15,705.38	12,092.69	53.57	62.08	-64.77	-3,561.73	1,926.46	1,045.70	938.07	107.63	9.716		
16,300.00	12,539.26	15,805.38	12,093.39	54.83	63.41	-64.76	-3,661.73	1,927.37	1,045.82	935.84	109.98	9.509		
16,400.00	12,540.13	15,905.38	12,094.08	56.09	64.74	-64.76	-3,761.72	1,928.28	1,045.94	933.61	112.33	9.311		
16,500.00	12,541.01	16,005.38	12,094.78	57.36	66.08	-64.75	-3,861.71	1,929.18	1,046.05	931.36	114.69	9.121		
16,600.00	12,541.88	16,105.38	12,095.48	58.64	67.41	-64.74	-3,961.71	1,930.09	1,046.17	929.11	117.05	8.937		
16,700.00	12,542.75	16,205.38	12,096.18	59.91	68.75	-64.73	-4,061.70	1,931.00	1,046.28	926.86	119.42	8.761		
16,800.00	12,543.63	16,305.38	12,096.88	61.20	70.09	-64.73	-4,161.69	1,931.90	1,046.40	924.60	121.80	8.591		
16,900.00	12,544.50	16,405.38	12,097.58	62.48	71.43	-64.72	-4,261.69	1,932.81	1,046.52	922.34	124.18	8.427		
17,000.00	12,545.37	16,505.38	12,098.27	63.77	72.77	-64.71	-4,361.68	1,933.72	1,046.63	920.07	126.57	8.269		
17,100.00	12,546.25	16,605.38	12,098.97	65.06	74.11	-64.70	-4,461.67	1,934.63	1,046.75	917.79	128.95	8.117		
17,200.00	12,547.12	16,705.38	12,099.67	66.36	75.45	-64.70	-4,561.67	1,935.53	1,046.86	915.52	131.35	7.970		
17,300.00	12,547.99	16,805.38	12,100.37	67.66	76.79	-64.69	-4,661.66	1,936.44	1,046.98	913.24	133.74	7.828		
17,400.00	12,548.87	16,905.38	12,101.07	68.96	78.14	-64.68	-4,761.65	1,937.35	1,047.10	910.95	136.15	7.691		
17,500.00	12,549.74	17,005.38	12,101.76	70.26	79.48	-64.67	-4,861.65	1,938.25	1,047.21	908.66	138.55	7.558		
17,600.00	12,550.62	17,105.38	12,102.46	71.57	80.83	-64.67	-4,961.64	1,939.16	1,047.33	906.37	140.96	7.430		
17,700.00	12,551.49	17,205.38	12,103.16	72.88	82.18	-64.66	-5,061.63	1,940.07	1,047.45	904.08	143.37	7.306		
17,800.00	12,552.36	17,305.38	12,103.86	74.19	83.52	-64.65	-5,161.63	1,940.97	1,047.56	901.78	145.78	7.186		
17,900.00	12,553.24	17,405.38	12,104.56	75.50	84.87	-64.64	-5,261.62	1,941.88	1,047.68	899.48	148.19	7.070		
18,000.00	12,554.11	17,505.38	12,105.26	76.81	86.22	-64.63	-5,361.61	1,942.79	1,047.79	897.18	150.61	6.957		
18,100.00	12,554.98	17,605.38	12,105.95	78.13	87.57	-64.63	-5,461.61	1,943.69	1,047.91	894.88	153.03	6.848		
18,200.00	12,555.86	17,705.38	12,106.65	79.45	88.92	-64.62	-5,561.60	1,944.60	1,048.03	892.57	155.45	6.742		
18,300.00	12,556.73	17,805.38	12,107.35	80.77	90.27	-64.61	-5,661.59	1,945.51	1,048.14	890.27	157.88	6.639		
18,400.00	12,557.60	17,905.38	12,108.05	82.09	91.62	-64.60	-5,761.59	1,946.41	1,048.26	887.95	160.31	6.539		
18,500.00	12,558.48	18,005.38	12,108.75	83.42	92.97	-64.60	-5,861.58	1,947.32	1,048.38	885.64	162.73	6.442		
18,600.00	12,559.35	18,105.38	12,109.45	84.74	94.33	-64.59	-5,961.57	1,948.23	1,048.49	883.33	165.16	6.348		
18,700.00	12,560.23	18,205.38	12,110.14	86.07	95.68	-64.58	-6,061.57	1,949.13	1,048.61	881.01	167.60	6.257		
18,800.00	12,561.10	18,305.37	12,110.84	87.40	97.03	-64.57	-6,161.56	1,950.04	1,048.73	878.70	170.03	6.168		
18,900.00	12,561.97	18,405.37	12,111.54	88.72	98.38	-64.57	-6,261.55	1,950.95	1,048.84	876.38	172.47	6.081		
19,000.00	12,562.85	18,505.37	12,112.24	90.05	99.74	-64.56	-6,361.55	1,951.85	1,048.96	874.06	174.90	5.997		
19,100.00	12,563.72	18,605.37	12,112.94	91.39	101.09	-64.55	-6,461.54	1,952.76	1,049.08	871.74	177.34	5.916		
19,200.00	12,564.59	18,705.37	12,113.63	92.72	102.45	-64.54	-6,561.53	1,953.67	1,049.19	869.41	179.78	5.836		
19,300.00	12,565.47	18,805.37	12,114.33	94.05	103.80	-64.54	-6,661.53	1,954.58	1,049.31	867.09	182.22	5.758		
19,400.00	12,566.34	18,905.37	12,115.03	95.39	105.16	-64.53	-6,761.52	1,955.48	1,049.43	864.76	184.66	5.683		
19,500.00	12,567.21	19,005.37	12,115.73	96.72	106.51	-64.52	-6,861.51	1,956.39	1,049.54	862.44	187.11	5.609		
19,600.00	12,568.09	19,105.37	12,116.43	98.06	107.87	-64.51	-6,961.51	1,957.30	1,049.66	860.11	189.55	5.538		
19,700.00	12,568.96	19,205.37	12,117.13	99.40	109.23	-64.51	-7,061.50	1,958.20	1,049.78	857.78	192.00	5.468		
19,800.00	12,569.83	19,305.37	12,117.82	100.73	110.58	-64.50	-7,161.49	1,959.11	1,049.89	855.45	194.44	5.400		
19,900.00	12,570.71	19,405.37	12,118.52	102.07	111.94	-64.49	-7,261.49	1,960.02	1,050.01	853.12	196.89	5.333		
20,000.00	12,571.58	19,505.37	12,119.22	103.41	113.30	-64.48	-7,361.48	1,960.92	1,050.13	850.79	199.34	5.268		
20,100.00	12,572.46	19,605.37	12,119.92	104.75	114.66	-64.48	-7,461.47	1,961.83	1,050.24	848.46	201.79	5.205		
20,200.00	12,573.33	19,705.37	12,120.62	106.10	116.01	-64.47	-7,561.47	1,962.74	1,050.36	846.12	204.24	5.143		
20,300.00	12,574.20	19,805.37	12,121.32	107.44	117.37	-64.46	-7,661.46	1,963.64	1,050.48	843.79	206.69	5.082		
20,400.00	12,575.08	19,905.37	12,122.01	108.78	118.73	-64.45	-7,761.45	1,964.55	1,050.59	841.46	209.14	5.023		
20,500.00	12,575.95	20,005.37	12,122.71	110.12	120.09	-64.45	-7,861.45	1,965.46	1,050.71	839.12	211.59	4.966		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 20 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 133H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned:		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)			
20,600.00	12,576.82	20,105.37	12,123.41	111.47	121.45	-64.44	-7,961.44	1,966.36	1,050.83	836.78	214.04	4.909			
20,700.00	12,577.70	20,205.37	12,124.11	112.81	122.81	-64.43	-8,061.43	1,967.27	1,050.94	834.45	216.50	4.854			
20,800.00	12,578.57	20,305.37	12,124.81	114.16	124.17	-64.42	-8,161.43	1,968.18	1,051.06	832.11	218.95	4.800			
20,900.00	12,579.44	20,405.37	12,125.50	115.51	125.53	-64.42	-8,261.42	1,969.08	1,051.18	829.77	221.40	4.748			
21,000.00	12,580.32	20,505.37	12,126.20	116.85	126.89	-64.41	-8,361.41	1,969.99	1,051.29	827.44	223.86	4.696			
21,100.00	12,581.19	20,605.37	12,126.90	118.20	128.25	-64.40	-8,461.41	1,970.90	1,051.41	825.10	226.31	4.646			
21,200.00	12,582.06	20,705.37	12,127.60	119.55	129.61	-64.39	-8,561.40	1,971.80	1,051.53	822.76	228.77	4.596			
21,300.00	12,582.94	20,805.37	12,128.30	120.89	130.97	-64.39	-8,661.39	1,972.71	1,051.64	820.42	231.23	4.548			
21,400.00	12,583.81	20,905.37	12,129.00	122.24	132.33	-64.38	-8,761.39	1,973.62	1,051.76	818.08	233.68	4.501			
21,500.00	12,584.69	21,005.37	12,129.69	123.59	133.69	-64.37	-8,861.38	1,974.52	1,051.88	815.74	236.14	4.454			
21,600.00	12,585.56	21,105.37	12,130.39	124.94	135.05	-64.36	-8,961.37	1,975.43	1,052.00	813.40	238.60	4.409			
21,700.00	12,586.43	21,205.37	12,131.09	126.29	136.41	-64.35	-9,061.37	1,976.34	1,052.11	811.06	241.06	4.365			
21,800.00	12,587.31	21,305.37	12,131.79	127.64	137.77	-64.35	-9,161.36	1,977.25	1,052.23	808.71	243.52	4.321			
21,900.00	12,588.18	21,405.37	12,132.49	128.99	139.14	-64.34	-9,261.35	1,978.15	1,052.35	806.37	245.97	4.278			
22,000.00	12,589.05	21,505.37	12,133.19	130.34	140.50	-64.33	-9,361.35	1,979.06	1,052.46	804.03	248.43	4.236			
22,100.00	12,589.93	21,605.37	12,133.88	131.70	141.86	-64.32	-9,461.34	1,979.97	1,052.58	801.69	250.89	4.195			
22,200.00	12,590.80	21,705.37	12,134.58	133.05	143.22	-64.32	-9,561.33	1,980.87	1,052.70	799.35	253.35	4.155			
22,300.00	12,591.67	21,805.37	12,135.28	134.40	144.58	-64.31	-9,661.33	1,981.78	1,052.82	797.00	255.81	4.116			
22,400.00	12,592.55	21,905.37	12,135.98	135.75	145.95	-64.30	-9,761.32	1,982.69	1,052.93	794.66	258.27	4.077			
22,500.00	12,593.42	22,005.37	12,136.68	137.11	147.31	-64.29	-9,861.31	1,983.59	1,053.05	792.32	260.73	4.039			
22,600.00	12,594.30	22,105.37	12,137.38	138.46	148.67	-64.29	-9,961.30	1,984.50	1,053.17	789.97	263.19	4.001			
22,700.00	12,595.17	22,205.37	12,138.07	139.81	150.03	-64.28	-10,061.30	1,985.41	1,053.28	787.63	265.65	3.965			
22,800.00	12,596.04	22,305.37	12,138.77	141.17	151.40	-64.27	-10,161.29	1,986.31	1,053.40	785.29	268.12	3.929			
22,875.30	12,596.70	22,380.67	12,139.30	142.19	152.42	-64.27	-10,236.59	1,987.00	1,053.49	783.52	269.97	3.902	ES, SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 134H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Rule Assigned:		Offset Site Error:		Offset Well Error:						
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Minimum Separation (usft)	Separation Factor	Warning
0.00	0.00	0.00	0.00	0.50	0.50	73.29	696.00	2,319.00	2,421.19			
100.00	100.00	100.00	100.00	0.98	0.98	73.29	696.00	2,319.00	2,421.19	2,419.23	1.96	1,233.928
200.00	200.00	200.00	200.00	1.56	1.56	73.29	696.00	2,319.00	2,421.19	2,418.07	3.12	775.464
300.00	300.00	300.00	300.00	1.98	1.98	73.29	696.00	2,319.00	2,421.19	2,417.23	3.96	611.055
400.00	400.00	400.00	400.00	2.33	2.33	73.29	696.00	2,319.00	2,421.19	2,416.53	4.66	519.700
500.00	500.00	500.00	500.00	2.63	2.63	73.29	696.00	2,319.00	2,421.19	2,415.92	5.27	459.514
600.00	600.00	600.00	600.00	2.91	2.91	73.29	696.00	2,319.00	2,421.19	2,415.37	5.82	416.003
700.00	700.00	700.00	700.00	3.16	3.16	73.29	696.00	2,319.00	2,421.19	2,414.87	6.33	382.641
800.00	800.00	800.00	800.00	3.40	3.40	73.29	696.00	2,319.00	2,421.19	2,414.39	6.80	355.996
900.00	900.00	900.00	900.00	3.62	3.62	73.29	696.00	2,319.00	2,421.19	2,413.95	7.25	334.070
1,000.00	1,000.00	1,000.00	1,000.00	3.76	3.84	-18.71	696.00	2,319.00	2,421.14	2,413.55	7.60	318.757
1,100.00	1,099.98	1,099.98	1,099.98	4.00	4.04	-18.73	696.00	2,319.00	2,419.41	2,411.37	8.03	301.126
1,200.00	1,199.88	1,199.88	1,199.88	4.24	4.23	-18.78	696.00	2,319.00	2,415.19	2,406.74	8.46	285.565
1,300.00	1,299.63	1,299.63	1,299.63	4.46	4.42	-18.87	696.00	2,319.00	2,408.51	2,399.64	8.87	271.604
1,400.00	1,399.25	1,410.23	1,410.23	4.60	4.52	-18.94	695.53	2,319.00	2,400.17	2,391.07	9.10	263.888
1,500.00	1,498.87	1,531.96	1,531.89	4.78	4.74	-18.93	691.67	2,319.00	2,391.01	2,381.56	9.45	253.034
1,600.00	1,598.49	1,653.35	1,653.03	4.96	4.94	-18.84	683.96	2,319.00	2,380.93	2,371.15	9.78	243.456
1,700.00	1,698.11	1,732.83	1,732.21	5.14	5.03	-18.73	677.05	2,319.30	2,370.60	2,360.55	10.05	235.921
1,800.00	1,797.73	1,800.00	1,799.07	5.32	5.13	-18.62	670.74	2,320.69	2,361.62	2,351.27	10.34	228.303
1,900.00	1,897.34	1,864.66	1,863.36	5.49	5.23	-18.49	664.32	2,323.09	2,354.07	2,343.45	10.62	221.581
2,000.00	1,996.96	1,930.62	1,928.87	5.67	5.34	-18.35	657.42	2,326.60	2,347.97	2,337.06	10.91	215.263
2,100.00	2,096.58	2,008.56	2,006.13	5.85	5.47	-18.16	648.83	2,332.14	2,343.36	2,332.15	11.21	208.959
2,200.00	2,196.20	2,089.87	2,086.64	6.04	5.59	-17.96	639.60	2,338.70	2,339.65	2,328.14	11.51	203.326
2,300.00	2,295.72	2,189.18	2,184.99	6.23	5.74	-11.40	628.33	2,346.72	2,334.87	2,323.02	11.85	197.045
2,400.00	2,394.97	2,288.28	2,283.12	6.43	5.89	-6.88	617.09	2,354.72	2,327.57	2,315.36	12.21	190.580
2,500.00	2,493.89	2,387.10	2,380.99	6.64	6.05	-3.66	605.88	2,362.70	2,317.78	2,305.20	12.58	184.189
2,600.00	2,592.40	2,485.59	2,478.51	6.85	6.21	-1.21	594.71	2,370.65	2,305.50	2,292.54	12.96	177.911
2,700.00	2,690.45	2,583.65	2,575.62	7.07	6.37	0.76	583.58	2,378.57	2,290.75	2,277.41	13.34	171.759
2,800.00	2,787.96	2,681.24	2,672.26	7.28	6.53	2.40	572.51	2,386.45	2,273.54	2,259.83	13.72	165.737
2,900.00	2,884.87	2,778.29	2,768.36	7.49	6.70	3.81	561.50	2,394.28	2,253.91	2,239.82	14.10	159.874
3,000.00	2,981.46	2,875.04	2,864.17	7.68	6.86	4.18	550.53	2,402.10	2,233.16	2,218.70	14.46	154.476
3,100.00	3,078.05	2,971.80	2,959.99	7.87	7.03	4.56	539.55	2,409.91	2,212.50	2,197.68	14.82	149.306
3,200.00	3,174.64	3,068.56	3,055.80	8.06	7.19	4.95	528.57	2,417.72	2,191.93	2,176.75	15.18	144.354
3,300.00	3,271.24	3,165.31	3,151.62	8.26	7.36	5.34	517.60	2,425.53	2,171.47	2,155.91	15.55	139.609
3,400.00	3,367.83	3,262.07	3,247.43	8.51	7.53	5.74	506.62	2,433.34	2,151.10	2,135.18	15.93	135.064
3,500.00	3,464.42	3,358.83	3,343.24	8.80	7.70	6.15	495.64	2,441.16	2,130.84	2,114.54	16.30	130.707
3,600.00	3,561.01	3,455.59	3,439.06	9.09	7.87	6.56	484.67	2,448.97	2,110.69	2,094.01	16.68	126.531
3,700.00	3,657.60	3,552.34	3,534.87	9.38	8.05	6.99	473.69	2,456.78	2,090.65	2,073.59	17.06	122.527
3,800.00	3,754.20	3,649.10	3,630.69	9.68	8.22	7.42	462.72	2,464.59	2,070.73	2,053.28	17.45	118.687
3,900.00	3,850.79	3,745.86	3,726.50	9.98	8.40	7.86	451.74	2,472.40	2,050.92	2,033.08	17.83	115.002
4,000.00	3,947.38	3,842.61	3,822.32	10.28	8.58	8.30	440.76	2,480.21	2,031.23	2,013.01	18.22	111.466
4,100.00	4,043.97	3,939.37	3,918.13	10.59	8.75	8.76	429.79	2,488.03	2,011.67	1,993.05	18.61	108.070
4,200.00	4,140.56	4,036.13	4,013.94	10.90	8.93	9.22	418.81	2,495.84	1,992.23	1,973.23	19.01	104.808
4,300.00	4,237.16	4,132.88	4,109.76	11.21	9.11	9.70	407.83	2,503.65	1,972.93	1,953.53	19.40	101.673
4,400.00	4,333.75	4,229.64	4,205.57	11.52	9.30	10.18	396.86	2,511.46	1,953.76	1,933.96	19.80	98.659
4,500.00	4,430.34	4,326.40	4,301.39	11.84	9.48	10.67	385.88	2,519.27	1,934.74	1,914.53	20.20	95.761
4,600.00	4,526.93	4,423.15	4,397.20	12.16	9.66	11.17	374.90	2,527.09	1,915.85	1,895.25	20.61	92.973
4,700.00	4,623.53	4,519.91	4,493.02	12.48	9.85	11.68	363.93	2,534.90	1,897.12	1,876.11	21.01	90.289
4,800.00	4,720.12	4,616.67	4,588.83	12.80	10.03	12.20	352.95	2,542.71	1,878.54	1,857.12	21.42	87.705
4,900.00	4,816.71	4,713.42	4,684.64	13.12	10.22	12.73	341.97	2,550.52	1,860.11	1,838.29	21.83	85.216
5,000.00	4,913.30	4,810.18	4,780.46	13.45	10.40	13.27	331.00	2,558.33	1,841.85	1,819.61	22.24	82.818
5,100.00	5,009.89	4,906.94	4,876.27	13.78	10.59	13.83	320.02	2,566.15	1,823.76	1,801.10	22.65	80.506

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 22 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 134H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Rule Assigned:		Offset Site Error:		Offset Well Error:							
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
5,200.00	5,106.49	5,003.69	4,972.09	14.10	10.78	14.39	309.04	2,573.96	1,805.84	1,782.77	23.07	78.278	
5,300.00	5,203.08	5,103.81	5,071.23	14.43	10.96	14.98	297.70	2,582.03	1,788.08	1,764.60	23.48	76.155	
5,400.00	5,299.67	5,233.76	5,200.25	14.75	11.19	15.69	285.11	2,590.99	1,769.44	1,745.51	23.93	73.949	
5,500.00	5,396.65	5,364.35	5,330.36	15.07	11.39	16.20	276.07	2,597.43	1,750.54	1,726.17	24.36	71.848	
5,600.00	5,494.23	5,495.64	5,461.47	15.36	11.56	16.58	270.63	2,601.30	1,732.33	1,707.57	24.76	69.966	
5,700.00	5,592.35	5,627.34	5,593.15	15.62	11.70	16.81	268.87	2,602.55	1,714.74	1,689.66	25.08	68.365	
5,800.00	5,690.94	5,725.13	5,690.94	15.86	11.73	16.90	268.87	2,602.55	1,698.72	1,673.39	25.33	67.054	
5,900.00	5,789.93	5,824.12	5,789.93	16.07	11.79	16.98	268.87	2,602.55	1,685.20	1,659.61	25.59	65.849	
6,000.00	5,889.26	5,923.45	5,889.26	16.25	11.84	17.05	268.87	2,602.55	1,674.17	1,648.33	25.84	64.786	
6,100.00	5,988.86	6,023.05	5,988.86	16.41	11.89	17.10	268.87	2,602.55	1,665.63	1,639.55	26.08	63.864	
6,200.00	6,088.66	6,122.85	6,088.66	16.53	11.94	17.14	268.87	2,602.55	1,659.59	1,633.29	26.31	63.083	
6,300.00	6,188.59	6,222.78	6,188.59	16.64	12.00	17.16	268.87	2,602.55	1,656.06	1,629.54	26.52	62.445	
6,400.00	6,288.58	6,322.77	6,288.58	16.71	12.05	89.59	268.87	2,602.55	1,655.01	1,628.36	26.66	62.087	
6,500.00	6,388.58	6,422.77	6,388.58	16.76	12.11	89.59	268.87	2,602.55	1,655.01	1,628.25	26.76	61.835	
6,600.00	6,488.58	6,522.77	6,488.58	16.82	12.16	89.59	268.87	2,602.55	1,655.01	1,628.14	26.87	61.585	
6,700.00	6,588.58	6,622.77	6,588.58	16.88	12.22	89.59	268.87	2,602.55	1,655.01	1,628.03	26.98	61.335	
6,800.00	6,688.58	6,722.77	6,688.58	16.94	12.27	89.59	268.87	2,602.55	1,655.01	1,627.92	27.09	61.085	
6,900.00	6,788.58	6,822.77	6,788.58	17.00	12.33	89.59	268.87	2,602.55	1,655.01	1,627.81	27.20	60.837	
7,000.00	6,888.58	6,922.77	6,888.58	17.05	12.38	89.59	268.87	2,602.55	1,655.01	1,627.70	27.32	60.589	
7,100.00	6,988.58	7,022.77	6,988.58	17.11	12.44	89.59	268.87	2,602.55	1,655.01	1,627.59	27.43	60.342	
7,200.00	7,088.58	7,122.77	7,088.58	17.17	12.50	89.59	268.87	2,602.55	1,655.01	1,627.47	27.54	60.096	
7,300.00	7,188.58	7,222.77	7,188.58	17.23	12.55	89.59	268.87	2,602.55	1,655.01	1,627.36	27.65	59.851	
7,400.00	7,288.58	7,322.77	7,288.58	17.29	12.61	89.59	268.87	2,602.55	1,655.01	1,627.25	27.77	59.607	
7,500.00	7,388.58	7,422.77	7,388.58	17.35	12.67	89.59	268.87	2,602.55	1,655.01	1,627.13	27.88	59.364	
7,600.00	7,488.58	7,522.77	7,488.58	17.41	12.72	89.59	268.87	2,602.55	1,655.01	1,627.02	27.99	59.122	
7,700.00	7,588.58	7,622.77	7,588.58	17.47	12.78	89.59	268.87	2,602.55	1,655.01	1,626.90	28.11	58.880	
7,800.00	7,688.58	7,722.77	7,688.58	17.53	12.84	89.59	268.87	2,602.55	1,655.01	1,626.79	28.22	58.640	
7,900.00	7,788.58	7,822.77	7,788.58	17.59	12.90	89.59	268.87	2,602.55	1,655.01	1,626.67	28.34	58.400	
8,000.00	7,888.58	7,922.77	7,888.58	17.65	12.96	89.59	268.87	2,602.55	1,655.01	1,626.56	28.46	58.162	
8,100.00	7,988.58	8,022.77	7,988.58	17.71	13.02	89.59	268.87	2,602.55	1,655.01	1,626.44	28.57	57.924	
8,200.00	8,088.58	8,122.77	8,088.58	17.77	13.08	89.59	268.87	2,602.55	1,655.01	1,626.32	28.69	57.688	
8,300.00	8,188.58	8,222.77	8,188.58	17.83	13.13	89.59	268.87	2,602.55	1,655.01	1,626.21	28.81	57.452	
8,400.00	8,288.58	8,322.77	8,288.58	17.89	13.19	89.59	268.87	2,602.55	1,655.01	1,626.09	28.92	57.218	
8,500.00	8,388.58	8,422.77	8,388.58	17.95	13.25	89.59	268.87	2,602.55	1,655.01	1,625.97	29.04	56.985	
8,600.00	8,488.58	8,522.77	8,488.58	18.02	13.31	89.59	268.87	2,602.55	1,655.01	1,625.85	29.16	56.752	
8,700.00	8,588.58	8,622.77	8,588.58	18.08	13.37	89.59	268.87	2,602.55	1,655.01	1,625.73	29.28	56.521	
8,800.00	8,688.58	8,722.77	8,688.58	18.14	13.43	89.59	268.87	2,602.55	1,655.01	1,625.61	29.40	56.291	
8,900.00	8,788.58	8,822.77	8,788.58	18.20	13.50	89.59	268.87	2,602.55	1,655.01	1,625.49	29.52	56.061	
9,000.00	8,888.58	8,922.77	8,888.58	18.26	13.56	89.59	268.87	2,602.55	1,655.01	1,625.37	29.64	55.833	
9,100.00	8,988.58	9,022.77	8,988.58	18.32	13.62	89.59	268.87	2,602.55	1,655.01	1,625.25	29.76	55.606	
9,200.00	9,088.58	9,122.77	9,088.58	18.39	13.68	89.59	268.87	2,602.55	1,655.01	1,625.13	29.88	55.380	
9,300.00	9,188.58	9,222.77	9,188.58	18.45	13.74	89.59	268.87	2,602.55	1,655.01	1,625.01	30.01	55.155	
9,400.00	9,288.58	9,322.77	9,288.58	18.51	13.80	89.59	268.87	2,602.55	1,655.01	1,624.88	30.13	54.932	
9,500.00	9,388.58	9,422.77	9,388.58	18.57	13.86	89.59	268.87	2,602.55	1,655.01	1,624.76	30.25	54.709	
9,600.00	9,488.58	9,522.77	9,488.58	18.64	13.93	89.59	268.87	2,602.55	1,655.01	1,624.64	30.37	54.487	
9,700.00	9,588.58	9,622.77	9,588.58	18.70	13.99	89.59	268.87	2,602.55	1,655.01	1,624.51	30.50	54.267	
9,800.00	9,688.58	9,722.77	9,688.58	18.76	14.05	89.59	268.87	2,602.55	1,655.01	1,624.39	30.62	54.047	
9,900.00	9,788.58	9,822.77	9,788.58	18.83	14.11	89.59	268.87	2,602.55	1,655.01	1,624.27	30.75	53.829	
10,000.00	9,888.58	9,922.77	9,888.58	18.89	14.18	89.59	268.87	2,602.55	1,655.01	1,624.14	30.87	53.612	
10,100.00	9,988.58	10,022.77	9,988.58	18.95	14.24	89.59	268.87	2,602.55	1,655.01	1,624.02	31.00	53.396	
10,200.00	10,088.58	10,122.77	10,088.58	19.02	14.30	89.59	268.87	2,602.55	1,655.01	1,623.89	31.12	53.181	
10,300.00	10,188.58	10,222.77	10,188.58	19.08	14.37	89.59	268.87	2,602.55	1,655.01	1,623.77	31.25	52.967	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 23 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 134H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
10,400.00	10,288.58	10,322.77	10,288.58	19.15	14.43	89.59	268.87	2,602.55	1,655.01	1,623.64	31.37	52.755			
10,500.00	10,388.58	10,422.77	10,388.58	19.21	14.50	89.59	268.87	2,602.55	1,655.01	1,623.51	31.50	52.543			
10,600.00	10,488.58	10,522.77	10,488.58	19.27	14.56	89.59	268.87	2,602.55	1,655.01	1,623.39	31.62	52.333			
10,700.00	10,588.58	10,622.77	10,588.58	19.34	14.62	89.59	268.87	2,602.55	1,655.01	1,623.26	31.75	52.123			
10,800.00	10,688.58	10,722.77	10,688.58	19.40	14.69	89.59	268.87	2,602.55	1,655.01	1,623.13	31.88	51.915			
10,900.00	10,788.58	10,822.77	10,788.58	19.47	14.75	89.59	268.87	2,602.55	1,655.01	1,623.01	32.01	51.708			
11,000.00	10,888.58	10,922.77	10,888.58	19.53	14.82	89.59	268.87	2,602.55	1,655.01	1,622.88	32.13	51.502			
11,100.00	10,988.58	11,022.77	10,988.58	19.60	14.88	89.59	268.87	2,602.55	1,655.01	1,622.75	32.26	51.297			
11,200.00	11,088.58	11,122.77	11,088.58	19.66	14.95	89.59	268.87	2,602.55	1,655.01	1,622.62	32.39	51.094			
11,300.00	11,188.58	11,222.77	11,188.58	19.73	15.01	89.59	268.87	2,602.55	1,655.01	1,622.49	32.52	50.891			
11,400.00	11,288.58	11,322.77	11,288.58	19.79	15.08	89.59	268.87	2,602.55	1,655.01	1,622.36	32.65	50.690			
11,500.00	11,388.58	11,422.77	11,388.58	19.86	15.14	89.59	268.87	2,602.55	1,655.01	1,622.23	32.78	50.487	CC		
11,511.16	11,399.73	11,433.92	11,399.73	19.87	15.15	89.59	268.87	2,602.55	1,655.01	1,622.22	32.80	50.464			
11,600.00	11,488.58	11,522.68	11,488.49	19.92	15.22	89.60	268.69	2,602.55	1,655.01	1,622.10	32.91	50.286			
11,700.00	11,588.58	11,620.66	11,585.75	19.99	15.41	89.97	257.87	2,602.65	1,655.07	1,622.03	33.05	50.084			
11,800.00	11,688.58	11,712.44	11,673.96	20.05	15.62	90.84	232.85	2,602.88	1,655.54	1,622.28	33.26	49.781			
11,900.00	11,788.58	11,794.51	11,748.56	20.12	15.81	92.02	198.81	2,603.19	1,657.12	1,623.58	33.53	49.416			
12,000.00	11,888.58	11,865.54	11,808.63	20.19	15.99	93.32	161.00	2,603.53	1,660.66	1,626.79	33.87	49.026			
12,100.00	11,988.51	11,926.97	11,856.47	20.25	16.15	-84.56	122.53	2,603.88	1,666.79	1,632.57	34.22	48.714			
12,200.00	12,086.82	11,985.88	11,898.24	20.31	16.35	-82.64	81.01	2,604.26	1,674.50	1,639.93	34.57	48.437			
12,300.00	12,180.57	12,050.00	11,938.60	20.35	16.63	-80.70	31.23	2,604.71	1,683.00	1,648.01	34.99	48.105			
12,400.00	12,266.93	12,100.00	11,966.05	20.39	16.92	-79.12	-10.54	2,605.09	1,691.59	1,656.18	35.41	47.769			
12,500.00	12,343.26	12,150.00	11,989.76	20.44	17.25	-7									

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 134H - OH - Plan 1													Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Offset Well Error: 0.50 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned: Distance			Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
15,500.00	12,532.27	14,959.76	12,064.81	44.94	50.45	-74.24	-2,855.47	2,630.94	1,721.19	1,628.54	92.65	18.577		
15,600.00	12,533.14	15,059.76	12,065.51	46.15	51.76	-74.24	-2,955.46	2,631.85	1,721.29	1,626.17	95.11	18.097		
15,700.00	12,534.02	15,159.76	12,066.21	47.37	53.08	-74.23	-3,055.45	2,632.76	1,721.38	1,623.80	97.58	17.640		
15,800.00	12,534.89	15,259.76	12,066.91	48.59	54.40	-74.23	-3,155.45	2,633.67	1,721.47	1,621.41	100.06	17.204		
15,900.00	12,535.76	15,359.76	12,067.61	49.83	55.73	-74.22	-3,255.44	2,634.58	1,721.57	1,619.02	102.55	16.788		
16,000.00	12,536.64	15,459.76	12,068.31	51.07	57.05	-74.22	-3,355.43	2,635.49	1,721.66	1,616.62	105.04	16.390		
16,100.00	12,537.51	15,559.76	12,069.01	52.32	58.38	-74.21	-3,455.43	2,636.40	1,721.75	1,614.21	107.55	16.009		
16,200.00	12,538.39	15,659.76	12,069.70	53.57	59.71	-74.20	-3,555.42	2,637.31	1,721.85	1,611.79	110.06	15.645		
16,300.00	12,539.26	15,759.76	12,070.40	54.83	61.04	-74.20	-3,655.41	2,638.21	1,721.94	1,609.37	112.57	15.297		
16,400.00	12,540.13	15,859.76	12,071.10	56.09	62.38	-74.19	-3,755.41	2,639.12	1,722.03	1,606.94	115.09	14.962		
16,500.00	12,541.01	15,959.76	12,071.80	57.36	63.71	-74.19	-3,855.40	2,640.03	1,722.13	1,604.51	117.62	14.642		
16,600.00	12,541.88	16,059.76	12,072.50	58.64	65.05	-74.18	-3,955.39	2,640.94	1,722.22	1,602.07	120.15	14.334		
16,700.00	12,542.75	16,159.76	12,073.20	59.91	66.39	-74.18	-4,055.39	2,641.85	1,722.31	1,599.62	122.69	14.038		
16,800.00	12,543.63	16,259.76	12,073.90	61.20	67.73	-74.17	-4,155.38	2,642.76	1,722.41	1,597.18	125.23	13.754		
16,900.00	12,544.50	16,359.76	12,074.60	62.48	69.07	-74.17	-4,255.37	2,643.67	1,722.50	1,594.72	127.77	13.481		
17,000.00	12,545.37	16,459.76	12,075.30	63.77	70.41	-74.16	-4,355.37	2,644.58	1,722.59	1,592.27	130.32	13.218		
17,100.00	12,546.25	16,559.76	12,076.00	65.06	71.75	-74.16	-4,455.36	2,645.48	1,722.69	1,589.81	132.88	12.965		
17,200.00	12,547.12	16,659.76	12,076.70	66.36	73.09	-74.15	-4,555.35	2,646.39	1,722.78	1,587.35	135.43	12.721		
17,300.00	12,547.99	16,759.76	12,077.40	67.66	74.44	-74.15	-4,655.35	2,647.30	1,722.87	1,584.88	137.99	12.485		
17,400.00	12,548.87	16,859.76	12,078.09	68.96	75.78	-74.14	-4,755.34	2,648.21	1,722.97	1,582.41	140.56	12.258		
17,500.00	12,549.74	16,959.76	12,078.79	70.26	77.13	-74.14	-4,855.33	2,649.12	1,723.06	1,579.94	143.12	12.039		
17,600.00	12,550.62	17,059.76	12,079.49	71.57	78.48	-74.13	-4,955.33	2,650.03	1,723.15	1,577.46	145.69	11.828		
17,700.00	12,551.49	17,159.76	12,080.19	72.88	79.82	-74.13								

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 134H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft
Reference						Offset				Distance				Offset Well Error:		0.50 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning			
20,700.00	12,577.70	20,159.75	12,101.17	112.81	120.48	-73.97	-8,055.12	2,678.20	1,726.06	1,499.92	226.13	7.633				
20,800.00	12,578.57	20,259.75	12,101.87	114.16	121.84	-73.97	-8,155.11	2,679.11	1,726.15	1,497.41	228.75	7.546				
20,900.00	12,579.44	20,359.75	12,102.56	115.51	123.20	-73.96	-8,255.10	2,680.02	1,726.24	1,494.89	231.36	7.461				
21,000.00	12,580.32	20,459.75	12,103.26	116.85	124.56	-73.96	-8,355.10	2,680.92	1,726.34	1,492.37	233.97	7.379				
21,100.00	12,581.19	20,559.75	12,103.96	118.20	125.92	-73.95	-8,455.09	2,681.83	1,726.43	1,489.85	236.58	7.297				
21,200.00	12,582.06	20,659.75	12,104.66	119.55	127.29	-73.95	-8,555.08	2,682.74	1,726.53	1,487.33	239.19	7.218				
21,300.00	12,582.94	20,759.75	12,105.36	120.89	128.65	-73.94	-8,655.08	2,683.65	1,726.62	1,484.81	241.81	7.140				
21,400.00	12,583.81	20,859.75	12,106.06	122.24	130.01	-73.94	-8,755.07	2,684.56	1,726.71	1,482.29	244.42	7.065				
21,500.00	12,584.69	20,959.75	12,106.76	123.59	131.37	-73.93	-8,855.06	2,685.47	1,726.81	1,479.77	247.03	6.990				
21,600.00	12,585.56	21,059.75	12,107.46	124.94	132.73	-73.93	-8,955.06	2,686.38	1,726.90	1,477.25	249.65	6.917				
21,700.00	12,586.43	21,159.75	12,108.16	126.29	134.09	-73.92	-9,055.05	2,687.29	1,727.00	1,474.73	252.26	6.846				
21,800.00	12,587.31	21,259.75	12,108.86	127.64	135.45	-73.92	-9,155.04	2,688.19	1,727.09	1,472.21	254.88	6.776				
21,900.00	12,588.18	21,359.75	12,109.56	128.99	136.82	-73.91	-9,255.04	2,689.10	1,727.18	1,469.69	257.50	6.708				
22,000.00	12,589.05	21,459.75	12,110.25	130.34	138.18	-73.91	-9,355.03	2,690.01	1,727.28	1,467.17	260.11	6.641				
22,100.00	12,589.93	21,559.75	12,110.95	131.70	139.54	-73.90	-9,455.02	2,690.92	1,727.37	1,464.64	262.73	6.575				
22,200.00	12,590.80	21,659.75	12,111.65	133.05	140.90	-73.90	-9,555.02	2,691.83	1,727.47	1,462.12	265.35	6.510				
22,300.00	12,591.67	21,759.75	12,112.35	134.40	142.27	-73.89	-9,655.01	2,692.74	1,727.56	1,459.60	267.96	6.447				
22,400.00	12,592.55	21,859.75	12,113.05	135.75	143.63	-73.89	-9,755.00	2,693.65	1,727.65	1,457.08	270.58	6.385				
22,500.00	12,593.42	21,959.75	12,113.75	137.11	144.99	-73.88	-9,855.00	2,694.56	1,727.75	1,454.55	273.20	6.324				
22,600.00	12,594.30	22,059.75	12,114.45	138.46	146.36	-73.88	-9,954.99	2,695.46	1,727.84	1,452.03	275.82	6.264				
22,700.00	12,595.17	22,159.75	12,115.15	139.81	147.72	-73.87	-10,054.98	2,696.37	1,727.94	1,449.50	278.43	6.206				
22,800.00	12,596.04	22,259.75	12,115.85	141.17	149.08	-73.87	-10,154.98	2,697.28	1,728.03	1,446.98	281.05	6.148				
22,875.30	12,596.70	22,335.05	12,116.37	142.19	150.11	-73.86	-10,230.27	2,697.97	1,728.10	1,445.08	283.02	6.106	ES, SF			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 26 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 135H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)														Rule Assigned:	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
0.00	0.00	0.00	1.00	0.50	0.50	173.21	-210.00	25.00	211.49	211.49					
100.00	100.00	99.00	100.00	0.98	0.97	173.21	-210.00	25.00	211.48	209.53	1.95	108.179			
200.00	200.00	199.00	200.00	1.56	1.56	173.21	-210.00	25.00	211.48	208.37	3.12	67.865			
300.00	300.00	299.00	300.00	1.98	1.98	173.21	-210.00	25.00	211.48	207.52	3.96	53.431			
400.00	400.00	399.00	400.00	2.33	2.33	173.21	-210.00	25.00	211.48	206.83	4.66	45.428			
500.00	500.00	499.00	500.00	2.63	2.63	173.21	-210.00	25.00	211.48	206.22	5.27	40.160			
600.00	600.00	599.00	600.00	2.91	2.91	173.21	-210.00	25.00	211.48	205.67	5.82	36.354			
700.00	700.00	699.00	700.00	3.16	3.16	173.21	-210.00	25.00	211.48	205.16	6.33	33.436			
800.00	800.00	799.00	800.00	3.40	3.40	173.21	-210.00	25.00	211.48	204.68	6.80	31.106			
900.00	900.00	904.61	905.60	3.62	3.69	173.30	-208.66	24.50	210.16	202.85	7.31	19.876			
1,000.00	1,000.00	1,009.58	1,010.48	3.76	3.96	81.61	-204.62	23.02	206.17	198.46	7.71	26.741			
1,100.00	1,099.98	1,109.39	1,110.15	4.00	4.17	82.57	-199.72	21.21	200.84	192.74	8.10	24.785			
1,200.00	1,199.88	1,209.06	1,209.68	4.24	4.36	84.33	-194.82	19.41	195.29	186.81	8.48	23.038			
1,300.00	1,299.63	1,311.39	1,311.85	4.46	4.48	87.11	-189.34	17.39	189.31	180.54	8.77	21.587			
1,400.00	1,399.25	1,415.12	1,415.22	4.60	4.73	90.86	-181.38	14.45	181.47	172.34	9.13	19.876			
1,500.00	1,498.87	1,518.12	1,517.61	4.78	4.96	95.31	-170.87	10.58	172.02	162.52	9.50	18.104			
1,600.00	1,598.49	1,617.76	1,616.41	4.96	5.09	100.48	-158.79	6.13	161.91	152.12	9.79	16.541			
1,700.00	1,698.11	1,716.10	1,713.91	5.14	5.28	106.22	-146.75	1.69	153.16	143.01	10.15	15.096			
1,800.00	1,797.73	1,814.43	1,811.40	5.32	5.47	112.57	-134.71	-2.75	146.16	135.66	10.50	13.918			
1,900.00	1,897.34	1,912.77	1,908.90	5.49	5.66	119.44	-122.66	-7.19	141.16	130.30	10.86	13.002			
2,000.00	1,996.96	2,011.11	2,006.39	5.67	5.86	126.68	-110.62	-11.63	138.38	127.16	11.21	12.341			
2,067.73	2,064.43	2,077.71	2,072.42	5.79	5.99	131.70	-102.46	-14.64	137.83	126.37	11.46	12.031	CC, ES		
2,100.00	2,096.58	2,109.44	2,103.89	5.85	6.05	134.09	-98.57	-16.07	137.95	126.38	11.57	11.921			
2,200.00	2,196.20	2,207.78	2,201.38	6.04	6.24	141.43	-86.53	-20.51	139.91	127.97	11.94	11.715			
2,300.00	2,295.72	2,306.03	2,298.80	6.23	6.43	154.75	-74.50	-24.95	145.35	133.03	12.32	11.797			
2,400.00	2,394.97	2,404.06	2,395.99	6.43	6.62	165.38	-62.49	-29.37	155.47	142.75	12.72	12.222			
2,500.00	2,493.89	2,501.80	2,492.89	6.64	6.81	173.75	-50.52	-33.79	169.88	156.76	13.12	12.944			
2,600.00	2,592.40	2,599.17	2,589.43	6.85	7.00	-179.68	-38.59	-38.18	188.09	174.57	13.53	13.905			
2,700.00	2,690.45	2,696.12	2,685.55	7.07	7.19	-174.59	-26.72	-42.56	209.65	195.73	13.92	15.056			
2,800.00	2,787.96	2,792.58	2,781.19	7.28	7.38	-170.67	-14.90	-46.91	234.19	219.87	14.32	16.355			
2,900.00	2,884.87	2,888.49	2,876.27	7.49	7.56	-167.67	-3.16	-51.24	261.44	246.73	14.71	17.773			
3,000.00	2,981.46	2,984.09	2,971.06	7.68	7.75	-166.26	8.55	-55.56	290.02	274.94	15.08	19.238			
3,100.00	3,078.05	3,079.70	3,065.85	7.87	7.94	-165.11	20.26	-59.88	318.73	303.28	15.44	20.639			
3,200.00	3,174.64	3,175.31	3,160.64	8.06	8.12	-164.15	31.97	-64.19	347.54	331.73	15.81	21.977			
3,300.00	3,271.24	3,270.92	3,255.43	8.26	8.31	-163.33	43.68	-68.51	376.43	360.24	16.19	23.254			
3,400.00	3,367.83	3,366.53	3,350.22	8.51	8.49	-162.63	55.39	-72.83	405.38	388.81	16.56	24.474			
3,500.00	3,464.42	3,462.14	3,445.01	8.80	8.68	-162.02	67.10	-77.14	434.37	417.43	16.94	25.639			
3,600.00	3,561.01	3,557.75	3,539.80	9.09	8.86	-161.49	78.81	-81.46	463.41	446.08	17.32	26.751			
3,700.00	3,657.60	3,653.36	3,634.59	9.38	9.05	-161.02	90.52	-85.78	492.48	474.77	17.71	27.814			
3,800.00	3,754.20	3,748.96	3,729.38	9.68	9.23	-160.60	102.23	-90.09	521.57	503.48	18.09	28.830			
3,900.00	3,850.79	3,844.57	3,824.17	9.98	9.42	-160.23	113.94	-94.41	550.69	532.21	18.48	29.802			
4,000.00	3,947.38	3,940.18	3,918.97	10.28	9.60	-159.90	125.65	-98.73	579.82	560.96	18.87	30.731			
4,100.00	4,043.97	4,035.79	4,013.76	10.59	9.79	-159.59	137.36	-103.04	608.98	589.72	19.26	31.621			
4,200.00	4,140.56	4,131.40	4,108.55	10.90	9.97	-159.32	149.07	-107.36	638.14	618.49	19.65	32.474			
4,300.00	4,237.16	4,227.01	4,203.34	11.21	10.16	-159.07	160.78	-111.68	667.32	647.28	20.05	33.291			
4,400.00	4,333.75	4,322.62	4,298.13	11.52	10.35	-158.84	172.49	-115.99	696.51	676.07	20.44	34.074			
4,500.00	4,430.34	4,418.23	4,392.92	11.84	10.53	-158.62	184.20	-120.31	725.71	704.87	20.84	34.826			
4,600.00	4,526.93	4,513.84	4,487.71	12.16	10.72	-158.43	195.91	-124.62	754.92	733.68	21.24	35.547			
4,700.00	4,623.53	4,609.44	4,582.50	12.48	10.90	-158.25	207.62	-128.94	784.14	762.50	21.64	36.240			
4,800.00	4,720.12	4,705.33	4,677.56	12.80	11.09	-158.08	219.36	-133.27	813.36	791.32	22.04	36.902			
4,900.00	4,816.71	4,801.32	4,781.84	13.12	11.30	-158.01	230.80	-137.48	842.02	819.55	22.47	37.475			
5,000.00	4,913.30	4,915.98	4,887.09	13.45	11.51	-158.12	239.59	-140.72	869.62	846.74	22.88	38.010			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 27 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 135H - OH - Plan 1														Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error: 0.50 usft			
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Warning				
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor			
10,300.00	10,188.58	10,217.74	10,188.58	19.08	16.33	-90.39	249.64	-144.43	1,092.04	1,059.25	32.78	33.311			
10,400.00	10,288.58	10,317.74	10,288.58	19.15	16.41	-90.39	249.64	-144.43	1,092.04	1,059.10	32.93	33.158			
10,500.00	10,388.58	10,417.74	10,388.58	19.21	16.50	-90.39	249.64	-144.43	1,092.04	1,058.95	33.09	33.007			
10,600.00	10,488.58	10,517.74	10,488.58	19.27	16.58	-90.39	249.64	-144.43	1,092.04	1,058.80	33.24	32.857			
10,700.00	10,588.58	10,617.74	10,588.58	19.34	16.67	-90.39	249.64	-144.43	1,092.04	1,058.65	33.39	32.708			
10,800.00	10,688.58	10,717.74	10,688.58	19.40	16.75	-90.39	249.64	-144.43	1,092.04	1,058.50	33.54	32.560			
10,900.00	10,788.58	10,817.74	10,788.58	19.47	16.84	-90.39	249.64	-144.43	1,092.04	1,058.35	33.69	32.414			
11,000.00	10,888.58	10,917.74	10,888.58	19.53	16.92	-90.39	249.64	-144.43	1,092.04	1,058.19	33.84	32.269			
11,100.00	10,988.58	11,017.74	10,988.58	19.60	17.01	-90.39	249.64	-144.43	1,092.04	1,058.04	33.99	32.125			
11,200.00	11,088.58	11,117.74	11,088.58	19.66	17.09	-90.39	249.64	-144.43	1,092.04	1,057.89	34.14	31.982			
11,300.00	11,188.58	11,217.74	11,188.58	19.73	17.18	-90.39	249.64	-144.43	1,092.04	1,057.74	34.30	31.841			
11,400.00	11,288.58	11,317.74	11,288.58	19.79	17.26	-90.39	249.64	-144.43	1,092.04	1,057.59	34.45	31.700			
11,500.00	11,388.58	11,417.74	11,388.58	19.86	17.35	-90.39	249.64	-144.43	1,092.04	1,057.43	34.60	31.561			
11,600.00	11,488.58	11,517.74	11,488.58	19.92	17.43	-90.39	249.64	-144.43	1,092.04	1,057.28	34.75	31.425			
11,700.00	11,588.58	11,617.82	11,588.63	19.99	17.48	-90.45	248.47	-144.42	1,092.03	1,057.18	34.85	31.333			
11,710.92	11,599.50	11,628.72	11,599.50	20.00	17.49	-90.49	247.67	-144.41	1,092.03	1,057.18	34.85	31.333			
11,800.00	11,688.58	11,715.69	11,685.29	20.05	17.51	-91.21	233.92	-144.29	1,092.12	1,057.31	34.81	31.371			
11,900.00	11,788.58	11,806.22	11,771.32	20.12	17.52	-92.68	206.01	-144.05	1,092.96	1,058.25	34.71	31.486			
12,000.00	11,888.58	11,886.34	11,842.95	20.19	17.52	-94.55	170.27	-143.75	1,095.72	1,061.11	34.61	31.655			
12,100.00	11,988.51	11,956.26	11,900.87	20.25	17.53	83.65	131.18	-143.41	1,101.48	1,066.94	34.54	31.893			
12,200.00	12,086.82	12,022.60	11,951.04	20.31	17.53	81.12	87.84	-143.04	1,109.30	1,074.79	34.51	32.141			
12,300.00	12,180.57	12,086.99	11,994.63	20.35	17.53	78.74	40.50	-142.63	1,118.24	1,083.65	34.59	32.324			
12,400.00	12,266.93	12,150.00	12,031.89	20.39	17.53	76.57	-10.28	-142.19	1,127.53	1,092.74	34.79	32.413			
12,500.00	12,343.26	12,211.80	12,062.80	20.44	17.53	74.67	-63.76	-141.73	1,136.44	1,101.36	35.08	32.395			
12,600.00	12,407.24	12,272.88	12,087.51	20.52	17.54	73.09	-119.57	-141.25	1,144.36	1,108.92	35.44	32.287			
12,700.00	12,456.94	12,333.38	12,106.00	20.67	17.56	71.88	-177.15	-140.76	1,150.77	1,114.93	35.84	32.108			
12,800.00	12,490.84	12,400.00	12,119.22	20.88	17.58	71.02	-242.41	-140.19	1,155.30	1,119.07	36.23	31.889			
12,900.00	12,507.91	12,450.00	12,124.11	21.18	17.60	70.64	-292.15	-139.77	1,157.62	1,121.02	36.59	31.633			
13,000.00	12,510.43	12,538.07	12,125.48	21.56	17.65	70.58	-380.20	-139.01	1,157.90	1,120.91	37.00	31.297			
13,100.00	12,511.30	12,638.07	12,126.35	22.01	17.73	70.58	-480.19	-138.15	1,157.90	1,120.32	37.59	30.807			
13,200.00	12,512.18	12,738.07	12,127.22	22.52	17.85	70.58	-580.18	-137.29	1,157.91	1,119.56	38.34	30.198			
13,300.00	12,513.05	12,838.07	12,128.09	23.10	18.04	70.58	-680.18	-136.42	1,157.91	1,118.65	39.26	29.494			
13,400.00	12,513.92	12,938.07	12,128.96	23.73	18.35	70.58	-780.17	-135.56	1,157.91	1,117.58	40.32	28.716			
13,500.00	12,514.80	13,038.07	12,129.83	24.41	18.82	70.58	-880.16	-134.70	1,157.91	1,116.39	41.52	27.886			
13,600.00	12,515.67	13,138.07	12,130.70	25.15	19.43	70.58	-980.15	-133.84	1,157.91	1,115.06	42.85	27.023			
13,700.00	12,516.55	13,238.07	12,131.57	25.93	20.17	70.58	-1,080.15	-132.98	1,157.91	1,113.62	44.29	26.145			
13,800.00	12,517.42	13,338.07	12,132.45	26.76	20.99	70.58	-1,180.14	-132.12	1,157.91	1,112.08	45.83	25.266			
13,900.00	12,518.29	13,438.07	12,133.32	27.63	21.88	70.58	-1,280.13	-131.26	1,157.91	1,110.45	47.46	24.396			
14,000.00	12,519.17	13,538.07	12,134.19	28.53	22.82	70.58	-1,380.12	-130.40	1,157.91	1,108.73	49.18	23.544			
14,100.00	12,520.04	13,638.07	12,135.06	29.47	23.81	70.58	-1,480.12	-129.54	1,157.91	1,106.94	50.97	22.716			
14,200.00	12,520.91	13,738.07	12,135.93	30.44	24.84	70.58	-1,580.11	-128.68	1,157.92	1,105.08	52.83	21.916			
14,300.00	12,521.79	13,838.07	12,136.80	31.44	25.91	70.58	-1,680.10	-127.81	1,157.92	1,103.16	54.76	21.147			
14,400.00	12,522.66	13,938.07	12,137.67	32.46	27.00	70.58	-1,780.09	-126.95	1,157.92	1,101.19	56.73	20.411			
14,500.00	12,523.53	14,038.07	12,138.54	33.51	28.12	70.58	-1,880.09	-126.09	1,157.92	1,099.16	58.75	19.708			
14,600.00	12,524.41	14,138.07	12,139.42	34.58	29.26	70.58	-1,980.08	-125.23	1,157.92	1,097.10	60.82	19.038			
14,700.00	12,525.28	14,238.07	12,140.29	35.67	30.42	70.58	-2,080.07	-124.37	1,157.92	1,094.99	62.93	18.400			
14,800.00	12,526.16	14,338.07	12,141.16	36.78	31.60	70.58	-2,180.06	-123.51	1,157.92	1,092.85	65.07	17.794			
14,900.00	12,527.03	14,438.07	12,142.03	37.90	32.79	70.58	-2,280.06	-122.65	1,157.92	1,090.67	67.25	17.219			
15,000.00	12,527.90	14,538.07	12,142.90	39.04	34.00	70.58	-2,380.05	-121.79	1,157.92	1,088.47	69.45	16.672			
15,100.00	12,528.78	14,638.07	12,143.77	40.20	35.22	70.58	-2,480.04	-120.93	1,157.92	1,086.24	71.68	16.153			
15,200.00	12,529.65	14,738.07	12,144.64	41.37	36.45	70.58	-2,580.03	-120.07	1,157.93	1,083.99	73.94	15.661			
15,300.00	12,530.52	14,838.07	12,145.51	42.55	37.69	70.58	-2,680.03	-119.20	1,157.93	1,081.71	76.22	15.193			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 29 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 135H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
15,400.00	12,531.40	14,938.07	12,146.39	43.74	38.93	70.58	-2,780.02	-118.34	1,157.93	1,079.41	78.51	14.748			
15,500.00	12,532.27	15,038.07	12,147.26	44.94	40.19	70.58	-2,880.01	-117.48	1,157.93	1,077.10	80.83	14.326			
15,600.00	12,533.14	15,138.07	12,148.13	46.15	41.45	70.58	-2,980.00	-116.62	1,157.93	1,074.77	83.16	13.924			
15,700.00	12,534.02	15,238.07	12,149.00	47.37	42.72	70.58	-3,080.00	-115.76	1,157.93	1,072.42	85.51	13.542			
15,800.00	12,534.89	15,338.07	12,149.87	48.59	44.00	70.58	-3,179.99	-114.90	1,157.93	1,070.06	87.87	13.178			
15,900.00	12,535.76	15,438.07	12,150.74	49.83	45.28	70.58	-3,279.98	-114.04	1,157.93	1,067.69	90.25	12.831			
16,000.00	12,536.64	15,538.07	12,151.61	51.07	46.57	70.58	-3,379.97	-113.18	1,157.93	1,065.30	92.63	12.500			
16,100.00	12,537.51	15,638.07	12,152.48	52.32	47.86	70.58	-3,479.97	-112.32	1,157.93	1,062.90	95.03	12.185			
16,200.00	12,538.39	15,738.07	12,153.36	53.57	49.16	70.58	-3,579.96	-111.46	1,157.93	1,060.49	97.44	11.883			
16,300.00	12,539.26	15,838.07	12,154.23	54.83	50.46	70.58	-3,679.95	-110.60	1,157.94	1,058.08	99.86	11.596			
16,400.00	12,540.13	15,938.07	12,155.10	56.09	51.76	70.58	-3,779.94	-109.73	1,157.94	1,055.65	102.29	11.320			
16,500.00	12,541.01	16,038.07	12,155.97	57.36	53.07	70.58	-3,879.94	-108.87	1,157.94	1,053.21	104.72	11.057			
16,600.00	12,541.88	16,138.07	12,156.84	58.64	54.38	70.58	-3,979.93	-108.01	1,157.94	1,050.77	107.17	10.805			
16,700.00	12,542.75	16,238.07	12,157.71	59.91	55.69	70.58	-4,079.92	-107.15	1,157.94	1,048.32	109.62	10.563			
16,800.00	12,543.63	16,338.07	12,158.58	61.20	57.01	70.58	-4,179.91	-106.29	1,157.94	1,045.87	112.08	10.332			
16,900.00	12,544.50	16,438.07	12,159.45	62.48	58.32	70.58	-4,279.91	-105.43	1,157.94	1,043.40	114.54	10.110			
17,000.00	12,545.37	16,538.07	12,160.33	63.77	59.64	70.58	-4,379.90	-104.57	1,157.94	1,040.93	117.01	9.896			
17,100.00	12,546.25	16,638.07	12,161.20	65.06	60.97	70.58	-4,479.89	-103.71	1,157.94	1,038.46	119.48	9.691			
17,200.00	12,547.12	16,738.07	12,162.07	66.36	62.29	70.58	-4,579.88	-102.85	1,157.94	1,035.98	121.96	9.494			
17,300.00	12,547.99	16,838.07	12,162.94	67.66	63.62	70.58	-4,679.88	-101.99	1,157.95	1,033.50	124.45	9.304			
17,400.00	12,548.87	16,938.07	12,163.81	68.96	64.95	70.58	-4,779.87	-101.12	1,157.95	1,031.01	126.94	9.122			
17,500.00	12,549.74	17,038.07	12,164.68	70.26	66.28	70.58	-4,879.86	-100.26	1,157.95	1,028.51	129.43	8.946			
17,600.00	12,550.62	17,138.07	12,165.55	71.57	67.61	70.58	-4,979.85								

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 135H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error:	
Reference				Offset		Semi Major Axis				Distance		Offset Well Error:	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
20,600.00	12,576.82	20,138.07	12,191.69	111.47	108.00	70.57	-7,979.63	-73.57	1,157.98	949.92	208.05	5.566	
20,700.00	12,577.70	20,238.07	12,192.56	112.81	109.36	70.57	-8,079.62	-72.71	1,157.98	947.36	210.61	5.498	
20,800.00	12,578.57	20,338.07	12,193.43	114.16	110.71	70.57	-8,179.61	-71.85	1,157.98	944.80	213.18	5.432	
20,900.00	12,579.44	20,438.07	12,194.31	115.51	112.07	70.57	-8,279.61	-70.99	1,157.98	942.24	215.74	5.368	
21,000.00	12,580.32	20,538.07	12,195.18	116.85	113.43	70.57	-8,379.60	-70.13	1,157.98	939.68	218.30	5.304	
21,100.00	12,581.19	20,638.07	12,196.05	118.20	114.78	70.57	-8,479.59	-69.27	1,157.98	937.11	220.87	5.243	
21,200.00	12,582.06	20,738.07	12,196.92	119.55	116.14	70.57	-8,579.58	-68.41	1,157.98	934.55	223.43	5.183	
21,300.00	12,582.94	20,838.07	12,197.79	120.89	117.50	70.57	-8,679.58	-67.55	1,157.98	931.98	226.00	5.124	
21,400.00	12,583.81	20,938.07	12,198.66	122.24	118.86	70.57	-8,779.57	-66.69	1,157.98	929.42	228.57	5.066	
21,500.00	12,584.69	21,038.07	12,199.53	123.59	120.21	70.57	-8,879.56	-65.83	1,157.99	926.85	231.14	5.010	
21,600.00	12,585.56	21,138.07	12,200.40	124.94	121.57	70.57	-8,979.55	-64.96	1,157.99	924.28	233.70	4.955	
21,700.00	12,586.43	21,238.07	12,201.28	126.29	122.93	70.57	-9,079.55	-64.10	1,157.99	921.71	236.27	4.901	
21,800.00	12,587.31	21,338.07	12,202.15	127.64	124.29	70.57	-9,179.54	-63.24	1,157.99	919.15	238.84	4.848	
21,900.00	12,588.18	21,438.07	12,203.02	128.99	125.65	70.57	-9,279.53	-62.38	1,157.99	916.58	241.41	4.797	
22,000.00	12,589.05	21,538.07	12,203.89	130.34	127.01	70.57	-9,379.52	-61.52	1,157.99	914.01	243.99	4.746	
22,100.00	12,589.93	21,638.07	12,204.76	131.70	128.37	70.57	-9,479.52	-60.66	1,157.99	911.43	246.56	4.697	
22,200.00	12,590.80	21,738.07	12,205.63	133.05	129.73	70.57	-9,579.51	-59.80	1,157.99	908.86	249.13	4.648	
22,300.00	12,591.67	21,838.07	12,206.50	134.40	131.09	70.57	-9,679.50	-58.94	1,157.99	906.29	251.70	4.601	
22,400.00	12,592.55	21,938.07	12,207.37	135.75	132.45	70.57	-9,779.49	-58.08	1,157.99	903.72	254.28	4.554	
22,500.00	12,593.42	22,038.07	12,208.25	137.11	133.81	70.57	-9,879.49	-57.22	1,158.00	901.14	256.85	4.508	
22,600.00	12,594.30	22,138.07	12,209.12	138.46	135.17	70.57	-9,979.48	-56.36	1,158.00	898.57	259.43	4.464	
22,700.00	12,595.17	22,238.07	12,209.99	139.81	136.53	70.57	-10,079.47	-55.49	1,158.00	896.00	262.00	4.420	
22,800.00	12,596.04	22,338.07	12,210.86	141.17	137.89	70.57	-10,179.46	-54.63	1,158.00	893.42	264.58	4.377	
22,807.56	12,596.11	22,345.63	12,210.93	141.27	137.99	70.57	-10,187.02	-54.57	1,158.00	893.23	264.77	4.374	
22,875.30	12,596.70	22,411.61	12,211.50	142.19	138.89	70.57	-10,253.00	-54.00	1,158.00	891.52	266.48	4.345	SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 31 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 137H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)														Rule Assigned:	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Reference (usft)	Major Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
0.00	0.00	0.00	1.00	0.50	0.50	135.00	-25.00	25.00	35.37						
100.00	100.00	99.00	100.00	0.98	0.97	135.00	-25.00	25.00	35.36	33.40	1.95	18.085			
200.00	200.00	199.00	200.00	1.56	1.56	135.00	-25.00	25.00	35.36	32.24	3.12	11.346			
300.00	300.00	299.00	300.00	1.98	1.98	135.00	-25.00	25.00	35.36	31.40	3.96	8.932	CC		
400.00	400.00	398.51	399.50	2.33	2.41	133.27	-24.70	26.23	36.03	31.36	4.68	7.707	ES		
500.00	500.00	497.87	498.79	2.63	2.77	128.42	-23.77	29.98	38.28	32.97	5.31	7.207			
600.00	600.00	596.98	597.68	2.91	3.11	121.56	-22.24	36.20	42.55	36.65	5.90	7.207			
700.00	700.00	696.31	696.65	3.16	3.25	114.45	-20.21	44.44	48.93	42.62	6.32	7.746			
800.00	800.00	795.93	795.89	3.40	3.49	108.93	-18.13	52.87	56.04	49.23	6.82	8.221			
900.00	900.00	895.55	895.13	3.62	3.73	104.67	-16.05	61.30	63.55	56.26	7.29	8.716			
1,000.00	1,000.00	995.17	994.37	3.76	3.96	9.33	-13.97	69.73	71.29	63.62	7.67	9.295			
1,100.00	1,099.98	1,094.93	1,093.75	4.00	4.19	6.80	-11.89	78.17	77.45	69.31	8.14	9.512			
1,200.00	1,199.88	1,194.82	1,193.26	4.24	4.41	4.79	-9.81	86.63	81.14	72.54	8.60	9.433			
1,300.00	1,299.63	1,294.78	1,292.84	4.46	4.63	3.06	-7.72	95.09	82.30	73.25	9.05	9.092			
1,400.00	1,399.25	1,394.75	1,392.43	4.60	4.85	1.41	-5.63	103.54	81.90	72.49	9.41	8.707			
1,500.00	1,498.87	1,494.72	1,492.02	4.78	5.06	-0.25	-3.55	112.00	81.54	71.74	9.80	8.319			
1,600.00	1,598.49	1,594.69	1,591.61	4.96	5.27	-1.93	-1.46	120.46	81.26	71.06	10.20	7.969			
1,700.00	1,698.11	1,694.66	1,691.20	5.14	5.47	-3.62	0.62	128.92	81.05	70.46	10.59	7.655			
1,800.00	1,797.73	1,794.63	1,790.79	5.32	5.68	-5.32	2.71	137.38	80.90	69.93	10.98	7.371			
1,900.00	1,897.34	1,894.60	1,890.38	5.49	5.88	-7.02	4.79	145.84	80.83	69.47	11.36	7.114			
1,951.30	1,948.45	1,945.89	1,941.47	5.59	5.98	-7.90	5.86	150.18	80.82	69.26	11.56	6.992			
2,000.00	1,996.96	1,994.58	1,989.97	5.67	6.08	-8.72	6.88	154.30	80.83	69.08	11.75	6.882			
2,100.00	2,096.58	2,094.55	2,089.56	5.85	6.28	-10.43	8.97	162.76	80.90	68.77	12.13	6.671			
2,200.00	2,196.20	2,194.52	2,189.15	6.04	6.49	-12.12	11.05	171.22	81.04	68.52	12.52	6.472			
2,300.00	2,295.72	2,292.67	2,286.84	6.23	6.70	-7.31	13.33	180.47	81.08	68.16	12.92	6.277			
2,400.00	2,394.97	2,390.58	2,384.01	6.43	6.92	-4.15	16.20	192.10	81.17	67.84	13.33	6.088			
2,500.00	2,493.89	2,488.49	2,480.84	6.64	7.15	-1.89	19.66	206.15	81.31	67.56	13.75	5.912			
2,600.00	2,592.40	2,586.40	2,577.28	6.85	7.38	-0.03	23.72	222.60	81.47	67.30	14.17	5.750			
2,700.00	2,690.45	2,684.31	2,673.24	7.07	7.61	1.72	28.36	241.44	81.64	67.06	14.58	5.598			
2,800.00	2,787.96	2,782.21	2,768.67	7.28	7.84	3.53	33.59	262.67	81.84	66.84	15.00	5.457			
2,900.00	2,884.87	2,880.25	2,863.64	7.49	8.03	5.47	39.42	286.29	82.06	66.69	15.36	5.341			
3,000.00	2,981.46	2,980.24	2,960.21	7.68	8.23	6.64	45.61	311.42	82.19	66.42	15.76	5.213			
3,100.00	3,078.05	3,080.22	3,056.79	7.87	8.45	7.81	51.81	336.55	82.35	66.17	16.18	5.089			
3,200.00	3,174.64	3,180.21	3,153.37	8.06	8.66	8.97	58.00	361.69	82.55	65.95	16.60	4.972			
3,300.00	3,271.24	3,280.19	3,249.94	8.26	8.89	10.13	64.20	386.82	82.78	65.75	17.02	4.862			
3,400.00	3,367.83	3,380.18	3,346.52	8.51	9.12	11.27	70.39	411.95	83.04	65.59	17.45	4.759			
3,500.00	3,464.42	3,480.16	3,443.10	8.80	9.37	12.42	76.59	437.08	83.34	65.46	17.88	4.661			
3,600.00	3,561.01	3,580.15	3,539.68	9.09	9.64	13.55	82.78	462.21	83.67	65.36	18.31	4.569			
3,700.00	3,657.60	3,680.14	3,636.25	9.38	9.94	14.67	88.98	487.34	84.04	65.29	18.75	4.482			
3,800.00	3,754.20	3,780.12	3,732.83	9.68	10.24	15.78	95.17	512.48	84.43	65.24	19.19	4.400			
3,900.00	3,850.79	3,880.11	3,829.41	9.98	10.55	16.89	101.36	537.61	84.86	65.22	19.64	4.322			
4,000.00	3,947.38	3,980.09	3,925.99	10.28	10.87	17.98	107.56	562.74	85.32	65.23	20.09	4.248			
4,100.00	4,043.97	4,080.08	4,022.56	10.59	11.18	19.06	113.75	587.87	85.80	65.26	20.54	4.177			
4,200.00	4,140.56	4,180.07	4,119.14	10.90	11.50	20.12	119.95	613.00	86.32	65.32	21.00	4.110			
4,300.00	4,237.16	4,280.05	4,215.72	11.21	11.82	21.18	126.14	638.13	86.87	65.40	21.47	4.046			
4,400.00	4,333.75	4,380.04	4,312.30	11.52	12.15	22.22	132.34	663.27	87.45	65.50	21.95	3.984			
4,500.00	4,430.34	4,480.02	4,408.87	11.84	12.47	23.24	138.53	688.40	88.05	65.62	22.43	3.926			
4,600.00	4,526.93	4,580.01	4,505.45	12.16	12.80	24.25	144.73	713.53	88.69	65.77	22.92	3.870			
4,700.00	4,623.53	4,679.99	4,602.03	12.48	13.13	25.25	150.92	738.66	89.35	65.94	23.41	3.816			
4,800.00	4,720.12	4,779.98	4,698.61	12.80	13.46	26.23	157.12	763.79	90.03	66.12	23.91	3.765			
4,900.00	4,816.71	4,879.97	4,795.18	13.12	13.79	27.20	163.31	788.92	90.75	66.33	24.42	3.716			
5,000.00	4,913.30	4,979.95	4,891.76	13.45	14.13	28.15	169.51	814.06	91.49	66.55	24.94	3.669			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 32 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 137H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Rule Assigned:	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Reference (usft)	Major Axis Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre		Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
							+N/-S (usft)	+E/-W (usft)						
5,100.00	5,009.89	5,079.94	4,988.34	13.78	14.46	29.08	175.70	839.19	92.25	66.79	25.46	3.623		
5,200.00	5,106.49	5,179.92	5,084.91	14.10	14.79	30.00	181.90	864.32	93.04	67.04	25.99	3.580		
5,300.00	5,203.08	5,279.91	5,181.49	14.43	15.13	30.91	188.09	889.45	93.85	67.32	26.53	3.538		
5,400.00	5,299.67	5,379.90	5,278.07	14.75	15.47	31.80	194.29	914.58	94.69	67.63	27.06	3.499		
5,500.00	5,396.65	5,479.87	5,374.63	15.07	15.80	32.20	200.48	939.71	96.84	69.25	27.59	3.510		
5,600.00	5,494.23	5,579.77	5,471.13	15.36	16.14	31.80	206.67	964.82	101.21	73.15	28.06	3.607		
5,700.00	5,592.35	5,679.52	5,567.48	15.62	16.48	30.73	212.85	989.89	107.83	79.35	28.48	3.786		
5,800.00	5,690.94	5,779.07	5,663.64	15.86	16.82	29.16	219.02	1,014.92	116.76	87.90	28.85	4.047		
5,900.00	5,789.93	5,878.34	5,759.52	16.07	17.15	27.30	225.17	1,039.87	128.07	98.88	29.19	4.387		
6,000.00	5,889.26	5,979.48	5,857.35	16.25	17.48	25.34	231.31	1,064.78	141.37	111.83	29.54	4.786		
6,100.00	5,988.86	6,082.19	5,957.32	16.41	17.79	23.62	236.95	1,087.67	154.86	124.96	29.90	5.179		
6,200.00	6,088.66	6,185.32	6,058.29	16.53	18.08	22.13	241.97	1,108.02	168.34	138.08	30.25	5.564		
6,300.00	6,188.59	6,288.85	6,160.19	16.64	18.34	20.82	246.35	1,125.78	181.77	151.19	30.58	5.943		
6,400.00	6,288.58	6,392.80	6,262.96	16.71	18.57	19.27	250.08	1,140.90	195.14	164.31	30.83	6.330		
6,500.00	6,388.58	6,497.36	6,366.72	16.76	18.77	18.09	253.15	1,153.37	206.99	175.95	31.04	6.669		
6,600.00	6,488.58	6,602.54	6,471.42	16.82	18.94	17.00	255.55	1,163.13	216.24	185.01	31.23	6.924		
6,700.00	6,588.58	6,708.21	6,576.84	16.88	19.08	15.95	257.27	1,170.11	222.84	191.43	31.41	7.095		
6,800.00	6,688.58	6,814.19	6,682.73	16.94	19.19	14.69	258.30	1,174.27	226.77	195.20	31.56	7.184		
6,900.00	6,788.58	6,920.05	6,788.58	17.00	19.26	13.61	258.62	1,175.57	228.00	196.32	31.67	7.198		
7,000.00	6,888.58	7,020.05	6,888.58	17.05	19.31	12.61	258.62	1,175.57	228.00	196.22	31.78	7.175		
7,100.00	6,988.58	7,120.05	6,988.58	17.11	19.36	11.61	258.62	1,175.57	228.00	196.11	31.89	7.150		
7,200.00	7,088.58	7,220.05	7,088.58	17.17	19.41	10.61	258.62	1,175.57	228.00	196.00	32.00	7.125		
7,300.00	7,188.58	7,320.05	7,188.58	17.23	19.46	9.61	258.62	1,175.57	228.00	195.88	32.11	7.100		
7,400.00	7,288.58	7,420.05	7,288.58	17.29	19.51	8.61	258.62	1,175.57	228.00	195.77	32.22	7.076		
7,500.00	7,388.58	7,520.05	7,388.58	17.35	19.56	7.61	258.62	1,175.57	228.00	195.66	32.34	7.051		
7,600.00	7,488.58	7,620.05	7,488.58	17.41	19.61	6.61	258.62	1,175.57	228.00	195.55	32.45	7.026		
7,700.00	7,588.58	7,720.05	7,588.58	17.47	19.66	5.61	258.62	1,175.57	228.00	195.43	32.56	7.002		
7,800.00	7,688.58	7,820.05	7,688.58	17.53	19.72	4.61	258.62	1,175.57	228.00	195.32	32.68	6.978		
7,900.00	7,788.58	7,920.05	7,788.58	17.59	19.77	3.61	258.62	1,175.57	228.00	195.21	32.79	6.953		
8,000.00	7,888.58	8,020.05	7,888.58	17.65	19.82	2.61	258.62	1,175.57	228.00	195.09	32.90	6.929		
8,100.00	7,988.58	8,120.05	7,988.58	17.71	19.87	1.61	258.62	1,175.57	228.00	194.98	33.02	6.905		
8,200.00	8,088.58	8,220.05	8,088.58	17.77	19.93	0.61	258.62	1,175.57	228.00	194.86	33.13	6.881		
8,300.00	8,188.58	8,320.05	8,188.58	17.83	19.98	0.61	258.62	1,175.57	228.00	194.74	33.25	6.857		
8,400.00	8,288.58	8,420.05	8,288.58	17.89	20.03	0.61	258.62	1,175.57	228.00	194.63	33.37	6.833		
8,500.00	8,388.58	8,520.05	8,388.58	17.95	20.09	0.61	258.62	1,175.57	228.00	194.51	33.48	6.809		
8,600.00	8,488.58	8,620.05	8,488.58	18.02	20.14	0.61	258.62	1,175.57	228.00	194.40	33.60	6.786		
8,700.00	8,588.58	8,720.05	8,588.58	18.08	20.19	0.61	258.62	1,175.57	228.00	194.28	33.72	6.762		
8,800.00	8,688.58	8,820.05	8,688.58	18.14	20.25	0.61	258.62	1,175.57	228.00	194.16	33.84	6.738		
8,900.00	8,788.58	8,920.05	8,788.58	18.20	20.30	0.61	258.62	1,175.57	228.00	194.04	33.95	6.715		
9,000.00	8,888.58	9,020.05	8,888.58	18.26	20.36	0.61	258.62	1,175.57	228.00	193.92	34.07	6.692		
9,100.00	8,988.58	9,120.05	8,988.58	18.32	20.41	0.61	258.62	1,175.57	228.00	193.80	34.19	6.668		
9,200.00	9,088.58	9,220.05	9,088.58	18.39	20.47	0.61	258.62	1,175.57	228.00	193.69	34.31	6.645		
9,300.00	9,188.58	9,320.05	9,188.58	18.45	20.52	0.61	258.62	1,175.57	228.00	193.57	34.43	6.622		
9,400.00	9,288.58	9,420.05	9,288.58	18.51	20.58	0.61	258.62	1,175.57	228.00	193.45	34.55	6.599		
9,500.00	9,388.58	9,520.05	9,388.58	18.57	20.63	0.61	258.62	1,175.57	228.00	193.33	34.67	6.576		
9,600.00	9,488.58	9,620.05	9,488.58	18.64	20.69	0.61	258.62	1,175.57	228.00	193.21	34.79	6.554		
9,700.00	9,588.58	9,720.05	9,588.58	18.70	20.74	0.61	258.62	1,175.57	228.00	193.08	34.91	6.531		
9,800.00	9,688.58	9,820.05	9,688.58	18.76	20.80	0.61	258.62	1,175.57	228.00	192.96	35.03	6.508		
9,900.00	9,788.58	9,920.05	9,788.58	18.83	20.85	0.61	258.62	1,175.57	228.00	192.84	35.15	6.486		
10,000.00	9,888.58	10,020.05	9,888.58	18.89	20.91	0.61	258.62	1,175.57	228.00	192.72	35.28	6.463		
10,100.00	9,988.58	10,120.05	9,988.58	18.95	20.97	0.61	258.62	1,175.57	228.00	192.60	35.40	6.441		
10,200.00	10,088.58	10,220.05	10,088.58	19.02	21.02	0.61	258.62	1,175.57	228.00	192.47	35.52	6.419		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 33 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 137H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
10,300.00	10,188.58	10,320.05	10,188.58	19.08	21.08	89.61	258.62	1,175.57	228.00	192.35	35.64	6.397	
10,400.00	10,288.58	10,420.05	10,288.58	19.15	21.14	89.61	258.62	1,175.57	228.00	192.23	35.77	6.375	
10,500.00	10,388.58	10,520.05	10,388.58	19.21	21.19	89.61	258.62	1,175.57	228.00	192.11	35.89	6.353	
10,600.00	10,488.58	10,620.05	10,488.58	19.27	21.25	89.61	258.62	1,175.57	228.00	191.98	36.01	6.331	
10,700.00	10,588.58	10,720.05	10,588.58	19.34	21.31	89.61	258.62	1,175.57	228.00	191.86	36.14	6.309	
10,800.00	10,688.58	10,820.05	10,688.58	19.40	21.36	89.61	258.62	1,175.57	228.00	191.73	36.26	6.287	
10,900.00	10,788.58	10,920.05	10,788.58	19.47	21.42	89.61	258.62	1,175.57	228.00	191.61	36.39	6.266	
11,000.00	10,888.58	11,020.05	10,888.58	19.53	21.48	89.61	258.62	1,175.57	228.00	191.48	36.51	6.244	
11,100.00	10,988.58	11,120.05	10,988.58	19.60	21.54	89.61	258.62	1,175.57	228.00	191.36	36.64	6.223	
11,200.00	11,088.58	11,220.05	11,088.58	19.66	21.60	89.61	258.62	1,175.57	228.00	191.23	36.76	6.202	
11,300.00	11,188.58	11,320.05	11,188.58	19.73	21.65	89.61	258.62	1,175.57	228.00	191.11	36.89	6.181	
11,400.00	11,288.58	11,420.05	11,288.58	19.79	21.71	89.61	258.62	1,175.57	228.00	190.98	37.02	6.159	
11,500.00	11,388.58	11,520.05	11,388.58	19.86	21.77	89.61	258.62	1,175.57	228.00	190.85	37.14	6.138	
11,600.00	11,488.58	11,620.05	11,488.58	19.92	21.83	89.61	258.62	1,175.57	228.00	190.73	37.27	6.118	
11,607.38	11,495.96	11,627.43	11,495.96	19.93	21.83	89.61	258.62	1,175.57	228.00	190.72	37.28	6.116	
11,700.00	11,588.58	11,719.98	11,588.50	19.99	21.88	89.86	257.64	1,175.58	228.00	190.63	37.37	6.101	
11,800.00	11,688.58	11,817.61	11,685.00	20.05	21.93	93.36	243.68	1,175.70	228.54	191.03	37.50	6.094	
11,900.00	11,788.58	11,908.12	11,771.16	20.12	21.97	100.13	216.28	1,175.93	232.62	194.77	37.85	6.145	
12,000.00	11,888.58	11,988.37	11,843.12	20.19	22.00	108.42	180.91	1,176.24	245.26	206.56	38.70	6.338	
12,100.00	11,988.51	12,058.50	11,901.44	20.25	22.03	-61.84	142.02	1,176.57	269.66	229.52	40.14	6.717	
12,200.00	12,086.82	12,125.05	11,951.99	20.31	22.07	-53.18	98.80	1,176.95	299.74	257.95	41.79	7.172	
12,300.00	12,180.57	12,189.65	11,995.95	20.35	22.12	-46.40	51.52	1,177.35	330.95	287.50	43.45	7.616	
12,400.00	12,266.93	12,250.00	12,031.97	20.39	22.19	-41.35	3.13	1,177.77	360.70	315.56	45.14	7.991	
12,500.00	12,343.26	12,314.85	12,064.77	20.44	22.29	-37.40	-52.77	1,178.25	387.23	340.64	46.60	8.310	
12,600.00	12,407.24	12,376.11	12,089.77	20.52	22.41	-34.62	-108.66	1,178.73	409.48	361.46	48.03	8.526	
12,700.00	12,456.94	12,436.79	12,108.52	20.67	22.56	-32.69	-166.34	1,179.23	426.68	377.35	49.33	8.649	
12,800.00	12,490.84	12,500.00	12,121.45	20.88	22.75	-31.46	-228.18	1,179.76	438.36	387.90	50.46	8.687	
12,900.00	12,507.91	12,557.16	12,127.21	21.18	22.96	-30.90	-285.03	1,180.25	444.18	392.66	51.52	8.622	
13,000.00	12,510.43	12,640.96	12,128.45	21.56	23.29	-30.83	-368.81	1,180.97	444.86	392.77	52.09	8.540	
13,100.00	12,511.30	12,740.96	12,129.33	22.01	23.76	-30.83	-468.80	1,181.84	444.86	392.34	52.52	8.471	
13,200.00	12,512.18	12,840.96	12,130.20	22.52	24.28	-30.83	-568.79	1,182.70	444.86	391.88	52.98	8.396	
13,300.00	12,513.05	12,940.96	12,131.07	23.10	24.85	-30.83	-668.78	1,183.56	444.86	391.36	53.50	8.315	
13,400.00	12,513.92	13,040.96	12,131.94	23.73	25.48	-30.83	-768.78	1,184.42	444.86	390.81	54.06	8.230	
13,500.00	12,514.80	13,140.96	12,132.81	24.41	26.15	-30.83	-868.77	1,185.28	444.87	390.21	54.65	8.140	
13,600.00	12,515.67	13,240.96	12,133.68	25.15	26.86	-30.83	-968.76	1,186.14	444.87	389.58	55.29	8.046	
13,700.00	12,516.55	13,340.96	12,134.56	25.93	27.62	-30.83	-1,068.75	1,187.00	444.87	388.90	55.97	7.948	
13,800.00	12,517.42	13,440.96	12,135.43	26.76	28.41	-30.83	-1,168.75	1,187.86	444.87	388.19	56.69	7.848	
13,900.00	12,518.29	13,540.96	12,136.30	27.63	29.24	-30.83	-1,268.74	1,188.73	444.87	387.44	57.44	7.745	
14,000.00	12,519.17	13,640.96	12,137.17	28.53	30.11	-30.83	-1,368.73	1,189.59	444.88	386.65	58.22	7.641	
14,100.00	12,520.04	13,740.96	12,138.04	29.47	31.01	-30.83	-1,468.72	1,190.45	444.88	385.84	59.04	7.535	
14,200.00	12,520.91	13,840.96	12,138.91	30.44	31.94	-30.83	-1,568.72	1,191.31	444.88	384.99	59.89	7.428	
14,300.00	12,521.79	13,940.96	12,139.79	31.44	32.89	-30.83	-1,668.71	1,192.17	444.88	384.11	60.78	7.320	
14,400.00	12,522.66	14,040.96	12,140.66	32.46	33.88	-30.83	-1,768.70	1,193.03	444.88	383.20	61.69	7.212	
14,500.00	12,523.53	14,140.96	12,141.53	33.51	34.88	-30.83	-1,868.69	1,193.89	444.88	382.26	62.63	7.104	
14,600.00	12,524.41	14,240.96	12,142.40	34.58	35.91	-30.83	-1,968.69	1,194.75	444.89	381.30	63.59	6.996	
14,700.00	12,525.28	14,340.96	12,143.27	35.67	36.96	-30.83	-2,068.68	1,195.62	444.89	380.31	64.58	6.889	
14,800.00	12,526.16	14,440.96	12,144.14	36.78	38.03	-30.83	-2,168.67	1,196.48	444.89	379.29	65.60	6.782	
14,900.00	12,527.03	14,540.96	12,145.02	37.90	39.12	-30.83	-2,268.66	1,197.34	444.89	378.25	66.64	6.676	
15,000.00	12,527.90	14,640.96	12,145.89	39.04	40.22	-30.83	-2,368.66	1,198.20	444.89	377.19	67.70	6.572	
15,100.00	12,528.78	14,740.96	12,146.76	40.20	41.34	-30.83	-2,468.65	1,199.06	444.89	376.11	68.78	6.468	
15,200.00	12,529.65	14,840.96	12,147.63	41.37	42.48	-30.83	-2,568.64	1,199.92	444.90	375.01	69.88	6.366	
15,300.00	12,530.52	14,940.96	12,148.50	42.55	43.62	-30.83	-2,668.63	1,200.78	444.90	373.89	71.01	6.266	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 34 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 137H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5) Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,400.00	12,531.40	15,040.96	12,149.37	43.74	44.78	-30.83	-2,768.63	1,201.65	444.90	372.75	72.15	6.167	
15,500.00	12,532.27	15,140.96	12,150.25	44.94	45.95	-30.83	-2,868.62	1,202.51	444.90	371.60	73.30	6.069	
15,600.00	12,533.14	15,240.96	12,151.12	46.15	47.13	-30.83	-2,968.61	1,203.37	444.90	370.43	74.48	5.974	
15,700.00	12,534.02	15,340.96	12,151.99	47.37	48.32	-30.83	-3,068.60	1,204.23	444.91	369.24	75.67	5.880	
15,800.00	12,534.89	15,440.96	12,152.86	48.59	49.52	-30.83	-3,168.60	1,205.09	444.91	368.03	76.87	5.787	
15,900.00	12,535.76	15,540.96	12,153.73	49.83	50.73	-30.83	-3,268.59	1,205.95	444.91	366.81	78.09	5.697	
16,000.00	12,536.64	15,640.96	12,154.60	51.07	51.95	-30.83	-3,368.58	1,206.81	444.91	365.58	79.33	5.608	
16,100.00	12,537.51	15,740.96	12,155.47	52.32	53.17	-30.83	-3,468.57	1,207.67	444.91	364.34	80.58	5.522	
16,200.00	12,538.39	15,840.96	12,156.35	53.57	54.40	-30.83	-3,568.57	1,208.54	444.91	363.08	81.84	5.437	
16,300.00	12,539.26	15,940.96	12,157.22	54.83	55.63	-30.83	-3,668.56	1,209.40	444.92	361.81	83.11	5.354	
16,400.00	12,540.13	16,040.96	12,158.09	56.09	56.88	-30.83	-3,768.55	1,210.26	444.92	360.53	84.39	5.272	
16,500.00	12,541.01	16,140.96	12,158.96	57.36	58.13	-30.83	-3,868.54	1,211.12	444.92	359.24	85.68	5.193	
16,600.00	12,541.88	16,240.96	12,159.83	58.64	59.38	-30.83	-3,968.54	1,211.98	444.92	357.93	86.99	5.115	
16,700.00	12,542.75	16,340.96	12,160.70	59.91	60.64	-30.83	-4,068.53	1,212.84	444.92	356.62	88.30	5.039	
16,800.00	12,543.63	16,440.96	12,161.58	61.20	61.90	-30.83	-4,168.52	1,213.70	444.92	355.30	89.63	4.964	
16,900.00	12,544.50	16,540.96	12,162.45	62.48	63.17	-30.83	-4,268.51	1,214.56	444.93	353.97	90.96	4.891	
17,000.00	12,545.37	16,640.96	12,163.32	63.77	64.44	-30.83	-4,368.51	1,215.43	444.93	352.63	92.30	4.820	
17,100.00	12,546.25	16,740.96	12,164.19	65.06	65.71	-30.83	-4,468.50	1,216.29	444.93	351.28	93.65	4.751	
17,200.00	12,547.12	16,840.96	12,165.06	66.36	66.99	-30.83	-4,568.49	1,217.15	444.93	349.92	95.01	4.683	
17,300.00	12,547.99	16,940.96	12,165.93	67.66	68.28	-30.83	-4,668.48	1,218.01	444.93	348.56	96.38	4.617	
17,400.00	12,548.87	17,040.96	12,166.81	68.96	69.56	-30.83	-4,768.48	1,218.87	444.94	347.19	97.75	4.552	
17,500.00	12,549.74	17,140.96	12,167.68	70.26	70.85	-30.83	-4,868.47	1,219.73	444.94	345.81	99.13	4.488	
17,600.00	12,550.62	17,240.96	12,168.55	71.57	72.14	-30.83	-4,968.46	1,220.59	444.94	344.42	100.52	4.427	
17,700.00	12,551.49	17,340.96	12,169.42	72.88	73.44	-30.83	-5,068.45	1,221.45	444.94	343.03	101.91	4.366	
17,800.00	12,552.36	17,440.96	12,170.29	74.19	74.74	-30.83	-5,168.45	1,222.32	444.94	341.63	103.31	4.307	
17,900.00	12,553.24	17,540.96	12,171.16	75.50	76.04	-30.83	-5,268.44	1,223.18	444.94	340.23	104.72	4.249	
18,000.00	12,554.11	17,640.96	12,172.04	76.81	77.34	-30.83	-5,368.43	1,224.04	444.95	338.82	106.13	4.193	
18,100.00	12,554.98	17,740.96	12,172.91	78.13	78.65	-30.83	-5,468.42	1,224.90	444.95	337.40	107.54	4.137	
18,200.00	12,555.86	17,840.96	12,173.78	79.45	79.95	-30.83	-5,568.42	1,225.76	444.95	335.98	108.97	4.083	
18,300.00	12,556.73	17,940.96	12,174.65	80.77	81.26	-30.83	-5,668.41	1,226.62	444.95	334.56	110.39	4.031	
18,400.00	12,557.60	18,040.96	12,175.52	82.09	82.57	-30.83	-5,768.40	1,227.48	444.95	333.13	111.82	3.979	
18,500.00	12,558.48	18,140.96	12,176.39	83.42	83.89	-30.83	-5,868.39	1,228.35	444.95	331.69	113.26	3.929	
18,600.00	12,559.35	18,240.96	12,177.27	84.74	85.20	-30.82	-5,968.39	1,229.21	444.96	330.25	114.70	3.879	
18,700.00	12,560.23	18,340.96	12,178.14	86.07	86.52	-30.82	-6,068.38	1,230.07	444.96	328.81	116.15	3.831	
18,800.00	12,561.10	18,440.96	12,179.01	87.40	87.83	-30.82	-6,168.37	1,230.93	444.96	327.36	117.60	3.784	
18,900.00	12,561.97	18,540.96	12,179.88	88.72	89.15	-30.82	-6,268.36	1,231.79	444.96	325.91	119.05	3.738	
19,000.00	12,562.85	18,640.96	12,180.75	90.05	90.48	-30.82	-6,368.36	1,232.65	444.96	324.45	120.51	3.692	
19,100.00	12,563.72	18,740.96	12,181.62	91.39	91.80	-30.82	-6,468.35	1,233.51	444.97	322.99	121.97	3.648	
19,200.00	12,564.59	18,840.96	12,182.50	92.72	93.12	-30.82	-6,568.34	1,234.37	444.97	321.53	123.44	3.605	
19,300.00	12,565.47	18,940.96	12,183.37	94.05	94.45	-30.82	-6,668.33	1,235.24	444.97	320.06	124.90	3.562	
19,400.00	12,566.34	19,040.96	12,184.24	95.39	95.77	-30.82	-6,768.33	1,236.10	444.97	318.59	126.38	3.521	
19,500.00	12,567.21	19,140.96	12,185.11	96.72	97.10	-30.82	-6,868.32	1,236.96	444.97	317.12	127.85	3.480	
19,600.00	12,568.09	19,240.96	12,185.98	98.06	98.43	-30.82	-6,968.31	1,237.82	444.97	315.64	129.33	3.441	
19,700.00	12,568.96	19,340.96	12,186.85	99.40	99.76	-30.82	-7,068.30	1,238.68	444.98	314.16	130.81	3.402	
19,800.00	12,569.83	19,440.96	12,187.72	100.73	101.09	-30.82	-7,168.30	1,239.54	444.98	312.68	132.30	3.363	
19,900.00	12,570.71	19,540.96	12,188.60	102.07	102.42	-30.82	-7,268.29	1,240.40	444.98	311.20	133.78	3.326	
20,000.00	12,571.58	19,640.96	12,189.47	103.41	103.76	-30.82	-7,368.28	1,241.26	444.98	309.71	135.27	3.290	
20,100.00	12,572.46	19,740.96	12,190.34	104.75	105.09	-30.82	-7,468.27	1,242.13	444.98	308.22	136.77	3.254	
20,200.00	12,573.33	19,840.96	12,191.21	106.10	106.43	-30.82	-7,568.27	1,242.99	444.98	306.72	138.26	3.218	
20,300.00	12,574.20	19,940.96	12,192.08	107.44	107.76	-30.82	-7,668.26	1,243.85	444.99	305.23	139.76	3.184	
20,400.00	12,575.08	20,040.96	12,192.95	108.78	109.10	-30.82	-7,768.25	1,244.71	444.99	303.73	141.26	3.150	
20,500.00	12,575.95	20,140.96	12,193.83	110.12	110.44	-30.82	-7,868.24	1,245.57	444.99	302.23	142.76	3.117	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 35 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 137H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:		Warning	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,600.00	12,576.82	20,240.96	12,194.70	111.47	111.77	-30.82	-7,968.24	1,246.43	444.99	300.73	144.27	3.085			
20,700.00	12,577.70	20,340.96	12,195.57	112.81	113.11	-30.82	-8,068.23	1,247.29	444.99	299.22	145.77	3.053			
20,800.00	12,578.57	20,440.96	12,196.44	114.16	114.45	-30.82	-8,168.22	1,248.15	445.00	297.71	147.28	3.021			
20,900.00	12,579.44	20,540.96	12,197.31	115.51	115.79	-30.82	-8,268.21	1,249.02	445.00	296.21	148.79	2.991			
21,000.00	12,580.32	20,640.96	12,198.18	116.85	117.13	-30.82	-8,368.21	1,249.88	445.00	294.69	150.30	2.961			
21,100.00	12,581.19	20,740.96	12,199.06	118.20	118.48	-30.82	-8,468.20	1,250.74	445.00	293.18	151.82	2.931			
21,200.00	12,582.06	20,840.96	12,199.93	119.55	119.82	-30.82	-8,568.19	1,251.60	445.00	291.67	153.34	2.902			
21,300.00	12,582.94	20,940.96	12,200.80	120.89	121.16	-30.82	-8,668.18	1,252.46	445.00	290.15	154.85	2.874			
21,400.00	12,583.81	21,040.96	12,201.67	122.24	122.50	-30.82	-8,768.18	1,253.32	445.01	288.63	156.37	2.846			
21,500.00	12,584.69	21,140.96	12,202.54	123.59	123.85	-30.82	-8,868.17	1,254.18	445.01	287.11	157.90	2.818			
21,600.00	12,585.56	21,240.96	12,203.41	124.94	125.19	-30.82	-8,968.16	1,255.05	445.01	285.59	159.42	2.791			
21,700.00	12,586.43	21,340.96	12,204.29	126.29	126.54	-30.82	-9,068.15	1,255.91	445.01	284.07	160.95	2.765			
21,800.00	12,587.31	21,440.96	12,205.16	127.64	127.88	-30.82	-9,168.15	1,256.77	445.01	282.54	162.47	2.739			
21,900.00	12,588.18	21,540.96	12,206.03	128.99	129.23	-30.82	-9,268.14	1,257.63	445.01	281.01	164.00	2.713			
22,000.00	12,589.05	21,640.96	12,206.90	130.34	130.58	-30.82	-9,368.13	1,258.49	445.02	279.49	165.53	2.688			
22,100.00	12,589.93	21,740.96	12,207.77	131.70	131.93	-30.82	-9,468.12	1,259.35	445.02	277.96	167.06	2.664			
22,200.00	12,590.80	21,840.96	12,208.64	133.05	133.27	-30.82	-9,568.12	1,260.21	445.02	276.43	168.59	2.640			
22,300.00	12,591.67	21,940.96	12,209.52	134.40	134.62	-30.82	-9,668.11	1,261.07	445.02	274.89	170.13	2.616			
22,400.00	12,592.55	22,040.96	12,210.39	135.75	135.97	-30.82	-9,768.10	1,261.94	445.02	273.36	171.66	2.592			
22,500.00	12,593.42	22,140.96	12,211.26	137.11	137.32	-30.82	-9,868.09	1,262.80	445.03	271.82	173.20	2.569			
22,600.00	12,594.30	22,240.96	12,212.13	138.46	138.67	-30.82	-9,968.09	1,263.66	445.03	270.29	174.74	2.547			
22,700.00	12,595.17	22,340.96	12,213.00	139.81	140.02	-30.82	-10,068.08	1,264.52	445.03	268.75	176.28	2.525			
22,800.00	12,596.04	22,440.96	12,213.87	141.17	141.37	-30.82	-10,168.07	1,265.38	445.03	267.21	177.82	2.503			
22,807.14	12,596.10	22,448.10	12,213.94	141.26	141.46	-30.82	-10,175.21	1,265.44	445.03	267.10	177.93	2.501			
22,875.30	12,596.70	22,512.90	12,214.50	142.19	142.34	-30.82	-10,240.00	1,266.00	445.04	265.85	179.20	2.484	SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 36 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 138H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Rule Assigned:		Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)
Reference Depth (usft)	Offset Depth (usft)	Reference Depth (usft)	Offset Depth (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)
Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
0.00	0.00	0.00	1.00	0.50	0.50
100.00	100.00	99.00	100.00	0.98	0.97
200.00	200.00	199.00	200.00	1.56	1.56
300.00	300.00	299.00	300.00	1.98	1.98
400.00	400.00	373.21	374.20	2.33	2.29
500.00	500.00	447.10	448.06	2.63	2.58
600.00	600.00	520.88	521.76	2.91	2.84
700.00	700.00	600.00	600.69	3.16	3.10
800.00	800.00	680.29	680.69	3.40	3.20
900.00	900.00	779.91	779.93	3.62	3.43
1,000.00	1,000.00	879.53	879.17	3.76	3.66
1,100.00	1,099.98	979.26	978.52	4.00	3.89
1,200.00	1,199.88	1,079.08	1,077.96	4.24	4.12
1,300.00	1,299.63	1,178.93	1,177.43	4.46	4.34
1,400.00	1,399.25	1,278.77	1,276.89	4.60	4.56
1,500.00	1,498.87	1,378.61	1,376.35	4.78	4.78
1,600.00	1,598.49	1,450.21	1,447.66	4.96	4.93
1,700.00	1,698.11	1,500.00	1,497.18	5.14	5.04
1,738.03	1,735.99	1,536.20	1,533.16	5.21	5.13
1,800.00	1,797.73	1,574.79	1,571.46	5.32	5.22
1,900.00	1,897.34	1,637.02	1,633.13	5.49	5.37
2,000.00	1,996.96	1,700.00	1,695.41	5.67	5.52
2,100.00	2,096.58	1,771.09	1,765.53	5.85	5.64
2,200.00	2,196.20	1,854.66	1,847.82	6.04	5.79
2,300.00	2,295.72	1,954.23	1,945.88	6.23	5.99
2,400.00	2,394.97	2,053.85	2,043.98	6.43	6.20
2,500.00	2,493.89	2,153.44	2,142.06	6.64	6.41
2,600.00	2,592.40	2,252.94	2,240.04	6.85	6.61
2,700.00	2,690.45	2,352.27	2,337.86	7.07	6.82
2,800.00	2,787.96	2,451.37	2,435.46	7.28	7.02
2,900.00	2,884.87	2,550.17	2,532.76	7.49	7.23
3,000.00	2,981.46	2,648.81	2,629.90	7.68	7.43
3,100.00	3,078.05	2,747.44	2,727.03	7.87	7.64
3,200.00	3,174.64	2,846.08	2,824.17	8.06	7.84
3,300.00	3,271.24	2,944.72	2,921.30	8.26	8.05
3,400.00	3,367.83	3,043.35	3,018.44	8.51	8.27
3,500.00	3,464.42	3,141.99	3,115.58	8.80	8.51
3,600.00	3,561.01	3,240.62	3,212.71	9.09	8.74
3,700.00	3,657.60	3,339.26	3,309.85	9.38	8.98
3,800.00	3,754.20	3,437.89	3,406.98	9.68	9.22
3,900.00	3,850.79	3,536.53	3,504.12	9.98	9.46
4,000.00	3,947.38	3,635.16	3,601.26	10.28	9.70
4,100.00	4,043.97	3,733.80	3,698.39	10.59	9.93
4,200.00	4,140.56	3,832.44	3,795.53	10.90	10.17
4,300.00	4,237.16	3,931.07	3,892.66	11.21	10.41
4,400.00	4,333.75	4,029.71	3,989.80	11.52	10.65
4,500.00	4,430.34	4,128.34	4,086.94	11.84	10.89
4,600.00	4,526.93	4,226.98	4,184.07	12.16	11.13
4,700.00	4,623.53	4,325.61	4,281.21	12.48	11.37
4,800.00	4,720.12	4,424.25	4,378.34	12.80	11.61
4,900.00	4,816.71	4,522.89	4,475.48	13.12	11.85
5,000.00	4,913.30	4,621.52	4,572.61	13.45	12.09

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 37 of 108

Total Directional Anticollision Report

Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 138H - OH - Plan 1													Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Offset Well Error: 0.50 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned: Distance			Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Tooflance (")	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
5,100.00	5,009.89	4,720.16	4,669.75	13.78	12.34	11.71	412.58	2,901.73	2,187.73	2,163.61	24.11	90.724		
5,200.00	5,106.49	4,818.79	4,766.89	14.10	12.58	12.05	406.43	2,917.72	2,177.75	2,153.20	24.55	88.690		
5,300.00	5,203.08	4,917.43	4,864.02	14.43	12.82	12.40	400.27	2,933.71	2,167.86	2,142.87	25.00	86.729		
5,400.00	5,299.67	5,016.06	4,961.16	14.75	13.06	12.74	394.11	2,949.70	2,158.06	2,132.63	25.43	84.872		
5,500.00	5,396.65	5,114.88	5,058.47	15.07	13.30	13.06	387.94	2,965.72	2,149.82	2,123.94	25.88	83.064		
5,600.00	5,494.23	5,213.94	5,156.02	15.36	13.54	13.37	381.75	2,981.78	2,144.20	2,117.86	26.33	81.433		
5,700.00	5,592.35	5,313.18	5,253.76	15.62	13.79	13.67	375.56	2,997.87	2,141.19	2,114.41	26.77	79.972		
5,765.48	5,656.86	5,378.24	5,317.83	15.78	13.95	13.87	371.49	3,008.41	2,140.63	2,113.57	27.06	79.107	CC	
5,800.00	5,690.94	5,412.54	5,351.61	15.86	14.03	13.97	369.35	3,013.97	2,140.78	2,113.57	27.21	78.674		
5,900.00	5,789.93	5,511.95	5,449.50	16.07	14.28	14.26	363.15	3,030.09	2,142.98	2,115.34	27.64	77.535		
6,000.00	5,889.26	5,611.33	5,547.38	16.25	14.52	14.55	356.94	3,046.20	2,147.76	2,119.70	28.06	76.548		
6,100.00	5,988.86	5,710.63	5,645.16	16.41	14.76	14.82	350.74	3,062.30	2,155.11	2,126.64	28.47	75.709		
6,200.00	6,088.66	5,809.76	5,742.79	16.53	15.01	15.09	344.55	3,078.37	2,165.01	2,136.15	28.86	75.016		
6,300.00	6,188.59	5,908.68	5,840.20	16.64	15.25	15.34	338.37	3,094.40	2,177.47	2,148.23	29.24	74.471		
6,400.00	6,288.58	6,007.30	5,937.32	16.71	15.49	88.01	332.22	3,110.39	2,192.44	2,162.89	29.54	74.217		
6,500.00	6,388.58	6,105.77	6,034.30	16.76	15.74	88.19	326.07	3,126.35	2,208.47	2,178.65	29.81	74.080		
6,600.00	6,488.58	6,204.25	6,131.28	16.82	15.98	88.36	319.92	3,142.32	2,224.52	2,194.44	30.08	73.946		
6,700.00	6,588.58	6,302.73	6,228.27	16.88	16.22	88.53	313.77	3,158.28	2,240.59	2,210.24	30.35	73.815		
6,800.00	6,688.58	6,401.21	6,325.25	16.94	16.46	88.70	307.62	3,174.25	2,256.68	2,226.06	30.63	73.686		
6,900.00	6,788.58	6,499.69	6,422.23	17.00	16.70	88.87	301.47	3,190.21	2,272.79	2,241.89	30.90	73.560		
7,000.00	6,888.58	6,598.17	6,519.21	17.05	16.95	89.03	295.32	3,206.18	2,288.92	2,257.75	31.17	73.436		
7,100.00	6,988.58	6,695.25	6,723.91	17.11	17.40	89.32	284.14	3,235.22	2,303.06	2,271.41	31.65	72.772		
7,200.00	7,088.58	7,032.51	6,950.13	17.17	17.77	89.52	276.46	3,255.16	2,311.81	2,279.73	32.08	72.070		
7,300.00	7,188.58	7,261.53	7,178.98	17.23	17.99	89.59	273.62	3,262.51	2,315.01	2,282.67	32.34	71.580		
7,400.00	7,288.58	7,371.13	7,288.58	17.29	18.03	89.59	273.61	3,262.55	2,315.03	2,282.60	32.43	71.393		
7,500.00	7,388.58	7,471.13	7,388.58	17.35	18.06	89.59	273.61	3,262.55	2,315.03	2,282.51	32.52	71.188		
7,600.00	7,488.58	7,571.13	7,488.58	17.41	18.10	89.59	273.61	3,262.55	2,315.03	2,282.42	32.61	70.983		
7,700.00	7,588.58	7,671.13	7,588.58	17.47	18.14	89.59	273.61	3,262.55	2,315.03	2,282.32	32.71	70.778		
7,800.00	7,688.58	7,771.13	7,688.58	17.53	18.17	89.59	273.61	3,262.55	2,315.03	2,282.23	32.80	70.573		
7,900.00	7,788.58	7,871.13	7,788.58	17.59	18.21	89.59	273.61	3,262.55	2,315.03	2,282.13	32.90	70.368		
8,000.00	7,888.58	7,971.13	7,888.58	17.65	18.25	89.59	273.61	3,262.55	2,315.03	2,282.03	32.99	70.163		
8,100.00	7,988.58	8,071.13	7,988.58	17.71	18.29	89.59	273.61	3,262.55	2,315.03	2,281.94	33.09	69.959		
8,200.00	8,088.58	8,171.13	8,088.58	17.77	18.33	89.59	273.61	3,262.55	2,315.03	2,281.84	33.19	69.754		
8,300.00	8,188.58	8,271.13	8,188.58	17.83	18.36	89.59	273.61	3,262.55	2,315.03	2,281.74	33.29	69.550		
8,400.00	8,288.58	8,371.13	8,288.58	17.89	18.40	89.59	273.61	3,262.55	2,315.03	2,281.65	33.38	69.346		
8,500.00	8,388.58	8,471.13	8,388.58	17.95	18.44	89.59	273.61	3,262.55	2,315.03	2,281.55	33.48	69.142		
8,600.00	8,488.58	8,571.13	8,488.58	18.02	18.48	89.59	273.61	3,262.55	2,315.03	2,281.45	33.58	68.938		
8,700.00	8,588.58	8,671.13	8,588.58	18.08	18.52	89.59	273.61	3,262.55	2,315.03	2,281.35	33.68	68.734		
8,800.00	8,688.58	8,771.13	8,688.58	18.14	18.56	89.59	273.61	3,262.55	2,315.03	2,281.25	33.78	68.531		
8,900.00	8,788.58	8,871.13	8,788.58	18.20	18.60	89.59	273.61	3,262.55	2,315.03	2,281.15	33.88	68.328		
9,000.00	8,888.58	8,971.13	8,888.58	18.26	18.64	89.59	273.61	3,262.55	2,315.03	2,281.05	33.98	68.126		
9,100.00	8,988.58	9,071.13	8,988.58	18.32	18.68	89.59	273.61	3,262.55	2,315.03	2,280.95	34.08	67.923		
9,200.00	9,088.58	9,171.13	9,088.58	18.39	18.73	89.59	273.61	3,262.55	2,315.03	2,280.84	34.18	67.721		
9,300.00	9,188.58	9,271.13	9,188.58	18.45	18.77	89.59	273.61	3,262.55	2,315.03	2,280.74	34.29	67.519		
9,400.00	9,288.58	9,371.13	9,288.58	18.51	18.81	89.59	273.61	3,262.55	2,315.03	2,280.64	34.39	67.318		
9,500.00	9,388.58	9,471.13	9,388.58	18.57	18.85	89.59	273.61	3,262.55	2,315.03	2,280.54	34.49	67.117		
9,600.00	9,488.58	9,571.13	9,488.58	18.64	18.89	89.59	273.61	3,262.55	2,315.03	2,280.43	34.60	66.916		
9,700.00	9,588.58	9,671.13	9,588.58	18.70	18.94	89.59	273.61	3,262.55	2,315.03	2,280.33	34.70	66.715		
9,800.00	9,688.58	9,771.13	9,688.58	18.76	18.98	89.59	273.61	3,262.55	2,315.03	2,280.22	34.80	66.515		
9,900.00	9,788.58	9,871.13	9,788.58	18.83	19.02	89.59	273.61	3,262.55	2,315.03	2,280.12	34.91	66.316		
10,000.00	9,888.58	9,971.13	9,888.58	18.89	19.06	89.59	273.61	3,262.55	2,315.03	2,280.01	35.01	66.116		
10,100.00	9,988.58	10,071.13	9,988.58	18.95	19.11	89.59	273.61	3,262.55	2,315.03	2,279.91	35.12	65.917		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 138H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference		Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,300.00	12,530.52	14,788.05	12,044.64	42.55	49.94	-78.15	-2,649.67	3,289.11	2,366.82	2,277.16	89.66	26.397	
15,400.00	12,531.40	14,888.05	12,045.35	43.74	51.19	-78.15	-2,749.66	3,290.02	2,366.90	2,274.79	92.12	25.694	
15,500.00	12,532.27	14,988.05	12,046.06	44.94	52.45	-78.15	-2,849.65	3,290.93	2,366.98	2,272.40	94.58	25.025	
15,600.00	12,533.14	15,088.05	12,046.77	46.15	53.72	-78.14	-2,949.65	3,291.84	2,367.07	2,270.00	97.06	24.387	
15,700.00	12,534.02	15,188.05	12,047.48	47.37	54.99	-78.14	-3,049.64	3,292.75	2,367.15	2,267.59	99.55	23.778	
15,800.00	12,534.89	15,288.05	12,048.18	48.59	56.26	-78.14	-3,149.63	3,293.66	2,367.23	2,265.17	102.05	23.196	
15,900.00	12,535.76	15,388.05	12,048.89	49.83	57.54	-78.13	-3,249.63	3,294.56	2,367.31	2,262.74	104.56	22.640	
16,000.00	12,536.64	15,488.05	12,049.60	51.07	58.82	-78.13	-3,349.62	3,295.47	2,367.39	2,260.30	107.08	22.108	
16,100.00	12,537.51	15,588.05	12,050.31	52.32	60.11	-78.12	-3,449.61	3,296.38	2,367.47	2,257.86	109.61	21.599	
16,200.00	12,538.39	15,688.05	12,051.02	53.57	61.40	-78.12	-3,549.61	3,297.29	2,367.55	2,255.40	112.14	21.112	
16,300.00	12,539.26	15,788.05	12,051.73	54.83	62.69	-78.12	-3,649.60	3,298.20	2,367.63	2,252.94	114.68	20.645	
16,400.00	12,540.13	15,888.05	12,052.44	56.09	63.99	-78.11	-3,749.59	3,299.11	2,367.71	2,250.48	117.23	20.197	
16,500.00	12,541.01	15,988.05	12,053.15	57.36	65.28	-78.11	-3,849.58	3,300.02	2,367.79	2,248.00	119.78	19.767	
16,600.00	12,541.88	16,088.05	12,053.86	58.64	66.58	-78.11	-3,949.58	3,300.92	2,367.87	2,245.53	122.34	19.354	
16,700.00	12,542.75	16,188.05	12,054.57	59.91	67.89	-78.10	-4,049.57	3,301.83	2,367.95	2,243.04	124.91	18.958	
16,800.00	12,543.63	16,288.05	12,055.28	61.20	69.19	-78.10	-4,149.56	3,302.74	2,368.03	2,240.55	127.48	18.576	
16,900.00	12,544.50	16,388.05	12,055.98	62.48	70.50	-78.09	-4,249.56	3,303.65	2,368.11	2,238.06	130.05	18.209	
17,000.00	12,545.37	16,488.04	12,056.69	63.77	71.81	-78.09	-4,349.55	3,304.56	2,368.19	2,235.56	132.63	17.856	
17,100.00	12,546.25	16,588.04	12,057.40	65.06	73.13	-78.09	-4,449.54	3,305.47	2,368.27	2,233.06	135.21	17.515	
17,200.00	12,547.12	16,688.04	12,058.11	66.36	74.44	-78.08	-4,549.54	3,306.38	2,368.35	2,230.55	137.80	17.187	
17,300.00	12,547.99	16,788.04	12,058.82	67.66	75.76	-78.08	-4,649.53	3,307.28	2,368.43	2,228.04	140.39	16.870	
17,400.00	12,548.87	16,888.04	12,059.53	68.96	77.07	-78.08	-4,749.52	3,308.19	2,368.51	2,225.53	142.98	16.565	
17,500.00	12,549.74	16,988.04	12,060.24	70.26	78.39	-78.07	-4,849.52	3,309.10	2,368.59	2,223.01	145.58	16.270	
17,600.00	12,550.62	17,088.04	12,060.95	71.57	79.72	-78.07	-4,949.51	3,310.01	2,368.67	2,220.49	148.18	15.985	
17,700.00	12,551.49	17,188.04	12,061.66	72.88	81.04	-78.07	-5,049.50	3,310.92	2,368.75	2,217.97	150.79	15.709	
17,800.00	12,552.36	17,288.04	12,062.37	74.19	82.36	-78.06	-5,149.50	3,311.83	2,368.83	2,215.44	153.39	15.443	
17,900.00	12,553.24	17,388.04	12,063.08	75.50	83.69	-78.06	-5,249.49	3,312.74	2,368.91	2,212.91	156.00	15.185	
18,000.00	12,554.11	17,488.04	12,063.78	76.81	85.02	-78.05	-5,349.48	3,313.64	2,368.99	2,210.38	158.61	14.936	
18,100.00	12,554.98	17,588.04	12,064.49	78.13	86.34	-78.05	-5,449.48	3,314.55	2,369.07	2,207.85	161.23	14.694	
18,200.00	12,555.86	17,688.04	12,065.20	79.45	87.67	-78.05	-5,549.47	3,315.46	2,369.15	2,205.31	163.84	14.460	
18,300.00	12,556.73	17,788.04	12,065.91	80.77	89.00	-78.04	-5,649.46	3,316.37	2,369.23	2,202.77	166.46	14.233	
18,400.00	12,557.60	17,888.04	12,066.62	82.09	90.34	-78.04	-5,749.46	3,317.28	2,369.32	2,200.23	169.08	14.013	
18,500.00	12,558.48	17,988.04	12,067.33	83.42	91.67	-78.04	-5,849.45	3,318.19	2,369.40	2,197.69	171.70	13.799	
18,600.00	12,559.35	18,088.04	12,068.04	84.74	93.00	-78.03	-5,949.44	3,319.10	2,369.48	2,195.15	174.33	13.592	
18,700.00	12,560.23	18,188.04	12,068.75	86.07	94.34	-78.03	-6,049.44	3,320.00	2,369.56	2,192.60	176.95	13.391	
18,800.00	12,561.10	18,288.04	12,069.46	87.40	95.67	-78.03	-6,149.43	3,320.91	2,369.64	2,190.06	179.58	13.195	
18,900.00	12,561.97	18,388.04	12,070.17	88.72	97.01	-78.02	-6,249.42	3,321.82	2,369.72	2,187.51	182.21	13.005	
19,000.00	12,562.85	18,488.04	12,070.88	90.05	98.35	-78.02	-6,349.42	3,322.73	2,369.80	2,184.96	184.84	12.821	
19,100.00	12,563.72	18,588.04	12,071.58	91.39	99.69	-78.01	-6,449.41	3,323.64	2,369.88	2,182.41	187.47	12.641	
19,200.00	12,564.59	18,688.04	12,072.29	92.72	101.03	-78.01	-6,549.40	3,324.55	2,369.96	2,179.85	190.11	12.466	
19,300.00	12,565.47	18,788.04	12,073.00	94.05	102.37	-78.01	-6,649.39	3,325.46	2,370.04	2,177.30	192.74	12.296	
19,400.00	12,566.34	18,888.04	12,073.71	95.39	103.71	-78.00	-6,749.39	3,326.36	2,370.12	2,174.74	195.38	12.131	
19,500.00	12,567.21	18,988.04	12,074.42	96.72	105.05	-78.00	-6,849.38	3,327.27	2,370.20	2,172.19	198.02	11.970	
19,600.00	12,568.09	19,088.04	12,075.13	98.06	106.39	-78.00	-6,949.37	3,328.18	2,370.28	2,169.63	200.65	11.813	
19,700.00	12,568.96	19,188.04	12,075.84	99.40	107.74	-77.99	-7,049.37	3,329.09	2,370.36	2,167.07	203.29	11.660	
19,800.00	12,569.83	19,288.04	12,076.55	100.73	109.08	-77.99	-7,149.36	3,330.00	2,370.44	2,164.51	205.94	11.511	
19,900.00	12,570.71	19,388.04	12,077.26	102.07	110.42	-77.99	-7,249.35	3,330.91	2,370.52	2,161.95	208.58	11.365	
20,000.00	12,571.58	19,488.04	12,077.97	103.41	111.77	-77.98	-7,349.35	3,331.82	2,370.60	2,159.38	211.22	11.223	
20,100.00	12,572.46	19,588.04	12,078.67	104.75	113.11	-77.98	-7,449.34	3,332.72	2,370.68	2,156.82	213.86	11.085	
20,200.00	12,573.33	19,688.04	12,079.38	106.10	114.46	-77.97	-7,549.33	3,333.63	2,370.77	2,154.26	216.51	10.950	
20,300.00	12,574.20	19,788.04	12,080.09	107.44	115.81	-77.97	-7,649.33	3,334.54	2,370.85	2,151.69	219.16	10.818	
20,400.00	12,575.08	19,888.04	12,080.80	108.78	117.15	-77.97	-7,749.32	3,335.45	2,370.93	2,149.12	221.80	10.689	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 40 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 138H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:					Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
20,500.00	12,575.95	19,988.04	12,081.51	110.12	118.50	-77.96	-7,849.31	3,336.36	2,371.01	2,146.56	224.45	10.564	
20,600.00	12,576.82	20,088.04	12,082.22	111.47	119.85	-77.96	-7,949.31	3,337.27	2,371.09	2,143.99	227.10	10.441	
20,700.00	12,577.70	20,188.04	12,082.93	112.81	121.20	-77.96	-8,049.30	3,338.18	2,371.17	2,141.42	229.75	10.321	
20,800.00	12,578.57	20,288.04	12,083.64	114.16	122.55	-77.95	-8,149.29	3,339.08	2,371.25	2,138.85	232.40	10.203	
20,900.00	12,579.44	20,388.04	12,084.35	115.51	123.90	-77.95	-8,249.29	3,339.99	2,371.33	2,136.28	235.05	10.089	
21,000.00	12,580.32	20,488.04	12,085.06	116.85	125.24	-77.95	-8,349.28	3,340.90	2,371.41	2,133.71	237.70	9.977	
21,100.00	12,581.19	20,588.04	12,085.77	118.20	126.60	-77.94	-8,449.27	3,341.81	2,371.49	2,131.14	240.35	9.867	
21,200.00	12,582.06	20,688.04	12,086.47	119.55	127.95	-77.94	-8,549.27	3,342.72	2,371.57	2,128.57	243.00	9.759	
21,300.00	12,582.94	20,788.04	12,087.18	120.89	129.30	-77.93	-8,649.26	3,343.63	2,371.65	2,126.00	245.66	9.654	
21,400.00	12,583.81	20,888.04	12,087.89	122.24	130.65	-77.93	-8,749.25	3,344.54	2,371.73	2,123.42	248.31	9.551	
21,500.00	12,584.69	20,988.04	12,088.60	123.59	132.00	-77.93	-8,849.25	3,345.44	2,371.81	2,120.85	250.97	9.451	
21,600.00	12,585.56	21,088.04	12,089.31	124.94	133.35	-77.92	-8,949.24	3,346.35	2,371.90	2,118.28	253.62	9.352	
21,700.00	12,586.43	21,188.04	12,090.02	126.29	134.70	-77.92	-9,049.23	3,347.26	2,371.98	2,115.70	256.28	9.256	
21,800.00	12,587.31	21,288.04	12,090.73	127.64	136.06	-77.92	-9,149.23	3,348.17	2,372.06	2,113.13	258.93	9.161	
21,900.00	12,588.18	21,388.04	12,091.44	128.99	137.41	-77.91	-9,249.22	3,349.08	2,372.14	2,110.55	261.59	9.068	
22,000.00	12,589.05	21,488.04	12,092.15	130.34	138.76	-77.91	-9,349.21	3,349.99	2,372.22	2,107.97	264.25	8.977	
22,100.00	12,589.93	21,588.04	12,092.86	131.70	140.12	-77.91	-9,449.20	3,350.90	2,372.30	2,105.40	266.90	8.888	
22,200.00	12,590.80	21,688.04	12,093.57	133.05	141.47	-77.90	-9,549.20	3,351.80	2,372.38	2,102.82	269.56	8.801	
22,300.00	12,591.67	21,788.04	12,094.27	134.40	142.83	-77.90	-9,649.19	3,352.71	2,372.46	2,100.24	272.22	8.715	
22,400.00	12,592.55	21,888.04	12,094.98	135.75	144.18	-77.89	-9,749.18	3,353.62	2,372.54	2,097.66	274.88	8.631	
22,500.00	12,593.42	21,988.04	12,095.69	137.11	145.54	-77.89	-9,849.18	3,354.53	2,372.62	2,095.09	277.54	8.549	
22,600.00	12,594.30	22,088.04	12,096.40	138.46	146.89	-77.89	-9,949.17	3,355.44	2,372.70	2,092.51	280.20	8.468	
22,700.00	12,595.17	22,188.04	12,097.11	139.81	148.25	-77.88	-10,049.16	3,356.35	2,372.78	2,089.93	282.86	8.389	
22,800.00	12,596.04	22,288.04	12,097.82	141.17	149.60	-77.88	-10,149.16	3,357.26	2,372.87	2,087.35	285.52	8.311	
22,875.30	12,596.70	22,363.34	12,098.35	142.19	150.62	-77.88	-10,224.45	3,357.94	2,372.93	2,085.41	287.52	8.253	ES, SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 41 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 151H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:
Reference										Offset Well Error:		0.00 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Minimum Separation (usft)	Separation Factor	Warning
5,100.00	5,009.89	4,826.50	4,755.95	13.78	13.33	-164.09	123.52	-652.89	1,429.04	1,405.05	23.99	59.561
5,200.00	5,106.49	4,917.33	4,844.95	14.10	13.57	-164.01	131.02	-669.36	1,470.85	1,446.44	24.41	60.257
5,300.00	5,203.08	5,008.15	4,933.95	14.43	13.82	-163.94	138.51	-685.84	1,512.66	1,487.84	24.83	60.928
5,400.00	5,299.67	5,098.98	5,022.96	14.75	14.06	-163.89	146.01	-702.31	1,554.47	1,529.23	25.24	61.596
5,500.00	5,396.65	5,190.40	5,112.54	15.07	14.31	-163.99	153.56	-718.90	1,594.93	1,569.27	25.67	62.142
5,600.00	5,494.23	5,282.79	5,203.08	15.36	14.56	-164.05	161.19	-735.65	1,633.09	1,607.00	26.09	62.588
5,700.00	5,592.35	5,376.08	5,294.51	15.62	14.81	-164.08	168.89	-752.58	1,668.92	1,642.40	26.52	62.937
5,800.00	5,690.94	5,470.22	5,386.76	15.86	15.07	-164.08	176.66	-769.65	1,702.39	1,675.45	26.94	63.196
5,900.00	5,789.93	5,565.14	5,479.77	16.07	15.33	-164.05	184.49	-786.87	1,733.49	1,706.14	27.36	63.370
6,000.00	5,889.26	5,660.77	5,573.48	16.25	15.59	-163.99	192.39	-804.22	1,762.21	1,734.44	27.77	63.466
6,100.00	5,988.86	5,757.05	5,667.83	16.41	15.85	-163.90	200.34	-821.68	1,788.52	1,760.35	28.17	63.490
6,200.00	6,088.66	5,853.91	5,762.75	16.53	16.11	-163.78	208.33	-839.25	1,812.43	1,783.86	28.57	63.446
6,300.00	6,188.59	5,956.02	5,862.37	16.64	16.46	-163.56	218.90	-862.46	1,833.48	1,804.40	29.09	63.038
6,400.00	6,288.58	6,160.96	6,065.14	16.71	16.85	-90.84	230.21	-887.32	1,848.65	1,818.99	29.66	62.334
6,500.00	6,388.58	6,338.35	6,241.44	16.76	17.17	-90.58	238.33	-905.15	1,858.66	1,828.51	30.14	61.663
6,600.00	6,488.58	6,517.20	6,419.90	16.82	17.41	-90.43	243.07	-915.56	1,864.46	1,833.91	30.55	61.022
6,700.00	6,588.58	6,685.92	6,588.58	16.88	17.53	-90.39	244.37	-918.43	1,866.05	1,835.24	30.81	60.568
6,800.00	6,688.58	6,785.92	6,688.58	16.94	17.59	-90.39	244.37	-918.43	1,866.05	1,835.13	30.92	60.349
6,900.00	6,788.58	6,885.92	6,788.58	17.00	17.65	-90.39	244.37	-918.43	1,866.05	1,835.02	31.04	60.121
7,000.00	6,888.58	6,985.92	6,888.58	17.05	17.71	-90.39	244.37	-918.43	1,866.05	1,834.90	31.16	59.894
7,100.00	6,988.58	7,085.92	6,988.58	17.11	17.76	-90.39	244.37	-918.43	1,866.05	1,834.78	31.27	59.668
7,200.00	7,088.58	7,185.92	7,088.58	17.17	17.82	-90.39	244.37	-918.43	1,866.05	1,834.66	31.39	59.443
7,300.00	7,188.58	7,285.92	7,188.58	17.23	17.88	-90.39	244.37	-918.43	1,866.05	1,834.54	31.51	59.219
7,400.00	7,288.58	7,385.92	7,288.58	17.29	17.94	-90.39	244.37	-918.43	1,866.05	1,834.42	31.63	58.995
7,500.00	7,388.58	7,485.92	7,388.58	17.35	18.00	-90.39	244.37	-918.43	1,866.05	1,834.30	31.75	58.773
7,600.00	7,488.58	7,585.92	7,488.58	17.41	18.06	-90.39	244.37	-918.43	1,866.05	1,834.18	31.87	58.552
7,700.00	7,588.58	7,685.92	7,588.58	17.47	18.12	-90.39	244.37	-918.43	1,866.05	1,834.06	31.99	58.331
7,800.00	7,688.58	7,785.92	7,688.58	17.53	18.18	-90.39	244.37	-918.43	1,866.05	1,833.94	32.11	58.112
7,900.00	7,788.58	7,885.92	7,788.58	17.59	18.24	-90.39	244.37	-918.43	1,866.05	1,833.82	32.23	57.893
8,000.00	7,888.58	7,985.92	7,888.58	17.65	18.30	-90.39	244.37	-918.43	1,866.05	1,833.70	32.35	57.676
8,100.00	7,988.58	8,085.92	7,988.58	17.71	18.37	-90.39	244.37	-918.43	1,866.05	1,833.58	32.48	57.459
8,200.00	8,088.58	8,185.92	8,088.58	17.77	18.43	-90.39	244.37	-918.43	1,866.05	1,833.45	32.60	57.244
8,300.00	8,188.58	8,285.92	8,188.58	17.83	18.49	-90.39	244.37	-918.43	1,866.05	1,833.33	32.72	57.029
8,400.00	8,288.58	8,385.92	8,288.58	17.89	18.55	-90.39	244.37	-918.43	1,866.05	1,833.21	32.84	56.816
8,500.00	8,388.58	8,485.92	8,388.58	17.95	18.61	-90.39	244.37	-918.43	1,866.05	1,833.09	32.97	56.603
8,600.00	8,488.58	8,585.92	8,488.58	18.02	18.67	-90.39	244.37	-918.43	1,866.05	1,832.96	33.09	56.392
8,700.00	8,588.58	8,685.92	8,588.58	18.08	18.73	-90.39	244.37	-918.43	1,866.05	1,832.84	33.21	56.181
8,800.00	8,688.58	8,785.92	8,688.58	18.14	18.80	-90.39	244.37	-918.43	1,866.05	1,832.71	33.34	55.972
8,900.00	8,788.58	8,885.92	8,788.58	18.20	18.86	-90.39	244.37	-918.43	1,866.05	1,832.59	33.46	55.763
9,000.00	8,888.58	8,985.92	8,888.58	18.26	18.92	-90.39	244.37	-918.43	1,866.05	1,832.46	33.59	55.555
9,100.00	8,988.58	9,085.92	8,988.58	18.32	18.98	-90.39	244.37	-918.43	1,866.05	1,832.34	33.71	55.349
9,200.00	9,088.58	9,185.92	9,088.58	18.39	19.04	-90.39	244.37	-918.43	1,866.05	1,832.21	33.84	55.143
9,300.00	9,188.58	9,285.92	9,188.58	18.45	19.11	-90.39	244.37	-918.43	1,866.05	1,832.09	33.97	54.939
9,400.00	9,288.58	9,385.92	9,288.58	18.51	19.17	-90.39	244.37	-918.43	1,866.05	1,831.96	34.09	54.735
9,500.00	9,388.58	9,485.92	9,388.58	18.57	19.23	-90.39	244.37	-918.43	1,866.05	1,831.83	34.22	54.533
9,600.00	9,488.58	9,585.92	9,488.58	18.64	19.30	-90.39	244.37	-918.43	1,866.05	1,831.71	34.35	54.331
9,700.00	9,588.58	9,685.92	9,588.58	18.70	19.36	-90.39	244.37	-918.43	1,866.05	1,831.58	34.47	54.131
9,800.00	9,688.58	9,785.92	9,688.58	18.76	19.42	-90.39	244.37	-918.43	1,866.05	1,831.45	34.60	53.931
9,900.00	9,788.58	9,885.92	9,788.58	18.83	19.49	-90.39	244.37	-918.43	1,866.05	1,831.32	34.73	53.733
10,000.00	9,888.58	9,985.92	9,888.58	18.89	19.55	-90.39	244.37	-918.43	1,866.05	1,831.20	34.86	53.535
10,100.00	9,988.58	10,085.92	9,988.58	18.95	19.61	-90.39	244.37	-918.43	1,866.05	1,831.07	34.98	53.339
10,200.00	10,088.58	10,185.92	10,088.58	19.02	19.68	-90.39	244.37	-918.43	1,866.05	1,830.94	35.11	53.143

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 43 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 151H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
10,300.00	10,188.58	10,285.92	10,188.58	19.08	19.74	-90.39	244.37	-918.43	1,866.05	1,830.81	35.24	52.949			
10,400.00	10,288.58	10,385.92	10,288.58	19.15	19.80	-90.39	244.37	-918.43	1,866.05	1,830.68	35.37	52.755			
10,500.00	10,388.58	10,485.92	10,388.58	19.21	19.87	-90.39	244.37	-918.43	1,866.05	1,830.55	35.50	52.563			
10,600.00	10,488.58	10,585.92	10,488.58	19.27	19.93	-90.39	244.37	-918.43	1,866.05	1,830.42	35.63	52.371			
10,700.00	10,588.58	10,685.92	10,588.58	19.34	20.00	-90.39	244.37	-918.43	1,866.05	1,830.29	35.76	52.181			
10,800.00	10,688.58	10,785.92	10,688.58	19.40	20.06	-90.39	244.37	-918.43	1,866.05	1,830.16	35.89	51.991			
10,900.00	10,788.58	10,885.92	10,788.58	19.47	20.13	-90.39	244.37	-918.43	1,866.05	1,830.03	36.02	51.803			
11,000.00	10,888.58	10,985.92	10,888.58	19.53	20.19	-90.39	244.37	-918.43	1,866.05	1,829.90	36.15	51.615			
11,100.00	10,988.58	11,085.92	10,988.58	19.60	20.26	-90.39	244.37	-918.43	1,866.05	1,829.77	36.28	51.429			
11,200.00	11,088.58	11,185.98	11,088.64	19.66	20.31	-90.39	244.27	-918.43	1,866.05	1,829.65	36.40	51.267			
11,251.40	11,139.98	11,237.44	11,139.98	19.70	20.33	-90.49	241.01	-918.40	1,866.05	1,829.63	36.42	51.243			
11,300.00	11,188.58	11,285.20	11,187.19	19.73	20.34	-90.71	233.87	-918.34	1,866.06	1,829.65	36.41	51.245			
11,400.00	11,288.58	11,378.23	11,276.68	19.79	20.35	-91.48	208.82	-918.12	1,866.37	1,829.99	36.38	51.308			
11,500.00	11,388.58	11,461.36	11,352.29	19.86	20.35	-92.54	174.45	-917.83	1,867.59	1,831.28	36.31	51.429			
11,600.00	11,488.58	11,533.19	11,413.03	19.92	20.33	-93.71	136.21	-917.50	1,870.52	1,834.25	36.26	51.580			
11,700.00	11,588.58	11,600.00	11,464.83	19.99	20.33	-95.00	94.08	-917.14	1,875.91	1,839.67	36.24	51.764			
11,800.00	11,688.58	11,650.00	11,500.20	20.05	20.34	-96.07	58.75	-916.83	1,884.37	1,848.07	36.30	51.908			
11,900.00	11,788.58	11,688.18	11,525.06	20.12	20.34	-96.95	29.78	-916.58	1,896.37	1,859.90	36.46	52.008			
12,000.00	11,888.58	11,724.38	11,546.79	20.19	20.36	-97.83	0.84	-916.33	1,912.24	1,875.54	36.70	52.108			
12,100.00	11,988.51	11,750.00	11,561.05	20.25	20.38	80.97	-20.44	-916.15	1,931.84	1,894.86	36.99	52.228			
12,200.00	12,086.82	11,800.00	11,586.06	20.31	20.42	77.73	-63.71	-915.78	1,952.95	1,915.74	37.21	52.488			
12,300.00	12,180.57	11,824.87	11,597.08	20.35	20.45	75.15	-86.01	-915.59	1,974.07	1,936.50	37.57	52.546			
12,400.00	12,266.93	11,850.00	11,607.21	20.39	20.48	72.72	-109.00	-915.39	1,994.40	1,956.45	37.95	52.549			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 151H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:			Offset Well Error:	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
15,400.00	12,531.40	14,537.72	11,672.30	43.74	41.99	65.28	-2,790.76	-892.30	2,054.33	1,975.14	79.20	25.940		
15,500.00	12,532.27	14,637.72	11,673.17	44.94	43.17	65.28	-2,890.76	-891.44	2,054.34	1,972.95	81.39	25.241		
15,600.00	12,533.14	14,737.72	11,674.04	46.15	44.36	65.28	-2,990.75	-890.58	2,054.34	1,970.74	83.60	24.573		
15,700.00	12,534.02	14,837.72	11,674.90	47.37	45.56	65.28	-3,090.74	-889.72	2,054.34	1,968.52	85.83	23.936		
15,800.00	12,534.89	14,937.72	11,675.77	48.59	46.78	65.28	-3,190.73	-888.86	2,054.35	1,966.28	88.07	23.326		
15,900.00	12,535.76	15,037.72	11,676.63	49.83	47.99	65.28	-3,290.73	-888.00	2,054.35	1,964.02	90.33	22.743		
16,000.00	12,536.64	15,137.72	11,677.50	51.07	49.22	65.28	-3,390.72	-887.14	2,054.36	1,961.75	92.60	22.185		
16,100.00	12,537.51	15,237.72	11,678.37	52.32	50.46	65.28	-3,490.71	-886.28	2,054.36	1,959.47	94.88	21.651		
16,200.00	12,538.39	15,337.72	11,679.23	53.57	51.70	65.28	-3,590.70	-885.42	2,054.36	1,957.18	97.18	21.140		
16,300.00	12,539.26	15,437.72	11,680.10	54.83	52.95	65.28	-3,690.70	-884.56	2,054.37	1,954.88	99.49	20.650		
16,400.00	12,540.13	15,537.72	11,680.96	56.09	54.20	65.28	-3,790.69	-883.70	2,054.37	1,952.57	101.80	20.180		
16,500.00	12,541.01	15,637.72	11,681.83	57.36	55.46	65.28	-3,890.68	-882.84	2,054.37	1,950.25	104.13	19.730		
16,600.00	12,541.88	15,737.72	11,682.70	58.64	56.73	65.28	-3,990.67	-881.97	2,054.38	1,947.92	106.46	19.297		
16,700.00	12,542.75	15,837.72	11,683.56	59.91	58.00	65.28	-4,090.67	-881.11	2,054.38	1,945.58	108.80	18.882		
16,800.00	12,543.63	15,937.72	11,684.43	61.20	59.27	65.28	-4,190.66	-880.25	2,054.38	1,943.23	111.15	18.483		
16,900.00	12,544.50	16,037.72	11,685.29	62.48	60.55	65.28	-4,290.65	-879.39	2,054.39	1,940.88	113.51	18.099		
17,000.00	12,545.37	16,137.72	11,686.16	63.77	61.83	65.28	-4,390.64	-878.53	2,054.39	1,938.52	115.87	17.730		
17,100.00	12,546.25	16,237.72	11,687.03	65.06	63.12	65.28	-4,490.64	-877.67	2,054.39	1,936.15	118.24	17.374		
17,200.00	12,547.12	16,337.72	11,687.89	66.36	64.41	65.28	-4,590.63	-876.81	2,054.40	1,933.78	120.62	17.032		
17,300.00	12,547.99	16,437.72	11,688.76	67.66	65.70	65.28	-4,690.62	-875.95	2,054.40	1,931.40	123.00	16.703		
17,400.00	12,548.87	16,537.72	11,689.62	68.96	66.99	65.28	-4,790.61	-875.09	2,054.40	1,929.02	125.39	16.385		
17,500.00	12,549.74	16,637.72	11,690.49	70.26	68.29	65.27	-4,890.61	-874.23	2,054.41	1,926.63	127.78	16.078		
17,600.00	12,550.62	16,737.72	11,691.36	71.57	69.60	65.27	-4,990.60	-873.37	2,054.41	1,924.24	130.17	15.782		
17,700.00	12,551.49	16,837.72	11,692.22	72.88	70.90	65.27	-5,090.59	-872.51	2,054.42	1,921.84	132.57	15.496		
17,800.00	12,552.36	16,937.72	11,693.09	74.19	72.21	65.27	-5,190.58	-871.65	2,054.42	1,919.44	134.98	15.220		
17,900.00	12,553.24	17,037.72	11,693.95	75.50	73.52	65.27	-5,290.58	-870.79	2,054.42	1,917.03	137.39	14.953		
18,000.00	12,554.11	17,137.72	11,694.82	76.81	74.83	65.27	-5,390.57	-869.92	2,054.43	1,914.63	139.80	14.695		
18,100.00	12,554.98	17,237.72	11,695.69	78.13	76.14	65.27	-5,490.56	-869.06	2,054.43	1,912.21	142.22	14.446		
18,200.00	12,555.86	17,337.72	11,696.55	79.45	77.46	65.27	-5,590.55	-868.20	2,054.43	1,909.80	144.64	14.204		
18,300.00	12,556.73	17,437.72	11,697.42	80.77	78.77	65.27	-5,690.55	-867.34	2,054.44	1,907.38	147.06	13.970		
18,400.00	12,557.60	17,537.72	11,698.28	82.09	80.09	65.27	-5,790.54	-866.48	2,054.44	1,904.95	149.49	13.743		
18,500.00	12,558.48	17,637.72	11,699.15	83.42	81.41	65.27	-5,890.53	-865.62	2,054.44	1,902.53	151.92	13.524		
18,600.00	12,559.35	17,737.72	11,700.02	84.74	82.74	65.27	-5,990.52	-864.76	2,054.45	1,900.10	154.35	13.311		
18,700.00	12,560.23	17,837.72	11,700.88	86.07	84.06	65.27	-6,090.52	-863.90	2,054.45	1,897.67	156.78	13.104		
18,800.00	12,561.10	17,937.72	11,701.75	87.40	85.38	65.27	-6,190.51	-863.04	2,054.45	1,895.24	159.22	12.903		
18,900.00	12,561.97	18,037.72	11,702.61	88.72	86.71	65.27	-6,290.50	-862.18	2,054.46	1,892.80	161.66	12.709		
19,000.00	12,562.85	18,137.72	11,703.48	90.05	88.04	65.27	-6,390.49	-861.32	2,054.46	1,890.36	164.10	12.520		
19,100.00	12,563.72	18,237.72	11,704.35	91.39	89.37	65.27	-6,490.49	-860.46	2,054.47	1,887.92	166.54	12.336		
19,200.00	12,564.59	18,337.72	11,705.21	92.72	90.70	65.27	-6,590.48	-859.60	2,054.47	1,885.48	168.99	12.157		
19,300.00	12,565.47	18,437.72	11,706.08	94.05	92.03	65.27	-6,690.47	-858.74	2,054.47	1,883.04	171.44	11.984		
19,400.00	12,566.34	18,537.72	11,706.94	95.39	93.36	65.27	-6,790.46	-857.87	2,054.48	1,880.59	173.89	11.815		
19,500.00	12,567.21	18,637.72	11,707.81	96.72	94.70	65.27	-6,890.46	-857.01	2,054.48	1,878.14	176.34	11.651		
19,600.00	12,568.09	18,737.72	11,708.68	98.06	96.03	65.27	-6,990.45	-856.15	2,054.48	1,875.69	178.79	11.491		
19,700.00	12,568.96	18,837.72	11,709.54	99.40	97.37	65.27	-7,090.44	-855.29	2,054.49	1,873.24	181.25	11.335		
19,800.00	12,569.83	18,937.72	11,710.41	100.73	98.71	65.27	-7,190.44	-854.43	2,054.49	1,870.79	183.71	11.184		
19,900.00	12,570.71	19,037.72	11,711.27	102.07	100.04	65.27	-7,290.43	-853.57	2,054.49	1,868.33	186.16	11.036		
20,000.00	12,571.58	19,137.72	11,712.14	103.41	101.38	65.27	-7,390.42	-852.71	2,054.50	1,865.87	188.62	10.892		
20,100.00	12,572.46	19,237.72	11,713.01	104.75	102.72	65.27	-7,490.41	-851.85	2,054.50	1,863.42	191.09	10.752		
20,200.00	12,573.33	19,337.72	11,713.87	106.10	104.06	65.27	-7,590.41	-850.99	2,054.50	1,860.96	193.55	10.615		
20,300.00	12,574.20	19,437.72	11,714.74	107.44	105.40	65.27	-7,690.40	-850.13	2,054.51	1,858.50	196.01	10.481		
20,400.00	12,575.08	19,537.72	11,715.60	108.78	106.75	65.27	-7,790.39	-849.27	2,054.51	1,856.03	198.48	10.351		
20,500.00	12,575.95	19,637.72	11,716.47	110.12	108.09	65.27	-7,890.38	-848.41	2,054.52	1,853.57	200.95	10.224		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 151H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:			
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,600.00	12,576.82	19,737.72	11,717.34	111.47	109.43	65.27	-7,990.38	-847.55	2,054.52	1,851.11	203.41	10.100			
20,700.00	12,577.70	19,837.72	11,718.20	112.81	110.77	65.27	-8,090.37	-846.68	2,054.52	1,848.64	205.88	9.979			
20,800.00	12,578.57	19,937.72	11,719.07	114.16	112.12	65.27	-8,190.36	-845.82	2,054.53	1,846.17	208.35	9.861			
20,900.00	12,579.44	20,037.72	11,719.93	115.51	113.46	65.27	-8,290.35	-844.96	2,054.53	1,843.70	210.82	9.745			
21,000.00	12,580.32	20,137.72	11,720.80	116.85	114.81	65.27	-8,390.35	-844.10	2,054.53	1,841.24	213.30	9.632			
21,100.00	12,581.19	20,237.72	11,721.67	118.20	116.16	65.27	-8,490.34	-843.24	2,054.54	1,838.77	215.77	9.522			
21,200.00	12,582.06	20,337.72	11,722.53	119.55	117.50	65.27	-8,590.33	-842.38	2,054.54	1,836.30	218.25	9.414			
21,300.00	12,582.94	20,437.72	11,723.40	120.89	118.85	65.27	-8,690.32	-841.52	2,054.54	1,833.82	220.72	9.308			
21,400.00	12,583.81	20,537.72	11,724.26	122.24	120.20	65.27	-8,790.32	-840.66	2,054.55	1,831.35	223.20	9.205			
21,500.00	12,584.69	20,637.72	11,725.13	123.59	121.55	65.27	-8,890.31	-839.80	2,054.55	1,828.88	225.67	9.104			
21,600.00	12,585.56	20,737.72	11,726.00	124.94	122.90	65.27	-8,990.30	-838.94	2,054.55	1,826.40	228.15	9.005			
21,700.00	12,586.43	20,837.72	11,726.86	126.29	124.24	65.27	-9,090.29	-838.08	2,054.56	1,823.93	230.63	8.908			
21,800.00	12,587.31	20,937.72	11,727.73	127.64	125.59	65.27	-9,190.29	-837.22	2,054.56	1,821.45	233.11	8.814			
21,900.00	12,588.18	21,037.72	11,728.59	128.99	126.94	65.27	-9,290.28	-836.36	2,054.57	1,818.97	235.59	8.721			
22,000.00	12,589.05	21,137.72	11,729.46	130.34	128.30	65.27	-9,390.27	-835.50	2,054.57	1,816.50	238.07	8.630			
22,100.00	12,589.93	21,237.72	11,730.33	131.70	129.65	65.27	-9,490.26	-834.63	2,054.57	1,814.02	240.55	8.541			
22,200.00	12,590.80	21,337.72	11,731.19	133.05	131.00	65.27	-9,590.26	-833.77	2,054.58	1,811.54	243.04	8.454			
22,300.00	12,591.67	21,437.72	11,732.06	134.40	132.35	65.27	-9,690.25	-832.91	2,054.58	1,809.06	245.52	8.368			
22,400.00	12,592.55	21,537.72	11,732.92	135.75	133.70	65.27	-9,790.24	-832.05	2,054.58	1,806.58	248.00	8.284			
22,500.00	12,593.42	21,637.72	11,733.79	137.11	135.05	65.27	-9,890.23	-831.19	2,054.59	1,804.10	250.49	8.202			
22,600.00	12,594.30	21,737.72	11,734.66	138.46	136.41	65.27	-9,990.23	-830.33	2,054.59	1,801.62	252.97	8.122			
22,700.00	12,595.17	21,837.72	11,735.52	139.81	137.76	65.27	-10,090.22	-829.47	2,054.59	1,799.13	255.46	8.043			
22,800.00	12,596.04	21,937.72	11,736.39	141.17	139.11	65.27	-10,190.21	-828.61	2,054.60	1,796.65	257.95	7.965			
22,806.13	12,596.10	21,943.85	11,736.44	141.25	139.20	65.27	-10,196.34	-828.56	2,054.60	1,796.50	258.10	7.961			
22,875.30	12,596.70	22,008.51	11,737.00	142.19	140.07	65.26	-10,261.00	-828.00	2,054.60	1,794.83	259.77	7.909	SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 46 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 152H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Offset Site Error: 0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned:			Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,300.00	10,188.58	10,217.88	10,188.58	19.08	15.74	-90.39	253.35	401.58	546.01	513.47	32.55	16.777		
10,400.00	10,288.58	10,317.88	10,288.58	19.15	15.82	-90.39	253.35	401.58	546.01	513.32	32.69	16.701		
10,500.00	10,388.58	10,417.88	10,388.58	19.21	15.91	-90.39	253.35	401.58	546.01	513.17	32.84	16.626		
10,600.00	10,488.58	10,517.88	10,488.58	19.27	15.99	-90.39	253.35	401.58	546.01	513.02	32.99	16.551		
10,700.00	10,588.58	10,617.88	10,588.58	19.34	16.07	-90.39	253.35	401.58	546.01	512.87	33.14	16.477		
10,800.00	10,688.58	10,717.88	10,688.58	19.40	16.15	-90.39	253.35	401.58	546.01	512.73	33.29	16.404		
10,900.00	10,788.58	10,817.88	10,788.58	19.47	16.24	-90.39	253.35	401.58	546.01	512.58	33.43	16.331		
11,000.00	10,888.58	10,917.88	10,888.58	19.53	16.32	-90.39	253.35	401.58	546.01	512.43	33.58	16.259		
11,100.00	10,988.58	11,017.88	10,988.58	19.60	16.40	-90.39	253.35	401.58	546.01	512.28	33.73	16.187		
11,200.00	11,088.58	11,117.90	11,088.60	19.66	16.49	-90.40	253.23	401.58	546.01	512.14	33.88	16.118		
11,221.94	11,110.52	11,139.84	11,110.52	19.68	16.50	-90.49	252.37	401.59	546.01	512.12	33.89	16.111		
11,300.00	11,188.58	11,216.69	11,186.70	19.73	16.53	-91.50	242.75	401.67	546.10	512.20	33.90	16.110		
11,400.00	11,288.58	11,309.30	11,275.78	19.79	16.57	-94.12	217.76	401.89	547.26	513.38	33.88	16.152		
11,500.00	11,388.58	11,392.09	11,351.09	19.86	16.62	-97.68	183.54	402.18	551.61	517.68	33.93	16.257		
11,600.00	11,488.58	11,463.68	11,411.65	19.92	16.68	-101.57	145.47	402.51	561.67	527.48	34.19	16.426		
11,700.00	11,588.58	11,524.40	11,458.97	19.99	16.73	-105.36	107.46	402.84	579.59	544.78	34.81	16.649		
11,800.00	11,688.58	11,575.47	11,495.46	20.05	16.77	-108.80	71.77	403.14	606.66	570.84	35.83	16.932		
11,900.00	11,788.58	11,618.38	11,523.57	20.12	16.82	-111.81	39.36	403.42	643.22	606.05	37.17	17.303		
12,000.00	11,888.58	11,650.00	11,542.70	20.19	16.85	-114.06	14.18	403.64	688.84	650.08	38.76	17.773		
12,100.00	11,988.51	11,686.27	11,562.88	20.25	16.90	60.96	-15.94	403.90	741.65	701.40	40.25	18.425		
12,200.00	12,086.82	11,719.66	11,579.74	20.31	16.94	53.76	-44.76	404.15	795.05	753.33	41.71	19.060		
12,300.00	12,180.57	11,750.00	11,593.58	20.35	16.99	47.88	-71.75	404.38	845.86	802.74	43.12	19.617		
12,400.00	12,266.93	11,800.00	11,613.22	20.39	17.07	42.61	-117.72	404.78	892.19	847.95	44.24	20.166		
12,500.00	12,343.26	11,829.74	11,622.97	20.44	17.13	39.08	-145.81	405.02	932.47	887.08	45.40	20.541		
12,60														

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 49 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 152H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
15,400.00	12,531.40	14,466.40	11,671.54	43.74	41.58	32.41	-2,779.50	427.69	1,018.60	952.84	65.76	15.490			
15,500.00	12,532.27	14,566.40	11,672.42	44.94	42.84	32.42	-2,879.49	428.55	1,018.60	951.69	66.90	15.225			
15,600.00	12,533.14	14,666.40	11,673.29	46.15	44.11	32.42	-2,979.48	429.42	1,018.59	950.53	68.07	14.964			
15,700.00	12,534.02	14,766.40	11,674.17	47.37	45.38	32.42	-3,079.48	430.28	1,018.59	949.34	69.25	14.708			
15,800.00	12,534.89	14,866.40	11,675.05	48.59	46.66	32.42	-3,179.47	431.14	1,018.59	948.13	70.46	14.457			
15,900.00	12,535.76	14,966.40	11,675.92	49.83	47.94	32.42	-3,279.46	432.00	1,018.59	946.91	71.68	14.210			
16,000.00	12,536.64	15,066.40	11,676.80	51.07	49.23	32.42	-3,379.45	432.86	1,018.59	945.67	72.92	13.969			
16,100.00	12,537.51	15,166.40	11,677.68	52.32	50.52	32.42	-3,479.45	433.72	1,018.58	944.41	74.17	13.732			
16,200.00	12,538.39	15,266.40	11,678.55	53.57	51.82	32.42	-3,579.44	434.58	1,018.58	943.14	75.44	13.501			
16,300.00	12,539.26	15,366.40	11,679.43	54.83	53.12	32.42	-3,679.43	435.44	1,018.58	941.85	76.73	13.275			
16,400.00	12,540.13	15,466.40	11,680.30	56.09	54.42	32.42	-3,779.42	436.30	1,018.58	940.55	78.03	13.054			
16,500.00	12,541.01	15,566.40	11,681.18	57.36	55.73	32.42	-3,879.41	437.16	1,018.57	939.23	79.34	12.838			
16,600.00	12,541.88	15,666.40	11,682.06	58.64	57.04	32.42	-3,979.41	438.03	1,018.57	937.91	80.67	12.627			
16,700.00	12,542.75	15,766.40	11,682.93	59.91	58.35	32.42	-4,079.40	438.89	1,018.57	936.57	82.00	12.421			
16,800.00	12,543.63	15,866.40	11,683.81	61.20	59.67	32.42	-4,179.39	439.75	1,018.57	935.22	83.35	12.220			
16,900.00	12,544.50	15,966.40	11,684.69	62.48	60.99	32.42	-4,279.38	440.61	1,018.57	933.85	84.71	12.024			
17,000.00	12,545.37	16,066.40	11,685.56	63.77	62.31	32.42	-4,379.38	441.47	1,018.56	932.48	86.08	11.833			
17,100.00	12,546.25	16,166.40	11,686.44	65.06	63.63	32.42	-4,479.37	442.33	1,018.56	931.10	87.46	11.646			
17,200.00	12,547.12	16,266.40	11,687.32	66.36	64.95	32.42	-4,579.36	443.19	1,018.56	929.71	88.85	11.464			
17,300.00	12,547.99	16,366.40	11,688.19	67.66	66.28	32.42	-4,679.35	444.05	1,018.56	928.31	90.25	11.286			
17,400.00	12,548.87	16,466.40	11,689.07	68.96	67.61	32.42	-4,779.35	444.91	1,018.55	926.90	91.65	11.113			
17,500.00	12,549.74	16,566.40	11,689.95	70.26	68.94	32.42	-4,879.34	445.77	1,018.55	925.48	93.07	10.944			
17,600.00	12,550.62	16,666.40	11,690.82	71.57	70.27	32.42	-4,979.33	446.64	1,018.55	924.06	94.49				

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 152H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)		
20,600.00	12,576.82	19,666.40	11,717.11	111.47	110.64	32.42	-7,979.11	472.46	1,018.48	878.90	139.58	7.297
20,700.00	12,577.70	19,766.40	11,717.99	112.81	112.00	32.42	-8,079.10	473.33	1,018.48	877.34	141.14	7.216
20,800.00	12,578.57	19,866.40	11,718.87	114.16	113.35	32.42	-8,179.09	474.19	1,018.48	875.78	142.70	7.137
20,900.00	12,579.44	19,966.40	11,719.74	115.51	114.71	32.42	-8,279.08	475.05	1,018.47	874.22	144.26	7.060
21,000.00	12,580.32	20,066.40	11,720.62	116.85	116.06	32.42	-8,379.08	475.91	1,018.47	872.65	145.82	6.985
21,100.00	12,581.19	20,166.40	11,721.50	118.20	117.42	32.42	-8,479.07	476.77	1,018.47	871.09	147.38	6.910
21,200.00	12,582.06	20,266.40	11,722.37	119.55	118.78	32.42	-8,579.06	477.63	1,018.47	869.52	148.95	6.838
21,300.00	12,582.94	20,366.40	11,723.25	120.89	120.13	32.42	-8,679.05	478.49	1,018.46	867.95	150.52	6.766
21,400.00	12,583.81	20,466.40	11,724.13	122.24	121.49	32.42	-8,779.05	479.35	1,018.46	866.37	152.09	6.696
21,500.00	12,584.69	20,566.40	11,725.00	123.59	122.85	32.42	-8,879.04	480.21	1,018.46	864.80	153.66	6.628
21,600.00	12,585.56	20,666.40	11,725.88	124.94	124.20	32.42	-8,979.03	481.07	1,018.46	863.22	155.24	6.561
21,700.00	12,586.43	20,766.40	11,726.75	126.29	125.56	32.42	-9,079.02	481.93	1,018.46	861.64	156.81	6.495
21,800.00	12,587.31	20,866.40	11,727.63	127.64	126.92	32.42	-9,179.02	482.80	1,018.45	860.07	158.39	6.430
21,900.00	12,588.18	20,966.40	11,728.51	128.99	128.28	32.42	-9,279.01	483.66	1,018.45	858.48	159.97	6.367
22,000.00	12,589.05	21,066.40	11,729.38	130.34	129.64	32.42	-9,379.00	484.52	1,018.45	856.90	161.55	6.304
22,100.00	12,589.93	21,166.40	11,730.26	131.70	131.00	32.42	-9,478.99	485.38	1,018.45	855.32	163.13	6.243
22,200.00	12,590.80	21,266.40	11,731.14	133.05	132.36	32.42	-9,578.98	486.24	1,018.44	853.73	164.71	6.183
22,300.00	12,591.67	21,366.40	11,732.01	134.40	133.72	32.42	-9,678.98	487.10	1,018.44	852.14	166.30	6.124
22,400.00	12,592.55	21,466.40	11,732.89	135.75	135.08	32.42	-9,778.97	487.96	1,018.44	850.56	167.88	6.066
22,500.00	12,593.42	21,566.40	11,733.77	137.11	136.44	32.42	-9,878.96	488.82	1,018.44	848.97	169.47	6.009
22,600.00	12,594.30	21,666.40	11,734.64	138.46	137.80	32.42	-9,978.95	489.68	1,018.44	847.37	171.06	5.954
22,700.00	12,595.17	21,766.40	11,735.52	139.81	139.16	32.42	-10,078.95	490.54	1,018.43	845.78	172.65	5.899
22,800.00	12,596.04	21,866.40	11,736.39	141.17	140.52	32.42	-10,178.94	491.41	1,018.43	844.19	174.24	5.845
22,866.92	12,596.63	21,933.32	11,736.98	142.07	141.43	32.42	-10,245.85	491.98	1,018.43	843.12	175.31	5.809
22,875.30	12,596.70	21,935.47	11,737.00	142.19	141.45	32.42	-10,248.00	492.00	1,018.45	843.07	175.38	5.807

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 51 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 156H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
0.00	0.00	2.00	0.00	0.50	0.50	70.29	831.00	2,319.00	2,463.40				
100.00	100.00	102.00	100.00	0.98	0.99	70.29	831.00	2,319.00	2,463.40	2,461.42	1.97	1,248.473	
200.00	200.00	202.00	200.00	1.56	1.57	70.29	831.00	2,319.00	2,463.40	2,460.27	3.13	786.888	
300.00	300.00	303.65	301.65	1.98	2.00	70.29	831.00	2,319.00	2,463.40	2,459.42	3.98	619.647	
400.00	400.00	486.22	484.15	2.33	2.72	70.36	826.88	2,317.09	2,461.65	2,456.68	4.97	495.058	
500.00	500.00	652.37	649.87	2.63	3.15	70.55	816.31	2,312.19	2,456.63	2,450.96	5.67	433.247	
600.00	600.00	751.98	749.11	2.91	3.35	70.70	808.43	2,308.54	2,450.54	2,444.39	6.15	398.776	
700.00	700.00	851.60	848.35	3.16	3.59	70.85	800.55	2,304.89	2,444.46	2,437.82	6.64	368.278	
800.00	800.00	951.22	947.59	3.40	3.82	70.99	792.68	2,301.24	2,438.40	2,431.30	7.11	343.167	
900.00	900.00	1,050.84	1,046.83	3.62	4.05	71.14	784.80	2,297.58	2,432.36	2,424.80	7.55	322.051	
1,000.00	1,000.00	1,150.46	1,146.07	3.76	4.27	-20.72	776.92	2,293.93	2,426.28	2,418.37	7.91	306.842	
1,100.00	1,099.98	1,250.00	1,245.23	4.00	4.44	-20.62	769.05	2,290.28	2,418.56	2,410.25	8.31	291.063	
1,200.00	1,199.88	1,423.21	1,417.39	4.24	4.82	-20.42	751.92	2,282.34	2,406.92	2,398.04	8.88	271.012	
1,300.00	1,299.63	1,595.61	1,587.72	4.46	5.26	-20.14	727.86	2,271.19	2,389.80	2,380.29	9.51	251.410	
1,400.00	1,399.25	1,745.31	1,734.55	4.60	5.60	-19.74	701.41	2,258.92	2,368.33	2,358.37	9.96	237.701	
1,500.00	1,498.87	1,842.05	1,829.18	4.78	5.79	-19.44	683.17	2,250.47	2,346.12	2,335.77	10.35	226.620	
1,600.00	1,598.49	1,938.79	1,923.81	4.96	5.99	-19.13	664.93	2,242.01	2,323.98	2,313.21	10.76	215.918	
1,700.00	1,698.11	2,035.53	2,018.44	5.14	6.20	-18.82	646.69	2,233.55	2,301.90	2,290.72	11.18	205.972	
1,800.00	1,797.73	2,132.27	2,113.06	5.32	6.41	-18.50	628.44	2,225.09	2,279.88	2,268.29	11.59	196.706	
1,900.00	1,897.34	2,229.01	2,207.69	5.49	6.61	-18.18	610.20	2,216.63	2,257.94	2,245.93	12.01	188.059	
2,000.00	1,996.96	2,325.75	2,302.32	5.67	6.82	-17.84	591.96	2,208.18	2,236.07	2,223.65	12.42	180.000	
2,100.00	2,096.58	2,422.49	2,396.94	5.85	7.06	-17.51	573.72	2,199.72	2,214.27	2,201.42	12.85	172.359	
2,200.00	2,196.20	2,519.23	2,491.57	6.04	7.33	-17.16	555.48	2,191.26	2,192.55	2,179.28	13.27	165.178	
2,300.00	2,295.72	2,615.67	2,585.91	6.23	7.60	-10.46	537.29	2,182.83	2,169.75	2,156.04	13.71	158.253	
2,400.00	2,394.97	2,711.43	2,679.57	6.43	7.86	-5.77	519.23	2,174.45	2,144.55	2,130.39	14.16	151.410	
2,500.00	2,493.89	2,806.44	2,772.50	6.64	8.13	-2.37	501.32	2,166.15	2,116.98	2,102.36	14.62	144.807	
2,600.00	2,592.40	2,900.63	2,864.64	6.85	8.40	0.28	483.55	2,157.91	2,087.08	2,072.00	15.07	138.446	
2,700.00	2,690.45	2,993.94	2,955.91	7.07	8.66	2.46	465.96	2,149.75	2,054.86	2,039.33	15.53	132.314	
2,800.00	2,787.96	3,086.31	3,046.27	7.28	8.93	4.33	448.54	2,141.68	2,020.39	2,004.40	15.98	126.398	
2,900.00	2,884.87	3,177.67	3,135.63	7.49	9.19	6.00	431.31	2,133.69	1,983.69	1,967.25	16.44	120.690	
3,000.00	2,981.46	3,268.52	3,224.50	7.68	9.45	6.56	414.18	2,125.75	1,946.01	1,929.14	16.86	115.402	
3,100.00	3,078.05	3,359.38	3,313.37	7.87	9.71	7.14	397.05	2,117.80	1,908.49	1,891.20	17.29	110.359	
3,200.00	3,174.64	3,450.23	3,402.23	8.06	9.97	7.74	379.92	2,109.86	1,871.17	1,853.44	17.73	105.546	
3,300.00	3,271.24	3,541.08	3,491.10	8.26	10.23	8.36	362.78	2,101.92	1,834.03	1,815.86	18.17	100.952	
3,400.00	3,367.83	3,631.93	3,579.97	8.51	10.48	9.01	345.65	2,093.97	1,797.09	1,778.50	18.60	96.622	
3,500.00	3,464.42	3,700.00	3,646.60	8.80	10.64	9.51	333.02	2,088.11	1,760.65	1,741.68	18.97	92.794	
3,600.00	3,561.01	3,782.81	3,727.95	9.09	10.87	10.09	319.00	2,081.61	1,725.28	1,705.88	19.40	88.929	
3,700.00	3,657.60	3,857.03	3,801.14	9.38	11.05	10.58	307.79	2,076.42	1,691.10	1,671.30	19.80	85.397	
3,800.00	3,754.20	3,932.28	3,875.57	9.68	11.22	11.05	297.76	2,071.77	1,658.08	1,637.88	20.20	82.090	
3,900.00	3,850.79	4,000.00	3,942.72	9.98	11.37	11.45	289.86	2,068.11	1,626.22	1,605.64	20.57	79.040	
4,000.00	3,947.38	4,085.69	4,027.91	10.28	11.54	11.91	281.42	2,064.19	1,595.42	1,574.45	20.96	76.111	
4,100.00	4,043.97	4,163.76	4,105.68	10.59	11.67	12.30	275.24	2,061.33	1,565.74	1,544.42	21.33	73.422	
4,200.00	4,140.56	4,242.68	4,184.41	10.90	11.79	12.64	270.46	2,059.11	1,537.16	1,515.48	21.68	70.909	
4,300.00	4,237.16	4,322.38	4,264.03	11.21	11.89	12.94	267.14	2,057.57	1,509.64	1,487.62	22.02	68.564	
4,400.00	4,333.75	4,400.00	4,341.63	11.52	11.98	13.19	265.34	2,056.74	1,483.18	1,460.83	22.34	66.384	
4,500.00	4,430.34	4,488.72	4,430.34	11.84	12.00	13.42	264.94	2,056.55	1,457.70	1,435.11	22.59	64.536	
4,600.00	4,526.93	4,585.31	4,526.93	12.16	12.04	13.66	264.94	2,056.55	1,432.49	1,409.65	22.84	62.723	
4,700.00	4,623.53	4,681.90	4,623.53	12.48	12.07	13.91	264.94	2,056.55	1,407.30	1,384.21	23.10	60.933	
4,800.00	4,720.12	4,778.49	4,720.12	12.80	12.11	14.16	264.94	2,056.55	1,382.14	1,358.79	23.36	59.179	
4,900.00	4,816.71	4,875.09	4,816.71	13.12	12.15	14.43	264.94	2,056.55	1,357.01	1,333.39	23.62	57.460	
5,000.00	4,913.30	4,971.68	4,913.30	13.45	12.19	14.71	264.94	2,056.55	1,331.91	1,308.03	23.88	55.776	
5,100.00	5,009.89	5,068.27	5,009.89	13.78	12.23	15.00	264.94	2,056.55	1,306.83	1,282.69	24.14	54.125	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 52 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 156H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
5,200.00	5,106.49	5,164.86	5,106.49	14.10	12.27	15.29	264.94	2,056.55	1,281.79	1,257.38	24.41	52.508			
5,300.00	5,203.08	5,261.45	5,203.08	14.43	12.31	15.60	264.94	2,056.55	1,256.78	1,232.10	24.68	50.923			
5,400.00	5,299.67	5,358.05	5,299.67	14.75	12.35	15.92	264.94	2,056.55	1,231.82	1,206.88	24.94	49.391			
5,500.00	5,396.65	5,455.02	5,396.65	15.07	12.39	16.13	264.94	2,056.55	1,208.32	1,183.09	25.22	47.907			
5,600.00	5,494.23	5,552.60	5,494.23	15.36	12.43	16.34	264.94	2,056.55	1,187.30	1,161.80	25.50	46.562			
5,700.00	5,592.35	5,650.72	5,592.35	15.62	12.47	16.52	264.94	2,056.55	1,168.77	1,143.00	25.77	45.353			
5,800.00	5,690.94	5,749.31	5,690.94	15.86	12.52	16.69	264.94	2,056.55	1,152.74	1,126.70	26.03	44.276			
5,900.00	5,789.93	5,848.31	5,789.93	16.07	12.56	16.83	264.94	2,056.55	1,139.20	1,112.91	26.29	43.329			
6,000.00	5,889.26	5,947.64	5,889.26	16.25	12.60	16.95	264.94	2,056.55	1,128.16	1,101.62	26.54	42.509			
6,100.00	5,988.86	6,047.24	5,988.86	16.41	12.65	17.05	264.94	2,056.55	1,119.62	1,092.84	26.78	41.813			
6,200.00	6,088.66	6,147.03	6,088.66	16.53	12.69	17.12	264.94	2,056.55	1,113.58	1,086.58	27.00	41.242			
6,300.00	6,188.59	6,246.96	6,188.59	16.64	12.74	17.16	264.94	2,056.55	1,110.04	1,082.83	27.21	40.796			
6,400.00	6,288.58	6,346.95	6,288.58	16.71	12.78	89.59	264.94	2,056.55	1,109.00	1,081.66	27.34	40.561			
6,500.00	6,388.58	6,446.95	6,388.58	16.76	12.83	89.59	264.94	2,056.55	1,109.00	1,081.55	27.45	40.407			
6,600.00	6,488.58	6,546.95	6,488.58	16.82	12.87	89.59	264.94	2,056.55	1,109.00	1,081.45	27.55	40.253			
6,700.00	6,588.58	6,646.95	6,588.58	16.88	12.92	89.59	264.94	2,056.55	1,109.00	1,081.34	27.66	40.100			
6,800.00	6,688.58	6,746.95	6,688.58	16.94	12.97	89.59	264.94	2,056.55	1,109.00	1,081.24	27.76	39.947			
6,900.00	6,788.58	6,846.95	6,788.58	17.00	13.02	89.59	264.94	2,056.55	1,109.00	1,081.13	27.87	39.794			
7,000.00	6,888.58	6,946.95	6,888.58	17.05	13.06	89.59	264.94	2,056.55	1,109.00	1,081.02	27.98	39.642			
7,100.00	6,988.58	7,046.95	6,988.58	17.11	13.11	89.59	264.94	2,056.55	1,109.00	1,080.92	28.08	39.490			
7,200.00	7,088.58	7,146.95	7,088.58	17.17	13.16	89.59	264.94	2,056.55	1,109.00	1,080.81	28.19	39.339			
7,300.00	7,188.58	7,246.95	7,188.58	17.23	13.21	89.59	264.94	2,056.55	1,109.00	1,080.70	28.30	39.188			
7,400.00	7,288.58	7,346.95	7,288.58	17.29	13.26	89.59	264.94	2,056.55	1,109.00	1,080.59	28.41	39.037			
7,500.00	7,388.58														

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 156H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
10,400.00	10,288.58	10,346.95	10,288.58	19.15	14.87	89.59	264.94	2,056.55	1,109.00	1,077.10	31.90	34.764	
10,500.00	10,388.58	10,446.95	10,388.58	19.21	14.93	89.59	264.94	2,056.55	1,109.00	1,076.97	32.02	34.631	
10,600.00	10,488.58	10,546.95	10,488.58	19.27	14.99	89.59	264.94	2,056.55	1,109.00	1,076.85	32.15	34.498	
10,700.00	10,588.58	10,646.95	10,588.58	19.34	15.05	89.59	264.94	2,056.55	1,109.00	1,076.73	32.27	34.366	
10,800.00	10,688.58	10,746.95	10,688.58	19.40	15.11	89.59	264.94	2,056.55	1,109.00	1,076.60	32.39	34.235	
10,900.00	10,788.58	10,846.95	10,788.58	19.47	15.16	89.59	264.94	2,056.55	1,109.00	1,076.48	32.52	34.104	
11,000.00	10,888.58	10,946.95	10,888.58	19.53	15.22	89.59	264.94	2,056.55	1,109.00	1,076.36	32.64	33.974	
11,100.00	10,988.58	11,046.95	10,988.58	19.60	15.28	89.59	264.94	2,056.55	1,109.00	1,076.23	32.76	33.849	
11,102.18	10,990.76	11,049.13	10,990.76	19.60	15.28	89.59	264.94	2,056.55	1,109.00	1,076.23	32.77	33.846	CC
11,200.00	11,088.58	11,146.51	11,088.03	19.66	15.35	89.75	261.89	2,056.58	1,109.01	1,076.13	32.88	33.731	ES
11,300.00	11,188.58	11,242.44	11,182.18	19.73	15.54	90.67	244.09	2,056.74	1,109.25	1,076.16	33.09	33.523	
11,400.00	11,288.58	11,330.28	11,264.69	19.79	15.77	92.21	214.22	2,057.01	1,110.52	1,077.11	33.41	33.239	
11,500.00	11,388.58	11,407.50	11,332.73	19.86	16.03	94.08	177.82	2,057.34	1,113.99	1,080.17	33.82	32.938	
11,600.00	11,488.58	11,473.64	11,386.66	19.92	16.30	96.04	139.60	2,057.69	1,120.95	1,086.62	34.33	32.655	
11,700.00	11,588.58	11,529.50	11,428.54	19.99	16.57	97.92	102.66	2,058.03	1,132.49	1,097.57	34.93	32.424	
11,800.00	11,688.58	11,576.48	11,460.83	20.05	16.84	99.63	68.56	2,058.34	1,149.43	1,113.80	35.63	32.260	
11,900.00	11,788.58	11,616.04	11,485.78	20.12	17.08	101.16	37.87	2,058.61	1,172.23	1,135.80	36.43	32.175	
12,000.00	11,888.58	11,650.00	11,505.47	20.19	17.31	102.52	10.21	2,058.87	1,201.11	1,163.79	37.33	32.178	
12,100.00	11,988.51	11,678.99	11,520.95	20.25	17.52	-73.93	-14.30	2,059.09	1,235.48	1,197.22	38.26	32.294	
12,200.00	12,086.82	11,700.00	11,531.39	20.31	17.68	-69.50	-32.53	2,059.25	1,271.48	1,232.31	39.16	32.465	
12,300.00	12,180.57	11,750.00	11,553.49	20.35	18.08	-64.51	-77.36	2,059.66	1,306.66	1,266.54	40.12	32.567	
12,400.00	12,266.93	11,779.21	11,564.56	20.39	18.34	-60.70	-104.39	2,059.91	1,339.63	1,298.62	41.01	32.668	
12,500.00	12,343.26	11,815.61	11,576.40	20.44	18.66	-57.36	-138.80	2,060.22	1,369.05	1,327.18	41.87	32.697	
12,600.00	12,407.24	11,850.00	11,585.57	20.52	18.98	-54.73	-171.94	2,060.52	1,393.81	1,351.13	42.69	32.651	
12,700.00	12,456.94	11,900.00	11,595.31	20.67	19.46	-52.63	-220.96	2,060.97	1,413.13	1,369.62	43.51	32.478	
12,800.00	12,490.84	11,929.19	11,599.01	20.88	19.75	-51.41	-249.91	2,061.23	1,426.17	1,381.95	44.22	32.250	
12,900.00	12,507.91	11,967.79	11,601.62	21.18	20.14	-50.77	-288.41	2,061.58	1,432.74	1,387.83	44.91	31.904	
13,000.00	12,510.43	12,041.51	11,602.25	21.56	20.91	-50.69	-362.13	2,062.25	1,433.65	1,387.97	45.67	31.389	
13,100.00	12,511.30	12,141.51	11,602.78	22.01	21.98	-50.68	-462.12	2,063.16	1,433.91	1,387.29	46.61	30.761	
13,200.00	12,512.18	12,241.51	11,603.30	22.52	23.09	-50.67	-562.12	2,064.07	1,434.16	1,386.53	47.64	30.107	
13,300.00	12,513.05	12,341.51	11,603.83	23.10	24.22	-50.66	-662.11	2,064.98	1,434.42	1,385.69	48.73	29.435	
13,400.00	12,513.92	12,441.51	11,604.35	23.73	25.38	-50.65	-762.10	2,065.89	1,434.68	1,384.78	49.90	28.751	
13,500.00	12,514.80	12,541.51	11,604.88	24.41	26.56	-50.64	-862.10	2,066.79	1,434.94	1,383.80	51.13	28.063	
13,600.00	12,515.67	12,641.51	11,605.40	25.15	27.75	-50.64	-962.09	2,067.70	1,435.20	1,382.77	52.43	27.374	
13,700.00	12,516.55	12,741.51	11,605.93	25.93	28.96	-50.63	-1,062.08	2,068.61	1,435.45	1,381.67	53.78	26.691	
13,800.00	12,517.42	12,841.51	11,606.45	26.76	30.19	-50.62	-1,162.08	2,069.52	1,435.71	1,380.52	55.19	26.016	
13,900.00	12,518.29	12,941.51	11,606.98	27.63	31.42	-50.61	-1,262.07	2,070.43	1,435.97	1,379.33	56.64	25.352	
14,000.00	12,519.17	13,041.51	11,607.50	28.53	32.67	-50.60	-1,362.07	2,071.34	1,436.23	1,378.09	58.14	24.702	
14,100.00	12,520.04	13,141.51	11,608.03	29.47	33.92	-50.59	-1,462.06	2,072.25	1,436.49	1,376.80	59.68	24.069	
14,200.00	12,520.91	13,241.50	11,608.55	30.44	35.19	-50.58	-1,562.05	2,073.16	1,436.74	1,375.48	61.26	23.452	
14,300.00	12,521.79	13,341.50	11,609.08	31.44	36.46	-50.57	-1,662.05	2,074.07	1,437.00	1,374.12	62.88	22.853	
14,400.00	12,522.66	13,441.50	11,609.60	32.46	37.74	-50.56	-1,762.04	2,074.97	1,437.26	1,372.73	64.53	22.272	
14,500.00	12,523.53	13,541.50	11,610.13	33.51	39.02	-50.55	-1,862.04	2,075.88	1,437.52	1,371.31	66.21	21.710	
14,600.00	12,524.41	13,641.50	11,610.65	34.58	40.31	-50.54	-1,962.03	2,076.79	1,437.78	1,369.85	67.92	21.168	
14,700.00	12,525.28	13,741.50	11,611.18	35.67	41.60	-50.53	-2,062.02	2,077.70	1,438.04	1,368.38	69.66	20.644	
14,800.00	12,526.16	13,841.50	11,611.70	36.78	42.90	-50.52	-2,162.02	2,078.61	1,438.29	1,366.87	71.42	20.139	
14,900.00	12,527.03	13,941.50	11,612.23	37.90	44.21	-50.51	-2,262.01	2,079.52	1,438.55	1,365.35	73.20	19.652	
15,000.00	12,527.90	14,041.50	11,612.75	39.04	45.51	-50.50	-2,362.00	2,080.43	1,438.81	1,363.80	75.01	19.182	
15,100.00	12,528.78	14,141.50	11,613.28	40.20	46.83	-50.49	-2,462.00	2,081.34	1,439.07	1,362.24	76.83	18.730	
15,200.00	12,529.65	14,241.50	11,613.80	41.37	48.14	-50.48	-2,561.99	2,082.25	1,439.33	1,360.65	78.67	18.295	
15,300.00	12,530.52	14,341.50	11,614.33	42.55	49.46	-50.47	-2,661.99	2,083.15	1,439.59	1,359.05	80.53	17.876	
15,400.00	12,531.40	14,441.50	11,614.85	43.74	50.78	-50.46	-2,761.98	2,084.06	1,439.84	1,357.44	82.41	17.473	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 54 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 156H - OH - Plan 1													Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Offset Well Error: 0.50 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned: Distance			Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
15,500.00	12,532.27	14,541.50	11,615.38	44.94	52.10	-50.45	-2,861.97	2,084.97	1,440.10	1,355.81	84.29	17.084		
15,600.00	12,533.14	14,641.50	11,615.90	46.15	53.42	-50.45	-2,961.97	2,085.88	1,440.36	1,354.16	86.20	16.710		
15,700.00	12,534.02	14,741.50	11,616.43	47.37	54.75	-50.44	-3,061.96	2,086.79	1,440.62	1,352.51	88.11	16.350		
15,800.00	12,534.89	14,841.49	11,616.95	48.59	56.08	-50.43	-3,161.96	2,087.70	1,440.88	1,350.84	90.04	16.003		
15,900.00	12,535.76	14,941.49	11,617.48	49.83	57.41	-50.42	-3,261.95	2,088.61	1,441.14	1,349.16	91.98	15.668		
16,000.00	12,536.64	15,041.49	11,618.00	51.07	58.74	-50.41	-3,361.94	2,089.52	1,441.40	1,347.47	93.93	15.346		
16,100.00	12,537.51	15,141.49	11,618.53	52.32	60.08	-50.40	-3,461.94	2,090.43	1,441.66	1,345.77	95.88	15.035		
16,200.00	12,538.39	15,241.49	11,619.05	53.57	61.41	-50.39	-3,561.93	2,091.34	1,441.92	1,344.06	97.85	14.736		
16,300.00	12,539.26	15,341.49	11,619.58	54.83	62.75	-50.38	-3,661.93	2,092.24	1,442.17	1,342.35	99.83	14.447		
16,400.00	12,540.13	15,441.49	11,620.10	56.09	64.09	-50.37	-3,761.92	2,093.15	1,442.43	1,340.62	101.81	14.168		
16,500.00	12,541.01	15,541.49	11,620.63	57.36	65.43	-50.36	-3,861.91	2,094.06	1,442.69	1,338.89	103.80	13.899		
16,600.00	12,541.88	15,641.49	11,621.15	58.64	66.77	-50.35	-3,961.91	2,094.97	1,442.95	1,337.15	105.80	13.639		
16,700.00	12,542.75	15,741.49	11,621.68	59.91	68.11	-50.34	-4,061.90	2,095.88	1,443.21	1,335.41	107.80	13.387		
16,800.00	12,543.63	15,841.49	11,622.20	61.20	69.45	-50.33	-4,161.89	2,096.79	1,443.47	1,333.66	109.81	13.145		
16,900.00	12,544.50	15,941.49	11,622.73	62.48	70.80	-50.32	-4,261.89	2,097.70	1,443.73	1,331.90	111.83	12.910		
17,000.00	12,545.37	16,041.49	11,623.25	63.77	72.14	-50.31	-4,361.88	2,098.61	1,443.99	1,330.14	113.85	12.683		
17,100.00	12,546.25	16,141.49	11,623.78	65.06	73.49	-50.30	-4,461.88	2,099.52	1,444.25	1,328.37	115.88	12.463		
17,200.00	12,547.12	16,241.49	11,624.30	66.36	74.84	-50.29	-4,561.87	2,100.42	1,444.51	1,326.59	117.91	12.251		
17,300.00	12,547.99	16,341.49	11,624.83	67.66	76.18	-50.28	-4,661.86	2,101.33	1,444.77	1,324.82	119.95	12.045		
17,400.00	12,548.87	16,441.48	11,625.35	68.96	77.53	-50.28	-4,761.86	2,102.24	1,445.03	1,323.04	121.99	11.845		
17,500.00	12,549.74	16,541.48	11,625.88	70.26	78.88	-50.27	-4,861.85	2,103.15	1,445.29	1,321.25	124.04	11.652		
17,600.00	12,550.62	16,641.48	11,626.40	71.57	80.23	-50.26	-4,961.85	2,104.06	1,445.54	1,319.46	126.08	11.465		
17,700.00	12,551.49	16,741.48	11,626.93	72.88	81.58	-50.25	-5,06							

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 156H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error:		0.00 usft
Reference Offset				Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
20,700.00	12,577.70	19,741.46	11,642.68	112.81	122.29	-49.97	-8,061.66	2,132.24	1,453.61	1,262.87	190.74	7.621		
20,800.00	12,578.57	19,841.46	11,643.21	114.16	123.65	-49.96	-8,161.65	2,133.14	1,453.87	1,261.02	192.85	7.539		
20,900.00	12,579.44	19,941.46	11,643.73	115.51	125.01	-49.95	-8,261.64	2,134.05	1,454.13	1,259.17	194.96	7.459		
21,000.00	12,580.32	20,041.46	11,644.26	116.85	126.38	-49.94	-8,361.64	2,134.96	1,454.39	1,257.33	197.06	7.380		
21,100.00	12,581.19	20,141.46	11,644.78	118.20	127.74	-49.93	-8,461.63	2,135.87	1,454.65	1,255.48	199.17	7.303		
21,200.00	12,582.06	20,241.46	11,645.31	119.55	129.10	-49.92	-8,561.63	2,136.78	1,454.91	1,253.63	201.28	7.228		
21,300.00	12,582.94	20,341.46	11,645.83	120.89	130.46	-49.91	-8,661.62	2,137.69	1,455.17	1,251.78	203.39	7.155		
21,400.00	12,583.81	20,441.46	11,646.36	122.24	131.82	-49.90	-8,761.61	2,138.60	1,455.43	1,249.93	205.50	7.082		
21,500.00	12,584.69	20,541.46	11,646.88	123.59	133.19	-49.89	-8,861.61	2,139.51	1,455.70	1,248.09	207.61	7.012		
21,600.00	12,585.56	20,641.46	11,647.41	124.94	134.55	-49.88	-8,961.60	2,140.42	1,455.96	1,246.24	209.72	6.942		
21,700.00	12,586.43	20,741.46	11,647.93	126.29	135.91	-49.87	-9,061.59	2,141.33	1,456.22	1,244.39	211.83	6.874		
21,800.00	12,587.31	20,841.46	11,648.46	127.64	137.27	-49.86	-9,161.59	2,142.23	1,456.48	1,242.54	213.94	6.808		
21,900.00	12,588.18	20,941.46	11,648.98	128.99	138.64	-49.85	-9,261.58	2,143.14	1,456.74	1,240.69	216.06	6.742		
22,000.00	12,589.05	21,041.46	11,649.51	130.34	140.00	-49.85	-9,361.58	2,144.05	1,457.00	1,238.83	218.17	6.678		
22,100.00	12,589.93	21,141.46	11,650.03	131.70	141.36	-49.84	-9,461.57	2,144.96	1,457.26	1,236.98	220.28	6.616		
22,200.00	12,590.80	21,241.46	11,650.56	133.05	142.73	-49.83	-9,561.56	2,145.87	1,457.52	1,235.13	222.39	6.554		
22,300.00	12,591.67	21,341.45	11,651.08	134.40	144.09	-49.82	-9,661.56	2,146.78	1,457.79	1,233.28	224.51	6.493		
22,400.00	12,592.55	21,441.45	11,651.61	135.75	145.45	-49.81	-9,761.55	2,147.69	1,458.05	1,231.43	226.62	6.434		
22,500.00	12,593.42	21,541.45	11,652.13	137.11	146.82	-49.80	-9,861.55	2,148.60	1,458.31	1,229.58	228.73	6.376		
22,600.00	12,594.30	21,641.45	11,652.66	138.46	148.18	-49.79	-9,961.54	2,149.51	1,458.57	1,227.72	230.85	6.318		
22,700.00	12,595.17	21,741.45	11,653.18	139.81	149.55	-49.78	-10,061.53	2,150.41	1,458.83	1,225.87	232.96	6.262		
22,800.00	12,596.04	21,841.45	11,653.71	141.17	150.91	-49.77	-10,161.53	2,151.32	1,459.09	1,224.02	235.07	6.207		
22,875.30	12,596.70	21,915.93	11,654.10	142.19	151.93	-49.76	-10,236.00	2,152.00	1,459.29	1,222.63	236.66	6.166	SF	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 56 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 211H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:					Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)				
5,100.00	5,009.89	4,769.63	4,677.42	13.78	14.34	-163.86	118.47	-782.21	1,571.29	1,547.00	24.29	64.694		
5,200.00	5,106.49	4,858.95	4,764.27	14.10	14.62	-163.77	126.55	-801.44	1,616.19	1,591.48	24.71	65.400		
5,300.00	5,203.08	4,948.26	4,851.11	14.43	14.90	-163.67	134.62	-820.67	1,661.11	1,635.97	25.14	66.078		
5,400.00	5,299.67	5,037.58	4,937.97	14.75	15.18	-163.61	142.70	-839.90	1,706.01	1,680.46	25.56	66.755		
5,500.00	5,396.65	5,127.54	5,025.43	15.07	15.46	-163.71	150.83	-859.26	1,749.61	1,723.61	25.99	67.309		
5,600.00	5,494.23	5,218.53	5,113.91	15.36	15.75	-163.78	159.06	-878.85	1,790.93	1,764.50	26.43	67.765		
5,700.00	5,592.35	5,310.51	5,203.35	15.62	16.04	-163.82	167.37	-898.65	1,829.97	1,803.10	26.86	68.125		
5,800.00	5,690.94	5,403.40	5,293.67	15.86	16.33	-163.83	175.77	-918.65	1,866.68	1,839.39	27.29	68.397		
5,900.00	5,789.93	5,497.14	5,384.82	16.07	16.62	-163.80	184.24	-938.83	1,901.06	1,873.34	27.72	68.586		
6,000.00	5,889.26	5,591.68	5,476.74	16.25	16.92	-163.75	192.79	-959.18	1,933.09	1,904.95	28.14	68.699		
6,100.00	5,988.86	5,686.93	5,569.37	16.41	17.22	-163.68	201.40	-979.69	1,962.74	1,934.19	28.55	68.747		
6,200.00	6,088.66	5,860.35	5,738.75	16.53	17.73	-163.43	215.78	-1,013.92	1,988.37	1,959.10	29.27	67.931		
6,300.00	6,188.59	6,048.83	5,924.54	16.64	18.19	-163.20	228.01	-1,043.06	2,007.25	1,977.28	29.97	66.982		
6,400.00	6,288.58	6,241.06	6,115.40	16.71	18.55	-90.58	236.82	-1,064.04	2,019.16	1,988.64	30.52	66.161		
6,500.00	6,388.58	6,435.39	6,309.25	16.76	18.80	-90.43	241.94	-1,076.22	2,025.41	1,994.46	30.96	65.426		
6,600.00	6,488.58	6,614.76	6,488.58	16.82	18.96	-90.39	243.28	-1,079.42	2,027.05	1,995.83	31.22	64.927		
6,700.00	6,588.58	6,714.76	6,588.58	16.88	19.01	-90.39	243.28	-1,079.42	2,027.05	1,995.71	31.33	64.691		
6,800.00	6,688.58	6,814.76	6,688.58	16.94	19.06	-90.39	243.28	-1,079.42	2,027.05	1,995.60	31.45	64.456		
6,900.00	6,788.58	6,914.76	6,788.58	17.00	19.12	-90.39	243.28	-1,079.42	2,027.05	1,995.48	31.56	64.222		
7,000.00	6,888.58	7,014.76	6,888.58	17.05	19.17	-90.39	243.28	-1,079.42	2,027.05	1,995.37	31.68	63.989		
7,100.00	6,988.58	7,114.76	6,988.58	17.11	19.23	-90.39	243.28	-1,079.42	2,027.05	1,995.25	31.79	63.757		
7,200.00	7,088.58	7,214.76	7,088.58	17.17	19.28	-90.39	243.28	-1,079.42	2,027.05	1,995.14	31.91	63.525		
7,300.00	7,188.58	7,314.76	7,188.58	17.23	19.34	-90.39	243.28	-1,079.42	2,027.05	1,995.02	32.03	63.295		
7,400.00	7,288.58	7,414.76	7,288.58	17.29	19.39	-90.39	243.28	-1,079.42	2,027.05	1,994.90	32.14	63.065		
7,500.00	7,388.58	7,514.76	7,388.58	17.35	19.45	-90.39	243.28	-1,079.42	2,027.05	1,994.79	32.26	62.836		
7,600.00	7,488.58	7,614.76	7,488.58	17.41	19.50	-90.39	243.28	-1,079.42	2,027.05	1,994.67	32.38	62.608		
7,700.00	7,588.58	7,714.76	7,588.58	17.47	19.56	-90.39	243.28	-1,079.42	2,027.05	1,994.55	32.49	62.381		
7,800.00	7,688.58	7,814.76	7,688.58	17.53	19.61	-90.39	243.28	-1,079.42	2,027.05	1,994.43	32.61	62.155		
7,900.00	7,788.58	7,914.76	7,788.58	17.59	19.67	-90.39	243.28	-1,079.42	2,027.05	1,994.32	32.73	61.929		
8,000.00	7,888.58	8,014.76	7,888.58	17.65	19.72	-90.39	243.28	-1,079.42	2,027.05	1,994.20	32.85	61.705		
8,100.00	7,988.58	8,114.76	7,988.58	17.71	19.78	-90.39	243.28	-1,079.42	2,027.05	1,994.08	32.97	61.482		
8,200.00	8,088.58	8,214.76	8,088.58	17.77	19.84	-90.39	243.28	-1,079.42	2,027.05	1,993.96	33.09	61.259		
8,300.00	8,188.58	8,314.76	8,188.58	17.83	19.89	-90.39	243.28	-1,079.42	2,027.05	1,993.84	33.21	61.038		
8,400.00	8,288.58	8,414.76	8,288.58	17.89	19.95	-90.39	243.28	-1,079.42	2,027.05	1,993.72	33.33	60.817		
8,500.00	8,388.58	8,514.76	8,388.58	17.95	20.01	-90.39	243.28	-1,079.42	2,027.05	1,993.60	33.45	60.597		
8,600.00	8,488.58	8,614.76	8,488.58	18.02	20.07	-90.39	243.28	-1,079.42	2,027.05	1,993.47	33.57	60.378		
8,700.00	8,588.58	8,714.76	8,588.58	18.08	20.12	-90.39	243.28	-1,079.42	2,027.05	1,993.35	33.69	60.160		
8,800.00	8,688.58	8,814.76	8,688.58	18.14	20.18	-90.39	243.28	-1,079.42	2,027.05	1,993.23	33.82	59.944		
8,900.00	8,788.58	8,914.76	8,788.58	18.20	20.24	-90.39	243.28	-1,079.42	2,027.05	1,993.11	33.94	59.728		
9,000.00	8,888.58	9,014.76	8,888.58	18.26	20.30	-90.39	243.28	-1,079.42	2,027.05	1,992.99	34.06	59.513		
9,100.00	8,988.58	9,114.76	8,988.58	18.32	20.35	-90.39	243.28	-1,079.42	2,027.05	1,992.86	34.18	59.299		
9,200.00	9,088.58	9,214.76	9,088.58	18.39	20.41	-90.39	243.28	-1,079.42	2,027.05	1,992.74	34.31	59.086		
9,300.00	9,188.58	9,314.76	9,188.58	18.45	20.47	-90.39	243.28	-1,079.42	2,027.05	1,992.62	34.43	58.873		
9,400.00	9,288.58	9,414.76	9,288.58	18.51	20.53	-90.39	243.28	-1,079.42	2,027.05	1,992.49	34.55	58.662		
9,500.00	9,388.58	9,514.76	9,388.58	18.57	20.59	-90.39	243.28	-1,079.42	2,027.05	1,992.37	34.68	58.452		
9,600.00	9,488.58	9,614.76	9,488.58	18.64	20.65	-90.39	243.28	-1,079.42	2,027.05	1,992.24	34.80	58.243		
9,700.00	9,588.58	9,714.76	9,588.58	18.70	20.71	-90.39	243.28	-1,079.42	2,027.05	1,992.12	34.93	58.035		
9,800.00	9,688.58	9,814.76	9,688.58	18.76	20.76	-90.39	243.28	-1,079.42	2,027.05	1,991.99	35.05	57.827		
9,900.00	9,788.58	9,914.76	9,788.58	18.83	20.82	-90.39	243.28	-1,079.42	2,027.05	1,991.87	35.18	57.621		
10,000.00	9,888.58	10,014.76	9,888.58	18.89	20.88	-90.39	243.28	-1,079.42	2,027.05	1,991.74	35.30	57.416		
10,100.00	9,988.58	10,114.76	9,988.58	18.95	20.94	-90.39	243.28	-1,079.42	2,027.05	1,991.62	35.43	57.211		
10,200.00	10,088.58	10,214.76	10,088.58	19.02	21.00	-90.39	243.28	-1,079.42	2,027.05	1,991.49	35.56	57.008		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 211H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)		
10,300.00	10,188.58	10,314.76	10,188.58	19.08	21.06	-90.39	243.28	-1,079.42	2,027.05	1,991.36	35.68	56.805
10,400.00	10,288.58	10,414.76	10,288.58	19.15	21.12	-90.39	243.28	-1,079.42	2,027.05	1,991.24	35.81	56.604
10,500.00	10,388.58	10,514.76	10,388.58	19.21	21.18	-90.39	243.28	-1,079.42	2,027.05	1,991.11	35.94	56.403
10,600.00	10,488.58	10,614.76	10,488.58	19.27	21.24	-90.39	243.28	-1,079.42	2,027.05	1,990.98	36.07	56.204
10,700.00	10,588.58	10,714.76	10,588.58	19.34	21.30	-90.39	243.28	-1,079.42	2,027.05	1,990.85	36.19	56.005
10,800.00	10,688.58	10,814.76	10,688.58	19.40	21.36	-90.39	243.28	-1,079.42	2,027.05	1,990.72	36.32	55.808
10,900.00	10,788.58	10,914.76	10,788.58	19.47	21.43	-90.39	243.28	-1,079.42	2,027.05	1,990.60	36.45	55.611
11,000.00	10,888.58	11,014.76	10,888.58	19.53	21.49	-90.39	243.28	-1,079.42	2,027.05	1,990.47	36.58	55.415
11,100.00	10,988.58	11,114.76	10,988.58	19.60	21.55	-90.39	243.28	-1,079.42	2,027.05	1,990.34	36.71	55.221
11,200.00	11,088.58	11,214.76	11,088.58	19.66	21.61	-90.39	243.28	-1,079.42	2,027.05	1,990.21	36.84	55.027
11,300.00	11,188.58	11,314.76	11,188.58	19.73	21.67	-90.39	243.28	-1,079.42	2,027.05	1,990.08	36.97	54.834
11,400.00	11,288.58	11,414.76	11,288.58	19.79	21.73	-90.39	243.28	-1,079.42	2,027.05	1,989.95	37.10	54.642
11,500.00	11,388.58	11,514.76	11,388.58	19.86	21.79	-90.39	243.28	-1,079.42	2,027.05	1,989.82	37.23	54.451
11,600.00	11,488.58	11,614.76	11,488.58	19.92	21.85	-90.39	243.28	-1,079.42	2,027.05	1,989.69	37.36	54.261
11,700.00	11,588.58	11,714.76	11,588.58	19.99	21.92	-90.39	243.28	-1,079.42	2,027.05	1,989.56	37.49	54.072
11,800.00	11,688.58	11,814.76	11,688.58	20.05	21.98	-90.39	243.28	-1,079.42	2,027.05	1,989.43	37.62	53.884
11,900.00	11,788.58	11,914.76	11,788.58	20.12	22.04	-90.39	243.28	-1,079.42	2,027.05	1,989.30	37.75	53.697
12,000.00	11,888.58	12,014.76	11,888.58	20.19	22.10	-90.39	243.28	-1,079.42	2,027.05	1,989.17	37.88	53.515
12,100.00	11,988.51	12,115.09	11,988.84	20.25	22.14	90.11	241.02	-1,079.40	2,027.05	1,989.15	37.90	53.482
12,200.00	12,086.82	12,215.75	12,087.81	20.31	22.16	90.11	223.35	-1,079.25	2,027.05	1,989.29	37.76	53.680
12,300.00	12,180.57	12,316.41	12,182.16	20.35	22.14	90.11	188.65	-1,078.95	2,027.05	1,989.52	37.53	54.018
12,400.00	12,266.93	12,417.06	12,268.99	20.39	22.11	90.10	138.01	-1,078.51	2,027.05	1,989.81	37.23	54.442
12,500.00	12,343.26	12,517.66	12,345.59	20.44	22.07	90.09	73.00	-1,077.95	2,027.05	1,990.11	36.94	54.875
12,600.00	12,407.24	12,618.20	12,409.63	20.52	22.06	90.08	-4.34	-1,077.29	2,027.05	1,990.34	36.71	55.220
12,700.00	12,456.94	12,718.67	12,459.16	20.67	22.10	90.07	-91.60	-1,076.54	2,027.05	1,990.45	36.60	55.381
12,800.00	12,490.84	12,819.05	12,492.67	20.88	22.20	90.05	-186.08	-1,075.72	2,027.05	1,990.38	36.67	55.278
12,831.79	12,498.13	12,850.93	12,499.80	20.97	22.26	90.05	-217.15	-1,075.46	2,027.05	1,990.30	36.74	55.169
12,900.00	12,507.91	12,919.33	12,509.20	21.18	22.39	90.04	-284.85	-1,074.87	2,027.05	1,990.11	36.94	54.873
13,000.00	12,510.43	13,019.41	12,511.46	21.56	22.65	90.03	-384.88	-1,074.01	2,027.05	1,989.63	37.42	54.170
13,100.00	12,511.30	13,119.41	12,512.34	22.01	22.98	90.03	-484.87	-1,073.15	2,027.05	1,988.94	38.11	53.191
13,200.00	12,512.18	13,219.41	12,513.21	22.52	23.37	90.03	-584.86	-1,072.29	2,027.05	1,988.07	38.98	52.006
13,300.00	12,513.05	13,319.41	12,514.08	23.10	23.82	90.03	-684.86	-1,071.43	2,027.05	1,987.03	40.01	50.658
13,400.00	12,513.92	13,419.41	12,514.95	23.73	24.32	90.03	-784.85	-1,070.57	2,027.05	1,985.84	41.21	49.192
13,500.00	12,514.80	13,519.41	12,515.83	24.41	24.88	90.03	-884.84	-1,069.71	2,027.05	1,984.51	42.54	47.648
13,600.00	12,515.67	13,619.41	12,516.70	25.15	25.48	90.03	-984.83	-1,068.85	2,027.05	1,983.04	44.01	46.062
13,700.00	12,516.55	13,719.41	12,517.57	25.93	26.14	90.03	-1,084.83	-1,067.99	2,027.05	1,981.46	45.59	44.463
13,800.00	12,517.42	13,819.41	12,518.45	26.76	26.84	90.03	-1,184.82	-1,067.13	2,027.05	1,979.77	47.28	42.875
13,900.00	12,518.29	13,919.41	12,519.32	27.63	27.58	90.03	-1,284.81	-1,066.27	2,027.05	1,977.99	49.06	41.316
14,000.00	12,519.17	14,019.41	12,520.19	28.53	28.37	90.03	-1,384.80	-1,065.41	2,027.05	1,976.12	50.93	39.801
14,100.00	12,520.04	14,119.41	12,521.07	29.47	29.19	90.03	-1,484.80	-1,064.55	2,027.05	1,974.18	52.87	38.337
14,200.00	12,520.91	14,219.41	12,521.94	30.44	30.05	90.03	-1,584.79	-1,063.69	2,027.05	1,972.17	54.89	36.932
14,300.00	12,521.79	14,319.41	12,522.81	31.44	30.95	90.03	-1,684.78	-1,062.83	2,027.05	1,970.09	56.96	35.587
14,400.00	12,522.66	14,419.41	12,523.68	32.46	31.88	90.03	-1,784.77	-1,061.96	2,027.05	1,967.97	59.09	34.306
14,500.00	12,523.53	14,519.41	12,524.56	33.51	32.84	90.03	-1,884.77	-1,061.10	2,027.05	1,965.79	61.26	33.087
14,600.00	12,524.41	14,619.41	12,525.43	34.58	33.82	90.03	-1,984.76	-1,060.24	2,027.06	1,963.57	63.48	31.930
14,700.00	12,525.28	14,719.41	12,526.30	35.67	34.83	90.03	-2,084.75	-1,059.38	2,027.06	1,961.31	65.74	30.833
14,800.00	12,526.16	14,819.41	12,527.18	36.78	35.87	90.03	-2,184.74	-1,058.52	2,027.06	1,959.02	68.04	29.793
14,900.00	12,527.03	14,919.41	12,528.05	37.90	36.92	90.03	-2,284.74	-1,057.66	2,027.06	1,956.69	70.36	28.808
15,000.00	12,527.90	15,019.41	12,528.92	39.04	38.00	90.03	-2,384.73	-1,056.80	2,027.06	1,954.34	72.72	27.875
15,100.00	12,528.78	15,119.41	12,529.80	40.20	39.09	90.03	-2,484.72	-1,055.94	2,027.06	1,951.96	75.10	26.991
15,200.00	12,529.65	15,219.41	12,530.67	41.37	40.20	90.03	-2,584.71	-1,055.08	2,027.06	1,949.55	77.51	26.153
15,300.00	12,530.52	15,319.41	12,531.54	42.55	41.33	90.03	-2,684.71	-1,054.22	2,027.06	1,947.13	79.93	25.359

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 59 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 211H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (")	Offset Wellbore Centre			Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)		
15,400.00	12,531.40	15,419.41	12,532.42	43.74	42.47	90.03	-2,784.70	-1,053.36	2,027.06	1,944.68	82.38	24.606	
15,500.00	12,532.27	15,519.41	12,533.29	44.94	43.62	90.03	-2,884.69	-1,052.50	2,027.06	1,942.22	84.84	23.891	
15,600.00	12,533.14	15,619.41	12,534.16	46.15	44.79	90.03	-2,984.68	-1,051.64	2,027.06	1,939.73	87.33	23.213	
15,700.00	12,534.02	15,719.41	12,535.03	47.37	45.97	90.03	-3,084.68	-1,050.78	2,027.06	1,937.24	89.82	22.568	
15,800.00	12,534.89	15,819.41	12,535.91	48.59	47.15	90.03	-3,184.67	-1,049.92	2,027.06	1,934.73	92.33	21.954	
15,900.00	12,535.76	15,919.41	12,536.78	49.83	48.35	90.03	-3,284.66	-1,049.05	2,027.06	1,932.21	94.85	21.370	
16,000.00	12,536.64	16,019.41	12,537.65	51.07	49.56	90.03	-3,384.65	-1,048.19	2,027.06	1,929.67	97.39	20.814	
16,100.00	12,537.51	16,119.41	12,538.53	52.32	50.77	90.03	-3,484.65	-1,047.33	2,027.06	1,927.13	99.93	20.284	
16,200.00	12,538.39	16,219.41	12,539.40	53.57	52.00	90.03	-3,584.64	-1,046.47	2,027.06	1,924.57	102.49	19.778	
16,300.00	12,539.26	16,319.41	12,540.27	54.83	53.22	90.03	-3,684.63	-1,045.61	2,027.06	1,922.01	105.05	19.296	
16,400.00	12,540.13	16,419.41	12,541.15	56.09	54.46	90.03	-3,784.62	-1,044.75	2,027.06	1,919.44	107.63	18.834	
16,500.00	12,541.01	16,519.41	12,542.02	57.36	55.70	90.03	-3,884.62	-1,043.89	2,027.06	1,916.86	110.21	18.393	
16,600.00	12,541.88	16,619.41	12,542.89	58.64	56.95	90.03	-3,984.61	-1,043.03	2,027.07	1,914.27	112.80	17.971	
16,700.00	12,542.75	16,719.41	12,543.76	59.91	58.21	90.03	-4,084.60	-1,042.17	2,027.07	1,911.67	115.39	17.567	
16,800.00	12,543.63	16,819.41	12,544.64	61.20	59.47	90.03	-4,184.59	-1,041.31	2,027.07	1,909.07	117.99	17.179	
16,900.00	12,544.50	16,919.41	12,545.51	62.48	60.73	90.03	-4,284.59	-1,040.45	2,027.07	1,906.46	120.60	16.808	
17,000.00	12,545.37	17,019.41	12,546.38	63.77	62.00	90.03	-4,384.58	-1,039.59	2,027.07	1,903.85	123.22	16.451	
17,100.00	12,546.25	17,119.41	12,547.26	65.06	63.27	90.03	-4,484.57	-1,038.73	2,027.07	1,901.23	125.84	16.109	
17,200.00	12,547.12	17,219.41	12,548.13	66.36	64.55	90.03	-4,584.56	-1,037.87	2,027.07	1,898.61	128.46	15.780	
17,300.00	12,547.99	17,319.41	12,549.00	67.66	65.83	90.03	-4,684.56	-1,037.01	2,027.07	1,895.98	131.09	15.463	
17,400.00	12,548.87	17,419.41	12,549.88	68.96	67.11	90.03	-4,784.55	-1,036.15	2,027.07	1,893.35	133.72	15.159	
17,500.00	12,549.74	17,519.41	12,550.75	70.26	68.40	90.03	-4,884.54	-1,035.28	2,027.07	1,890.71	136.36	14.865	
17,600.00	12,550.62	17,619.41	12,551.62	71.57	69.69	90.03	-4,98						

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 60 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 211H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
20,600.00	12,576.82	20,619.41	12,577.81	111.47	109.32	90.03	-7,984.31	-1,008.60	2,027.09	1,807.71	219.38	9.240	
20,700.00	12,577.70	20,719.41	12,578.69	112.81	110.66	90.03	-8,084.30	-1,007.74	2,027.09	1,805.01	222.08	9.128	
20,800.00	12,578.57	20,819.41	12,579.56	114.16	112.00	90.03	-8,184.29	-1,006.88	2,027.09	1,802.31	224.78	9.018	
20,900.00	12,579.44	20,919.41	12,580.43	115.51	113.34	90.03	-8,284.29	-1,006.02	2,027.09	1,799.60	227.48	8.911	
21,000.00	12,580.32	21,019.41	12,581.31	116.85	114.69	90.03	-8,384.28	-1,005.16	2,027.09	1,796.90	230.19	8.806	
21,100.00	12,581.19	21,119.41	12,582.18	118.20	116.03	90.03	-8,484.27	-1,004.30	2,027.09	1,794.19	232.89	8.704	
21,200.00	12,582.06	21,219.41	12,583.05	119.55	117.37	90.03	-8,584.26	-1,003.44	2,027.09	1,791.49	235.60	8.604	
21,300.00	12,582.94	21,319.41	12,583.92	120.89	118.72	90.03	-8,684.26	-1,002.58	2,027.09	1,788.78	238.31	8.506	
21,400.00	12,583.81	21,419.41	12,584.80	122.24	120.06	90.03	-8,784.25	-1,001.72	2,027.09	1,786.07	241.01	8.411	
21,500.00	12,584.69	21,519.41	12,585.67	123.59	121.40	90.03	-8,884.24	-1,000.86	2,027.09	1,783.37	243.72	8.317	
21,600.00	12,585.56	21,619.41	12,586.54	124.94	122.75	90.03	-8,984.23	-1,000.00	2,027.09	1,780.66	246.43	8.226	
21,700.00	12,586.43	21,719.41	12,587.42	126.29	124.10	90.03	-9,084.23	-999.14	2,027.09	1,777.95	249.14	8.136	
21,800.00	12,587.31	21,819.41	12,588.29	127.64	125.44	90.03	-9,184.22	-998.28	2,027.09	1,775.24	251.85	8.049	
21,900.00	12,588.18	21,919.41	12,589.16	128.99	126.79	90.03	-9,284.21	-997.42	2,027.09	1,772.53	254.56	7.963	
22,000.00	12,589.05	22,019.41	12,590.04	130.34	128.14	90.03	-9,384.20	-996.56	2,027.09	1,769.82	257.28	7.879	
22,100.00	12,589.93	22,119.41	12,590.91	131.70	129.48	90.03	-9,484.20	-995.69	2,027.09	1,767.11	259.99	7.797	
22,200.00	12,590.80	22,219.41	12,591.78	133.05	130.83	90.03	-9,584.19	-994.83	2,027.09	1,764.39	262.70	7.716	
22,300.00	12,591.67	22,319.41	12,592.66	134.40	132.18	90.03	-9,684.18	-993.97	2,027.09	1,761.68	265.41	7.637	
22,400.00	12,592.55	22,419.41	12,593.53	135.75	133.53	90.03	-9,784.17	-993.11	2,027.09	1,758.97	268.13	7.560	
22,500.00	12,593.42	22,519.41	12,594.40	137.11	134.88	90.03	-9,884.17	-992.25	2,027.10	1,756.25	270.84	7.484	
22,600.00	12,594.30	22,619.41	12,595.27	138.46	136.23	90.03	-9,984.16	-991.39	2,027.10	1,753.54	273.56	7.410	
22,700.00	12,595.17	22,719.41	12,596.15	139.81	137.58	90.03	-10,084.15	-990.53	2,027.10	1,750.82	276.27	7.337	
22,800.00	12,596.04	22,819.41	12,597.02	141.17	138.93	90.03	-10,184.14	-989.67	2,027.10	1,748.11	278.99	7.266	
22,875.30	12,596.70	22,894.71	12,597.68	142.19	139.95	90.03	-10,259.44	-989.02	2,027.10	1,746.06	281.03	7.213	SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 212H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)														Rule Assigned:	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
0.00	0.00	0.00	1.00	0.50	0.50	180.00	-25.00	0.00	25.02						
100.00	100.00	99.00	100.00	0.98	0.97	180.00	-25.00	0.00	25.00	23.05	1.95	12.788			
200.00	200.00	199.00	200.00	1.56	1.56	180.00	-25.00	0.00	25.00	21.88	3.12	8.022			
300.00	300.00	299.00	300.00	1.98	1.98	180.00	-25.00	0.00	25.00	21.04	3.96	6.316			
400.00	400.00	399.00	400.00	2.33	2.33	180.00	-25.00	0.00	25.00	20.34	4.66	5.370			
500.00	500.00	499.00	500.00	2.63	2.63	180.00	-25.00	0.00	25.00	19.73	5.27	4.747			
600.00	600.00	599.00	600.00	2.91	2.91	180.00	-25.00	0.00	25.00	19.18	5.82	4.297			
700.00	700.00	699.00	700.00	3.16	3.16	180.00	-25.00	0.00	25.00	18.67	6.33	3.953			
800.00	800.00	799.00	800.00	3.40	3.40	180.00	-25.00	0.00	25.00	18.20	6.80	3.677			
900.00	900.00	899.00	900.00	3.62	3.62	180.00	-25.00	0.00	25.00	17.75	7.25	3.451			
1,000.00	1,000.00	999.00	1,000.00	3.76	3.83	88.12	-25.00	0.00	25.00	17.40	7.59	3.292			
1,061.64	1,061.64	1,060.64	1,061.64	3.91	3.96	90.00	-25.00	0.00	24.98	17.15	7.84	3.189	CC		
1,100.00	1,099.98	1,098.98	1,099.98	4.00	4.04	92.32	-25.00	0.00	25.01	17.02	7.99	3.131	ES		
1,200.00	1,199.88	1,198.88	1,199.88	4.24	4.23	102.31	-25.00	0.00	25.57	17.21	8.37	3.056			
1,300.00	1,299.63	1,298.63	1,299.63	4.46	4.42	116.54	-25.00	0.00	27.95	19.19	8.76	3.189			
1,400.00	1,399.25	1,398.25	1,399.25	4.60	4.60	130.23	-25.00	0.00	32.78	23.67	9.11	3.598			
1,500.00	1,498.87	1,497.87	1,498.87	4.78	4.77	140.04	-25.00	0.00	38.99	29.50	9.49	4.108			
1,600.00	1,598.49	1,597.49	1,598.49	4.96	4.94	147.02	-25.00	0.00	46.02	36.16	9.86	4.669			
1,700.00	1,698.11	1,697.11	1,698.11	5.14	5.11	152.10	-25.00	0.00	53.55	43.34	10.21	5.243			
1,800.00	1,797.73	1,796.73	1,797.73	5.32	5.27	155.90	-25.00	0.00	61.39	50.83	10.56	5.813			
1,900.00	1,897.34	1,896.34	1,897.34	5.49	5.43	158.84	-25.00	0.00	69.44	58.54	10.90	6.369			
2,000.00	1,996.96	1,995.96	1,996.96	5.67	5.58	161.16	-25.00	0.00	77.64	66.40	11.24	6.907			
2,100.00	2,096.58	2,095.58	2,096.58	5.85	5.74	163.04	-25.00	0.00	85.94	74.36	11.57	7.425			
2,200.00	2,196.20	2,195.20	2,196.20	6.04	5.89	164.58	-25.00	0.00	94.31	82.40	11.91	7.918			
2,300.00	2,295.72	2,296.79	2,297.78	6.23	6.06	172.45	-24.07	0.80	102.96	90.68	12.27	8.389			
2,400.00	2,394.97	2,398.56	2,399.47	6.43	6.24	178.52	-21.08	3.35	112.11	99.47	12.64	8.868			
2,500.00	2,493.89	2,500.38	2,501.07	6.64	6.42	-176.54	-16.02	7.66	121.83	108.83	13.01	9.366			
2,600.00	2,592.40	2,602.24	2,602.50	6.85	6.59	-172.30	-8.90	13.74	132.18	118.81	13.37	9.888			
2,700.00	2,690.45	2,704.13	2,703.66	7.07	6.77	-168.50	0.27	21.56	143.21	129.48	13.72	10.437			
2,800.00	2,787.96	2,804.02	2,802.60	7.28	6.86	-165.25	10.76	30.51	155.41	141.40	14.02	11.089			
2,900.00	2,884.87	2,902.88	2,900.50	7.49	7.01	-162.90	21.22	39.44	170.02	155.65	14.37	11.834			
3,000.00	2,981.46	3,001.59	2,998.25	7.68	7.15	-162.02	31.67	48.36	185.81	171.11	14.70	12.638			
3,100.00	3,078.05	3,100.30	3,096.00	7.87	7.30	-161.28	42.12	57.27	201.64	186.60	15.04	13.403			
3,200.00	3,174.64	3,199.01	3,193.75	8.06	7.45	-160.65	52.56	66.19	217.50	202.11	15.39	14.132			
3,300.00	3,271.24	3,297.72	3,291.50	8.26	7.61	-160.10	63.01	75.10	233.37	217.63	15.74	14.825			
3,400.00	3,367.83	3,396.43	3,389.24	8.51	7.76	-159.62	73.46	84.02	249.27	233.17	16.10	15.485			
3,500.00	3,464.42	3,495.13	3,486.99	8.80	7.92	-159.20	83.90	92.93	265.18	248.72	16.46	16.112			
3,600.00	3,561.01	3,593.84	3,584.74	9.09	8.08	-158.83	94.35	101.85	281.11	264.28	16.82	16.709			
3,700.00	3,657.60	3,692.55	3,682.49	9.38	8.24	-158.49	104.80	110.76	297.04	279.85	17.19	17.278			
3,800.00	3,754.20	3,791.26	3,780.24	9.68	8.40	-158.19	115.24	119.68	312.98	295.42	17.56	17.819			
3,900.00	3,850.79	3,889.97	3,877.99	9.98	8.57	-157.92	125.69	128.59	328.93	310.99	17.94	18.335			
4,000.00	3,947.38	3,988.68	3,975.73	10.28	8.73	-157.68	136.14	137.51	344.89	326.57	18.32	18.827			
4,100.00	4,043.97	4,087.38	4,073.48	10.59	8.90	-157.46	146.58	146.43	360.85	342.15	18.70	19.296			
4,200.00	4,140.56	4,186.09	4,171.23	10.90	9.06	-157.25	157.03	155.34	376.82	357.73	19.09	19.743			
4,300.00	4,237.16	4,284.80	4,268.98	11.21	9.23	-157.06	167.48	164.26	392.79	373.32	19.47	20.170			
4,400.00	4,333.75	4,383.51	4,366.73	11.52	9.40	-156.89	177.93	173.17	408.77	388.90	19.86	20.578			
4,500.00	4,430.34	4,482.22	4,464.48	11.84	9.57	-156.73	188.37	182.09	424.75	404.49	20.26	20.968			
4,600.00	4,526.93	4,580.93	4,562.22	12.16	9.74	-156.58	198.82	191.00	440.73	420.08	20.65	21.341			
4,700.00	4,623.53	4,679.63	4,659.97	12.48	9.91	-156.44	209.27	199.92	456.71	435.67	21.05	21.698			
4,800.00	4,720.12	4,778.34	4,757.72	12.80	10.09	-156.31	219.71	208.83	472.70	451.25	21.45	22.040			
4,900.00	4,816.71	4,873.07	4,851.58	13.12	10.24	-156.24	229.45	217.14	488.93	467.11	21.82	22.412			
5,000.00	4,913.30	4,964.71	4,942.63	13.45	10.40	-156.36	237.33	223.86	506.40	484.21	22.18	22.828			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 62 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 212H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Offset Site Error: 0.00 usft	
Rule Assigned:										Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Minimum Separation (usft)	Warning
5,100.00	5,009.89	5,055.80	5,033.36	13.78	10.57	-156.67	243.51	229.14	525.22	502.68	23.300
5,200.00	5,106.49	5,146.27	5,123.62	14.10	10.73	-157.15	248.03	232.99	545.42	522.54	23.834
5,300.00	5,203.08	5,236.00	5,213.28	14.43	10.88	-157.77	250.90	235.44	567.02	543.81	24.430
5,400.00	5,299.67	5,324.92	5,302.18	14.75	11.00	-158.52	252.16	236.52	590.06	566.56	25.113
5,500.00	5,396.65	5,419.39	5,396.65	15.07	11.07	-159.44	252.23	236.58	612.86	589.08	25.777
5,600.00	5,494.23	5,516.97	5,494.23	15.36	11.16	-160.24	252.23	236.58	633.43	609.34	26.297
5,700.00	5,592.35	5,615.09	5,592.35	15.62	11.25	-160.90	252.23	236.58	651.66	627.26	26.713
5,800.00	5,690.94	5,713.68	5,690.94	15.86	11.35	-161.45	252.23	236.58	667.50	642.80	27.028
5,900.00	5,789.93	5,812.68	5,789.93	16.07	11.44	-161.89	252.23	236.58	680.92	655.93	27.245
6,000.00	5,889.26	5,912.01	5,889.26	16.25	11.53	-162.24	252.23	236.58	691.90	666.62	27.369
6,100.00	5,988.86	6,011.60	5,988.86	16.41	11.63	-162.50	252.23	236.58	700.41	674.85	27.403
6,200.00	6,088.66	6,111.40	6,088.66	16.53	11.72	-162.68	252.23	236.58	706.44	680.61	27.351
6,300.00	6,188.59	6,211.33	6,188.59	16.64	11.81	-162.78	252.23	236.58	709.97	683.89	27.221
6,400.00	6,288.58	6,311.32	6,288.58	16.71	11.90	-90.39	252.23	236.58	711.02	684.76	26.267
6,500.00	6,388.58	6,411.32	6,388.58	16.76	12.00	-90.39	252.23	236.58	711.02	684.60	26.920
6,600.00	6,488.58	6,511.32	6,488.58	16.82	12.09	-90.39	252.23	236.58	711.02	684.45	26.767
6,700.00	6,588.58	6,611.32	6,588.58	16.88	12.18	-90.39	252.23	236.58	711.02	684.30	26.616
6,800.00	6,688.58	6,711.32	6,688.58	16.94	12.27	-90.39	252.23	236.58	711.02	684.15	26.466
6,900.00	6,788.58	6,811.32	6,788.58	17.00	12.37	-90.39	252.23	236.58	711.02	684.00	26.318
7,000.00	6,888.58	6,911.32	6,888.58	17.05	12.46	-90.39	252.23	236.58	711.02	683.85	26.171
7,100.00	6,988.58	7,011.32	6,988.58	17.11	12.55	-90.39	252.23	236.58	711.02	683.70	26.026
7,200.00	7,088.58	7,111.32	7,088.58	17.17	12.64	-90.39	252.23	236.58	711.02	683.55	25.883
7,300.00	7,188.58	7,211.32	7,188.58	17.23	12.73	-90.39	252.23	236.58	711.02	683.39	25.741
7,400.00	7,288.58	7,311.32	7,288.58	17.29	12.82	-90.39	252.23	236.58	711.02	683.24	25.600
7,500.00	7,388.58	7,411.32	7,388.58	17.35	12.91	-90.39	252.23	236.58	711.02	683.09	25.461
7,600.00	7,488.58	7,511.32	7,488.58	17.41	13.01	-90.39	252.23	236.58	711.02	682.94	25.324
7,700.00	7,588.58	7,611.32	7,588.58	17.47	13.10	-90.39	252.23	236.58	711.02	682.79	25.188
7,800.00	7,688.58	7,711.32	7,688.58	17.53	13.19	-90.39	252.23	236.58	711.02	682.64	25.053
7,900.00	7,788.58	7,811.32	7,788.58	17.59	13.28	-90.39	252.23	236.58	711.02	682.48	24.919
8,000.00	7,888.58	7,911.32	7,888.58	17.65	13.37	-90.39	252.23	236.58	711.02	682.33	24.787
8,100.00	7,988.58	8,011.32	7,988.58	17.71	13.46	-90.39	252.23	236.58	711.02	682.18	24.657
8,200.00	8,088.58	8,111.32	8,088.58	17.77	13.55	-90.39	252.23	236.58	711.02	682.03	24.527
8,300.00	8,188.58	8,211.32	8,188.58	17.83	13.64	-90.39	252.23	236.58	711.02	681.88	24.399
8,400.00	8,288.58	8,311.32	8,288.58	17.89	13.73	-90.39	252.23	236.58	711.02	681.72	24.272
8,500.00	8,388.58	8,411.32	8,388.58	17.95	13.82	-90.39	252.23	236.58	711.02	681.57	24.147
8,600.00	8,488.58	8,511.32	8,488.58	18.02	13.91	-90.39	252.23	236.58	711.02	681.42	24.023
8,700.00	8,588.58	8,611.32	8,588.58	18.08	14.00	-90.39	252.23	236.58	711.02	681.27	23.899
8,800.00	8,688.58	8,711.32	8,688.58	18.14	14.09	-90.39	252.23	236.58	711.02	681.11	23.778
8,900.00	8,788.58	8,811.32	8,788.58	18.20	14.18	-90.39	252.23	236.58	711.02	680.96	23.657
9,000.00	8,888.58	8,911.32	8,888.58	18.26	14.27	-90.39	252.23	236.58	711.02	680.81	23.537
9,100.00	8,988.58	9,011.32	8,988.58	18.32	14.36	-90.39	252.23	236.58	711.02	680.66	23.419
9,200.00	9,088.58	9,111.32	9,088.58	18.39	14.45	-90.39	252.23	236.58	711.02	680.50	23.302
9,300.00	9,188.58	9,211.32	9,188.58	18.45	14.54	-90.39	252.23	236.58	711.02	680.35	23.186
9,400.00	9,288.58	9,311.32	9,288.58	18.51	14.63	-90.39	252.23	236.58	711.02	680.20	23.070
9,500.00	9,388.58	9,411.32	9,388.58	18.57	14.72	-90.39	252.23	236.58	711.02	680.04	22.957
9,600.00	9,488.58	9,511.32	9,488.58	18.64	14.81	-90.39	252.23	236.58	711.02	679.89	22.844
9,700.00	9,588.58	9,611.32	9,588.58	18.70	14.90	-90.39	252.23	236.58	711.02	679.74	22.732
9,800.00	9,688.58	9,711.32	9,688.58	18.76	14.98	-90.39	252.23	236.58	711.02	679.58	22.621
9,900.00	9,788.58	9,811.32	9,788.58	18.83	15.07	-90.39	252.23	236.58	711.02	679.43	22.511
10,000.00	9,888.58	9,911.32	9,888.58	18.89	15.16	-90.39	252.23	236.58	711.02	679.28	22.403
10,100.00	9,988.58	10,011.32	9,988.58	18.95	15.25	-90.39	252.23	236.58	711.02	679.12	22.295
10,200.00	10,088.58	10,111.32	10,088.58	19.02	15.34	-90.39	252.23	236.58	711.02	678.97	22.188

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 63 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 212H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,300.00	10,188.58	10,211.32	10,188.58	19.08	15.43	-90.39	252.23	236.58	711.02	678.82	32.20	22.082		
10,400.00	10,288.58	10,311.32	10,288.58	19.15	15.52	-90.39	252.23	236.58	711.02	678.66	32.35	21.977		
10,500.00	10,388.58	10,411.32	10,388.58	19.21	15.60	-90.39	252.23	236.58	711.02	678.51	32.51	21.873		
10,600.00	10,488.58	10,511.32	10,488.58	19.27	15.69	-90.39	252.23	236.58	711.02	678.36	32.66	21.771		
10,700.00	10,588.58	10,611.32	10,588.58	19.34	15.78	-90.39	252.23	236.58	711.02	678.20	32.81	21.669		
10,800.00	10,688.58	10,711.32	10,688.58	19.40	15.87	-90.39	252.23	236.58	711.02	678.05	32.97	21.567		
10,900.00	10,788.58	10,811.32	10,788.58	19.47	15.96	-90.39	252.23	236.58	711.02	677.90	33.12	21.467		
11,000.00	10,888.58	10,911.32	10,888.58	19.53	16.05	-90.39	252.23	236.58	711.02	677.74	33.28	21.368		
11,100.00	10,988.58	11,011.32	10,988.58	19.60	16.13	-90.39	252.23	236.58	711.02	677.59	33.43	21.269		
11,200.00	11,088.58	11,111.32	11,088.58	19.66	16.22	-90.39	252.23	236.58	711.02	677.43	33.58	21.172		
11,300.00	11,188.58	11,211.32	11,188.58	19.73	16.31	-90.39	252.23	236.58	711.02	677.28	33.74	21.075		
11,400.00	11,288.58	11,311.32	11,288.58	19.79	16.40	-90.39	252.23	236.58	711.02	677.12	33.89	20.979		
11,500.00	11,388.58	11,411.32	11,388.58	19.86	16.49	-90.39	252.23	236.58	711.02	676.97	34.05	20.884		
11,600.00	11,488.58	11,511.32	11,488.58	19.92	16.57	-90.39	252.23	236.58	711.02	676.82	34.20	20.790		
11,700.00	11,588.58	11,611.32	11,588.58	19.99	16.66	-90.39	252.23	236.58	711.02	676.66	34.35	20.696		
11,800.00	11,688.58	11,711.32	11,688.58	20.05	16.75	-90.39	252.23	236.58	711.02	676.51	34.51	20.604		
11,900.00	11,788.58	11,811.32	11,788.58	20.12	16.84	-90.39	252.23	236.58	711.02	676.35	34.66	20.512		
12,000.00	11,888.58	11,911.32	11,888.58	20.19	16.92	-90.39	252.23	236.58	711.02	676.20	34.82	20.422		
12,100.00	11,988.51	12,011.44	11,988.65	20.25	16.97	90.15	250.49	236.60	711.02	676.16	34.86	20.398		
12,200.00	12,086.82	12,111.87	12,087.58	20.31	17.02	90.24	233.95	236.74	711.02	676.30	34.72	20.476		
12,300.00	12,180.57	12,212.49	12,182.28	20.35	17.07	90.33	200.33	237.03	711.03	676.52	34.51	20.602		
12,400.00	12,266.93	12,313.29	12,269.80	20.39	17.12	90.41	150.59	237.46	711.03	676.77	34.26	20.754		
12,500.00	12,343.26	12,414.25	12,347.38	20.44	17.17	90.47	86.18	238.01	711.04	677.01	34.03	20.895		
12,600.00	12,407.24	12,515.34	12,412.53	20.52	17.23	90.52	9.06	238.67	711.05	677.16	33.89	20.98		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 64 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 212H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)													Offset Site Error: 0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned:				Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
15,400.00	12,531.40	15,319.54	12,538.40	43.74	41.04	90.56	-2,773.32	262.63	711.06	627.98	83.08	8.559		
15,500.00	12,532.27	15,419.54	12,539.28	44.94	42.30	90.56	-2,873.31	263.49	711.06	625.46	85.59	8.308		
15,600.00	12,533.14	15,519.54	12,540.15	46.15	43.57	90.56	-2,973.31	264.35	711.06	622.94	88.11	8.070		
15,700.00	12,534.02	15,619.54	12,541.02	47.37	44.84	90.56	-3,073.30	265.21	711.06	620.40	90.65	7.844		
15,800.00	12,534.89	15,719.54	12,541.90	48.59	46.12	90.56	-3,173.29	266.08	711.06	617.86	93.20	7.629		
15,900.00	12,535.76	15,819.54	12,542.77	49.83	47.41	90.56	-3,273.28	266.94	711.06	615.30	95.76	7.426		
16,000.00	12,536.64	15,919.54	12,543.64	51.07	48.70	90.56	-3,373.28	267.80	711.06	612.73	98.33	7.232		
16,100.00	12,537.51	16,019.54	12,544.52	52.32	49.99	90.56	-3,473.27	268.66	711.06	610.15	100.90	7.047		
16,200.00	12,538.39	16,119.54	12,545.39	53.57	51.28	90.56	-3,573.26	269.52	711.06	607.57	103.49	6.871		
16,300.00	12,539.26	16,219.54	12,546.26	54.83	52.59	90.56	-3,673.25	270.38	711.06	604.97	106.08	6.703		
16,400.00	12,540.13	16,319.54	12,547.14	56.09	53.89	90.56	-3,773.25	271.24	711.06	602.37	108.68	6.543		
16,500.00	12,541.01	16,419.54	12,548.01	57.36	55.20	90.56	-3,873.24	272.10	711.06	599.77	111.29	6.389		
16,600.00	12,541.88	16,519.54	12,548.88	58.64	56.51	90.56	-3,973.23	272.96	711.06	597.15	113.90	6.243		
16,700.00	12,542.75	16,619.54	12,549.76	59.91	57.82	90.56	-4,073.22	273.82	711.06	594.53	116.52	6.102		
16,800.00	12,543.63	16,719.54	12,550.63	61.20	59.14	90.56	-4,173.22	274.68	711.06	591.91	119.15	5.968		
16,900.00	12,544.50	16,819.54	12,551.50	62.48	60.45	90.56	-4,273.21	275.55	711.06	589.28	121.78	5.839		
17,000.00	12,545.37	16,919.54	12,552.38	63.77	61.77	90.56	-4,373.20	276.41	711.06	586.65	124.41	5.715		
17,100.00	12,546.25	17,019.54	12,553.25	65.06	63.10	90.56	-4,473.19	277.27	711.06	584.01	127.05	5.597		
17,200.00	12,547.12	17,119.54	12,554.12	66.36	64.42	90.56	-4,573.19	278.13	711.06	581.37	129.69	5.483		
17,300.00	12,547.99	17,219.54	12,555.00	67.66	65.75	90.56	-4,673.18	278.99	711.06	578.72	132.34	5.373		
17,400.00	12,548.87	17,319.54	12,555.87	68.96	67.08	90.56	-4,773.17	279.85	711.06	576.07	134.99	5.267		
17,500.00	12,549.74	17,419.54	12,556.74	70.26	68.41	90.56	-4,873.16	280.71	711.06	573.41	137.64	5.166		
17,600.00	12,550.62	17,519.54	12,557.62	71.57	69.74	90.56	-4,973.16	281.57	711.06	570.76	140.30	5.068		
17,700.00	12,551.49	17,619.54	12,558.49	72.88	71.07	90.56	-5,073.15	282.43	711.06	568.10	142.96	4.974		
17,800.00	12,552.36	17,719.54	12,559.36	74.19	72.40	90.56	-5,173.14	283.29	711.06	565.43	145.63	4.883		
17,900.00	12,553.24	17,819.54	12,560.24	75.50	73.74	90.56	-5,273.13	284.16	711.06	562.77	148.29	4.795		
18,000.00	12,554.11	17,919.54	12,561.11	76.81	75.08	90.56	-5,373.13	285.02	711.06	560.10	150.96	4.710		
18,100.00	12,554.98	18,019.54	12,561.98	78.13	76.41	90.56	-5,473.12	285.88	711.06	557.43	153.63	4.628		
18,200.00	12,555.86	18,119.54	12,562.86	79.45	77.75	90.56	-5,573.11	286.74	711.06	554.75	156.31	4.549		
18,300.00	12,556.73	18,219.54	12,563.73	80.77	79.09	90.56	-5,673.10	287.60	711.06	552.08	158.98	4.473		
18,400.00	12,557.60	18,319.54	12,564.60	82.09	80.43	90.56	-5,773.10	288.46	711.06	549.40	161.66	4.398		
18,500.00	12,558.48	18,419.54	12,565.48	83.42	81.78	90.56	-5,873.09	289.32	711.06	546.72	164.34	4.327		
18,600.00	12,559.35	18,519.54	12,566.35	84.74	83.12	90.56	-5,973.08	290.18	711.06	544.04	167.02	4.257		
18,700.00	12,560.23	18,619.54	12,567.22	86.07	84.46	90.56	-6,073.07	291.04	711.06	541.36	169.71	4.190		
18,800.00	12,561.10	18,719.54	12,568.10	87.40	85.81	90.56	-6,173.07	291.90	711.06	538.67	172.39	4.125		
18,900.00	12,561.97	18,819.54	12,568.97	88.72	87.15	90.56	-6,273.06	292.77	711.06	535.98	175.08	4.061		
19,000.00	12,562.85	18,919.54	12,569.85	90.05	88.50	90.56	-6,373.05	293.63	711.06	533.29	177.77	4.000		
19,100.00	12,563.72	19,019.54	12,570.72	91.39	89.85	90.56	-6,473.04	294.49	711.06	530.60	180.46	3.940		
19,200.00	12,564.59	19,119.54	12,571.59	92.72	91.19	90.56	-6,573.04	295.35	711.06	527.91	183.15	3.882		
19,300.00	12,565.47	19,219.54	12,572.47	94.05	92.54	90.56	-6,673.03	296.21	711.06	525.22	185.84	3.826		
19,400.00	12,566.34	19,319.54	12,573.34	95.39	93.89	90.56	-6,773.02	297.07	711.06	522.52	188.54	3.771		
19,500.00	12,567.21	19,419.54	12,574.21	96.72	95.24	90.56	-6,873.01	297.93	711.06	519.83	191.23	3.718		
19,600.00	12,568.09	19,519.54	12,575.09	98.06	96.59	90.56	-6,973.01	298.79	711.06	517.13	193.93	3.667		
19,700.00	12,568.96	19,619.54	12,575.96	99.40	97.94	90.56	-7,073.00	299.65	711.06	514.43	196.63	3.616		
19,800.00	12,569.83	19,719.54	12,576.83	100.73	99.29	90.56	-7,172.99	300.51	711.06	511.74	199.33	3.567		
19,900.00	12,570.71	19,819.54	12,577.71	102.07	100.64	90.56	-7,272.98	301.38	711.06	509.03	202.03	3.520		
20,000.00	12,571.58	19,919.54	12,578.58	103.41	101.99	90.56	-7,372.98	302.24	711.06	506.33	204.73	3.473		
20,100.00	12,572.46	20,019.54	12,579.45	104.75	103.35	90.56	-7,472.97	303.10	711.06	503.63	207.43	3.428		
20,200.00	12,573.33	20,119.54	12,580.33	106.10	104.70	90.56	-7,572.96	303.96	711.06	500.93	210.14	3.384		
20,300.00	12,574.20	20,219.54	12,581.20	107.44	106.05	90.56	-7,672.95	304.82	711.06	498.22	212.84	3.341		
20,400.00	12,575.08	20,319.54	12,582.07	108.78	107.41	90.56	-7,772.95	305.68	711.06	495.52	215.55	3.299		
20,500.00	12,575.95	20,419.54	12,582.95	110.12	108.76	90.56	-7,872.94	306.54	711.06	492.81	218.25	3.258		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 65 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 212H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:			
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,600.00	12,576.82	20,519.54	12,583.82	111.47	110.12	90.56	-7,972.93	307.40	711.06	490.11	220.96	3.218			
20,700.00	12,577.70	20,619.54	12,584.69	112.81	111.47	90.56	-8,072.92	308.26	711.06	487.40	223.67	3.179			
20,800.00	12,578.57	20,719.54	12,585.57	114.16	112.83	90.56	-8,172.92	309.12	711.06	484.69	226.37	3.141			
20,900.00	12,579.44	20,819.54	12,586.44	115.51	114.18	90.56	-8,272.91	309.99	711.06	481.98	229.08	3.104			
21,000.00	12,580.32	20,919.54	12,587.31	116.85	115.54	90.56	-8,372.90	310.85	711.07	479.27	231.79	3.068			
21,100.00	12,581.19	21,019.54	12,588.19	118.20	116.90	90.56	-8,472.89	311.71	711.07	476.56	234.50	3.032			
21,200.00	12,582.06	21,119.54	12,589.06	119.55	118.25	90.56	-8,572.89	312.57	711.07	473.85	237.22	2.998			
21,300.00	12,582.94	21,219.54	12,589.93	120.89	119.61	90.56	-8,672.88	313.43	711.07	471.14	239.93	2.964			
21,400.00	12,583.81	21,319.54	12,590.81	122.24	120.97	90.56	-8,772.87	314.29	711.07	468.43	242.64	2.931			
21,500.00	12,584.69	21,419.54	12,591.68	123.59	122.32	90.56	-8,872.86	315.15	711.07	465.71	245.35	2.898			
21,600.00	12,585.56	21,519.54	12,592.55	124.94	123.68	90.56	-8,972.86	316.01	711.07	463.00	248.07	2.866			
21,700.00	12,586.43	21,619.54	12,593.43	126.29	125.04	90.56	-9,072.85	316.87	711.07	460.29	250.78	2.835			
21,800.00	12,587.31	21,719.54	12,594.30	127.64	126.40	90.56	-9,172.84	317.73	711.07	457.57	253.50	2.805			
21,900.00	12,588.18	21,819.54	12,595.17	128.99	127.76	90.56	-9,272.83	318.59	711.07	454.86	256.21	2.775			
22,000.00	12,589.05	21,919.54	12,596.05	130.34	129.12	90.56	-9,372.83	319.46	711.07	452.14	258.93	2.746			
22,100.00	12,589.93	22,019.54	12,596.92	131.70	130.47	90.56	-9,472.82	320.32	711.07	449.42	261.64	2.718			
22,200.00	12,590.80	22,119.54	12,597.79	133.05	131.83	90.56	-9,572.81	321.18	711.07	446.71	264.36	2.690			
22,300.00	12,591.67	22,219.54	12,598.67	134.40	133.19	90.56	-9,672.80	322.04	711.07	443.99	267.08	2.662			
22,400.00	12,592.55	22,319.54	12,599.54	135.75	134.55	90.56	-9,772.80	322.90	711.07	441.27	269.80	2.636			
22,500.00	12,593.42	22,419.54	12,600.41	137.11	135.91	90.56	-9,872.79	323.76	711.07	438.55	272.51	2.609			
22,600.00	12,594.30	22,519.54	12,601.29	138.46	137.27	90.56	-9,972.78	324.62	711.07	435.84	275.23	2.584			
22,700.00	12,595.17	22,619.54	12,602.16	139.81	138.63	90.56	-10,072.77	325.48	711.07	433.12	277.95	2.558			
22,800.00	12,596.04	22,719.54	12,603.03	141.17	139.99	90.56	-10,172.77	326.34	711.07	430.40	280.67	2.533			
22,875.30	12,596.70	22,794.84	12,603.69	142.19	141.02	90.56	-10,248.06	326.99	711.07	428.35	282.72	2.515	SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 66 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 213H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre				Distance		Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
0.00	0.00	1.00	0.00	0.50	0.50	70.48	831.00	2,344.00	2,486.95								
100.00	100.00	101.00	100.00	0.98	0.99	70.48	831.00	2,344.00	2,486.95	2,484.98	1.97	1,263.916					
200.00	200.00	201.00	200.00	1.56	1.57	70.48	831.00	2,344.00	2,486.95	2,483.82	3.13	795.466					
300.00	300.00	301.00	300.00	1.98	1.98	70.48	831.00	2,344.00	2,486.95	2,482.98	3.97	627.101					
400.00	400.00	401.00	400.00	2.33	2.33	70.48	831.00	2,344.00	2,486.95	2,482.28	4.66	533.465					
500.00	500.00	501.71	500.71	2.63	2.64	70.48	831.00	2,344.00	2,486.95	2,481.67	5.27	471.568					
600.00	600.00	672.33	671.27	2.91	3.18	70.55	827.35	2,342.67	2,485.50	2,479.47	6.02	412.734					
700.00	700.00	838.59	837.15	3.16	3.57	70.75	816.91	2,338.87	2,481.22	2,474.61	6.61	375.116					
800.00	800.00	938.21	936.39	3.40	3.73	70.90	808.75	2,335.90	2,475.71	2,468.70	7.01	353.123					
900.00	900.00	1,037.83	1,035.63	3.62	3.94	71.06	800.59	2,332.93	2,470.21	2,462.76	7.44	331.843					
1,000.00	1,000.00	1,137.45	1,134.87	3.76	4.15	-20.79	792.43	2,329.96	2,464.68	2,456.89	7.79	316.560					
1,100.00	1,099.98	1,237.00	1,234.04	4.00	4.32	-20.69	784.28	2,327.00	2,457.50	2,449.32	8.19	300.175					
1,200.00	1,199.88	1,486.65	1,482.21	4.24	4.80	-20.44	761.62	2,312.72	2,445.31	2,436.45	8.86	275.983					
1,300.00	1,299.63	1,755.71	1,747.54	4.46	5.40	-20.28	731.68	2,280.09	2,423.75	2,414.10	9.65	251.143					
1,400.00	1,399.25	2,014.10	1,999.08	4.60	5.97	-20.05	697.65	2,232.03	2,394.05	2,383.74	10.31	232.226					
1,500.00	1,498.87	2,107.02	2,088.83	4.78	6.15	-19.96	684.52	2,211.88	2,361.20	2,350.53	10.67	221.324					
1,600.00	1,598.49	2,201.40	2,179.99	4.96	6.37	-19.86	671.18	2,191.42	2,328.36	2,317.31	11.05	210.727					
1,700.00	1,698.11	2,295.77	2,271.16	5.14	6.62	-19.76	657.84	2,170.95	2,295.52	2,284.09	11.43	200.797					
1,800.00	1,797.73	2,390.15	2,362.32	5.32	6.90	-19.66	644.51	2,150.48	2,262.68	2,250.87	11.81	191.516					
1,900.00	1,897.34	2,484.53	2,453.48	5.49	7.18	-19.56	631.17	2,130.02	2,229.86	2,217.66	12.20	182.781					
2,000.00	1,996.96	2,578.91	2,544.64	5.67	7.47	-19.45	617.83	2,109.55	2,197.04	2,184.45	12.59	174.558					
2,100.00	2,096.58	2,673.29	2,635.81	5.85	7.76	-19.34	604.49	2,089.08	2,164.23	2,151.25	12.97	166.808					
2,200.00	2,196.20	2,767.67	2,726.97	6.04	8.06	-19.22	591.16	2,068.62	2,131.42	2,118.05	13.37	159.414					
2,300.00	2,295.72	2,861.64	2,817.74														

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 67 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 213H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre				Distance		Offset Well Error:		0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
5,200.00	5,106.49	5,279.52	5,165.41	14.10	15.99	13.56	268.65	1,573.71	802.32	776.27	26.05	30.797			
5,300.00	5,203.08	5,359.56	5,245.24	14.43	16.10	14.15	265.46	1,568.82	770.98	744.52	26.47	29.128			
5,400.00	5,299.67	5,440.72	5,326.29	14.75	16.20	14.72	263.16	1,565.29	741.51	714.65	26.86	27.603			
5,500.00	5,396.65	5,523.29	5,408.82	15.07	16.28	15.14	261.78	1,563.18	715.32	688.07	27.25	26.251			
5,600.00	5,494.23	5,608.70	5,494.23	15.36	16.34	15.50	261.38	1,562.56	693.47	665.89	27.58	25.147			
5,700.00	5,592.35	5,706.82	5,592.35	15.62	16.38	15.85	261.38	1,562.56	674.87	647.01	27.86	24.222			
5,800.00	5,690.94	5,805.41	5,690.94	15.86	16.41	16.18	261.38	1,562.56	658.79	630.65	28.14	23.412			
5,900.00	5,789.93	5,904.41	5,789.93	16.07	16.45	16.47	261.38	1,562.56	645.22	616.82	28.41	22.714			
6,000.00	5,889.26	6,003.74	5,889.26	16.25	16.49	16.72	261.38	1,562.56	634.17	605.50	28.66	22.125			
6,100.00	5,988.86	6,103.34	5,988.86	16.41	16.52	16.92	261.38	1,562.56	625.62	596.71	28.91	21.644			
6,200.00	6,088.66	6,203.13	6,088.66	16.53	16.56	17.06	261.38	1,562.56	619.58	590.45	29.13	21.268			
6,300.00	6,188.59	6,303.06	6,188.59	16.64	16.60	17.15	261.38	1,562.56	616.04	586.70	29.34	20.997			
6,400.00	6,288.58	6,403.05	6,288.58	16.71	16.64	89.60	261.38	1,562.56	615.00	585.53	29.47	20.871			
6,500.00	6,388.58	6,503.05	6,388.58	16.76	16.68	89.60	261.38	1,562.56	615.00	585.43	29.56	20.802			
6,600.00	6,488.58	6,603.05	6,488.58	16.82	16.71	89.60	261.38	1,562.56	615.00	585.33	29.66	20.733			
6,700.00	6,588.58	6,703.05	6,588.58	16.88	16.75	89.60	261.38	1,562.56	615.00	585.23	29.76	20.665			
6,800.00	6,688.58	6,803.05	6,688.58	16.94	16.79	89.60	261.38	1,562.56	615.00	585.13	29.86	20.596			
6,900.00	6,788.58	6,903.05	6,788.58	17.00	16.83	89.60	261.38	1,562.56	615.00	585.04	29.96	20.527			
7,000.00	6,888.58	7,003.05	6,888.58	17.05	16.87	89.60	261.38	1,562.56	615.00	584.93	30.06	20.459			
7,100.00	6,988.58	7,103.05	6,988.58	17.11	16.91	89.60	261.38	1,562.56	615.00	584.83	30.16	20.390			
7,200.00	7,088.58	7,203.05	7,088.58	17.17	16.95	89.60	261.38	1,562.56	615.00	584.73	30.26	20.322			
7,300.00	7,188.58	7,303.05	7,188.58	17.23	17.00	89.60	261.38	1,562.56	615.00	584.63	30.36	20.254			
7,400.00	7,288.58	7,403.05	7,288.58	17.29	17.04	89.60	261.38	1,562.56	615.00	584.53	30.47	20.186			
7,500.00	7,388.58	7,503.05	7,388.58	17.35	17.08	89.60	261.38	1,562.56	615.00	584.42	30.57	20.117			
7,600.00	7,488.58	7,603.05	7,488.58	17.41	17.12	89.60	261.38	1,562.56	615.00	584.32	30.67	20.050			
7,700.00	7,588.58	7,703.05	7,588.58	17.47	17.16	89.60	261.38	1,562.56	615.00	584.22	30.78	19.982			
7,800.00	7,688.58	7,803.05	7,688.58	17.53	17.21	89.60	261.38	1,562.56	615.00	584.11	30.88	19.914			
7,900.00	7,788.58	7,903.05	7,788.58	17.59	17.25	89.60	261.38	1,562.56	615.00	584.01	30.99	19.847			
8,000.00	7,888.58	8,003.05	7,888.58	17.65	17.29	89.60	261.38	1,562.56	615.00	583.90	31.09	19.779			
8,100.00	7,988.58	8,103.05	7,988.58	17.71	17.34	89.60	261.38	1,562.56	615.00	583.80	31.20	19.712			
8,200.00	8,088.58	8,203.05	8,088.58	17.77	17.38	89.60	261.38	1,562.56	615.00	583.69	31.31	19.645			
8,300.00	8,188.58	8,303.05	8,188.58	17.83	17.42	89.60	261.38	1,562.56	615.00	583.58	31.41	19.578			
8,400.00	8,288.58	8,403.05	8,288.58	17.89	17.47	89.60	261.38	1,562.56	615.00	583.48	31.52	19.512			
8,500.00	8,388.58	8,503.05	8,388.58	17.95	17.51	89.60	261.38	1,562.56	615.00	583.37	31.63	19.445			
8,600.00	8,488.58	8,603.05	8,488.58	18.02	17.56	89.60	261.38	1,562.56	615.00	583.26	31.74	19.379			
8,700.00	8,588.58	8,703.05	8,588.58	18.08	17.60	89.60	261.38	1,562.56	615.00	583.15	31.84	19.312			
8,800.00	8,688.58	8,803.05	8,688.58	18.14	17.65	89.60	261.38	1,562.56	615.00	583.04	31.95	19.246			
8,900.00	8,788.58	8,903.05	8,788.58	18.20	17.69	89.60	261.38	1,562.56	615.00	582.93	32.06	19.180			
9,000.00	8,888.58	9,003.05	8,888.58	18.26	17.74	89.60	261.38	1,562.56	615.00	582.82	32.17	19.115			
9,100.00	8,988.58	9,103.05	8,988.58	18.32	17.79	89.60	261.38	1,562.56	615.00	582.71	32.28	19.049			
9,200.00	9,088.58	9,203.05	9,088.58	18.39	17.83	89.60	261.38	1,562.56	615.00	582.60	32.40	18.984			
9,300.00	9,188.58	9,303.05	9,188.58	18.45	17.88	89.60	261.38	1,562.56	615.00	582.49	32.51	18.919			
9,400.00	9,288.58	9,403.05	9,288.58	18.51	17.93	89.60	261.38	1,562.56	615.00	582.38	32.62	18.854			
9,500.00	9,388.58	9,503.05	9,388.58	18.57	17.97	89.60	261.38	1,562.56	615.00	582.26	32.73	18.789			
9,600.00	9,488.58	9,603.05	9,488.58	18.64	18.02	89.60	261.38	1,562.56	615.00	582.15	32.84	18.725			
9,700.00	9,588.58	9,703.05	9,588.58	18.70	18.07	89.60	261.38	1,562.56	615.00	582.04	32.96	18.660			
9,800.00	9,688.58	9,803.05	9,688.58	18.76	18.12	89.60	261.38	1,562.56	615.00	581.92	33.07	18.596			
9,900.00	9,788.58	9,903.05	9,788.58	18.83	18.16	89.60	261.38	1,562.56	615.00	581.81	33.18	18.532			
10,000.00	9,888.58	10,003.05	9,888.58	18.89	18.21	89.60	261.38	1,562.56	615.00	581.70	33.30	18.469			
10,100.00	9,988.58	10,103.05	9,988.58	18.95	18.26	89.60	261.38	1,562.56	615.00	581.58	33.41	18.405			
10,200.00	10,088.58	10,203.05	10,088.58	19.02	18.31	89.60	261.38	1,562.56	615.00	581.47	33.53	18.342			
10,300.00	10,188.58	10,303.05	10,188.58	19.08	18.36	89.60	261.38	1,562.56	615.00	581.35	33.64	18.279			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 68 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 213H - OH - Plan 1													Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance			Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,400.00	10,288.58	10,403.05	10,288.58	19.15	18.41	89.60	261.38	1,562.56	615.00	581.23	33.76	18.216		
10,500.00	10,388.58	10,503.05	10,388.58	19.21	18.46	89.60	261.38	1,562.56	615.00	581.12	33.88	18.154		
10,600.00	10,488.58	10,603.05	10,488.58	19.27	18.51	89.60	261.38	1,562.56	615.00	581.00	33.99	18.091		
10,700.00	10,588.58	10,703.05	10,588.58	19.34	18.56	89.60	261.38	1,562.56	615.00	580.88	34.11	18.029		
10,800.00	10,688.58	10,803.05	10,688.58	19.40	18.61	89.60	261.38	1,562.56	615.00	580.77	34.23	17.967		
10,900.00	10,788.58	10,903.05	10,788.58	19.47	18.66	89.60	261.38	1,562.56	615.00	580.65	34.35	17.906		
11,000.00	10,888.58	11,003.05	10,888.58	19.53	18.71	89.60	261.38	1,562.56	615.00	580.53	34.46	17.844		
11,100.00	10,988.58	11,103.05	10,988.58	19.60	18.76	89.60	261.38	1,562.56	615.00	580.41	34.58	17.783		
11,200.00	11,088.58	11,203.05	11,088.58	19.66	18.81	89.60	261.38	1,562.56	615.00	580.29	34.70	17.722		
11,300.00	11,188.58	11,303.05	11,188.58	19.73	18.86	89.60	261.38	1,562.56	615.00	580.17	34.82	17.661		
11,400.00	11,288.58	11,403.05	11,288.58	19.79	18.92	89.60	261.38	1,562.56	615.00	580.05	34.94	17.601		
11,500.00	11,388.58	11,503.05	11,388.58	19.86	18.97	89.60	261.38	1,562.56	615.00	579.93	35.06	17.541		
11,600.00	11,488.58	11,603.05	11,488.58	19.92	19.02	89.60	261.38	1,562.56	615.00	579.81	35.18	17.481		
11,700.00	11,588.58	11,703.05	11,588.58	19.99	19.07	89.60	261.38	1,562.56	615.00	579.69	35.30	17.421		
11,800.00	11,688.58	11,803.05	11,688.58	20.05	19.13	89.60	261.38	1,562.56	615.00	579.57	35.42	17.362		
11,900.00	11,788.58	11,903.05	11,788.58	20.12	19.18	89.60	261.38	1,562.56	615.00	579.45	35.54	17.302		
11,914.36	11,802.94	11,917.41	11,802.94	20.13	19.19	89.60	261.38	1,562.56	615.00	579.43	35.56	17.294	CC	
12,000.00	11,888.58	12,003.04	11,888.56	20.19	19.23	89.60	261.34	1,562.56	615.00	579.33	35.66	17.245		
12,100.00	11,988.51	12,101.98	11,986.91	20.25	19.36	-89.21	251.69	1,562.65	615.06	579.29	35.76	17.198		
12,200.00	12,086.82	12,200.00	12,081.27	20.31	19.57	-88.35	225.61	1,562.88	615.26	579.36	35.90	17.138		
12,300.00	12,180.57	12,295.19	12,167.37	20.35	19.84	-87.56	185.26	1,563.24	615.59	579.50	36.09	17.057		
12,400.00	12,266.93	12,389.85	12,245.19	20.39	20.18	-86.84	131.56	1,563.73	615.99	579.63	36.36	16.940		
12,500.00	12,343.26	12,483.46	12,312.43	20.44	20.59	-86.21	66.59	1,564.31	616.43	579.68	36.74	16.		

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 213H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5) Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,500.00	12,532.27	15,447.11	12,468.39	44.94	53.28	-84.08	-2,862.05	1,590.65	619.49	523.87	95.62	6.479	
15,600.00	12,533.14	15,547.10	12,468.91	46.15	54.57	-84.05	-2,962.04	1,591.55	619.57	521.40	98.16	6.312	
15,700.00	12,534.02	15,647.10	12,469.44	47.37	55.86	-84.02	-3,062.04	1,592.45	619.64	518.93	100.71	6.153	
15,800.00	12,534.89	15,747.10	12,469.97	48.59	57.16	-83.99	-3,162.03	1,593.35	619.71	516.44	103.27	6.001	
15,900.00	12,535.76	15,847.10	12,470.49	49.83	58.46	-83.95	-3,262.02	1,594.25	619.79	513.95	105.84	5.856	
16,000.00	12,536.64	15,947.10	12,471.02	51.07	59.77	-83.92	-3,362.02	1,595.15	619.86	511.45	108.42	5.718	
16,100.00	12,537.51	16,047.10	12,471.54	52.32	61.07	-83.89	-3,462.01	1,596.05	619.94	508.94	111.00	5.585	
16,200.00	12,538.39	16,147.10	12,472.07	53.57	62.38	-83.86	-3,562.00	1,596.95	620.01	506.43	113.59	5.459	
16,300.00	12,539.26	16,247.10	12,472.60	54.83	63.69	-83.83	-3,662.00	1,597.85	620.09	503.91	116.18	5.337	
16,400.00	12,540.13	16,347.10	12,473.12	56.09	65.01	-83.80	-3,761.99	1,598.75	620.16	501.39	118.78	5.221	
16,500.00	12,541.01	16,447.10	12,473.65	57.36	66.32	-83.77	-3,861.99	1,599.65	620.24	498.86	121.38	5.110	
16,600.00	12,541.88	16,547.10	12,474.18	58.64	67.64	-83.73	-3,961.98	1,600.55	620.32	496.32	123.99	5.003	
16,700.00	12,542.75	16,647.10	12,474.70	59.91	68.96	-83.70	-4,061.97	1,601.45	620.39	493.79	126.61	4.900	
16,800.00	12,543.63	16,747.10	12,475.23	61.20	70.28	-83.67	-4,161.97	1,602.35	620.47	491.24	129.22	4.801	
16,900.00	12,544.50	16,847.10	12,475.75	62.48	71.61	-83.64	-4,261.96	1,603.25	620.54	488.70	131.85	4.707	
17,000.00	12,545.37	16,947.10	12,476.28	63.77	72.93	-83.61	-4,361.96	1,604.15	620.62	486.15	134.47	4.615	
17,100.00	12,546.25	17,047.10	12,476.81	65.06	74.26	-83.58	-4,461.95	1,605.05	620.70	483.60	137.10	4.527	
17,200.00	12,547.12	17,147.09	12,477.33	66.36	75.59	-83.55	-4,561.94	1,605.94	620.78	481.04	139.73	4.443	
17,300.00	12,547.99	17,247.09	12,477.86	67.66	76.92	-83.51	-4,661.94	1,606.84	620.85	478.49	142.37	4.361	
17,400.00	12,548.87	17,347.09	12,478.38	68.96	78.25	-83.48	-4,761.93	1,607.74	620.93	475.92	145.00	4.282	
17,500.00	12,549.74	17,447.09	12,478.91	70.26	79.58	-83.45	-4,861.93	1,608.64	621.01	473.36	147.65	4.206	
17,600.00	12,550.62	17,547.09	12,479.44	71.57	80.92	-83.42	-4,961.92	1,609.54	621.09	470.80	150.29	4.133	
17,700.00	12,551.49	17,647.09	12,479.96	72.88	82.25	-83.39	-5,061.91	1,610.44	621.16	468.23	152.93	4.062	
17,800.00	12,552.36	17,747.09	12,480.49	74.19	83.59	-83.36	-5,161.91	1					

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 70 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 213H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:		Warning	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,700.00	12,577.70	20,647.07	12,495.75	112.81	122.64	-82.45	-8,061.73	1,637.42	623.59	390.71	232.88	2.678			
20,800.00	12,578.57	20,747.07	12,496.27	114.16	124.00	-82.42	-8,161.73	1,638.32	623.67	388.12	235.56	2.648			
20,900.00	12,579.44	20,847.07	12,496.80	115.51	125.35	-82.39	-8,261.72	1,639.22	623.75	385.52	238.23	2.618			
21,000.00	12,580.32	20,947.07	12,497.33	116.85	126.71	-82.36	-8,361.72	1,640.12	623.84	382.93	240.91	2.590			
21,100.00	12,581.19	21,047.07	12,497.85	118.20	128.06	-82.32	-8,461.71	1,641.02	623.92	380.34	243.58	2.561			
21,200.00	12,582.06	21,147.07	12,498.38	119.55	129.42	-82.29	-8,561.70	1,641.92	624.01	377.75	246.26	2.534			
21,300.00	12,582.94	21,247.07	12,498.91	120.89	130.77	-82.26	-8,661.70	1,642.82	624.09	375.16	248.93	2.507			
21,400.00	12,583.81	21,347.07	12,499.43	122.24	132.13	-82.23	-8,761.69	1,643.72	624.18	372.57	251.61	2.481			
21,500.00	12,584.69	21,447.07	12,499.96	123.59	133.48	-82.20	-8,861.68	1,644.62	624.26	369.97	254.29	2.455			
21,600.00	12,585.56	21,547.07	12,500.48	124.94	134.84	-82.17	-8,961.68	1,645.52	624.35	367.38	256.96	2.430			
21,700.00	12,586.43	21,647.07	12,501.01	126.29	136.20	-82.14	-9,061.67	1,646.42	624.43	364.79	259.64	2.405			
21,800.00	12,587.31	21,747.07	12,501.54	127.64	137.55	-82.11	-9,161.67	1,647.32	624.52	362.20	262.32	2.381			
21,900.00	12,588.18	21,847.07	12,502.06	128.99	138.91	-82.08	-9,261.66	1,648.22	624.60	359.61	264.99	2.357			
22,000.00	12,589.05	21,947.07	12,502.59	130.34	140.27	-82.04	-9,361.65	1,649.12	624.69	357.02	267.67	2.334			
22,100.00	12,589.93	22,047.06	12,503.12	131.70	141.63	-82.01	-9,461.65	1,650.02	624.78	354.43	270.35	2.311			
22,200.00	12,590.80	22,147.06	12,503.64	133.05	142.98	-81.98	-9,561.64	1,650.92	624.86	351.84	273.02	2.289			
22,300.00	12,591.67	22,247.06	12,504.17	134.40	144.34	-81.95	-9,661.64	1,651.82	624.95	349.25	275.70	2.267			
22,400.00	12,592.55	22,347.06	12,504.69	135.75	145.70	-81.92	-9,761.63	1,652.72	625.03	346.66	278.38	2.245			
22,500.00	12,593.42	22,447.06	12,505.22	137.11	147.06	-81.89	-9,861.62	1,653.61	625.12	344.07	281.06	2.224			
22,600.00	12,594.30	22,547.06	12,505.75	138.46	148.42	-81.86	-9,961.62	1,654.51	625.21	341.48	283.73	2.204			
22,700.00	12,595.17	22,647.06	12,506.27	139.81	149.78	-81.83	-10,061.61	1,655.41	625.30	338.89	286.41	2.183			
22,800.00	12,596.04	22,747.06	12,506.80	141.17	151.14	-81.80	-10,161.61	1,656.31	625.38	336.30	289.09	2.163			
22,875.30	12,596.70	22,822.36	12,507.19	142.19	152.15	-81.77	-10,236.90	1,656.99	625.45	334.38	291.07	2.149	ES, SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 71 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 214H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Rule Assigned:		Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Major Axis Reference (usft)	Offset (usft)
Reference Depth (usft)	Offset Depth (usft)	Reference Depth (usft)	Offset Depth (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)
Distance Between Centres (usft)	Distance Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor		
0.00	0.00	0.00	1.00	0.50	0.50
100.00	100.00	99.00	100.00	0.98	0.97
200.00	200.00	199.00	200.00	1.56	1.56
300.00	300.00	299.00	300.00	1.98	1.98
400.00	400.00	365.27	366.27	2.33	2.26
500.00	500.00	431.17	432.14	2.63	2.52
600.00	600.00	500.00	500.91	2.91	2.77
700.00	700.00	595.28	596.06	3.16	3.03
800.00	800.00	695.14	695.78	3.40	3.28
900.00	900.00	795.00	795.51	3.62	3.52
1,000.00	1,000.00	894.87	895.24	3.76	3.75
1,100.00	1,099.98	994.80	995.03	4.00	3.97
1,200.00	1,199.88	1,094.79	1,094.88	4.24	4.19
1,300.00	1,299.63	1,194.75	1,194.71	4.46	4.40
1,400.00	1,399.25	1,294.67	1,294.49	4.60	4.61
1,500.00	1,498.87	1,394.58	1,394.27	4.78	4.81
1,600.00	1,598.49	1,494.50	1,494.05	4.96	5.02
1,700.00	1,698.11	1,573.71	1,573.11	5.14	5.19
1,800.00	1,797.73	1,651.36	1,650.51	5.32	5.37
1,900.00	1,897.34	1,728.92	1,727.70	5.49	5.54
2,000.00	1,996.96	1,800.00	1,798.28	5.67	5.71
2,047.15	2,043.93	1,842.78	1,840.70	5.76	5.79
2,100.00	2,096.58	1,883.75	1,881.24	5.85	5.87
2,200.00	2,196.20	1,983.07	1,979.47	6.04	6.05
2,300.00	2,295.72	2,082.61	2,077.91	6.23	6.25
2,400.00	2,394.97	2,182.04	2,176.25	6.43	6.44
2,500.00	2,493.89	2,281.30	2,274.43	6.64	6.64
2,600.00	2,592.40	2,380.32	2,372.36	6.85	6.84
2,700.00	2,690.45	2,479.04	2,469.99	7.07	7.03
2,800.00	2,787.96	2,577.39	2,567.26	7.28	7.23
2,900.00	2,884.87	2,675.29	2,664.08	7.49	7.43
3,000.00	2,981.46	2,772.95	2,760.68	7.68	7.62
3,100.00	3,078.05	2,870.62	2,857.27	7.87	7.82
3,200.00	3,174.64	2,968.29	2,953.87	8.06	8.01
3,300.00	3,271.24	3,065.95	3,050.46	8.26	8.21
3,400.00	3,367.83	3,163.62	3,147.05	8.51	8.40
3,500.00	3,464.42	3,261.29	3,243.65	8.80	8.60
3,600.00	3,561.01	3,358.95	3,340.24	9.09	8.80
3,700.00	3,657.60	3,456.62	3,436.83	9.38	8.99
3,800.00	3,754.20	3,554.29	3,533.43	9.68	9.19
3,900.00	3,850.79	3,651.95	3,630.02	9.98	9.39
4,000.00	3,947.38	3,749.62	3,726.61	10.28	9.59
4,100.00	4,043.97	3,847.29	3,823.21	10.59	9.78
4,200.00	4,140.56	3,944.95	3,919.80	10.90	9.98
4,300.00	4,237.16	4,042.62	4,016.40	11.21	10.18
4,400.00	4,333.75	4,140.29	4,112.99	11.52	10.38
4,500.00	4,430.34	4,237.95	4,209.58	11.84	10.58
4,600.00	4,526.93	4,335.62	4,306.18	12.16	10.78
4,700.00	4,623.53	4,433.29	4,402.77	12.48	10.98
4,800.00	4,720.12	4,530.95	4,499.36	12.80	11.18
4,900.00	4,816.71	4,628.62	4,595.96	13.12	11.38
5,000.00	4,913.30	4,726.29	4,692.55	13.45	11.59

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 72 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 214H - OH - Plan 1														Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis			Rule Assigned:		Offset Well Error: 0.50 usft				
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Distance Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
5,100.00	5,009.89	4,823.95	4,789.15	13.78	11.79	12.97	359.72	2,769.85	2,036.96	2,013.01	23.96	85.031			
5,200.00	5,106.49	4,921.62	4,885.74	14.10	11.99	13.42	350.73	2,781.14	2,022.41	1,998.02	24.39	82.927			
5,300.00	5,203.08	5,019.28	4,982.33	14.43	12.19	13.87	341.74	2,792.44	2,007.98	1,983.16	24.82	80.897			
5,400.00	5,299.67	5,116.95	5,078.93	14.75	12.40	14.32	332.76	2,803.74	1,993.69	1,968.45	25.25	78.970			
5,500.00	5,396.65	5,214.88	5,175.78	15.07	12.60	14.73	323.75	2,815.07	1,980.99	1,955.30	25.69	77.100			
5,600.00	5,494.23	5,313.19	5,273.01	15.36	12.81	15.13	314.70	2,826.44	1,970.93	1,944.79	26.14	75.408			
5,700.00	5,592.35	5,411.82	5,370.56	15.62	13.01	15.52	305.63	2,837.85	1,963.50	1,936.92	26.57	73.886			
5,800.00	5,690.94	5,513.98	5,471.59	15.86	13.23	15.92	296.23	2,849.66	1,958.69	1,931.67	27.02	72.501			
5,900.00	5,789.93	5,677.91	5,634.24	16.07	13.56	16.48	283.54	2,865.62	1,954.68	1,927.14	27.54	70.977			
6,000.00	5,889.26	5,842.60	5,798.36	16.25	13.85	16.87	275.17	2,876.14	1,949.93	1,921.94	28.00	69.642			
6,100.00	5,988.86	6,007.62	5,963.25	16.41	14.10	17.09	271.21	2,881.12	1,944.38	1,916.00	28.38	68.516			
6,200.00	6,088.66	6,133.03	6,088.66	16.53	14.15	17.14	270.87	2,881.55	1,938.60	1,910.02	28.58	67.831			
6,300.00	6,188.59	6,232.96	6,188.59	16.64	14.19	17.16	270.87	2,881.55	1,935.06	1,906.28	28.78	67.237			
6,400.00	6,288.58	6,332.95	6,288.58	16.71	14.23	89.59	270.87	2,881.55	1,934.02	1,905.12	28.90	66.912			
6,500.00	6,388.58	6,432.95	6,388.58	16.76	14.27	89.59	270.87	2,881.55	1,934.02	1,905.02	29.00	66.689			
6,600.00	6,488.58	6,532.95	6,488.58	16.82	14.30	89.59	270.87	2,881.55	1,934.02	1,904.92	29.10	66.466			
6,700.00	6,588.58	6,632.95	6,588.58	16.88	14.34	89.59	270.87	2,881.55	1,934.02	1,904.82	29.20	66.244			
6,800.00	6,688.58	6,732.95	6,688.58	16.94	14.38	89.59	270.87	2,881.55	1,934.02	1,904.73	29.29	66.022			
6,900.00	6,788.58	6,832.95	6,788.58	17.00	14.42	89.59	270.87	2,881.55	1,934.02	1,904.63	29.39	65.800			
7,000.00	6,888.58	6,932.95	6,888.58	17.05	14.46	89.59	270.87	2,881.55	1,934.02	1,904.53	29.49	65.578			
7,100.00	6,988.58	7,032.95	6,988.58	17.11	14.50	89.59	270.87	2,881.55	1,934.02	1,904.43	29.59	65.357			
7,200.00	7,088.58	7,132.95	7,088.58	17.17	14.54	89.59	270.87	2,881.55	1,934.02	1,904.33	29.69	65.136			
7,300.00	7,188.58	7,232.95	7,188.58	17.23	14.58	89.59	270.87	2,881.55	1,934.02	1,904.23	29.79	64.915			
7,400.00	7,288.58	7,332.95	7,288.58	17.29	14.62	89.59	270.87	2,881.55	1,934.02	1,904.12	29.89	64.694			
7,500.00	7,388.58	7,432.95	7,388.58	17.35	14.66	89.59	270.87	2,881.55	1,934.02	1,904.02	30.00	64.474			
7,600.00	7,488.58	7,532.95	7,488.58	17.41	14.71	89.59	270.87	2,881.55	1,934.02	1,903.92	30.10	64.254			
7,700.00	7,588.58	7,632.95	7,588.58	17.47	14.75	89.59	270.87	2,881.55	1,934.02	1,903.82	30.20	64.035			
7,800.00	7,688.58	7,732.95	7,688.58	17.53	14.79	89.59	270.87	2,881.55	1,934.02	1,903.71	30.31	63.816			
7,900.00	7,788.58	7,832.95	7,788.58	17.59	14.83	89.59	270.87	2,881.55	1,934.02	1,903.61	30.41	63.597			
8,000.00	7,888.58	7,932.95	7,888.58	17.65	14.88	89.59	270.87	2,881.55	1,934.02	1,903.50	30.52	63.379			
8,100.00	7,988.58	8,032.95	7,988.58	17.71	14.92	89.59	270.87	2,881.55	1,934.02	1,903.40	30.62	63.161			
8,200.00	8,088.58	8,132.95	8,088.58	17.77	14.96	89.59	270.87	2,881.55	1,934.02	1,903.29	30.73	62.944			
8,300.00	8,188.58	8,232.95	8,188.58	17.83	15.01	89.59	270.87	2,881.55	1,934.02	1,903.19	30.83	62.727			
8,400.00	8,288.58	8,332.95	8,288.58	17.89	15.05	89.59	270.87	2,881.55	1,934.02	1,903.08	30.94	62.511			
8,500.00	8,388.58	8,432.95	8,388.58	17.95	15.10	89.59	270.87	2,881.55	1,934.02	1,902.97	31.05	62.295			
8,600.00	8,488.58	8,532.95	8,488.58	18.02	15.14	89.59	270.87	2,881.55	1,934.02	1,902.87	31.15	62.080			
8,700.00	8,588.58	8,632.95	8,588.58	18.08	15.19	89.59	270.87	2,881.55	1,934.02	1,902.76	31.26	61.865			
8,800.00	8,688.58	8,732.95	8,688.58	18.14	15.23	89.59	270.87	2,881.55	1,934.02	1,902.65	31.37	61.651			
8,900.00	8,788.58	8,832.95	8,788.58	18.20	15.28	89.59	270.87	2,881.55	1,934.02	1,902.54	31.48	61.437			
9,000.00	8,888.58	8,932.95	8,888.58	18.26	15.33	89.59	270.87	2,881.55	1,934.02	1,902.43	31.59	61.224			
9,100.00	8,988.58	9,032.95	8,988.58	18.32	15.37	89.59	270.87	2,881.55	1,934.02	1,902.32	31.70	61.012			
9,200.00	9,088.58	9,132.95	9,088.58	18.39	15.42	89.59	270.87	2,881.55	1,934.02	1,902.21	31.81	60.800			
9,300.00	9,188.58	9,232.95	9,188.58	18.45	15.47	89.59	270.87	2,881.55	1,934.02	1,902.10	31.92	60.589			
9,400.00	9,288.58	9,332.95	9,288.58	18.51	15.51	89.59	270.87	2,881.55	1,934.02	1,901.99	32.03	60.378			
9,500.00	9,388.58	9,432.95	9,388.58	18.57	15.56	89.59	270.87	2,881.55	1,934.02	1,901.88	32.14	60.168			
9,600.00	9,488.58	9,532.95	9,488.58	18.64	15.61	89.59	270.87	2,881.55	1,934.02	1,901.76	32.26	59.959			
9,700.00	9,588.58	9,632.95	9,588.58	18.70	15.66	89.59	270.87	2,881.55	1,934.02	1,901.65	32.37	59.751			
9,800.00	9,688.58	9,732.95	9,688.58	18.76	15.70	89.59	270.87	2,881.55	1,934.02	1,901.54	32.48	59.543			
9,900.00	9,788.58	9,832.95	9,788.58	18.83	15.75	89.59	270.87	2,881.55	1,934.02	1,901.42	32.59	59.335			
10,000.00	9,888.58	9,932.95	9,888.58	18.89	15.80	89.59	270.87	2,881.55	1,934.02	1,901.31	32.71	59.129			
10,100.00	9,988.58	10,032.95	9,988.58	18.95	15.85	89.59	270.87	2,881.55	1,934.02	1,901.20	32.82	58.923			
10,200.00	10,088.58	10,132.95	10,088.58	19.02	15.90	89.59	270.87	2,881.55	1,934.02	1,901.08	32.94	58.718			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 73 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 214H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned: Distance		Offset Well Error:		0.50 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
10,300.00	10,188.58	10,232.95	10,188.58	19.08	15.95	89.59	270.87	2,881.55	1,934.02	1,900.97	33.05	58.513	
10,400.00	10,288.58	10,332.95	10,288.58	19.15	16.00	89.59	270.87	2,881.55	1,934.02	1,900.85	33.17	58.310	
10,500.00	10,388.58	10,432.95	10,388.58	19.21	16.05	89.59	270.87	2,881.55	1,934.02	1,900.74	33.28	58.106	
10,600.00	10,488.58	10,532.95	10,488.58	19.27	16.10	89.59	270.87	2,881.55	1,934.02	1,900.62	33.40	57.904	
10,700.00	10,588.58	10,632.95	10,588.58	19.34	16.15	89.59	270.87	2,881.55	1,934.02	1,900.50	33.52	57.703	
10,800.00	10,688.58	10,732.95	10,688.58	19.40	16.20	89.59	270.87	2,881.55	1,934.02	1,900.39	33.63	57.502	
10,900.00	10,788.58	10,832.95	10,788.58	19.47	16.26	89.59	270.87	2,881.55	1,934.02	1,900.27	33.75	57.302	
11,000.00	10,888.58	10,932.95	10,888.58	19.53	16.31	89.59	270.87	2,881.55	1,934.02	1,900.15	33.87	57.102	
11,100.00	10,988.58	11,032.95	10,988.58	19.60	16.36	89.59	270.87	2,881.55	1,934.02	1,900.03	33.99	56.904	
11,200.00	11,088.58	11,132.95	11,088.58	19.66	16.41	89.59	270.87	2,881.55	1,934.02	1,899.91	34.11	56.706	
11,300.00	11,188.58	11,232.95	11,188.58	19.73	16.46	89.59	270.87	2,881.55	1,934.02	1,899.79	34.23	56.509	
11,400.00	11,288.58	11,332.95	11,288.58	19.79	16.52	89.59	270.87	2,881.55	1,934.02	1,899.67	34.34	56.313	
11,500.00	11,388.58	11,432.95	11,388.58	19.86	16.57	89.59	270.87	2,881.55	1,934.02	1,899.56	34.46	56.117	
11,600.00	11,488.58	11,532.95	11,488.58	19.92	16.62	89.59	270.87	2,881.55	1,934.02	1,899.44	34.58	55.922	
11,700.00	11,588.58	11,632.95	11,588.58	19.99	16.68	89.59	270.87	2,881.55	1,934.02	1,899.31	34.70	55.728	
11,800.00	11,688.58	11,732.95	11,688.58	20.05	16.73	89.59	270.87	2,881.55	1,934.02	1,899.19	34.83	55.535	
11,900.00	11,788.58	11,832.95	11,788.58	20.12	16.78	89.59	270.87	2,881.55	1,934.02	1,899.08	34.94	55.349	
11,901.48	11,790.06	11,834.43	11,790.06	20.12	16.78	89.59	270.87	2,881.55	1,934.02	1,899.08	34.94	55.347	CC
12,000.00	11,888.58	11,932.45	11,888.00	20.19	16.82	89.66	268.41	2,881.57	1,934.03	1,898.98	35.05	55.186	
12,100.00	11,988.51	12,029.00	11,982.93	20.25	16.94	-89.40	251.44	2,881.73	1,934.14	1,899.00	35.14	55.044	
12,200.00	12,086.82	12,122.72	12,071.10	20.31	17.13	-88.91	219.96	2,882.01	1,934.40	1,899.17	35.23	54.904	
12,300.00	12,180.57	12,214.23	12,151.12	20.35	17.38	-88.46	175.77	2,882.41	1,934.78	1,899.42	35.36	54.714	
12,400.00	12,266.93	12,303.86	12,221.71	20.39	17.72	-88.05	120.69	2,882.91	1,935.23	1,899.67	35.55	54.433	
12,500.00	12,343.26	12,391.95	12,281.89	20.44	18.15	-87.70	56.48	2,883.50	1,935.70	1,899.85	35.84	54.003	
12,600.00	12,407.24	12,478.82	12,330.92	20.52	18.66	-87.41	-15.12	2,884.15	1,936.14	1,899.87	36.27	53.378	
12,700.00	12,456.94	12,564.77	12,368.24	20.67	19.25	-87.20	-92.46	2,884.85	1,936.52	1,899.66	36.87	52.530	
12,800.00	12,490.84	12,650.00	12,393.41	20.88	19.90	-87.05	-173.79	2,885.59	1,936.80	1,899.16	37.64	51.457	
12,900.00	12,507.91	12,735.07	12,406.25	21.18	20.62	-86.98	-257.81	2,886.35	1,936.95	1,898.35	38.60	50.181	
13,000.00	12,510.43	12,827.71	12,408.22	21.56	21.45	-86.98	-350.40	2,887.20	1,937.01	1,897.25	39.76	48.713	
13,100.00	12,511.30	12,927.71	12,408.74	22.01	22.40	-86.97	-450.40	2,888.10	1,937.08	1,895.95	41.13	47.096	
13,200.00	12,512.18	13,027.71	12,409.27	22.52	23.38	-86.96	-550.39	2,889.01	1,937.14	1,894.52	42.63	45.444	
13,300.00	12,513.05	13,127.71	12,409.79	23.10	24.40	-86.94	-650.38	2,889.92	1,937.21	1,892.97	44.24	43.787	
13,400.00	12,513.92	13,227.71	12,410.32	23.73	25.45	-86.93	-750.38	2,890.83	1,937.27	1,891.31	45.96	42.149	
13,500.00	12,514.80	13,327.71	12,410.84	24.41	26.52	-86.92	-850.37	2,891.74	1,937.34	1,889.56	47.78	40.548	
13,600.00	12,515.67	13,427.71	12,411.37	25.15	27.62	-86.91	-950.36	2,892.65	1,937.41	1,887.73	49.68	38.997	
13,700.00	12,516.55	13,527.71	12,411.89	25.93	28.74	-86.90	-1,050.36	2,893.56	1,937.47	1,885.81	51.66	37.505	
13,800.00	12,517.42	13,627.71	12,412.42	26.76	29.88	-86.89	-1,150.35	2,894.46	1,937.54	1,883.83	53.70	36.078	
13,900.00	12,518.29	13,727.71	12,412.94	27.63	31.04	-86.88	-1,250.35	2,895.37	1,937.61	1,881.79	55.81	34.717	
14,000.00	12,519.17	13,827.71	12,413.47	28.53	32.21	-86.87	-1,350.34	2,896.28	1,937.67	1,879.70	57.97	33.425	
14,100.00	12,520.04	13,927.71	12,413.99	29.47	33.40	-86.86	-1,450.33	2,897.19	1,937.74	1,877.56	60.18	32.199	
14,200.00	12,520.91	14,027.70	12,414.52	30.44	34.60	-86.85	-1,550.33	2,898.10	1,937.81	1,875.37	62.43	31.040	
14,300.00	12,521.79	14,127.70	12,415.04	31.44	35.81	-86.84	-1,650.32	2,899.01	1,937.87	1,873.15	64.72	29.943	
14,400.00	12,522.66	14,227.70	12,415.57	32.46	37.03	-86.83	-1,750.32	2,899.92	1,937.94	1,870.89	67.04	28.906	
14,500.00	12,523.53	14,327.70	12,416.09	33.51	38.26	-86.82	-1,850.31	2,900.83	1,938.01	1,868.61	69.40	27.926	
14,600.00	12,524.41	14,427.70	12,416.62	34.58	39.50	-86.81	-1,950.30	2,901.73	1,938.07	1,866.29	71.78	27.000	
14,700.00	12,525.28	14,527.70	12,417.14	35.67	40.75	-86.80	-2,050.30	2,902.64	1,938.14	1,863.95	74.19	26.125	
14,800.00	12,526.16	14,627.70	12,417.67	36.78	42.00	-86.79	-2,150.29	2,903.55	1,938.21	1,861.59	76.62	25.297	
14,900.00	12,527.03	14,727.70	12,418.19	37.90	43.26	-86.78	-2,250.28	2,904.46	1,938.27	1,859.20	79.07	24.514	
15,000.00	12,527.90	14,827.70	12,418.72	39.04	44.53	-86.77	-2,350.28	2,905.37	1,938.34	1,856.80	81.54	23.772	
15,100.00	12,528.78	14,927.70	12,419.24	40.20	45.81	-86.76	-2,450.27	2,906.28	1,938.41	1,854.38	84.02	23.070	
15,200.00	12,529.65	15,027.70	12,419.77	41.37	47.08	-86.75	-2,550.27	2,907.19	1,938.47	1,851.95	86.52	22.404	
15,300.00	12,530.52	15,127.70	12,420.29	42.55	48.37	-86.74	-2,650.26	2,908.09	1,938.54	1,849.50	89.04	21.772	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 74 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 214H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5)		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,400.00	12,531.40	15,227.70	12,420.82	43.74	49.65	-86.73	-2,750.25	2,909.00	1,938.61	1,847.04	91.57	21.171	
15,500.00	12,532.27	15,327.70	12,421.34	44.94	50.95	-86.72	-2,850.25	2,909.91	1,938.68	1,844.57	94.11	20.600	
15,600.00	12,533.14	15,427.70	12,421.87	46.15	52.24	-86.71	-2,950.24	2,910.82	1,938.74	1,842.08	96.66	20.057	
15,700.00	12,534.02	15,527.70	12,422.39	47.37	53.54	-86.70	-3,050.24	2,911.73	1,938.81	1,839.59	99.22	19.540	
15,800.00	12,534.89	15,627.69	12,422.92	48.59	54.84	-86.69	-3,150.23	2,912.64	1,938.88	1,837.09	101.79	19.048	
15,900.00	12,535.76	15,727.69	12,423.44	49.83	56.15	-86.68	-3,250.22	2,913.55	1,938.95	1,834.58	104.37	18.578	
16,000.00	12,536.64	15,827.69	12,423.97	51.07	57.46	-86.67	-3,350.22	2,914.46	1,939.01	1,832.06	106.96	18.129	
16,100.00	12,537.51	15,927.69	12,424.49	52.32	58.77	-86.66	-3,450.21	2,915.36	1,939.08	1,829.53	109.55	17.700	
16,200.00	12,538.39	16,027.69	12,425.02	53.57	60.08	-86.65	-3,550.21	2,916.27	1,939.15	1,827.00	112.15	17.291	
16,300.00	12,539.26	16,127.69	12,425.54	54.83	61.40	-86.64	-3,650.20	2,917.18	1,939.22	1,824.46	114.76	16.898	
16,400.00	12,540.13	16,227.69	12,426.07	56.09	62.72	-86.63	-3,750.19	2,918.09	1,939.28	1,821.91	117.37	16.523	
16,500.00	12,541.01	16,327.69	12,426.59	57.36	64.04	-86.62	-3,850.19	2,919.00	1,939.35	1,819.36	119.99	16.163	
16,600.00	12,541.88	16,427.69	12,427.12	58.64	65.36	-86.61	-3,950.18	2,919.91	1,939.42	1,816.81	122.61	15.817	
16,700.00	12,542.75	16,527.69	12,427.64	59.91	66.68	-86.60	-4,050.17	2,920.82	1,939.49	1,814.25	125.24	15.486	
16,800.00	12,543.63	16,627.69	12,428.17	61.20	68.01	-86.59	-4,150.17	2,921.72	1,939.56	1,811.68	127.87	15.168	
16,900.00	12,544.50	16,727.69	12,428.69	62.48	69.33	-86.58	-4,250.16	2,922.63	1,939.62	1,809.11	130.51	14.862	
17,000.00	12,545.37	16,827.69	12,429.22	63.77	70.66	-86.57	-4,350.16	2,923.54	1,939.69	1,806.54	133.15	14.568	
17,100.00	12,546.25	16,927.69	12,429.74	65.06	71.99	-86.56	-4,450.15	2,924.45	1,939.76	1,803.96	135.80	14.284	
17,200.00	12,547.12	17,027.69	12,430.27	66.36	73.33	-86.55	-4,550.14	2,925.36	1,939.83	1,801.38	138.44	14.012	
17,300.00	12,547.99	17,127.69	12,430.79	67.66	74.66	-86.54	-4,650.14	2,926.27	1,939.90	1,798.80	141.10	13.749	
17,400.00	12,548.87	17,227.68	12,431.32	68.96	75.99	-86.53	-4,750.13	2,927.18	1,939.97	1,796.22	143.75	13.495	
17,500.00	12,549.74	17,327.68	12,431.84	70.26	77.33	-86.52	-4,850.13	2,928.09	1,940.04	1,793.63	146.41	13.251	
17,600.00	12,550.62	17,427.68	12,432.37	71.57	78.67	-86.51	-4,950.12	2,928.99	1,940.10	1,791.03	149.07	13.015	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 75 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 214H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:					Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)				
20,600.00	12,576.82	20,427.66	12,448.11	111.47	119.11	-86.20	-7,949.94	2,956.25	1,942.19	1,712.52	229.67	8.456		
20,700.00	12,577.70	20,527.66	12,448.64	112.81	120.47	-86.19	-8,049.93	2,957.16	1,942.26	1,709.89	232.37	8.358		
20,800.00	12,578.57	20,627.66	12,449.16	114.16	121.82	-86.18	-8,149.92	2,958.07	1,942.33	1,707.26	235.07	8.263		
20,900.00	12,579.44	20,727.66	12,449.69	115.51	123.18	-86.17	-8,249.92	2,958.98	1,942.40	1,704.62	237.78	8.169		
21,000.00	12,580.32	20,827.66	12,450.21	116.85	124.53	-86.16	-8,349.91	2,959.89	1,942.47	1,701.99	240.48	8.077		
21,100.00	12,581.19	20,927.66	12,450.74	118.20	125.89	-86.15	-8,449.91	2,960.80	1,942.54	1,699.36	243.19	7.988		
21,200.00	12,582.06	21,027.66	12,451.26	119.55	127.25	-86.14	-8,549.90	2,961.71	1,942.61	1,696.72	245.89	7.900		
21,300.00	12,582.94	21,127.66	12,451.79	120.89	128.60	-86.13	-8,649.89	2,962.61	1,942.69	1,694.09	248.60	7.814		
21,400.00	12,583.81	21,227.66	12,452.31	122.24	129.96	-86.12	-8,749.89	2,963.52	1,942.76	1,691.45	251.31	7.731		
21,500.00	12,584.69	21,327.66	12,452.84	123.59	131.32	-86.11	-8,849.88	2,964.43	1,942.83	1,688.81	254.01	7.648		
21,600.00	12,585.56	21,427.66	12,453.36	124.94	132.68	-86.10	-8,949.87	2,965.34	1,942.90	1,686.18	256.72	7.568		
21,700.00	12,586.43	21,527.66	12,453.89	126.29	134.04	-86.09	-9,049.87	2,966.25	1,942.97	1,683.54	259.43	7.489		
21,800.00	12,587.31	21,627.66	12,454.41	127.64	135.39	-86.08	-9,149.86	2,967.16	1,943.04	1,680.90	262.14	7.412		
21,900.00	12,588.18	21,727.66	12,454.94	128.99	136.75	-86.07	-9,249.86	2,968.07	1,943.11	1,678.26	264.85	7.337		
22,000.00	12,589.05	21,827.66	12,455.46	130.34	138.11	-86.06	-9,349.85	2,968.97	1,943.18	1,675.63	267.56	7.263		
22,100.00	12,589.93	21,927.66	12,455.99	131.70	139.47	-86.05	-9,449.84	2,969.88	1,943.26	1,672.99	270.27	7.190		
22,200.00	12,590.80	22,027.66	12,456.51	133.05	140.83	-86.04	-9,549.84	2,970.79	1,943.33	1,670.35	272.98	7.119		
22,300.00	12,591.67	22,127.65	12,457.04	134.40	142.19	-86.03	-9,649.83	2,971.70	1,943.40	1,667.71	275.69	7.049		
22,400.00	12,592.55	22,227.65	12,457.56	135.75	143.55	-86.02	-9,749.83	2,972.61	1,943.47	1,665.07	278.40	6.981		
22,500.00	12,593.42	22,327.65	12,458.09	137.11	144.91	-86.01	-9,849.82	2,973.52	1,943.54	1,662.43	281.11	6.914		
22,600.00	12,594.30	22,427.65	12,458.61	138.46	146.27	-86.00	-9,949.81	2,974.43	1,943.61	1,659.79	283.82	6.848		
22,700.00	12,595.17	22,527.65	12,459.14	139.81	147.63	-85.99	-10,049.81	2,975.34	1,943.68	1,657.15	286.53	6.783		
22,800.00	12,596.04	22,627.65	12,459.66	141.17	148.99	-85.98	-10,149.80	2,976.24	1,943.76	1,654.51	289.25	6.720		
22,875.30	12,596.70	22,702.95	12,460.06	142.19	150.01	-85.97	-10,225.10	2,976.93	1,943.81	1,652.52	291.29	6.673	ES, SF	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 76 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 215H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
0.00	0.00	0.00	1.00	0.50	0.50	180.00	-185.00	0.00	185.00				
100.00	100.00	99.00	100.00	0.98	0.97	180.00	-185.00	0.00	185.00	183.05	1.95	94.633	
200.00	200.00	199.00	200.00	1.56	1.56	180.00	-185.00	0.00	185.00	181.88	3.12	59.366	
300.00	300.00	299.00	300.00	1.98	1.98	180.00	-185.00	0.00	185.00	181.04	3.96	46.740	
400.00	400.00	402.75	403.74	2.33	2.42	-179.72	-183.95	-0.90	183.99	179.28	4.72	39.012	
500.00	500.00	506.39	507.29	2.63	2.81	-178.85	-180.77	-3.63	180.96	175.58	5.37	33.684	
600.00	600.00	609.72	610.38	2.91	3.13	-177.33	-175.48	-8.18	175.98	170.04	5.94	29.630	
700.00	700.00	710.13	710.42	3.16	3.29	-175.32	-168.90	-13.84	169.79	163.45	6.34	26.787	
800.00	800.00	809.75	809.66	3.40	3.54	-173.15	-162.32	-19.50	163.77	156.95	6.82	24.019	
900.00	900.00	909.37	908.90	3.62	3.78	-170.82	-155.74	-25.16	158.01	150.73	7.27	21.723	
1,000.00	1,000.00	1,008.99	1,008.13	3.76	4.01	99.71	-149.15	-30.82	152.53	144.90	7.63	19.985	
1,100.00	1,099.98	1,108.48	1,107.25	4.00	4.24	103.14	-142.58	-36.48	147.76	139.73	8.04	18.387	
1,200.00	1,199.88	1,207.83	1,206.22	4.24	4.47	107.75	-136.01	-42.12	144.31	135.88	8.43	17.113	
1,300.00	1,299.63	1,308.27	1,306.13	4.46	4.73	114.06	-128.27	-48.78	142.27	133.45	8.82	16.130	
1,365.32	1,364.71	1,373.26	1,370.63	4.55	4.90	119.05	-122.21	-53.99	141.86	132.82	9.04	15.689	
1,400.00	1,399.25	1,407.56	1,404.61	4.60	4.98	121.92	-118.67	-57.04	142.08	132.93	9.15	15.526	
1,500.00	1,498.87	1,505.49	1,501.49	4.78	5.12	130.29	-107.77	-66.41	144.35	134.88	9.47	15.242	
1,600.00	1,598.49	1,603.14	1,598.06	4.96	5.33	138.27	-96.82	-75.82	149.69	139.82	9.88	15.157	
1,700.00	1,698.11	1,700.80	1,694.64	5.14	5.54	145.59	-85.88	-85.24	157.82	147.53	10.29	15.340	
1,800.00	1,797.73	1,798.45	1,791.22	5.32	5.75	152.12	-74.93	-94.65	168.33	157.63	10.70	15.728	
1,900.00	1,897.34	1,896.10	1,887.80	5.49	5.96	157.85	-63.98	-104.06	180.81	169.69	11.12	16.266	
2,000.00	1,996.96	1,993.75	1,984.37	5.67	6.17	162.81	-53.04	-113.48	194.88	183.35	11.53	16.909	
2,100.00	2,096.58	2,091.40	2,080.95	5.85	6.37	167.10	-42.09	-122.89	210.21	198.28	11.93	17.620	
2,200.00	2,196.20	2,189.05	2,177.53	6.04	6.58	170.79	-31.14	-132.30	226.57	214.23	12.34	18.363	
2,300.00	2,295.72	2,286.56	2,273.96	6.23	6.78	-179.74	-20.21	-141.70	244.83	232.08	12.75	19.204	
2,400.00	2,394.97	2,383.71	2,370.05	6.43	6.99	-172.96	-9.32	-151.07	266.01	252.84	13.17	20.201	
2,500.00	2,493.89	2,480.44	2,465.71	6.64	7.19	-168.07	1.52	-160.39	289.85	276.27	13.58	21.338	
2,600.00	2,592.40	2,576.68	2,560.90	6.85	7.39	-164.45	12.31	-169.67	316.15	302.16	13.99	22.591	
2,700.00	2,690.45	2,672.36	2,655.53	7.07	7.59	-161.74	23.04	-178.90	344.77	330.37	14.40	23.939	
2,800.00	2,787.96	2,767.43	2,749.55	7.28	7.79	-159.70	33.69	-188.06	375.61	360.81	14.81	25.367	
2,900.00	2,884.87	2,861.81	2,842.90	7.49	7.98	-158.18	44.27	-197.16	408.61	393.40	15.21	26.866	
3,000.00	2,981.46	2,955.84	2,935.89	7.68	8.18	-158.05	54.82	-206.22	442.63	427.05	15.59	28.394	
3,100.00	3,078.05	3,049.87	3,028.89	7.87	8.37	-157.94	65.36	-215.29	476.66	460.69	15.97	29.844	
3,200.00	3,174.64	3,143.90	3,121.88	8.06	8.56	-157.84	75.90	-224.35	510.69	494.34	16.36	31.222	
3,300.00	3,271.24	3,237.92	3,214.88	8.26	8.76	-157.75	86.44	-233.42	544.73	527.98	16.74	32.531	
3,400.00	3,367.83	3,331.95	3,307.87	8.51	8.95	-157.68	96.98	-242.48	578.76	561.62	17.14	33.776	
3,500.00	3,464.42	3,425.98	3,400.87	8.80	9.15	-157.61	107.52	-251.54	612.79	595.27	17.53	34.962	
3,600.00	3,561.01	3,520.01	3,493.86	9.09	9.34	-157.55	118.06	-260.61	646.83	628.91	17.92	36.091	
3,700.00	3,657.60	3,614.04	3,586.86	9.38	9.53	-157.49	128.60	-269.67	680.86	662.55	18.32	37.168	
3,800.00	3,754.20	3,708.06	3,679.85	9.68	9.73	-157.44	139.14	-278.74	714.90	696.18	18.72	38.196	
3,900.00	3,850.79	3,802.09	3,772.84	9.98	9.92	-157.40	149.68	-287.80	748.94	729.82	19.12	39.178	
4,000.00	3,947.38	3,896.12	3,865.84	10.28	10.11	-157.36	160.22	-296.87	782.97	763.45	19.52	40.116	
4,100.00	4,043.97	3,990.15	3,958.83	10.59	10.31	-157.32	170.76	-305.93	817.01	797.09	19.92	41.013	
4,200.00	4,140.56	4,084.18	4,051.83	10.90	10.50	-157.29	181.30	-315.00	851.05	830.72	20.33	41.871	
4,300.00	4,237.16	4,178.20	4,144.82	11.21	10.69	-157.25	191.84	-324.06	885.08	864.35	20.73	42.694	
4,400.00	4,333.75	4,272.23	4,237.82	11.52	10.88	-157.22	202.38	-333.12	919.12	897.98	21.14	43.482	
4,500.00	4,430.34	4,366.26	4,330.81	11.84	11.08	-157.20	212.92	-342.19	953.16	931.61	21.54	44.243	
4,600.00	4,526.93	4,474.63	4,438.11	12.16	11.30	-157.20	224.47	-352.11	986.73	964.72	22.01	44.836	
4,700.00	4,623.53	4,591.03	4,553.76	12.48	11.54	-157.35	234.38	-360.64	1,018.38	995.89	22.49	45.286	
4,800.00	4,720.12	4,708.90	4,671.23	12.80	11.78	-157.63	241.69	-366.93	1,047.99	1,025.04	22.94	45.675	
4,900.00	4,816.71	4,828.04	4,790.21	13.12	11.99	-158.04	246.29	-370.88	1,075.53	1,052.16	23.37	46.026	
5,000.00	4,913.30	4,948.23	4,910.38	13.45	12.16	-158.57	248.07	-372.41	1,101.02	1,077.28	23.74	46.387	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 77 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 215H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:
												Offset Well Error:
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Reference (usft)	Major Axis Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre		Distance Between Centres (usft)	Minimum Separation (usft)	Separation Factor	Warning
							+N/-S (usft)	+E/-W (usft)	Ellipses (usft)			
5,100.00	5,009.89	5,047.75	5,009.89	13.78	12.23	-159.07	248.09	-372.43	1,125.28	1,101.26	24.01	46.859
5,200.00	5,106.49	5,144.34	5,106.49	14.10	12.31	-159.53	248.09	-372.43	1,149.59	1,125.28	24.31	47.295
5,300.00	5,203.08	5,240.93	5,203.08	14.43	12.39	-159.97	248.09	-372.43	1,173.97	1,149.37	24.60	47.722
5,400.00	5,299.67	5,337.53	5,299.67	14.75	12.47	-160.40	248.09	-372.43	1,198.41	1,173.52	24.88	48.160
5,500.00	5,396.65	5,434.50	5,396.65	15.07	12.54	-160.90	248.09	-372.43	1,221.50	1,196.31	25.19	48.496
5,600.00	5,494.23	5,532.08	5,494.23	15.36	12.62	-161.33	248.09	-372.43	1,242.23	1,216.74	25.49	48.739
5,700.00	5,592.35	5,630.20	5,592.35	15.62	12.70	-161.70	248.09	-372.43	1,260.55	1,234.77	25.78	48.893
5,800.00	5,690.94	5,728.79	5,690.94	15.86	12.79	-162.01	248.09	-372.43	1,276.46	1,250.39	26.07	48.960
5,900.00	5,789.93	5,827.79	5,789.93	16.07	12.87	-162.26	248.09	-372.43	1,289.92	1,263.56	26.35	48.945
6,000.00	5,889.26	5,927.12	5,889.26	16.25	12.95	-162.47	248.09	-372.43	1,300.91	1,274.28	26.63	48.852
6,100.00	5,988.86	6,026.71	5,988.86	16.41	13.03	-162.62	248.09	-372.43	1,309.43	1,282.53	26.90	48.684
6,200.00	6,088.66	6,126.51	6,088.66	16.53	13.11	-162.73	248.09	-372.43	1,315.46	1,288.31	27.15	48.447
6,300.00	6,188.59	6,226.44	6,188.59	16.64	13.19	-162.80	248.09	-372.43	1,319.00	1,291.60	27.39	48.149
6,400.00	6,288.58	6,326.43	6,288.58	16.71	13.27	-90.39	248.09	-372.43	1,320.04	1,292.48	27.56	47.896
6,500.00	6,388.58	6,426.43	6,388.58	16.76	13.36	-90.39	248.09	-372.43	1,320.04	1,292.34	27.70	47.655
6,600.00	6,488.58	6,526.43	6,488.58	16.82	13.44	-90.39	248.09	-372.43	1,320.04	1,292.20	27.84	47.416
6,700.00	6,588.58	6,626.43	6,588.58	16.88	13.52	-90.39	248.09	-372.43	1,320.04	1,292.06	27.98	47.179
6,800.00	6,688.58	6,726.43	6,688.58	16.94	13.60	-90.39	248.09	-372.43	1,320.04	1,291.92	28.12	46.945
6,900.00	6,788.58	6,826.43	6,788.58	17.00	13.68	-90.39	248.09	-372.43	1,320.04	1,291.78	28.26	46.712
7,000.00	6,888.58	6,926.43	6,888.58	17.05	13.77	-90.39	248.09	-372.43	1,320.04	1,291.64	28.40	46.481
7,100.00	6,988.58	7,026.43	6,988.58	17.11	13.85	-90.39	248.09	-372.43	1,320.04	1,291.50	28.54	46.252
7,200.00	7,088.58	7,126.43	7,088.58	17.17	13.93	-90.39	248.09	-372.43	1,320.04	1,291.36	28.68	46.025
7,300.00	7,188.58	7,226.43	7,188.58	17.23	14.01	-90.39	248.09	-372.43	1,320.04	1,291.22	28.82	45.800
7,400.00	7,288.58	7,326.43	7,288.58	17.29	14.09	-90.39	248.09	-372.43	1,320.04	1,291.08	28.96	45.577
7,500.00	7,388.58	7,426.43	7,388.58	17.35	14.18	-90.39	248.09	-372.43	1,320.04	1,290.94	29.10	45.355
7,600.00	7,488.58	7,526.43	7,488.58	17.41	14.26	-90.39	248.09	-372.43	1,320.04	1,290.79	29.25	45.135
7,700.00	7,588.58	7,626.43	7,588.58	17.47	14.34	-90.39	248.09	-372.43	1,320.04	1,290.65	29.39	44.918
7,800.00	7,688.58	7,726.43	7,688.58	17.53	14.42	-90.39	248.09	-372.43	1,320.04	1,290.51	29.53	44.702
7,900.00	7,788.58	7,826.43	7,788.58	17.59	14.50	-90.39	248.09	-372.43	1,320.04	1,290.37	29.67	44.487
8,000.00	7,888.58	7,926.43	7,888.58	17.65	14.59	-90.39	248.09	-372.43	1,320.04	1,290.23	29.81	44.275
8,100.00	7,988.58	8,026.43	7,988.58	17.71	14.67	-90.39	248.09	-372.43	1,320.04	1,290.08	29.96	44.064
8,200.00	8,088.58	8,126.43	8,088.58	17.77	14.75	-90.39	248.09	-372.43	1,320.04	1,289.94	30.10	43.855
8,300.00	8,188.58	8,226.43	8,188.58	17.83	14.83	-90.39	248.09	-372.43	1,320.04	1,289.80	30.24	43.648
8,400.00	8,288.58	8,326.43	8,288.58	17.89	14.91	-90.39	248.09	-372.43	1,320.04	1,289.65	30.39	43.442
8,500.00	8,388.58	8,426.43	8,388.58	17.95	15.00	-90.39	248.09	-372.43	1,320.04	1,289.51	30.53	43.238
8,600.00	8,488.58	8,526.43	8,488.58	18.02	15.08	-90.39	248.09	-372.43	1,320.04	1,289.37	30.67	43.036
8,700.00	8,588.58	8,626.43	8,588.58	18.08	15.16	-90.39	248.09	-372.43	1,320.04	1,289.22	30.82	42.835
8,800.00	8,688.58	8,726.43	8,688.58	18.14	15.24	-90.39	248.09	-372.43	1,320.04	1,289.08	30.96	42.636
8,900.00	8,788.58	8,826.43	8,788.58	18.20	15.33	-90.39	248.09	-372.43	1,320.04	1,288.94	31.10	42.439
9,000.00	8,888.58	8,926.43	8,888.58	18.26	15.41	-90.39	248.09	-372.43	1,320.04	1,288.79	31.25	42.243
9,100.00	8,988.58	9,026.43	8,988.58	18.32	15.49	-90.39	248.09	-372.43	1,320.04	1,288.65	31.39	42.048
9,200.00	9,088.58	9,126.43	9,088.58	18.39	15.57	-90.39	248.09	-372.43	1,320.04	1,288.50	31.54	41.856
9,300.00	9,188.58	9,226.43	9,188.58	18.45	15.65	-90.39	248.09	-372.43	1,320.04	1,288.36	31.68	41.665
9,400.00	9,288.58	9,326.43	9,288.58	18.51	15.74	-90.39	248.09	-372.43	1,320.04	1,288.21	31.83	41.475
9,500.00	9,388.58	9,426.43	9,388.58	18.57	15.82	-90.39	248.09	-372.43	1,320.04	1,288.07	31.97	41.287
9,600.00	9,488.58	9,526.43	9,488.58	18.64	15.90	-90.39	248.09	-372.43	1,320.04	1,287.92	32.12	41.100
9,700.00	9,588.58	9,626.43	9,588.58	18.70	15.98	-90.39	248.09	-372.43	1,320.04	1,287.78	32.26	40.915
9,800.00	9,688.58	9,726.43	9,688.58	18.76	16.06	-90.39	248.09	-372.43	1,320.04	1,287.63	32.41	40.731
9,900.00	9,788.58	9,826.43	9,788.58	18.83	16.15	-90.39	248.09	-372.43	1,320.04	1,287.49	32.55	40.549
10,000.00	9,888.58	9,926.43	9,888.58	18.89	16.23	-90.39	248.09	-372.43	1,320.04	1,287.34	32.70	40.368
10,100.00	9,988.58	10,026.43	9,988.58	18.95	16.31	-90.39	248.09	-372.43	1,320.04	1,287.19	32.85	40.189
10,200.00	10,088.58	10,126.43	10,088.58	19.02	16.39	-90.39	248.09	-372.43	1,320.04	1,287.05	32.99	40.011

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 78 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 215H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:			Offset Site Error:		0.00 usft	
Reference Offset				Semi Major Axis		Offset Wellbore Centre				Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning			
10,300.00	10,188.58	10,226.43	10,188.58	19.08	16.47	-90.39	248.09	-372.43	1,320.04	1,286.90	33.14	39.834				
10,400.00	10,288.58	10,326.43	10,288.58	19.15	16.56	-90.39	248.09	-372.43	1,320.04	1,286.76	33.28	39.659				
10,500.00	10,388.58	10,426.43	10,388.58	19.21	16.64	-90.39	248.09	-372.43	1,320.04	1,286.61	33.43	39.485				
10,600.00	10,488.58	10,526.43	10,488.58	19.27	16.72	-90.39	248.09	-372.43	1,320.04	1,286.46	33.58	39.312				
10,700.00	10,588.58	10,626.43	10,588.58	19.34	16.80	-90.39	248.09	-372.43	1,320.04	1,286.32	33.73	39.141				
10,800.00	10,688.58	10,726.43	10,688.58	19.40	16.89	-90.39	248.09	-372.43	1,320.04	1,286.17	33.87	38.971				
10,900.00	10,788.58	10,826.43	10,788.58	19.47	16.97	-90.39	248.09	-372.43	1,320.04	1,286.02	34.02	38.803				
11,000.00	10,888.58	10,926.43	10,888.58	19.53	17.05	-90.39	248.09	-372.43	1,320.04	1,285.87	34.17	38.636				
11,100.00	10,988.58	11,026.43	10,988.58	19.60	17.13	-90.39	248.09	-372.43	1,320.04	1,285.73	34.31	38.470				
11,200.00	11,088.58	11,126.43	11,088.58	19.66	17.21	-90.39	248.09	-372.43	1,320.04	1,285.58	34.46	38.305				
11,300.00	11,188.58	11,226.43	11,188.58	19.73	17.30	-90.39	248.09	-372.43	1,320.04	1,285.43	34.61	38.142				
11,400.00	11,288.58	11,326.43	11,288.58	19.79	17.38	-90.39	248.09	-372.43	1,320.04	1,285.28	34.76	37.979				
11,500.00	11,388.58	11,426.43	11,388.58	19.86	17.46	-90.39	248.09	-372.43	1,320.04	1,285.14	34.90	37.818				
11,600.00	11,488.58	11,526.43	11,488.58	19.92	17.54	-90.39	248.09	-372.43	1,320.04	1,284.99	35.05	37.659				
11,700.00	11,588.58	11,626.43	11,588.58	19.99	17.62	-90.39	248.09	-372.43	1,320.04	1,284.84	35.20	37.500				
11,800.00	11,688.58	11,726.43	11,688.58	20.05	17.71	-90.39	248.09	-372.43	1,320.04	1,284.69	35.35	37.343				
11,900.00	11,788.58	11,826.43	11,788.58	20.12	17.79	-90.39	248.09	-372.43	1,320.04	1,284.54	35.50	37.187				
12,000.00	11,888.58	11,926.43	11,888.58	20.19	17.87	-90.39	248.09	-372.43	1,320.04	1,284.40	35.64	37.036				
12,100.00	11,988.51	12,026.65	11,988.73	20.25	17.91	90.11	245.84	-372.41	1,320.04	1,284.37	35.67	37.009				
12,200.00	12,086.82	12,127.09	12,087.49	20.31	17.94	90.11	228.25	-372.26	1,320.04	1,284.53	35.51	37.172				
12,300.00	12,180.57	12,227.54	12,181.67	20.35	17.96	90.11	193.69	-371.96	1,320.04	1,284.79	35.26	37.443				
12,400.00	12,266.93	12,327.99	12,268.38	20.39	17.99	90.11	143.25	-371.53	1,320.04	1,285.10	34.94	37.782				
12,500.00	12,343.26	12,428.42	12,344.96	20.44	18.01	90.11	78.46	-370.97	1,320.04	1,285.42	34.62	38.129				
12,600.00	12,407.24	12,528.82	12,409.04	20.52	18.05	90.09	1.34	-370.31	1,320.04	1,285.67	34.37	38.408				
12,700.00	12,456.94	12,629.18	12,458.67	20.67	18.11	90.08	-85.73	-369.56	1,320.04	1,285.79	34.25	38.539				
12,800.00	12,490.84	12,729.49	12,492.36	20.88	18.19	90.07	-180.07	-368.74	1,320.04	1,285.72	34.32	38.458				
12,900.00	12,507.91	12,829.73	12,509.10	21.18	18.31	90.05	-278.77	-367.89	1,320.04	1,285.43	34.61	38.135				
12,943.84	12,510.89	12,873.62	12,510.96	21.34	18.38	90.00	-322.61	-367.52	1,320.04	1,285.22	34.82	37.911				
13,000.00	12,510.43	12,929.81	12,511.45	21.56	18.48	90.04	-378.80	-367.03	1,320.04	1,284.91	35.13	37.572				
13,100.00	12,511.30	13,029.81	12,512.32	22.01	18.69	90.04	-478.79	-366.17	1,320.04	1,284.17	35.87	36.800				
13,200.00	12,512.18	13,129.81	12,513.20	22.52	18.97	90.04	-578.78	-365.31	1,320.04	1,283.24	36.80	35.872				
13,300.00	12,513.05	13,229.81	12,514.07	23.10	19.32	90.04	-678.77	-364.45	1,320.04	1,282.14	37.90	34.827				
13,400.00	12,513.92	13,329.81	12,514.94	23.73	19.76	90.04	-778.77	-363.59	1,320.04	1,280.87	39.17	33.702				
13,500.00	12,514.80	13,429.81	12,515.82	24.41	20.28	90.04	-878.76	-362.73	1,320.04	1,279.46	40.58	32.529				
13,600.00	12,515.67	13,529.81	12,516.69	25.15	20.89	90.04	-978.75	-361.87	1,320.04	1,277.92	42.12	31.337				
13,700.00	12,516.55	13,629.81	12,517.56	25.93	21.59	90.04	-1,078.74	-361.01	1,320.04	1,276.26	43.79	30.148				
13,800.00	12,517.42	13,729.81	12,518.44	26.76	22.36	90.04	-1,178.74	-360.15	1,320.04	1,274.49	45.55	28.979				
13,900.00	12,518.29	13,829.81	12,519.31	27.63	23.19	90.04	-1,278.73	-359.28	1,320.04	1,272.63	47.41	27.843				
14,000.00	12,519.17	13,929.81	12,520.18	28.53	24.08	90.04	-1,378.72	-358.42	1,320.04	1,270.69	49.35	26.747				
14,100.00	12,520.04	14,029.81	12,521.06	29.47	25.01	90.04	-1,478.71	-357.56	1,320.04	1,268.67	51.37	25.698				
14,200.00	12,520.91	14,129.81	12,521.93	30.44	25.99	90.04	-1,578.71	-356.70	1,320.04	1,266.60	53.45	24.698				
14,300.00	12,521.79	14,229.81	12,522.80	31.44	27.01	90.04	-1,678.70	-355.84	1,320.04	1,264.46	55.58	23.748				
14,400.00	12,522.66	14,329.81	12,523.68	32.46	28.06	90.04	-1,778.69	-354.98	1,320.04	1,262.27	57.77	22.849				
14,500.00	12,523.53	14,429.81	12,524.55	33.51	29.14	90.04	-1,878.68	-354.12	1,320.04	1,260.04	60.01	21.998				
14,600.00	12,524.41	14,529.81	12,525.42	34.58	30.25	90.04	-1,978.68	-353.26	1,320.04	1,257.76	62.28	21.195				
14,700.00	12,525.28	14,629.81	12,526.30	35.67	31.38	90.04	-2,078.67	-352.40	1,320.04	1,255.45	64.59	20.437				
14,800.00	12,526.16	14,729.81	12,527.17	36.78	32.52	90.04	-2,178.66	-351.54	1,320.04	1,253.11	66.93	19.721				
14,900.00	12,527.03	14,829.81	12,528.04	37.90	33.69	90.04	-2,278.65	-350.68	1,320.04	1,250.74	69.31	19.047				
15,000.00	12,527.90	14,929.81	12,528.92	39.04	34.87	90.04	-2,378.65	-349.81	1,320.04	1,248.34	71.70	18.409				
15,100.00	12,528.78	15,029.81	12,529.79	40.20	36.06	90.04	-2,478.64	-348.95	1,320.05	1,245.92	74.13	17.808				
15,200.00	12,529.65	15,129.81	12,530.66	41.37	37.27	90.04	-2,578.63	-348.09	1,320.05	1,243.48	76.57	17.240				
15,300.00	12,530.52	15,229.81	12,531.54	42.55	38.49	90.04	-2,678.62	-347.23	1,320.05	1,241.01	79.03	16.702				

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 215H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:		Offset Well Error:		0.50 usft		
Reference		Offset		Semi Major Axis		Highside Toolface (")	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
15,400.00	12,531.40	15,329.81	12,532.41	43.74	39.71	90.04	-2,778.62	-346.37	1,320.05	1,238.53	81.51	16.194	
15,500.00	12,532.27	15,429.81	12,533.28	44.94	40.95	90.04	-2,878.61	-345.51	1,320.05	1,236.04	84.01	15.713	
15,600.00	12,533.14	15,529.81	12,534.16	46.15	42.20	90.04	-2,978.60	-344.65	1,320.05	1,233.52	86.52	15.257	
15,700.00	12,534.02	15,629.81	12,535.03	47.37	43.45	90.04	-3,078.59	-343.79	1,320.05	1,231.00	89.05	14.824	
15,800.00	12,534.89	15,729.81	12,535.90	48.59	44.71	90.04	-3,178.59	-342.93	1,320.05	1,228.46	91.58	14.414	
15,900.00	12,535.76	15,829.81	12,536.77	49.83	45.98	90.04	-3,278.58	-342.07	1,320.05	1,225.91	94.13	14.023	
16,000.00	12,536.64	15,929.81	12,537.65	51.07	47.25	90.04	-3,378.57	-341.21	1,320.05	1,223.36	96.69	13.652	
16,100.00	12,537.51	16,029.81	12,538.52	52.32	48.53	90.04	-3,478.56	-340.34	1,320.05	1,220.79	99.26	13.299	
16,200.00	12,538.39	16,129.81	12,539.39	53.57	49.81	90.04	-3,578.56	-339.48	1,320.05	1,218.21	101.84	12.962	
16,300.00	12,539.26	16,229.81	12,540.27	54.83	51.10	90.04	-3,678.55	-338.62	1,320.05	1,215.62	104.42	12.641	
16,400.00	12,540.13	16,329.81	12,541.14	56.09	52.39	90.04	-3,778.54	-337.76	1,320.05	1,213.03	107.02	12.335	
16,500.00	12,541.01	16,429.81	12,542.01	57.36	53.69	90.04	-3,878.53	-336.90	1,320.05	1,210.43	109.62	12.042	
16,600.00	12,541.88	16,529.81	12,542.89	58.64	54.99	90.04	-3,978.53	-336.04	1,320.05	1,207.82	112.22	11.763	
16,700.00	12,542.75	16,629.81	12,543.76	59.91	56.29	90.04	-4,078.52	-335.18	1,320.05	1,205.21	114.84	11.495	
16,800.00	12,543.63	16,729.81	12,544.63	61.20	57.60	90.04	-4,178.51	-334.32	1,320.05	1,202.59	117.46	11.239	
16,900.00	12,544.50	16,829.81	12,545.51	62.48	58.91	90.04	-4,278.50	-333.46	1,320.05	1,199.97	120.08	10.993	
17,000.00	12,545.37	16,929.81	12,546.38	63.77	60.22	90.04	-4,378.50	-332.60	1,320.05	1,197.34	122.71	10.757	
17,100.00	12,546.25	17,029.81	12,547.25	65.06	61.54	90.04	-4,478.49	-331.73	1,320.05	1,194.70	125.35	10.531	
17,200.00	12,547.12	17,129.81	12,548.13	66.36	62.85	90.04	-4,578.48	-330.87	1,320.05	1,192.07	127.98	10.314	
17,300.00	12,547.99	17,229.81	12,549.00	67.66	64.17	90.04	-4,678.47	-330.01	1,320.05	1,189.42	130.63	10.106	
17,400.00	12,548.87	17,329.81	12,549.87	68.96	65.49	90.04	-4,778.47	-329.15	1,320.05	1,186.78	133.27	9.905	
17,500.00	12,549.74	17,429.81	12,550.75	70.26	66.82	90.04	-4,878.46	-328.29	1,320.05	1,184.13	135.92	9.712	
17,600.00	12,550.62	17,529.81	12,551.62	71.57	68.14	90.04	-4,978.45	-327.43	1,320.05	1,181.4			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 80 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 215H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Rule Assigned:		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)			
20,600.00	12,576.82	20,529.81	12,577.82	111.47	108.42	90.04	-7,978.23	-301.60	1,320.06	1,100.88	219.18	6.023			
20,700.00	12,577.70	20,629.81	12,578.69	112.81	109.77	90.04	-8,078.22	-300.74	1,320.06	1,098.17	221.88	5.949			
20,800.00	12,578.57	20,729.81	12,579.56	114.16	111.13	90.04	-8,178.21	-299.88	1,320.06	1,095.47	224.59	5.878			
20,900.00	12,579.44	20,829.81	12,580.44	115.51	112.48	90.04	-8,278.20	-299.02	1,320.06	1,092.76	227.30	5.808			
21,000.00	12,580.32	20,929.81	12,581.31	116.85	113.84	90.04	-8,378.20	-298.16	1,320.06	1,090.05	230.01	5.739			
21,100.00	12,581.19	21,029.81	12,582.18	118.20	115.19	90.04	-8,478.19	-297.30	1,320.06	1,087.34	232.72	5.672			
21,200.00	12,582.06	21,129.81	12,583.06	119.55	116.55	90.04	-8,578.18	-296.44	1,320.06	1,084.63	235.43	5.607			
21,300.00	12,582.94	21,229.81	12,583.93	120.89	117.90	90.04	-8,678.17	-295.58	1,320.06	1,081.92	238.14	5.543			
21,400.00	12,583.81	21,329.81	12,584.80	122.24	119.26	90.04	-8,778.17	-294.72	1,320.06	1,079.21	240.85	5.481			
21,500.00	12,584.69	21,429.81	12,585.68	123.59	120.61	90.04	-8,878.16	-293.85	1,320.06	1,076.50	243.56	5.420			
21,600.00	12,585.56	21,529.81	12,586.55	124.94	121.97	90.04	-8,978.15	-292.99	1,320.06	1,073.78	246.28	5.360			
21,700.00	12,586.43	21,629.81	12,587.42	126.29	123.33	90.04	-9,078.14	-292.13	1,320.06	1,071.07	248.99	5.302			
21,800.00	12,587.31	21,729.81	12,588.30	127.64	124.68	90.04	-9,178.14	-291.27	1,320.06	1,068.36	251.70	5.244			
21,900.00	12,588.18	21,829.81	12,589.17	128.99	126.04	90.04	-9,278.13	-290.41	1,320.06	1,065.64	254.42	5.189			
22,000.00	12,589.05	21,929.81	12,590.04	130.34	127.40	90.04	-9,378.12	-289.55	1,320.06	1,062.93	257.13	5.134			
22,100.00	12,589.93	22,029.81	12,590.92	131.70	128.75	90.04	-9,478.11	-288.69	1,320.06	1,060.21	259.85	5.080			
22,200.00	12,590.80	22,129.81	12,591.79	133.05	130.11	90.04	-9,578.11	-287.83	1,320.06	1,057.50	262.57	5.028			
22,300.00	12,591.67	22,229.81	12,592.66	134.40	131.47	90.04	-9,678.10	-286.97	1,320.06	1,054.78	265.28	4.976			
22,400.00	12,592.55	22,329.81	12,593.54	135.75	132.83	90.04	-9,778.09	-286.11	1,320.06	1,052.06	268.00	4.926			
22,500.00	12,593.42	22,429.81	12,594.41	137.11	134.19	90.04	-9,878.08	-285.25	1,320.06	1,049.34	270.72	4.876			
22,600.00	12,594.30	22,529.81	12,595.28	138.46	135.55	90.04	-9,978.08	-284.38	1,320.06	1,046.63	273.44	4.828			
22,700.00	12,595.17	22,629.81	12,596.16	139.81	136.91	90.04	-10,078.07	-283.52	1,320.06	1,043.91	276.15	4.780			
22,800.00	12,596.04	22,729.81	12,597.03	141.17	138.27	90.04	-10,178.06	-282.66	1,320.06	1,041.19	278.87	4.734			
22,875.30	12,596.70	22,805.11	12,597.69	142.19	139.29	90.04	-10,253.36	-282.01	1,320.06	1,039.14	280.92	4.699	SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 81 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 216H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Well Error:		Offset Site Error:	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Warning		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor			
0.00	0.00	2.00	0.00	0.50	0.50	69.20	881.00	2,319.00	2,480.71						
100.00	100.00	102.00	100.00	0.98	0.99	69.20	881.00	2,319.00	2,480.71	2,478.74	1.97	1,257.247			
200.00	200.00	202.00	200.00	1.56	1.57	69.20	881.00	2,319.00	2,480.71	2,477.58	3.13	792.419			
300.00	300.00	302.00	300.00	1.98	1.99	69.20	881.00	2,319.00	2,480.71	2,476.74	3.97	624.982			
400.00	400.00	402.00	400.00	2.33	2.34	69.20	881.00	2,319.00	2,480.71	2,476.05	4.66	531.780			
500.00	500.00	502.00	500.00	2.63	2.64	69.20	881.00	2,319.00	2,480.71	2,475.44	5.27	470.318			
600.00	600.00	602.00	600.00	2.91	2.92	69.20	881.00	2,319.00	2,480.71	2,474.88	5.83	425.858			
700.00	700.00	702.76	700.76	3.16	3.17	69.20	881.00	2,319.00	2,480.71	2,474.38	6.33	391.653			
800.00	800.00	840.77	838.73	3.40	3.55	69.25	878.41	2,318.80	2,479.91	2,473.03	6.88	360.377			
900.00	900.00	956.93	954.76	3.62	3.81	69.37	872.81	2,318.38	2,477.84	2,470.50	7.34	337.809			
1,000.00	1,000.00	1,056.80	1,054.49	3.76	4.00	-22.52	867.60	2,317.99	2,475.59	2,467.93	7.66	323.276			
1,100.00	1,099.98	1,156.64	1,154.19	4.00	4.18	-22.45	862.39	2,317.59	2,471.70	2,463.62	8.07	306.133			
1,200.00	1,199.88	1,258.54	1,255.95	4.24	4.32	-22.42	857.06	2,317.19	2,465.39	2,456.97	8.42	292.687			
1,300.00	1,299.63	1,394.58	1,391.64	4.46	4.57	-22.35	847.27	2,316.45	2,455.85	2,447.00	8.85	277.449			
1,400.00	1,399.25	1,508.61	1,505.08	4.60	4.70	-22.20	835.79	2,315.58	2,443.61	2,434.51	9.10	268.595			
1,500.00	1,498.87	1,607.64	1,603.57	4.78	4.89	-22.05	825.47	2,314.80	2,431.23	2,421.77	9.46	257.070			
1,600.00	1,598.49	1,706.68	1,702.07	4.96	5.08	-21.90	815.15	2,314.02	2,418.87	2,409.05	9.82	246.425			
1,700.00	1,698.11	1,805.72	1,800.56	5.14	5.26	-21.75	804.83	2,313.24	2,406.52	2,396.35	10.17	236.560			
1,800.00	1,797.73	1,904.76	1,899.06	5.32	5.45	-21.60	794.51	2,312.46	2,394.19	2,383.66	10.53	227.388			
1,900.00	1,897.34	2,003.79	1,997.55	5.49	5.63	-21.45	784.18	2,311.68	2,381.88	2,371.00	10.88	218.838			
2,000.00	1,996.96	2,102.83	2,096.05	5.67	5.82	-21.30	773.86	2,310.90	2,369.59	2,358.35	11.24	210.845			
2,100.00	2,096.58	2,201.87	2,194.54	5.85	6.00	-21.14	763.54	2,310.12	2,357.31	2,345.71	11.59	203.356			
2,200.00	2,196.20	2,300.90	2,293.04	6.04	6.19	-20.98	753.22	2,309.34	2,345.05	2,333.09	11.95	196.210			
2,300.00	2,295.72	2,399.77	2,391.36	6.23	6.37	-14.51	742.92	2,308.56	2,331.61	2,319.30	12.32	189.296		</	

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 82 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 216H - OH - Plan 1														Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance			Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
5,200.00	5,106.49	5,168.39	5,144.81	14.10	11.48	8.46	454.38	2,286.75	1,531.77	1,508.70	23.07	66.383			
5,300.00	5,203.08	5,263.44	5,239.35	14.43	11.65	8.98	444.48	2,286.00	1,503.80	1,480.34	23.46	64.111			
5,400.00	5,299.67	5,358.50	5,333.88	14.75	11.82	9.52	434.57	2,285.26	1,475.96	1,452.13	23.83	61.940			
5,500.00	5,396.65	5,453.99	5,428.85	15.07	12.00	10.01	424.62	2,284.50	1,449.69	1,425.47	24.22	59.843			
5,600.00	5,494.23	5,550.18	5,524.52	15.36	12.18	10.50	414.59	2,283.75	1,426.06	1,401.44	24.62	57.927			
5,700.00	5,592.35	5,647.02	5,620.82	15.62	12.35	10.99	404.50	2,282.98	1,405.06	1,380.05	25.01	56.183			
5,800.00	5,690.94	5,744.41	5,717.69	15.86	12.53	11.49	394.35	2,282.22	1,386.71	1,361.32	25.39	54.606			
5,900.00	5,789.93	5,842.32	5,815.05	16.07	12.71	11.98	384.15	2,281.44	1,371.01	1,345.24	25.78	53.190			
6,000.00	5,889.26	5,940.65	5,912.85	16.25	12.89	12.47	373.90	2,280.67	1,357.97	1,331.82	26.15	51.930			
6,100.00	5,988.86	6,039.36	6,011.02	16.41	13.07	12.95	363.61	2,279.89	1,347.58	1,321.06	26.52	50.823			
6,200.00	6,088.66	6,138.36	6,109.48	16.53	13.26	13.42	353.29	2,279.11	1,339.83	1,312.96	26.87	49.864			
6,300.00	6,188.59	6,237.60	6,208.17	16.64	13.44	13.88	342.95	2,278.33	1,334.72	1,307.52	27.21	49.055			
6,400.00	6,288.58	6,337.00	6,307.03	16.71	13.62	14.35	332.59	2,277.55	1,332.24	1,304.77	27.47	48.496			
6,500.00	6,388.58	6,436.45	6,405.94	16.76	13.80	14.82	322.23	2,276.76	1,330.89	1,303.19	27.71	48.038			
6,600.00	6,488.58	6,535.90	6,504.84	16.82	13.99	15.29	311.86	2,275.98	1,329.63	1,301.69	27.94	47.590			
6,700.00	6,588.58	6,635.36	6,603.75	16.88	14.17	15.76	301.50	2,275.20	1,328.45	1,300.27	28.17	47.152			
6,800.00	6,688.58	6,734.81	6,702.66	16.94	14.35	16.23	291.14	2,274.41	1,327.34	1,298.94	28.40	46.734			
6,900.00	6,788.58	6,832.27	6,799.63	17.00	14.51	16.70	281.46	2,273.68	1,326.37	1,297.76	28.61	46.360			
7,000.00	6,888.58	6,928.92	6,896.00	17.05	14.69	17.17	274.14	2,273.13	1,325.68	1,296.86	28.82	45.998			
7,100.00	6,988.58	7,025.88	6,992.84	17.11	14.86	17.64	269.24	2,272.76	1,325.24	1,296.23	29.01	45.685			
7,200.00	7,088.58	7,123.04	7,089.96	17.17	15.00	18.11	266.79	2,272.57	1,325.03	1,295.87	29.16	45.435			
7,265.82	7,154.39	7,187.47	7,154.39	17.21	15.03	18.58	266.49	2,272.55	1,325.00	1,295.78	29.22	45.345			
7,300.00	7,188.58	7,221.66	7,188.58	17.23	15.03	19.05	266.49	2,272.55	1,325.00	1,295.76	29.24	45.310			
7,400.00	7,288.58	7,321.66	7,288.58	17.29	15.06	19.52	266.49	2,272.55	1,325.00	1,295.68	29.32	45.184			
7,500.00	7,388.58	7,421.66	7,388.58	17.35	15.08	19.99	266.49	2,272.55	1,325.00	1,295.60	29.41	45.057			
7,600.00	7,488.58	7,521.66	7,488.58	17.41	15.11	20.46	266.49	2,272.55	1,325.00	1,295.51	29.49	44.931			
7,700.00	7,588.58	7,621.66	7,588.58	17.47	15.13	20.93	266.49	2,272.55	1,325.00	1,295.43	29.57	44.804			
7,800.00	7,688.58	7,721.66	7,688.58	17.53	15.16	21.40	266.49	2,272.55	1,325.00	1,295.35	29.66	44.677			
7,900.00	7,788.58	7,821.66	7,788.58	17.59	15.18	21.87	266.49	2,272.55	1,325.00	1,295.26	29.74	44.550			
8,000.00	7,888.58	7,921.66	7,888.58	17.65	15.21	22.34	266.49	2,272.55	1,325.00	1,295.18	29.83	44.423			
8,100.00	7,988.58	8,021.66	7,988.58	17.71	15.24	22.81	266.49	2,272.55	1,325.00	1,295.09	29.91	44.295			
8,200.00	8,088.58	8,121.66	8,088.58	17.77	15.27	23.28	266.49	2,272.55	1,325.00	1,295.00	30.00	44.168			
8,300.00	8,188.58	8,221.66	8,188.58	17.83	15.29	23.75	266.49	2,272.55	1,325.00	1,294.92	30.09	44.040			
8,400.00	8,288.58	8,321.66	8,288.58	17.89	15.32	24.22	266.49	2,272.55	1,325.00	1,294.83	30.17	43.912			
8,500.00	8,388.58	8,421.66	8,388.58	17.95	15.35	24.69	266.49	2,272.55	1,325.00	1,294.74	30.26	43.784			
8,600.00	8,488.58	8,521.66	8,488.58	18.02	15.38	25.16	266.49	2,272.55	1,325.00	1,294.65	30.35	43.656			
8,700.00	8,588.58	8,621.66	8,588.58	18.08	15.41	25.63	266.49	2,272.55	1,325.00	1,294.56	30.44	43.527			
8,800.00	8,688.58	8,721.66	8,688.58	18.14	15.44	26.10	266.49	2,272.55	1,325.00	1,294.47	30.53	43.399			
8,900.00	8,788.58	8,821.66	8,788.58	18.20	15.47	26.57	266.49	2,272.55	1,325.00	1,294.38	30.62	43.271			
9,000.00	8,888.58	8,921.66	8,888.58	18.26	15.50	27.04	266.49	2,272.55	1,325.00	1,294.29	30.71	43.142			
9,100.00	8,988.58	9,021.66	8,988.58	18.32	15.53	27.51	266.49	2,272.55	1,325.00	1,294.20	30.80	43.014			
9,200.00	9,088.58	9,121.66	9,088.58	18.39	15.56	27.98	266.49	2,272.55	1,325.00	1,294.11	30.90	42.885			
9,300.00	9,188.58	9,221.66	9,188.58	18.45	15.59	28.45	266.49	2,272.55	1,325.00	1,294.01	30.99	42.757			
9,400.00	9,288.58	9,321.66	9,288.58	18.51	15.63	28.92	266.49	2,272.55	1,325.00	1,293.92	31.08	42.628			
9,500.00	9,388.58	9,421.66	9,388.58	18.57	15.66	29.39	266.49	2,272.55	1,325.00	1,293.83	31.18	42.500			
9,600.00	9,488.58	9,521.66	9,488.58	18.64	15.69	29.86	266.49	2,272.55	1,325.00	1,293.73	31.27	42.371			
9,700.00	9,588.58	9,621.66	9,588.58	18.70	15.72	30.33	266.49	2,272.55	1,325.00	1,293.64	31.37	42.243			
9,800.00	9,688.58	9,721.66	9,688.58	18.76	15.76	30.80	266.49	2,272.55	1,325.00	1,293.54	31.46	42.115			
9,900.00	9,788.58	9,821.66	9,788.58	18.83	15.79	31.27	266.49	2,272.55	1,325.00	1,293.45	31.56	41.986			
10,000.00	9,888.58	9,921.66	9,888.58	18.89	15.83	31.74	266.49	2,272.55	1,325.00	1,293.35	31.65	41.858			
10,100.00	9,988.58	10,021.66	9,988.58	18.95	15.86	32.21	266.49	2,272.55	1,325.00	1,293.25	31.75	41.730			
10,200.00	10,088.58	10,121.66	10,088.58	19.02	15.89	32.68	266.49	2,272.55	1,325.00	1,293.15	31.85	41.602			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 216H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)		
10,300.00	10,188.58	10,221.66	10,188.58	19.08	15.93	89.59	266.49	2,272.55	1,325.00	1,293.06	31.95	41.474
10,400.00	10,288.58	10,321.66	10,288.58	19.15	15.97	89.59	266.49	2,272.55	1,325.00	1,292.96	32.05	41.346
10,500.00	10,388.58	10,421.66	10,388.58	19.21	16.00	89.59	266.49	2,272.55	1,325.00	1,292.86	32.15	41.219
10,600.00	10,488.58	10,521.66	10,488.58	19.27	16.04	89.59	266.49	2,272.55	1,325.00	1,292.76	32.25	41.091
10,700.00	10,588.58	10,621.66	10,588.58	19.34	16.07	89.59	266.49	2,272.55	1,325.00	1,292.66	32.35	40.964
10,800.00	10,688.58	10,721.66	10,688.58	19.40	16.11	89.59	266.49	2,272.55	1,325.00	1,292.56	32.45	40.837
10,900.00	10,788.58	10,821.66	10,788.58	19.47	16.15	89.59	266.49	2,272.55	1,325.00	1,292.46	32.55	40.710
11,000.00	10,888.58	10,921.66	10,888.58	19.53	16.19	89.59	266.49	2,272.55	1,325.00	1,292.35	32.65	40.583
11,100.00	10,988.58	11,021.66	10,988.58	19.60	16.22	89.59	266.49	2,272.55	1,325.00	1,292.25	32.75	40.456
11,200.00	11,088.58	11,121.66	11,088.58	19.66	16.26	89.59	266.49	2,272.55	1,325.00	1,292.15	32.85	40.330
11,300.00	11,188.58	11,221.66	11,188.58	19.73	16.30	89.59	266.49	2,272.55	1,325.00	1,292.05	32.96	40.203
11,400.00	11,288.58	11,321.66	11,288.58	19.79	16.34	89.59	266.49	2,272.55	1,325.00	1,291.94	33.06	40.077
11,500.00	11,388.58	11,421.66	11,388.58	19.86	16.38	89.59	266.49	2,272.55	1,325.00	1,291.84	33.17	39.952
11,600.00	11,488.58	11,521.66	11,488.58	19.92	16.42	89.59	266.49	2,272.55	1,325.00	1,291.73	33.27	39.826
11,700.00	11,588.58	11,621.66	11,588.58	19.99	16.46	89.59	266.49	2,272.55	1,325.00	1,291.63	33.37	39.701
11,800.00	11,688.58	11,721.66	11,688.58	20.05	16.50	89.59	266.49	2,272.55	1,325.00	1,291.52	33.48	39.575
11,900.00	11,788.58	11,821.66	11,788.58	20.12	16.54	89.59	266.49	2,272.55	1,325.00	1,291.42	33.58	39.452
11,903.47	11,792.05	11,825.13	11,792.05	20.12	16.54	89.59	266.49	2,272.55	1,325.00	1,291.42	33.59	39.448
12,000.00	11,888.58	11,921.48	11,888.38	20.19	16.61	89.63	265.57	2,272.56	1,325.01	1,291.32	33.69	39.329
12,100.00	11,988.51	12,019.23	11,985.04	20.25	16.86	-89.37	251.77	2,272.68	1,325.09	1,291.26	33.83	39.168
12,200.00	12,086.82	12,114.66	12,075.80	20.31	17.13	-88.79	222.66	2,272.95	1,325.32	1,291.30	34.02	38.955
12,300.00	12,180.57	12,208.19	12,158.86	20.35	17.39	-88.26	179.90	2,273.34	1,325.66	1,291.37	34.29	38.659
12,400.00	12,266.93	12,300.00	12,232.59	20.39	17.64	-87.78	125.35	2,273.83	1,326.08	1,291.42	34.66	38.264
12,500.00	12,343.26	12,390.61	12,295.89	20.44	17.86	-87.36	60.66	2,274.42	1,326.52	1,291.37	35.15	37.738
12,600.00	12,407.24	12,480.04	12,347.62	20.52	18.05	-87.02	-12.19	2,275.08	1,326.94	1,291.15	35.79	37.073
12,700.00	12,456.94	12,568.64	12,387.07	20.67	18.66	-86.76	-91.41	2,275.80	1,327.30	1,290.70	36.60	36.261
12,800.00	12,490.84	12,656.66	12,413.72	20.88	19.50	-86.59	-175.21	2,276.56	1,327.57	1,289.98	37.59	35.315
12,900.00	12,507.91	12,744.36	12,427.21	21.18	20.40	-86.51	-261.77	2,277.35	1,327.72	1,288.97	38.75	34.263
13,000.00	12,510.43	12,838.46	12,429.23	21.56	21.41	-86.49	-355.82	2,278.21	1,327.78	1,287.68	40.11	33.105
13,100.00	12,511.30	12,938.46	12,429.75	22.01	22.51	-86.48	-455.82	2,279.12	1,327.85	1,286.20	41.65	31.878
13,200.00	12,512.18	13,038.46	12,430.28	22.52	23.64	-86.46	-555.81	2,280.02	1,327.92	1,284.61	43.31	30.659
13,300.00	12,513.05	13,138.46	12,430.80	23.10	24.80	-86.45	-655.80	2,280.93	1,327.99	1,282.92	45.07	29.462
13,400.00	12,513.92	13,238.46	12,431.33	23.73	25.98	-86.43	-755.80	2,281.84	1,328.06	1,281.13	46.93	28.299
13,500.00	12,514.80	13,338.46	12,431.85	24.41	27.18	-86.42	-855.79	2,282.75	1,328.13	1,279.26	48.87	27.179
13,600.00	12,515.67	13,438.46	12,432.38	25.15	28.39	-86.40	-955.79	2,283.66	1,328.20	1,277.32	50.88	26.106
13,700.00	12,516.55	13,538.46	12,432.90	25.93	29.61	-86.39	-1,055.78	2,284.57	1,328.27	1,275.31	52.96	25.083
13,800.00	12,517.42	13,638.46	12,433.43	26.76	30.85	-86.37	-1,155.77	2,285.48	1,328.34	1,273.25	55.09	24.111
13,900.00	12,518.29	13,738.46	12,433.95	27.63	32.10	-86.36	-1,255.77	2,286.39	1,328.41	1,271.13	57.28	23.191
14,000.00	12,519.17	13,838.45	12,434.48	28.53	33.35	-86.35	-1,355.76	2,287.29	1,328.48	1,268.96	59.52	22.320
14,100.00	12,520.04	13,938.45	12,435.00	29.47	34.62	-86.33	-1,455.75	2,288.20	1,328.55	1,266.75	61.80	21.499
14,200.00	12,520.91	14,038.45	12,435.53	30.44	35.89	-86.32	-1,555.75	2,289.11	1,328.62	1,264.51	64.11	20.723
14,300.00	12,521.79	14,138.45	12,436.05	31.44	37.18	-86.30	-1,655.74	2,290.02	1,328.69	1,262.23	66.46	19.992
14,400.00	12,522.66	14,238.45	12,436.58	32.46	38.46	-86.29	-1,755.74	2,290.93	1,328.76	1,259.92	68.84	19.302
14,500.00	12,523.53	14,338.45	12,437.10	33.51	39.75	-86.27	-1,855.73	2,291.84	1,328.83	1,257.58	71.25	18.651
14,600.00	12,524.41	14,438.45	12,437.63	34.58	41.05	-86.26	-1,955.72	2,292.75	1,328.90	1,255.22	73.68	18.037
14,700.00	12,525.28	14,538.45	12,438.15	35.67	42.35	-86.24	-2,055.72	2,293.66	1,328.97	1,252.84	76.13	17.457
14,800.00	12,526.16	14,638.45	12,438.68	36.78	43.66	-86.23	-2,155.71	2,294.57	1,329.04	1,250.44	78.60	16.910
14,900.00	12,527.03	14,738.45	12,439.20	37.90	44.97	-86.21	-2,255.71	2,295.47	1,329.11	1,248.02	81.09	16.392
15,000.00	12,527.90	14,838.45	12,439.73	39.04	46.28	-86.20	-2,355.70	2,296.38	1,329.18	1,245.59	83.59	15.901
15,100.00	12,528.78	14,938.45	12,440.25	40.20	47.60	-86.18	-2,455.69	2,297.29	1,329.25	1,243.14	86.11	15.437
15,200.00	12,529.65	15,038.45	12,440.78	41.37	48.92	-86.17	-2,555.69	2,298.20	1,329.32	1,240.68	88.64	14.997
15,300.00	12,530.52	15,138.45	12,441.30	42.55	50.24	-86.15	-2,655.68	2,299.11	1,329.39	1,238.21	91.19	14.579

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 84 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 216H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: Reference		0-MWD+HRGM+SAG+FDIR (rev.5)		Semi Major Axis		Offset Wellbore Centre		Distance		Rule Assigned:		Offset Well Error:		0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
15,400.00	12,531.40	15,238.45	12,441.83	43.74	51.56	-86.14	-2,755.68	2,300.02	1,329.46	1,235.72	93.74	14.182			
15,500.00	12,532.27	15,338.45	12,442.35	44.94	52.89	-86.12	-2,855.67	2,300.93	1,329.54	1,233.23	96.31	13.805			
15,600.00	12,533.14	15,438.45	12,442.88	46.15	54.22	-86.11	-2,955.66	2,301.84	1,329.61	1,230.73	98.88	13.447			
15,700.00	12,534.02	15,538.44	12,443.40	47.37	55.55	-86.09	-3,055.66	2,302.75	1,329.68	1,228.21	101.46	13.105			
15,800.00	12,534.89	15,638.44	12,443.93	48.59	56.88	-86.08	-3,155.65	2,303.65	1,329.75	1,225.69	104.06	12.779			
15,900.00	12,535.76	15,738.44	12,444.45	49.83	58.22	-86.06	-3,255.64	2,304.56	1,329.82	1,223.17	106.65	12.468			
16,000.00	12,536.64	15,838.44	12,444.98	51.07	59.55	-86.05	-3,355.64	2,305.47	1,329.89	1,220.63	109.26	12.172			
16,100.00	12,537.51	15,938.44	12,445.50	52.32	60.89	-86.03	-3,455.63	2,306.38	1,329.96	1,218.09	111.87	11.888			
16,200.00	12,538.39	16,038.44	12,446.03	53.57	62.23	-86.02	-3,555.63	2,307.29	1,330.04	1,215.55	114.49	11.617			
16,300.00	12,539.26	16,138.44	12,446.55	54.83	63.57	-86.00	-3,655.62	2,308.20	1,330.11	1,213.00	117.11	11.358			
16,400.00	12,540.13	16,238.44	12,447.08	56.09	64.91	-85.99	-3,755.61	2,309.11	1,330.18	1,210.44	119.74	11.109			
16,500.00	12,541.01	16,338.44	12,447.60	57.36	66.25	-85.97	-3,855.61	2,310.02	1,330.25	1,207.88	122.37	10.871			
16,600.00	12,541.88	16,438.44	12,448.13	58.64	67.60	-85.96	-3,955.60	2,310.93	1,330.32	1,205.31	125.01	10.642			
16,700.00	12,542.75	16,538.44	12,448.65	59.91	68.94	-85.94	-4,055.60	2,311.83	1,330.40	1,202.75	127.65	10.422			
16,800.00	12,543.63	16,638.44	12,449.18	61.20	70.29	-85.93	-4,155.59	2,312.74	1,330.47	1,200.17	130.29	10.211			
16,900.00	12,544.50	16,738.44	12,449.70	62.48	71.63	-85.91	-4,255.58	2,313.65	1,330.54	1,197.60	132.94	10.008			
17,000.00	12,545.37	16,838.44	12,450.23	63.77	72.98	-85.90	-4,355.58	2,314.56	1,330.61	1,195.02	135.59	9.813			
17,100.00	12,546.25	16,938.44	12,450.75	65.06	74.33	-85.88	-4,455.57	2,315.47	1,330.69	1,192.44	138.25	9.625			
17,200.00	12,547.12	17,038.44	12,451.28	66.36	75.68	-85.87	-4,555.57	2,316.38	1,330.76	1,189.85	140.91	9.444			
17,300.00	12,547.99	17,138.43	12,451.80	67.66	77.03	-85.86	-4,655.56	2,317.29	1,330.83	1,187.26	143.57	9.270			
17,400.00	12,548.87	17,238.43	12,452.33	68.96	78.38	-85.84	-4,755.55	2,318.20	1,330.90	1,184.67	146.23	9.101			
17,500.00	12,549.74	17,338.43	12,452.85	70.26	79.73	-85.83	-4,855.55	2,319.11	1,330.98	1,182.08	148.90	8.939			
17,600.00	12,550.62	17,438.43	12,453.38	71.57	81.08	-85.81									

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 85 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 216H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			Minimum Separation (usft)
20,600.00	12,576.82	20,438.41	12,469.13	111.47	121.82	-85.37	-7,955.36	2,347.28	1,333.28	1,101.03	232.25	5.741	
20,700.00	12,577.70	20,538.41	12,469.66	112.81	123.18	-85.35	-8,055.35	2,348.19	1,333.36	1,098.40	234.95	5.675	
20,800.00	12,578.57	20,638.41	12,470.18	114.16	124.54	-85.34	-8,155.34	2,349.10	1,333.43	1,095.77	237.66	5.611	
20,900.00	12,579.44	20,738.41	12,470.71	115.51	125.90	-85.32	-8,255.34	2,350.01	1,333.51	1,093.15	240.36	5.548	
21,000.00	12,580.32	20,838.41	12,471.23	116.85	127.27	-85.31	-8,355.33	2,350.92	1,333.58	1,090.52	243.06	5.487	
21,100.00	12,581.19	20,938.41	12,471.76	118.20	128.63	-85.29	-8,455.33	2,351.82	1,333.66	1,087.89	245.77	5.426	
21,200.00	12,582.06	21,038.41	12,472.28	119.55	129.99	-85.28	-8,555.32	2,352.73	1,333.74	1,085.26	248.47	5.368	
21,300.00	12,582.94	21,138.41	12,472.81	120.89	131.35	-85.26	-8,655.31	2,353.64	1,333.81	1,082.63	251.18	5.310	
21,400.00	12,583.81	21,238.41	12,473.33	122.24	132.72	-85.25	-8,755.31	2,354.55	1,333.89	1,080.00	253.88	5.254	
21,500.00	12,584.69	21,338.41	12,473.86	123.59	134.08	-85.23	-8,855.30	2,355.46	1,333.96	1,077.38	256.59	5.199	
21,600.00	12,585.56	21,438.41	12,474.38	124.94	135.44	-85.22	-8,955.30	2,356.37	1,334.04	1,074.75	259.30	5.145	
21,700.00	12,586.43	21,538.41	12,474.91	126.29	136.81	-85.20	-9,055.29	2,357.28	1,334.12	1,072.12	262.00	5.092	
21,800.00	12,587.31	21,638.41	12,475.43	127.64	138.17	-85.19	-9,155.28	2,358.19	1,334.19	1,069.49	264.71	5.040	
21,900.00	12,588.18	21,738.41	12,475.96	128.99	139.53	-85.18	-9,255.28	2,359.10	1,334.27	1,066.86	267.42	4.989	
22,000.00	12,589.05	21,838.41	12,476.48	130.34	140.90	-85.16	-9,355.27	2,360.00	1,334.35	1,064.22	270.12	4.940	
22,100.00	12,589.93	21,938.40	12,477.01	131.70	142.26	-85.15	-9,455.26	2,360.91	1,334.43	1,061.59	272.83	4.891	
22,200.00	12,590.80	22,038.40	12,477.53	133.05	143.62	-85.13	-9,555.26	2,361.82	1,334.50	1,058.96	275.54	4.843	
22,300.00	12,591.67	22,138.40	12,478.06	134.40	144.99	-85.12	-9,655.25	2,362.73	1,334.58	1,056.33	278.25	4.796	
22,400.00	12,592.55	22,238.40	12,478.58	135.75	146.35	-85.10	-9,755.25	2,363.64	1,334.66	1,053.70	280.96	4.750	
22,500.00	12,593.42	22,338.40	12,479.11	137.11	147.72	-85.09	-9,855.24	2,364.55	1,334.73	1,051.07	283.66	4.705	
22,600.00	12,594.30	22,438.40	12,479.63	138.46	149.08	-85.07	-9,955.23	2,365.46	1,334.81	1,048.44	286.37	4.661	
22,700.00	12,595.17	22,538.40	12,480.16	139.81	150.45	-85.06	-10,055.23	2,366.37	1,334.89	1,045.81	289.08	4.618	
22,800.00	12,596.04	22,638.40	12,480.68	141.17	151.81	-85.04	-10,155.22	2,367.27	1,334.97	1,043.18	291.79	4.575	
22,875.30	12,596.70	22,713.70	12,481.08	142.19	152.84	-85.03	-10,230.52	2,367.96	1,335.03	1,041.20	293.83	4.544	ES, SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 86 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 221H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance			Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
0.00	0.00	0.00	0.00	0.50	0.50	180.00	-235.00	0.00	235.00								
100.00	100.00	100.00	100.00	0.98	0.98	180.00	-235.00	0.00	235.00	233.04	1.96	119.765					
200.00	200.00	200.00	200.00	1.56	1.56	180.00	-235.00	0.00	235.00	231.88	3.12	75.266					
300.00	300.00	300.00	300.00	1.98	1.98	180.00	-235.00	0.00	235.00	231.04	3.96	59.309					
400.00	400.00	400.00	400.00	2.33	2.33	180.00	-235.00	0.00	235.00	230.34	4.66	50.442					
500.00	500.00	500.00	500.00	2.63	2.63	180.00	-235.00	0.00	235.00	229.73	5.27	44.600					
600.00	600.00	600.00	600.00	2.91	2.91	180.00	-235.00	0.00	235.00	229.18	5.82	40.377					
700.00	700.00	700.00	700.00	3.16	3.16	180.00	-235.00	0.00	235.00	228.67	6.33	37.139					
800.00	800.00	804.92	804.91	3.40	3.47	-179.77	-233.90	-0.93	233.95	227.10	6.85	34.173					
900.00	900.00	909.68	909.58	3.62	3.76	-179.08	-230.59	-3.70	230.82	223.49	7.33	31.495					
1,000.00	1,000.00	1,014.12	1,013.77	3.76	4.01	90.14	-225.11	-8.30	225.68	218.00	7.69	29.365					
1,100.00	1,099.98	1,114.46	1,113.73	4.00	4.14	92.24	-218.45	-13.89	219.38	211.38	8.00	27.420					
1,200.00	1,199.88	1,213.72	1,212.61	4.24	4.35	95.13	-211.82	-19.45	213.55	205.16	8.38	25.476					
1,300.00	1,299.63	1,312.68	1,311.19	4.46	4.55	98.85	-205.22	-24.99	208.63	199.88	8.75	23.831					
1,400.00	1,399.25	1,411.41	1,409.55	4.60	4.75	103.09	-198.62	-30.52	204.98	195.91	9.07	22.589					
1,500.00	1,498.87	1,510.14	1,507.91	4.78	4.94	107.44	-192.03	-36.06	202.52	193.08	9.44	21.461					
1,600.00	1,598.49	1,608.88	1,606.26	4.96	5.14	111.88	-185.44	-41.59	201.28	191.48	9.80	20.549					
1,649.36	1,647.66	1,657.61	1,654.81	5.05	5.23	114.08	-182.19	-44.32	201.13	191.16	9.97	20.173	CC				
1,700.00	1,698.11	1,707.61	1,704.62	5.14	5.33	116.34	-178.85	-47.12	201.29	191.14	10.15	19.831	ES				
1,800.00	1,797.73	1,806.34	1,802.98	5.32	5.52	120.78	-172.26	-52.65	202.54	192.04	10.50	19.283					
1,900.00	1,897.34	1,905.07	1,901.33	5.49	5.71	125.13	-165.66	-58.18	205.02	194.17	10.86	18.887					
2,000.00	1,996.96	2,003.80	1,999.69	5.67	5.90	129.36	-159.07	-63.71	208.68	197.48	11.21	18.622					
2,100.00	2,096.58	2,102.54	2,098.04	5.85	6.09	133.43	-152.48	-69.24	213.47	201.91	11.56	18.469					
2,200.00	2,196.20	2,201.27	2,196.40	6.04	6.29	137.30	-145.89	-74.77	219.30	207.37	11.93	18.389					
2,300.00	2,295.72	2,296.93	2,291.60	6.23	6.48	147.40	-139.11	-81.17	227.89	215.62	12.28	18.564					
2,400.00	2,394.97	2,391.19	2,385.18	6.43	6.68	155.64	-131.61	-89.65	241.54	228.88	12.66	19.080					
2,500.00	2,493.89	2,483.87	2,476.91	6.64	6.88	162.50	-123.44	-100.09	260.47	247.41	13.05	19.954					
2,600.00	2,592.40	2,574.72	2,566.49	6.85	7.08	168.34	-114.67	-112.34	284.74	271.29	13.45	21.169					
2,700.00	2,690.45	2,663.49	2,653.68	7.07	7.27	173.32	-105.39	-126.25	314.25	300.41	13.84	22.705					
2,800.00	2,787.96	2,753.74	2,741.99	7.28	7.45	177.64	-95.37	-141.94	348.52	334.28	14.24	24.478					
2,900.00	2,884.87	2,845.21	2,831.45	7.49	7.63	-178.78	-85.16	-157.99	386.07	371.42	14.65	26.361					
3,000.00	2,981.46	2,936.23	2,920.49	7.68	7.81	-176.76	-75.00	-173.95	425.29	410.27	15.02	28.310					
3,100.00	3,078.05	3,027.26	3,009.52	7.87	8.00	-175.08	-64.84	-189.92	464.89	449.49	15.40	30.185					
3,200.00	3,174.64	3,118.28	3,098.56	8.06	8.18	-173.66	-54.68	-205.89	504.78	489.00	15.78	31.986					
3,300.00	3,271.24	3,209.31	3,187.59	8.26	8.37	-172.45	-44.52	-221.86	544.90	528.73	16.16	33.711					
3,400.00	3,367.83	3,300.33	3,276.63	8.51	8.57	-171.40	-34.36	-237.82	585.19	568.64	16.55	35.363					
3,500.00	3,464.42	3,391.36	3,365.67	8.80	8.76	-170.48	-24.20	-253.79	625.63	608.70	16.94	36.942					
3,600.00	3,561.01	3,482.38	3,454.70	9.09	8.96	-169.67	-14.04	-269.76	666.19	648.87	17.33	38.452					
3,700.00	3,657.60	3,573.41	3,543.74	9.38	9.16	-168.96	-3.88	-285.72	706.85	689.13	17.72	39.896					
3,800.00	3,754.20	3,664.43	3,632.77	9.68	9.37	-168.33	6.28	-301.69	747.59	729.48	18.11	41.277					
3,900.00	3,850.79	3,755.46	3,721.81	9.98	9.58	-167.75	16.44	-317.66	788.40	769.89	18.51	42.597					
4,000.00	3,947.38	3,846.48	3,810.84	10.28	9.79	-167.24	26.60	-333.63	829.27	810.36	18.91	43.860					
4,100.00	4,043.97	3,937.51	3,899.88	10.59	10.01	-166.77	36.76	-349.59	870.19	850.88	19.31	45.068					
4,200.00	4,140.56	4,028.53	3,988.92	10.90	10.23	-166.35	46.92	-365.56	911.15	891.44	19.71	46.225					
4,300.00	4,237.16	4,119.56	4,077.95	11.21	10.46	-165.96	57.08	-381.53	952.15	932.04	20.12	47.332					
4,400.00	4,333.75	4,210.58	4,166.99	11.52	10.68	-165.60	67.24	-397.50	993.19	972.66	20.52	48.393					
4,500.00	4,430.34	4,301.61	4,256.02	11.84	10.91	-165.28	77.40	-413.46	1,034.25	1,013.32	20.93	49.409					
4,600.00	4,526.93	4,392.63	4,345.06	12.16	11.14	-164.97	87.56	-429.43	1,075.34	1,054.00	21.34	50.383					
4,700.00	4,623.53	4,483.66	4,434.10	12.48	11.38	-164.69	97.72	-445.40	1,116.46	1,094.70	21.76	51.318					
4,800.00	4,720.12	4,574.68	4,523.13	12.80	11.61	-164.43	107.88	-461.36	1,157.59	1,135.42	22.17	52.215					
4,900.00	4,816.71	4,665.71	4,612.17	13.12	11.85	-164.19	118.04	-477.33	1,198.74	1,176.16	22.59	53.076					
5,000.00	4,913.30	4,756.73	4,701.20	13.45	12.09	-163.96	128.20	-493.30	1,239.92	1,216.91	23.00	53.903					

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 221H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)		
5,100.00	5,009.89	4,847.76	4,790.24	13.78	12.32	-163.75	138.36	-509.27	1,281.10	1,257.68	23.42	54.698
5,200.00	5,106.49	4,938.79	4,879.28	14.10	12.56	-163.55	148.52	-525.23	1,322.30	1,298.46	23.84	55.462
5,300.00	5,203.08	5,029.81	4,968.31	14.43	12.80	-163.36	158.68	-541.20	1,363.51	1,339.25	24.26	56.197
5,400.00	5,299.67	5,120.84	5,057.35	14.75	13.04	-163.20	168.84	-557.17	1,404.73	1,380.05	24.68	56.926
5,500.00	5,396.65	5,212.44	5,146.95	15.07	13.29	-163.20	179.07	-573.24	1,444.62	1,419.51	25.11	57.531
5,600.00	5,494.23	5,304.97	5,237.46	15.36	13.54	-163.17	189.39	-589.47	1,482.21	1,456.67	25.54	58.032
5,700.00	5,592.35	5,398.37	5,328.82	15.62	13.78	-163.11	199.82	-605.85	1,517.49	1,491.52	25.97	58.431
5,800.00	5,690.94	5,534.73	5,462.59	15.86	14.12	-162.94	213.98	-628.10	1,549.32	1,522.76	26.57	58.318
5,900.00	5,789.93	5,681.33	5,607.36	16.07	14.45	-162.81	226.34	-647.54	1,575.78	1,548.60	27.18	57.983
6,000.00	5,889.26	5,831.38	5,756.35	16.25	14.72	-162.74	235.90	-662.56	1,596.65	1,568.91	27.74	57.554
6,100.00	5,988.86	5,984.10	5,908.57	16.41	14.95	-162.72	242.39	-672.76	1,611.79	1,583.54	28.25	57.047
6,200.00	6,088.66	6,138.62	6,062.97	16.53	15.13	-162.74	245.64	-677.86	1,621.10	1,592.40	28.70	56.494
6,300.00	6,188.59	6,264.24	6,188.59	16.64	15.22	-162.80	246.00	-678.43	1,625.00	1,596.02	28.98	56.070
6,400.00	6,288.58	6,364.24	6,288.58	16.71	15.29	-90.39	246.00	-678.43	1,626.05	1,596.91	29.13	55.815
6,500.00	6,388.58	6,464.24	6,388.58	16.76	15.36	-90.39	246.00	-678.43	1,626.05	1,596.79	29.26	55.574
6,600.00	6,488.58	6,564.24	6,488.58	16.82	15.43	-90.39	246.00	-678.43	1,626.05	1,596.66	29.39	55.335
6,700.00	6,588.58	6,664.24	6,588.58	16.88	15.50	-90.39	246.00	-678.43	1,626.05	1,596.53	29.51	55.096
6,800.00	6,688.58	6,764.24	6,688.58	16.94	15.57	-90.39	246.00	-678.43	1,626.05	1,596.41	29.64	54.860
6,900.00	6,788.58	6,864.24	6,788.58	17.00	15.64	-90.39	246.00	-678.43	1,626.05	1,596.28	29.77	54.624
7,000.00	6,888.58	6,964.24	6,888.58	17.05	15.71	-90.39	246.00	-678.43	1,626.05	1,596.15	29.90	54.390
7,100.00	6,988.58	7,064.24	6,988.58	17.11	15.78	-90.39	246.00	-678.43	1,626.05	1,596.02	30.02	54.158
7,200.00	7,088.58	7,164.24	7,088.58	17.17	15.85	-90.39	246.00	-678.43	1,626.05	1,595.89	30.15	53.926
7,300.00	7,188.58	7,264.24	7,188.58	17.23	15.92	-90.39	246.00	-678.43	1,626.05	1,595.77	30.28	53.697
7,400.00	7,288.58	7,364.24	7,288.58	17.29	15.99	-90.39	246.00	-678.43	1,626.05	1,595.64	30.41	53.468
7,500.00	7,388.58	7,464.24	7,388.58	17.35	16.06	-90.39	246.00	-678.43	1,626.05	1,595.51	30.54	53.241
7,600.00	7,488.58	7,564.24	7,488.58	17.41	16.13	-90.39	246.00	-678.43	1,626.05	1,595.38	30.67	53.015
7,700.00	7,588.58	7,664.24	7,588.58	17.47	16.20	-90.39	246.00	-678.43	1,626.05	1,595.25	30.80	52.791
7,800.00	7,688.58	7,764.24	7,688.58	17.53	16.27	-90.39	246.00	-678.43	1,626.05	1,595.12	30.93	52.568
7,900.00	7,788.58	7,864.24	7,788.58	17.59	16.34	-90.39	246.00	-678.43	1,626.05	1,594.98	31.06	52.347
8,000.00	7,888.58	7,964.24	7,888.58	17.65	16.42	-90.39	246.00	-678.43	1,626.05	1,594.85	31.19	52.126
8,100.00	7,988.58	8,064.24	7,988.58	17.71	16.49	-90.39	246.00	-678.43	1,626.05	1,594.72	31.33	51.907
8,200.00	8,088.58	8,164.24	8,088.58	17.77	16.56	-90.39	246.00	-678.43	1,626.05	1,594.59	31.46	51.690
8,300.00	8,188.58	8,264.24	8,188.58	17.83	16.63	-90.39	246.00	-678.43	1,626.05	1,594.46	31.59	51.474
8,400.00	8,288.58	8,364.24	8,288.58	17.89	16.70	-90.39	246.00	-678.43	1,626.05	1,594.33	31.72	51.259
8,500.00	8,388.58	8,464.24	8,388.58	17.95	16.77	-90.39	246.00	-678.43	1,626.05	1,594.19	31.86	51.045
8,600.00	8,488.58	8,564.24	8,488.58	18.02	16.85	-90.39	246.00	-678.43	1,626.05	1,594.06	31.99	50.833
8,700.00	8,588.58	8,664.24	8,588.58	18.08	16.92	-90.39	246.00	-678.43	1,626.05	1,593.93	32.12	50.622
8,800.00	8,688.58	8,764.24	8,688.58	18.14	16.99	-90.39	246.00	-678.43	1,626.05	1,593.79	32.25	50.413
8,900.00	8,788.58	8,864.24	8,788.58	18.20	17.06	-90.39	246.00	-678.43	1,626.05	1,593.66	32.39	50.204
9,000.00	8,888.58	8,964.24	8,888.58	18.26	17.13	-90.39	246.00	-678.43	1,626.05	1,593.53	32.52	49.997
9,100.00	8,988.58	9,064.24	8,988.58	18.32	17.21	-90.39	246.00	-678.43	1,626.05	1,593.39	32.66	49.792
9,200.00	9,088.58	9,164.24	9,088.58	18.39	17.28	-90.39	246.00	-678.43	1,626.05	1,593.26	32.79	49.587
9,300.00	9,188.58	9,264.24	9,188.58	18.45	17.35	-90.39	246.00	-678.43	1,626.05	1,593.12	32.93	49.384
9,400.00	9,288.58	9,364.24	9,288.58	18.51	17.42	-90.39	246.00	-678.43	1,626.05	1,592.99	33.06	49.183
9,500.00	9,388.58	9,464.24	9,388.58	18.57	17.50	-90.39	246.00	-678.43	1,626.05	1,592.85	33.20	48.982
9,600.00	9,488.58	9,564.24	9,488.58	18.64	17.57	-90.39	246.00	-678.43	1,626.05	1,592.72	33.33	48.783
9,700.00	9,588.58	9,664.24	9,588.58	18.70	17.64	-90.39	246.00	-678.43	1,626.05	1,592.58	33.47	48.585
9,800.00	9,688.58	9,764.24	9,688.58	18.76	17.71	-90.39	246.00	-678.43	1,626.05	1,592.44	33.60	48.388
9,900.00	9,788.58	9,864.24	9,788.58	18.83	17.79	-90.39	246.00	-678.43	1,626.05	1,592.31	33.74	48.192
10,000.00	9,888.58	9,964.24	9,888.58	18.89	17.86	-90.39	246.00	-678.43	1,626.05	1,592.17	33.88	47.998
10,100.00	9,988.58	10,064.24	9,988.58	18.95	17.93	-90.39	246.00	-678.43	1,626.05	1,592.03	34.01	47.805
10,200.00	10,088.58	10,164.24	10,088.58	19.02	18.01	-90.39	246.00	-678.43	1,626.05	1,591.90	34.15	47.613

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 88 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 221H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft	
Reference Offset				Semi Major Axis		Offset Wellbore Centre				Distance		Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
10,300.00	10,188.58	10,264.24	10,188.58	19.08	18.08	-90.39	246.00	-678.43	1,626.05	1,591.76	34.29	47.423					
10,400.00	10,288.58	10,364.24	10,288.58	19.15	18.15	-90.39	246.00	-678.43	1,626.05	1,591.62	34.43	47.233					
10,500.00	10,388.58	10,464.24	10,388.58	19.21	18.23	-90.39	246.00	-678.43	1,626.05	1,591.48	34.56	47.045					
10,600.00	10,488.58	10,564.24	10,488.58	19.27	18.30	-90.39	246.00	-678.43	1,626.05	1,591.35	34.70	46.858					
10,700.00	10,588.58	10,664.24	10,588.58	19.34	18.37	-90.39	246.00	-678.43	1,626.05	1,591.21	34.84	46.673					
10,800.00	10,688.58	10,764.24	10,688.58	19.40	18.45	-90.39	246.00	-678.43	1,626.05	1,591.07	34.98	46.488					
10,900.00	10,788.58	10,864.24	10,788.58	19.47	18.52	-90.39	246.00	-678.43	1,626.05	1,590.93	35.12	46.304					
11,000.00	10,888.58	10,964.24	10,888.58	19.53	18.59	-90.39	246.00	-678.43	1,626.05	1,590.79	35.26	46.122					
11,100.00	10,988.58	11,064.24	10,988.58	19.60	18.67	-90.39	246.00	-678.43	1,626.05	1,590.65	35.39	45.941					
11,200.00	11,088.58	11,164.24	11,088.58	19.66	18.74	-90.39	246.00	-678.43	1,626.05	1,590.51	35.53	45.761					
11,300.00	11,188.58	11,264.24	11,188.58	19.73	18.82	-90.39	246.00	-678.43	1,626.05	1,590.37	35.67	45.582					
11,400.00	11,288.58	11,364.24	11,288.58	19.79	18.89	-90.39	246.00	-678.43	1,626.05	1,590.24	35.81	45.405					
11,500.00	11,388.58	11,464.24	11,388.58	19.86	18.96	-90.39	246.00	-678.43	1,626.05	1,590.10	35.95	45.228					
11,600.00	11,488.58	11,564.24	11,488.58	19.92	19.04	-90.39	246.00	-678.43	1,626.05	1,589.96	36.09	45.053					
11,700.00	11,588.58	11,664.24	11,588.58	19.99	19.11	-90.39	246.00	-678.43	1,626.05	1,589.82	36.23	44.878					
11,800.00	11,688.58	11,764.24	11,688.58	20.05	19.19	-90.39	246.00	-678.43	1,626.05	1,589.68	36.37	44.705					
11,900.00	11,788.58	11,864.24	11,788.58	20.12	19.26	-90.39	246.00	-678.43	1,626.05	1,589.53	36.51	44.533					
12,000.00	11,888.58	11,964.24	11,888.58	20.19	19.34	-90.39	246.00	-678.43	1,626.05	1,589.39	36.65	44.362					
12,000.00	11,888.58	11,964.24	11,888.58	20.19	19.34	-90.39	246.00	-678.43	1,626.05	1,589.39	36.65	44.362					
12,100.00	11,988.51	12,064.17	11,988.51	20.25	19.41	90.18	246.00	-678.43	1,626.05	1,589.32	36.74	44.262					
12,200.00	12,086.82	12,162.47	12,086.82	20.31	19.48	90.78	246.00	-678.43	1,626.21	1,589.45	36.76	44.242					
12,300.00	12,180.57	12,256.23	12,180.57	20.35	19.55	91.83	246.00	-678.43	1,627.05	1,590.31	36.74	44.286					
12,400.00	12,266.93	12,342.58	12,266.93	20.39	19.61	93.09	246.00	-678.43	1,629.59	1,592.91	36.69	44.421					
12,500.00	12,343.26	12,418.80	12,343.03	20.44	19.65	94.18	242.76	-678.74	1,635.10	1,598.54	36.56	44.722					
12,600.00	12,407.24	12,499.49	12,422.39	20.52	19.68	95.07	228.61	-680.10	1,644.27	1,607.89	36.38	45.191					
12,700.00	12,456.94	12,589.04	12,507.14	20.67	19.70	95.85	200.12	-682.85	1,657.09	1,620.88	36.21	45.765					
12,800.00	12,490.84	12,692.29	12,597.93	20.88	19.72	96.60	151.46	-687.53	1,673.27	1,637.17	36.10	46.345					
12,900.00	12,507.91	12,817.74	12,694.21	21.18	19.76	97.47	71.80	-695.20	1,692.17	1,655.99	36.18	46.766					
13,000.00	12,510.43	12,983.07	12,790.41	21.56	19.90	99.68	-61.34	-708.02	1,712.00	1,675.39	36.61	46.759					
13,100.00	12,511.30	13,209.66	12,852.95	22.01	20.32	101.55	-276.60	-728.75	1,727.48	1,690.02	37.46	46.121					
13,200.00	12,512.18	13,455.06	12,856.71	22.52	21.08	101.48	-521.32	-745.13	1,734.99	1,696.30	38.69	44.843					
13,300.00	12,513.05	13,612.78	12,858.09	23.10	21.69	101.47	-679.02	-745.43	1,735.65	1,695.73	39.92	43.475					
13,400.00	12,513.92	13,712.78	12,858.97	23.73	22.15	101.47	-779.02	-744.57	1,735.65	1,694.60	41.05	42.280					
13,500.00	12,514.80	13,812.78	12,859.85	24.41	22.66	101.47	-879.01	-743.71	1,735.65	1,693.33	42.32	41.011					
13,600.00	12,515.67	13,912.78	12,860.73	25.15	23.23	101.47	-979.00	-742.85	1,735.66	1,691.94	43.72	39.698					
13,700.00	12,516.55	14,012.78	12,861.60	25.93	23.86	101.47	-1,078.99	-741.99	1,735.66	1,690.42	45.24	38.367					
13,800.00	12,517.42	14,112.78	12,862.48	26.76	24.54	101.47	-1,178.99	-741.13	1,735.66	1,688.80	46.86	37.039					
13,900.00	12,518.29	14,212.78	12,863.36	27.63	25.28	101.47	-1,278.98	-740.27	1,735.66	1,687.08	48.58	35.729					
14,000.00	12,519.17	14,312.78	12,864.24	28.53	26.07	101.47	-1,378.97	-739.41	1,735.66	1,685.28	50.38	34.450					
14,100.00	12,520.04	14,412.78	12,865.12	29.47	26.91	101.47	-1,478.96	-738.55	1,735.66	1,683.40	52.26	33.211					
14,200.00	12,520.91	14,512.78	12,865.99	30.44	27.79	101.47	-1,578.96	-737.68	1,735.67	1,681.45	54.21	32.017					
14,300.00	12,521.79	14,612.78	12,866.87	31.44	28.71	101.47	-1,678.95	-736.82	1,735.67	1,679.45	56.22	30.872					
14,400.00	12,522.66	14,712.78	12,867.75	32.46	29.66	101.47	-1,778.94	-735.96	1,735.67	1,677.38	58.29	29.777					
14,500.00	12,523.53	14,812.78	12,868.63	33.51	30.65	101.47	-1,878.93	-735.10	1,735.67	1,675.27	60.40	28.734					
14,600.00	12,524.41	14,912.78	12,869.50	34.58	31.67	101.47	-1,978.93	-734.24	1,735.67	1,673.11	62.56	27.742					
14,700.00	12,525.28	15,012.78	12,870.38	35.67	32.71	101.47	-2,078.92	-733.38	1,735.67	1,670.91	64.76	26.800					
14,800.00	12,526.16	15,112.78	12,871.26	36.78	33.78	101.47	-2,178.91	-732.52	1,735.68	1,668.67	67.00	25.905					
14,900.00	12,527.03	15,212.78	12,872.14	37.90	34.88	101.47	-2,278.90	-731.66	1,735.68	1,666.41	69.27	25.057					
15,000.00	12,527.90	15,312.78	12,873.02	39.04	35.99	101.47	-2,378.90	-730.80	1,735.68	1,664.11	71.57	24.252					
15,100.00	12,528.78	15,412.78	12,873.89	40.20	37.12	101.47	-2,478.89	-729.94	1,735.68	1,661.79	73.89	23.489					
15,200.00	12,529.65	15,512.78	12,874.77	41.37	38.26	101.47	-2,578.88	-729.08	1,735.68	1,659.44	76.24	22.765					
15,300.00	12,530.52	15,612.78	12,875.65	42.55	39.42	101.47	-2,678.87	-728.22	1,735.68	1,657.07	78.61	22.078					

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 221H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (")	Offset Wellbore Centre			Distance		Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)		
15,400.00	12,531.40	15,712.78	12,876.53	43.74	40.60	101.47	-2,778.87	-727.36	1,735.69	1,654.68	81.01	21.427	
15,500.00	12,532.27	15,812.78	12,877.41	44.94	41.78	101.47	-2,878.86	-726.50	1,735.69	1,652.27	83.42	20.808	
15,600.00	12,533.14	15,912.78	12,878.28	46.15	42.98	101.47	-2,978.85	-725.64	1,735.69	1,649.85	85.84	20.220	
15,700.00	12,534.02	16,012.78	12,879.16	47.37	44.19	101.47	-3,078.84	-724.78	1,735.69	1,647.41	88.28	19.660	
15,800.00	12,534.89	16,112.78	12,880.04	48.59	45.41	101.47	-3,178.84	-723.92	1,735.69	1,644.95	90.74	19.128	
15,900.00	12,535.76	16,212.78	12,880.92	49.83	46.63	101.47	-3,278.83	-723.06	1,735.69	1,642.48	93.21	18.621	
16,000.00	12,536.64	16,312.78	12,881.80	51.07	47.87	101.47	-3,378.82	-722.20	1,735.70	1,640.00	95.69	18.139	
16,100.00	12,537.51	16,412.78	12,882.67	52.32	49.11	101.47	-3,478.81	-721.34	1,735.70	1,637.51	98.18	17.678	
16,200.00	12,538.39	16,512.78	12,883.55	53.57	50.36	101.47	-3,578.81	-720.48	1,735.70	1,635.01	100.69	17.239	
16,300.00	12,539.26	16,612.78	12,884.43	54.83	51.62	101.47	-3,678.80	-719.62	1,735.70	1,632.50	103.20	16.819	
16,400.00	12,540.13	16,712.78	12,885.31	56.09	52.88	101.47	-3,778.79	-718.76	1,735.70	1,629.98	105.72	16.418	
16,500.00	12,541.01	16,812.78	12,886.18	57.36	54.14	101.47	-3,878.78	-717.90	1,735.70	1,627.46	108.25	16.034	
16,600.00	12,541.88	16,912.78	12,887.06	58.64	55.41	101.47	-3,978.78	-717.04	1,735.71	1,624.92	110.79	15.667	
16,700.00	12,542.75	17,012.78	12,887.94	59.91	56.69	101.47	-4,078.77	-716.18	1,735.71	1,622.38	113.33	15.316	
16,800.00	12,543.63	17,112.78	12,888.82	61.20	57.97	101.47	-4,178.76	-715.32	1,735.71	1,619.83	115.88	14.978	
16,900.00	12,544.50	17,212.78	12,889.70	62.48	59.26	101.47	-4,278.75	-714.46	1,735.71	1,617.27	118.44	14.655	
17,000.00	12,545.37	17,312.78	12,890.57	63.77	60.55	101.47	-4,378.75	-713.59	1,735.71	1,614.71	121.00	14.345	
17,100.00	12,546.25	17,412.78	12,891.45	65.06	61.84	101.47	-4,478.74	-712.73	1,735.71	1,612.15	123.57	14.047	
17,200.00	12,547.12	17,512.78	12,892.33	66.36	63.13	101.47	-4,578.73	-711.87	1,735.72	1,609.57	126.14	13.760	
17,300.00	12,547.99	17,612.78	12,893.21	67.66	64.43	101.47	-4,678.72	-711.01	1,735.72	1,607.00	128.72	13.484	
17,400.00	12,548.87	17,712.78	12,894.09	68.96	65.73	101.47	-4,778.72	-710.15	1,735.72	1,604.42	131.30	13.219	
17,500.00	12,549.74	17,812.78	12,894.96	70.26	67.04	101.47	-4,878.71	-709.29	1,735.72	1,601.83	133.89	12.964	
17,600.00	12,550.62	17,912.78	12,895.84	71.57	68.35	101.47	-4,978.70	-708.43	1				

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 90 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 221H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)							Rule Assigned:				Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
20,600.00	12,576.82	20,912.78	12,922.18	111.47	108.29	101.48	-7,978.47	-682.62	1,735.77	1,520.41	215.36	8.060	
20,700.00	12,577.70	21,012.78	12,923.06	112.81	109.64	101.48	-8,078.47	-681.76	1,735.77	1,517.76	218.01	7.962	
20,800.00	12,578.57	21,112.78	12,923.93	114.16	110.99	101.48	-8,178.46	-680.90	1,735.77	1,515.11	220.67	7.866	
20,900.00	12,579.44	21,212.78	12,924.81	115.51	112.33	101.48	-8,278.45	-680.04	1,735.78	1,512.46	223.32	7.773	
21,000.00	12,580.32	21,312.78	12,925.69	116.85	113.68	101.48	-8,378.44	-679.18	1,735.78	1,509.80	225.98	7.681	
21,100.00	12,581.19	21,412.78	12,926.57	118.20	115.03	101.48	-8,478.44	-678.32	1,735.78	1,507.15	228.63	7.592	
21,200.00	12,582.06	21,512.78	12,927.45	119.55	116.38	101.48	-8,578.43	-677.46	1,735.78	1,504.49	231.29	7.505	
21,300.00	12,582.94	21,612.78	12,928.32	120.89	117.73	101.48	-8,678.42	-676.60	1,735.78	1,501.84	233.95	7.420	
21,400.00	12,583.81	21,712.78	12,929.20	122.24	119.08	101.48	-8,778.41	-675.74	1,735.78	1,499.18	236.61	7.336	
21,500.00	12,584.69	21,812.78	12,930.08	123.59	120.43	101.48	-8,878.41	-674.88	1,735.79	1,496.52	239.26	7.255	
21,600.00	12,585.56	21,912.78	12,930.96	124.94	121.78	101.48	-8,978.40	-674.02	1,735.79	1,493.86	241.92	7.175	
21,700.00	12,586.43	22,012.78	12,931.84	126.29	123.13	101.48	-9,078.39	-673.16	1,735.79	1,491.20	244.59	7.097	
21,800.00	12,587.31	22,112.78	12,932.71	127.64	124.48	101.48	-9,178.38	-672.30	1,735.79	1,488.54	247.25	7.020	
21,900.00	12,588.18	22,212.78	12,933.59	128.99	125.84	101.48	-9,278.38	-671.44	1,735.79	1,485.88	249.91	6.946	
22,000.00	12,589.05	22,312.78	12,934.47	130.34	127.19	101.48	-9,378.37	-670.58	1,735.79	1,483.22	252.57	6.872	
22,100.00	12,589.93	22,412.78	12,935.35	131.70	128.54	101.48	-9,478.36	-669.72	1,735.80	1,480.56	255.23	6.801	
22,200.00	12,590.80	22,512.78	12,936.22	133.05	129.90	101.48	-9,578.35	-668.86	1,735.80	1,477.90	257.90	6.731	
22,300.00	12,591.67	22,612.78	12,937.10	134.40	131.25	101.48	-9,678.35	-668.00	1,735.80	1,475.24	260.56	6.662	
22,400.00	12,592.55	22,712.78	12,937.98	135.75	132.60	101.48	-9,778.34	-667.14	1,735.80	1,472.57	263.23	6.594	
22,500.00	12,593.42	22,812.78	12,938.86	137.11	133.96	101.48	-9,878.33	-666.28	1,735.80	1,469.91	265.89	6.528	
22,600.00	12,594.30	22,912.78	12,939.74	138.46	135.31	101.48	-9,978.32	-665.42	1,735.80	1,467.24	268.56	6.463	
22,700.00	12,595.17	23,012.78	12,940.61	139.81	136.67	101.48	-10,078.31	-664.55	1,735.81	1,464.58	271.23	6.400	
22,800.00	12,596.04	23,112.78	12,941.49	141.17	138.01	101.48	-10,178.31	-663.69	1,735.81	1,461.93	273.87	6.338	
22,875.30	12,596.70	23,188.08	12,942.15	142.19	138.93	101.48	-10,253.60	-663.05	1,735.81	1,460.04	275.77	6.294	SF

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 222H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)														Rule Assigned:	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Semi Reference (usft)	Major Offset (usft)	Highside Toolface (°)	Offset Wellbore Centre +N/-S (usft)	+E/-W (usft)	Distance Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
0.00	0.00	0.00	1.00	0.50	0.50	180.00	-50.00	0.00	50.01						
100.00	100.00	99.00	100.00	0.98	0.97	180.00	-50.00	0.00	50.00	48.05	1.95	25.576			
200.00	200.00	199.00	200.00	1.56	1.56	180.00	-50.00	0.00	50.00	46.88	3.12	16.045			
300.00	300.00	299.00	300.00	1.98	1.98	180.00	-50.00	0.00	50.00	46.04	3.96	12.632			
400.00	400.00	399.00	400.00	2.33	2.33	180.00	-50.00	0.00	50.00	45.34	4.66	10.740			
500.00	500.00	499.00	500.00	2.63	2.63	180.00	-50.00	0.00	50.00	44.73	5.27	9.495			
600.00	600.00	599.00	600.00	2.91	2.91	180.00	-50.00	0.00	50.00	44.18	5.82	8.595			
700.00	700.00	699.00	700.00	3.16	3.16	180.00	-50.00	0.00	50.00	43.67	6.33	7.905			
800.00	800.00	799.00	800.00	3.40	3.40	180.00	-50.00	0.00	50.00	43.20	6.80	7.354			
900.00	900.00	899.00	900.00	3.62	3.62	180.00	-50.00	0.00	50.00	42.75	7.25	6.901			
1,000.00	1,000.00	999.00	1,000.00	3.76	3.83	88.06	-50.00	0.00	50.00	42.40	7.59	6.584			
1,095.46	1,095.44	1,094.44	1,095.44	3.99	4.03	90.00	-50.00	0.00	49.97	42.00	7.97	6.271	CC		
1,100.00	1,099.98	1,098.98	1,099.98	4.00	4.04	90.16	-50.00	0.00	49.97	41.98	7.99	6.257			
1,200.00	1,199.88	1,198.88	1,199.88	4.24	4.23	95.24	-50.00	0.00	50.18	41.81	8.37	5.998	ES		
1,300.00	1,299.63	1,298.63	1,299.63	4.46	4.42	103.08	-50.00	0.00	51.31	42.57	8.74	5.871			
1,400.00	1,399.25	1,398.25	1,399.25	4.60	4.60	112.08	-50.00	0.00	53.95	44.88	9.07	5.950			
1,500.00	1,498.87	1,497.87	1,498.87	4.78	4.77	120.08	-50.00	0.00	57.80	48.37	9.44	6.125			
1,600.00	1,598.49	1,598.63	1,599.62	4.96	4.98	126.24	-49.84	1.26	61.74	51.93	9.81	6.291			
1,700.00	1,698.11	1,699.74	1,700.64	5.14	5.17	130.10	-49.36	5.18	64.27	54.10	10.18	6.316			
1,800.00	1,797.73	1,801.02	1,801.71	5.32	5.36	132.23	-48.56	11.77	64.98	54.45	10.53	6.172			
1,900.00	1,897.34	1,901.44	1,901.76	5.49	5.44	133.20	-47.51	20.32	64.16	53.37	10.79	5.947			
2,000.00	1,996.96	2,001.43	2,001.37	5.67	5.60	134.12	-46.44	28.97	63.25	52.13	11.12	5.687			
2,100.00	2,096.58	2,101.42	2,100.98	5.85	5.75	135.06	-45.38	37.62	62.35	50.90	11.46	5.443			
2,200.00	2,196.20	2,201.42	2,200.59	6.04	5.91	136.03	-44.32	46.27	61.47	49.67	11.80	5.209			
2,300.00	2,295.72	2,303.02	2,301.70	6.23	6.08	143.61	-42.37	56.07	60.47	48.32	12.15	4.977			
2,400.00	2,394.97	2,404.58	2,402.50	6.43	6.27	149.79	-38.66	67.90	59.39	46.86	12.53	4.740			
2,500.00	2,493.89	2,506.10	2,502.92	6.64	6.46	155.35	-33.21	81.76	58.31	45.39	12.92	4.512			
2,600.00	2,592.40	2,607.57	2,602.88	6.85	6.66	160.85	-26.02	97.62	57.32	43.99	13.33	4.300			
2,700.00	2,690.45	2,708.88	2,702.20	7.07	6.86	166.58	-17.10	115.45	56.56	42.81	13.75	4.114			
2,715.13	2,705.24	2,723.99	2,716.99	7.10	6.88	167.46	-15.66	118.24	56.53	42.72	13.81	4.093			
2,800.00	2,787.96	2,808.77	2,799.92	7.28	7.02	172.22	-7.57	133.90	57.59	43.42	14.16	4.066			
2,900.00	2,884.87	2,908.61	2,897.57	7.49	7.19	177.13	1.97	152.33	61.54	46.97	14.58	4.222			
3,000.00	2,981.46	3,008.39	2,995.18	7.68	7.37	-179.62	11.49	170.75	67.00	52.04	14.96	4.478			
3,100.00	3,078.05	3,108.18	3,092.78	7.87	7.54	-176.87	21.02	189.17	72.65	57.30	15.35	4.733			
3,200.00	3,174.64	3,207.96	3,190.39	8.06	7.72	-174.51	30.55	207.60	78.43	62.70	15.74	4.984			
3,300.00	3,271.24	3,307.75	3,287.99	8.26	7.90	-172.49	40.08	226.02	84.33	68.21	16.13	5.229			
3,400.00	3,367.83	3,407.53	3,385.60	8.51	8.08	-170.73	49.61	244.44	90.32	73.80	16.52	5.467			
3,500.00	3,464.42	3,507.32	3,483.20	8.80	8.31	-169.19	59.13	262.86	96.39	79.47	16.92	5.697			
3,600.00	3,561.01	3,607.10	3,580.81	9.09	8.54	-167.83	68.66	281.29	102.52	85.19	17.32	5.918			
3,700.00	3,657.60	3,706.89	3,678.41	9.38	8.77	-166.63	78.19	299.71	108.69	90.96	17.73	6.130			
3,800.00	3,754.20	3,806.67	3,776.02	9.68	9.00	-165.56	87.72	318.13	114.91	96.77	18.14	6.334			
3,900.00	3,850.79	3,906.45	3,873.62	9.98	9.24	-164.59	97.24	336.55	121.17	102.61	18.56	6.529			
4,000.00	3,947.38	4,006.24	3,971.23	10.28	9.48	-163.73	106.77	354.98	127.46	108.48	18.98	6.715			
4,100.00	4,043.97	4,106.02	4,068.83	10.59	9.72	-162.94	116.30	373.40	133.77	114.37	19.41	6.894			
4,200.00	4,140.56	4,205.81	4,166.44	10.90	9.97	-162.22	125.83	391.82	140.11	120.27	19.83	7.064			
4,300.00	4,237.16	4,305.59	4,264.04	11.21	10.22	-161.57	135.35	410.24	146.46	126.20	20.27	7.227			
4,400.00	4,333.75	4,405.38	4,361.65	11.52	10.46	-160.97	144.88	428.67	152.84	132.13	20.70	7.382			
4,500.00	4,430.34	4,505.16	4,459.25	11.84	10.71	-160.42	154.41	447.09	159.23	138.08	21.14	7.531			
4,600.00	4,526.93	4,604.95	4,556.86	12.16	10.97	-159.91	163.94	465.51	165.63	144.04	21.59	7.673			
4,700.00	4,623.53	4,704.73	4,654.47	12.48	11.22	-159.44	173.46	483.93	172.04	150.01	22.03	7.809			
4,800.00	4,720.12	4,804.51	4,752.07	12.80	11.47	-159.00	182.99	502.36	178.47	155.99	22.48	7.938			
4,900.00	4,816.71	4,904.30	4,849.68	13.12	11.73	-158.60	192.52	520.78	184.90	161.97	22.93	8.063			

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 222H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:						Offset Well Error:		0.50 usft
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)				
5,000.00	4,913.30	5,004.08	4,947.28	13.45	11.99	-158.22	202.05	539.20	191.34	167.96	23.39	8.181		
5,100.00	5,009.89	5,103.87	5,044.89	13.78	12.24	-157.86	211.57	557.62	197.80	173.95	23.84	8.296		
5,200.00	5,106.49	5,200.00	5,138.97	14.10	12.46	-157.58	220.65	575.16	204.49	180.23	24.26	8.428		
5,300.00	5,203.08	5,296.86	5,234.16	14.43	12.69	-157.61	228.85	591.03	212.98	188.27	24.71	8.620		
5,400.00	5,299.67	5,391.68	5,327.77	14.75	12.90	-157.97	235.81	604.48	223.58	198.47	25.11	8.903		
5,500.00	5,396.65	5,486.17	5,421.39	15.07	13.09	-158.51	241.68	615.83	234.88	209.37	25.52	9.205		
5,600.00	5,494.23	5,580.44	5,515.08	15.36	13.25	-159.08	246.47	625.10	245.89	220.00	25.89	9.497		
5,700.00	5,592.35	5,674.49	5,608.77	15.62	13.39	-159.67	250.19	632.30	256.60	230.35	26.24	9.779		
5,800.00	5,690.94	5,768.33	5,702.43	15.86	13.52	-160.28	252.85	637.43	267.00	240.44	26.56	10.052		
5,900.00	5,789.93	5,861.94	5,795.98	16.07	13.62	-160.90	254.45	640.52	277.12	250.26	26.85	10.320		
6,000.00	5,889.26	5,956.98	5,891.00	16.25	13.69	-161.55	254.99	641.57	286.94	259.85	27.09	10.590		
6,100.00	5,988.86	6,054.84	5,988.86	16.41	13.75	-162.13	254.99	641.57	295.42	268.11	27.31	10.818		
6,200.00	6,088.66	6,154.64	6,088.66	16.53	13.82	-162.53	254.99	641.57	301.44	273.89	27.55	10.943		
6,300.00	6,188.59	6,254.57	6,188.59	16.64	13.89	-162.75	254.99	641.57	304.97	277.20	27.78	10.980		
6,400.00	6,288.58	6,354.56	6,288.58	16.71	13.96	-90.39	254.99	641.57	306.02	278.09	27.93	10.956		
6,500.00	6,388.58	6,454.56	6,388.58	16.76	14.04	-90.39	254.99	641.57	306.02	277.95	28.06	10.905		
6,600.00	6,488.58	6,554.56	6,488.58	16.82	14.11	-90.39	254.99	641.57	306.02	277.82	28.19	10.854		
6,700.00	6,588.58	6,654.56	6,588.58	16.88	14.18	-90.39	254.99	641.57	306.02	277.69	28.32	10.804		
6,800.00	6,688.58	6,754.56	6,688.58	16.94	14.26	-90.39	254.99	641.57	306.02	277.56	28.46	10.754		
6,900.00	6,788.58	6,854.56	6,788.58	17.00	14.33	-90.39	254.99	641.57	306.02	277.43	28.59	10.704		
7,000.00	6,888.58	6,954.56	6,888.58	17.05	14.41	-90.39	254.99	641.57	306.02	277.30	28.72	10.655		
7,100.00	6,988.58	7,054.56	6,988.58	17.11	14.48	-90.39	254.99	641.57	306.02	277.16	28.85	10.606		
7,200.00	7,088.58	7,154.56	7,088.58	17.17	14.55	-90.39	254.99	641.57	306.02	277.03	28.99	10.557		
7,300.00	7,188.58	7,254.56	7,188.58	17.23	14.63	-90.39	254.99	641.57	306.02	276.90	29.12	10.509		
7,400.00	7,288.58	7,354.56	7,288.58	17.29	14.70	-90.39	254.99	641.57	306.02	276.76	29.25	10.461		
7,500.00	7,388.58	7,454.56	7,388.58	17.35	14.78	-90.39	254.99	641.57	306.02	276.63	29.39	10.414		
7,600.00	7,488.58	7,554.56	7,488.58	17.41	14.85	-90.39	254.99	641.57	306.02	276.50	29.52	10.366		
7,700.00	7,588.58	7,654.56	7,588.58	17.47	14.92	-90.39	254.99	641.57	306.02	276.36	29.65	10.319		
7,800.00	7,688.58	7,754.56	7,688.58	17.53	15.00	-90.39	254.99	641.57	306.02	276.23	29.79	10.273		
7,900.00	7,788.58	7,854.56	7,788.58	17.59	15.07	-90.39	254.99	641.57	306.02	276.09	29.92	10.227		
8,000.00	7,888.58	7,954.56	7,888.58	17.65	15.15	-90.39	254.99	641.57	306.02	275.96	30.06	10.181		
8,100.00	7,988.58	8,054.56	7,988.58	17.71	15.22	-90.39	254.99	641.57	306.02	275.82	30.19	10.135		
8,200.00	8,088.58	8,154.56	8,088.58	17.77	15.30	-90.39	254.99	641.57	306.02	275.69	30.33	10.090		
8,300.00	8,188.58	8,254.56	8,188.58	17.83	15.37	-90.39	254.99	641.57	306.02	275.55	30.47	10.045		
8,400.00	8,288.58	8,354.56	8,288.58	17.89	15.45	-90.39	254.99	641.57	306.02	275.42	30.60	10.000		
8,500.00	8,388.58	8,454.56	8,388.58	17.95	15.52	-90.39	254.99	641.57	306.02	275.28	30.74	9.956		
8,600.00	8,488.58	8,554.56	8,488.58	18.02	15.60	-90.39	254.99	641.57	306.02	275.14	30.87	9.911		
8,700.00	8,588.58	8,654.56	8,588.58	18.08	15.67	-90.39	254.99	641.57	306.02	275.01	31.01	9.868		
8,800.00	8,688.58	8,754.56	8,688.58	18.14	15.75	-90.39	254.99	641.57	306.02	274.87	31.15	9.824		
8,900.00	8,788.58	8,854.56	8,788.58	18.20	15.82	-90.39	254.99	641.57	306.02	274.73	31.29	9.781		
9,000.00	8,888.58	8,954.56	8,888.58	18.26	15.90	-90.39	254.99	641.57	306.02	274.59	31.42	9.738		
9,100.00	8,988.58	9,054.56	8,988.58	18.32	15.97	-90.39	254.99	641.57	306.02	274.46	31.56	9.696		
9,200.00	9,088.58	9,154.56	9,088.58	18.39	16.05	-90.39	254.99	641.57	306.02	274.32	31.70	9.654		
9,300.00	9,188.58	9,254.56	9,188.58	18.45	16.12	-90.39	254.99	641.57	306.02	274.18	31.84	9.612		
9,400.00	9,288.58	9,354.56	9,288.58	18.51	16.20	-90.39	254.99	641.57	306.02	274.04	31.98	9.570		
9,500.00	9,388.58	9,454.56	9,388.58	18.57	16.27	-90.39	254.99	641.57	306.02	273.90	32.12	9.529		
9,600.00	9,488.58	9,554.56	9,488.58	18.64	16.35	-90.39	254.99	641.57	306.02	273.76	32.25	9.487		
9,700.00	9,588.58	9,654.56	9,588.58	18.70	16.43	-90.39	254.99	641.57	306.02	273.62	32.39	9.447		
9,800.00	9,688.58	9,754.56	9,688.58	18.76	16.50	-90.39	254.99	641.57	306.02	273.48	32.53	9.406		
9,900.00	9,788.58	9,854.56	9,788.58	18.83	16.58	-90.39	254.99	641.57	306.02	273.34	32.67	9.366		
10,000.00	9,888.58	9,954.56	9,888.58	18.89	16.65	-90.39	254.99	641.57	306.02	273.20	32.81	9.326		
10,100.00	9,988.58	10,054.56	9,988.58	18.95	16.73	-90.39	254.99	641.57	306.02	273.06	32.95	9.286		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 93 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 222H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference		Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
10,200.00	10,088.58	10,154.56	10,088.58	19.02	16.81	-90.39	254.99	641.57	306.02	272.92	33.09	9.247	
10,300.00	10,188.58	10,254.56	10,188.58	19.08	16.88	-90.39	254.99	641.57	306.02	272.78	33.23	9.208	
10,400.00	10,288.58	10,354.56	10,288.58	19.15	16.96	-90.39	254.99	641.57	306.02	272.64	33.37	9.169	
10,500.00	10,388.58	10,454.56	10,388.58	19.21	17.03	-90.39	254.99	641.57	306.02	272.50	33.52	9.131	
10,600.00	10,488.58	10,554.56	10,488.58	19.27	17.11	-90.39	254.99	641.57	306.02	272.36	33.66	9.092	
10,700.00	10,588.58	10,654.56	10,588.58	19.34	17.19	-90.39	254.99	641.57	306.02	272.22	33.80	9.054	
10,800.00	10,688.58	10,754.56	10,688.58	19.40	17.26	-90.39	254.99	641.57	306.02	272.08	33.94	9.017	
10,900.00	10,788.58	10,854.56	10,788.58	19.47	17.34	-90.39	254.99	641.57	306.02	271.94	34.08	8.979	
11,000.00	10,888.58	10,954.56	10,888.58	19.53	17.42	-90.39	254.99	641.57	306.02	271.79	34.22	8.942	
11,100.00	10,988.58	11,054.56	10,988.58	19.60	17.49	-90.39	254.99	641.57	306.02	271.65	34.36	8.905	
11,200.00	11,088.58	11,154.56	11,088.58	19.66	17.57	-90.39	254.99	641.57	306.02	271.51	34.51	8.868	
11,300.00	11,188.58	11,254.56	11,188.58	19.73	17.65	-90.39	254.99	641.57	306.02	271.37	34.65	8.832	
11,400.00	11,288.58	11,354.56	11,288.58	19.79	17.72	-90.39	254.99	641.57	306.02	271.22	34.79	8.796	
11,500.00	11,388.58	11,454.56	11,388.58	19.86	17.80	-90.39	254.99	641.57	306.02	271.08	34.93	8.760	
11,600.00	11,488.58	11,554.56	11,488.58	19.92	17.88	-90.39	254.99	641.57	306.02	270.94	35.08	8.724	
11,700.00	11,588.58	11,654.56	11,588.58	19.99	17.95	-90.39	254.99	641.57	306.02	270.80	35.22	8.689	
11,800.00	11,688.58	11,754.56	11,688.58	20.05	18.03	-90.39	254.99	641.57	306.02	270.65	35.36	8.653	
11,900.00	11,788.58	11,854.56	11,788.58	20.12	18.11	-90.39	254.99	641.57	306.02	270.51	35.51	8.618	
12,000.00	11,888.58	11,954.56	11,888.58	20.19	18.18	-90.39	254.99	641.57	306.02	270.37	35.65	8.584	
12,000.29	11,888.87	11,954.84	11,888.87	20.19	18.18	90.10	254.99	641.57	306.02	270.37	35.65	8.584	
12,100.00	11,988.51	12,054.49	11,988.51	20.25	18.26	90.54	254.99	641.57	306.03	270.29	35.75	8.561	
12,200.00	12,086.82	12,152.79	12,086.82	20.31	18.34	93.70	254.99	641.57	306.70	270.87	35.84	8.559	
12,300.00	12,180.57	12,246.55	12,180.57	20.35	18.41	99.22	254.99	641.57	310.90	274.92	35.98	8.641	
12,400.00	12,266.93	12,332.90	12,266.93	20.39	18.47	105.68	254.99	641.57	323.56	287.35	36.20	8.937	
12,500.00	12,343.26	12,426.73	12,360.										

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 94 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 222H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Reference		Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
15,300.00	12,530.52	15,604.73	12,879.41	42.55	40.50	132.48	-2,667.52	591.77	516.61	440.63	75.98	6.799	
15,400.00	12,531.40	15,704.73	12,880.28	43.74	41.72	132.48	-2,767.51	592.63	516.60	438.94	77.66	6.652	
15,500.00	12,532.27	15,804.73	12,881.15	44.94	42.95	132.48	-2,867.50	593.49	516.60	437.24	79.36	6.509	
15,600.00	12,533.14	15,904.73	12,882.02	46.15	44.19	132.48	-2,967.50	594.35	516.60	435.51	81.08	6.371	
15,700.00	12,534.02	16,004.73	12,882.88	47.37	45.44	132.48	-3,067.49	595.21	516.59	433.77	82.82	6.237	
15,800.00	12,534.89	16,104.73	12,883.75	48.59	46.69	132.48	-3,167.48	596.07	516.59	432.01	84.58	6.108	
15,900.00	12,535.76	16,204.73	12,884.62	49.83	47.95	132.48	-3,267.47	596.93	516.59	430.23	86.35	5.982	
16,000.00	12,536.64	16,304.73	12,885.49	51.07	49.21	132.48	-3,367.47	597.79	516.58	428.44	88.14	5.861	
16,100.00	12,537.51	16,404.73	12,886.36	52.32	50.49	132.48	-3,467.46	598.65	516.58	426.64	89.94	5.743	
16,200.00	12,538.39	16,504.73	12,887.22	53.57	51.76	132.48	-3,567.45	599.51	516.58	424.82	91.76	5.630	
16,300.00	12,539.26	16,604.73	12,888.09	54.83	53.04	132.48	-3,667.44	600.37	516.57	422.98	93.59	5.520	
16,400.00	12,540.13	16,704.73	12,888.96	56.09	54.33	132.48	-3,767.44	601.23	516.57	421.14	95.43	5.413	
16,500.00	12,541.01	16,804.73	12,889.83	57.36	55.62	132.48	-3,867.43	602.09	516.57	419.29	97.28	5.310	
16,600.00	12,541.88	16,904.73	12,890.70	58.64	56.91	132.48	-3,967.42	602.96	516.56	417.42	99.14	5.210	
16,700.00	12,542.75	17,004.73	12,891.56	59.91	58.21	132.48	-4,067.41	603.82	516.56	415.55	101.01	5.114	
16,800.00	12,543.63	17,104.73	12,892.43	61.20	59.51	132.48	-4,167.41	604.68	516.56	413.66	102.89	5.020	
16,900.00	12,544.50	17,204.73	12,893.30	62.48	60.81	132.48	-4,267.40	605.54	516.55	411.77	104.78	4.930	
17,000.00	12,545.37	17,304.73	12,894.17	63.77	62.11	132.47	-4,367.39	606.40	516.55	409.87	106.68	4.842	
17,100.00	12,546.25	17,404.73	12,895.04	65.06	63.42	132.47	-4,467.38	607.26	516.55	407.96	108.59	4.757	
17,200.00	12,547.12	17,504.73	12,895.90	66.36	64.73	132.47	-4,567.38	608.12	516.54	406.04	110.50	4.675	
17,300.00	12,547.99	17,604.73	12,896.77	67.66	66.05	132.47	-4,667.37	608.98	516.54	404.12	112.42	4.595	
17,400.00	12,548.87	17,704.73	12,897.64	68.96	67.36	132.47	-4,767.36	609.84	516.54	402.19	114.35	4.517	
17,500.00	12,549.74	17,804.73	12,898.51	70.26	68.68	132.47	-4,867.35	610.70	516.53	400.25	116.28	4.442	
17,600.00	12,550.62	17,904.73	12,899.38	71.57	70.00	132.47	-4,967.35	611.56	516.53	398.30			

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 95 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 222H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:		Warning	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,500.00	12,575.95	20,804.73	12,924.55	110.12	108.82	132.46	-7,867.13	636.52	516.43	340.18	176.25	2.930			
20,600.00	12,576.82	20,904.73	12,925.42	111.47	110.17	132.46	-7,967.12	637.38	516.43	338.14	178.29	2.897			
20,700.00	12,577.70	21,004.73	12,926.29	112.81	111.52	132.46	-8,067.12	638.24	516.42	336.09	180.33	2.864			
20,800.00	12,578.57	21,104.73	12,927.15	114.16	112.87	132.46	-8,167.11	639.11	516.42	334.04	182.37	2.832			
20,900.00	12,579.44	21,204.73	12,928.02	115.51	114.23	132.46	-8,267.10	639.97	516.42	332.00	184.42	2.800			
21,000.00	12,580.32	21,304.73	12,928.89	116.85	115.58	132.46	-8,367.09	640.83	516.41	329.95	186.47	2.769			
21,100.00	12,581.19	21,404.73	12,929.76	118.20	116.93	132.45	-8,467.09	641.69	516.41	327.89	188.52	2.739			
21,200.00	12,582.06	21,504.73	12,930.63	119.55	118.28	132.45	-8,567.08	642.55	516.41	325.84	190.57	2.710			
21,300.00	12,582.94	21,604.73	12,931.49	120.89	119.64	132.45	-8,667.07	643.41	516.40	323.78	192.62	2.681			
21,400.00	12,583.81	21,704.73	12,932.36	122.24	120.99	132.45	-8,767.06	644.27	516.40	321.73	194.67	2.653			
21,500.00	12,584.69	21,804.73	12,933.23	123.59	122.34	132.45	-8,867.06	645.13	516.40	319.67	196.72	2.625			
21,600.00	12,585.56	21,904.73	12,934.10	124.94	123.70	132.45	-8,967.05	645.99	516.39	317.61	198.78	2.598			
21,700.00	12,586.43	22,004.73	12,934.97	126.29	125.05	132.45	-9,067.04	646.85	516.39	315.55	200.84	2.571			
21,800.00	12,587.31	22,104.73	12,935.83	127.64	126.41	132.45	-9,167.03	647.71	516.38	313.49	202.89	2.545			
21,900.00	12,588.18	22,204.73	12,936.70	128.99	127.76	132.45	-9,267.03	648.57	516.38	311.43	204.95	2.520			
22,000.00	12,589.05	22,304.73	12,937.57	130.34	129.12	132.45	-9,367.02	649.43	516.38	309.36	207.01	2.494			
22,100.00	12,589.93	22,404.73	12,938.44	131.70	130.47	132.45	-9,467.01	650.29	516.37	307.30	209.07	2.470			
22,200.00	12,590.80	22,504.73	12,939.31	133.05	131.83	132.45	-9,567.00	651.16	516.37	305.23	211.14	2.446			
22,300.00	12,591.67	22,604.73	12,940.17	134.40	133.19	132.45	-9,667.00	652.02	516.37	303.17	213.20	2.422			
22,400.00	12,592.55	22,704.73	12,941.04	135.75	134.54	132.45	-9,766.99	652.88	516.36	301.10	215.27	2.399			
22,500.00	12,593.42	22,804.73	12,941.91	137.11	135.90	132.45	-9,866.98	653.74	516.36	299.03	217.33	2.376			
22,600.00	12,594.30	22,904.73	12,942.78	138.46	137.26	132.45	-9,966.97	654.60	516.36	296.96	219.40	2.354			
22,700.00	12,595.17	23,004.73	12,943.65	139.81	138.62	132.45	-10,066.97	655.46	516.35	294.89	221.46	2.332			
22,800.00	12,596.04	23,104.73	12,944.51	141.17	139.97	132.45	-10,166.96	656.32	516.35	292.82	223.53	2.310			
22,875.30	12,596.70	23,180.03	12,945.17	142.19	140.99	132.45	-10,242.26	656.97	516.35	291.26	225.09	2.294	SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 223H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Offset		Semi Major Axis		Offset Wellbore Centre			Rule Assigned: Distance		Offset Well Error: 0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Major Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning
0.00	0.00	2.00	0.00	0.50	0.50	69.40	881.00	2,344.00	2,504.10				
100.00	100.00	102.00	100.00	0.98	0.99	69.40	881.00	2,344.00	2,504.10	2,502.12	1.97	1,269.100	
200.00	200.00	202.00	200.00	1.56	1.57	69.40	881.00	2,344.00	2,504.10	2,500.97	3.13	799.889	
300.00	300.00	302.00	300.00	1.98	1.99	69.40	881.00	2,344.00	2,504.10	2,500.13	3.97	630.874	
400.00	400.00	402.00	400.00	2.33	2.34	69.40	881.00	2,344.00	2,504.10	2,499.43	4.66	536.793	
500.00	500.00	502.00	500.00	2.63	2.64	69.40	881.00	2,344.00	2,504.10	2,498.82	5.27	474.752	
600.00	600.00	602.00	600.00	2.91	2.92	69.40	881.00	2,344.00	2,504.10	2,498.27	5.83	429.873	
700.00	700.00	702.00	700.00	3.16	3.17	69.40	881.00	2,344.00	2,504.10	2,497.76	6.33	395.447	
800.00	800.00	802.00	800.00	3.40	3.41	69.40	881.00	2,344.00	2,504.10	2,497.29	6.81	367.944	
900.00	900.00	902.00	900.00	3.62	3.63	69.40	881.00	2,344.00	2,504.10	2,496.84	7.25	345.307	
1,000.00	1,000.00	1,002.00	1,000.00	3.76	3.84	-22.60	881.00	2,344.00	2,504.05	2,496.45	7.60	329.496	
1,100.00	1,099.98	1,101.98	1,099.98	4.00	4.04	-22.63	881.00	2,344.00	2,502.36	2,494.32	8.04	311.388	
1,200.00	1,199.88	1,201.88	1,199.88	4.24	4.24	-22.69	881.00	2,344.00	2,498.25	2,489.79	8.46	295.412	
1,300.00	1,299.63	1,301.63	1,299.63	4.46	4.42	-22.79	881.00	2,344.00	2,491.73	2,482.87	8.86	281.082	
1,400.00	1,399.25	1,401.25	1,399.25	4.60	4.60	-22.87	881.00	2,344.00	2,483.72	2,474.54	9.18	270.533	
1,500.00	1,498.87	1,500.87	1,498.87	4.78	4.78	-22.95	881.00	2,344.00	2,475.69	2,466.15	9.54	259.631	
1,600.00	1,598.49	1,600.49	1,598.49	4.96	4.95	-23.03	881.00	2,344.00	2,467.66	2,457.77	9.88	249.648	
1,700.00	1,698.11	1,700.11	1,698.11	5.14	5.11	-23.11	881.00	2,344.00	2,459.63	2,449.41	10.23	240.460	
1,800.00	1,797.73	1,799.73	1,797.73	5.32	5.28	-23.19	881.00	2,344.00	2,451.62	2,441.05	10.57	231.967	
1,900.00	1,897.34	1,899.34	1,897.34	5.49	5.43	-23.27	881.00	2,344.00	2,443.60	2,432.70	10.90	224.086	
2,000.00	1,996.96	1,998.96	1,996.96	5.67	5.59	-23.35	881.00	2,344.00	2,435.59	2,424.36	11.24	216.748	
2,100.00	2,096.58	2,227.42	2,225.28	5.85	5.94	-23.47	875.95	2,339.49	2,424.97	2,413.24	11.73	206.676	
2,200.00	2,196.20	2,454.07	2,451.00	6.04	6.28	-23.43	860.90	2,326.03	2,409.07	2,396.87	12.19	197.596	
2,300.00	2,295.72	2,675.41	2,669.89	6.23	6.62	-16.94	836.60	2,304.31	2,386.84	2,374.20	12.64	188.817	
2,400.00	2,394.97	2,794.17	2,786.61	6.43	6.75	-12.51	820.25	2,289.69	2,358.78	2,345.83	12.96		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 97 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 223H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:		Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning		
5,200.00	5,106.49	5,347.32	5,294.96	14.10	11.75	5.61	465.23	1,972.32	1,238.92	1,215.78	23.14	53.542			
5,300.00	5,203.08	5,438.06	5,384.11	14.43	11.96	6.25	452.62	1,961.04	1,198.81	1,175.26	23.55	50.904			
5,400.00	5,299.67	5,528.81	5,473.27	14.75	12.18	6.92	440.00	1,949.76	1,158.85	1,134.89	23.96	48.373			
5,500.00	5,396.65	5,620.17	5,563.02	15.07	12.40	7.56	427.29	1,938.40	1,120.43	1,096.04	24.39	45.940			
5,600.00	5,494.23	5,712.53	5,653.76	15.36	12.62	8.23	414.45	1,926.92	1,084.58	1,059.75	24.82	43.693			
5,700.00	5,592.35	5,805.83	5,745.43	15.62	12.85	8.92	401.48	1,915.32	1,051.33	1,026.07	25.26	41.620			
5,800.00	5,690.94	5,900.01	5,837.95	15.86	13.08	9.64	388.38	1,903.61	1,020.71	995.02	25.70	39.718			
5,900.00	5,789.93	5,995.00	5,931.28	16.07	13.31	10.39	375.17	1,891.80	992.76	966.62	26.14	37.981			
6,000.00	5,889.26	6,090.74	6,025.33	16.25	13.55	11.15	361.86	1,879.90	967.48	940.90	26.58	36.404			
6,100.00	5,988.86	6,187.15	6,120.06	16.41	13.78	11.92	348.46	1,867.92	944.89	917.88	27.01	34.982			
6,200.00	6,088.66	6,284.19	6,215.39	16.53	14.02	12.71	334.96	1,855.86	925.01	897.57	27.44	33.710			
6,300.00	6,188.59	6,381.77	6,311.26	16.64	14.26	13.50	321.39	1,843.73	907.84	879.98	27.86	32.588			
6,400.00	6,288.58	6,474.43	6,402.32	16.71	14.47	86.67	308.61	1,832.30	893.49	865.30	28.18	31.703			
6,500.00	6,388.58	6,559.07	6,485.76	16.76	14.66	87.32	298.05	1,822.86	881.61	853.12	28.49	30.941			
6,600.00	6,488.58	6,644.30	6,570.09	16.82	14.84	87.90	288.82	1,814.61	871.43	842.63	28.79	30.264			
6,700.00	6,588.58	6,730.05	6,655.19	16.88	15.00	88.41	280.95	1,807.57	862.89	833.82	29.08	29.677			
6,800.00	6,688.58	6,816.24	6,740.93	16.94	15.14	88.83	274.47	1,801.78	855.98	826.64	29.34	29.178			
6,900.00	6,788.58	6,900.00	6,824.43	17.00	15.26	89.16	269.56	1,797.39	850.66	821.08	29.58	28.763			
7,000.00	6,888.58	6,989.58	6,913.87	17.05	15.37	89.41	265.82	1,794.05	846.89	817.10	29.79	28.429			
7,100.00	6,988.58	7,076.56	7,000.80	17.11	15.46	89.55	263.69	1,792.14	844.67	814.70	29.98	28.176			
7,200.00	7,088.58	7,164.35	7,088.58	17.17	15.50	89.60	263.03	1,791.55	843.99	813.88	30.11	28.032			
7,300.00	7,188.58	7,264.35	7,188.58	17.23	15.53	89.60	263.03	1,791.55	843.99	813.80	30.19	27.952			
7,400.00	7,288.58	7,364.35	7,288.58	17.29	15.57	89.60	263.03	1,791.55	843.99	813.70	30.29	27.861			
7,500.00	7,388.58	7,464.35	7,388.58	17.35	15.61	89.60	263.03	1,79							

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 98 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 223H - OH - Plan 1													Offset Site Error: 0.00 usft	
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance			Offset Well Error: 0.50 usft	
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,400.00	10,288.58	10,364.35	10,288.58	19.15	16.88	89.60	263.03	1,791.55	843.99	810.51	33.48	25.209		
10,500.00	10,388.58	10,464.35	10,388.58	19.21	16.93	89.60	263.03	1,791.55	843.99	810.40	33.59	25.124		
10,600.00	10,488.58	10,564.35	10,488.58	19.27	16.98	89.60	263.03	1,791.55	843.99	810.28	33.71	25.039		
10,700.00	10,588.58	10,664.35	10,588.58	19.34	17.03	89.60	263.03	1,791.55	843.99	810.17	33.82	24.955		
10,800.00	10,688.58	10,764.35	10,688.58	19.40	17.08	89.60	263.03	1,791.55	843.99	810.06	33.94	24.871		
10,900.00	10,788.58	10,864.35	10,788.58	19.47	17.13	89.60	263.03	1,791.55	843.99	809.94	34.05	24.787		
11,000.00	10,888.58	10,964.35	10,888.58	19.53	17.18	89.60	263.03	1,791.55	843.99	809.83	34.17	24.703		
11,100.00	10,988.58	11,064.35	10,988.58	19.60	17.23	89.60	263.03	1,791.55	843.99	809.71	34.28	24.620		
11,200.00	11,088.58	11,164.35	11,088.58	19.66	17.28	89.60	263.03	1,791.55	843.99	809.59	34.40	24.537		
11,300.00	11,188.58	11,264.35	11,188.58	19.73	17.33	89.60	263.03	1,791.55	843.99	809.48	34.51	24.454		
11,400.00	11,288.58	11,364.35	11,288.58	19.79	17.38	89.60	263.03	1,791.55	843.99	809.36	34.63	24.372		
11,500.00	11,388.58	11,464.35	11,388.58	19.86	17.43	89.60	263.03	1,791.55	843.99	809.24	34.75	24.290		
11,600.00	11,488.58	11,564.35	11,488.58	19.92	17.48	89.60	263.03	1,791.55	843.99	809.13	34.86	24.208		
11,700.00	11,588.58	11,664.35	11,588.58	19.99	17.53	89.60	263.03	1,791.55	843.99	809.01	34.98	24.126		
11,800.00	11,688.58	11,764.35	11,688.58	20.05	17.59	89.60	263.03	1,791.55	843.99	808.89	35.10	24.045		
11,900.00	11,788.58	11,864.35	11,788.58	20.12	17.64	89.60	263.03	1,791.55	843.99	808.77	35.22	23.964		
12,000.00	11,888.58	11,964.35	11,888.58	20.19	17.69	89.60	263.03	1,791.55	843.99	808.65	35.34	23.884		
12,053.96	11,942.52	12,018.29	11,942.52	20.22	17.72	-90.00	263.03	1,791.55	843.99	808.62	35.37	23.863		
12,100.00	11,988.51	12,064.28	11,988.51	20.25	17.74	-90.07	263.03	1,791.55	843.99	808.60	35.39	23.846		
12,200.00	12,086.82	12,162.58	12,086.82	20.31	17.79	-91.22	263.03	1,791.55	844.20	808.84	35.35	23.879		
12,300.00	12,180.57	12,256.34	12,180.57	20.35	17.84	-93.26	263.03	1,791.55	845.66	810.39	35.26	23.983		
12,400.00	12,266.93	12,341.90	12,266.10	20.39	17.91	-95.59	261.42	1,791.78	850.30	815.13	35.17	24.178		
12,500.00	12,343.26	12,429.34	12,352.45	20.44	18.06	-97.70	248.36	1,793.64	859.71	824.51	35.20	24.422		
12,600.00	12,407.24	12,524.81	12,443.23	20.52	18.28	-99.63	219.45							

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 223H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:				Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance			Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning				
15,500.00	12,532.27	15,753.22	12,809.40	44.94	53.26	-106.33	-2,857.22	1,920.07	985.41	891.46	93.95	10.489					
15,600.00	12,533.14	15,853.22	12,809.92	46.15	54.57	-106.31	-2,957.21	1,920.98	985.36	888.96	96.39	10.222					
15,700.00	12,534.02	15,953.22	12,810.45	47.37	55.88	-106.29	-3,057.21	1,921.89	985.30	886.45	98.85	9.968					
15,800.00	12,534.89	16,053.22	12,810.97	48.59	57.20	-106.27	-3,157.20	1,922.79	985.25	883.93	101.32	9.724					
15,900.00	12,535.76	16,153.22	12,811.50	49.83	58.51	-106.25	-3,257.20	1,923.70	985.20	881.40	103.79	9.492					
16,000.00	12,536.64	16,253.21	12,812.02	51.07	59.83	-106.23	-3,357.19	1,924.61	985.14	878.86	106.28	9.269					
16,100.00	12,537.51	16,353.21	12,812.55	52.32	61.15	-106.21	-3,457.18	1,925.52	985.09	876.31	108.77	9.056					
16,200.00	12,538.39	16,453.21	12,813.08	53.57	62.48	-106.19	-3,557.18	1,926.42	985.04	873.76	111.28	8.852					
16,300.00	12,539.26	16,553.21	12,813.60	54.83	63.80	-106.17	-3,657.17	1,927.33	984.98	871.20	113.79	8.656					
16,400.00	12,540.13	16,653.21	12,814.13	56.09	65.13	-106.15	-3,757.17	1,928.24	984.93	868.63	116.30	8.469					
16,500.00	12,541.01	16,753.21	12,814.65	57.36	66.46	-106.13	-3,857.16	1,929.14	984.88	866.05	118.83	8.288					
16,600.00	12,541.88	16,853.21	12,815.18	58.64	67.79	-106.11	-3,957.15	1,930.05	984.82	863.47	121.35	8.115					
16,700.00	12,542.75	16,953.21	12,815.71	59.91	69.12	-106.09	-4,057.15	1,930.96	984.77	860.88	123.89	7.949					
16,800.00	12,543.63	17,053.21	12,816.23	61.20	70.46	-106.07	-4,157.14	1,931.86	984.72	858.29	126.43	7.789					
16,900.00	12,544.50	17,153.21	12,816.76	62.48	71.79	-106.05	-4,257.14	1,932.77	984.67	855.69	128.98	7.634					
17,000.00	12,545.37	17,253.21	12,817.28	63.77	73.13	-106.03	-4,357.13	1,933.68	984.61	853.09	131.53	7.486					
17,100.00	12,546.25	17,353.21	12,817.81	65.06	74.46	-106.01	-4,457.12	1,934.58	984.56	850.48	134.08	7.343					
17,200.00	12,547.12	17,453.21	12,818.33	66.36	75.80	-105.99	-4,557.12	1,935.49	984.51	847.87	136.64	7.205					
17,300.00	12,547.99	17,553.21	12,818.86	67.66	77.14	-105.97	-4,657.11	1,936.40	984.46	845.25	139.21	7.072					
17,400.00	12,548.87	17,653.21	12,819.39	68.96	78.48	-105.95	-4,757.10	1,937.30	984.41	842.63	141.77	6.943					
17,500.00	12,549.74	17,753.21	12,819.91	70.26	79.82	-105.93	-4,857.10	1,938.21	984.35	840.01	144.35	6.819					
17,600.00	12,550.62	17,853.20	12,820.44	71.57	81.17	-105.91	-4,957.09	1,939.12	984.30	837.38	146.92	6.700					
17,700.00	12,551.49	17,953.20	12,820.96	72.88	82.51	-105.89	-5,057.09	1,940.02	984.25	834.75	149.50	6.584					
17,800.00	12,552.36	18,053.20	12,821.49	74.19	83.85	-105.87	-5,157.08	1,940.93	984.20	832.12	152.08	6.471					
17,900.00	12,553.24	18,153.20	12,822.01	75.50	85.20	-105.85	-5,257.07	1,941.84	984.15	829.48	154.67	6.363					
18,000.00	12,554.11	18,253.20	12,822.54	76.81	86.54	-105.83	-5,357.07	1,942.74	984.10	826.84	157.26	6.258					
18,100.00	12,554.98	18,353.20	12,823.07	78.13	87.89	-105.81	-5,457.06	1,943.65	984.05	824.20	159.85	6.156					
18,200.00	12,555.86	18,453.20	12,823.59	79.45	89.24	-105.79	-5,557.06	1,944.56	984.00	821.56	162.44	6.058					
18,300.00	12,556.73	18,553.20	12,824.12	80.77	90.58	-105.77	-5,657.05	1,945.47	983.95	818.91	165.04	5.962					
18,400.00	12,557.60	18,653.20	12,824.64	82.09	91.93	-105.75	-5,757.04	1,946.37	983.90	816.26	167.64	5.869					
18,500.00	12,558.48	18,753.20	12,825.17	83.42	93.28	-105.73	-5,857.04	1,947.28	983.85	813.61	170.24	5.779					
18,600.00	12,559.35	18,853.20	12,825.70	84.74	94.63	-105.71	-5,957.03	1,948.19	983.80	810.95	172.84	5.692					
18,700.00	12,560.23	18,953.20	12,826.22	86.07	95.98	-105.69	-6,057.03	1,949.09	983.74	808.30	175.45	5.607					
18,800.00	12,561.10	19,053.20	12,826.75	87.40	97.33	-105.67	-6,157.02	1,950.00	983.69	805.64	178.05	5.525					
18,900.00	12,561.97	19,153.20	12,827.27	88.72	98.68	-105.65	-6,257.01	1,950.91	983.65	802.98	180.66	5.445					
19,000.00	12,562.85	19,253.20	12,827.80	90.05	100.03	-105.63	-6,357.01	1,951.81	983.60	800.32	183.28	5.367					
19,100.00	12,563.72	19,353.20	12,828.32	91.39	101.39	-105.61	-6,457.00	1,952.72	983.55	797.65	185.89	5.291					
19,200.00	12,564.59	19,453.20	12,828.85	92.72	102.74	-105.59	-6,556.99	1,953.63	983.50	794.99	188.51	5.217					
19,300.00	12,565.47	19,553.19	12,829.38	94.05	104.09	-105.57	-6,656.99	1,954.53	983.45	792.32	191.13	5.146					
19,400.00	12,566.34	19,653.19	12,829.90	95.39	105.44	-105.55	-6,756.98	1,955.44	983.40	789.65	193.74	5.076					
19,500.00	12,567.21	19,753.19	12,830.43	96.72	106.80	-105.53	-6,856.98	1,956.35	983.35	786.98	196.37	5.008					
19,600.00	12,568.09	19,853.19	12,830.95	98.06	108.15	-105.51	-6,956.97	1,957.25	983.30	784.31	198.99	4.941					
19,700.00	12,568.96	19,953.19	12,831.48	99.40	109.51	-105.49	-7,056.96	1,958.16	983.25	781.64	201.61	4.877					
19,800.00	12,569.83	20,053.19	12,832.00	100.73	110.86	-105.47	-7,156.96	1,959.07	983.20	778.96	204.24	4.814					
19,900.00	12,570.71	20,153.19	12,832.53	102.07	112.22	-105.45	-7,256.95	1,959.97	983.15	776.28	206.87	4.753					
20,000.00	12,571.58	20,253.19	12,833.06	103.41	113.57	-105.42	-7,356.95	1,960.88	983.10	773.61	209.50	4.693					
20,100.00	12,572.46	20,353.19	12,833.58	104.75	114.93	-105.40	-7,456.94	1,961.79	983.06	770.93	212.13	4.634					
20,200.00	12,573.33	20,453.19	12,834.11	106.10	116.29	-105.38	-7,556.93	1,962.69	983.01	768.25	214.76	4.577					
20,300.00	12,574.20	20,553.19	12,834.63	107.44	117.64	-105.36	-7,656.93	1,963.60	982.96	765.57	217.39	4.522					
20,400.00	12,575.08	20,653.19	12,835.16	108.78	119.00	-105.34	-7,756.92	1,964.51	982.91	762.88	220.03	4.467					
20,500.00	12,575.95	20,753.19	12,835.69	110.12	120.36	-105.32	-7,856.92	1,965.42	982.86	760.20	222.66	4.414					
20,600.00	12,576.82	20,853.19	12,836.21	111.47	121.71	-105.30	-7,956.91	1,966.32	982.82	757.51	225.30	4.362					

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 223H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)												Rule Assigned:		Warning	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,700.00	12,577.70	20,953.19	12,836.74	112.81	123.07	-105.28	-8,056.90	1,967.23	982.77	754.83	227.94	4.312			
20,800.00	12,578.57	21,053.19	12,837.26	114.16	124.43	-105.26	-8,156.90	1,968.14	982.72	752.14	230.58	4.262			
20,900.00	12,579.44	21,153.18	12,837.79	115.51	125.79	-105.24	-8,256.89	1,969.04	982.67	749.45	233.22	4.213			
21,000.00	12,580.32	21,253.18	12,838.31	116.85	127.15	-105.22	-8,356.88	1,969.95	982.63	746.76	235.86	4.166			
21,100.00	12,581.19	21,353.18	12,838.84	118.20	128.50	-105.20	-8,456.88	1,970.86	982.58	744.07	238.51	4.120			
21,200.00	12,582.06	21,453.18	12,839.37	119.55	129.86	-105.18	-8,556.87	1,971.76	982.53	741.38	241.15	4.074			
21,300.00	12,582.94	21,553.18	12,839.89	120.89	131.22	-105.16	-8,656.87	1,972.67	982.48	738.69	243.80	4.030			
21,400.00	12,583.81	21,653.18	12,840.42	122.24	132.58	-105.14	-8,756.86	1,973.58	982.44	735.99	246.44	3.986			
21,500.00	12,584.69	21,753.18	12,840.94	123.59	133.94	-105.12	-8,856.85	1,974.48	982.39	733.30	249.09	3.944			
21,600.00	12,585.56	21,853.18	12,841.47	124.94	135.30	-105.10	-8,956.85	1,975.39	982.34	730.61	251.74	3.902			
21,700.00	12,586.43	21,953.18	12,841.99	126.29	136.66	-105.08	-9,056.84	1,976.30	982.30	727.91	254.39	3.861			
21,800.00	12,587.31	22,053.18	12,842.52	127.64	138.02	-105.06	-9,156.84	1,977.20	982.25	725.21	257.04	3.821			
21,900.00	12,588.18	22,153.18	12,843.05	128.99	139.38	-105.04	-9,256.83	1,978.11	982.20	722.51	259.69	3.782			
22,000.00	12,589.05	22,253.18	12,843.57	130.34	140.74	-105.02	-9,356.82	1,979.02	982.16	719.82	262.34	3.744			
22,100.00	12,589.93	22,353.18	12,844.10	131.70	142.10	-105.00	-9,456.82	1,979.92	982.11	717.12	265.00	3.706			
22,200.00	12,590.80	22,453.18	12,844.62	133.05	143.46	-104.98	-9,556.81	1,980.83	982.07	714.42	267.65	3.669			
22,300.00	12,591.67	22,553.18	12,845.15	134.40	144.82	-104.96	-9,656.81	1,981.74	982.02	711.72	270.31	3.633			
22,400.00	12,592.55	22,653.18	12,845.68	135.75	146.18	-104.94	-9,756.80	1,982.65	981.98	709.01	272.96	3.597			
22,500.00	12,593.42	22,753.17	12,846.20	137.11	147.55	-104.92	-9,856.79	1,983.55	981.93	706.31	275.62	3.563			
22,600.00	12,594.30	22,853.17	12,846.73	138.46	148.91	-104.90	-9,956.79	1,984.46	981.88	703.61	278.28	3.528			
22,700.00	12,595.17	22,953.17	12,847.25	139.81	150.27	-104.88	-10,056.78	1,985.37	981.84	700.90	280.94	3.495			
22,800.00	12,596.04	23,053.17	12,847.78	141.17	151.63	-104.86	-10,156.77	1,986.27	981.79	698.20	283.60	3.462			
22,875.30	12,596.70	23,128.47	12,848.17	142.19	152.66	-104.84	-10,232.07	1,986.96	981.76	696.16	285.60	3.438	ES, SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 101 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 224H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)						Rule Assigned:				Offset Well Error:		0.50 usft	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
0.00	0.00	0.00	1.00	0.50	0.50	73.46	696.00	2,344.00	2,445.15				
100.00	100.00	99.00	100.00	0.98	0.97	73.46	696.00	2,344.00	2,445.15	2,443.19	1.95	1,250.760	
200.00	200.00	199.00	200.00	1.56	1.56	73.46	696.00	2,344.00	2,445.15	2,442.03	3.12	784.648	
300.00	300.00	299.00	300.00	1.98	1.98	73.46	696.00	2,344.00	2,445.15	2,441.19	3.96	617.762	
400.00	400.00	362.94	363.94	2.33	2.25	73.47	695.91	2,344.51	2,445.88	2,441.31	4.57	535.101	
500.00	500.00	426.49	427.47	2.63	2.51	73.48	695.64	2,346.06	2,448.10	2,442.98	5.12	478.124	
600.00	600.00	500.00	500.91	2.91	2.78	73.52	695.09	2,349.16	2,451.84	2,446.18	5.65	433.651	
700.00	700.00	553.33	554.15	3.16	2.95	73.55	694.54	2,352.27	2,457.00	2,450.92	6.08	404.401	
800.00	800.00	616.56	617.20	3.40	3.12	73.60	693.72	2,356.91	2,463.68	2,457.20	6.47	380.652	
900.00	900.00	706.49	706.79	3.62	3.26	73.68	692.37	2,364.59	2,471.44	2,464.61	6.83	361.910	
1,000.00	1,000.00	806.11	806.03	3.76	3.50	-18.22	690.86	2,373.14	2,479.21	2,472.00	7.21	343.751	
1,100.00	1,099.98	905.87	905.41	4.00	3.74	-18.12	689.35	2,381.71	2,485.30	2,477.61	7.69	323.306	
1,200.00	1,199.88	1,005.77	1,004.93	4.24	3.97	-18.05	687.84	2,390.28	2,488.91	2,480.76	8.15	305.476	
1,300.00	1,299.63	1,105.75	1,104.53	4.46	4.20	-18.00	686.33	2,398.86	2,490.03	2,481.43	8.60	289.616	
1,400.00	1,399.25	1,205.74	1,204.14	4.60	4.42	-17.98	684.81	2,407.45	2,489.59	2,480.64	8.96	278.001	
1,500.00	1,498.87	1,305.73	1,303.75	4.78	4.64	-17.95	683.30	2,416.03	2,489.14	2,479.79	9.35	266.095	
1,600.00	1,598.49	1,405.73	1,403.36	4.96	4.85	-17.93	681.79	2,424.61	2,488.69	2,478.94	9.75	255.273	
1,700.00	1,698.11	1,505.72	1,502.98	5.14	5.06	-17.90	680.27	2,433.19	2,488.23	2,478.09	10.14	245.383	
1,800.00	1,797.73	1,605.71	1,602.59	5.32	5.27	-17.87	678.76	2,441.78	2,487.78	2,477.25	10.53	236.288	
1,900.00	1,897.34	1,704.50	1,701.00	5.49	5.48	-17.85	677.26	2,450.25	2,487.33	2,476.41	10.92	227.776	
1,957.97	1,955.09	1,752.43	1,748.73	5.60	5.58	-17.83	676.30	2,454.55	2,487.20	2,476.08	11.12	223.691	
2,000.00	1,996.96	1,786.46	1,782.59	5.67	5.65	-17.81	675.32	2,457.81	2,487.27	2,476.00	11.26	220.857	
2,100.00	2,096.58	1,867.35	1,862.96	5.85	5.83	-17.73	672.03	2,466.30	2,487.97	2,476.36	11.61	214.300	
2,200.00	2,196.20	1,948.06	1,942.97	6.04	6.00	-17.62	667.38	2,475.78	2,489.46	2,477.49	11.97	208.032	
2,300.00	2,295.72	2,031.42	2,025.39	6.23	6.17	-11.18	661.17	2,486.62	2,490.53	2,478.22	12.31	202.267	
2,400.00	2,394.97	2,130.96	2,123.71	6.43	6.35	-6.74	653.18	2,499.99	2,489.35	2,476.63	12.71	195.819	
2,500.00	2,493.89	2,230.39	2,221.92	6.64	6.55	-3.59	645.20	2,513.34	2,485.63	2,472.50	13.14	189.237	
2,600.00	2,592.40	2,329.64	2,319.94	6.85	6.76	-1.22	637.23	2,526.67	2,479.40	2,465.84	13.56	182.840	
2,700.00	2,690.45	2,428.64	2,417.72	7.07	6.96	0.66	629.29	2,539.96	2,470.67	2,456.68	13.99	176.630	
2,800.00	2,787.96	2,527.32	2,515.19	7.28	7.16	2.21	621.37	2,553.22	2,459.44	2,445.02	14.42	170.601	
2,900.00	2,884.87	2,625.62	2,612.27	7.49	7.36	3.53	613.48	2,566.42	2,445.73	2,430.88	14.84	164.779	
3,000.00	2,981.46	2,723.71	2,709.16	7.68	7.57	3.83	605.60	2,579.59	2,430.85	2,415.60	15.25	159.442	
3,100.00	3,078.05	2,821.80	2,806.04	7.87	7.77	4.13	597.73	2,592.76	2,416.04	2,400.39	15.65	154.361	
3,200.00	3,174.64	2,919.89	2,902.92	8.06	7.97	4.43	589.86	2,605.94	2,401.30	2,385.24	16.06	149.517	
3,300.00	3,271.24	3,017.97	2,999.80	8.26	8.18	4.74	581.98	2,619.11	2,386.62	2,370.15	16.47	144.911	
3,400.00	3,367.83	3,116.06	3,096.68	8.51	8.38	5.05	574.11	2,632.28	2,372.01	2,355.13	16.88	140.509	
3,500.00	3,464.42	3,214.15	3,193.56	8.80	8.59	5.36	566.24	2,645.46	2,357.47	2,340.18	17.30	136.309	
3,600.00	3,561.01	3,312.24	3,290.44	9.09	8.79	5.68	558.36	2,658.63	2,343.01	2,325.30	17.71	132.297	
3,700.00	3,657.60	3,410.33	3,387.32	9.38	9.00	6.00	550.49	2,671.80	2,328.61	2,310.48	18.13	128.462	
3,800.00	3,754.20	3,508.42	3,484.20	9.68	9.21	6.33	542.62	2,684.97	2,314.29	2,295.75	18.54	124.794	
3,900.00	3,850.79	3,606.51	3,581.09	9.98	9.41	6.66	534.74	2,698.15	2,300.05	2,281.08	18.96	121.284	
4,000.00	3,947.38	3,704.60	3,677.97	10.28	9.62	6.99	526.87	2,711.32	2,285.88	2,266.49	19.38	117.921	
4,100.00	4,043.97	3,802.69	3,774.85	10.59	9.83	7.33	519.00	2,724.49	2,271.79	2,251.98	19.81	114.698	
4,200.00	4,140.56	3,900.78	3,871.73	10.90	10.04	7.67	511.12	2,737.67	2,257.78	2,237.55	20.23	111.607	
4,300.00	4,237.16	3,998.87	3,968.61	11.21	10.25	8.01	503.25	2,750.84	2,243.85	2,223.20	20.65	108.641	
4,400.00	4,333.75	4,096.95	4,065.49	11.52	10.47	8.36	495.38	2,764.01	2,230.00	2,208.93	21.08	105.793	
4,500.00	4,430.34	4,195.04	4,162.37	11.84	10.68	8.72	487.50	2,777.19	2,216.24	2,194.74	21.51	103.057	
4,600.00	4,526.93	4,293.13	4,259.25	12.16	10.89	9.08	479.63	2,790.36	2,202.57	2,180.64	21.93	100.426	
4,700.00	4,623.53	4,391.22	4,356.14	12.48	11.11	9.44	471.75	2,803.53	2,188.98	2,166.62	22.36	97.895	
4,800.00	4,720.12	4,489.31	4,453.02	12.80	11.32	9.81	463.88	2,816.70	2,175.48	2,152.69	22.79	95.459	
4,900.00	4,816.71	4,587.40	4,549.90	13.12	11.54	10.18	456.01	2,829.88	2,162.07	2,138.85	23.22	93.113	
5,000.00	4,913.30	4,685.49	4,646.78	13.45	11.75	10.56	448.13	2,843.05	2,148.76	2,125.11	23.65	90.853	

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 102 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 224H - OH - Plan 1

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)										Rule Assigned:			Offset Site Error:		0.00 usft	
Reference		Offset		Semi Major Axis		Offset Wellbore Centre			Distance		Offset Well Error:		0.50 usft			
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Toolface (°)	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning			
5,100.00	5,009.89	4,783.58	4,743.66	13.78	11.97	10.94	440.26	2,856.22	2,135.53	2,111.45	24.08	88.674	CC			
5,200.00	5,106.49	4,881.67	4,840.54	14.10	12.19	11.32	432.39	2,869.40	2,122.41	2,097.89	24.52	86.572				
5,300.00	5,203.08	4,979.76	4,937.42	14.43	12.40	11.71	424.51	2,882.57	2,109.38	2,084.43	24.95	84.544				
5,400.00	5,299.67	5,077.85	5,034.30	14.75	12.62	12.11	416.64	2,895.74	2,096.46	2,071.09	25.37	82.621				
5,500.00	5,396.65	5,176.16	5,131.41	15.07	12.84	12.46	408.75	2,908.94	2,085.12	2,059.30	25.82	80.749				
5,600.00	5,494.23	5,274.81	5,228.84	15.36	13.06	12.81	400.83	2,922.19	2,076.42	2,050.16	26.27	79.056				
5,700.00	5,592.35	5,373.72	5,326.53	15.62	13.28	13.16	392.89	2,935.48	2,070.36	2,043.66	26.70	77.532	CC			
5,800.00	5,690.94	5,472.83	5,424.42	15.86	13.50	13.50	384.94	2,948.79	2,066.92	2,039.79	27.13	76.173				
5,881.13	5,771.22	5,553.34	5,503.94	16.03	13.68	13.77	378.47	2,959.60	2,066.06	2,038.59	27.48	75.189				
5,900.00	5,789.93	5,572.07	5,522.44	16.07	13.72	13.83	376.97	2,962.11	2,066.11	2,038.55	27.56	74.973				
6,000.00	5,889.26	5,671.38	5,620.52	16.25	13.94	14.16	369.00	2,975.45	2,067.91	2,039.93	27.97	73.926				
6,100.00	5,988.86	5,770.67	5,718.60	16.41	14.16	14.48	361.03	2,988.79	2,072.30	2,043.93	28.38	73.029				
6,200.00	6,088.66	5,869.90	5,816.60	16.53	14.38	14.79	353.06	3,002.11	2,079.28	2,050.51	28.77	72.278				
6,300.00	6,188.59	5,968.98	5,914.46	16.64	14.61	15.09	345.11	3,015.42	2,088.83	2,059.69	29.14	71.676				
6,400.00	6,288.58	6,067.85	6,012.12	16.71	14.83	87.80	337.17	3,028.70	2,100.93	2,071.49	29.44	71.362				
6,500.00	6,388.58	6,166.62	6,109.67	16.76	15.05	88.03	329.25	3,041.96	2,114.10	2,084.39	29.71	71.163				
6,600.00	6,488.58	6,265.39	6,207.22	16.82	15.27	88.25	321.32	3,055.22	2,127.31	2,097.34	29.98	70.969				
6,700.00	6,588.58	6,364.16	6,304.78	16.88	15.49	88.48	313.39	3,068.49	2,140.55	2,110.31	30.24	70.779				
6,800.00	6,688.58	6,462.93	6,402.33	16.94	15.71	88.70	305.46	3,081.75	2,153.83	2,123.32	30.51	70.593				
6,900.00	6,788.58	6,561.70	6,499.88	17.00	15.93	88.92	297.53	3,095.02	2,167.13	2,136.37	30.77	70.436				
7,000.00	6,888.58	6,745.99	6,682.48	17.05	16.29	89.27	284.79	3,116.33	2,178.70	2,147.53	31.18	69.884				
7,100.00	6,988.58	6,940.52	6,876.27	17.11	16.61	89.50	276.26	3,130.61	2,186.01	2,154.46	31.54	69.305				
7,200.00	7,088.58	7,136.24	7,071.86	17.17	16.82	89.59	272.79	3,136.42	2,188.96	2,157.17	31.79	68.853				
7,300.00	7,188.58	7,252.97	7,188.58	17.23	16.86	89.59	272.71	3,136.55	2,189.03	2,157.15	31.87	68.679				
7,400.00	7,288.58	7,352.97	7,288.58	17.29	16.89	89.59	272.71	3,136.55	2,189.03	2,157.06	31.97	68.478				
7,500.00	7,388.58	7,452.97	7,388.58	17.35	16.93	89.59	272.71	3,136.55	2,189.03	2,156.97	32.06	68.278				
7,600.00	7,488.58	7,552.97	7,488.58	17.41	16.96	89.59	272.71	3,136.55	2,189.03	2,156.87	32.15	68.078				
7,700.00	7,588.58	7,652.97	7,588.58	17.47	17.00	89.59	272.71	3,136.55	2,189.03	2,156.78	32.25	67.878				
7,800.00	7,688.58	7,752.97	7,688.58	17.53	17.03	89.59	272.71	3,136.55	2,189.03	2,156.68	32.34	67.678				
7,900.00	7,788.58	7,852.97	7,788.58	17.59	17.07	89.59	272.71	3,136.55	2,189.03	2,156.59	32.44	67.478				
8,000.00	7,888.58	7,952.97	7,888.58	17.65	17.11	89.59	272.71	3,136.55	2,189.03	2,156.49	32.54	67.278				
8,100.00	7,988.58	8,052.97	7,988.58	17.71	17.14	89.59	272.71	3,136.55	2,189.03	2,156.39	32.63	67.079				
8,200.00	8,088.58	8,152.97	8,088.58	17.77	17.18	89.59	272.71	3,136.55	2,189.03	2,156.29	32.73	66.879				
8,300.00	8,188.58	8,252.97	8,188.58	17.83	17.22	89.59	272.71	3,136.55	2,189.03	2,156.20	32.83	66.680				
8,400.00	8,288.58	8,352.97	8,288.58	17.89	17.26	89.59	272.71	3,136.55	2,189.03	2,156.10	32.93	66.481				
8,500.00	8,388.58	8,452.97	8,388.58	17.95	17.29	89.59	272.71	3,136.55	2,189.03	2,156.00	33.03	66.282				
8,600.00	8,488.58	8,552.97	8,488.58	18.02	17.33	89.59	272.71	3,136.55	2,189.03	2,155.90	33.13	66.083				
8,700.00	8,588.58	8,652.97	8,588.58	18.08	17.37	89.59	272.71	3,136.55	2,189.03	2,155.80	33.23	65.885				
8,800.00	8,688.58	8,752.97	8,688.58	18.14	17.41	89.59	272.71	3,136.55	2,189.03	2,155.70	33.33	65.686				
8,900.00	8,788.58	8,852.97	8,788.58	18.20	17.45	89.59	272.71	3,136.55	2,189.03	2,155.60	33.43	65.488				
9,000.00	8,888.58	8,952.97	8,888.58	18.26	17.49	89.59	272.71	3,136.55	2,189.03	2,155.50	33.53	65.291				
9,100.00	8,988.58	9,052.97	8,988.58	18.32	17.53	89.59	272.71	3,136.55	2,189.03	2,155.40	33.63	65.093				
9,200.00	9,088.58	9,152.97	9,088.58	18.39	17.57	89.59	272.71	3,136.55	2,189.03	2,155.29	33.73	64.896				
9,300.00	9,188.58	9,252.97	9,188.58	18.45	17.61	89.59	272.71	3,136.55	2,189.03	2,155.19	33.83	64.700				
9,400.00	9,288.58	9,352.97	9,288.58	18.51	17.65	89.59	272.71	3,136.55	2,189.03	2,155.09	33.94	64.503				
9,500.00	9,388.58	9,452.97	9,388.58	18.57	17.69	89.59	272.71	3,136.55	2,189.03	2,154.99	34.04	64.307				
9,600.00	9,488.58	9,552.97	9,488.58	18.64	17.74	89.59	272.71	3,136.55	2,189.03	2,154.88	34.14	64.111				
9,700.00	9,588.58	9,652.97	9,588.58	18.70	17.78	89.59	272.71	3,136.55	2,189.03	2,154.78	34.25	63.916				
9,800.00	9,688.58	9,752.97	9,688.58	18.76	17.82	89.59	272.71	3,136.55	2,189.03	2,154.67	34.35	63.721				
9,900.00	9,788.58	9,852.97	9,788.58	18.83	17.86	89.59	272.71	3,136.55	2,189.03	2,154.57	34.46	63.527				
10,000.00	9,888.58	9,952.97	9,888.58	18.89	17.91	89.59	272.71	3,136.55	2,189.03	2,154.46	34.56	63.332				
10,100.00	9,988.58	10,052.97	9,988.58	18.95	17.95	89.59	272.71	3,136.55	2,189.03	2,154.36	34.67	63.139				

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 103 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 224H - OH - Plan 1													Offset Site Error:	0.00 usft
Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)				Offset		Semi Major Axis		Offset Wellbore Centre		Rule Assigned: Distance		Offset Well Error:		0.50 usft
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)	Highside Tooflance (")	+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)	Minimum Separation (usft)	Separation Factor	Warning	
10,200.00	10,088.58	10,152.97	10,088.58	19.02	17.99	89.59	272.71	3,136.55	2,189.03	2,154.25	34.78	62.945		
10,300.00	10,188.58	10,252.97	10,188.58	19.08	18.04	89.59	272.71	3,136.55	2,189.03	2,154.14	34.88	62.752		
10,400.00	10,288.58	10,352.97	10,288.58	19.15	18.08	89.59	272.71	3,136.55	2,189.03	2,154.03	34.99	62.560		
10,500.00	10,388.58	10,452.97	10,388.58	19.21	18.12	89.59	272.71	3,136.55	2,189.03	2,153.93	35.10	62.368		
10,600.00	10,488.58	10,552.97	10,488.58	19.27	18.17	89.59	272.71	3,136.55	2,189.03	2,153.82	35.21	62.176		
10,700.00	10,588.58	10,652.97	10,588.58	19.34	18.21	89.59	272.71	3,136.55	2,189.03	2,153.71	35.32	61.985		
10,800.00	10,688.58	10,752.97	10,688.58	19.40	18.26	89.59	272.71	3,136.55	2,189.03	2,153.60	35.42	61.794		
10,900.00	10,788.58	10,852.97	10,788.58	19.47	18.30	89.59	272.71	3,136.55	2,189.03	2,153.49	35.53	61.604		
11,000.00	10,888.58	10,952.97	10,888.58	19.53	18.35	89.59	272.71	3,136.55	2,189.03	2,153.38	35.64	61.414		
11,100.00	10,988.58	11,052.97	10,988.58	19.60	18.40	89.59	272.71	3,136.55	2,189.03	2,153.27	35.75	61.225		
11,200.00	11,088.58	11,152.97	11,088.58	19.66	18.44	89.59	272.71	3,136.55	2,189.03	2,153.16	35.86	61.037		
11,300.00	11,188.58	11,252.97	11,188.58	19.73	18.49	89.59	272.71	3,136.55	2,189.03	2,153.05	35.98	60.848		
11,400.00	11,288.58	11,352.97	11,288.58	19.79	18.54	89.59	272.71	3,136.55	2,189.03	2,152.94	36.09	60.661		
11,500.00	11,388.58	11,452.97	11,388.58	19.86	18.58	89.59	272.71	3,136.55	2,189.03	2,152.83	36.20	60.473		
11,600.00	11,488.58	11,552.97	11,488.58	19.92	18.63	89.59	272.71	3,136.55	2,189.03	2,152.72	36.31	60.287		
11,700.00	11,588.58	11,652.97	11,588.58	19.99	18.68	89.59	272.71	3,136.55	2,189.03	2,152.60	36.42	60.101		
11,800.00	11,688.58	11,752.97	11,688.58	20.05	18.73	89.59	272.71	3,136.55	2,189.03	2,152.49	36.54	59.915		
11,900.00	11,788.58	11,852.97	11,788.58	20.12	18.77	89.59	272.71	3,136.55	2,189.03	2,152.38	36.65	59.730		
12,000.00	11,888.58	11,952.97	11,888.58	20.19	18.82	89.59	272.71	3,136.55	2,189.03	2,152.26	36.76	59.546		
12,100.00	11,988.51	12,052.90	11,988.51	20.25	18.87	-89.98	272.71	3,136.55	2,189.02	2,152.21	36.82	59.456		
12,108.00	11,996.47	12,060.86	11,996.47	20.25	18.87	-90.00	272.71	3,136.55	2,189.02	2,152.21	36.82	59.457		
12,200.00	12,086.82	12,151.20	12,086.82	20.31	18.92	-90.42	272.71	3,136.55	2,189.09	2,152.28	36.81	59.474		
12,300.00	12,180.57	12,242.69	12,178.30	20.35	18.95	-91.19	272.66	3,136.56	2,189.63	2,152.87	36.75	59.578		
12,400.00	12,266.93	12,313.28	12,248.65	20.39	19.01	-91.78	267.46	3,137.15	2,191.76	2,155.06	36.70	59.715		
12,500.00	12,343.26	12,386.66	12,320.52	20.44	19.13	-92.27	252.98	3,138.80	2,196.08	2,159.34	36.74	59.778		
12,600.00	12,407.24	12,463.77	12,393.38	20.52	19.32	-92.65	228.08	3,141.63	2,202.66	2,165.76	36.90	59.687		
12,700.00	12,456.94	12,545.97	12,466.59	20.67	19.58	-92.94	191.10	3,145.85	2,211.52	2,174.27	37.25	59.369		
12,800.00	12,490.84	12,635.24	12,539.18	20.88	19.93	-93.14	139.62	3,151.71	2,222.54	2,184.71	37.83	58.755		
12,900.00	12,507.91	12,734.59	12,609.40	21.18	20.43	-93.31	69.96	3,159.65	2,235.50	2,196.84	38.66	57.822		
13,000.00	12,510.43	12,850.63	12,674.64	21.56	21.16	-94.30	-25.14	3,170.49	2,249.79	2,210.01	39.78	56.551		
13,100.00	12,511.30	12,995.68	12,727.01	22.01	22.27	-95.58	-159.13	3,185.75	2,263.43	2,222.18	41.25	54.871		
13,200.00	12,512.18	13,211.23	12,744.36	22.52	24.19	-95.91	-372.03	3,208.92	2,274.57	2,231.35	43.22	52.631		
13,300.00	12,513.05	13,485.12	12,745.80	23.10	26.84	-95.87	-645.61	3,219.86	2,276.35	2,230.72	45.63	49.889		
13,400.00	12,513.92	13,585.12	12,746.33	23.73	27.84	-95.86	-745.61	3,220.77	2,276.36	2,229.11	47.25	48.175		
13,500.00	12,514.80	13,685.12	12,746.85	24.41	28.87	-95.85	-845.60	3,221.67	2,276.37	2,227.40	48.98	46.480		
13,600.00	12,515.67	13,785.12	12,747.38	25.15	29.92	-95.84	-945.59	3,222.58	2,276.39	2,225.60	50.79	44.820		
13,700.00	12,516.55	13,885.12	12,747.91	25.93	30.99	-95.83	-1,045.59	3,223.49	2,276.40	2,223.71	52.68	43.208		
13,800.00	12,517.42	13,985.12	12,748.43	26.76	32.08	-95.82	-1,145.58	3,224.40	2,276.41	2,221.76	54.65	41.652		
13,900.00	12,518.29	14,085.12	12,748.96	27.63	33.19	-95.82	-1,245.57	3,225.31	2,276.42	2,219.74	56.69	40.159		
14,000.00	12,519.17	14,185.11	12,749.48	28.53	34.32	-95.81	-1,345.57	3,226.22	2,276.44	2,217.66	58.78	38.731		
14,100.00	12,520.04	14,285.11	12,750.01	29.47	35.46	-95.80	-1,445.56	3,227.13	2,276.45	2,215.53	60.92	37.368		
14,200.00	12,520.91	14,385.11	12,750.53	30.44	36.61	-95.79	-1,545.56	3,228.04	2,276.46	2,213.35	63.11	36.072		
14,300.00	12,521.79	14,485.11	12,751.06	31.44	37.78	-95.78	-1,645.55	3,228.95	2,276.47	2,211.13	65.34	34.840		
14,400.00	12,522.66	14,585.11	12,751.59	32.46	38.96	-95.77	-1,745.54	3,229.86	2,276.49	2,208.88	67.61	33.671		
14,500.00	12,523.53	14,685.11	12,752.11	33.51	40.15	-95.76	-1,845.54	3,230.76	2,276.50	2,206.58	69.91	32.562		
14,600.00	12,524.41	14,785.11	12,752.64	34.58	41.36	-95.75	-1,945.53	3,231.67	2,276.51	2,204.26	72.25	31.510		
14,700.00	12,525.28	14,885.11	12,753.16	35.67	42.57	-95.75	-2,045.53	3,232.58	2,276.52	2,201.92	74.61	30.513		
14,800.00	12,526.16	14,985.11	12,753.69	36.78	43.79	-95.74	-2,145.52	3,233.49	2,276.54	2,199.54	76.99	29.568		
14,900.00	12,527.03	15,085.11	12,754.21	37.90	45.01	-95.73	-2,245.51	3,234.40	2,276.55	2,197.15	79.40	28.671		
15,000.00	12,527.90	15,185.11	12,754.74	39.04	46.25	-95.72	-2,345.51	3,235.31	2,276.56	2,194.73	81.83	27.820		
15,100.00	12,528.78	15,285.11	12,755.27	40.20	47.49	-95.71	-2,445.50	3,236.22	2,276.57	2,192.29	84.28	27.012		
15,200.00	12,529.65	15,385.11	12,755.79	41.37	48.74	-95.70	-2,545.50	3,237.13	2,276.59	2,189.84	86.75	26.244		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 224H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)		Rule Assigned:							Offset Well Error:		0.50 usft		
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)			
15,300.00	12,530.52	15,485.11	12,756.32	42.55	49.99	-95.69	-2,645.49	3,238.04	2,276.60	2,187.37	89.23	25.514	
15,400.00	12,531.40	15,585.11	12,756.84	43.74	51.25	-95.68	-2,745.48	3,238.94	2,276.61	2,184.89	91.72	24.820	
15,500.00	12,532.27	15,685.11	12,757.37	44.94	52.52	-95.67	-2,845.48	3,239.85	2,276.63	2,182.39	94.23	24.159	
15,600.00	12,533.14	15,785.11	12,757.89	46.15	53.79	-95.67	-2,945.47	3,240.76	2,276.64	2,179.89	96.75	23.530	
15,700.00	12,534.02	15,885.10	12,758.42	47.37	55.06	-95.66	-3,045.46	3,241.67	2,276.65	2,177.37	99.29	22.930	
15,800.00	12,534.89	15,985.10	12,758.94	48.59	56.34	-95.65	-3,145.46	3,242.58	2,276.67	2,174.84	101.83	22.357	
15,900.00	12,535.76	16,085.10	12,759.47	49.83	57.62	-95.64	-3,245.45	3,243.49	2,276.68	2,172.30	104.38	21.811	
16,000.00	12,536.64	16,185.10	12,760.00	51.07	58.91	-95.63	-3,345.45	3,244.40	2,276.69	2,169.75	106.94	21.289	
16,100.00	12,537.51	16,285.10	12,760.52	52.32	60.20	-95.62	-3,445.44	3,245.31	2,276.71	2,167.19	109.51	20.789	
16,200.00	12,538.39	16,385.10	12,761.05	53.57	61.49	-95.61	-3,545.43	3,246.22	2,276.72	2,164.63	112.09	20.311	
16,300.00	12,539.26	16,485.10	12,761.57	54.83	62.78	-95.60	-3,645.43	3,247.13	2,276.73	2,162.06	114.68	19.853	
16,400.00	12,540.13	16,585.10	12,762.10	56.09	64.08	-95.60	-3,745.42	3,248.03	2,276.75	2,159.48	117.27	19.415	
16,500.00	12,541.01	16,685.10	12,762.62	57.36	65.38	-95.59	-3,845.42	3,248.94	2,276.76	2,156.89	119.87	18.994	
16,600.00	12,541.88	16,785.10	12,763.15	58.64	66.69	-95.58	-3,945.41	3,249.85	2,276.77	2,154.30	122.47	18.590	
16,700.00	12,542.75	16,885.10	12,763.68	59.91	67.99	-95.57	-4,045.40	3,250.76	2,276.79	2,151.71	125.08	18.203	
16,800.00	12,543.63	16,985.10	12,764.20	61.20	69.30	-95.56	-4,145.40	3,251.67	2,276.80	2,149.11	127.69	17.830	
16,900.00	12,544.50	17,085.10	12,764.73	62.48	70.61	-95.55	-4,245.39	3,252.58	2,276.82	2,146.50	130.31	17.472	
17,000.00	12,545.37	17,185.10	12,765.25	63.77	71.93	-95.54	-4,345.39	3,253.49	2,276.83	2,143.89	132.94	17.127	
17,100.00	12,546.25	17,285.10	12,765.78	65.06	73.24	-95.53	-4,445.38	3,254.40	2,276.84	2,141.28	135.57	16.795	
17,200.00	12,547.12	17,385.10	12,766.30	66.36	74.56	-95.52	-4,545.37	3,255.31	2,276.86	2,138.66	138.20	16.475	
17,300.00	12,547.99	17,485.09	12,766.83	67.66	75.88	-95.52	-4,645.37	3,256.22	2,276.87	2,136.04	140.83	16.167	
17,400.00	12,548.87	17,585.09	12,767.36	68.96	77.20	-95.51	-4,745.36	3,257.12	2,276.89	2,133.41	143.47	15.870	
17,500.00	12,549.74	17,685.09	12,767.88	70.26	78.52	-95.50	-4,845.35	3,258.03	2,276.90				

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 105 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Offset Design: Junior Mint Fed Pad - Junior Mint Fed 224H - OH - Plan 1

Offset Site Error: 0.00 usft

Offset Well Error: 0.50 usft

Survey Program: 0-MWD+HRGM+SAG+FDIR (rev.5)														Rule Assigned:	
Reference		Offset		Semi Major Axis		Highside Toolface (°)	Offset Wellbore Centre		Distance		Minimum Separation (usft)	Separation Factor	Warning		
Measured Depth (usft)	Vertical Depth (usft)	Measured Depth (usft)	Vertical Depth (usft)	Reference (usft)	Offset (usft)		+N/-S (usft)	+E/-W (usft)	Between Centres (usft)	Between Ellipses (usft)					
20,500.00	12,575.95	20,685.07	12,783.65	110.12	118.66	-95.23	-7,845.17	3,285.30	2,277.35	2,050.94	226.42	10.058			
20,600.00	12,576.82	20,785.07	12,784.18	111.47	120.01	-95.22	-7,945.16	3,286.21	2,277.37	2,048.26	229.11	9.940			
20,700.00	12,577.70	20,885.07	12,784.70	112.81	121.36	-95.22	-8,045.16	3,287.12	2,277.39	2,045.57	231.81	9.824			
20,800.00	12,578.57	20,985.07	12,785.23	114.16	122.71	-95.21	-8,145.15	3,288.03	2,277.40	2,042.89	234.51	9.711			
20,900.00	12,579.44	21,085.07	12,785.76	115.51	124.06	-95.20	-8,245.15	3,288.94	2,277.42	2,040.20	237.21	9.601			
21,000.00	12,580.32	21,185.07	12,786.28	116.85	125.41	-95.19	-8,345.14	3,289.85	2,277.43	2,037.52	239.91	9.493			
21,100.00	12,581.19	21,285.07	12,786.81	118.20	126.76	-95.18	-8,445.13	3,290.76	2,277.45	2,034.83	242.62	9.387			
21,200.00	12,582.06	21,385.07	12,787.33	119.55	128.11	-95.17	-8,545.13	3,291.67	2,277.47	2,032.15	245.32	9.284			
21,300.00	12,582.94	21,485.07	12,787.86	120.89	129.46	-95.16	-8,645.12	3,292.57	2,277.48	2,029.46	248.02	9.183			
21,400.00	12,583.81	21,585.07	12,788.38	122.24	130.82	-95.15	-8,745.12	3,293.48	2,277.50	2,026.77	250.73	9.084			
21,500.00	12,584.69	21,685.07	12,788.91	123.59	132.17	-95.14	-8,845.11	3,294.39	2,277.51	2,024.08	253.43	8.987			
21,600.00	12,585.56	21,785.07	12,789.43	124.94	133.52	-95.14	-8,945.10	3,295.30	2,277.53	2,021.39	256.14	8.892			
21,700.00	12,586.43	21,885.07	12,789.96	126.29	134.87	-95.13	-9,045.10	3,296.21	2,277.55	2,018.70	258.84	8.799			
21,800.00	12,587.31	21,985.07	12,790.49	127.64	136.23	-95.12	-9,145.09	3,297.12	2,277.56	2,016.01	261.55	8.708			
21,900.00	12,588.18	22,085.07	12,791.01	128.99	137.58	-95.11	-9,245.08	3,298.03	2,277.58	2,013.32	264.26	8.619			
22,000.00	12,589.05	22,185.07	12,791.54	130.34	138.94	-95.10	-9,345.08	3,298.94	2,277.60	2,010.63	266.97	8.531			
22,100.00	12,589.93	22,285.07	12,792.06	131.70	140.29	-95.09	-9,445.07	3,299.85	2,277.61	2,007.94	269.67	8.446			
22,200.00	12,590.80	22,385.06	12,792.59	133.05	141.64	-95.08	-9,545.07	3,300.76	2,277.63	2,005.25	272.38	8.362			
22,300.00	12,591.67	22,485.06	12,793.11	134.40	143.00	-95.07	-9,645.06	3,301.66	2,277.65	2,002.55	275.09	8.280			
22,400.00	12,592.55	22,585.06	12,793.64	135.75	144.35	-95.07	-9,745.05	3,302.57	2,277.66	1,999.86	277.80	8.199			
22,500.00	12,593.42	22,685.06	12,794.17	137.11	145.71	-95.06	-9,845.05	3,303.48	2,277.68	1,997.17	280.51	8.120			
22,600.00	12,594.30	22,785.06	12,794.69	138.46	147.06	-95.05	-9,945.04	3,304.39	2,277.70	1,994.47	283.23	8.042			
22,700.00	12,595.17	22,885.06	12,795.22	139.81	148.42	-95.04	-10,045.04	3,305.30	2,277.72	1,991.78	285.94	7.966			
22,800.00	12,596.04	22,985.06	12,795.74	141.17	149.78	-95.03	-10,145.03	3,306.21	2,277.73	1,989.08	288.65	7.891			
22,875.30	12,596.70	23,060.36	12,796.14	142.19	150.73	-95.02	-10,220.33	3,306.89	2,277.75	1,987.14	290.60	7.838	ES, SF		

CC - Min centre to center distance or convergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:55PM

Page 106 of 108

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Reference Depths are relative to GE 3221 + 26 @ 3247.00usft (26' KB) Coordinates are relative to: Junior Mint Fed 217H


Offset Depths are relative to Offset Datum

Coordinate System is US State Plane 1983, New Mexico Eastern Zone

Central Meridian is -104.3333333

Grid Convergence at Surface is: 0.52°

Ladder Plot



LEGEND

Junior Mint Fed 131H, OH, Plan 1 V0	Junior Mint Fed 224H, OH, Plan 1 V0	Junior Mint Fed 137H, OH, Plan 1 V0
Junior Mint Fed 138H, OH, Plan 1 V0	Junior Mint Fed 223H, OH, Plan 1 V0	Junior Mint Fed 151H, OH, Plan 1 V0
Junior Mint Fed 152H, OH, Plan 1 V0	Junior Mint Fed 132H, OH, Plan 1 V0	Junior Mint Fed 212H, OH, Plan 1 V0
Junior Mint Fed 133H, OH, Plan 1 V0	Junior Mint Fed 156H, OH, Plan 1 V0	Junior Mint Fed 215H, OH, Plan 1 V0
Junior Mint Fed 213H, OH, Plan 1 V0	Junior Mint Fed 134H, OH, Plan 1 V0	Junior Mint Fed 222H, OH, Plan 1 V0
Junior Mint Fed 221H, OH, Plan 1 V0	Junior Mint Fed 135H, OH, Plan 1 V0	Junior Mint Fed 214H, OH, Plan 1 V0
Junior Mint Fed 211H, OH, Plan 1 V0	(O) Montera Federal 023H, OH, OH V0	Junior Mint Fed 216H, OH, Plan 1 V0

Total Directional Anticollision Report



Company:	Civitas Resources	Local Co-ordinate Reference:	Well Junior Mint Fed 217H
Project:	Lea County, NM (NAD 83)	TVD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Reference Site:	Junior Mint Fed Pad	MD Reference:	GE 3221 + 26 @ 3247.00usft (26' KB)
Site Error:	0.00 usft	North Reference:	Grid
Reference Well:	Junior Mint Fed 217H	Survey Calculation Method:	Minimum Curvature
Well Error:	0.50 usft	Output errors are at	2.00 sigma
Reference Wellbore	OH	Database:	.Total Directional Production DB
Reference Design:	Plan 1	Offset TVD Reference:	Reference Datum

Reference Depths are relative to GE 3221 + 26 @ 3247.00usft (26' KB)Coordinates are relative to: Junior Mint Fed 217H


Offset Depths are relative to Offset Datum

Coordinate System is US State Plane 1983, New Mexico Eastern Zone

Central Meridian is -104.3333333

Grid Convergence at Surface is: 0.52°

Separation Factor Plot



LEGEND

Junior Mint Fed 131H, OH, Plan 1 V0	Junior Mint Fed 224H, OH, Plan 1 V0	Junior Mint Fed 137H, OH, Plan 1 V0
Junior Mint Fed 138H, OH, Plan 1 V0	Junior Mint Fed 223H, OH, Plan 1 V0	Junior Mint Fed 151H, OH, Plan 1 V0
Junior Mint Fed 152H, OH, Plan 1 V0	Junior Mint Fed 132H, OH, Plan 1 V0	Junior Mint Fed 212H, OH, Plan 1 V0
Junior Mint Fed 133H, OH, Plan 1 V0	Junior Mint Fed 156H, OH, Plan 1 V0	Junior Mint Fed 215H, OH, Plan 1 V0
Junior Mint Fed 213H, OH, Plan 1 V0	Junior Mint Fed 134H, OH, Plan 1 V0	Junior Mint Fed 222H, OH, Plan 1 V0
Junior Mint Fed 221H, OH, Plan 1 V0	Junior Mint Fed 135H, OH, Plan 1 V0	Junior Mint Fed 214H, OH, Plan 1 V0
Junior Mint Fed 211H, OH, Plan 1 V0	(O) Montera Federal 023H, OH, OH V0	Junior Mint Fed 216H, OH, Plan 1 V0

CC - Min centre to center distance or covergent point, SF - min separation factor, ES - min ellipse separation

3/25/2025 1:45:51PM

Page 108 of 108

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/ocd/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 476281

CONDITIONS

Operator: Civitas Permian Operating, LLC 555 17th Street Denver, CO 80202	OGRID: 332195
	Action Number: 476281
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
matthew.gomez	Any previous COA's not addressed within the updated COA's still apply.	6/25/2025