

Phone: (505) 476-3441
General Information
Phone: (505) 629-6116

Online Phone Directory Visit:
<https://www.emnrd.nm.gov/ocd/contact-us/>

State of New Mexico
Energy, Minerals and Natural Resources

Form **Page 1 of 6**
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-56167
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-67620001
7. Lease Name or Unit Agreement Name War Pigeon Fed Com
8. Well Number 422H
9. OGRID Number 332762
10. Pool name or Wildcat Purple Sage; Wolfcamp (Gas) Pool (98220)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other
2. Name of Operator Admiral Permian Operating, LLC
3. Address of Operator 200 N. Loraine St., Suite 800, Midland, Texas 79701
4. Well Location Unit Letter <u>Unit M/Lot 7</u> <u>930</u> feet from the <u>South</u> line and <u>200</u> feet from the <u>West</u> line Section <u>6</u> Township <u>24 South</u> Range <u>27 East</u> NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3,253'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
DOWNHOLE COMMINGLE <input type="checkbox"/>	P AND A <input type="checkbox"/>
CLOSED-LOOP SYSTEM <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

By Action Number 491353 the Oil Conservation Division approved a request by Admiral Permian Operating, LLC ("Admiral") to change the surface casing from a 14.75" hole and 10.75" casing to a 17.5" hole and 13.375" casing. This amendment to the drilling plan was requested in order allow Admiral the ability to run an additional intermediate casing string in the event any hazards such as large water flows due to the Capitan Reef or karsts were encountered.

In conjunction with the surface casing amendment, attached please find the contingent casing design proposed by Admiral. This casing program will only be used in the event a hazard is encountered during drilling operations. Also, the casing setting depth of the contingent intermediate casing string has been estimated and may be adjusted depending on the depth of the issue. If the contingent intermediate casing string is not run, the casing program for the well will be in conformance with that approved by the APD and the approved surface casing amendment.

Admiral respectfully requests OCD approval of the attached contingency casing design.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: David Catanach TITLE: Regulatory Agent DATE: 9/25/25

Type or print name David Catanach E-mail address: catanach_david@comcast.net PHONE: (505) 690-9453
For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____
Conditions of Approval (if any): _____

War Pigeon Fed Com No. 422H: Proposed Casing Program w/10.75" Contingency String

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Length	Grade	Weight	Joint Type	Collapse	Burst	Yield Strength Body	Yield Strength Joint	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	Surface	17.50	13.375	New	API	N	0'	525	0	525	3299	2774	525	J-55	54.5	BTC	1130	2740	853000	909000	4.83	1.83	DRY	7.07	DRY	6.63
2	Contingent Intermediate	12.25	10.750	New	API	N	0'	2000	0	2000	3299	1299	2000	J-55	45.5	BTC	2090	3580	715000	796000	2.12	2.39	DRY	4.17	DRY	3.74
3	Intermediate	9.875	7.625	New	API	N	0'	8473	0	8323	3299	-5024	8473	HCP-110	29.7	BTC	6700	9460	940000	960000	1.63	5.17	DRY	2.73	DRY	2.67
4	Production	6.75	5.50	New	Non API	N	0'	19247	0	8900	3299	-5601	19247	CY P-110	20	TLW	12200	14360	729000	668000	2.05	1.25	WET	2.16	WET	2.36

Surface Casing Design Criteria and Load Case Assumptions

- 1.Collapse
 - a.Full Internal Evacuation: External force equal to the mud gradient (.434 psi/ft) in which the casing will be run. No internal force is present in a full internal evacuation.
 - b.Cementing: Collapse force equal to the gradient of planned cement slurries to planned cement tops with an internal force equal to the mud gradient of freshwater displacement fluid (0.434 psi/ft).
- 2.Burst
 - a.Pressure Test: Casing is tested in accordance with BLM Onshore Order No. 2 with 0.22 psi/ft or 1500 psi, whichever is greater. Test is not to exceed 70% of the minimum internal yield.
- 3.Tensile
 - a.Overpull: A tensile force of 100,000 lbs over string weight.

Contingent Intermediate Casing Design Criteria and Load Case Assumptions

- 1.Collapse
 - a.Full Internal Evacuation: Collapse force is equal to mud gradient (.494 psi/ft) in which the casing will be run. No internal force is present in a full internal evacuation.
 - b.Cementing: External forces is equal to the gradient of planned cement slurries to planned cement tops with an internal force equal to the mud gradient of freshwater displacement fluid (0.43 psi/ft)
- 2.Burst
 - a.Pressure Test: Casing is tested in accordance with BLM Onshore Order No. 2 with 0.22 psi/ft or 1500 psi, whichever is greater. Test is not to exceed 70% of the minimum internal yield.
 - b.Full Displacement to Gas: Internal force would be the pore pressure gradient at the deepest TVD minus a full column of gas. External force fresh water gradient at casing shoe.
- 3.Tensile
 - a.Overpull: A tensile force of 100,000 lbs over string weight.

Intermediate Casing Design Criteria and Load Case Assumptions

- 1.Collapse
 - a.Full Internal Evacuation: Collapse force is equal to mud gradient (.494 psi/ft) in which the casing will be run. No internal force is present in a full internal evacuation.
 - b.Cementing: External forces is equal to the gradient of planned cement slurries to planned cement tops with an internal force equal to the mud gradient of freshwater displacement fluid (0.43 psi/ft)
- 2.Burst
 - a.Pressure Test: Casing is tested in accordance with BLM Onshore Order No. 2 with 0.22 psi/ft or 1500 psi, whichever is greater. Test is not to exceed 70% of the minimum internal yield.
 - b.Full Displacement to Gas: Internal force would be the pore pressure gradient at the deepest TVD minus a full column of gas. External force fresh water gradient at casing shoe.
- 3.Tensile
 - a.Overpull: A tensile force of 100,000 lbs over string weight.

Production Casing Design Criteria and Load Case Assumptions

- 1.Collapse
 - a.Full Internal Evacuation: Collapse force is equal to mud gradient (.494 psi/ft) in which the casing will be run. No internal force is present in a full internal evacuation.
 - b.Cementing: External force is equal to the gradient of planned cement slurries to planned cement tops with an internal force equal to the mud gradient of freshwater displacement fluid (0.43 psi/ft)
- 2.Burst
 - a.Pressure Test: Pressure test will be to 80% of Internal Yield Pressure of the casing intended for Fracture stimulation
- 3.Tensile
 - a.Overpull: A tensile force of 100,000 lbs over string weight with a buoyancy factor of 0.809 in Oil Based Mud (12.5 ppg).

String	Lead/Tail	Top of Cement	Sacks	Yield	Density	Cu Ft	Excess%	Cement Type	Additives
Surface	Lead	0	266	1.41	12.8	375	125	Class C	Salt, Defoamer, LCM
	Tail	225	379	1.33	14.8	504	125	Class C	-
Contingent Intermediate	Lead	0	260	2.4	11	624	100	Trident 8LT	Fluid Loss, Expansion Agent, LCM, Dispersant, retarder
	Tail	1500	75	1.67	13.5	125	30	Class C	Gel, Fluid Loss
Intermediate	Lead	0	1370	2.4	11	3288	100	Trident 8LT	Fluid Loss, Expansion Agent, LCM, Dispersant, retarder
	Tail	7473	180	1.67	13.5	301	30	Class C	Gel, Fluid Loss
Production	Tail	6482	955	1.45	13.2	1385	30	Class C 35/65 Poz	Gel, Latex, Fluid Loss, Dispersant, Free Water Control, Defoamer, Retarder, LCM

Sante Fe Main Office
Phone: (505) 476-3441

General Information
Phone: (505) 629-6116

Online Phone Directory
<https://www.emnrd.nm.gov/oed/contact-us>

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 509393

CONDITIONS

Operator: Admiral Permian Operating LLC 200 N. Loraine St Midland, TX 79701	OGRID: 332762
	Action Number: 509393
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
ward.rikala	No additives containing PFAS chemicals will be added to the drilling fluids or completion fluids used during drilling, completions, or recompletions operations.	9/26/2025