

Sundry Print Report

U.S. Department of the Interior BUREAU OF LAND MANAGEMENT

Well Name: BUFFALO TRACE 1/36 H3PA Well Location: T26S / R29E / SEC 12 / NENE County or Parish/State: EDDY / NM

FEDCOM / 32.0627741 / -103.9307513

Well Number: 2H Type of Well: CONVENTIONAL GAS WELL Allottee or Tribe Name:

Lease Number: NMNM23765,

NMNM57261

Unit or CA Name:

Unit or CA Number: NMNM105785253

Subsequent Report

Sundry ID: 2860771

Type of Submission: Subsequent Report **Type of Action:** Drilling Operations

Date Sundry Submitted: 07/01/2025 Time Sundry Submitted: 11:18

Date Operation Actually Began: 02/22/2022

Actual Procedure: PREVOUSLY APPROVED ON SUNDRY ID 2660231. ADDED DEPTHS BEFORE CASING WAS RAN PER NMOCD. 02/02/2022 Spudded well w/Patterson/UTI #597 @ 5:00 P.M. 02/03/22 TD 17 1/2" hole @ 895'. Ran 13 3/8" 54.5# J55 ST&C csg to 880'. Cmt w/625 sks Class C w/2% Extender, 1.5% Accelerator & ¼#/sk Poly Flake (yd @ 1.98 cuft/sk @ 12.4 PPG). Tail w/200 sks Class C Neat (yd @ 1.33 cuft/sk @ 14.8 PPG). Displaced w/130 bbls of BW. Plug down @ 6:30 P.M. 02/03/22. Circ 415 sks of cmt to the pit. Drill out w/ 12 1/4" bit. 02/05/22 Tested BOPE to 5000# high/250# low & Annular to 3500# high/250# low. Tested standpipe & mud lines back to pumps to 5000#. At 4:30 A.M. 02/05/22, tested csg to 1500# for 30 mins, held OK. FIT to 10.5 PPG EMW. 02/06/22 TD 12 1/4" hole @ 4515'. Ran 9 5/8" 40# ICL80 LT&C csg to 4500'. Cmt w/925 sks Class C w/3% Gypsum, 1% CaCl2 & ¼#/sk Poly Flake (yd @ 2.19 cuft/sk @ 12.4 PPG). Tail w/200 sk Class C Neat (yd @ 1.33 cuft/sk @ 14.8 PPG). Displaced w/338 bbls of FW. Slow rate lift pressure 1150 psi @ 3 BPM. Plug down @ 3:30 A.M. 02/08/22. Did not circ cmt. Ran temp survey, TOC @ 870'. Drill out w/8 3/4" bit. 02/09/22 At 8:00 P.M. on 02/09/22 tested csg to 1500# for 30 min, held OK. FIT to 10.0 PPG EMW. 2/12/22 TD 8 3/4" hole @ 9148'. Ran 7" 29# HCIP110 BT&C csg to 9071'. cmt w/350 sks Class C w/17.6#/sk Strength enhancer, 32% Glass beads, 0.6% Suspension agent & 0.35#/sk Polyflake (yd @ 3.96 cuft/sk @ 9.3 PPG). Tail w/400 sks Class H w/0.27% Retarder (yd @ 1.18 cuft/sk @ 15.6 PPG). Displaced w/335 bbls of OBM. Slow rate lift pressure 580# @ 3 BPM. Plug down @ 12:30 P.M. 02/13/22. Did not circ cmt (Est TOC @ 4300'). Lost partial returns w/85 bbls left to displace. Circ spacer to pit. Drill out w/6 1/8" bit. 02/14/22 At 12:45 A.M. 02/14/22, tested csg to 1500# for 30 min, held OK. FIT to 11.5 PPG EMW TD well @ 20496' 02/22/22. Ran 4 1/2" 13.5# ICP110 BPN csg from 8846' (top of liner) to 20493'. Cmt w/975 sks Class H w/37#/sk Poz, 3% Gel, 3% Gypsum, 0.35% Fluid Loss, 0.3% Suspension Agent & 0.1% Retarder (1.49 ft³/sk @ 13.5 ppg). Plug down @ 6:15 P.M. 02/24/22. Bumped plug w/3100#. Circ 229 sks cmt off liner top. At 7:45 P.M. 02/24/22, test liner top to 2500# for

eived by OCD: 7/3/2025 1:27:43 PM Well Name: BUFFALO TRACE 1/36 H3PA

FEDCOM

Well Location: T26S / R29E / SEC 12 / NENE

/32.0627741 / -103.9307513

County or Parish/State: EDDY / NM

Well Number: 2H Type of Well: CONVENTIONAL GAS WELL

Allottee or Tribe Name:

Lease Number: NMNM23765, NMNM57261

Unit or CA Name:

Unit or CA Number: NMNM105785253

US Well Number: 3001546801

Operator: MEWBOURNE OIL COMPANY

30 mins, held OK. Rig released to walk @ 11:30 A.M. 02/25/22.

SR Attachments

PActual Procedure

Mewbourne_Bufflao_trace_136_h3pa_fed_com_2H_Temp_Survey_20250701111750.pdf

Operator

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a

Operator Electronic Signature: JACKIE LATHAN Signed on: JUL 01, 2025 11:18 AM

Name: MEWBOURNE OIL COMPANY

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs State: NM

Phone: (575) 393-5905

Email address: Jlathan@mewbourne.com

Field

Representative Name:

Street Address:

City:

State:

Zip:

Phone:

Email address:

BLM Point of Contact

BLM POC Name: JONATHON W SHEPARD

BLM POC Phone: 5752345972

Disposition: Accepted

Signature: Jonathon Shepard

BLM POC Title: Petroleum Engineer

BLM POC Email Address: jshepard@blm.gov

Disposition Date: 07/03/2025

Page 2 of 2

Sante Fe Main Office Phone: (505) 476-3441

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 481633

CONDITIONS

Operator:	OGRID:
MEWBOURNE OIL CO	14744
P.O. Box 5270	Action Number:
Hobbs, NM 88241	481633
	Action Type:
	[C-103] Sub. Drilling (C-103N)

CONDITIONS

Created By	Condition	Condition Date
crystal.walker	None	9/29/2025