

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-007-20559
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name VPR B
8. Well Number 73
9. OGRID Number 180514
10. Pool name or Wildcat Van Bremmer - Vermejo Gas

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
8,095' (GL)

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/27/05 Schlumberger ran Acoustic Cement Bond Log. TOC at 46'.
02/23/05 Schlumberger perf'd 1st stage - 2,300' - 2,305' 20 Holes
HES frac'd 1st stage - Pumped 463 mscf 70 quality nitrogen foam with 12,987 lbs 16/30 brown sand at 18.1 bpm, ATP 2562 psi, ISIP 2359 psi.
Schlumberger perf'd 2nd stage - 1,301' - 1,307', 1,348' - 1,350', 1,380' - 1,382' 40 Holes
HES frac'd 2nd stage - Pumped 401 mscf 70 quality nitrogen foam with 47,666 lbs 16/30 brown sand at 24.6 bpm, ATP 2129 psi, ISIP 1391 psi.
Schlumberger perf'd 3rd stage - 859' - 864', 914' - 917', 946' - 950' 48 Holes
HES frac'd 3rd stage - Pumped 265 mscf 70 quality nitrogen foam with 51,045 lbs 16/30 brown sand at 23.8 bpm, ATP 1498 psi, ISIP 1052 psi
03/04/054 RIH tubing, rods and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 03/28/05

Type or print name Shirley A Mitchell E-mail address: Shirley.mitchell@elpaso.com Telephone No. (505) 445-6785
For State Use Only

APPROVED BY: [Signature] TITLE DISTRICT SUPERVISOR DATE 4/8/05
Conditions of Approval (if any):