

State of New Mexico  
Energy, Minerals and Natural Resources

WELL API NO.

**30-007-20580**

7. Indicate Type of Lease

STATE ☐ FEE ☒

7. State Oil &amp; Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other **Coalbed Methane**

2. Name of Operator

**EL PASO ENERGY RATON, L.L.C.**

3. Address of Operator

**P.O. BOX 190, RATON, NM 87740**

4. Well Location

Unit Letter **F** : **2473** feet from the **North** line and **1560** feet from the **West** lineSection **20** Township **30N** Range **19E** **NMPM** **Colfax** County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

**7,570' (GL)**Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type \_\_\_\_\_ Depth to Groundwater \_\_\_\_\_ Distance from nearest fresh water well \_\_\_\_\_ Distance from nearest surface water \_\_\_\_\_

Pit Liner Thickness: \_\_\_\_\_ mil Below-Grade Tank: Volume \_\_\_\_\_ bbls; Construction Material \_\_\_\_\_

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☒ P AND A ☐CASING/CEMENT JOB ☐OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

- 03/30/05 Spud @ 12:00 noon. Drill 11" surface hole to 325'. Run 8 jts. of 8 5/8", 24#, J55 ST & C casing at 315'. Halliburton mixed and pumped 100 sx Midcon II cement, 14 ppg, yield 1.66. Circulate 5 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes. ✓
- 03/31/05 Drill 7 7/8" hole from 325' - 2,015'. Reached TD 2,015' at 7:30 a.m. MIRU Schlumberger and log well. Logger's TD at 1,910'. Run 46 jts 5 1/2", 15.5#, J-55 LT & C casing at 1,898'.
- 04/01/05 HES mixed and pumped 285 sks Midcon II cement. Plug down at 11:52 a.m. Circulated 24 bbls cement to surface. Well shut in. ✓

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE

TITLE **Regulatory Analyst**DATE **04/07/05**

Type or print name

**Shirley A. Mitchell**E-mail address: **shirley.mitchell@elpaso.com**Telephone No. **(505) 445-6785**

For State Use Only

APPROVED BY:

TITLE **DISTRICT SUPERVISOR**DATE **4/15/05**

Conditions of Approval (if any):