

Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003
		WELL API NO. 30-007-20571
		5. Indicate Type of Lease STATE ☐ FEE ☒
		State Oil & Gas Lease No.
WELL COMPLETION OR RECOMPLETION REPORT AND LOG		
1a. Type of Well: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER <u>Coalbed Methane</u>		7. Lease Name or Unit Agreement Name VPR B
b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER BACK RESVR. ☐ OTHER		
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		8. Well No. 96
3. Address of Operator PO BOX 190 RATON, NEW MEXICO 87740		9. Pool name or Wildcat Van Bremmer - Vermejo Gas 97047
4. Well Location Unit Letter <u>E</u> : <u>2100</u> Feet From The <u>North</u> Line and <u>1022</u> Feet From The <u>West</u> Line Section <u>34</u> Township <u>30N</u> Range <u>18E</u> NMPM Colfax County		
10. Date Spudded 01/26/05	11. Date T.D. Reached 01/27/05	12. Date Compl. (Ready to Prod.) 04/15/05
13. Elevations (DF& RKB, RT, GR, etc.) 8,280'		14. Elev. Casinghead 8,280'
15. Total Depth 2,850'	16. Plug Back T.D. 2,850'	17. If Multiple Compl. How Many Zones? 0 - TD
18. Intervals Drilled By		19. Producing Interval(s), of this completion - Top, Bottom, Name 1,045' - 2,573' Raton - Vermejo Coals
20. Was Directional Survey Made		21. Type Electric and Other Logs Run Compensated Density Single Induction Log and Cement Bond Log
22. Was Well Cored		No
23. CASING RECORD (Report all strings set in well)		
CASING SIZE	WEIGHT LB./FT.	DEPTH SET
8 5/8"	23 lbs	300'
5 1/2"	15.5 lbs	2,738'
24. LINER RECORD		
SIZE	TOP	BOTTOM
25. TUBING RECORD		
SIZE	DEPTH SET	PACKER SET
2 7/8"	2,576'	
26. Perforation record (interval, size, and number) 2,527' - 2,529', 2,563' - 2,567', 2,569' - 2,573' 40 Holes 2,349' - 2,352' 12 Holes 1,249' - 1,255' 24 Holes 1,045' - 1,050', 1,132' - 1,136', 1,140' - 1,143', 1,182' - 1,186' 64 Holes		
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED 1,045' - 2,573' 190,459 lbs 16/30 brown sand		
28. PRODUCTION		
Date First Production 04/14/05	Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/ 2' x 1 1/4" x 10' insert pump. Flowing gas up 5 1/2" casing.	Well Status (Prod. or Shut-in) Production
Date of Test 04/14/05	Hours Tested 24 Hours	Choke Size Full 2"
Flow Tubing Press. 200 psi	Casing Pressure 3 psi	Calculated 24-Hour Rate N/A
Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 29
Water - Bbl. 198	Gas - Oil Ratio N/A	Oil Gravity - API - (Corr.) N/A
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.		Test Witnessed By Gary Blundell
30. List Attachments		
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief		
Signature <u>Shirley Mitchell</u> Printed Name Shirley A. Mitchell Title Regulatory Analyst Date 04/26/05 E-mail Address shirley.mitchell@elpaso.com		

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or reopened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
F. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
F. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
F. Yates	T. Miss	T. Cliff House	T. Leadville
F. 7 Rivers	T. Devonian	T. Menefee	T. Madison
F. Queen	T. Silurian	T. Point Lookout	T. Elbert
F. Grayburg	T. Montoya	T. Mancos	T. McCracken
F. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzite
F. Glorieta	T. McKee	Base Greenhorn	T. Granite
F. Paddock	T. Ellenburger	T. Dakota	T. <u>Raton</u> <u>403'</u>
F. Blinebry	T. Gr. Wash	T. Morrison	T. <u>Vermejo</u> <u>2,268'</u>
F. Tubb	T. Delaware Sand	T. Todilto	T. <u>Trinidad</u> <u>2,590'</u>
F. Drinkard	T. Bone Springs	T. Entrada	T.
F. Abo	T.	T. Wingate	T.
F. Wolfcamp	T.	T. Chinle	T.
F. Penn	T.	T. Permian	T.
F. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

o. 1, from.....to..... No. 3, from.....to.....
o. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

include data on rate of water inflow and elevation to which water rose in hole.

o. 1, from.....to.....feet.....

o. 2, from.....to.....feet.....

o. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology