| Office District I Energy, Minerals and Natural Resources | Form C-103 |
|--|---|
| | May 27, 2004 |
| 7 | WELL API NO. 30-007-20570 |
| DISHICH OF CONCEDUATION DIVICION | |
| District III 1220 South St. Francis Dr. | 5. Indicate Type of Lease |
| 1000 Dia Prozon Pet Agten NM MMA10 20185 | STATE FEE 🛇 |
| District IV Salita Pe, INIVI 67505 | 6. State Oil & Gas Lease No. |
| 1220 S. St. Francis Dr., South Fe NASERVATION | |
| SUNDRY MOTORS AND REPORTS ON WELLS | 7. Lease Name or Unit Agreement Name |
| (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A | 7. Bease Name of Sine Agreement Name |
| DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH | VPR B |
| PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other Coalbed Methane | 8. Well Number 95 |
| | |
| 2. Name of Operator | 9. OGRID Number 180514 |
| EL PASO ENERGY RATON, L.L.C. | 10 Peal Wilder |
| 3. Address of Operator | 10. Pool name or Wildcat |
| PO BOX 190, RATON, NM 87740 | Van Bremmer – Vermejo Gas |
| 4. Well Location | |
| Unit Letter P: 1574 feet from the South line and | feet from the <u>East</u> line |
| Section 28 Township 30N Range 18E NMPN | I Colfax County |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc. | |
| 8,378' (GL) | |
| Pit or Below-grade Tank Application or Closure | |
| Pit type Depth to Groundwater Distance from nearest fresh water well Di | stance from nearest surface water |
| | Construction Material |
| | |
| 12. Check Appropriate Box to Indicate Nature of Notice | Report or Other Data |
| NOTICE OF INTENTION TO: | SECUENT DEPORT OF |
| PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOI | SSEQUENT REPORT OF: |
| · · · · · · · · · · · · · · · · · · · | |
| | |
| | RILLING OPNS. P AND A |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN | |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN | IT JOB |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENOTHER: | IT JOB ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: OTHER: | Completion s, including estimated date of starting any proposed work) |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: OTHER: OTHER: 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. | Completion s, including estimated date of starting any proposed work) |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: OTHER: OTHER: OTHER: 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. Other: 03/05 Schlumberger perf'd 1st stage - 2585'- 2589'' 16 Holes | Completion Ses, including estimated date of starting any proposed work) completion. |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re O3/09/05 Schlumberger ran Cement Bond Log. Cement to surface. O4/15/05 Schlumberger perf'd 1st stage - 2585'- 2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear | Completion Ses, including estimated date of starting any proposed work) completion. r gel with 24,592 lbs 16/30 brown sand. |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1st stage - 2585'- 2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linea Schlumberger perf'd 2nd stage - 2460'- 2463, 2490'- 2494, 2523'- 2525', 2532'- 253 | Completion Ses, including estimated date of starting any proposed work) completion. r gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. r gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes |
| OTHER: OTHER: | Completion es, including estimated date of starting any proposed work) completion. r gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion es, including estimated date of starting any proposed work) completion. r gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. r gel with 25,193 lbs 16/30 brown sand. r gel with 25,193 lbs 16/30 brown sand. 37', 1250'- 1255' 64 Holes |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. Triggl with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. Triggl with 25,193 lbs 16/30 brown sand. Triggl with 25,193 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. Trigel with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. Trigel with 25,193 lbs 16/30 brown sand. Trigel with 25,193 lbs 16/30 brown sand. Trigel with 78,506 lbs 16/30 brown sand. Trigel with 78,506 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. To gel with 25,193 lbs 16/30 brown sand. To gel with 25,193 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. To gel with 25,193 lbs 16/30 brown sand. To gel with 25,193 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. Triggl with 24,592 lbs 16/30 brown sand. 6' 52 Holes gel with 72,583 lbs 16/30 brown sand. Triggl with 25,193 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. 64 Holes gel with 79,848 lbs 16/30 brown sand. Triggl with 79,848 lbs 16/30 brown sand. |
| OTHER: OTHER: | Completion Ses, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1st stage - 2585'-2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd stage - 2460'-2463, 2490'-2494, 2523'-2525', 2532'-253 HES frac'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3rd stage - 1993'-1996', 2000'-2002', 2044'-2048' 36 holes HES frac'd 3rd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear 04/16/05 Schlumberger perf'd 4th stage - 1118'-1122', 1125'-1127', 1181'-1184', 1235'-12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear 04/18/05 Schlumberger perf'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear 05/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on put of the proposed complete to the best of my knowledger part to the best of my knowledger tank has been/will be constructed or closed according to NMOCD guidelines \[\begin{array}{c} \text{ a general permit } \begin{array}{c} April 1 the part to the best of my knowledger pa | Completion Es, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 25,193 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1st stage - 2585'- 2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 2nd stage - 2460'- 2463, 2490'- 2494, 2523'- 2525', 2532'- 253 HES frac'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3nd stage - 1993'- 1996', 2000'- 2002', 2044'- 2048' 36 holes HES frac'd 3nd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear O4/16/05 Schlumberger perf'd 4th stage - 1118'- 1122', 1125'- 1127', 1181'- 1184', 1235'- 12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear O4/18/05 Schlumberger perf'd 5th stage - 949'- 953', 984'- 986', 1038'- 1043', 1079'- 1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear O5/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on purple of the stage of th | Completion Es, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1st stage - 2585'-2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 2nd stage - 2460'-2463, 2490'-2494, 2523'-2525', 2532'-253 HES frac'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3rd stage - 1993'-1996', 2000'-2002', 2044'-2048' 36 holes HES frac'd 3rd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear O4/16/05 Schlumberger perf'd 4th stage - 1118'-1122', 1125'-1127', 1181'-1184', 1235'-12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear O4/18/05 Schlumberger perf'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear 05/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on pure I hereby certify that the information above is true and complete to the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines \(\Delta \), a general permit \(\Delta \) | Completion Es, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dat SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1st stage - 2585'- 2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 2nd stage - 2460'- 2463, 2490'- 2494, 2523'- 2525', 2532'- 253 HES frac'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3nd stage - 1993'- 1996', 2000'- 2002', 2044'- 2048' 36 holes HES frac'd 3nd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear O4/16/05 Schlumberger perf'd 4th stage - 1118'- 1122', 1125'- 1127', 1181'- 1184', 1235'- 12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear O4/18/05 Schlumberger perf'd 5th stage - 949'- 953', 984'- 986', 1038'- 1043', 1079'- 1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear O5/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on purple of the stage of th | Completion Es, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or reconstructions. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or reconstruction. Schlumberger perf d 1st stage - 2585'-2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3rd stage - 1993'-1996', 2000'-2002', 2044'-2048' 36 holes HES frac'd 3rd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear 1118'-1122', 1125'-1127', 1181'-1184', 1235'-12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear 05/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed tank has been/will be constructed or closed according to NMOCD guidelines \(\precedits \), a general permit \(\precedits \). SIGNATURE \(\text{Multiple Amitchell Permail address: shirley.mitchell@elpaso.ce} \) | Completion Es, including estimated date of starting any proposed work) completion. Triggl with 24,592 lbs 16/30 brown sand. Triggl with 72,583 lbs 16/30 brown sand. Triggl with 25,193 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or re 03/09/05 Schlumberger ran Cement Bond Log. Cement to surface. 04/15/05 Schlumberger perf'd 1stage - 2585'-2589'' 16 Holes HES frac'd 1stage - Pumped 292,863 sef 70% quality nitrogen foam with 20# Linear Schlumberger perf'd stage - Pumped 620,057 sef 70% quality nitrogen foam with 20# Linear Schlumberger perf'd stage - Pumped 329,763 sef 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 4th stage - 1118'-1122', 1125'-1127', 1181'-1184', 1235'-12 HES frac'd 4th stage - Pumped 594,866 sef 70% quality nitrogen foam with 20# Linear 04/18/05 Schlumberger perf'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - Pumped 686,971 sef 70% quality nitrogen foam with 20# Linear 05/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on purple of the best of my knowled grade tank has been/will be constructed or closed according to NMOCD guidelines \(\), a general permit \(\) SIGNATURE Shally Additchell F-mail address: shirley.mitchell@elpaso.ce For State Use Only APPROVED BY: | Completion Es, including estimated date of starting any proposed work) completion. To gel with 24,592 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 72,583 lbs 16/30 brown sand. To gel with 78,506 lbs 16/30 brown sand. To gel with 79,848 lbs 16/30 brown sand. |
| OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or reconstructions. (Clearly state all pertinent details, and give pertinent data SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or reconstruction. Schlumberger perf d 1st stage - 2585'-2589'' 16 Holes HES frac'd 1st stage - Pumped 292,863 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 2nd stage - Pumped 620,057 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 3rd stage - 1993'-1996', 2000'-2002', 2044'-2048' 36 holes HES frac'd 3rd stage - Pumped 329,763 scf 70% quality nitrogen foam with 20# Linear 1118'-1122', 1125'-1127', 1181'-1184', 1235'-12 HES frac'd 4th stage - Pumped 594,866 scf 70% quality nitrogen foam with 20# Linear Schlumberger perf'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - 949'-953', 984'-986', 1038'-1043', 1079'-1084' HES frac'd 5th stage - Pumped 686,971 scf 70% quality nitrogen foam with 20# Linear 05/12/05 Clean out well bore. RIH tubing, rods and pump. Well is ready to be tested and put on proceed tank has been/will be constructed or closed according to NMOCD guidelines \(\precedits \), a general permit \(\precedits \). SIGNATURE \(\text{Multiple Amitchell Permail address: shirley.mitchell@elpaso.ce} \) | Completion Es, including estimated date of starting any proposed work) completion. Triggl with 24,592 lbs 16/30 brown sand. Triggl with 72,583 lbs 16/30 brown sand. Triggl with 25,193 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 78,506 lbs 16/30 brown sand. Triggl with 79,848 lbs 16/30 brown sand. |